

# TEST REPORT

FCC DTS Test for LAN5900WR  
Certification

APPLICANT  
LG Electronics Inc.

REPORT NO.  
HCT-RF-1912-FC020-R1

DATE OF ISSUE  
December 24, 2019

**HCT Co., Ltd.**

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA  
Tel. +82 31 634 6300 F ax. +82 31 645 6401



HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA  
Tel. +82 31 634 6300 Fax. +82 31 645 6401

# TEST REPORT

FCC DTS Test for  
LAN5900WR

REPORT NO.  
HCT-RF-1912-FC020-R1

DATE OF ISSUE  
December 24, 2019

FCC ID  
BEJLAN5900WR

Applicant **LG Electronics Inc.**  
10, Magokjungang 10-ro, Gangseo-gu, Seoul, Republic of Korea

Eut Type  
Model Name **RADIO – CAR**  
**LAN5900WR**

Modulation type **CCK/DSSS/OFDM**

FCC Classification **Digital Transmission System(DTS)**

FCC Rule Part(s) **Part 15.247**

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

This test results were applied only to the test methods required by the standard.

Tested by  
**Kwon Jeong**

(signature)

Technical Manager  
**Jong Seok Lee**

(signature)

**HCT CO., LTD.**

*Soo Chan Lee*

SooChan Lee

/ CEO

## REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	December 18, 2019	Initial Release
1	December 24, 2019	Added the note on page 5.

The front design of LAN5900WR is changed by applied RENAULT vehicle variant without PCB and circuit design.

### Engineering Statement:

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

## CONTENTS

1. EUT DESCRIPTION	5
2. TEST METHODOLOGY	6
EUT CONFIGURATION	6
EUT EXERCISE	6
GENERAL TEST PROCEDURES	6
DESCRIPTION OF TEST MODES	7
3. INSTRUMENT CALIBRATION	7
4. FACILITIES AND ACCREDITATIONS	7
FACILITIES	7
EQUIPMENT	7
5. ANTENNA REQUIREMENTS	8
6. MEASUREMENT UNCERTAINTY	8
7. DESCRIPTION OF TESTS	9
8. SUMMARY TEST OF RESULTS	24
9. TEST RESULT	25
9.1 DUTY CYCLE	25
9.2 6dB BANDWIDTH	28
9.3 OUTPUT POWER	31
9.4 POWER SPECTRAL DENSITY	37
9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS	40
9.6 RADIATED SPURIOUS EMISSIONS	51
9.7 RADIATED RESTRICTED BAND EDGES	59
10. LIST OF TEST EQUIPMENT	62
11. ANNEX A_ TEST SETUP PHOTO	64

## 1. EUT DESCRIPTION

Model	LAN5900WR	
EUT Type	RADIO – CAR	
Power Supply	DC 12 V	
Frequency Range	2412 MHz - 2462 MHz	
Max. RF Output Power	<b><u>Peak Power</u></b>	802.11b: 22.84 dBm 802.11g: 21.05 dBm 802.11n(HT20): 21.21 dBm
	<b><u>Average Power</u></b>	802.11b: 17.07 dBm 802.11g: 13.40 dBm 802.11n(HT20): 13.31 dBm
Modulation Type	DSSS/CCK : 802.11b / OFDM : 802.11g, 802.11n(HT20)	
Number of Channels	11 Channels	
Antenna Specification	Antenna type: Multilayer Chip Antenna Peak Gain: 2.20 dBi	
Date(s) of Tests	November 11, 2019 ~ December 17, 2019	

### Note

: The front design of LAN5900WR is changed by applied RENAULT vehicle variant without PCB and circuit design

## 2. TEST METHODOLOGY

FCC KDB 558074 D01 15.247 Meas Guidance v05r02 dated April 02, 2019 entitled “guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices and the measurement procedure described in ANSI C63.10 (Version : 2013) ‘the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices’.

### EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

### GENERAL TEST PROCEDURES

#### Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version :2013) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

#### Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3.75 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 6.6.5 of ANSI C63.10. (Version: 2013)

## DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition. Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

## 3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment's, which is traceable to recognized national standards.

Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2017).

## 4. FACILITIES AND ACCREDITATIONS

### FACILITIES

The SAC(Semi-Anechoic Chamber) and conducted measurement facility used to collect the radiated data are located at the 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA.

The site is constructed in conformance with the requirements of ANSI C63.4. (Version :2014) and CISPR Publication 22.

Detailed description of test facility was submitted to the Commission and accepted dated April 02, 2018 (Registration Number: KR0032 ).

### EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements. Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

## 5. ANTENNA REQUIREMENTS

According to FCC 47 CFR § 15.203:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- (1) The antennas of this E.U.T are permanently attached.
- (2) The E.U.T Complies with the requirement of § 15.203

## 6. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of  $k=2$  to indicate a 95 % level of confidence.

The measurement data shown herein meets or exceeds the  $U_{\text{CISPR}}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.


Parameter	Expanded Uncertainty ( $\pm$ dB)
Conducted Disturbance (150 kHz ~ 30 MHz)	1.82
Radiated Disturbance (9 kHz ~ 30 MHz)	3.40
Radiated Disturbance (30 MHz ~ 1 GHz)	4.80
Radiated Disturbance (1 GHz ~ 18 GHz)	5.70
Radiated Disturbance (18 GHz ~ 40 GHz)	5.05



## 7. DESCRIPTION OF TESTS

### 7.1. Duty Cycle

#### Test Configuration



#### Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to the zero-span measurement method.

The largest available value of RBW is 8 MHz and VBW is 50 MHz.

The zero-span method of measuring duty cycle shall not be used if  $T \leq 6.25$  microseconds. ( $50/6.25 = 8$ )

The zero-span method was used because all measured T data are  $> 6.25$  microseconds and both RBW and VBW are  $> 50/T$ .


1. RBW = 8 MHz (the largest available value)
2. VBW = 8 MHz ( $\geq$  RBW)
3. SPAN = 0 Hz
4. Detector = Peak
5. Number of points in sweep  $> 100$
6. Trace mode = Clear write
7. Measure  $T_{total}$  and  $T_{on}$
8. Calculate Duty Cycle =  $T_{on}/T_{total}$  and Duty Cycle Factor =  $10\log(1/\text{Duty Cycle})$

## 7.2. 6dB Bandwidth

### Limit

The minimum permissible 6 dB bandwidth is 500 kHz.

### Test Configuration



### Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

The Spectrum Analyzer is set to (Procedure 11.8.1 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW  $\geq 3 \times$  RBW
- 3) Detector = Peak
- 4) Trace mode = max hold
- 5) Sweep = auto couple
- 6) Allow the trace to stabilize
- 7) We tested 6 dB bandwidth using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 6 dB.


Note : We tested OBW using the automatic bandwidth measurement capability of a spectrum analyzer.

### 7.3. Output Power

#### Limit

The maximum permissible conducted output power is 1 Watt.

#### Test Configuration



#### Test Procedure

The transmitter output is connected to the Power Meter.

- Peak Power (Procedure 11.9.1.3 in ANSI 63.10-2013)  
: Measure the peak power of the transmitter.
  
- Average Power (Procedure 11.9.2.3 in ANSI 63.10-2013)
  - 1) Measure the duty cycle.
  - 2) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
  - 3) Add  $10 \log (1/x)$ , where  $x$  is the duty cycle, to the measured power in order to compute the average power during the actual transmission times.

#### Sample Calculation


- Conducted Output Power(Peak) = Reading Value + ATT loss + Cable loss
- Conducted Output Power(Average) = Reading Value + ATT loss + Cable loss + Duty Cycle Factor

## 7.4. Power Spectral Density

### Limit

The transmitter power density average over 1-second interval shall not be greater than 8dBm in any 3kHz BW.

### Test Configuration



### Test Procedure

The transmitter output is connected to the Spectrum Analyzer.

We tested according to Procedure 8.4 in KDB 558074 v05r02, Procedure 11.10 in ANSI 63.10-2013.

The spectrum analyzer is set to :

- 1) Set analyzer center frequency to DTS channel center frequency.
- 2) Span = 1.5 times the DTS channel bandwidth.
- 3)  $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$ .
- 4)  $VBW \geq 3 \times RBW$ .
- 5) Sweep = auto couple
- 6) Detector = peak
- 7) Trace Mode = max hold
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### Sample Calculation

- Power Spectral Density = Reading Value + ATT loss + Cable loss


## 7.5. Conducted Band Edge(Out of Band Emissions) & Conducted Spurious Emissions

### Limit

The maximum conducted (Average) output power was used to demonstrate compliance, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

[ Conducted > 20 dBc ]

### Test Configuration



### Test Procedure

The transmitter output is connected to the spectrum analyzer.

(Procedure 11.11 in ANSI 63.10-2013)

- 1) RBW = 100 kHz
- 2) VBW  $\geq 3 \times$  RBW
- 3) Set span to encompass the spectrum to be examined
- 4) Detector = Peak
- 5) Trace Mode = max hold
- 6) Sweep time = auto couple
- 7) Ensure that the number of measurement points  $\geq 2 \times$  Span/RBW
- 8) Allow trace to fully stabilize.
- 9) Use peak marker function to determine the maximum amplitude level.

Measurements are made over the 30 MHz to 25 GHz range with the transmitter set to the lowest, middle, and highest channels.

### Factors for frequency

Freq(MHz)	Factor(dB)
30	20.07
100	20.08
200	20.11
300	20.13
400	20.17
500	20.19
600	20.20
700	20.22
800	20.24
900	20.25
1000	20.27
2000	20.48
2400	20.55
2500	20.54
3000	20.53
4000	20.62
5000	20.63
6000	20.63
7000	20.71
8000	20.75
9000	20.86
10000	20.97
11000	21.06
12000	21.07
13000	21.20
14000	21.42
15000	21.50
16000	21.29
17000	21.17
18000	21.07
19000	21.12
20000	21.19
21000	21.31
22000	21.35
23000	21.52
24000	21.64
25000	21.80
26000	21.58
27000	21.59

Note : 1. 2400 ~ 2500 MHz is fundamental frequency range.

2. Factor = Attenuator loss + Cable loss


## 7.6. Radiated Test

### Limit


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	$2400/F(\text{kHz})$	300
0.490 – 1.705	$24000/F(\text{kHz})$	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

### Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz





**Test Procedure of Radiated spurious emissions(Below 30 MHz)**

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3m from the EUT
3. The EUT is placed on a turntable, which is 0.8m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization and Parallel to the ground plane in detecting antenna.
5. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor(0.009 MHz – 0.490 MHz) =  $40\log(3\text{ m}/300\text{ m}) = -80\text{ dB}$   
Measurement Distance : 3 m
7. Distance Correction Factor(0.490 MHz – 30 MHz) =  $40\log(3\text{ m}/30\text{ m}) = -40\text{ dB}$   
Measurement Distance : 3 m
8. Spectrum Setting
  - Frequency Range = 9 kHz ~ 30 MHz
  - Detector = Peak
  - Trace = Maxhold
  - RBW = 9 kHz
  - VBW  $\geq 3 \times$  RBW
9. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F)
10. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

**KDB 414788 OFS and Chamber Correlation Justification**

Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

OFS and chamber correlation testing had been performed and chamber measured test result is the worst case test result.

**Test Procedure of Radiated spurious emissions(Below 1GHz)**

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.

**5. Spectrum Setting****(1) Measurement Type(Peak):**

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 100 kHz
- VBW  $\geq 3 \times$  RBW

**(2) Measurement Type(Quasi-peak):**

- Measured Frequency Range : 30 MHz – 1 GHz
- Detector = Quasi-Peak
- RBW = 120 kHz

In general, (1) is used mainly

6. Total = Reading Value + Antenna Factor(A.F) + Cable Loss(C.L)
7. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

**Test Procedure of Radiated spurious emissions (Above 1 GHz)**

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor( reference distance : 3 m).
  - ◆ Distance extrapolation factor =  $20 \log (\text{test distance} / \text{specific distance})$  (dB)
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

## 8. Spectrum Setting (Method 8.6 in KDB 558074 v05r02, Procedure 11.12 in ANSI 63.10-2013)

### (1) Measurement Type(Peak):

- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = Peak
- Trace = Maxhold
- RBW = 1 MHz
- VBW  $\geq 3 \times$  RBW

### (2) Measurement Type(Average): Duty cycle $\geq 98\%$

- Measured Frequency Range : 1 GHz – 25 GHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW  $\geq 3 \times$  RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).

9. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

## 10. Total(Measurement Type : Peak)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

## Total(Measurement Type : Average, Duty cycle $\geq 98\%$ )

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) - Amp Gain(G) + Distance Factor(D.F)

### **Test Procedure of Radiated Restricted Band Edge**

1. The EUT is placed on a turntable, which is 1.5 m above ground plane.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
4. EUT is set 3.75 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
5. According to SVSWR requirement in ANSI 63.4-2014, We performed the radiated test at 3.75 m distance from center of turn table. So, we applied the distance factor( reference distance : 3 m).
  - ◆ Distance extrapolation factor =  $20\log(\text{test distance} / \text{specific distance})$  (dB)
6. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
7. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
8. Spectrum Setting
  - (1) Measurement Type(Peak):
    - Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
    - Detector = Peak
    - Trace = Maxhold
    - RBW = 1 MHz
    - VBW  $\geq 3 \times$  RBW
  - (2) Measurement Type(Average): Duty cycle  $\geq 98\%$ ,
    - Measured Frequency Range : 2310 MHz ~ 2390 MHz/ 2483.5 MHz ~ 2500 MHz
    - Detector = RMS
    - Averaging type = power (*i.e.*, RMS)
    - RBW = 1 MHz
    - VBW  $\geq 3 \times$  RBW
    - Sweep time = auto.
    - Trace mode = average (at least 100 traces).
9. Measurement value only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

## 10. Total(Measurement Type : Peak)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F) – AMP Gain (A.G)  
+Attenuator(ATT)

Total(Measurement Type : Average, Duty cycle  $\geq$  98%)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F) – AMP Gain (A.G)  
+Attenuator(ATT)

Total(Measurement Type : Average, Duty cycle < 98%)

= Reading Value + Antenna Factor(A.F) + Cable Loss(C.L) + Distance Factor(D.F) – AMP Gain (A.G)  
+Attenuator(ATT) + Duty Cycle Factor

## 7.7. AC Power line Conducted Emissions

### Limit

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56 <sup>(a)</sup>	56 to 46 <sup>(a)</sup>
0.50 to 5	56	46
5 to 30	60	50

<sup>(a)</sup>Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

### Test Configuration

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

### Test Procedure

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors : Quasi Peak and Average Detector.

### Sample Calculation

Quasi-peak(Final Result) = Reading Value + Correction Factor

## 7.9. Worst case configuration and mode

### Radiated test

1. All modes of operation were investigated and the worst case configuration results are reported.

- Mode : Stand alone
- Worstcase : Stand alone

2. EUT Axis

- Radiated Spurious Emissions : X
- Radiated Restricted Band Edge : X

3. All position of loop antenna were investigated and the test result is a no critical peak found at all positions.

- Position : Horizontal, Vertical, Parallel to the ground plane

### AC Power line Conducted Emissions

1. We don't perform powerline conducted emission test. Because this EUT is used with vehicle.

### Conducted test

1. The EUT was configured with data rate of highest power.

## 8. SUMMARY TEST OF RESULTS

Test Description	FCC Part Section(s)	Test Limit	Test Condition	Test Result
6 dB Bandwidth	§ 15.247(a)(2)	> 500 kHz	Conducted	PASS
Conducted Maximum Output Power	§ 15.247(b)(3)	< 1 Watt		PASS
Power Spectral Density	§ 15.247(e)	< 8 dBm / 3 kHz Band		PASS
Band Edge (Out of Band Emissions)	§ 15.247(d)	Conducted > 20 dBc		PASS
AC Power line Conducted Emissions	§ 15.207	cf. Section 7.7		N/A
Radiated Spurious Emissions	§ 15.247(d), 15.205, 15.209	cf. Section 7.6	Radiated	PASS
Radiated Restricted Band Edge	§ 15.247(d), 15.205, 15.209	cf. Section 7.6		PASS

**Note:**

We don't perform AC Conducted Emissions test. Because this EUT is used with vehicle.




## 9. TEST RESULT

### 9.1 DUTY CYCLE


Mode	Data Rate (Mbps)	T <sub>on</sub> (ms)	T <sub>total</sub> (ms)	Duty Cycle	Duty Cycle Factor (dB)
802.11b	1	8.616	8.710	0.989	0.047
	2	4.306	4.404	0.978	0.098
	5.5	4.306	4.395	0.980	0.089
	11	0.861	0.956	0.900	0.456
802.11g	6	1.429	1.530	0.934	0.297
	9	0.961	1.062	0.905	0.435
	12	0.723	0.825	0.877	0.569
	18	0.492	0.593	0.829	0.814
	24	0.372	0.474	0.786	1.046
	36	0.257	0.358	0.717	1.444
	48	0.196	0.298	0.658	1.820
	54	0.180	0.282	0.641	1.934
802.11n (HT20)	6.5 (MCS0)	1.336	1.436	0.930	0.315
	13 (MCS1)	0.687	0.788	0.871	0.600
	19.5 (MCS2)	0.471	0.573	0.822	0.851
	26 (MCS3)	0.364	0.465	0.783	1.063
	39 (MCS4)	0.256	0.357	0.717	1.447
	52 (MCS5)	0.200	0.301	0.664	1.777
	58.5 (MCS6)	0.185	0.286	0.645	1.904
	65 (MCS7)	0.168	0.270	0.623	2.052

## Test Plots


Duty cycle plot (802.11b(1Mbps))



Duty cycle plot (802.11g(6Mbps))



Duty cycle plot (802.11n(MCS0))



### Note:

In order to simplify the report, attached plots were only the most lowest datarate.

## 9.2 6dB BANDWIDTH


802.11b Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]
Frequency [MHz]	Channel No.		
2412	1	7.113	0.5
2437	6	7.129	0.5
2462	11	7.109	0.5

802.11g Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]
Frequency [MHz]	Channel No.		
2412	1	16.02	0.5
2437	6	15.97	0.5
2462	11	16.09	0.5


802.11n Mode		Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]
Frequency [MHz]	Channel No.		
2412	1	17.00	0.5
2437	6	17.19	0.5
2462	11	16.56	0.5

## Test Plots


6dB Bandwidth plot (802.11b-CH 11)



6dB Bandwidth plot (802.11g-CH 6)



6dB Bandwidth plot (802.11n\_HT20-CH 11)



#### Note:

In order to simplify the report, attached plots were only the most narrow 6 dB BW channel.

### 9.3 OUTPUT POWER

#### Peak Power

1. Power Meter offset = Attenuator loss + Cable loss

2. We apply to the offset in the 2.4 GHz range that was rounded off to the closest twentieth dB.

So, 20.55 dB is offset for 2.4 GHz Band. And, additional cable loss is 0.5 dB.

802.11b Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.			
2412	1	1	17.52	30
		2	17.53	30
		5.5	17.51	30
		11	20.83	30
2437	6	1	17.83	30
		2	17.99	30
		5.5	17.91	30
		11	21.20	30
2462	11	1	19.46	30
		2	19.50	30
		5.5	19.51	30
		11	22.84	30

802.11g Mode		Rate (Mbps)	Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.			
2412	1	6	20.65	30
		9	20.57	30
		12	20.33	30
		18	19.95	30
		24	20.43	30
		36	20.36	30
		48	20.36	30
		54	20.33	30
2437	6	6	21.05	30
		9	20.98	30
		12	20.76	30
		18	20.21	30
		24	20.52	30
		36	20.68	30
		48	20.83	30
		54	20.76	30
2462	11	6	19.89	30
		9	19.82	30
		12	19.59	30
		18	19.21	30
		24	19.35	30
		36	19.45	30
		48	19.50	30
		54	19.54	30



802.11n(HT20) Mode		MCS Index	Measured Power(dBm)	Limit (dBm)
Frequency[MHz]	Channel No.			
2412	1	0	20.77	30
		1	20.58	30
		2	20.54	30
		3	20.89	30
		4	20.74	30
		5	20.88	30
		6	20.81	30
		7	20.49	30
2437	6	0	21.03	30
		1	20.97	30
		2	20.79	30
		3	21.05	30
		4	21.08	30
		5	21.10	30
		6	21.21	30
		7	21.01	30
2462	11	0	19.80	30
		1	19.76	30
		2	19.75	30
		3	19.73	30
		4	19.64	30
		5	19.77	30
		6	19.85	30
		7	19.64	30

### Average Power

1. Power Meter offset = Attenuator loss + Cable loss

2. We apply to the offset in the 2.4 GHz range that was rounded off to the closest twentieth dB.

So, 20.55 dB is offset for 2.4 GHz Band. And, additional cable loss is 0.5 dB.

802.11b Mode		Rate (Mbps)	Measured Power (dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)
Frequency [MHz]	Channel No.					
2412	1	1	14.87	0.047	14.92	30
		2	14.87	0.098	14.96	30
		5.5	14.83	0.089	14.92	30
		11	14.58	0.456	15.04	30
2437	6	1	15.23	0.047	15.28	30
		2	15.21	0.098	15.31	30
		5.5	15.15	0.089	15.24	30
		11	14.88	0.456	15.34	30
2462	11	1	17.03	0.047	17.07	30
		2	16.72	0.098	16.82	30
		5.5	16.78	0.089	16.87	30
		11	16.49	0.456	16.95	30

802.11g Mode		Rate (Mbps)	Measured Power (dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)
Frequency [MHz]	Channel No.					
2412	1	6	12.64	0.297	12.93	30
		9	12.50	0.435	12.93	30
		12	12.38	0.569	12.95	30
		18	11.74	0.814	12.55	30
		24	11.62	1.046	12.67	30
		36	11.18	1.444	12.63	30
		48	10.92	1.820	12.74	30
		54	10.69	1.934	12.62	30
2437	6	6	13.05	0.297	13.34	30
		9	12.84	0.435	13.27	30
		12	12.83	0.569	13.40	30
		18	11.99	0.814	12.80	30
		24	11.80	1.046	12.85	30
		36	11.52	1.444	12.96	30
		48	11.31	1.820	13.13	30
		54	11.11	1.934	13.05	30
2462	11	6	11.87	0.297	12.17	30
		9	11.70	0.435	12.14	30
		12	11.71	0.569	12.28	30
		18	10.99	0.814	11.80	30
		24	10.60	1.046	11.65	30
		36	10.28	1.444	11.73	30
		48	10.03	1.820	11.85	30
		54	9.86	1.934	11.79	30

802.11n(HT20) Mode		MCS Index	Measured Power (dBm)	Duty Cycle Factor	Measured Power(dBm) + Duty Cycle Factor	Limit (dBm)
Frequency [MHz]	Channel No.					
2412	1	0	12.81	0.315	13.12	30
		1	12.39	0.600	12.99	30
		2	12.18	0.851	13.03	30
		3	11.73	1.063	12.79	30
		4	11.25	1.447	12.69	30
		5	11.04	1.777	12.82	30
		6	10.93	1.904	12.83	30
		7	10.65	2.052	12.70	30
2437	6	0	12.97	0.315	13.29	30
		1	12.72	0.600	13.31	30
		2	12.40	0.851	13.25	30
		3	11.87	1.063	12.93	30
		4	11.65	1.447	13.09	30
		5	11.19	1.777	12.97	30
		6	11.18	1.904	13.08	30
		7	10.94	2.052	12.99	30
2462	11	0	11.79	0.315	12.11	30
		1	11.56	0.600	12.16	30
		2	11.40	0.851	12.25	30
		3	10.70	1.063	11.76	30
		4	10.31	1.447	11.75	30
		5	9.99	1.777	11.77	30
		6	9.95	1.904	11.86	30
		7	9.76	2.052	11.81	30

#### 9.4 POWER SPECTRAL DENSITY

Mode	Frequency (MHz)	Channel No.	Test Result	
			Measured PSD (dBm)	Limit (dBm)
802.11b	2412	1	-6.066	8
	2437	6	-4.860	8
	2462	11	-5.684	8
802.11g	2412	1	-10.023	8
	2437	6	-9.783	8
	2462	11	-10.795	8
802.11n	2412	1	-12.894	8
	2437	6	-13.726	8
	2462	11	-14.462	8

**Note :**

1. Spectrum reading values are not plot data.


The PSD results in plot is already including the actual values of loss for the attenuator and cable combination.

2. Spectrum offset = Attenuator loss + Cable loss


3. 20.55 dB is offset for 2.4 GHz Band.

## Test Plots


Power Spectral Density (802.11b-CH 6)



Power Spectral Density (802.11g-CH 6)



Power Spectral Density (802.11n\_HT20 -CH 1)



#### Note :

In order to simplify the report, attached plots were only the worstcase PSD channel.

## 9.5 BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS


Test Result : please refer to the plot below.

In order to simplify the report, attached plots were only the worst case channel and data rate.




# Test Plots(BandEdge)

Band Edge (802.11b-CH1)




Band Edge (802.11b-CH11)




Band Edge (802.11g-CH1)




Band Edge (802.11g-CH11)



Band Edge (802.11n\_HT20 -CH1)




Band Edge (802.11n\_HT20 -CH11)



## Test Plots(Conducted Spurious Emission)


30 MHz ~ 1 GHz

Conducted Spurious Emission (802.11b\_Ch.11)




1 GHz ~ 3 GHz

Conducted Spurious Emission (802.11b\_Ch.11)




3 GHz ~ 5 GHz

Conducted Spurious Emission (802.11b\_Ch.11)




5 GHz ~ 7 GHz

Conducted Spurious Emission (802.11b\_Ch.11)




7 GHz ~ 9 GHz

## Conducted Spurious Emission (802.11b\_Ch.11)



9 GHz ~ 11 GHz


## Conducted Spurious Emission (802.11b\_Ch.11)






11 GHz ~ 13 GHz

## Conducted Spurious Emission (802.11b\_Ch.11)




13 GHz ~ 15 GHz

## Conducted Spurious Emission (802.11b\_Ch.11)




15 GHz ~ 17 GHz

## Conducted Spurious Emission (802.11b\_Ch.11)



17 GHz ~ 19 GHz


## Conducted Spurious Emission (802.11b\_Ch.11)






19 GHz ~ 21 GHz

## Conducted Spurious Emission (802.11b\_Ch.11)




21 GHz ~ 23 GHz

## Conducted Spurious Emission (802.11b\_Ch.11)



23 GHz ~ 25 GHz

Conducted Spurious Emission (802.11b\_Ch.11)



## 9.6 RADIATED SPURIOUS EMISSIONS

### Frequency Range : 9 kHz – 30MHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

#### Note:

1. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor =  $40\log(\text{specific distance} / \text{test distance})$  (dB)
3. Limit line = specific Limits (dBuV) + Distance extrapolation factor

### Frequency Range : Below 1 GHz

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dBuV/m	dBm/m	dBm	(H/V)	dBuV/m	dBuV/m	dB
No Critical peaks found							

#### Note:

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

**Frequency Range : Above 1 GHz**

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2412
Channel No.	01 Ch

Frequency [MHz]	Reading [dBuV]	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4824	45.05	2.74	V	47.79	73.98	26.19	PK
4824	32.31	2.74	V	35.05	53.98	18.93	AV
7236	47.93	8.72	V	56.65	73.98	17.33	PK
7236	40.93	8.72	V	49.65	53.98	4.33	AV
4824	44.58	2.74	H	47.32	73.98	26.66	PK
4824	32.28	2.74	H	35.02	53.98	18.96	AV
7236	46.16	8.72	H	54.88	73.98	19.10	PK
7236	40.12	8.72	H	48.84	53.98	5.14	AV

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2437
Channel No.	06 Ch

Frequency [MHz]	Reading [dBuV]	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4874	44.75	2.78	V	47.53	73.98	26.45	PK
4874	31.53	2.78	V	34.31	53.98	19.67	AV
7311	47.28	9.01	V	56.29	73.98	17.69	PK
7311	40.42	9.01	V	49.43	53.98	4.55	AV
4874	44.63	2.78	H	47.41	73.98	26.57	PK
4874	31.48	2.78	H	34.26	53.98	19.72	AV
7311	46.84	9.01	H	55.85	73.98	18.13	PK
7311	39.78	9.01	H	48.79	53.98	5.19	AV

Operation Mode: 802.11b  
 Transfer Rate: 1 Mbps  
 Operating Frequency: 2462  
 Channel No. 11 Ch

Frequency [MHz]	Reading [dBuV]	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
4924	43.70	2.43	V	46.13	73.98	27.85	PK
4924	31.35	2.43	V	33.78	53.98	20.20	AV
7386	47.36	9.44	V	56.80	73.98	17.18	PK
7386	40.47	9.44	V	49.91	53.98	4.07	AV
4924	43.61	2.43	H	46.04	73.98	27.94	PK
4924	31.28	2.43	H	33.71	53.98	20.27	AV
7386	46.50	9.44	H	55.94	73.98	18.04	PK
7386	39.56	9.44	H	49.00	53.98	4.98	AV

Operation Mode: 802.11g

Transfer Rate: 6 Mbps

Operating Frequency: 2412

Channel No. 01 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor	AN.+CL- AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4824	43.89	0.00	2.74	V	46.63	73.98	27.35	PK
4824	32.15	0.32	2.74	V	35.21	53.98	18.77	AV
7236	41.86	0.00	8.72	V	50.58	73.98	23.40	PK
7236	29.69	0.32	8.72	V	38.73	53.98	15.25	AV
4824	43.72	0.00	2.74	H	46.46	73.98	27.52	PK
4824	32.12	0.32	2.74	H	35.18	53.98	18.80	AV
7236	41.79	0.00	8.72	H	50.51	73.98	23.47	PK
7236	29.39	0.32	8.72	H	38.43	53.98	15.55	AV

Operation Mode: 802.11g

Transfer Rate: 6 Mbps

Operating Frequency: 2437

Channel No. 06 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor	AN.+CL- AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4874	43.02	0.00	2.78	V	45.80	73.98	28.18	PK
4874	31.52	0.32	2.78	V	34.62	53.98	19.36	AV
7311	41.57	0.00	9.01	V	50.58	73.98	23.40	PK
7311	29.49	0.32	9.01	V	38.82	53.98	15.16	AV
4874	42.98	0.00	2.78	H	45.76	73.98	28.22	PK
4874	31.36	0.32	2.78	H	34.46	53.98	19.52	AV
7311	41.48	0.00	9.01	H	50.49	73.98	23.49	PK
7311	29.43	0.32	9.01	H	38.76	53.98	15.22	AV

Operation Mode: 802.11g  
 Transfer Rate: 6 Mbps  
 Operating Frequency: 2462  
 Channel No.: 11 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor	AN.+CL- AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4924	43.73	0.00	2.43	V	46.16	73.98	27.82	PK
4924	31.34	0.32	2.43	V	34.09	53.98	19.89	AV
7386	41.00	0.00	9.44	V	50.44	73.98	23.54	PK
7386	29.34	0.32	9.44	V	39.10	53.98	14.88	AV
4924	43.65	0.00	2.43	H	46.08	73.98	27.90	PK
4924	31.21	0.32	2.43	H	33.96	53.98	20.02	AV
7386	40.86	0.00	9.44	H	50.30	73.98	23.68	PK
7386	29.24	0.32	9.44	H	39.00	53.98	14.98	AV

Operation Mode:	802.11n (HT20)
Transfer MCS Index:	0
Operating Frequency	2412
Channel No.	01 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor	AN.+CL- AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4824	43.65	0.00	2.74	V	46.39	73.98	27.59	PK
4824	32.08	0.35	2.74	V	35.17	53.98	18.81	AV
7236	41.69	0.00	8.72	V	50.41	73.98	23.57	PK
7236	29.56	0.35	8.72	V	38.63	53.98	15.35	AV
4824	43.21	0.00	2.74	H	45.95	73.98	28.03	PK
4824	32.00	0.35	2.74	H	35.09	53.98	18.89	AV
7236	41.58	0.00	8.72	H	50.30	73.98	23.68	PK
7236	29.33	0.35	8.72	H	38.40	53.98	15.58	AV

Operation Mode:	802.11n (HT20)
Transfer MCS Index:	0
Operating Frequency	2437
Channel No.	06 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor	AN.+CL- AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4874	43.12	0.00	2.78	V	45.90	73.98	28.08	PK
4874	31.56	0.35	2.78	V	34.69	53.98	19.29	AV
7311	41.67	0.00	9.01	V	50.68	73.98	23.30	PK
7311	29.50	0.35	9.01	V	38.86	53.98	15.12	AV
4874	43.11	0.00	2.78	H	45.89	73.98	28.09	PK
4874	31.47	0.35	2.78	H	34.60	53.98	19.38	AV
7311	41.58	0.00	9.01	H	50.59	73.98	23.39	PK
7311	29.53	0.35	9.01	H	38.89	53.98	15.09	AV




Operation Mode:	802.11n (HT20)
Transfer MCS Index:	0
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor	AN.+CL- AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measure ment Type
4924	43.85	0.00	2.43	V	46.28	73.98	27.70	PK
4924	31.29	0.35	2.43	V	34.07	53.98	19.91	AV
7386	41.11	0.00	9.44	V	50.55	73.98	23.43	PK
7386	29.23	0.35	9.44	V	39.02	53.98	14.96	AV
4924	43.86	0.00	2.43	H	46.29	73.98	27.69	PK
4924	31.31	0.35	2.43	H	34.09	53.98	19.89	AV
7386	41.06	0.00	9.44	H	50.50	73.98	23.48	PK
7386	29.18	0.35	9.44	H	38.97	53.98	15.01	AV


### Test Plots (Worst case : X-V)

Radiated Spurious Emissions plot – Average Reading (802.11b, Ch.11 3rd Harmonic)



Date: 9.DEC.2019 04:14:44

Radiated Spurious Emissions plot – Peak Reading (802.11b, Ch.11 3rd Harmonic)



Date: 9.DEC.2019 04:15:19

### Note:

Plot of worst case are only reported.

## 9.7 RADIATED RESTRICTED BAND EDGES

Operation Mode:	802.11b
Transfer Rate:	1 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV]	A.F.+CL + AMP + ATT [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	56.17	0.85	H	57.02	73.98	16.96	PK
2390.0	46.70	0.85	H	47.55	53.98	6.43	AV
2390.0	56.38	0.85	V	57.23	73.98	16.75	PK
2390.0	46.85	0.85	V	47.70	53.98	6.28	AV
2483.5	55.97	1.13	H	57.10	73.98	16.88	PK
2483.5	45.88	1.13	H	47.01	53.98	6.97	AV
2483.5	56.17	1.13	V	57.30	73.98	16.68	PK
2483.5	45.91	1.13	V	47.04	53.98	6.94	AV

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch


Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor	A.F.+CL + AMP + ATT [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	64.23	0.00	0.85	H	65.08	73.98	8.90	PK
2390.0	49.04	0.32	0.85	H	50.21	53.98	3.77	AV
2390.0	64.50	0.00	0.85	V	65.35	73.98	8.63	PK
2390.0	49.08	0.32	0.85	V	50.25	53.98	3.73	AV
2483.5	58.43	0.00	1.13	H	59.56	73.98	14.42	PK
2483.5	44.85	0.32	1.13	H	46.30	53.98	7.68	AV
2483.5	58.49	0.00	1.13	V	59.62	73.98	14.36	PK
2483.5	45.01	0.32	1.13	V	46.46	53.98	7.52	AV

Operation Mode: 802.11n (HT20)  
 Transfer MCS Index: 0  
 Operating Frequency: 2412 MHz, 2462 MHz  
 Channel No. 01 Ch, 11 Ch

Frequency [MHz]	Reading [dBuV]	Duty Cycle Factor	A.F.+CL + AMP + ATT [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Measurement Type
2390.0	65.11	0.00	0.85	H	65.96	73.98	8.02	PK
2390.0	49.58	0.35	0.85	H	50.78	53.98	3.20	AV
2390.0	65.20	0.00	0.85	V	66.05	73.98	7.93	PK
2390.0	49.71	0.35	0.85	V	50.91	53.98	3.07	AV
2483.5	59.14	0.00	1.13	H	60.27	73.98	13.71	PK
2483.5	45.62	0.35	1.13	H	47.10	53.98	6.88	AV
2483.5	59.22	0.00	1.13	V	60.35	73.98	13.63	PK
2483.5	45.73	0.35	1.13	V	47.21	53.98	6.77	AV


## Test Plots (Worst case : X-V)

Radiated Restricted Band Edges plot – Average Reading (802.11n(HT20), Ch.1)



Date: 5.DEC.2019 11:10:54

Radiated Restricted Band Edges plot – Peak Reading (802.11n(HT20), Ch.1)



Date: 5.DEC.2019 11:11:43

## Note:

Plot of worst case are only reported.

## 10. LIST OF TEST EQUIPMENT

### Conducted Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Rohde & Schwarz	ENV216 / LISN	09/11/2019	Annual	102245
Rohde & Schwarz	ESCI / Test Receiver	06/18/2019	Annual	100033
ESPAC	SU-642 / Temperature Chamber	03/12/2019	Annual	0093008124
Agilent	N9020A / Signal Analyzer	05/23/2019	Annual	MY51110085
Agilent	N9030A / Signal Analyzer	01/10/2019	Annual	MY49431210
Rohde & Schwarz	OSP 120 / Power Measurement Set	07/24/2019	Annual	101231
Agilent	N1911A / Power Meter	04/10/2019	Annual	MY45100523
Agilent	N1921A / Power Sensor	04/10/2019	Annual	MY52260025
Agilent	87300B / Directional Coupler	11/11/2019	Annual	3116A03621
Hewlett Packard	11667B / Power Splitter	05/24/2019	Annual	05001
Hewlett Packard	E3632A / DC Power Supply	06/18/2019	Annual	KR75303960
Agilent	8493C / Attenuator(10 dB)	07/02/2019	Annual	07560
Rohde & Schwarz	EMC32 / Software	N/A	N/A	N/A
HCT CO., LTD.	FCC WLAN&BT&BLE Conducted Test Software v3.0	N/A	N/A	N/A

### Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

### Radiated Test

Manufacturer	Model / Equipment	Calibration Date	Calibration Interval	Serial No.
Innco system	CO3000 / Controller(Antenna mast)	N/A	N/A	CO3000-4p
Innco system	MA4640/800-XP-EP / Antenna Position Tower	N/A	N/A	N/A
Emco	2090 / Controller	N/A	N/A	060520
Ets	Turn Table	N/A	N/A	N/A
Rohde & Schwarz	Loop Antenna	01/18/2019	Biennial	1513-175
Schwarzbeck	VULB 9168 / Hybrid Antenna	08/31/2018	Biennial	00895
Schwarzbeck	BBHA 9120D / Horn Antenna	11/18/2019	Biennial	9120D-1191
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	11/29/2019	Biennial	BBHA9170541
Rohde & Schwarz	FSP(9 kHz ~ 30 GHz) / Spectrum Analyzer	09/11/2019	Annual	836650/016
Rohde & Schwarz	FSV40-N / Spectrum Analyzer	09/26/2019	Annual	101068-SZ
Wainwright Instruments	WHKX10-2700-3000-18000-40SS / High Pass Filter	01/03/2019	Annual	4
Wainwright Instruments	WHKX8-6090-7000-18000-40SS / High Pass Filter	01/03/2019	Annual	5
Wainwright Instruments	WRCJV2400/2483.5-2370/2520-60/12SS / Band Reject Filter	06/19/2019	Annual	2
Wainwright Instruments	WRCJV5100/5850-40/50-8EEK / Band Reject Filter	01/03/2019	Annual	2
Api tech.	18B-03 / Attenuator (3 dB)	06/04/2019	Annual	2
WEINSCHL	56-10 / Attenuator(10 dB)	10/08/2019	Annual	72316
CERNEX	CBLU1183540B-01/Broadband Bench Top LNA	01/03/2019	Annual	28549
CERNEX	CBL06185030 / Broadband Low Noise Amplifier	01/03/2019	Annual	24615
CERNEX	CBL18265035 / Power Amplifier	01/03/2019	Annual	22966
CERNEX	CBL26405040 / Power Amplifier	06/18/2019	Annual	25956
TESCOM	TC-3000C / Bluetooth Tester	03/26/2019	Annual	3000C000276

### Note:

1. Equipment listed above that calibrated during the testing period was set for test after the calibration.
2. Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

**11. ANNEX A\_ TEST SETUP PHOTO**

Please refer to test setup photo file no. as follows;

No.	Description
1	HCT-RF-1912-FC020-P