**MEASUREMENT REPORT**
FCC Part 15C**Manufacturer Name & Address:**LG Electronics Inc.
222 LG-ro
Jinwi-myeon, Pyeongtaek-si
Gyeonggi-do, 17709, Korea**Date of Testing:**

3/29 - 5/24/2016

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.:

0Y1604060726-R1.BEJ

FCC ID:	BEJWC900HO
APPLICANT:	LG Electronics Inc.

Application Type:	Certification
EUT Type:	Vehicle Wireless Charger System
Model:	WC900-HO
FCC Rule Part(s):	FCC Part 15, Subpart C (15.209)
FCC Classification:	Part 15 Low Power Transmitter Below 1705 kHz (DCD)
Test Procedure:	ANSI C63.10-2013, KDB 680106 D01 v02

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

This revised Test Report (S/N: 0Y1604060726-R1.BEJ) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.


Randy Ortañez
President






FCC ID: BEJWC900HO		 PCTEST ENGINEERING LABORATORY, INC.		FCC Pt. 15C MEASUREMENT TEST REPORT		 LG		Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ		Test Dates: 3/29 - 5/24/2016		EUT Type: Vehicle Wireless Charger System				Page 1 of 25

TABLE OF CONTENTS


FCC Class C (15.209) MEASUREMENT REPORT	3
1.0 INTRODUCTION	4
1.1 Scope	4
1.2 PCTEST Test Location	4
2.0 PRODUCT INFORMATION.....	5
2.1 Equipment Description.....	5
2.2 Test Configuration	5
2.3 EMI Suppression Device(s)/Modifications	5
3.0 DESCRIPTION OF TESTS	6
3.1 Evaluation Procedure	6
3.2 Radiated Emissions.....	6
3.3 Environmental Conditions.....	6
4.0 SAMPLE CALCULATIONS	7
4.1 Radiated Emission Measurement Sample Calculation	7
5.0 Measurement Uncertainty	8
6.0 TEST EQUIPMENT CALIBRATION DATA	9
7.0 TEST DATA.....	10
7.1 Summary	10
7.2 Radiated Measurement Data.....	11
8.0 CONCLUSION.....	25

FCC ID: BEJWC900HO		FCC Pt. 15C MEASUREMENT TEST REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 2 of 25



MEASUREMENT REPORT

FCC Part 15C



§ 2.1033 General Information

MANUFACTURER: LG Electronics Inc.
MANUFACTURER ADDRESS: 222 LG-ro
Jinwi-myeon, Pyeongtaek-si
Gyeonggi-do, 17709, Korea
TEST SITE: PCTEST ENGINEERING LABORATORY, INC.
TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21046 USA
FCC RULE PART(S): Part 15 Subpart C
MODEL: WC900-HO
EUT TYPE: Vehicle Wireless Charger System
Test Device Serial No.: 22MAR-2, 4,5 ☐ Production ☒ Pre-Production ☐ Engineering
FCC CLASSIFICATION: Part 15 Low Power Transmitter Below 1705 kHz (DCD)
DATE(S) OF TEST: 3/29 - 5/24/2016



Test Methodology

Both conducted and radiated measurements were taken using the methods and procedures described in ANSI C63.10-2013. Radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility / NVLAP Accreditation

Conducted and radiated tests were performed at PCTEST Engineering Lab in Columbia, MD 21046, U.S.A.

- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP) in EMC, Telecommunication, and FCC for satisfactory compliance with criteria established in Title 15, Part 285 Code of Federal Regulations. (NVLAP Lab code: 100431-0).
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.

FCC ID: BEJWC900HO	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT TEST REPORT	 LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System	Page 3 of 25	

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission.

1.2 PCTEST Test Location

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intern't'l (BWI) airport, the city of Baltimore and the Washington, DC area. (see Figure 1-1).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The site coordinates are 39° 10'23" N latitude and 76° 49'50" W longitude. The facility is 0.4 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2014 on January 22, 2015.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: BEJWC900HO	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT TEST REPORT	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 4 of 25

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **LGE Vehicle Wireless Charger System Model: WC900-HO**. The test data contained in this report pertains only to the emissions due to the digital circuitry of the EUT.



2.2 Test Configuration

The LGE Vehicle Wireless Charger System Model: WC900-HO is a vehicle power transfer device (pad). It was connected to a 12V DC Power Supply, and turned on. Two wireless power receiver blocks (dummy loads) were used for testing with the charging pad. One block was compliant with the WPC charging protocol and the other block was compliant with the PMA charging protocol.

All equipment is placed on the test table top and arranged in a typical configuration in accordance with ANSI C63.10-2013. For more information, please see Section 7.0 for test data and the test setup photos document for the test setup photographs.

2.3 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: BEJWC900HO	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT TEST REPORT	 LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 5 of 25

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedure described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2013) was used in the measurement of radiated and conducted emissions from the **LGE Vehicle Wireless Charger System Model: WC900-HO**.

Deviation from measurement procedure.....None

3.2 Radiated Emissions



The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, a 72.4cm high PVC support structure is placed on top of the turntable. A 3" (~7.6cm) sheet of high density polystyrene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm. For measurements above 1GHz, a high density expanded polystyrene block is placed on top of the test table to bring the total table height to 1.5m.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband loop antenna from 9kHz up to 30MHz and broadband hybrid antenna from 30MHz up to 1GHz. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 0.8 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission.

3.3 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: BEJWC900HO		FCC Pt. 15C MEASUREMENT TEST REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 6 of 25

4.0 SAMPLE CALCULATIONS

4.1 Radiated Emission Measurement Sample Calculation

@ 66.7 MHz



Class B limit	= 100 $\mu\text{V/m}$ = 40.0 dB $\mu\text{V/m}$
Reading	= - 76.0 dBm (calibrated level)
Convert to dB μV	= - 76.0 + 107 = 31.0 dB μV
Antenna Factor + Cable Loss	= 5.8 dB/m
Total	= 36.8 dB $\mu\text{V/m}$

Margin	= 36.8 - 40.0 = - 3.2 dB
	= 3.2 dB below limit

Note:

Level [dB μV] = 20 log₁₀ (Level [$\mu\text{V/m}$])



Level [dB μV] = Level [dBm] + 107

FCC ID: BEJWC900HO		FCC Pt. 15C MEASUREMENT TEST REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 7 of 25

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty (\pm dB)
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07

FCC ID: BEJWC900HO		FCC Pt. 15C MEASUREMENT TEST REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 8 of 25

6.0 TEST EQUIPMENT CALIBRATION DATA



Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	RE3	Radiated Emissions Cable Set	11/18/2015	Annual	5/18/2016	RE3
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	3/4/2016	Annual	9/4/2016	RE1
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	7/30/2015	Biennial	7/30/2017	121034
Com-Power	PAM-103	Pre-Amplifier (1-1000MHz)	2/26/2016	Annual	2/26/2017	441119
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	7/17/2015	Annual	7/17/2016	100348
Seekonk	NC-100	Torque Wrench 5/16", 8" lbs	3/2/2016	Biennial	3/2/2018	N/A
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	3/14/2016	Biennial	3/14/2018	A051107

Table 6-1. Annual Test Equipment Calibration Schedule

Note:

For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: BEJWC900HO		FCC Pt. 15C MEASUREMENT TEST REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System	Page 9 of 25	

7.0 TEST DATA

7.1 Summary

Test Date(s): 3/29 - 5/24/2016

Test Engineer:



Mohamed Elshahhat

FCC Part 15 Section	Description	Result
15.209	Radiated Emissions	PASS

Table 7-1. Summary of Test Results

Frequency [MHz]	Field Strength Limit [dB μ V/m]	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 – 960	200	3
> 960	500	3

Table 7-2. Radiated Limits (Section 15.209)

FCC ID: BEJWC900HO		FCC Pt. 15C MEASUREMENT TEST REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 10 of 25

7.2 Radiated Measurement Data

§15.209

Test Procedures Used

ANSI C63.10-2013

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer frequency set to the frequency of the radiated spurious emission of interest
2. Per the CISPR 16-1-1 standard, the RBW's are as follows:
 9kHz – 150kHz (Band A): 200Hz
 150kHz – 30MHz (Band B): 9kHz
 30MHz – 1GHz (Band C): 120kHz
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. Radiated Test Setup < 30MHz

FCC ID: BEJWC900HO	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT TEST REPORT	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 11 of 25




Figure 7-2. Radiated Test Setup < 1GHz

Sample Calculation:

- Field Strength Level [dB μ V/m] = Analyzer Level [dBm] + 107 + AFCL [dB]

Notes:



- AFCL = Antenna Factor [dB] + Cable Loss [dB]

Notes:

- All modes of operation were investigated and the worst-case emissions are reported.
- Radiated emissions were measured from 9kHz –1GHz.
- The radiated limits for unintentional radiators at a distance of 3 meters are used in the Table 7-2.
- All readings are calibrated by a signal generator with accuracy traceable to the National Institute of Standards and Technology (NIST).
- AFCL (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
- Level (dB μ V/m) = Analyzer Reading (dBm) + AFCL (dB/m) + 107
- Margin (dB) = Field strength (dB μ V/m) – Limit (dB μ V/m)
- Radiated measurements below 30MHz employed the Compower Active Loop Antenna. The antenna was positioned in three orthogonal planes (X front, Y side, Z top) and the position with the highest emission level is reported above.
- For measurements made below 1GHz, the results recorded using the broadband antenna are known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antennas was found to be less than 2:1.
- Calibrated low-loss microwaves cables are used.


FCC ID: BEJWC900HO	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT TEST REPORT	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 12 of 25

11. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. These plots were taken without using the correction factor. Any emissions found to be within 20dB of the limit (after applying the correction factor) are fully investigated and the results are shown in tables 7-3 and 7-4.


FCC ID: BEJWC900HO		FCC Pt. 15C MEASUREMENT TEST REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System	Page 13 of 25	

Radiated Spurious Emissions Measurements - PMA

\$15.209



Plot 7-1. Radiated Spurious Plot below 30 MHz (Pol. X)




Plot 7-2. Radiated Spurious Plot below 30MHz (Pol. X)


FCC ID: BEJWC900HO	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT TEST REPORT	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 14 of 25

Radiated Spurious Emissions Measurements - PMA

\$15.209



Plot 7-3. Radiated Spurious Plot below 30 MHz (Pol. Y)




Plot 7-4. Radiated Spurious Plot below 30MHz (Pol. Y)


FCC ID: BEJWC900HO	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT TEST REPORT	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 15 of 25

Radiated Spurious Emissions Measurements - PMA

\$15.209



Plot 7-5. Radiated Spurious Plot below 30 MHz (Pol. Z)




Plot 7-6. Radiated Spurious Plot below 30MHz (Pol. Z)


FCC ID: BEJWC900HO	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT TEST REPORT	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 16 of 25

Radiated Spurious Emissions Measurements - PMA

\$15.209



Plot 7-7. Radiated Spurious Plot above 30 MHz (Pol. H)




Plot 7-8. Radiated Spurious Plot above 30MHz (Pol. V)


FCC ID: BEJWC900HO	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT TEST REPORT	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 17 of 25

Radiated Spurious Emissions Measurements - WPC

\$15.209



Plot 7-9. Radiated Spurious Plot below 30 MHz (Pol. X)




Plot 7-10. Radiated Spurious Plot below 30MHz (Pol. X)


FCC ID: BEJWC900HO	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT TEST REPORT	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 18 of 25

Radiated Spurious Emissions Measurements - WPC

\$15.209




Plot 7-11. Radiated Spurious Plot below 30 MHz (Pol. Y)




Plot 7-12. Radiated Spurious Plot below 30MHz (Pol. Y)

FCC ID: BEJWC900HO	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT TEST REPORT	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 19 of 25



Radiated Spurious Emissions Measurements - WPC



Plot 7-13. Radiated Spurious Plot below 30MHz (Pol. Z)




Plot 7-14. Radiated Spurious Plot below 30MHz (Pol. Z)


FCC ID: BEJWC900HO	 FCC Pt. 15C MEASUREMENT TEST REPORT 		Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System	Page 20 of 25

Radiated Spurious Emissions Measurements - WPC

\$15.209



Plot 7-15. Radiated Spurious Plot above 30 MHz (Pol. H)



Plot 7-16. Radiated Spurious Plot above 30MHz (Pol. V)

FCC ID: BEJWC900HO	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT TEST REPORT	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 21 of 25

Radiated Spurious Emissions Measurements



\$15.209

Frequency [MHz]	Antenna Position	Antenna Height [cm]	Turntable Azimuth [degree]	Level [dBm]	AFCL [dB/m]	3m Field Strength [dBμV/m]	Distance Correction Factor (dB)	Field Strengths [dBμV/m] For A. .009-.49MHz: 300m Distance B. 0.4901-1.705MHz: 30m Distance C. 1.705 - 30MHz: 30m Distance D. 30MHz - 1GHz: 3m Distance	Corresponding Limit [dBμV/m]	Margin [dB]
0.061	Y	110	200	-67.41	14.68	54.27	-80.00	-25.73	31.86	-57.58
0.087	Y	125	222	-70.59	14.48	50.89	-80.00	-29.11	28.79	-57.90
0.111	X	110	122	-32.98	14.20	88.22	-80.00	8.22	26.71	-18.49
0.113	X	112	149	-65.90	14.19	55.29	-80.00	-24.71	26.54	-51.25
0.166	X	115	150	-60.93	14.14	60.21	-80.00	-19.79	23.20	-42.99
2.000	X	128	300	-80.67	14.41	40.75	-40.00	0.74	29.54	-28.80
200.020	H	100	320	-95.76	18.69	29.94	0.00	29.94	46.02	-16.09

Table 7-3. Radiated Measurements at 3-meters (with PMA Block)

Frequency [MHz]	Antenna Position	Antenna Height [cm]	Turntable Azimuth [degree]	Level [dBm]	AFCL [dB/m]	3m Field Strength [dBμV/m]	Distance Correction Factor (dB)	Field Strengths [dBμV/m] For A. .009-.49MHz: 300m Distance B. 0.4901-1.705MHz: 30m Distance C. 1.705 - 30MHz: 30m Distance D. 30MHz - 1GHz: 3m Distance	Corresponding Limit [dBμV/m]	Margin [dB]
0.036	Z	110	122	-66.99	15.43	55.44	-80.00	-24.56	36.48	-61.04
0.045	Z	112	200	-67.80	14.84	54.04	-80.00	-25.96	34.54	-60.50
0.094	Z	114	350	-76.74	14.39	44.65	-80.00	-35.35	28.14	-63.50
0.111	Z	110	120	-46.09	14.19	75.10	-80.00	-4.90	26.70	-31.59
0.150	Y	125	145	-66.85	14.15	54.30	-80.00	-25.70	24.08	-49.78
2.106	X	132	100	-71.98	14.41	49.43	-40.00	9.43	29.54	-20.11
180.117	H	110	150	-94.77	18.88	31.12	0.00	31.12	46.02	-14.91

Table 7-4. Radiated Measurements at 3-meters (with WPC Block)


FCC ID: BEJWC900HO		FCC Pt. 15C MEASUREMENT TEST REPORT		Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 22 of 25

Radiated Restricted Band Edge Measurements §15.205 §15.209

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna.

Supported Wireless Charging Protocol PMA

Restricted Band Frequency Span 90kHz -110kHz




Date: 24.MAY.2016 18:19:44

Plot 7-17. Radiated Restricted Band Measurement (PMA)

FCC ID: BEJWC900HO	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT TEST REPORT	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 23 of 25

Supported Wireless Charging Protocol WPC

Restricted Band Frequency Span 90kHz -110kHz





Date: 24.MAY.2016 18:15:48

Plot 7-18. Radiated Restricted Band Measurement (WPC)

FCC ID: BEJWC900HO	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT TEST REPORT	LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 24 of 25

8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **LGE Vehicle Wireless Charger System Model: WC900-HO** has been verified to comply with the requirements specified in Part 15 (§15.209) of the FCC Rules.

FCC ID: BEJWC900HO	 PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15C MEASUREMENT TEST REPORT	 LG	Reviewed by: Quality Manager
Test Report S/N: 0Y1604060726-R1.BEJ	Test Dates: 3/29 - 5/24/2016	EUT Type: Vehicle Wireless Charger System		Page 25 of 25