

**FCC PART 15.247
TEST REPORT**

For

REALTRACE

2, rue Georges Pompidou, 91140 VILLEBON SUR YVETTE. FRANCE

FCC ID: BSORT100V8

Report Type: Original Report	Product Type: PetScan RT100-V8
Test Engineer: Simon Wang <i>Simon Wang</i>	
Report Number: RSZ130325002-00A	
Report Date: 2013-04-15	
Reviewed By: RF Engineer	Sula Huang <i>Sula Huang</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
EUT EXERCISE SOFTWARE	5
LOCAL SUPPORT EQUIPMENT.....	5
EXTERNAL I/O CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE	8
APPLICABLE STANDARD	8
RESULT	8
FCC §15.203 – ANTENNA REQUIREMENT.....	9
APPLICABLE STANDARD	9
ANTENNA CONNECTOR CONSTRUCTION	9
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	10
APPLICABLE STANDARD	10
EUT SETUP	10
EMI TEST RECEIVER SETUP.....	10
TEST PROCEDURE	11
TEST EQUIPMENT LIST AND DETAILS.....	11
CORRECTED FACTOR & MARGIN CALCULATION	11
TEST RESULTS SUMMARY	11
TEST DATA	12
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	15
TEST PROCEDURE	15
CORRECTED AMPLITUDE & MARGIN CALCULATION	15
TEST EQUIPMENT LIST AND DETAILS.....	15
TEST RESULTS SUMMARY	16
TEST DATA	16
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	19
APPLICABLE STANDARD	19
TEST PROCEDURE	19
TEST EQUIPMENT LIST AND DETAILS.....	19
TEST DATA	19
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	26

APPLICABLE STANDARD	26
TEST PROCEDURE	26
TEST EQUIPMENT LIST AND DETAILS.....	26
TEST DATA	26
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST EQUIPMENT LIST AND DETAILS.....	32
TEST DATA	32
FCC §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWELL TIME).....	35
APPLICABLE STANDARD	35
TEST PROCEDURE	35
TEST EQUIPMENT LIST AND DETAILS.....	35
TEST DATA	35
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	51
APPLICABLE STANDARD	51
TEST PROCEDURE	51
TEST EQUIPMENT LIST AND DETAILS.....	51
TEST DATA	51
FCC §15.247(d) - BAND EDGES TESTING	57
APPLICABLE STANDARD	57
TEST PROCEDURE	57
TEST EQUIPMENT LIST AND DETAILS.....	57
TEST DATA	57

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *REALTRACE*'s product, model number: *RT100 V8 (FCC ID: BSORT100V8)* or the "EUT" in this report was a PetScan RT100-V8, which was measured approximately: 15.5 cm (L) x 8.2 cm (W) x 3.3 cm (H), rated input voltage: 3.7V rechargeable Li-ion battery or DC 5V charging from USB Port.

** All measurement and test data in this report was gathered from production sample serial number: 1303094 (Assigned by BACL, Shenzhen). The EUT was received on 2013-03-25.*

Objective

This test report is prepared on behalf of *REALTRACE* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.209 DCD submissions with FCC ID: BSORT100V8.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing with test software.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

CSR Bluetooth 2.2

Local Support Equipment


Manufacturer	Description	Model	Serial Number
DELL	PC	DELL 170L	CN-0TC670-70821-560-F4WQ
DELL	LCD Monitor	E178WFPC	CN-OWY564-64180-7C4-2SQH
DELL	Mouse	MOC5UO	G1B0096D
DELL	Keyboard	L100	CNORH656658907BL04TY
SAST	Modem	AEM-2100	0293

External I/O Cable

Cable Description	Length (m)	From/Port	To
Unshielded Detachable K/B Cable	1.5	Host PC	K/B
Unshielded Detachable USB Cable	1.5	Host PC	Mouse
Unshielded Detachable VGA Cable	1.5	Host PC	Monitor
Shielded Detachable Serial Cable	1.2	Host PC	Modem
Unshielded detachable USB Cable	1.0	EUT	PC

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

FCC§15.247 (i), §1.1307 (b) (1) &§2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance v05

Result

According to FCC KDB 447498 D01 General RF Exposure Guidance v05 generic portable criteria

The distance between antenna and test point is 5 mm

The Max output power: 4.375 mW

According to the Appendix A of KDB 447498, the exclusion thresholds for 2450 MHz is 10 mW.

Conclusion:

The time-averaged output power is 4.375 mW < the SAR exclusion thresholds is 10 mW

So stand-alone SAR evaluation is not required

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has an integral antenna arrangement for bluetooth, which was permanently attached, the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the internal photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.4-2009. The related limit was specified in FCC Part 15.207.

The spacing between the relevant peripherals was 10 cm.

The Host PC was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the Host PC and other related equipments were connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2012-11-24	2013-11-23
Rohde & Schwarz	L.I.S.N.	ESH2-Z5	892107/021	2012-08-22	2013-08-21
Com-Power	L.I.S.N.	LI-200	12005	N/A	N/A
Rohde & Schwarz	Pulse limiter	ESH3Z2	DE25985	2012-08-09	2013-08-09
BACL	CE Test software	BACL-CE	V1.0	-	-

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Pulse Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Pulse Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

6.44 dB at 1.765 MHz in the Line conducted mode


Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa


The testing was performed by Simon Wang on 2013-04-10.

EUT operation mode: Charging & transmitting

AC 120V/60 Hz, Line:



Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
1.765	39.56	10.20	46.00	6.44	Ave.
1.890	37.49	10.20	46.00	8.51	Ave.
1.105	36.37	10.20	46.00	9.63	Ave.
8.845	39.33	10.36	50.00	10.67	Ave.
1.510	34.97	10.20	46.00	11.03	Ave.
5.025	35.16	10.20	50.00	14.84	Ave.
1.765	39.96	10.20	56.00	16.04	QP
1.890	38.04	10.20	56.00	17.96	QP
8.845	41.93	10.36	60.00	18.07	QP
1.510	37.29	10.20	56.00	18.71	QP
1.105	36.99	10.20	56.00	19.01	QP
5.025	36.25	10.20	60.00	23.75	QP

AC 120V/60 Hz, Neutral:



Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
1.765	39.37	10.20	46.00	6.63	Ave.
1.890	37.19	10.20	46.00	8.81	Ave.
1.105	34.71	10.20	46.00	11.29	Ave.
1.510	33.70	10.20	46.00	12.30	Ave.
0.200	41.90	10.10	54.57	12.67	Ave.
8.950	37.08	10.30	50.00	12.92	Ave.
1.765	39.56	10.20	56.00	16.44	QP
1.890	37.85	10.20	56.00	18.15	QP
1.510	36.13	10.20	56.00	19.87	QP
1.105	35.24	10.20	56.00	20.76	QP
0.200	42.68	10.10	64.57	21.89	QP
8.950	37.73	10.30	60.00	22.27	QP

Note:

- 1) Correction Factor = LISN/ISN VDF (Voltage Division Factor) + Cable Loss + Pulse Limiter Attenuation
The corrected factor has been input into the transducer of the test software.
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

EUT Setup**Below 1 GHz:****Above 1 GHz:**

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Corrected Factor}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	8447E	1937A01046	2012-11-24	2013-11-23
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2012-08-08	2013-08-07
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2014-11-27
SUPER ULTRA	Amplifier	ZVA-213+	N/A	2012-11-24	2013-11-23
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-01	2014-11-30
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2012-11-24	2013-11-23
the electro-Mechanics Co.	Horn Antenna	3116	9510-2270	2010-10-14	2013-10-13

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

9.48 dB at 4804.0 MHz in the **Horizontal** polarization

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Simon Wang on 2013-04-10.

EUT operation mode: Transmitting

30 MHz -25 GHz: (Scan with GFSK, $\pi/4$ -DQPSK, 8-DPSK, the worst case is BDR Mode (GFSK))

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (2402 MHz)									
336.03	43.69	QP	33	1.1	H	-13.5	30.19	46	15.81
2402.0	88.08	PK	158	1.1	H	6.13	94.21	/	/
2402.0	49.73	Ave.	158	1.1	H	6.13	55.86	/	/
2402.0	90.61	PK	169	1.3	V	6.13	96.74	/	/
2402.0	52.88	Ave.	169	1.3	V	6.13	59.01	/	/
4804.0	32.12	Ave.	257	1.3	H	12.40	44.52	54	9.48
9608.0	24.17	Ave.	93	1.2	V	19.28	43.45	54	10.55
4804.0	50.16	PK	257	1.3	H	12.40	62.56	74	11.44
7206.0	24.93	Ave.	117	1.4	V	17.06	41.99	54	12.01
7206.0	40.96	PK	117	1.4	V	17.06	58.02	74	15.98
9608.0	38.45	PK	93	1.2	V	19.28	57.73	74	16.27
2386.3	27.13	Ave.	156	1.5	V	6.13	33.26	54	20.74
2496.2	25.99	Ave.	18	1.2	V	7.21	33.20	54	20.80
2312.7	27.29	Ave.	116	1.2	V	5.48	32.77	54	21.23
2496.2	40.99	PK	18	1.2	V	7.21	48.20	74	25.80
2386.3	41.72	PK	156	1.5	V	6.13	47.85	74	26.15
2312.7	41.84	PK	116	1.2	V	5.48	47.32	74	26.68
Middle Channel (2441 MHz)									
336.03	43.86	QP	21	1.1	H	-13.5	30.36	46	15.64
2441.0	88.41	PK	202	1.0	H	7.21	95.62	/	/
2441.0	51.77	Ave.	202	1.0	H	7.21	58.98	/	/
2441.0	88.06	PK	52	1.4	V	7.21	95.27	/	/
2441.0	51.46	Ave.	52	1.4	V	7.21	58.67	/	/
4882.0	31.49	Ave.	165	1.0	V	12.46	43.95	54	10.05
9764.0	24.23	Ave.	108	1.3	H	19.40	43.63	54	10.37
7323.0	24.47	Ave.	243	1.4	V	16.49	40.96	54	13.04
4882.0	47.83	PK	165	1.0	V	12.46	60.29	74	13.71
9764.0	39.24	PK	108	1.3	H	19.40	58.64	74	15.36
7323.0	39.04	PK	243	1.4	V	16.49	55.53	74	18.47
2497.3	26.19	Ave.	318	1.0	H	7.21	33.40	54	20.60
2488.7	26.17	Ave.	62	1.2	H	7.21	33.38	54	20.62
2382.1	26.98	Ave.	351	1.3	V	6.13	33.11	54	20.89
2497.3	41.02	PK	318	1.0	H	7.21	48.23	74	25.77
2488.7	40.82	PK	62	1.2	H	7.21	48.03	74	25.97
2382.1	41.75	PK	351	1.3	V	6.13	47.88	74	26.12

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.247/205/209	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
High Channel (2480 MHz)									
336.03	43.53	QP	158	1.1	H	-13.5	30.03	46	15.97
2480.0	88.27	PK	44	1.1	H	7.21	95.48	/	/
2480.0	49.52	Ave.	44	1.1	H	7.21	56.73	/	/
2480.0	89.80	PK	298	1.0	V	7.21	97.01	/	/
2480.0	50.31	Ave.	298	1.0	V	7.21	57.52	/	/
4960.0	31.45	Ave.	99	1.1	V	12.50	43.95	54	10.05
9920.0	24.14	Ave.	180	1.2	V	19.38	43.52	54	10.48
4960.0	48.43	PK	99	1.1	V	12.50	60.93	74	13.07
7440.0	24.75	Ave.	345	1.0	H	15.90	40.65	54	13.35
9920.0	39.30	PK	180	1.2	V	19.38	58.68	74	15.32
2483.5	50.36	PK	90	1.0	V	7.21	57.57	74	16.43
2483.5	29.90	Ave.	90	1.0	V	7.21	37.11	54	16.89
2485.6	29.82	Ave.	204	1.3	V	7.21	37.03	54	16.97
2485.6	49.66	PK	204	1.3	V	7.21	56.87	74	17.13
7440.0	40.60	PK	345	1.0	H	15.90	56.50	74	17.50
2322.3	26.68	Ave.	186	1.5	H	5.48	32.16	54	21.84
2322.3	40.89	PK	186	1.5	H	5.48	46.37	74	27.63

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST**Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2012-08-08	2013-08-07

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	100.1 kPa

The testing was performed by Simon Wang on 2013-04-09.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following tables and plots

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	$\geq$ Limit (MHz)	Result
BDR (GFSK)	Low	2402	1.000	0.613	Pass
	Adjacent	2403			
	Middle	2441	1.000	0.613	Pass
	Adjacent	2442			
	High	2480	1.000	0.613	Pass
	Adjacent	2479			
EDR ($\pi/4$-DQPSK)	Low	2402	1.000	0.813	Pass
	Adjacent	2403			
	Middle	2441	1.000	0.813	Pass
	Adjacent	2442			
	High	2480	1.000	0.813	Pass
	Adjacent	2479			
EDR (8DPSK)	Low	2402	1.000	0.805	Pass
	Adjacent	2403			
	Middle	2441	1.000	0.805	Pass
	Adjacent	2442			
	High	2480	1.000	0.805	Pass
	Adjacent	2479			


Note: Limit = 20 dB bandwidth *2/3

BDR (GFSK): Low Channel




Date: 9.APR.2013 01:03:40

BDR (GFSK): Middle Channel




Date: 9.APR.2013 01:05:15

BDR (GFSK): High Channel




Date: 9.APR.2013 01:06:23

EDR ($\pi/4$ -DQPSK): Low Channel




Date: 9.APR.2013 01:10:32

EDR ($\pi/4$ -DQPSK): Middle Channel




Date: 9.APR.2013 01:09:22

EDR ($\pi/4$ -DQPSK): High Channel




Date: 9.APR.2013 01:07:53

EDR (8DPSK): Low Channel




Date: 9.APR.2013 01:12:03

EDR (8DPSK): Middle Channel



Date: 9.APR.2013 01:13:16

EDR (8DPSK): High Channel



Date: 9.APR.2013 01:14:34

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH**Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2012-08-08	2013-08-07

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.1 kPa

The testing was performed by Simon Wang on 2013-04-09.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following tables and plots

Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.920
	Middle	2441	0.920
	High	2480	0.920
EDR ($\pi/4$ -DQPSK)	Low	2402	1.220
	Middle	2441	1.220
	High	2480	1.220
EDR (8DPSK)	Low	2402	1.208
	Middle	2441	1.208
	High	2480	1.208

1 PK MAXH

Ref 17 dBm Att 40 dB RBW 10 kHz VBW 30 kHz SWT 20 ms Delta 1 [T1] 0.11 dB 920.00000000 GHz

Offset 4.5 dB Marker 1 [T1] -19.22 dBm 2.401620000 GHz

D1 0.89 dBm D2 -19.11 dBm


1 1

3DB AC

Center 2.402 GHz 200 kHz/ Span 2 MHz


Page 27 of 60

BDR (GFSK): Middle Channel




Date: 9.APR.2013 00:33:36

BDR (GFSK): High Channel




Date: 9.APR.2013 00:35:02

EDR ($\pi/4$ -DQPSK): Low Channel




Date: 9.APR.2013 00:40:29

EDR ($\pi/4$ -DQPSK): Middle Channel




Date: 9.APR.2013 00:39:11

EDR ($\pi/4$ -DQPSK): High Channel




Date: 9.APR.2013 00:37:45

EDR (8DPSK): Low Channel




Date: 9.APR.2013 00:42:41

EDR (8DPSK): Middle Channel



Date: 9.APR.2013 00:44:34

EDR (8DPSK): High Channel



Date: 9.APR.2013 00:45:57

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2012-08-08	2013-08-07

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	100.1 kPa


The testing was performed by Simon Wang on 2013-04-09.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following tables and plots


Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR (π/4-DQPSK)	2400-2483.5	79	≥15
EDR (8DPSK)	2400-2483.5	79	≥15

BDR (GFSK): Number of Hopping Channels




Date: 9.APR.2013 01:32:17

EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



Date: 9.APR.2013 01:27:24

(8DPSK): Number of Hopping Channels



Date: 9.APR.2013 01:22:28

FCC §15.247(a) (1) (iii) -TIME OF OCCUPANCY (DWEELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as 0.4 X channel no. (s), the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell time = Pulse time*hope rate/number of hopping channels*31.6S

Hop rate=1600/S

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2012-08-08	2013-08-07

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	100.1 kPa

The testing was performed by Simon Wang on 2013-04-09.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to following tables and plots

Mode		Channel	Pulse Width (ms)	Dwell Time (S)	Limit (S)	Result
BDR (GFSK)	DH 1	Low	0.530	0.170	0.4	Pass
		Middle	0.530	0.170	0.4	Pass
		High	0.530	0.170	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH 3	Low	1.800	0.288	0.4	Pass
		Middle	1.800	0.288	0.4	Pass
		High	1.800	0.288	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH 5	Low	3.060	0.326	0.4	Pass
		Middle	3.060	0.326	0.4	Pass
		High	3.060	0.326	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR ($\pi/4$ -DQPSK)	DH 1	Low	0.540	0.173	0.4	Pass
		Middle	0.540	0.173	0.4	Pass
		High	0.540	0.173	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH 3	Low	1.806	0.289	0.4	Pass
		Middle	1.806	0.289	0.4	Pass
		High	1.806	0.289	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH 5	Low	3.060	0.326	0.4	Pass
		Middle	3.060	0.326	0.4	Pass
		High	3.060	0.326	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	DH 1	Low	0.540	0.173	0.4	Pass
		Middle	0.540	0.173	0.4	Pass
		High	0.540	0.173	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH 3	Low	1.818	0.291	0.4	Pass
		Middle	1.818	0.291	0.4	Pass
		High	1.818	0.291	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH 5	Low	3.060	0.326	0.4	Pass
		Middle	3.060	0.326	0.4	Pass
		High	3.060	0.326	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				


BDR (GFSK):

Pulse time, Low Channel, DH1




Date: 9.APR.2013 23:15:12

Pulse time, Middle Channel, DH1




Date: 9.APR.2013 23:17:09

Pulse time, High Channel, DH1



Date: 9.APR.2013 23:17:50

Pulse time, Low Channel, DH3



Date: 9.APR.2013 23:36:04


Ref 17 dBm * Att 40 dB RBW 1 MHz Delta 1 [T1] 1.96 dB
 * VBW 3 MHz SWT 3 ms 1.800000 ms

Offset 4.5 dB Marker 1 [T1] -49.02 dBm
 -110.000000 μs

1 PK MAX TRG -4.7 dBm


Center 2.441 GHz 300 μs/

Pulse time, High Channel, DH3




Page 39 of 60

Pulse time, Low Channel, DH5




Date: 9.APR.2013 23:50:21


Pulse time, Middle Channel, DH5



Date: 9.APR.2013 23:51:12


Pulse time, High Channel, DH5

Date: 9.APR.2013 23:51:28

EDR ($\pi/4$ -DQPSK):**Pulse time, Low Channel, DH1**


Date: 9.APR.2013 23:21:26

Pulse time, Middle Channel, DH1




Date: 9.APR.2013 23:20:01

Pulse time, High Channel, DH1




Date: 9.APR.2013 23:19:36

Pulse time, Low Channel, DH3




Date: 9.APR.2013 23:37:39

Pulse time, Middle Channel, DH3




Date: 9.APR.2013 23:39:09

Pulse time, High Channel, DH3




Date: 9.APR.2013 23:41:07

Pulse time, Low Channel, DH5




Date: 9.APR.2013 23:54:06

Pulse time, Middle Channel, DH5



Date: 9.APR.2013 23:53:43


Pulse time, High Channel, DH5



Date: 9.APR.2013 23:52:33


EDR (8DPSK):

Pulse time, Low Channel, DH1




Date: 9.APR.2013 23:22:29

Pulse time, Middle Channel, DH1




Date: 9.APR.2013 23:23:01

Pulse time, High Channel, DH1




Date: 9.APR.2013 23:24:39

Pulse time, Low Channel, DH3




Date: 9.APR.2013 23:45:27

Pulse time, Middle Channel, DH3




Date: 9.APR.2013 23:44:39

Pulse time, High Channel, DH3




Date: 9.APR.2013 23:43:32

Pulse time, Low Channel, DH5




Date: 9.APR.2013 23:55:11

Pulse time, Middle Channel, DH5



Date: 9.APR.2013 23:56:17

Pulse time, High Channel, DH5



Date: 9.APR.2013 23:57:15

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI test receiver.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2012-08-08	2013-08-07

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	100.1 kPa

The testing was performed by Simon Wang on 2013-04-09.

EUT operation mode: Transmitting


Test Result: Compliance. Please refer to following tables and plots

Mode	Channel	Frequency (MHz)	Conducted Output Power		Limit (mW)
			(dBm)	(mW)	
BDR (GFSK)	Low	2402	6.41	4.375	1000
	Middle	2441	4.94	3.119	1000
	High	2480	5.95	3.936	1000
EDR ($\pi/4$-DQPSK)	Low	2402	4.08	2.559	1000
	Middle	2441	2.40	1.738	1000
	High	2480	3.26	2.118	1000
EDR (8DPSK)	Low	2402	4.37	2.735	1000
	Middle	2441	2.74	1.879	1000
	High	2480	3.61	2.296	1000

BDR (GFSK): Low Channel


Date: 9.APR.2013 01:00:48

BDR (GFSK): Middle Channel




Date: 9.APR.2013 00:59:38

BDR (GFSK): High Channel




Date: 9.APR.2013 00:58:01

EDR($\pi/4$ -DQPSK): Low Channel




Date: 9.APR.2013 00:53:12

EDR($\pi/4$ -DQPSK): Middle Channel




Date: 9.APR.2013 00:53:53

EDR($\pi/4$ -DQPSK): High Channel




Date: 9.APR.2013 00:56:29

EDR(8DPSK): Low Channel




Date: 9.APR.2013 00:50:47

EDR(8DPSK): Middle Channel



Date: 9.APR.2013 00:50:09

EDR(8DPSK): High Channel



Date: 9.APR.2013 00:47:13

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2012-08-08	2013-08-07

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	50 %
ATM Pressure:	100.1 kPa

The testing was performed by Simon Wang on 2013-04-09.

EUT operation mode: Transmitting


Test Result: Compliance. Please refer to following plots

BDR (GFSK): Band Edge-Left Side




Date: 9.APR.2013 01:34:10

BDR (GFSK): Band Edge-Right Side




Date: 9.APR.2013 01:35:41

EDR ($\pi/4$ -DQPSK): Band Edge-Left Side




Date: 9.APR.2013 01:39:14

EDR ($\pi/4$ -DQPSK): Band Edge-Right Side




Date: 9.APR.2013 01:37:09

EDR (8DPSK): Band Edge-Left Side



Date: 9.APR.2013 01:40:41

BDR (8DPSK): Band Edge-Right Side



Date: 9.APR.2013 01:42:35

***** END OF REPORT *****