



RF EXPOSURE PART 2 WWAN TEST REPORT

Applicant Name:

Microsoft Corporation
One Microsoft Way
Redmond, WA 98052 USA

Date of Testing:

05/21/2025 – 06/12/2025

Test Site/Location:

Element, Columbia, MD, USA

Document Serial No.:

1M2504010035-06.C3K

FCC ID (Licensed): C3K2119**FCC ID (Unlicensed):** C3K00002102A**APPLICANT:****MICROSOFT CORPORATION****DUT Type:**

Modular Approval - Host Integration (Portable Computing Device)

Application Type:

Class II Permissive Change

FCC Rule Part(s):

CFR §2.1093

Host Device Model Name:

2119

Permissive Change(s):

Please see change document

Device Serial Numbers:

Pre-Production Samples [3494J, 34968, 348YG]

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.



RJ Ortanez

Executive Vice President



FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 1 of 69

T A B L E O F C O N T E N T S

1	DEVICE UNDER TEST	3
2	RF EXPOSURE LIMITS.....	5
3	SMART TRANSMIT VALIDATION TEST CASES.....	7
4	SUB-6 VALIDATION TEST PROCEDURES.....	9
5	TEST CONFIGURATIONS	19
6	CONDUCTED POWER MEASUREMENT FOR SUB-6 SMART TRANSMIT FEATURE VALIDATION	26
7	SYSTEM VERIFICATION (FREQ < 6 GHZ)	51
8	SAR TEST RESULTS (FREQ < 6 GHZ).....	53
9	EQUIPMENT LIST	66
10	CONCLUSION	67
11	REFERENCES.....	68
 APPENDIX A: VERIFICATION PLOTS		
APPENDIX B: SAR TISSUE SPECIFICATIONS		
APPENDIX C: SAR SYSTEM VALIDATION		
APPENDIX D: TEST SETUP PHOTOGRAPHS		
APPENDIX E: TEST SEQUENCES		
APPENDIX F: TEST PROCEDURES FOR SUB6 NR + NR RADIO		
APPENDIX G: CALIBRATION CERTIFICATES		

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 2 of 69

1 DEVICE UNDER TEST

1.1 Equipment Description

The equipment under test (EUT), Model 2119, is a portable computing device that incorporates two previously certified transmitter modules. The first is a WLAN/Bluetooth module authorized under FCC ID: C3K00002102A, and the second is a cellular module authorized under FCC ID: C3K2119. No hardware or software modifications have been made to either module for the purposes of this host integration. This report evaluates the host device for compliance with the applicable FCC rules, including assessment of co-location and simultaneous transmission conditions involving the integrated modules.

1.2 Device Overview

Band & Mode	Operating Modes	Tx Frequency
UMTS 850	Data	826.40 - 846.60 MHz
UMTS 1750	Data	1712.4 - 1752.6 MHz
UMTS 1900	Data	1852.4 - 1907.6 MHz
LTE Band 71	Data	665.5 - 695.5 MHz
LTE Band 12	Data	699.7 - 715.3 MHz
LTE Band 13	Data	779.5 - 784.5 MHz
LTE Band 14	Data	790.5 - 795.5 MHz
LTE Band 26	Data	814.7 - 848.3 MHz
LTE Band 5	Data	824.7 - 848.3 MHz
LTE Band 66	Data	1710.7 - 1779.3 MHz
LTE Band 4	Data	1710.7 - 1754.3 MHz
LTE Band 25	Data	1850.7 - 1914.3 MHz
LTE Band 2	Data	1850.7 - 1909.3 MHz
LTE Band 30	Data	2307.5 - 2312.5 MHz
LTE Band 41	Data	2498.5 - 2687.5 MHz
LTE Band 38	Data	2572.5 - 2617.5 MHz
LTE Band 48	Data	3552.5 - 3697.5 MHz
NR Band n71	Data	665.5 - 695.5 MHz
NR Band n12	Data	701.5 - 713.5 MHz
NR Band n14	Data	790.5 - 795.5 MHz
NR Band n26	Data	816.5 - 846.5 MHz
NR Band n5	Data	826.5 - 846.5 MHz
NR Band n66	Data	1712.5 - 1777.5 MHz
NR Band n25	Data	1852.5 - 1912.5 MHz
NR Band n2	Data	1852.5 - 1907.5 MHz
NR Band n30	Data	2307.5 - 2312.5 MHz
NR Band n41	Data	2501.01 - 2685 MHz
NR Band n48	Data	3555 - 3694.98 MHz
NR Band n77	Data	3705 - 3975 MHz
2.4 GHz WiFi	Data	2412 - 2472 MHz
5 GHz WiFi	Data	U-NII-1: 5180 - 5240 MHz U-NII-2A: 5260 - 5320 MHz U-NII-2C: 5500 - 5720 MHz U-NII-3: 5745 - 5825 MHz U-NII-4: 5845 - 5885 MHz
6 GHz WiFi	Data	U-NII-5: 5935 - 6415 MHz U-NII-6: 6435 - 6515 MHz U-NII-7: 6535 - 6875 MHz U-NII-8: 6895 - 7115 MHz
2.4 GHz Bluetooth	Data	2402 - 2480 MHz

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 3 of 69

1.3 Time-Averaging Algorithm for RF Exposure Compliance

This device is enabled with Qualcomm® Smart Transmit feature. This feature performs time averaging algorithm in real time to control and manage transmitting power and ensure the time-averaged RF exposure is in compliance with FCC requirements all the time. DUT contains embedded file system (EFS) version 19 configured for the second generation (GEN2) for Sub6.

The Smart Transmit algorithm maintains the time-averaged transmit power, in turn, time-averaged RF exposure of SAR_design_target, below the predefined time-averaged power limit (i.e., Plimit for sub-6 radio), for each characterized technology and band.

Smart Transmit allows the device to transmit at higher power instantaneously, as high as P_{max} , when needed, but enforces power limiting to maintain time-averaged transmit power to P_{limit} for frequencies < 6 GHz. Note that the device uncertainty for this DUT is 1.0 dB for sub-6GHz. Multi-Tx factor is set to 1.0 per manufacturer.

The following input parameters are key parameters that are required for functionality of the Smart Transmit feature. These parameters cannot be accessed by the end user, because at the factory they are entered through the embedded file system (EFS) entries by the OEM.

- *Tx_power_at_SAR_design_target (Plimit in dBm) for Tx transmitting frequency < 6 GHz*

The maximum time-average transmit power, in dBm, at which this radio configuration (i.e., band and technology) reaches the SAR_design_target. This SAR_design_target is pre-determined for the specific device and it shall be less than regulatory SAR limit after accounting for all design related tolerances. The time-averaged SAR is assessed against this SAR_design_target in real time to determine the compliance. The Plimit could vary with technology, band, antenna and DS1 (device state index), therefore it has the unique value for each technology, band, antenna and DS1.

This purpose of the Part 2 report is to demonstrate the DUT complies with FCC RF exposure requirement under Tx varying transmission scenarios, thereby validity of Qualcomm® Smart Transmit feature implementation in this device. It serves to compliment the Part 0 and Part 1 Test Reports to justify compliance per FCC.

1.4 Device Level Compliance

At device level, corner cases exist that could result in temporal non-compliance during transitions between radios managed under different RF exposure control mechanisms (WWAN –WLAN –BT –Satellite). Temporal noncompliance cases were identified by industry experts for:

- Radios controlled by two independent TAS solutions.
- Switch between non-TAS radio and TAS radio.

NOTE: This evaluation was performed in the Proprietary Analysis for Qualcomm Smart Transmit + Qualcomm FastConenct report.

1.5 Bibliography

Report Type	Report Serial Number
RF Exposure Part 1 Test Report	1M2504010035-03.C3K
RF Exposure Part 0 Test Report	1M2504010035-04.C3K
RF Exposure Compliance Summary	1M2504010035-05.C3K
RF Exposure Part 2 WLAN Test Report	1M2504010035-12.C3K

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 4 of 69

2 RF EXPOSURE LIMITS

2.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

2.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

2.3 RF Exposure Limits for Frequencies Below 6 GHz

Table 2-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
Peak Spatial Average SAR Head	1.6	8.0
Whole Body SAR	0.08	0.4
Peak Spatial Average SAR Hands, Feet, Ankle, Wrists, etc.	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 5 of 69

2.4 RF Exposure Limits for Frequencies Above 6 GHz

Per §1.1310 (d)(3), the MPE limits are applied for frequencies above 6 GHz. Power Density is expressed in units of W/m² or mW/cm².

Peak Spatially Averaged Power Density was evaluated over a circular area of 4 cm² per interim FCC Guidance for near-field power density evaluations per October 2018 TCB Workshop notes.

Table 2-2
Human Exposure Limits Specified in FCC 47 CFR §1.1310

Human Exposure to Radiofrequency (RF) Radiation Limits		
Frequency Range [MHz]	Power Density [mW/cm ²]	Averaging Time [Minutes]
(A) Limits for Occupational / Controlled Environments		
1,500 – 100,000	5.0	6
(B) Limits for General Population / Uncontrolled Environments		
1,500 – 100,000	1.0	30

Note: 1.0 mW/cm² is 10 W/m²

2.5 Time Averaging Windows for FCC Compliance

Per October 2018 TCB Workshop Notes, the below time-averaging windows can be used for assessing time-averaged exposures for devices that are capable of actively monitoring and adjusting power output over time to comply with exposure limits.

Interim Guidance	Frequency (GHz)	Maximum Averaging Time (sec)
SAR	< 3	100
	3 – 6	60
	6 - 10	30
	10 - 16	14
	16 – 24	8
MPE	24 – 42	4
	42 – 95	2

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 6 of 69

3 SMART TRANSMIT VALIDATION TEST CASES

To validate the time averaging feature and demonstrate the compliance in Tx varying transmission conditions, the following transmission scenarios are covered in the Part 2 test:

1. During a time-varying Tx power transmission: To prove that the Smart Transmit feature accounts for Tx power variations in time accurately.
2. During a call disconnect and re-establish scenario: To prove that the Smart Transmit feature accounts for history of past Tx power transmissions accurately.
3. During a technology/band handover: To prove that the Smart Transmit feature functions correctly during transitions in technology/band.
4. During a DS1 (Device State Index) change: To prove that the Smart Transmit feature functions correctly during transition from one device state (DSI) to another.
5. During an antenna switch: To prove that the Smart Transmit feature functions correctly during transitions in antenna (such as AsDiv scenario)
6. During time window switch: To prove that the Smart Transmit feature correctly handles the transition from one time window to another specified by FCC, and maintains the normalized time-averaged RF exposure to be less than normalized FCC limit of 1.0 at all times.
7. SAR exposure switching between two active radios (radio1 and radio2): To prove that the Smart Transmit feature functions correctly and ensures total RF exposure compliance when exposure varies among SAR_radio1 only, SAR_radio1 + SAR_radio2, and SAR_radio2 only scenarios.

As described in Part 0 report, the RF exposure is proportional to the Tx power for a SAR. Thus, feature validation in Part 2 can be effectively performed through conducted (for $f < 6\text{GHz}$) power measurement. Therefore, the compliance demonstration under dynamic transmission conditions and feature validation are done in conducted/radiated power measurement setup for transmission scenario 1 through 7.

To add confidence in the feature validation, the time-averaged SAR is also performed but only performed for transmission scenario 1 to avoid the complexity in SAR (such as, for scenario 3 requiring change in SAR probe calibration file to accommodate different bands and/or tissue simulating liquid).

The strategy for testing in Tx varying transmission condition is outlined as follows:

- Demonstrate the total RF exposure averaged over FCC defined time windows does not exceed FCC's SAR limits, through time-averaged power measurements
 - Measure conducted Tx power (for $f < 6\text{GHz}$) versus time, and radiated Tx power versus time.
 - Convert it into RF exposure and divide by respective FCC limits to get normalized exposure versus time.
 - Perform running time-averaging over FCC defined time windows.
 - Demonstrate that the total normalized time-averaged RF exposure is less than 1 for all transmission scenarios (i.e., transmission scenarios 1, 2, 3, 4, 5, 6, 7, and 8) at all times.

Mathematical expression:

For $< 6\text{ GHz}$ transmission only:

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 7 of 69

$$1g_or_10gSAR(t) = \frac{conducted_Tx_power(t)}{conducted_Tx_power_P_{limit}} * 1g_or_10gSAR_P_{limit} \quad (1a)$$

$$\frac{\frac{1}{T_{SAR}} \int_{t-T_{SAR}}^t 1g_or_10gSAR(t) dt}{FCC\ SAR\ limit} \leq 1 \quad (1b)$$

where, $conducted_Tx_power(t)$, $conducted_Tx_power_P_{limit}$, and $1g_or_10gSAR_P_{limit}$ correspond to the measured instantaneous conducted Tx power, measured conducted Tx power at P_{limit} , and measured 1gSAR or 10gSAR values at P_{limit} corresponding to sub-6 transmission. P_{limit} is the parameter pre-defined in Part 0 and loaded via Embedded File System (EFS) onto the EUT. T_{SAR} is the FCC defined time window for sub-6 radio.

- Demonstrate the total RF exposure averaged over FCC defined time windows does not exceed FCC's SAR limits, through time-averaged SAR measurements. Note as mentioned earlier, this measurement is performed for transmission scenario 1 only.
 - For sub-6 transmission only, measure instantaneous SAR versus time; for LTE+sub6 NR transmission, request low power (or all-down bits) on LTE so that measured SAR predominantly corresponds to sub6 NR.
 - For LTE transmission, measure instantaneous E-field versus time for mmW radio and instantaneous conducted power versus time for LTE radio.
 - Convert it into RF exposure and divide by respective FCC limits to obtain normalized exposure versus time.
 - Perform time averaging over FCC defined time window.
 - Demonstrate that the total normalized time-averaged RF exposure is less than 1 for transmission scenario 1 at all times.

Mathematical expression:

- For sub-6 transmission only:

$$1g_or_10gSAR(t) = \frac{pointSAR(t)}{pointSAR_P_{limit}} * 1g_or_10gSAR(t)_P_{limit} \quad (3a)$$

$$\frac{\frac{1}{T_{SAR}} \int_{t-T_{SAR}}^t 1g_or_10gSAR(t) dt}{FCC\ SAR\ limit} \leq 1 \quad (3b)$$

where, $pointSAR(t)$, $pointSAR_P_{limit}$, and $1g_or_10gSAR_P_{limit}$ correspond to the measured instantaneous point SAR, measured point SAR at P_{limit} , and measured 1gSAR or 10gSAR values at P_{limit} corresponding to sub-6 transmission.

Note: cDASY6 measurement system by Schmid & Partner Engineering AG (SPEAG) of Zurich, Switzerland measures relative E-field, and provides ratio of $\frac{[pointE(t)]^2}{[pointE_input.power.limit]^2}$ versus time.

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 8 of 69

4 SUB-6 VALIDATION TEST PROCEDURES

This chapter provides the test plan and test procedure for validating Qualcomm Smart Transmit feature for sub-6 transmission. The 100 seconds time window for operating $f < 3\text{GHz}$ is used as an example to detail the test procedures in this chapter. The same test plan and test procedures described in this chapter apply to 60 seconds time window for operating $f \geq 3\text{GHz}$.

4.1 Test Sequence Determination for Validation

Following the FCC recommendation, two test sequences having time-variation in Tx power are predefined for sub-6 ($f < 6\text{ GHz}$) validation:

- Test sequence 1: request DUT's Tx power to be at maximum power, measured P_{max}^t , for 80s, then requesting for half of the maximum power, i.e., measured $P_{max}/2$, for the rest of the time.
- Test sequence 2: request DUT's Tx power to vary with time. This sequence is generated relative to measured P_{max} , measured P_{limit} and calculated $P_{reserve}$ (= measured P_{limit} in dBm - *reserve_power_margin* in dB) of DUT based on measured P_{limit} .

The details for generating these two test sequences is described and listed in Appendix E.

NOTE: For test sequence generation, “measured P_{limit} ” and “measured P_{max} ” are used instead of the “ P_{limit} ” specified in EFS entry and “ P_{max} ” specified for the device, because the Smart Transmit feature operates against the actual power level of the “ P_{limit} ” that was calibrated for the DUT. The “measured P_{limit} ” accurately reflects what the feature is referencing to, therefore, it should be used during feature validation testing. The RF tune up and device-to-device variation are already considered in Part 0 report prior to determining P_{limit} .

4.2 Test Configuration Selection Criteria for Validating Smart Transmit Feature

For validating the Smart Transmit feature, this section provides the general guidance to select test cases.

4.2.1 Time-Varying Tx Power Transmission

The Smart Transmit time averaging feature operation is independent of bands, modes, and channels for a given technology. Hence, validation of Smart Transmit in one band/mode/channel per technology is sufficient. Two bands per technology are proposed and selected for this testing to provide high confidence in this validation.

Note this test is designed for single radio transmission scenario. If UE supports sub6 NR in both non-standalone (NSA) and standalone (SA) modes, then validation in time-varying Tx power transmission scenario described in this section needs to be performed in SA mode. Otherwise, it needs to be performed in NSA mode with LTE anchor set to low power. The choice between SA and NSA mode needs to also take into account the selection criteria described below. In general, one mode out of the two modes (NSA or SA) is sufficient for this test.

The criteria for the selection are based on the P_{limit} values determined in Part 0 report. Select two bands* in each supported technology that correspond to least** and highest*** P_{limit} values that are less than P_{max} for validating Smart Transmit. Note:

1. P_{max} refers to maximum Tx power configured for this device in this technology/band (not rated P_{max}).
This P_{max} definition applies throughout this Part 2 report.

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 9 of 69

2. If $P_{limit} > P_{max}$, the validation test with time-varying test sequences is not needed as no power enforcement will be required in this condition.

* If one P_{limit} level applies to all the bands within a technology, then only one band needs to be tested. In this case, within the bands having the same P_{limit} , the radio configuration (e.g., # of RBs, channel#) and device position that correspond to the highest *measured* 1gSAR at P_{limit} shown in Part 1 report is selected.

** In case of multiple bands having the same least P_{limit} within the technology, then select the band having the highest *measured* 1gSAR at P_{limit} .

*** The band having a higher P_{limit} needs to be properly selected so that the power limiting enforced by Smart Transmit can be validated using the pre-defined test sequences. If the highest P_{limit} in a technology is too high where the power limiting enforcement is not needed when testing with the pre-defined test sequences, then the next highest level is checked. This process is continued within the technology until the second band for validation testing is determined.

4.2.2 Change In Call

The criteria to select a test configuration for call-drop measurement is:

- Select technology/band with least P_{limit} among all supported technologies/bands, and select the radio configuration (e.g., # of RBs, channel#) in this technology/band that corresponds to the highest *measured* 1gSAR at P_{limit} listed in Part 1 report.
- In case of multiple bands having same least P_{limit} , then select one band/radio configuration for this test.

This test is performed with the DUT's Tx power requested to be at maximum power, the above band selection will result in Tx power enforcement (i.e., DUT forced to have Tx power at $P_{reserve}$) for longest duration in one FCC defined time window. The call change (call drop/reestablish) is performed during the Tx power enforcement duration (i.e., during the time when DUT is forced to have Tx power at $P_{reserve}$). One test is sufficient as the feature operation is independent of technology and band.

4.2.3 Change In Technology/Band

The selection criteria for this measurement is, for a given antenna, to have DUT switch from a technology/band with lowest P_{limit} within the technology group (in case of multiple bands having the same P_{limit} , then select the band with highest *measured* 1gSAR at P_{limit}) to a technology/band with highest P_{limit} within the technology group, in case of multiple bands having the same P_{limit} , then select the band with lowest *measured* 1gSAR at P_{limit} in Part 1 report, or vice versa.

This test is performed with the DUT's Tx power requested to be at maximum power, the technology/band switch is performed during Tx power enforcement duration (i.e., during the time when DUT is forced to have Tx power at $P_{reserve}$).

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 10 of 69

4.2.4 Change In Antenna

The criteria to select a test configuration for antenna switch measurement is:

- Whenever possible and supported by the DUT, first select antenna switch configuration within the same technology/band (i.e., same technology and band combination).
- Then, select any technology/band that supports multiple Tx antennas, and has the highest difference in P_{limit} among all supported antennas.
- In case of multiple bands having same difference in P_{limit} among supported antennas, then select the band having the highest *measured 1gSAR* at P_{limit} in Part 1 report.

This test is performed with the DUT's Tx power requested to be at maximum power in selected technology/band, and antenna change is conducted during Tx power enforcement duration (i.e., during the time when DUT is forced to have Tx power at $P_{reserve}$).

4.2.5 Change In DS1

The criteria to select a test configuration for DS1 change test is

- Select a technology/band having the $P_{limit} < P_{max}$ within any technology and DS1 group, and for the same technology/band having a different P_{limit} in any other DS1 group. Note that the selected DS1 transition need to be supported by the device.

This test is performed with the DUT's Tx power requested to be at maximum power in selected technology/band, and DS1 change is conducted during Tx power enforcement duration (i.e., during the time when DUT is forced to have Tx power at $P_{reserve}$).

4.2.6 Change In Time Window

FCC specifies different time window for time averaging based on operation frequency. The criteria to select a test configuration for validating Smart Transmit feature and demonstrating the compliance during the change in time window is

- Select any technology/band that has operation frequency classified in one time window defined by FCC (such as 100-seconds time window), and its corresponding P_{limit} is less than P_{max} if possible.
- Select the 2nd technology/band that has operation frequency classified in a different time window defined by FCC (such as 60-seconds time window), and its corresponding P_{limit} is less than P_{max} if possible.
- Note it is preferred both P_{limit} values of two selected technology/band less than corresponding P_{max} , but if not possible, at least one of technologies/bands has its P_{limit} less than P_{max} .

This test is performed with the EUT's Tx power requested to be at maximum power in selected technology/band. Test for one pair of time windows selected is sufficient as the feature operation is the same.

4.2.7 SAR Exposure Switching

If supported, the test configuration for SAR exposure switching should cover

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 11 of 69

1. SAR exposure switch when two active radios are in the same time window
2. SAR exposure switch when two active radios are in different time windows. One test with two active radios in any two different time windows is sufficient as Smart Transmit operation is the same for RF exposure switch in any combination of two different time windows. For device supporting LTE + mmW NR, this test is covered in SAR vs PD exposure switch validation.

The Smart Transmit time averaging operation is independent of the source of SAR exposure (for example, LTE vs. Sub6 NR) and ensures total time-averaged RF exposure compliance. Hence, validation of Smart Transmit in any one simultaneous SAR transmission scenario (i.e., one combination for LTE + Sub6 NR transmission) is sufficient, where the SAR exposure varies among SAR_{radio1} only, $SAR_{radio1} + SAR_{radio2}$, and SAR_{radio2} only scenarios.

The criteria to select a test configuration for validating Smart Transmit feature during SAR exposure switching scenarios is

- Select any two < 6GHz technologies/bands that the EUT supports simultaneous transmission (for example, LTE+Sub6 NR).
- Among all supported simultaneous transmission configurations, the selection order is
 1. select one configuration where both P_{limit} of radio1 and radio2 is less than their corresponding P_{max} , preferably, with different P_{limits} . If this configuration is not available, then,
 2. select one configuration that has P_{limit} less than its P_{max} for at least one radio. If this can not be found, then,
 3. select one configuration that has P_{limit} of radio1 and radio2 greater than P_{max} but with least $(P_{limit} - P_{max})$ delta.

Test for one simultaneous transmission scenario is sufficient as the feature operation is the same.

4.3 Test Procedures for Conducted Power Measurements

This section provides general conducted power measurement procedures to perform compliance test under dynamic transmission scenarios described in Section 3. In practice, an adjustment can be made in these procedures. The justification/clarification may be provided.

4.3.1 Time-Varying Tx Power Transmission

This test is performed with the two pre-defined test sequences described in Section 4.1 for all the technologies and bands selected in Section 4.2.1. The purpose of the test is to demonstrate the effectiveness of power limiting enforcement and that the time-averaged SAR (corresponding time-averaged Tx power) does not exceed the FCC limit at all times (see Eq. (1a) and (1b)).

Test procedure

1. Measure P_{max} , measure P_{limit} and calculate $P_{reserve}$ (measured P_{limit} in dBm – $total_min_reserve$ in dB) and follow Section 4.1 to generate the test sequences for all the technologies and bands selected in Section 4.2.1. Both test sequence 1 and test sequence 2 are created based on measured P_{max} and measured P_{limit} of the DUT. Test condition to measure P_{max} and P_{limit} is:

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 12 of 69

- a. Measure P_{max} with Smart Transmit disabled and callbox set to request maximum power.
- b. Measure P_{limit} with Smart Transmit peak exposure mode enabled, and callbox set to request maximum power.
2. Set DUT to the intended Smart Transmit exposure mode, establish radio link in desired radio configuration, with callbox requesting the DUT's Tx power to be at pre-defined test sequence 1, measure and record Tx power versus time, and then convert the conducted Tx power into 1gSAR or 10gSAR value (see Eq. (1a)) using measured P_{limit} from above Step 1. Perform running time average to determine time-averaged power and 1gSAR or 10gSAR versus time as illustrated in Figure 4-1 where using 100-seconds time window as an example.

Note: In Eq.(1a), instantaneous Tx power is converted into instantaneous 1gSAR or 10gSAR value by applying the measured worst-case 1gSAR or 10gSAR value at P_{limit} for the corresponding technology/band/antenna/DSI reported in Part 1 report.

Note: For an easier computation of the running time average, 0 dBm can be added at the beginning of the test sequences the length of the responding time window, for example, add 0dBm for 100-seconds so the running time average can be directly performed starting with the first 100-seconds data using excel spreadsheet. This technique applies to all tests performed in this Part 2 report for easier time-averaged computation using excel spreadsheet.

Time	Power/SAR
t_1	P_{t1} or SAR_{t1}
t_2	P_{t2} or SAR_{t2}
:	:
:	:
t_n (t_1+100s)	P_{tn} or SAR_{tn}
t_{n+1} (t_2+100s)	P_{tn+1} or SAR_{tn+1}
:	:

$$1^{\text{st}} \text{ 100s time window}$$

$$\text{time averaged } P1 \text{ or SAR1} = \frac{\sum_{i=1}^n P_{ti} \text{ or } SAR_{ti}}{n}$$

$$2^{\text{nd}} \text{ 100s time window}$$

$$\text{time averaged } P2 \text{ or SAR2} = \frac{\sum_{i=2}^{n+1} P_{ti} \text{ or } SAR_{ti}}{n}$$

\vdots

Figure 4-1
Running Average Illustration

3. Make one plot containing:
 - a. Instantaneous Tx power versus time measured in Step 2,
 - b. Requested Tx power used in Step 2 (test sequence 1),
 - c. Computed time-averaged power versus time determined in Step 2,
 - d. Time-averaged power limit (corresponding to FCC SAR limit of 1.6 W/kg for 1gSAR or 4.0W/kg for 10gSAR) given by

$$\text{Time averaged power limit} = \text{meas. } P_{limit} + 10 \times \log\left(\frac{\text{FCC SAR limit}}{\text{meas. SAR}_P_{limit}}\right) \quad (5a)$$

where $\text{meas. } P_{limit}$ and $\text{meas. SAR}_P_{limit}$ correspond to measured power at P_{limit} and measured SAR at P_{limit} .

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 13 of 69

4. Make another plot containing:
 - a. Computed time-averaged 1gSAR or 10gSAR versus time determined in Step 2
 - b. FCC $1gSAR_{limit}$ of 1.6W/kg or FCC $10gSAR_{limit}$ of 4.0W/kg.
5. Repeat Steps 2 ~ 4 for pre-defined test sequence 2 and replace the requested Tx power (test sequence 1) in Step 2 with test sequence 2.
6. Repeat Steps 2 ~ 5 for all the selected technologies and bands.
7. The validation criteria are, at all times, the time-averaged power versus time shown in Step 3 plot shall not exceed the time-averaged power limit (defined in Eq. (5a)), in turn, the time-averaged 1gSAR or 10gSAR versus time shown in Step 4 plot shall not exceed the FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR (i.e., Eq. (1b)).

4.3.2 Change in Call

This test is to demonstrate that Smart Transmit feature accurately accounts for the past Tx powers during time-averaging when a new call is established.

The call disconnect and re-establishment needs to be performed during power limit enforcement, i.e., when the DUT's Tx power is at $P_{reserve}$ level, to demonstrate the continuity of RF exposure management and limiting in call change scenario. In other words, the RF exposure averaged over any FCC defined time window (including the time windows containing the call change) doesn't exceed FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR.

Test procedure

1. Measure P_{limit} for the technology/band selected in Section 4.2.2. Measure P_{limit} with Smart Transmit peak exposure mode enabled, and callbox set to request maximum power.
2. Set DUT to the intended Smart Transmit exposure mode.
3. Establish radio link with callbox in the selected technology/band.
4. Request DUT's Tx power at 0 dBm for at least one time window specified for the selected technology/band, followed by requesting DUT's Tx power to be at maximum power for about ~60 seconds, and then drop the call for ~10 seconds. Afterwards, re-establish another call in the same radio configuration (i.e., same technology/band/channel) and continue callbox requesting DUT's Tx power to be at maximum power for the remaining time of at least another full duration of the specified time window. Measure and record Tx power versus time. Once the measurement is done, extract instantaneous Tx power versus time, convert the measured conducted Tx power into 1gSAR or 10gSAR value using Eq. (1a), and then perform the running time average to determine time-averaged power and 1gSAR or 10gSAR versus time.

NOTE: In Eq.(1a), instantaneous Tx power is converted into instantaneous 1gSAR or 10gSAR value by applying the measured worst-case 1gSAR or 10gSAR value at P_{limit} for the corresponding technology/band/antenna/DSI reported in Part 1 report.

5. Make one plot containing: (a) instantaneous Tx power versus time, (b) requested power, (c) computed time-averaged power, (d) time-averaged power limit calculated using Eq.(5a).

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 14 of 69

6. Make another plot containing: (a) computed time-averaged 1gSAR or 10gSAR versus time, and (b) FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR.

The validation criteria are, at all times, the time-averaged power versus time shall not exceed the time-averaged power limit (defined in Eq.(5a)), in turn, the time-averaged 1gSAR or 10gSAR versus time shall not exceed the FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR (i.e., Eq. (1b)).

4.3.3 Change In Technology/Band

This test is to demonstrate the correct power control by Smart Transmit during technology switches and/or band handovers.

Similar to the change in call test in Section 4.3.2, to validate the continuity of RF exposure limiting during the transition, the technology and band handover needs to be performed when DUT's Tx power is at P_{reserve} level (i.e., during Tx power enforcement) to make sure that the DUT's Tx power from previous P_{reserve} level to the new P_{reserve} level (corresponding to new technology/band). Since the P_{limit} could vary with technology and band, Eq. (1a) can be written as follows to convert the instantaneous Tx power in 1gSAR or 10gSAR exposure for the two given radios, respectively:

$$1g_or_10gSAR_1(t) = \frac{\text{conducted_Tx_power_1}(t)}{\text{conducted_Tx_power_P}_{\text{limit_1}}} * 1g_or_10gSAR_P_{\text{limit_1}} \quad (6a)$$

$$1g_or_10gSAR_2(t) = \frac{\text{conducted_Tx_power_2}(t)}{\text{conducted_Tx_power_P}_{\text{limit_2}}} * 1g_or_10gSAR_P_{\text{limit_2}} \quad (6b)$$

$$\frac{1}{T_{\text{SAR}}} \left[\int_{t-T_{\text{SAR}}}^{t_1} \frac{1g_or_10gSAR_1(t)}{\text{FCC SAR limit}} dt + \int_{t-T_{\text{SAR}}}^t \frac{1g_or_10gSAR_2(t)}{\text{FCC SAR limit}} dt \right] \leq 1 \quad (6c)$$

where, $\text{conducted_Tx_power_1}(t)$, $\text{conducted_Tx_power_P}_{\text{limit_1}}$, and $1g_or_10gSAR_P_{\text{limit_1}}$ correspond to the measured instantaneous conducted Tx power, measured conducted Tx power at P_{limit} , and measured 1gSAR or 10gSAR value at P_{limit} of technology1/band1; $\text{conducted_Tx_power_2}(t)$, $\text{conducted_Tx_power_P}_{\text{limit_2}}(t)$, and $1g_or_10gSAR_P_{\text{limit_2}}$ correspond to the measured instantaneous conducted Tx power, measured conducted Tx power at P_{limit} , and measured 1gSAR or 10gSAR value at P_{limit} of technology2/band2. Transition from technology1/band1 to the technology2/band2 happens at time-instant ' t_1 '.

Test procedure

1. Measure P_{limit} for both the technologies and bands selected in Section 4.2.3. Measure P_{limit} with Smart Transmit peak exposure mode enabled, and callbox set to request maximum power.
2. Set DUT to the intended Smart Transmit exposure mode. Establish radio link with callbox in first technology/band selected. Establish radio link with callbox in first technology/band selected.
3. Request DUT's Tx power at 0 dBm for at least one time window specified for the selected technology/band, followed by requesting DUT's Tx power to be at maximum power for about ~60 seconds, and then switch to second technology/band selected. Continue with callbox requesting DUT's Tx power to be at maximum power for the remaining time of at least another full duration of the specified time window. Measure and record Tx power versus time for the full duration of the test.
4. Once the measurement is done, extract instantaneous Tx power versus time, and convert the conducted Tx power into 1gSAR or 10gSAR value using Eq. (6a) and (6b) and corresponding

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 15 of 69

measured P_{limit} values from Step 1 of this section. Perform the running time average to determine time-averaged power and 1gSAR or 10gSAR versus time.

NOTE: In Eq.(6a) & (6b), instantaneous Tx power is converted into instantaneous 1gSAR or 10gSAR value by applying the measured worst-case 1gSAR or 10gSAR value at P_{limit} for the corresponding technology/band/antenna/DSI reported in Part 1 report.

5. Make one plot containing: (a) instantaneous Tx power versus time, (b) requested power, (c) computed time-averaged power, (d) time-averaged power limit calculated using Eq.(5a).
6. Make another plot containing: (a) computed time-averaged 1gSAR or 10gSAR versus time, and (b) FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR.

The validation criteria are, at all times, the time-averaged 1gSAR or 10gSAR versus time shall not exceed the FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR (i.e., Eq. (6c)).

4.3.4 Change In Antenna

This test is to demonstrate the correct power control by Smart Transmit during antenna switches from one antenna to another. The test procedure is identical to Section 4.3.3, by replacing technology/band switch operation with antenna switch. The validation criteria are, at all times, the time-averaged 1gSAR or 10gSAR versus time shall not exceed FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR.

NOTE: If the DUT does not support antenna switch within the same technology/band, but has multiple antennas to support different frequency bands, then the antenna switch test is included as part of change in technology and band (Section 4.3.3) test.

4.3.5 Change In DSI

This test is to demonstrate the correct power control by Smart Transmit during DSI switches from one DSI to another. The test procedure is identical to Section 4.3.3, by replacing technology/band switch operation with DSI switch. The validation criteria are, at all times, the time-averaged 1gSAR or 10gSAR versus time shall not exceed FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR.

4.3.6 Change In Time Window

This test is to demonstrate the correct power control by Smart Transmit during the change in averaging time window when a specific band handover occurs. FCC specifies time-averaging windows of 100s for Tx frequency < 3GHz, and 60s for Tx frequency between 3GHz and 6GHz.

To validate the continuity of RF exposure limiting during the transition, the band handover test needs to be performed when EUT handovers from operation band less than 3GHz to greater than 3GHz and vice versa. The equations (3a) and (3b) in Section 2 can be written as follows for transmission scenario having change in time window,

$$1gSAR_1(t) = \frac{\text{conducted_Tx_power_1}(t)}{\text{conducted_Tx_power_P}_{limit_1}} * 1g_or\ 10g_SAR_P_{limit_1} \quad (7a)$$

$$1gSAR_2(t) = \frac{\text{conducted_Tx_power_2}(t)}{\text{conducted_Tx_power_P}_{limit_2}} * 1g_or\ 10g_SAR_P_{limit_2} \quad (7b)$$

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 16 of 69

$$\frac{1}{T1_{SAR}} \left[\int_{t-T1_{SAR}}^{t_1} \frac{1g_or\ 10g_SAR_1(t)}{FCC\ SAR\ limit} dt \right] + \frac{1}{T2_{SAR}} \left[\int_{t-T2_{SAR}}^t \frac{1g_or\ 10g_SAR_2(t)}{FCC\ SAR\ limit} dt \right] \leq 1 \quad (7c)$$

where, *conducted_Tx_power_1(t)*, *conducted_Tx_power_P_{limit_1}(t)*, and *1g_ or 10g_SAR_P_{limit_1}* correspond to the instantaneous Tx power, conducted Tx power at *P_{limit}*, and compliance *1g_ or 10g_SAR* values at *P_{limit_1}* of band1 with time-averaging window '*T1_{SAR}*'; *conducted_Tx_power_2(t)*, *conducted_Tx_power_P_{limit_2}(t)*, and *1g_ or 10g_SAR_P_{limit_2}* correspond to the instantaneous Tx power, conducted Tx power at *P_{limit}*, and compliance *1g_ or 10g_SAR* values at *P_{limit_2}* of band2 with time-averaging window '*T2_{SAR}*'. One of the two bands is less than 3GHz, another is greater than 3GHz. Transition from first band with time-averaging window '*T1_{SAR}*' to the second band with time-averaging window '*T2_{SAR}*' happens at time-instant '*t₁*'.

Test procedure

1. Measure *P_{limit}* for both the technologies and bands selected in Section 4.2.6. Measure *P_{limit}* with Smart Transmit peak exposure mode enabled, and callbox set to request maximum power.
2. Set DUT to the intended Smart Transmit exposure mode.

Transition from 100s time window to 60s time window, and vice versa

3. Establish radio link with callbox in the technology/band having 100s time window selected in Section 4.2.6.
4. Request EUT's Tx power to be at 0 dBm for at least 100 seconds, followed by requesting EUT's Tx power to be at maximum power for about ~140 seconds, and then switch to second technology/band (having 60s time window) selected in Section 4.2.6. Continue with callbox requesting EUT's Tx power to be at maximum power for about ~60s in this second technology/band, and then switch back to the first technology/band. Continue with callbox requesting EUT's Tx power to be at maximum power for at least another 100s. Measure and record Tx power versus time for the entire duration of the test.
5. Once the measurement is done, extract instantaneous Tx power versus time, and convert the conducted Tx power into 1gSAR or 10gSAR value (see Eq. (7a) and (7b)) using corresponding technology/band Step 1 result, and then perform 100s running average to determine time-averaged 1gSAR or 10gSAR versus time. Note that in Eq.(7a) & (7b), instantaneous Tx power is converted into instantaneous 1gSAR or 10gSAR value by applying the worst-case 1gSAR or 10gSAR value tested in Part 1 for the selected technologies/bands at *P_{limit}*.
6. Make one plot containing: (a) instantaneous Tx power versus time measured in Step 4.
7. Make another plot containing: (a) instantaneous 1gSAR versus time determined in Step 5, (b) computed time-averaged 1gSAR versus time determined in Step 5, and (c) corresponding regulatory *1gSAR_{limit}* of 1.6W/kg or *10gSAR_{limit}* of 4.0W/kg.

Transition from 60s time window to 100s time window, and vice versa

8. Establish radio link with callbox in the technology/band having 60s time window selected in Section 4.2.6.
9. Request EUT's Tx power to be at 0 dBm for at least 60 seconds, followed by requesting EUT's Tx power to be at maximum power for about ~80 seconds, and then switch to second technology/band (having 100s time window) selected in Section 4.2.6. Continue with callbox requesting EUT's Tx power to be at maximum power for about ~100s in this second technology/band, and then switch back to the first technology/band. Continue with callbox requesting EUT's Tx power to be at maximum power for the remaining time for a total test time of 500 seconds. Measure and record Tx power versus time for the entire duration of the test.

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 17 of 69

10. Repeat above Step 5~7 to generate the plots

The validation criteria is, at all times, the time-averaged 1gSAR or 10gSAR versus time shall not exceed the regulatory $1gSAR_{limit}$ of 1.6W/kg or $10gSAR_{limit}$ of 4.0W/kg.

4.3.7 SAR Exposure Switching

This test is to demonstrate that Smart Transmit feature is accurately accounts for switching in exposures among SAR from radio1 only, SAR from both radio1 and radio2, and SAR from radio2 only scenarios, and ensures total time-averaged RF exposure complies with the FCC limit. Here, radio1 represents primary radio (for example, LTE anchor in a NR non-standalone mode call) and radio2 represents secondary radio (for example, sub6 NR or mmW NR). The detailed test procedure for SAR exposure switching in the case of LTE+Sub6 NR non-standalone mode transmission scenario is provided in APPENDIX F.

Test procedure:

1. Measure conducted Tx power corresponding to P_{limit} for radio1 and radio2 in selected band. Test condition to measure conducted P_{limit} is:
 - Establish device in call with the callbox for radio1 technology/band. Measure conducted Tx power corresponding to radio1 P_{limit} with Smart Transmit peak exposure mode enabled, and callbox set to request maximum power.
 - Repeat above step to measure conducted Tx power corresponding to radio2 P_{limit} . If radio2 is dependent on radio1 (for example, non-standalone mode of Sub6 NR requiring radio1 LTE as anchor), then establish radio1 + radio2 call with callbox, and request all down bits for radio1 LTE. In this scenario, with callbox requesting maximum power from radio2 Sub6 NR, measured conducted Tx power corresponds to radio2 P_{limit} (as radio1 LTE is at all-down bits)
2. Set DUT to the intended Smart Transmit exposure mode, with EUT setup for radio1 + radio2 call. In this description, it is assumed that radio2 has lower priority than radio1. Establish device in radio1+radio2 call, and request all-down bits or low power on radio1, with callbox requesting EUT's Tx power to be at maximum power in radio2 for at least one time window. After one time window, set callbox to request EUT's Tx power to be at maximum power on radio1, i.e., all-up bits. Continue radio1+radio2 call with both radios at maximum power for at least one time window, and drop (or request all-down bits on) radio2. Continue radio1 at maximum power for at least one time window. Record the conducted Tx power for both radio1 and radio2 for the entire duration of this test.
3. Once the measurement is done, extract instantaneous Tx power versus time for both radio1 and radio2 links. Convert the conducted Tx power for both these radios into 1gSAR or 10gSAR value (see Eq. (6a) and (6b)) using corresponding technology/band P_{limit} measured in Step 1, and then perform the running time average to determine time-averaged 1gSAR or 10gSAR versus time.
4. Make one plot containing: (a) instantaneous Tx power versus time measured in Step 2.
5. Make another plot containing: (a) instantaneous 1gSAR versus time determined in Step 3, (b) computed time-averaged 1gSAR versus time determined in Step 3, and (c) corresponding regulatory $1gSAR_{limit}$ of 1.6W/kg or $10gSAR_{limit}$ of 4.0W/kg.

The validation criteria is, at all times, the time-averaged 1gSAR or 10gSAR versus time shall not exceed the regulatory $1gSAR_{limit}$ of 1.6W/kg or $10gSAR_{limit}$ of 4.0W/kg.

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 18 of 69

NOTE: If *multi_Tx_factor* is set to > 1.0 with EFS version 19 (or higher), then in single Tx transmission scenarios, Smart Transmit ensures time-averaged RF exposure is $\leq (SAR_design_target * 10^{+ \text{sub6 device uncertainty}/10})$ < regulatory RF exposure limit for sub6 radio managed by Smart Transmit. In simultaneous Tx transmission scenarios, Smart Transmit ensures time-averaged RF exposure is $\leq (SAR_design_target * multi_Tx_factor * 10^{+ \text{sub6 device uncertainty}/10})$ < regulatory RF exposure limit for sub6 radios managed by Smart Transmit. These simultaneous transmission scenarios are listed below:

- 2-or-more radio scenarios within WWAN like EN-DC, LTE ULCA, etc.
- 2-or-more-radio across technologies such as WWAN+WLAN, WWAN+BT, WLAN+BT and WWAN+WLAN+BT transmission scenarios (if WLAN/BT radios are also managed by Smart Transmit).

4.4 Test Procedure for Time-Varying SAR Measurements

This section provides general time-varying SAR measurement procedures to perform compliance test under dynamic transmission scenarios described in Section 3. In practice, an adjustment can be made in these procedures. The justification/clarification may be provided.

To perform the validation through SAR measurement for transmission scenario 1 described in Section 3, the “path loss” between callbox antenna and DUT needs to be calibrated to ensure that the DUT Tx power reacts to the requested power from callbox in a radiated call. It should be noted that when signaling in closed loop mode, protocol-level power control is in play, resulting in DUT not solely following callbox TPC (Tx power control) commands. In other words, DUT response has many dependencies (RSSI, quality of signal, path loss variation, fading, etc..) other than just TPC commands. These dependencies have less impact in conducted setup (as it is a controlled environment and the path loss can be very well calibrated) but have significant impact on radiated testing in an uncontrolled environment, such as SAR test setup. Therefore, the deviation in DUT Tx power from callbox requested power is expected, however the time-averaged SAR should not exceed FCC SAR requirement at all times as Smart Transmit controls Tx power at DUT.

The following steps are for time averaging feature validation through SAR measurement:

1. “Path Loss” calibration: Place the DUT against the phantom in the worst-case position determined based on Section 4.2.1. For each band selected, prior to SAR measurement, perform “path loss” calibration between callbox antenna and DUT. Since the SAR test environment is not controlled and well calibrated for OTA (Over the Air) test, extreme care needs to be taken to avoid the influence from reflections. The test setup is described in Section 6.2.
2. Time averaging feature validation:
 - i For a given radio configuration (technology/band) selected in Section 4.2.1, enable Smart Transmit peak exposure mode, with callbox to request maximum power, perform area scan, conduct pointSAR measurement at peak location of the area scan. This point SAR value, $pointSAR_P_{limit}$, corresponds to point SAR at the measured P_{limit} (i.e., measured P_{limit} from the DUT in Step 1 of Section 4.3.1).
 - ii Set DUT to the intended Smart Transmit exposure mode. Note, if *Total_min_reserve* cannot be set wirelessly, care must be taken to re-position the DUT in the exact same position relative to the SAM phantom as in above Step 2.i. Establish radio link in desired radio configuration, with callbox

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 19 of 69

requesting the DUT's Tx power at power levels described by test sequence 1 generated in Step 1 of Section 4.3.1, conduct point SAR measurement versus time at peak location of the area scan determined in Step 2.i of this section. Once the measurement is done, extract instantaneous point SAR vs time data, $pointSAR(t)$, and convert it into instantaneous 1gSAR or 10gSAR vs. time using Eq. (3a), re-written below:

$$1g_or_10gSAR(t) = \frac{pointSAR(t)}{pointSAR_P_{limit}} * 1g_or_10gSAR_P_{limit}$$

where, $pointSAR_P_{limit}$ is the value determined in Step 2.i, and $pointSAR(t)$ is the instantaneous point SAR measured in Step 2.ii, $1g_or_10gSAR_P_{limit}$ is the measured 1gSAR or 10gSAR value listed in Part 1 report.

- iii Perform 100s running average to determine time-averaged 1gSAR or 10gSAR versus time.
- iv Make one plot containing: (a) time-averaged 1gSAR or 10gSAR versus time determined in Step 2.iii of this section, (b) FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR.
- v Repeat 2.ii ~ 2.iv for test sequence 2 generated in Step 1 of Section 4.3.1.
- vi Repeat 2.i ~ 2.v for all the technologies and bands selected in Section 4.2.1.

The time-averaging validation criteria for SAR measurement is that, at all times, the time-averaged 1gSAR or 10gSAR versus time shall not exceed FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR (i.e., Eq. (3b)).

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 20 of 69

5 TEST CONFIGURATIONS

5.1 Sub-6 Transmission

The P_{limit} values, corresponding to 1.0 W/kg (1gSAR) and 2.5 W/kg (10gSAR) of *SAR_design_target*, for technologies and bands supported by DUT are derived in Part 0 report and summarized in Table 6-1. Note all P_{limit} power levels entered in Table 6-1 correspond to average power levels after accounting for duty cycle in the case of TDD modulation schemes.

Table 5-1
 P_{limit} for supported technologies and bands (P_{limit} in EFS file)

Exposure Scenario	Maximum Tune-Up Output Power*	Body No Motion	Body Motion
Averaging Volume Spacing		1g	1g
		25mm	0mm
DSI		3	6
Technology/Band	Antenna	P_{max}	P_{limit}
UMTS 850	5	24.0	32.0
UMTS 1750	1	24.0	26.7
UMTS 1900	1	24.0	29.9
LTE Band 71	2	24.0	33.6
LTE Band 71	5	24.0	32.8
LTE Band 12	2	24.0	32.6
LTE Band 12	5	24.0	32.7
LTE Band 13	2	24.0	32.4
LTE Band 13	5	24.0	32.2
LTE Band 14	2	24.0	33.1
LTE Band 14	5	24.0	34.1
LTE Band 26	2	24.0	34.4
LTE Band 26	5	24.0	31.9
LTE Band 5	2	24.0	33.7
LTE Band 5	5	24.0	31.7
LTE Band 664	1	24.5	27.9
LTE Band 25	1	24.5	29.9
LTE Band 2	1	24.5	27.7
LTE Band 30	1	21.3	26.5
LTE Band 41 PC2	1	22.4	26.0
LTE Band 41 PC3	1	22.5	26.0
LTE Band 41 PC2	6	22.4	22.9
LTE Band 41 PC3	6	22.5	22.9
LTE Band 48	1	18.0	28.1
LTE Band 48	6	18.0	26.6
NR Band n71	2	24.0	34.0
NR Band n71	5	24.0	33.5
NR Band n12	2	24.0	31.0
NR Band n12	5	24.0	33.4
NR Band n14	2	24.0	32.8
NR Band n14	5	24.0	35.7
NR Band n26	2	24.0	30.4
NR Band n26	5	24.0	31.8
NR Band n6	1	24.5	26.5
NR Band n25n2	1	24.5	28.9
NR Band n30	1	21.3	25.5
NR Band n41 PC2	1	26.0	27.8
NR Band n41 PC3	1	24.5	27.8
NR Band n41 PC2	6	26.0	28.4
NR Band n41 PC3	6	24.5	28.4
NR Band n48 PC3	1	20.0	26.6
NR Band n48 PC3	3	20.0	28.5
NR Band n48 PC3	4	20.0	28.4
NR Band n48 PC3	6	20.0	24.4
NR Band n77 PC2	1	26.0	27.7
NR Band n77 PC3	1	24.0	27.7
NR Band n77 PC2	3	26.0	28.0
NR Band n77 PC3	3	24.0	28.0
NR Band n77 PC2	4	26.0	27.9
NR Band n77 PC3	4	24.0	27.9
NR Band n77 PC2	6	26.0	27.9
NR Band n77 PC3	6	24.0	27.9
NR Band n41 PC1.5 UL-MIMO	1	26.0	27.8
NR Band n41 PC1.5 UL-MIMO	6	26.0	28.4
NR Band n48 PC3 UL-MIMO	1	17.0	26.6
NR Band n48 PC3 UL-MIMO	6	17.0	24.4
NR Band n77 PC1.5 UL-MIMO	1	26.0	27.7
NR Band n77 PC1.5 UL-MIMO	6	26.0	27.9

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 21 of 69

* Maximum tune up target power, P_{max} , is configured in NV settings in DUT to limit maximum transmitting power. This power is converted into peak power in NV settings for TDD schemes. The DUT maximum allowed output power is equal to $P_{max} + 1$ dB device uncertainty.

Based on selection criteria described in Section 4.2.1, the selected technologies/bands for testing timevarying test sequences are highlighted in yellow in Table 6-1. Per the manufacturer, the Total_min_res_ratio is set to 0.5 and multi-Tx factor of 1.0 are set in EFS and used in Part 2 tests.

The radio configurations used in Part 2 test for selected technologies, bands, DSIs and antennas are listed in Table 5-2. The corresponding worst-case radio configuration 1gSAR values for selected technology/band/DSI are extracted from Part 1 report and are listed in the last column of Table 5-2.

Based on equations (1a), (2a), (3a) and (4a), it is clear that Part 2 testing outcome is normalized quantity, which implies that it can be applied to any radio configuration within a selected technology/band/DSI. Thus, as long as applying the worst-case SAR obtained from the worst radio configuration in Part 1 testing to calculate time-varying SAR exposure in equations (1a), (2a), (3a) and (4a), the accuracy in compliance demonstration remains the same. Therefore, there may be some differences between the radio configuration selected for Part 2 testing and the radio configuration associated with worst-case SAR obtained in the Part 1 evaluation.

The measured P_{limit} for all the selected radio configurations are listed in below Table 5-2. P_{max} was also measured for radio configurations selected for testing time-varying Tx power transmission scenarios in order to generate test sequences following the test procedures in Section 4.1.

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 22 of 69

Table 5-2
Radio configurations selected for Part 2 test

Test Case #	Test Scenario	Tech	Band	Antenna	DSI	Channel	Frequency [MHz]	Test Configurations	SAR Exposure Scenario	Part 1 Worst Case Measured SAR at Plimit (W/kg)	EFS Plimit [dBm]	Tune-up Pmax [dBm]	Measured Plimit [dBm]	Measured Pmax [dBm]
1	Time Varying Tx Power	WCDMA	5	5	6	4183	836.5	RMC	Bottom Edge, 0mm	0.619	21.2	24.0	21.24	24.09
2			2	1	6	9400	1880	RMC	Bottom Edge, 0mm	1.040	16.4	24.0	16.38	24.06
3		LTE	26	5	6	26865	831.5	QPSK 1/36/15 MHz BW	Bottom Edge, 0mm	0.753	21.2	24.0	20.80	23.67
4			48	6	6	56207	3646.7	QPSK 1/50/20 MHz BW	Bottom Edge, 0mm	0.856	14.5	18.0	14.46	17.71
5		NR	26	5	6	166300	831.5	DFT-S-OFDM, QPSK 1/1/20 MHz BW	Bottom Edge, 0mm	0.808	21.2	24.0	20.94	23.99
6			77 PC3	6	6	650000	3750	DFT-S-OFDM, QPSK 1/136/100 MHz BW	Bottom Edge, 0mm	0.788	14.5	23.0*	14.61	22.45*
7	Change in Call	LTE	48	6	6	56207	3646.7	QPSK 1/50/20 MHz BW	Bottom Edge, 0mm	0.856	14.5	18.0	14.46	17.71
8	Change in Technology/Band	LTE	26	5	6	26865	831.5	QPSK 1/36/15 MHz BW	Bottom Edge, 0mm	0.753	21.2	24.0	20.80	23.67
		WCDMA	2	1	6	9400	1880	RMC	Bottom Edge, 0mm	1.040	16.4	24.0	16.38	24.06
9	Change in Antenna	LTE	13	5	6	23230	782	QPSK 1/25/10 MHz BW	Bottom Edge, 0mm	0.495	20.9	24.0	20.50	23.66
				2	6	23230	782	QPSK 1/25/10 MHz BW	Bottom Edge, 0mm	0.566	20.4	24.0	19.73	23.34
10	Change in Device State (DSI)	LTE	5	5	3	20525	836.5	QPSK 1/25/10 MHz BW	Top Edge, 25mm	0.174	31.7	24.0	24.04	24.04
				5	6	20525	836.5	QPSK 1/25/10 MHz BW	Bottom Edge, 0mm	0.767	21.2	24.0	21.16	24.04
11	Change in Time Window	LTE	25	1	6	26365	1882.5	QPSK 1/50/20 MHz BW	Bottom Edge, 0mm	0.930	16.4	24.5	16.18	24.06
				48	6	56207	3646.7	QPSK 1/50/20 MHz BW	Bottom Edge, 0mm	0.856	14.5	18.0	14.46	17.71
12	WWAN SAR Exposure Switching (EN-DC) Same time-window	LTE	5	2	6	20525	836.5	QPSK 1/25/10 MHz BW	Bottom Edge, 0mm	0.752	21.1	24.0	21.08	23.98
		Sub6 NR	66	1	6	349000	1745	DFT-S-OFDM, QPSK 1/140 MHz BW	Bottom Edge, 0mm	0.849	17.2	24.5	16.41	23.85
13	WWAN SAR Exposure Switching (EN-DC) Different time-window	LTE	66	1	6	132322	1745	QPSK 1/50/20 MHz BW	Bottom Edge, 0mm	0.918	17.2	24.5	16.79	24.09
		Sub6 NR	77 PC3	6	6	650000	3750	DFT-S-OFDM, QPSK 1/136/100 MHz BW	Bottom Edge, 0mm	0.788	14.5	23.0*	14.61	22.45*

Note: The device uncertainty of P_{max} is +/- 1 dB as provided by manufacturer.

Note: *Due to equipment's capability, n77 TDD is 80% DC

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT					Approved by: Technical Manager	
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)					Page 23 of 69	

Table 5-3
DSI and Corresponding Exposure Scenarios

Scenario	Description	SAR Test Cases
Device Mode (DSI=3)	<ul style="list-style-type: none"> ▪ Device transmits at an angle $\leq 210^\circ$ or no motion is detected 	<i>SAR Testing per KDB Publication 616217 D04v01r02</i>
Device Mode (DSI=6)	<ul style="list-style-type: none"> ▪ Device transmits at an angle $> 210^\circ$ or motion is detected 	<i>SAR Testing per KDB Publication 616217 D04v01r02</i>

Based on the selection criteria described in Section 4.2, the radio configurations for the Tx varying transmission test cases listed in Section 3 are:

1. **Technologies and bands for time-varying Tx power transmission:** Based on selection criteria in Section 4.2.1, The test case 1~6 listed in Table 5-2 are selected to test with the test sequences in both time-varying conducted power measurement and time-varying SAR measurement.
2. **Technology and band for change in call:** Based on selection criteria in Section 4.2.2, LTE Band 4, antenna 6, having the lowest P_{limit} among all technologies and bands (test case 7 in Table 5-2), is selected for performing the call drop test in conducted power setup.
3. **Technologies and bands for change in technology/band:** Based on selection criteria in Section 4.2.3, test case 8 in Table 5-2 is selected for handover test from a technology/band within one technology group (LTE Band 26, DSI=6, antenna 5), to a technology/band in the same DSI within another technology group (WCDMA Band 2, DSI=6, antenna 1) in conducted power setup.
4. **Technologies and bands for change in Antenna:** Based on selection criteria in Section 4.2.4, test case 9 in Table 5-2 is selected for Antenna switch test by establishing a call in LTE Band 13, antenna 5 in DSI = 6, and then handing over to antenna 2 in DSI = 6 exposure scenario in conducted power setup.
5. **Technologies and bands for change in DSI:** Based on selection criteria in Section 4.2.5, test case 10 in Table 5-2 is selected for DSI switch test by establishing a call in LTE Band 5, antenna 5 in DSI = 3, and then handing over to DSI = 6 exposure scenario in conducted power setup.
6. **Technologies and bands for change in time-window:** Based on selection criteria in Section 4.2.6, for a given DSI=6, test case 11 in Table 5-2 is selected for time window switch between 60s window (LTE Band 48, Antenna 6) and 100s window (LTE Band 25, Antenna 1) in conducted power setup, and vice versa.
7. **Technologies and bands for switching in SAR exposure:** Based on selection criteria in Section 4.2.7 Scenario 1, test case 12 in Table 5-2 is selected for SAR exposure switching test in one of the supported simultaneous WWAN transmission scenario, i.e., LTE + Sub6 NR active in the same 100s time window, in conducted power setup. Based on selection criteria in Section 4.2.7 Scenario 2, test case 13 in Table 5-2 is selected for SAR exposure switching test in one of the supported simultaneous WWAN transmission scenario, i.e., LTE + Sub6 NR active in different time window, 100s time window to 60s time window, in conducted power setup.

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 24 of 69

5.2 EFS v19 Verification

Per Qualcomm's 80-w2112-5 document, embedded file system (EFS) version 19 products are required to be verified for Smart Tx generation for relevant MCC settings. It was confirmed that this DUT contains embedded file system (EFS) version 19 configured for Smart Tx second generation (GEN2) for Sub6 with MCC settings for the US market.

EFS v19 Generation	MCC
GEN2_Sub6	310

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 25 of 69

6 CONDUCTED POWER MEASUREMENT FOR SUB-6 SMART TRANSMIT FEATURE VALIDATION

6.1 Conducted Power Measurement Setup

Legacy test setup

The Rohde & Schwarz CMW500 callbox was used in this test. The test setup schematic is shown in Figure 6-1a (Appendix B – Test Setup Photo 1, 2, and 3) for measurements with a single antenna of DUT and in Figure 6-1b (Appendix B – Test Setup Photo 5 and 6) for measurements involving antenna switch. For single antenna measurement, one port (RF1 COM) of the callbox is connected to the RF port of the DUT using a directional coupler. For technology/band switch measurement, one port (RF1 COM) of the callbox used for signaling two different technologies is connected to a combiner, which is in turn connected to a directional coupler. The other end of the directional coupler is connected to a splitter to connect to two RF ports of the DUT corresponding to the two antennas of interest. In the setups, power meter is used to tap the directional coupler for measuring the conducted output power of the DUT. For all legacy conducted tests, only RF1 COM port of the callbox is used to communicate with the DUT.

All the path losses from RF port of DUT to the callbox RF COM port and to the power meter are calibrated and automatically entered as offsets in the callbox and the power meter via test scripts on the PC used to control callbox and power meter

Sub6 NR test setup:

The Anritsu MT8000A callbox was used in this test. The test setup schematic is the same as the Legacy Test Setup shown in Figure 6-1a (Appendix B – Test Setup Photo 4). One port of the callbox is connected to the RF port of the DUT using a directional coupler. In the setup, the power meter is used to tap the directional coupler for measuring the conducted output power of the DUT.


All the path losses from RF port of DUT to the callbox RF COM port and to the power meter are calibrated and automatically entered as offsets in the callbox and the power meter via test scripts on the PC used to control callbox and power meter.

LTE+Sub6 NR test setup:


LTE conducted port and Sub6 NR conducted port are different on this EUT, therefore, the LTE and Sub6 NR signals for power meter measurement are performed on separate paths as shown below in Figure 6-1c. (Appendix B – Test Setup Photo 7).

All the path losses from RF port of DUT to the callbox RF COM port and to the power meter are calibrated and automatically entered as offsets in the callbox and the power meter via test scripts on the PC used to control callbox and power meter.


FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 26 of 69



(a) Appendix B – Test Setup Photo 1, 2, 3, 4, 5



(b) Appendix B – Test Setup Photo 6, 7, 8



(c) Appendix B – Test Setup Photo 9, 10

Figure 6-1
Conducted power measurement setup

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Approved by: Technical Manager Page 27 of 69

Both the callbox and power meter are connected to the PC using GPIB cables. Two test scripts are custom made for automation, and the test duration set in the test scripts is 500 seconds.

For time-varying Tx power measurement, the PC runs the 1st test script to send GPIB commands to control the callbox's requested power versus time, while at the same time to record the conducted power measured at DUT RF port using the power meter. The commands sent to the callbox to request power are:

- 0dBm for 100 seconds
- test sequence 1 or test sequence 2 (defined in Section 4.1 and generated in Section 4.2.1), for 360 seconds.
- stay at the last power level of test sequence 1 or test sequence 2 for the remaining time.

Power meter readings are periodically recorded every 100ms. A running average of this measured Tx power over 100 seconds is performed in the post-data processing to determine the 100s-time averaged power.

For call drop, technology/band/antenna switch, and DS1 switch tests, after the call is established, the callbox is set to request the DUT's Tx power at 0dBm for 100 seconds while simultaneously starting the 2nd test script runs at the same time to start recording the Tx power measured at DUT RF port using the power meter. After the initial 100 seconds since starting the Tx power recording, the callbox is set to request maximum power from the DUT for the rest of the test. Note that the call drop/re-establish, or technology/band/antenna switch or DS1 switch is manually performed when the Tx power of DUT is at P_{reserve} level. See Section 4.3 for detailed test procedure of call drop test, technology/band/antenna switch test and DS1 switch test.

6.2 Time-varying Tx Power

The measurement setup is shown in Figure 6-1a. The purpose of the time-varying Tx power measurement is to demonstrate the effectiveness of power limiting enforcement and that the time-averaged Tx power when represented in time-averaged 1gSAR or 10gSAR values does not exceed FCC limit as shown in Eq. (1a) and (1b), rewritten below:

$$1g_or_10gSAR(t) = \frac{\text{conducted_Tx_power}(t)}{\text{conducted_Tx_power_P}_{\text{limit}}} * 1g_or_10gSAR_P_{\text{limit}} \quad (1a)$$

$$\frac{\frac{1}{T_{\text{SAR}}} \int_{t-T_{\text{SAR}}}^t 1g_or_10gSAR(t)dt}{\text{FCC SAR limit}} \leq 1 \quad (1b)$$

where, *conducted_Tx_power(t)*, *conducted_Tx_power_P_limit*, and *1g_or_10gSAR_P_limit* correspond to the measured instantaneous conducted Tx power, measured conducted Tx power at P_{limit} , and measured 1gSAR and 10gSAR values at P_{limit} reported in Part 1 test (listed in Table 5-2 of this report as well).

Following the test procedure in Section 4.3.1, the conducted Tx power measurement for all selected configurations are reported in this section. In all the conducted Tx power plots, the

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 28 of 69

green curve represents time-averaged power and red line represents the conducted power limit that corresponds to FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR.

Similarly, in all the 1g or 10gSAR plots (when converted using Eq. (1a)), the green curve represents the 100s/60s-time averaged 1gSAR or 10gSAR value calculated based on instantaneous 1gSAR or 10gSAR; and the red line limit represents the FCC limit of 1.6 W/kg for 1gSAR or 4.0 W/kg for 10gSAR.

Time-varying Tx power measurements were conducted on test cases #1 ~ #6 in Table 5-2, by generating test sequence 1 and test sequence 2 given in APPENDIX C: using measured P_{limit} and measured P_{max} (last two columns of Table 5-2) for each of these test cases. Measurement results for test cases #1 ~ #6 are given in Sections 6.2.1-6.2.6.


FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 29 of 69

6.2.1

WCDMA Band 5, Antenna 5

Test result for test sequence 1:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:




	(W/kg)
FCC 1gSAR limit	1.6
Max 100s-time averaged 1gSAR (green curve)	0.648
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 30 of 69

Test result for test sequence 2:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:



	(W/kg)
FCC 1gSAR limit	1.6
Max 100s-time averaged 1gSAR (green curve)	0.646
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	


FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A Document S/N: 1M2504010035-06.C3K	RF EXPOSURE PART 2 WWAN TEST REPORT DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Approved by: Technical Manager Page 31 of 69
--	---	---

6.2.2

WCDMA Band 2, Antenna 1

Test result for test sequence 1:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:




	(W/kg)
FCC 1gSAR limit	1.6
Max 100s-time averaged 1gSAR (green curve)	1.054
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 32 of 69

Test result for test sequence 2:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:



	(W/kg)
FCC 1gSAR limit	1.6
Max 100s-time averaged 1gSAR (green curve)	1.041
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	


FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 33 of 69

6.2.3

LTE Band 26, Antenna 5

Test result for test sequence 1:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:




	(W/kg)
FCC 1gSAR limit	1.6
Max 100s-time averaged 1gSAR (green curve)	0.774
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 34 of 69

Test result for test sequence 2:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:



	(W/kg)
FCC 1gSAR limit	1.6
Max 100s-time averaged 1gSAR (green curve)	0.783
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	


FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A Document S/N: 1M2504010035-06.C3K	RF EXPOSURE PART 2 WWAN TEST REPORT DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Approved by: Technical Manager Page 35 of 69
--	---	---

6.2.4

LTE Band 48, Antenna 6

Test result for test sequence 1:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:




		(W/kg)
FCC 1gSAR limit		1.6
Max 60s-time averaged 1gSAR (green curve)		0.862
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).		

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 36 of 69

Test result for test sequence 2:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:




	(W/kg)
FCC 1gSAR limit	1.6
Max 60s-time averaged 1gSAR (green curve)	0.859
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 37 of 69

6.2.5 NR n26 SA, Antenna 5

Test result for test sequence 1:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:




	(W/kg)
FCC 1gSAR limit	1.6
Max 100s-time averaged 1gSAR (green curve)	0.833
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 38 of 69

Test result for test sequence 2:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:



	(W/kg)
FCC 1gSAR limit	1.6
Max 100s-time averaged 1gSAR (green curve)	0.851
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	


FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 39 of 69

6.2.6

NR n77 SA, Antenna 6

Test result for test sequence 1:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:




	(W/kg)
FCC 1gSAR limit	1.6
Max 60s-time averaged 1gSAR (green curve)	0.806
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 40 of 69

Test result for test sequence 2:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:



	(W/kg)
FCC 1gSAR limit	1.6
Max 60s-time averaged 1gSAR (green curve)	0.802
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	


FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 41 of 69

6.3 Change in Call

This test was measured LTE Band 48, Antenna 6, DSI = 6, and with callbox requesting maximum power. The call drop was manually performed when the DUT is transmitting at P_{reserve} level as shown in the plot below. The measurement setup is shown in Figure 6-1a. The detailed test procedure is described in Section 4.3.2.

Call drop test result:

Time-averaged conducted Tx power is converted/calculated into time-averaged 1gSAR using Equation (1a) and plotted below to demonstrate that the time-averaged 1gSAR versus time does not exceed the FCC limit of 1.6 W/kg for 1gSAR:



		(W/kg)
FCC 1gSAR limit		1.6
Max 60s-time averaged 1gSAR (green curve)		0.878
Validated		

The test result validated the continuity of power limiting in call change scenario.


FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 42 of 69

6.4 Change in Technology/Band

This test was conducted with callbox requesting maximum power, and with a technology switch from LTE Band 26, Antenna 5, DSI = 6 to WCDMA Band 2, Antenna 1, DSI = 6. Following procedure detailed in Section 4.3.3, and using the measurement setup shown in Figure 6-1b, the technology/band switch was performed when the DUT is transmitting at P_{reserve} level as shown in the plot below.

Test result for change in technology/band/Antenna:

Time-averaged conducted Tx power measurement results were converted into time-averaged normalized SAR values using Equation (6a), (6b) and (6c), and plotted below to demonstrate that the time-averaged normalized SAR versus time does not exceed the normalized FCC limit of 1.0:



FCC normalized SAR limit	1.0
Max 100s-time averaged normalized SAR (green curve)	0.555
Validated	

The test result validated the continuity of power limiting in technology/band/Antenna switch scenario.


FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 43 of 69

6.1 Change in Antenna

This test was conducted with callbox requesting maximum power, and with antenna switch from LTE Band 13, antenna 5, DS1 = 6 to antenna 2, DS1 = 6. Following procedure detailed in Section 4.3.4 using the measurement setup shown in Figure 6-1b, the DS1 switch was performed when the DUT is transmitting at P_{reserve} level as shown in the plot below.

Test result for change in Antenna:

Time-averaged conducted Tx power measurement results were converted into time-averaged normalized SAR values using Equation (6a), (6b) and (6c), and plotted below to demonstrate that the time-averaged normalized SAR versus time does not exceed the normalized FCC limit of 1.0:



FCC normalized SAR limit	1.0
Max 100s-time averaged normalized SAR (green curve)	0.361
Validated	

The test result validated the continuity of power limiting in Antenna switch scenario.


FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 44 of 69

6.2 Change in Device State Index (DSI)

This test was conducted with callbox requesting maximum power, and with DSI switch from LTE Band 5, antenna 5, DSI = 3 to DSI = 6. Following procedure detailed in Section 4.3.5 using the measurement setup shown in Figure 6-1a, the DSI switch was performed when the DUT is transmitting at P_{reserve} level as shown in the plot below.

Test result for change in DSI:

All the time-averaged conducted Tx power measurement results were converted into time-averaged normalized SAR values using Equation (4a), (4b) and (4c), and plotted below to demonstrate that the time-averaged normalized SAR versus time does not exceed the FCC limit of 1 unit.



FCC normalized total exposure limit	1.0
Max 30s-time averaged normalized SAR (green curve)	0.490
Validated	

The test result validated the continuity of power limiting in DSI switch scenario.

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 45 of 69


6.3 Change in Time Window/Antenna

This test was conducted with callbox requesting maximum power, and with time-window between LTE Band 25, Antenna 1, DSI = 6 (100s window) and LTE Band 48, Antenna 6, DSI = 6 (60s window). Following procedure detailed in Section 4.3.6, and using the measurement setup shown in Figure 6-1b, the time-window switch via tech/band/antenna switch was performed when the EUT is transmitting at P_{reserve} level.

6.3.1 Test case 1: transition from LTE Band 25 to LTE Band 48 (i.e., 100s to 60s), then back to LTE Band 25

Test result for change in time-window (from 100s to 60s to 100s):

All the conducted Tx power measurement results were converted into time-averaged normalized SAR values using Equation (7a), (7b) and (7c), and plotted below to demonstrate that the time-averaged normalized SAR versus time does not exceed the FCC limit of 1 unit. Equation (7a) is used to convert the Tx power of device to obtain 100s-averaged normalized SAR in LTE Band 25 as shown in black curve. Similarly, equation (7b) is used to obtain 60s-averaged normalized SAR in LTE Band 48 as shown in orange curve. Equation (7c) is used to obtain total time-averaged normalized SAR as shown in green curve (i.e., sum of black and orange curves).



FCC normalized total exposure limit	1.0
Max time averaged normalized SAR (green curve)	0.603
Validated	

Plot Notes: Maximum power is requested by callbox for the entire duration of the test, with tech/band switches from 100s-to-60s window at ~248s time stamp, and from 60s-to-100s window at ~316s time stamp. Smart Transmit controls the Tx power during these time-window switches to ensure total time-averaged RF exposure, i.e., sum of black and orange curves given by equation (7c), is always compliant. In time-window switch test, at all times the total time-averaged normalized RF exposure (green curve) should not exceed normalized SAR_design_target + 1dB device uncertainty. In this test, with a maximum


FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 46 of 69

normalized SAR of 0.603 being ≤ 0.79 ($= 1.0/1.6 + 1\text{dB}$ device uncertainty), the above test result validated the continuity of power limiting in time-window switch scenario.

6.3.2 Test case 2: transition from LTE Band 48 to LTE Band 25 (i.e., 60s to 100s), then back to LTE Band 48

Test result for change in time-window (from 60s to 100s to 60s):

All the conducted Tx power measurement results were converted into time-averaged normalized SAR values using Equation (7a), (7b) and (7c), and plotted below to demonstrate that the time-averaged normalized SAR versus time does not exceed the FCC limit of 1 unit. Equation (7a) is used to convert the Tx power of device to obtain 60s-averaged normalized SAR in LTE Band 48 as shown in black curve. Similarly, equation (7b) is used to obtain 100s-averaged normalized SAR in LTE Band 25 as shown in orange curve. Equation (7c) is used to obtain total time-averaged normalized SAR as shown in green curve (i.e., sum of black and orange curves).



FCC normalized total exposure limit	1.0
Max time averaged normalized SAR (green curve)	0.598
Validated	


Plot Notes: Maximum power is requested by callbox for the entire duration of the test, with tech/band switches from 60s-to-100s window at ~ 215 time stamp, and from 100s-to-60s window at ~ 321 time stamp. Smart Transmit controls the Tx power during these time-window switches to ensure total time-averaged RF exposure, i.e., sum of black and orange curves given by equation (7c), is always compliant. In time-window switch test, at all times the total time-averaged normalized RF exposure (green curve) should not exceed normalized *SAR_design_target* + 1dB device uncertainty. In this test, with a maximum normalized SAR of 0.598 being ≤ 0.79 ($= 1.0/1.6 + 1\text{dB}$ device uncertainty), the above test result validated the continuity of power limiting in time-window switch scenario.

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 47 of 69

6.4 SAR Exposure Switching WWAN EN-DC – Same Time-Window

This test was conducted with callbox requesting maximum power, and with the EUT in LTE Band 5 + Sub6 NR Band n66 call. Following procedure detailed in Section 4.3.7 and Appendix F.2, and using the measurement setup shown in Figure 6-1c since LTE and Sub6 NR are on different antenna ports, the SAR exposure switch measurement is performed with the EUT in various SAR exposure scenarios, i.e., in SAR_{sub6NR} only scenario ($t = 0s \sim 120s$), SAR_{sub6NR} + SAR_{LTE} scenario ($t = 120s \sim 240s$) and SAR_{LTE} only scenario ($t > 240s$).

Plot Notes: All the conducted Tx power measurement results were converted into time-averaged normalized SAR values using Equation (7a), (7b) and (7c), and plotted below to demonstrate that the time-averaged normalized SAR versus time does not exceed the FCC limit of 1 unit. Equation (7a) is used to convert the LTE Tx power of device to obtain 100s-averaged normalized SAR in LTE Band 5 as shown in black curve. Similarly, equation (7b) is used to obtain 100s-averaged normalized SAR in Sub6 NR n66 as shown in orange curve. Equation (7c) is used to obtain total time-averaged normalized SAR as shown in green curve (i.e., sum of black and orange curves).



FCC normalized total exposure limit	1.0
Max time averaged normalized SAR (green curve)	0.558
Validated	

Plot Notes: Device starts predominantly in Sub6 NR SAR exposure scenario between 0s and 120s, and in LTE SAR + Sub6 NR SAR exposure scenario between 120s and 240s, and in predominantly in LTE SAR exposure scenario after $t = 240s$. Here, Smart Transmit allocates a maximum of 100% of exposure margin (based on 3dB reserve margin setting) for Sub6 NR. This corresponds to a normalized 1gSAR exposure value = $100\% * 0.849 \text{ W/kg measured SAR at Sub6 NR } P_{limit} / 1.6\text{W/kg limit} = 0.531 \pm 1\text{dB device related uncertainty}$ (see orange curve between 120s). For predominantly LTE SAR exposure scenario, maximum normalized 1gSAR exposure should correspond to 100% exposure margin = $0.752 \text{ W/kg measured SAR at LTE } P_{limit} / 1.6\text{W/kg limit} = 0.470 \pm 1\text{dB device related uncertainty}$ (see black curve after $t = 240s$). Additionally, in SAR exposure switch test, at all times the total time-averaged normalized RF exposure (green curve) should not exceed normalized SAR_{design_target} + 1dB device uncertainty.


FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 48 of 69

In this test, with a maximum normalized SAR of 0.558 being ≤ 0.79 ($= 1.0/1.6 + 1\text{dB}$ device uncertainty), the above test result validated the continuity of power limiting in SAR exposure switch scenario.

6.5 SAR Exposure Switching WWAN EN-DC – Different Time-Window

This test was conducted with callbox requesting maximum power, and with the EUT in LTE Band 66 + Sub6 NR Band n77 call. Following procedure detailed in Section 4.3.7 and Appendix F.2, and using the measurement setup shown in Figure 6-1c since LTE and Sub6 NR are on different antenna ports, the SAR exposure switch measurement is performed with the EUT in various SAR exposure scenarios, i.e., in SAR_{sub6NR} only scenario ($t = 0\text{s} \sim 120\text{s}$), SAR_{sub6NR} + SAR_{LTE} scenario ($t = 120\text{s} \sim 240\text{s}$) and SAR_{LTE} only scenario ($t > 240\text{s}$).

Plot Notes: All the conducted Tx power measurement results were converted into time-averaged normalized SAR values using Equation (7a), (7b) and (7c), and plotted below to demonstrate that the time-averaged normalized SAR versus time does not exceed the FCC limit of 1 unit. Equation (7a) is used to convert the LTE Tx power of device to obtain 100s-averaged normalized SAR in LTE Band 66 as shown in black curve. Similarly, equation (7b) is used to obtain 100s-averaged normalized SAR in Sub6 NR n77 as shown in orange curve. Equation (7c) is used to obtain total time-averaged normalized SAR as shown in green curve (i.e., sum of black and orange curves).



FCC normalized total exposure limit	1.0
Max time averaged normalized SAR (green curve)	0.566
Validated	

Plot Notes: Device starts predominantly in Sub6 NR SAR exposure scenario between 0s and 120s, and in LTE SAR + Sub6 NR SAR exposure scenario between 120s and 240s, and in predominantly in LTE SAR exposure scenario after $t=240\text{s}$. Here, Smart Transmit allocates a maximum of 100% of exposure margin (based on 3dB reserve margin setting) for Sub6 NR. This corresponds to a normalized 1gSAR exposure value = $100\% * 0.788 \text{ W/kg}$ measured SAR at Sub6 NR P_{limit} / 1.6W/kg limit = $0.493 \pm 1\text{dB}$ device related

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 49 of 69

uncertainty (see orange curve between 120s). For predominantly LTE SAR exposure scenario, maximum normalized 1gSAR exposure should correspond to 100% exposure margin = 0.918 W/kg measured SAR at LTE P_{limit} / 1.6W/kg limit = $0.574 \pm 1\text{dB}$ device related uncertainty (see black curve after t = 240s). Additionally, in SAR exposure switch test, at all times the total time-averaged normalized RF exposure (green curve) should not exceed normalized $SAR_{design_target} + 1\text{dB}$ device uncertainty. In this test, with a maximum normalized SAR of 0.566 being ≤ 0.79 ($= 1.0/1.6 + 1\text{dB}$ device uncertainty), the above test result validated the continuity of power limiting in SAR exposure switch scenario.

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 50 of 69

7 SYSTEM VERIFICATION (FREQ < 6 GHZ)

7.1 Tissue Verification

Table 7-1
Measured Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Tissue Temp During Calibration (°C)	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
6/3/2025	835 Head	20.9	815	0.897	42.521	0.898	41.594	-0.11%	2.23%
			820	0.899	42.511	0.899	41.578	0.00%	2.24%
			835	0.904	42.471	0.900	41.500	0.44%	2.34%
			850	0.909	42.423	0.916	41.500	-0.76%	2.22%
6/3/2025	1900 Head	20.9	1850	1.399	40.588	1.400	40.000	-0.07%	1.47%
			1860	1.405	40.575	1.400	40.000	0.36%	1.44%
			1880	1.415	40.548	1.400	40.000	1.07%	1.37%
			1900	1.425	40.520	1.400	40.000	1.79%	1.30%
			1905	1.428	40.512	1.400	40.000	2.00%	1.28%
			1910	1.431	40.506	1.400	40.000	2.21%	1.27%
			1920	1.437	40.494	1.400	40.000	2.64%	1.24%
6/6/2025	3600 Head	19.0	3600	2.886	38.889	3.015	37.814	-4.28%	2.84%
			3650	2.929	38.817	3.066	37.757	-4.47%	2.81%
			3690	2.973	38.729	3.107	37.711	-4.31%	2.70%
			3700	2.983	38.718	3.117	37.700	-4.30%	2.70%
			3750	3.027	38.653	3.169	37.643	-4.48%	2.68%
			3900	3.187	38.390	3.323	37.471	-4.09%	2.45%

The above measured tissue parameters were used in the DASY software. The DASY software was used to perform interpolation to determine the dielectric parameters at the SAR test device frequencies (per KDB Publication 865664 D01v01r04 and IEEE 1528-2013 6.6.1.2). The tissue parameters listed in the SAR test plots may slightly differ from the table above due to significant digit rounding in the software.

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 51 of 69

7.2 Test System Verification

Prior to SAR assessment, the system is verified to $\pm 10\%$ of the SAR measurement on the reference dipole at the time of calibration by the calibration facility. Full system validation status and result summary can be found in Appendix C.

Table 7-2
System Verification Results – 1g

System Verification TARGET & MEASURED													
SAR System #	Tissue Frequency (MHz)	Tissue Type	Date	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Source SN	Probe SN	DAE	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation _{1g} (%)
S	835	HEAD	6/3/2025	21.6	21.6	0.200	4d132	7803	1583	1.990	9.840	9.950	1.12%
S	1900	HEAD	6/3/2025	21.6	21.6	0.100	5d080	7803	1583	4.270	39.600	42.700	7.83%
E	3700	HEAD	6/6/2025	22.7	20.0	0.100	1067	7660	1678	6.950	66.900	69.500	3.89%




Figure 7-1
System Verification Setup Diagram



Figure 7-2
System Verification Setup Photo

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 52 of 69

8 SAR TEST RESULTS (FREQ < 6 GHZ)

8.1 SAR Measurement Setup

The measurement setup is similar to normal SAR measurements as described in the Part 1 Test Report. The difference in SAR measurement setup for time averaging feature validation is that the callbox is signaling in close loop power control mode (instead of requesting maximum power in open loop control mode) and callbox is connected to the PC using GPIB so that the test script executed on PC can send GPIB commands to control the callbox's requested power over time (test sequence). The same test script used in conducted setup for time-varying Tx power measurements is also used in this section for running the test sequences during SAR measurements, and the recorded values from the disconnected power meter by the test script were discarded.

As mentioned in Section 4.4, for DUT to follow TPC command sent from the callbox wirelessly, the “path loss” between callbox antenna and the DUT needs to be very well calibrated. Since the SAR chamber is in uncontrolled environment, precautions must be taken to minimize the environmental influences on “path loss”. Similarly, in the case of time-varying SAR measurements in Sub6 NR (with LTE as anchor), “path loss” between callbox antenna and the EUT needs to be carefully calibrated for both LTE link as well as for Sub6 NR link.

The DUT is placed in worst-case position according to Table 5-2.

8.2 Time-varying Tx Power

Following Section 4.4 procedure, time-averaged SAR measurements are conducted using a SAR probe at peak location of area scan over 500 seconds. cDASY6 system verification for SAR measurement is provided in Section 10, and the associated SPEAG certificates are attached in Appendix G.

SAR probe integration times depend on the communication signal being tested as defined in the probe calibration parameters.

Since the sampling rate used by cDASY6 for pointSAR measurements is not in user control, the number of points in 100s interval is determined from the scan duration setting in cDASY6 time-average pointSAR measurement by (100s cDASY6_scan_duration * total number of pointSAR values recorded). Running average is performed over these number of points in excel spreadsheet to obtain 100s averaged point SAR.

Following Section 4.4, for each of selected technology/band (listed in Table 5-2):

8. With *Reserve_power_margin* set to 0 dB, area scan is performed at P_{limit} , and time-averaged pointSAR measurements are conducted to determine the pointSAR at P_{limit} at peak location, denoted as $pointSAR_{P_{limit}}$.
9. With *Reserve_power_margin* set to actual (intended) value, two more time-averaged pointSAR measurements are performed at the same peak location for test sequences 1 and 2.

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 53 of 69


To demonstrate compliance, all the pointSAR measurement results were converted into 1gSAR or 10gSAR values by using Equation (3a), rewritten below:

$$1g_or_10gSAR(t) = \frac{pointSAR(t)}{pointSAR_P_{limit}} * 1g_or_10gSAR_P_{limit} \quad (3a)$$

where, $pointSAR(t)$, $pointSAR_P_{limit}$, and $1g_or_10gSAR_P_{limit}$ correspond to the measured instantaneous point SAR, measured point SAR at P_{limit} from above step 1 and 2, and measured 1gSAR or 10gSAR values at P_{limit} obtained from Part 1 report and listed in Table 5-2 of this report.


8.2.1 WCDMA Band 5, Antenna 5

SAR test results for test sequence 1:



	(W/kg)
FCC 1gSAR limit	1.6
Max 100s-time averaged point 1gSAR (green curve)	0.643
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 54 of 69

SAR test results for test sequence 2:



	(W/kg)
FCC 1gSAR limit	1.6
Max 100s-time averaged point 1gSAR (green curve)	0.640
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A Document S/N: 1M2504010035-06.C3K	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager Page 55 of 69
--	--	---

8.2.2

WCDMA Band 2, Antenna 1


SAR test results for test sequence 1:



	(W/kg)
FCC 1gSAR limit	1.6
Max 100s-time averaged point 1gSAR (green curve)	1.063

Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at P_{lim} column in Table 5-2).

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 56 of 69

SAR test results for test sequence 2:



	(W/kg)
FCC 1gSAR limit	1.6
Max 100s-time averaged point 1gSAR (green curve)	1.064
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A Document S/N: 1M2504010035-06.C3K	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager Page 57 of 69
--	--	--

8.2.3

LTE Band 26, Antenna 5


SAR test results for test sequence 1:



	(W/kg)
FCC 1gSAR limit	1.6
Max 100s-time averaged point 1gSAR (green curve)	0.777

Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 58 of 69

SAR test results for test sequence 2:



	(W/kg)
FCC 1gSAR limit	1.6
Max 100s-time averaged point 1gSAR (green curve)	0.772
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 59 of 69

8.2.4


LTE Band 48, Antenna 6

SAR test results for test sequence 1:



	(W/kg)
FCC 1gSAR limit	1.6
Max 60s-time averaged point 1gSAR (green curve)	0.866
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A Document S/N: 1M2504010035-06.C3K	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager Page 60 of 69
--	--	---


SAR test results for test sequence 2:


	(W/kg)
FCC 1gSAR limit	1.6
Max 60s-time averaged point 1gSAR (green curve)	0.866
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A Document S/N: 1M2504010035-06.C3K	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager Page 61 of 69
---	--	---


8.2.5 NR n26 SA, Antenna 5

SAR test results for test sequence 1:



	(W/kg)
FCC 1gSAR limit	1.6
Max 100s-time averaged point 1gSAR (green curve)	0.839
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 62 of 69

SAR test results for test sequence 2:



	(W/kg)
FCC 1gSAR limit	1.6
Max 100s-time averaged point 1gSAR (green curve)	0.830
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A Document S/N: 1M2504010035-06.C3K	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager Page 63 of 69
--	--	---

8.2.6

NR n77 SA, Antenna 6


SAR test results for test sequence 1:



	(W/kg)
FCC 1gSAR limit	1.6
Max 60s-time averaged point 1gSAR (green curve)	0.846

Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at P_{lim} column in Table 5-2).

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 64 of 69

SAR test results for test sequence 2:


	(W/kg)
FCC 1gSAR limit	1.6
Max 60s-time averaged point 1gSAR (green curve)	0.834
Validated: Max time averaged SAR (green curve) is within 1 dB device uncertainty of measured SAR at P_{limit} (worst case SAR at Plim column in Table 5-2).	

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A Document S/N: 1M2504010035-06.C3K	RF EXPOSURE PART 2 WWAN TEST REPORT DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Approved by: Technical Manager Page 65 of 69
---	--	---

9 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	E4404B	Spectrum Analyzer	N/A	N/A	N/A	MY45113242
Agilent	E4438C	ESG Vector Signal Generator	10/23/2024	Annual	10/23/2025	MY45093852
Agilent	E4438C	ESG Vector Signal Generator	11/15/2024	Annual	11/15/2025	MY45092078
Agilent	N5182A	MXG Vector Signal Generator	12/5/2024	Annual	12/5/2025	US46240505
Agilent	N5182A	MXG Vector Signal Generator	7/9/2024	Annual	7/9/2025	MY48180366
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433972
Amplifier Research	1551G6	Amplifier	CBT	N/A	CBT	433974
Anritsu	MT8000A	Radio Communication Test Station	11/12/2024	Annual	11/12/2025	6272337405
Anritsu	MT8821C	Radio Communication Analyzer MT8821C	CBT	Annual	CBT	6201144419
Anritsu	MA24106A	USB Power Sensor	7/9/2024	Annual	7/9/2025	1244512
Anritsu	ML2496A	Power Meter	7/15/2024	Annual	7/15/2025	1138001
Anritsu	MA2411B	Pulse Power Sensor	7/1/2024	Annual	7/1/2025	1911105
Anritsu	MA2411B	Pulse Power Sensor	7/10/2024	Annual	7/10/2025	1126066
COMTech	AR85729-5	Solid State Amplifier	CBT	N/A	CBT	M155A00-009
Control Company	4052	Long Stem Thermometer	2/27/2024	Biennial	2/27/2026	240174346
Control Company	4040	Therm./ Clock/ Humidity Monitor	4/15/2024	Biennial	4/15/2026	240310280
Control Company	4052	Long Stem Thermometer	2/27/2024	Biennial	2/27/2026	240171096
K & L	11SH10-1300/U4000	High Pass Filter	CBT	N/A	CBT	11SH10-1300/U4000 - 2
Keysight Technologies	772D	Dual Directional Coupler	CBT	N/A	CBT	MY52180215
Krytar	110067006	Directional Coupler, 10 - 67 GHz	CBT	N/A	CBT	200391
MiniCircuits	NLP-1200+	Low Pass Filter	CBT	N/A	CBT	VUU78201318
MiniCircuits	SLP-2400+	Low Pass Filter	CBT	N/A	CBT	R8979500903
MiniCircuits	VLF-6000+	Low Pass Filter	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-2950+	Low Pass Filter DC to 2700 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	NLP-1200+	Low Pass Filter DC to 1000 MHz	CBT	N/A	CBT	N/A
Mini-Circuits	BW-N20W5	Power Attenuator	CBT	N/A	CBT	1226
Narda	4216-10	Directional Coupler, 0.5 to 8.0 GHz, 10 dB	CBT	N/A	CBT	1492
Narda	4216-10	Directional Coupler, 0.5 to 8.0 GHz, 10 dB	CBT	N/A	CBT	1493
Narda	4772-3	Attenuator	CBT	N/A	CBT	9406
Narda	BW-S3W2	Attenuator	CBT	N/A	CBT	120
Narda	BW-S10W2+	Attenuator	CBT	N/A	CBT	831
Narda	4014C-6	4 - 8 GHz SMA 6 dB Directional Coupler	CBT	N/A	CBT	N/A
Newmark System	NSC-G2	Motion Controller	CBT	N/A	CBT	1007-D
Pasternack	PE2208-6	Bidirectional Coupler	CBT	N/A	CBT	N/A
Pasternack	PE2209-10	Bidirectional Coupler	CBT	N/A	CBT	N/A
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	1/6/2025	Annual	1/6/2026	150117
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	1/6/2025	Annual	1/6/2026	131454
Rohde & Schwarz	NRP8S	3 Path Dipole Power Sensor	10/28/2024	Annual	10/28/2025	109956
Rohde & Schwarz	NRP8S	3 Path Dipole Power Sensor	2/24/2025	Annual	2/24/2026	109961
Rohde & Schwarz	NRP8S	3-Path Dipole Power Sensor	9/24/2024	Annual	9/24/2025	109958
Rohde & Schwarz	NRP50S	3-Path Dipole Power Sensor	2/24/2025	Annual	2/24/2026	109959
SPEAG	DAK-3.5	Dielectric Assessment Kit	12/3/2024	Annual	12/3/2025	1278
SPEAG	D835V2	835 MHz SAR Dipole	3/11/2024	Biennial	3/11/2026	4d132
SPEAG	D1900V2	1900 MHz SAR Dipole	8/8/2022	Triennial	8/8/2025	5d080
SPEAG	D3700V2	3700 MHz SAR Dipole	1/13/2023	Triennial	1/13/2026	1067
SPEAG	DAE4	Dasy Data Acquisition Electronics	7/8/2024	Annual	7/8/2025	1583
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/9/2025	Annual	5/9/2026	1678
SPEAG	EX3DV4	SAR Probe	6/28/2024	Annual	6/28/2025	7803
SPEAG	EX3DV4	SAR Probe	5/9/2025	Annual	5/9/2026	7660

Notes:

1. CBT (Calibrated Before Testing). Prior to testing, the measurement paths containing a cable, amplifier, attenuator, coupler, or filter were connected to a calibrated source (i.e. a signal generator) to determine the losses of the measurement path. The power meter offset was then adjusted to compensate for the measurement system losses. This level offset is stored within the power meter before measurements are made. This calibration verification procedure applies to the system verification and output power measurements. The calibrated reading is then taken directly from the power meter after compensation of the losses for all final power measurements.
2. Each equipment item is used solely within its respective calibration period.

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 66 of 69

10 CONCLUSION

10.1 Measurement Conclusion

The SAR evaluation indicates that the DUT complies with the RF radiation exposure limits of the FCC and Innovation, Science, and Economic Development Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 67 of 69

11 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 3kHz to 300GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] IEEE Standards Coordinating Committee 39 –Standards Coordinating Committee 34 – IEEE Std. 1528-2013, IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 1 -124.
- [9] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no. 3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 68 of 69

- [17] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [18] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [19] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [20] IEC 62209-1, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz), July 2016.
- [21] Innovation, Science, Economic Development Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5, March 2015.
- [22] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2015
- [23] FCC SAR Test Procedures for 2G-3G Devices, Mobile Hotspot and UMPD Devices KDB Publications 941225, D01-D07
- [24] SAR Measurement Guidance for IEEE 802.11 Transmitters, KDB Publication 248227 D01
- [25] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publications 648474 D03-D04
- [26] FCC SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers, FCC KDB Publication 616217 D04
- [27] FCC SAR Measurement and Reporting Requirements for 100MHz – 6 GHz, KDB Publications 865664 D01-D02
- [28] FCC General RF Exposure Guidance and SAR Procedures for Dongles, KDB Publication 447498, D01-D02
- [29] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [30] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.

FCC ID: Licensed Module C3K2119 FCC ID: Unlicensed Module C3K00002102A	RF EXPOSURE PART 2 WWAN TEST REPORT	Approved by: Technical Manager
Document S/N: 1M2504010035-06.C3K	DUT Type: Modular Approval - Host Integration (Portable Computing Device)	Page 69 of 69