

RF Exposure Report

Report No.: SA150720E05

FCC ID: C3K1683

Test Model: 1683

Received Date: July 20, 2015

Test Date: Nov. 23, 2015

Issued Date: Dec. 18, 2015

Applicant: Microsoft Corporation.

Address: One Microsoft Way Redmond WA 98052

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location (1): E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location (2): No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin
Chu Hsien 307, Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.



A D T

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	5
2.5 Calculation Result of Maximum Conducted Power.....	6



A D T

Release Control Record

Issue No.	Description	Date Issued
SA150720E05	Original release.	Dec. 18, 2015



A D T

1 Certificate of Conformity

Product: 802.11a/b/g/n(/ac) 2T2R dual-band wireless LAN radio

Brand: Microsoft

Test Model: 1683

Sample Status: ENGINEERING SAMPLE

Applicant: Microsoft Corporation.


Test Date: Nov. 23, 2015


Standards: FCC Part 2 (Section 2.1091)

447498 D01 GENERAL RF EXPOSURE GUIDANCE V06

IEEE STD C95.1-2005

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : , **Date:** Dec. 18, 2015
Lori Chung / Specialist

Approved by : , **Date:** Dec. 18, 2015
May Chen / Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Antenna Type	Connector Type	Antenna Gain(dBi)	Frequency range (MHz to MHz)	Antenna Type
Chain (0)	Microsoft	NA	3	2400~2500	PCB
			3.9	5150~5850	
Chain (1)	Microsoft	NA	4.2	2400~2500	PCB
			3.8	5150~5850	

For 1TX configuration mode: max gain was selected as representative antenna.

2.5 Calculation Result of Maximum Conducted Power

For 1TX Configuration

Frequency Band (MHz)	Max Power (dBm)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (W/cm ²)
2412-2462	25.50	354.813	4.2	20	0.18566	1
5180-5240	23.50	223.872	3.9	20	0.10933	1
5260-5320	23.50	223.872	3.9	20	0.10933	1
5500-5700	23.50	223.872	3.9	20	0.10933	1
5745-5825	21.50	141.254	3.9	20	0.06898	1

NOTE: 1. This power include tune-up tolerance range (1.5dB) that specified by manufacturer.

For 2TX Configuration

Frequency Band (MHz)	Max Power (dBm)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (W/cm ²)
2412-2462	26.51	447.713	4.2	20	0.23428	1
5180-5240	24.51	282.488	3.9	20	0.13795	1
5260-5320	24.51	282.488	3.9	20	0.13795	1
5500-5700	24.51	282.488	3.9	20	0.13795	1
5745-5825	24.51	282.488	3.9	20	0.13795	1

NOTE: 1. This power include tune-up tolerance range (1.5dB) that specified by manufacturer.

--- END ---