


9.3.5 Test Data:

9.3.5.1 Chain A 802.11a 6-dB Bandwidth


Chain A 802.11a 6-dB Bandwidth		
Channel No.	Frequency (MHz)	6-dB Bandwidth (MHz)
144	5720	3.23
149	5745	16.37
157	5785	16.36
165	5825	16.34




Plot 9-131. 6-dB Bandwidth Chain A 802.11a (Ch. 144)



Plot 9-132. 6-dB Bandwidth Chain A 802.11a (Ch. 149)



Plot 9-133. 6-dB Bandwidth Chain A 802.11a (Ch. 157)




Plot 9-134. 6-dB Bandwidth Chain A 802.11a (Ch. 165)

9.3.5.2 Chain B 802.11a 6-dB Bandwidth


Chain B 802.11a 6-dB Bandwidth		
Channel No.	Frequency (MHz)	6-dB Bandwidth (MHz)
144	5720	3.18
149	5745	16.35
157	5785	16.47
165	5825	16.39




Plot 9-135. 6-dB Bandwidth Chain B 802.11a (Ch. 144)



Plot 9-136. 6-dB Bandwidth Chain B 802.11a (Ch. 149)



Plot 9-137. 6-dB Bandwidth Chain B 802.11a (Ch. 157)




Plot 9-138. 6-dB Bandwidth Chain B 802.11a (Ch. 165)

9.3.5.3 Chain A 802.11n HT20 6-dB Bandwidth


Chain A 802.11n HT20 6-dB Bandwidth		
Channel No.	Frequency (MHz)	6-dB Bandwidth (MHz)
144	5720	3.79
149	5745	17.66
157	5785	17.62
165	5825	17.66




Plot 9-139. 6-dB Bandwidth Chain A 802.11n HT20 (Ch. 144)



Plot 9-140. 6-dB Bandwidth Chain A 802.11n HT20 (Ch. 149)




Plot 9-141. 6-dB Bandwidth Chain A 802.11n HT20 (Ch. 157)




Plot 9-142. 6-dB Bandwidth Chain A 802.11n HT20 (Ch. 165)

9.3.5.4 Chain B 802.11n HT20 6-dB Bandwidth


Chain B 802.11n HT20 6-dB Bandwidth		
Channel No.	Frequency (MHz)	6-dB Bandwidth (MHz)
144	5720	3.82
149	5745	17.61
157	5785	17.66
165	5825	17.61




Plot 9-143. 6-dB Bandwidth Chain B 802.11n HT20 (Ch. 144)



Plot 9-144. 6-dB Bandwidth Chain B 802.11n HT20 (Ch. 157)



Plot 9-145. 6-dB Bandwidth Chain B 802.11n HT20 (Ch. 157)




Plot 9-146. 6-dB Bandwidth Chain B 802.11n HT20 (Ch. 165)

9.3.5.5 Chain A 802.11n HT40 6-dB Bandwidth


Chain A 802.11n HT40 6-dB Bandwidth		
Channel No.	Frequency (MHz)	6-dB Bandwidth (MHz)
151	5755	36.34
159	5795	35.69
142	5710	3.14



Plot 9-147. 6-dB Bandwidth Chain A 802.11n HT40 (Ch. 151)




Plot 9-148. 6-dB Bandwidth Chain A 802.11n HT40 (Ch. 159)




Plot 9-149. 6-dB Bandwidth Chain A 802.11n HT40 (Ch. 142)

9.3.5.6 Chain B 802.11n HT40 6-dB Bandwidth


Chain B 802.11n HT40 6-dB Bandwidth		
Channel No.	Frequency (MHz)	6-dB Bandwidth (MHz)
151	5755	35.52
159	5795	35.15
142	5710	2.78



Plot 9-150. 6-dB Bandwidth Chain B 802.11n HT40 (Ch. 151)




Plot 9-151. 6-dB Bandwidth Chain B 802.11n HT40 (Ch. 159)




Plot 9-152. 6-dB Bandwidth Chain B 802.11n HT40 (Ch. 142)

9.3.5.7 Chain A 802.11ac VHT20 6-dB Bandwidth


Chain A 802.11ac VHT20 6-dB Bandwidth		
Channel No.	Frequency (MHz)	6-dB Bandwidth (MHz)
149	5745	17.72
157	5785	17.61
165	5825	17.64
144	5720	3.82




Plot 9-153. 6-dB Bandwidth Chain A 802.11ac VHT20 (Ch. 149)



Plot 9-154. 6-dB Bandwidth Chain A 802.11ac VHT20 (Ch. 157)




Plot 9-155. 6-dB Bandwidth Chain A 802.11ac VHT20 (Ch. 165)




Plot 9-156. 6-dB Bandwidth Chain A 802.11ac VHT20 (Ch. 144)

9.3.5.8 Chain B 802.11ac VHT20 6-dB Bandwidth


Chain B 802.11ac VHT20 6-dB Bandwidth		
Channel No.	Frequency (MHz)	6-dB Bandwidth (MHz)
149	5745	17.59
157	5785	17.61
165	5825	17.33
144	5720	3.82




Plot 9-157. 6-dB Bandwidth Chain B 802.11ac VHT20 (Ch. 149)



Plot 9-158. 6-dB Bandwidth Chain B 802.11ac VHT20 (Ch. 157)




Plot 9-159. 6-dB Bandwidth Chain B 802.11ac VHT20 (Ch. 165)




Plot 9-160. 6-dB Bandwidth Chain B 802.11ac VHT20 (Ch. 144)

9.3.5.9 Chain A 802.11ac VHT40 6-dB Bandwidth


Chain A 802.11ac VHT40 6-dB Bandwidth		
Channel No.	Frequency (MHz)	6-dB Bandwidth (MHz)
151	5755	36.31
159	5795	35.57
142	5710	3.10



Plot 9-161. 6-dB Bandwidth Chain A 802.11ac VHT40 (Ch. 151)




Plot 9-162. 6-dB Bandwidth Chain A 802.11ac VHT40 (Ch. 159)



Plot 9-163. 6-dB Bandwidth Chain A 802.11ac VHT40 (Ch. 142)

9.3.5.10 Chain B 802.11ac VHT40 6-dB Bandwidth

Chain B 802.11ac VHT40 6-dB Bandwidth		
Channel No.	Frequency (MHz)	6-dB Bandwidth (MHz)
151	5755	35.5
159	5795	35.92
142	5710	2.85



Plot 9-164. 6-dB Bandwidth Chain B 802.11ac VHT40 (Ch. 151)




Plot 9-165. 6-dB Bandwidth Chain B 802.11ac VHT40 (Ch. 159)




Plot 9-166. 6-dB Bandwidth Chain B 802.11ac VHT40 (Ch. 142)

9.3.5.11 Chain A 802.11ac VHT80 6-dB Bandwidth

Chain A 802.11ac VHT80 6-dB Bandwidth		
Channel No.	Frequency (MHz)	6-dB Bandwidth (MHz)
155	5775	76.38
138	5690	3.20




Plot 9-167. 6-dB Bandwidth Chain A 802.11ac VHT80 (Ch. 155)




Plot 9-168. 6-dB Bandwidth Chain A 802.11ac VHT80 (Ch. 138)

9.3.5.12 Chain B 802.11ac VHT80 6-dB Bandwidth

Chain B 802.11ac VHT80 6-dB Bandwidth		
Channel No.	Frequency (MHz)	6-dB Bandwidth (MHz)
155	5775	76.43
138	5690	3.20



Plot 9-169. 6-dB Bandwidth Chain B 802.11ac VHT80 (Ch. 155)



Plot 9-170. 6-dB Bandwidth Chain B 802.11ac VHT80 (Ch. 138)

9.4 Maximum Conducted Output Power

9.4.1 Test Requirement:

FCC CFR 47 Rule Part 15.407 (a)

ISED RSS-247 [6.2]

9.4.2 Test Method:

Measurements were performed according to the procedures defined in KDBs 789033- General UNII Test Procedures New Rules v01r03, 662911 D01 Multiple Transmitter Output v02r01, and ANSI C63.10 2013.

Spectrum Analyzer settings:

Average Power:

RBW= 1 MHz

VBW= 3 MHz

Detector = RMS

Trace Mode= Average over 100 traces

Sweep time= Auto

Sweep Point $\geq 2 \times \text{Span} / \text{RBW}$

Span= large enough to encompass the 26-dB Emission Bandwidth or alternatively the 99% Occupied Bandwidth.

Use the band power measurement function to integrate the power over the 26-dB Emission Bandwidth or 99% Occupied Bandwidth.

9.4.3 Limits:

15.407: The maximum conducted output power shall not exceed the limits given the following table for antennas that do not exceed a directional gain > 6dBi:

Band of Operation (MHz)	15.407 Limit
5150 – 5250	24 dBm
5250 – 5350	24dBm or $11 \text{ dBm} + 10 \log (B)^{(1)}$
5470 – 5725	24dBm or $11 \text{ dBm} + 10 \log (B)^{(1)}$
5725 – 5825	30 dBm

Note(1): B is the 26-dB Emission bandwidth of signal in MHz.

RSS-247: The maximum conducted output power and/or EIRP shall not exceed the limits given the following table:

Band of Operation (MHz)	RSS-247 Conducted Output Power Limit	RSS-247 E.I.R.P Limit
5150 – 5250	--	23 dBm or $10 + 10 \log (B)^{(1)}$
5250 – 5350	24 dBm or $11 + 10 \log (B)^{(1)}$	30 dBm or $17 + 10 \log (B)^{(1)}$
5470 – 5725	24 dBm or $11 + 10 \log (B)^{(1)}$	30 dBm or $17 + 10 \log (B)^{(1)}$
5725 – 5825	30 dBm	--

Note(1): B is the 99% Occupied Bandwidth of the signal in MHz.

Conducted Output Power and EIRP measurements for Straddle Channels, 5720, 5710 and 5690, were compared against the 5470 – 5725 MHz band limits which also demonstrates compliance with the 5725 - 5825 MHz band. As the total power complies with the limits for both bands the power within each band also complies with the limits of each band.

Limits for these channels were computed using only the portion of the bandwidth that falls completely within the 5470 – 5725 band using the following formula.

$$B_{Straddle} \text{ MHz} = \frac{B_{Emission} \text{ MHz}}{2} + 5 \text{ MHz},$$

Where,

$B_{Straddle}$ is the bandwidth portion falling completely within the 5470 – 5725 MHz Band.

$B_{Emission}$ is the total measured 26-dB (FCC) or 99% bandwidth (ISED) of the emission in MHz.

e.g. $B_{Straddle} \text{ MHz (for 802.11a 5720MHz)} = \frac{19.2 \text{ MHz}}{2} + 5 \text{ MHz} = 14.6 \text{ MHz}$
 $Limit_{FCC_15.407} \text{ dBm} = 11 \text{ dBm} + 10 \times \log_{10} 14.6 = 22.64 \text{ dBm}$

Straddle Channel Conducted Output Power and EIRP Limits						
Straddle Channel	Mode	Measured Min 26-dB Bandwidth (MHz)	Measured Min 99% Occupied Bandwidth (MHz)	15.407 Conducted Output Power Limit (dBm)	RSS-247 Conducted Output Power Limit (dBm)	RSS-247 E.I.R.P Limit (dBm)
5720	802.11a	19.20	16.51	22.64	22.22	28.22
5720	802.11n HT20	19.87	17.52	22.74	22.39	28.39
5720	802.11ac VHT20	19.86	17.60	22.74	22.40	28.40
5710	802.11n HT40	39.69	36.13	24	24	30
5710	802.11ac VHT40	40.08	36.08	24	24	30
5690	802.11ac VHT80	81.00	75.92	24	24	30

9.4.4 Test Results:

Pass. See Section 9.5.5 for test data.

9.5 Power Spectral Density

9.5.1 Test Requirement:

FCC CFR 47 Rule Part 15.407 (a)
ISED RSS-247 [6.2]

9.5.2 Test Method:

Measurements were performed according to the procedures defined in KDBs 789033- General UNII Test Procedures New Rules v01r03, 662911 D01 Multiple Transmitter Output v02r01, and ANSI C63.10 2013.

Spectrum Analyzer settings for devices operating in the bands 5.15 – 5.25 GHz, 5.25 – 5.35GHz, and 5.47 – 5.725GHz:

RBW= 1 MHz

VBW= 3 MHz

Detector = RMS

Trace Mode= Average over 100 traces

Sweep time= Auto

Sweep Point $\geq 2 \times \text{Span} / \text{RBW}$

Span= large enough to encompass the 26-dB Emission Bandwidth or alternatively the 99% Occupied Bandwidth. Use the peak marker function to identify the Maximum Power Spectral Density

Spectrum Analyzer settings for devices operating in the bands 5.725 – 5.85 GHz:

RBW= 100 kHz

VBW= 300 kHz

Detector = RMS

Trace Mode= Average over 100 traces

Sweep time= Auto

Sweep Point $\geq 2 \times \text{Span} / \text{RBW}$

Span= large enough to encompass the 26-dB Emission Bandwidth or alternatively the 99% Occupied Bandwidth. Use the peak marker function to identify the Maximum Power Spectral Density

Offset is added if measurements are performed using a reduced resolution bandwidth 100 kHz, add $10 \times \log(500\text{kHz} / \text{RBW USED})$ to the measured result.

9.5.3 Limits:

15.407: The Maximum Power Spectral Density shall not exceed the limits given the following table for antennas that do not exceed a directional gain > 6dBi:

Band of Operation (MHz)	15.407 Limits
5150 – 5250	11dBm/MHz
5250 – 5350	11dBm/MHz
5470 – 5725	11dBm/MHz
5725 – 5825	30dBm/500kHz

Band of Operation (MHz)	RSS-247 Limits
5150 – 5250	10dBm/MHz e.i.r.p.
5250 – 5350	11dBm/MHz
5470 – 5725	11dBm/MHz
5725 – 5825	30dBm/500kHz

For antenna gains >6dBi, the PSD limits are reduced by the amount it exceeds 6dBi.

9.5.4 Test Results:

Pass.

PSD measurements for Straddle Channels, 5720, 5710 and 5690, were compared against the 5470 – 5725 MHz band limits demonstrating compliance with the less stringent 5725 - 5825 MHz band limits as well.

9.5.5 Test Data

9.5.5.1 Chain A+B 802.11a Maximum Conducted Output Power

Chain A+B 802.11a Maximum Conducted Output Power								
Chan. No.	Freq. (MHz)	Chain A (dBm)	Chain B (dBm)	Total Power (dBm)	15.407 Limit (dBm)	RSS-247 Limit (dBm)	15.407 Margin (dB)	RSS-247 Margin (dB)
36	5180	10.32	11.31	13.88	24.00	--	-10.12	--
44	5220	10.46	11.36	13.97	24.00	--	-10.03	--
48	5240	10.53	11.72	14.21	24.00	--	-9.79	--
52	5260	11.44	12.95	15.30	23.85	23.17	-8.55	-7.87
60	5300	11.56	13.03	15.40	23.85	23.18	-8.46	-7.78
64	5320	11.59	12.76	15.25	23.87	23.18	-8.61	-7.92
100	5500	13.28	13.49	16.43	23.88	23.18	-7.45	-6.75
116	5580	13.56	13.09	16.37	23.87	23.18	-7.50	-6.81
140	5700	13.51	12.95	16.28	23.89	23.18	-7.61	-6.90
144	5720	13.41	13.13	16.31	22.64	22.22	-6.33	-5.91
149	5745	12.31	11.78	15.09	30.00	30.00	-14.91	-14.91
157	5785	12.26	12.33	15.34	30.00	30.00	-14.66	-14.66
165	5825	12.09	12.97	15.59	30.00	30.00	-14.41	-14.41


Chain A+B 802.11a E.I.R.P						
Channel No.	Frequency (MHz)	Total Power (dBm)	Antenna Gain (dBi)	E.I.R.P (dBm)	RSS-247 E.I.R.P Limit (dBm)	RSS-247 E.I.R.P. Margin (dB)
36	5180	13.88	3.30	17.18	22.18	-5.00
44	5220	13.97	3.30	17.27	22.18	-4.91
48	5240	14.21	3.30	17.50	22.18	-4.68
52	5260	15.30	3.30	18.60	29.17	-10.58
60	5300	15.40	3.30	18.69	29.18	-10.48
64	5320	15.25	3.30	18.55	29.18	-10.62
100	5500	16.43	3.41	19.84	29.18	-9.34
116	5580	16.37	3.41	19.78	29.18	-9.40
140	5700	16.28	3.41	19.69	29.18	-9.49
144	5720	16.31	3.41	19.72	28.22	-8.5
149	5745	15.09	2.39	17.49	--	--
157	5785	15.34	2.39	17.73	--	--
165	5825	15.59	2.39	17.99	--	--

9.5.5.2 Chain A+B 802.11a Maximum Power Spectral Density


UNII-1 Chain A+B 802.11a Maximum Power Spectral Density/MHz										
Chan. No.	Freq. (MHz)	Chain A (dBm)	Chain B (dBm)	Total PSD $\left(\frac{dBm}{MHz}\right)$	Total Ant. Gain (dBi)	Total EIRP PSD $\left(\frac{dBm}{MHz}\right)$	15.407 Limit $\left(\frac{dBm}{MHz}\right)$	RSS-247 EIRP PSD Limit $\left(\frac{dBm}{MHz}\right)$	15.407 Margin (dB)	RSS-247 Margin (dB)
36	5180	-0.24	0.59	3.23	6.28	9.51	10.72	10.00	-7.49	-0.49
44	5220	-0.28	0.66	3.26	6.28	9.54	10.72	10.00	-7.46	-0.46
48	5240	-0.28	0.96	3.42	6.28	9.70	10.72	10.00	-7.30	-0.30

UNII-2A and UNII-2C Chain A+B 802.11a Maximum Power Spectral Density/MHz								
Channel No.	Frequency (MHz)	Chain A (dBm)	Chain B (dBm)	Total PSD $(\frac{dBm}{MHz})$	15.407 Limit $(\frac{dBm}{MHz})$	RSS-247 Limit $(\frac{dBm}{MHz})$	15.407 Margin (dB)	RSS-247 Margin (dB)
52	5260	0.74	2.09	4.51	10.72	11.00	-6.21	-6.49
60	5300	0.79	2.30	4.65	10.72	11.00	-6.07	-6.35
64	5320	0.84	2.08	4.54	10.72	11.00	-6.18	-6.46
100	5500	2.56	2.82	5.73	10.59	11.00	-4.85	-5.27
116	5580	2.70	2.43	5.61	10.59	11.00	-4.98	-5.39
140	5700	2.75	2.21	5.53	10.59	11.00	-5.06	-5.47
144	5720	2.54	2.31	5.47	10.59	11.00	-5.12	-5.53


UNII-3 Chain A+B 802.11a Maximum Power Spectral Density/500kHz								
Chan. No.	Freq. (MHz)	Chain A (dBm)	Chain B (dBm)	Total PSD $\left(\frac{dBm}{500 kHz}\right)$	15.407 Limit $\left(\frac{dBm}{500 kHz}\right)$	RSS-247 Limit $\left(\frac{dBm}{500 kHz}\right)$	15.407 Margin (dB)	RSS-247 Margin (dB)
149	5745	-0.15	-0.89	2.54	30.00	30.00	-27.46	-27.46
157	5785	0.11	0.13	3.16	30.00	30.00	-26.84	-26.84
165	5825	0.09	0.72	3.46	30.00	30.00	-26.54	-26.54
144	5720	-0.09	-0.23	2.88	30.00	30.00	-27.12	-27.12




Plot 9-171. Maximum Conducted Output Power and PSD Chain A 802.11a (Ch. 36)




Plot 9-172. Maximum Conducted Output Power and PSD Chain A 802.11a (Ch. 44)




Plot 9-173. Maximum Conducted Output Power and PSD Chain A 802.11a (Ch. 48)




Plot 9-174. Maximum Conducted Output Power and PSD Chain A 802.11a (Ch. 52)




Plot 9-175. Maximum Conducted Output Power and PSD Chain A 802.11a (Ch. 60)




Plot 9-176. Maximum Conducted Output Power and PSD Chain A 802.11a (Ch. 64)




Plot 9-177. Maximum Conducted Output Power and PSD Chain A 802.11a (Ch. 100)




Plot 9-178. Maximum Conducted Output Power and PSD Chain A 802.11a (Ch. 116)




Plot 9-179. Maximum Conducted Output Power and PSD Chain A 802.11a (Ch. 140)




Plot 9-180. Maximum Conducted Output Power and PSD Chain A 802.11a (Ch. 144)




Plot 9-181. Maximum Conducted Output Power Chain A 802.11a (Ch. 149)




Plot 9-182. Maximum Conducted Output Power Chain A 802.11a (Ch. 157)




Plot 9-183. Maximum Conducted Output Power Chain A 802.11a (Ch. 165)




Plot 9-184. Maximum Power Spectral Density Chain A 802.11a (Ch. 149)




Plot 9-185. Maximum Power Spectral Density Chain A 802.11a (Ch. 157)




Plot 9-186. Maximum Power Spectral Density Chain A 802.11a (Ch. 165)




Plot 9-187. Maximum Power Spectral Density Chain A 802.11a (Ch. 144)




Plot 9-188. Maximum Conducted Output Power and PSD Chain B 802.11a (Ch. 36)




Plot 9-189. Maximum Conducted Output Power and PSD Chain B 802.11a (Ch. 44)




Plot 9-190. Maximum Conducted Output Power and PSD Chain B 802.11a (Ch. 48)




Plot 9-191. Maximum Conducted Output Power and PSD Chain B 802.11a (Ch. 52)




Plot 9-192. Maximum Conducted Output Power and PSD Chain B 802.11a (Ch. 60)




Plot 9-193. Maximum Conducted Output Power and PSD Chain B 802.11a (Ch. 64)




Plot 9-194. Maximum Conducted Output Power and PSD Chain B 802.11a (Ch. 100)



Plot 9-195. Maximum Conducted Output Power and PSD Chain B 802.11a (Ch. 116)



Plot 9-196. Maximum Conducted Output Power and PSD Chain B 802.11a (Ch. 140)



Plot 9-197. Maximum Conducted Output Power and PSD Chain B 802.11a (Ch. 144)