RETLIF TESTING LABORATORIES

TABULAR DATA SHEET

TEST METHOD:	**Frequency Stability (DC Input Power 85% TO 115%)**		
CUSTOMER:	Samson Technologies	JOB No.:	R-8512-4
TEST SAMPLE:	UHF Wireless Transmitter		
MODEL No.:	AL1	SERIAL No.:	79U400001 FCC ID: CCRAL1M
TEST SPECIFICATION:	FCC Part 74, Subpart H;Experimental Radio, Auxiliary Special Broadcast, & other Program Distributional Services, Subpart H; Low Power Auxiliary Stations.	PARAGRAPH:	74.861 (e) (4)
OPERATING MODE:	Transmitting on channel U4 (803.75 MHz)		
TECHNICIAN:	N. Dragotta	DATE:	April 27, 2000
NOTES:	Tolerance: +/- 0.005% (+/- .040188 MHz) Temperature: 23° C. Humidity: 29%		

Channel	TRANSMIT FREQUENCY	INPUT VOLTAGE	INPUT VOLTAGE		LOWER LIMIT	METER READING	UPPER LIMIT	Pass / Fail
	MHz	%	VDC		MHz	MHz	MHz	
04	803.75	85	1.28		803.79	803.7735	803.71	Pass
04	803.75	100	1.50		803.79	803.7737	803.71	Pass
04	803.75	115	1.73		803.79	803.7737	803.71	Pass
04	803.75	Battery End Point	**1.15		803.79	803.7735	803.71	Pass

The test sample performed within the limits specified by the above listed specification.

** = At this input voltage, the low battery LED on the unit illuminated.