

**HONEYWELL SECURITY & CUSTOM ELECTRONICS**

165 EILEEN WAY

SYOSSET, NY 11791

EXHIBIT 5-3

FCC ID # CFS8DL5800RL-2

Date : 6/11/2007

Tested by :Y. Mohammed

Approved by :K.Addy

Test Sample (model) : 5800RL-2

Test method: ANSI C63.4 - 2003

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20 ]]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	H	76.70	1.2	14.78	43052.7	10.0%	4305.3	7292
690	H	45.00	1.8	19.10	1972.4	10.0%	197.2	729
1035	H	40.00	2.2	22.70	1757.9	10.0%	175.8	500
1380	H	38.00	2.5	24.96	1875.0	10.0%	187.5	500
1725	H	44.00	2.8	27.55	5218.0	10.0%	521.8	729
2070	H	44.00	3.0	29.52	6698.8	10.0%	669.9	729
2415	H	37.00	3.3	31.13	3728.2	10.0%	372.8	729
2760	H	36.00	3.7	31.50	3630.8	10.0%	363.1	500
3105	H	33.00	4.1	31.61	2725.8	10.0%	272.6	729
3450	H	36.00	4.4	32.22	4275.6	10.0%	427.6	729
4000			CABLE "A"	BICONILOG				