HONEYWELL SECURITY & CUSTOM ELECTRONICS **REV 10-17-2011-H**
2 Corporate Center Drive
Melville, NY 11747 **EXHIBIT 5-3** **FCC ID: CFS8DL 5800SS1**

Date : 29-Nov 2011 Tested by: G. BARBATO Approved by: K. Eskildsen
Test Sample (model): 5800SS1
Test method: ANSI C63.4 - 2003
Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 8

Notes: (1) Fo: 344.94
(2) Detector = Peak
(3) Frequency range scanned to 4 GHz.
(Emissions not reported were more than 20dB below the specified unit).
[(Meter reading + Cable/Amp factor + Antenna factor) / 20)]
(4) Conv. Reading = 10
(5) Corr. Reading = Conv. Reading X Duty Cycle
(6) Six Highest Emissions Recorded

PRESCAN: SENSE / UUT:	EL (cm):	AZ (deg):	Meter Reading (dB uV):
V/V	145.0	110.0	62.44
H/V	100.0	0/360	57.71
V/H	147.3	100.0	49.51
H/H	100.0	90.0	61.47
V/O	161.4	220.0	62.00
H/O	147.7	0/360	56.35

Freq. (MHz):	Sense Antenna Polarity (V/H):	ORENTATION OF THE UUT (V,H,O,):	Meter Reading (dB uV):	Cable/Amp Factor (dB):	Antenna Factor (dB/m):	Conv. Reading (uV/M):	Duty Cycle (%):	Corr. Reading (uV/M):	Limit @ 3M (uV/M):
344.94	V	V	62.44	2.5	15.28	10,256.5	10.0%	1025.7	7,289
689.88	V	V	38.08	3.7	19.89	1,214.8	10.0%	121.5	729
1034.82	V	V	31.46	4.7	24.12	1,032.8	10.0%	103.3	500
1379.76	V	V	21.27	5.6	26.06	443.6	10.0%	44.4	500
1724.70	V	V	27.44	6.3	28.54	1,294.2	10.0%	129.4	729
2069.64	V	V	25.22	7.3	31.75	1,625.5	10.0%	162.6	729
2414.58	V	V	24.54	8.1	31.79	1,657.7	10.0%	165.8	729
2759.52	V	V	25.04	8.6	31.54	1,817.6	10.0%	181.8	500
3104.46	V	V	25.21	9.1	31.95	2,058.3	10.0%	205.8	729
3449.40	V	V	24.55	10.0	33.70	2,576.3	10.0%	257.6	729
4000				LAST CAL 17 OCT 11 CABLE D	LAST CAL 21-AUG-11 BICONILOG S/N:00045682				