

HONEYWELL SECURITY & CUSTOM ELECTRONICS**165 EILEEN WAY****SYOSSET, NY 11791****EXHIBIT 5-3****FCC ID # CFS8DL5802-1**

Date : 4/20/2005

Tested by :Y. Mohammed

Approved by :K.Addy

Test Sample (model) : 5802

Test method: ANSI C63.4 - 1992

Test specification: FCC Part 15, Sub-part C

Notes: (1) Fo = 345MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"	BICONILOG				729
345	H	81.10	1.3	14.78	72277.0	10.0%	7227.7	7292
690	H	46.00	1.7	19.10	2187.8	10.0%	218.8	729
1035	H	46.00	2.3	22.70	3548.1	10.0%	354.8	500
1380	H	37.00	3.0	25.10	1798.9	10.0%	179.9	500
1725	H	32.00	3.3	27.55	1388.4	10.0%	138.8	729
2070	H	31.00	3.8	29.42	1625.5	10.0%	162.6	729
2415	H	30.00	4.1	31.85	1983.8	10.0%	198.4	729
2760	H	30.00	4.1	32.20	2065.4	10.0%	206.5	729
3105	H	30.00	5.7	31.75	2357.8	10.0%	235.8	729
3450	H	30.00	6.2	32.28	2654.6	10.0%	265.5	729
4000			CABLE "A"	BICONILOG				