

Date : 02/08/08 Tested by :Azadeh S Approved by :K.Addy

Test Sample (model) : 5802AP

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 7

Notes: (1) Fo = 315MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
30			CABLE "A"+"B"	03/12/2007 BICONILOG S/N:00029390				604.2
315	H	58.59	2.5	13.70	5489.1	10.0%	548.9	6042.0
630	H	41.09	3.5	18.60	1443.8	10.0%	144.4	604.2
945	H	38.09	4.6	21.80	1676.9	10.0%	167.7	604.2
1260	H	41.59	5.3	25.00	3931.0	10.0%	393.1	500.0
1575	H	30.29	6.1	27.10	1494.5	10.0%	149.5	604.2
1890	H	28.79	6.6	29.10	1676.9	10.0%	167.7	604.2
2205	H	20.19	7.4	30.90	840.4	10.0%	84.0	500.0
2520	H	23.79	7.8	32.50	1601.4	10.0%	160.1	604.2
2835	H	20.20	8.8	32.60	1202.3	10.0%	120.2	500.0
3150	H	18.30	9.1	32.60	1000.0	10.0%	100.0	604.2
4000			CABLE "A"+"B"	03/12/2007 BICONILOG S/N:00029390				