

Date : 03/12/2009 Tested by : G. Barbato Approved by : K. Eskildsen

Test Sample (model) : 5881-6

Test method: ANSI C63.4 - 2004

Test specification: FCC Part 15, Sub-part C and RSS 210 , Issue 7

Notes: (1) LO = 355.7MHz. (2) Detector = Peak (3) Frequency range scanned to 4 GHz.

Emissions not reported were more than 20dB below the specified unit.

[(Meter reading + Cable/Amp factor + Antenna factor) / 20]]

(4) Conv. Reading = 10

(5) Corr. Reading = Conv. Reading X Duty Cycle

(6) Six Highest Emissions Recorded

Freq. (MHz)	Antenna Polarity (V/H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/m)	Conv. Reading (uV/M)	Duty Cycle (%)	Corr. Reading (uV/M)	Limit @ 3M (uV/M)
			LAST CAL 04 Aug 08 CABLE C	LAST CAL 02 May 08 BICONILOG S/N:00045682				
32.20	v	19.87	0.9	16.69	74.6	100.0%	74.6	100
40.26	v	17.56	0.9	17.53	63.0	100.0%	63.0	100
47.26	v	15.23	0.9	16.22	41.4	100.0%	41.4	100
48.31	v	13.87	1.0	16.03	35.1	100.0%	35.1	100
59.58	v	9.87	1.0	13.39	16.3	100.0%	16.3	100
355.7	v	10.17	2.3	14.84	23.2	100.0%	23.2	200
			LAST CAL 04 Aug 08 CABLE C	LAST CAL 02 May 08 BICONILOG S/N:00045682				