

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

FCC ID# CFS8DL6150RF

DATE: 6/28/2000 TESTED BY: J. Fitzgerald APPROVED BY: Ken Addy

ADEMCO 6150RF (TRANSMITTER)

TEST SAMPLE (model): _____

TEST METHOD: ANSI C63.4-1992

TEST SPECIFICATION: FCC PART 15, SUBPART C.

NOTES: 1) Fo= 345 MHZ

2) DETECTOR = PEAK.

3) FREQUENCY RANGE SCANNED TO 4 GHz.

$$4) \text{ CONVERTED READING} = 10 \left[\frac{(\text{METER READING} + \text{CABLE /AMP FACTOR} + \text{ANTENNA FACTOR})}{20} \right]$$

5) CORRECTED READING = CONVERTED READING X DUTY CYCLE

6) SIX HIGHEST EMISSIONS RECORDED.

Frequency (MHz)	Antenna Polarity (V-H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Converted Reading (uV/M)	Duty Cycle (%)	Corrected Reading (uV/M)	Limit @ 3 Meter (uV/M)
30								729
345	H	78.95	1.4	16	65313	10	6531.3	7292
690	H	41.75	1.8	21.1	1708	10	170.8	729
1035	V	45.40	2.1	25.2	4315.1	10	431.5	500
1380	V	38.72	2.5	28.8	3169.5	10	316.95	500
1725	V	35.50	3.0	31.2	3055	10	305.5	729
4000								

NOTES: