

ALARM DEVICE MANUFACTURING COMPANY
165 EILEEN WAY
SYOSSET, NY 11791

FCC ID# CFS8DL6150RF

DATE: 6/28/2000

TESTED BY: J. Fitzgerald

APPROVED BY: Ken Addy

ADEMC0 6150RF (RECEIVER)

TEST SAMPLE (model): _____

TEST METHOD: ANSI C63.4-1992

TEST SPECIFICATION: FCC PART 15, SUBPART C.

NOTES: 1) Fc= 345 MHZ

2) DETECTOR = PEAK.

3) FREQUENCY RANGE SCANNED TO 4 GHz.

$$4) \text{ CONVERTED READING} = 10 \left[\frac{(\text{METER READING} + \text{CABLE /AMP FACTOR} + \text{ANTENNA FACTOR})}{20} \right]$$

5) CORRECTED READING = CONVERTED READING X DUTY CYCLE

6) SIX HIGHEST EMISSIONS RECORDED.

Frequency (MHz)	Antenna Polarity (V-H)	Meter Reading (dB uV)	Cable/Amp Factor (dB)	Antenna Factor (dB/M)	Converted Reading (uV/M)	Duty Cycle (%)	Corrected Reading (uV/M)	Limit @ 3 Meter (uV/M)
30						NONE		
334.3	H	13.3	1.4	16	43.15	NONE	43.15	200
668.5	H	4.4	1.8	21.1	23.17	NONE	23.17	200
1002.9	H	1.9	2.1	25.2	28.84	NONE	28.84	500
1337.2	H	0.61	2.5	28.8	39.40	NONE	39.40	500
1671.5	H	0.2	3.0	31.2	52.48	NONE	52.48	500
4000						NONE		

NOTES: