



## TEST DATA REPORT

Test Data Number: 102460119MIN-001

Project Number: G102460119

Testing performed on the  
LSD500

to

47 CFR Part 15.247:2015 / RSS-247, Issue 1:2015  
Spurious Radiated Emissions

47 CFR, Part 15:2015, §15.109, Class B / ICES-003, Issue 6:2016

For

Honeywell International Inc.

Test Performed by:  
Intertek Testing Services NA, Inc.  
7250 Hudson Blvd., Suite 100  
Oakdale, MN 55128 USA

Test Authorized by:  
Honeywell International Inc.  
2 Corporate Center Drive  
Melville, NY 11747 USA

Prepared by: Clay Huff  
Clay Huff

Reviewed by: Norman Shpilsher  
Norman Shpilsher

Date of issue: February 10, 2016

*This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.*



**TABLE OF CONTENTS**

- 1.0 GENERAL DESCRIPTION..... 3**
  - 1.1 Product Description; Test Facility.....4
  - 1.2 EUT Configuration.....5
  - 1.3 Measurement uncertainty.....6
  - 1.4 Field Strength Calculation .....6
- 2.0 TEST SUMMARY..... 7**
- 3.0 TEST CONDITIONS AND RESULTS..... 8**
  - 3.1 Radiated spurious emissions .....8
  - 3.2 Receiver/digital device radiated emissions .....43
- 4.0 TEST EQUIPMENT..... 50**
- 5.0 REVISION HISTORY..... 51**



## 1.0 GENERAL DESCRIPTION

<b>Model:</b>	LSD500
<b>Type of EUT:</b>	Wireless Smoke Alarm
<b>Sample ID:</b>	MEL-024 and MEL-025
<b>Company:</b>	Honeywell International Inc.
<b>Customer:</b>	Mr. Andrew Roussin
<b>Address:</b>	2 Corporate Center Drive Melville, NY 11747 USA
<b>Phone:</b>	(516) 577-5935
<b>e-mail:</b>	<a href="mailto:AndrewRoussin@Honeywell.com">AndrewRoussin@Honeywell.com</a>
<b>Date Sample Submitted:</b>	February 1, 2016
<b>Test Work Started:</b>	February 1, 2016
<b>Test Work Completed:</b>	February 8, 2016
<b>Test Sample Conditions:</b>	<input type="checkbox"/> Damaged <input type="checkbox"/> Poor (Usable) <input checked="" type="checkbox"/> Good



1.1 Product Description; Test Facility

<b>Product Description:</b>	Transceiver
<b>Transmitter power configuration:</b>	<input checked="" type="checkbox"/> Internal battery <input type="checkbox"/> External power source <input type="checkbox"/> 120VAC <input type="checkbox"/> 230VAC <input type="checkbox"/> 400VAC <input type="checkbox"/> █ VDC <input type="checkbox"/> Other: █ █ Amp. <input type="checkbox"/> 50Hz <input type="checkbox"/> 60Hz
<b>Permitted Band of Operation:</b>	2400 – 2483.5MHz
<b>Band of Operation:</b>	2405 – 2475MHz
<b>Test Facility Accreditation:</b>	A2LA (Certificate No. 1427.01)
<b>Test Methodology:</b>	Measurements performed according to the procedures in ANSI C63.10-2013

## 1.2 EUT Configuration

The equipment under test was operated during the measurement under the following conditions:

- Continuous (see details below)
- Test program (customer specific)
- 

### Operating modes of the EUT:

No.	Description
1	The both samples MEL-024 and MEL-025 were tested in continuous transmitting mode at channel 11 (2405MHz), channel 19 (2445MHz), and channel 25 (2475MHz), and in receive mode. Unit MEL-024 was set to operate with Antenna 1; Unit MEL-025 was set to operate with Antenna 2.

### Cables:

No.	Type	Length	Designation	Note
	None			

### Support equipment/Services:

No.	Item	Description
	None	

**General notes:** The both samples MEL-024 and MEL-025 were tested individually with fresh batteries.

---

### 1.3 Measurement uncertainty

The expanded uncertainty ( $k = 2$ ) for radiated emissions from 30 to 1000 MHz has been determined to be:  $\pm 4$  dB at 10m and  $\pm 5.4$  dB at 3m

The expanded uncertainty ( $k = 2$ ) for conducted emissions from 150 kHz to 30 MHz has been determined to be:  $\pm 2.6$  dB

### 1.4 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured emissions reading on the EMI Receiver.

The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

Where: FS = Field Strength in dB( $\mu$ V/m)

RA = Receiver Amplitude in dB( $\mu$ V)

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB( $m^{-1}$ )

AG = Amplifier Gain in dB

Assume a receiver reading of 48.1 dB( $\mu$ V) is obtained. The antenna factor of 7.4 dB( $m^{-1}$ ) and cable factor of 1.6 dB is added and amplifier gain of 16.0 dB is subtracted giving field strength of 41.1 dB( $\mu$ V/m).

$$RA = 48.1 \text{ dB}(\mu\text{V})$$

$$AF = 7.4 \text{ dB}(m^{-1})$$

$$CF = 1.6 \text{ dB}$$

$$AG = 16.0 \text{ dB}$$

$$FS = RA + AF + CF - AG$$

$$FS = 48.1 + 7.4 + 1.6 - 16.0$$

$$FS = 41.1 \text{ dB}(\mu\text{V}/\text{m})$$



## 2.0 TEST SUMMARY

Referring to the performance criteria and the operating mode during the tests specified in this report, the equipment complies with the requirements according to the following standards.

TEST SPECIFICATION	TEST PARAMETERS	RESULT
15.247(d) / RSS-247 5.5	Radiated spurious emissions	Pass
15.109 / ICES-003	Receiver/digital device radiated emissions	Pass



### 3.0 TEST CONDITIONS AND RESULTS

#### 3.1 Radiated spurious emissions

**Test location:**             OATS             Anechoic Chamber     Other

**Test result:**            **Pass**

**Max. Margin:**            13.3dB below the limits for Spurious Emissions

**Max. Margin:**            11.3dB below the limits for Bandedge Emissions

**Notes:**            The Radiated Emissions test was performed in the Anechoic chamber at 3m measurement distance.  
                          Graphs 3.1.1 to 3.1.60 show peak of emissions, limits lines show the Average limits.  
                          Tables 3.1.1 and 3.1.3 show Peak value of spurious emissions which are above the Average limits.  
                          Tables 3.1.2 and 3.1.4 show Average value of spurious emissions falling in the restricted band of operation per FCC Part 15.205.

---



<b>Date:</b>	February 1 – 3, 2016	<b>Result: Pass</b>
<b>Tested by:</b>	Clay Huff	
<b>Standard:</b>	FCC part 15.247(d)	
<b>Test Point:</b>	Enclosure Sample MEL-024	
<b>Operation mode:</b>	See page 5	
<b>Environmental Conditions:</b>	22.2°C; 23.4%(RH); 98kPa	
<b>Equipment Verification:</b>	<input checked="" type="checkbox"/>	
<b>Note:</b>	Sample MEL-024, Peak readings	

**Table 3.1.1**


Frequency MHz	Antenna		Ant. CF dB1/m	Cable loss dB	Pre-amp Gain (dB)	Peak readings dBµV	Total @ 3m dBµV/m	Limit dBµV/m	Margin dB	Comments
	Polarity	Hts(cm)								
Channel 11 . 2405 MHz										
7215.00	V	127	35.7	5.3	40.9	60.8	60.9	74.0	-13.1	
7215.00	H	108	35.7	5.3	40.9	57.8	57.9	74.0	-16.1	
12026.70	H	100	39.2	6.8	40.5	49.1	54.7	74.0	-19.3	
Channel 19 . 2445 MHz										
7330.00	V	105	36.0	5.3	40.8	55.4	55.9	74.0	-18.1	
7330.00	H	107	36.0	5.3	40.8	55.2	55.7	74.0	-18.3	
Channel 25 . 2475 MHz										
7430.00	V	100	36.2	5.4	40.7	54.2	55.1	74.0	-18.9	
7430.00	H	100	36.2	5.4	40.7	57.3	58.2	74.0	-15.8	




<b>Date:</b>	February 1 – 3, 2016	<b>Result: Pass</b>
<b>Tested by:</b>	Clay Huff	
<b>Standard:</b>	FCC part 15.247(d)	
<b>Test Point:</b>	Enclosure Sample MEL-024	
<b>Operation mode:</b>	See page 5	
<b>Environmental Conditions:</b>	22.2°C; 23.4%(RH); 98kPa	
<b>Equipment Verification:</b>	<input checked="" type="checkbox"/>	
<b>Note:</b>	Sample MEL-024, Average value	

**Table 3.1.2**


Frequency MHz	Antenna		Ant. CF dB1/m	Cable loss dB	Pre-amp Gain (dB)	AVG Reading dBµV	Total @ 3m dBµV/m	Limit dBµV/m	Margin dB	Comments
	Polarity	Hts(cm)								
Channel 11 . 2405 MHz										
2390.00	V	105	28.1	2.9	0.0	10.7	41.7	54.0	-12.3	Bandedge
2390.00	H	110	28.1	2.9	0.0	10.5	41.5	54.0	-12.5	Bandedge
7215.00	V	127	35.7	5.3	40.9	32.5	32.6	54.0	-21.4	
14010.00	V	100	41.7	7.1	40.5	21.2	29.6	54.0	-24.4	
7215.00	H	108	35.7	5.3	40.9	40.6	40.7	54.0	-13.3	
9620.00	H	100	38.0	6.0	40.5	18.2	21.7	54.0	-32.2	
14430.00	H	100	42.3	7.2	40.4	20.5	29.7	54.0	-24.3	
Channel 19 . 2445 MHz										
4890.00	V	100	33.0	4.1	41.8	32.3	27.6	54.0	-26.4	
7330.00	V	105	36.0	5.3	40.8	36.2	36.7	54.0	-17.3	
12230.00	V	105	39.0	6.9	40.6	22.3	27.5	54.0	-26.4	
7330.00	H	107	36.0	5.3	40.8	30.3	30.8	54.0	-23.2	
Channel 25 . 2475 MHz										
2483.50	V	130	28.4	2.9	0.0	11.3	42.6	54.0	-11.4	Bandedge
2483.50	H	110	28.4	2.9	0.0	10.7	42.0	54.0	-12.0	Bandedge
4950.00	V	100	33.1	4.1	41.7	31.3	26.8	54.0	-27.2	
7430.00	V	100	36.2	5.4	40.7	32.3	33.2	54.0	-20.8	
7430.00	H	112	36.2	5.4	40.7	28.9	29.8	54.0	-24.2	




Graph 3.1.1




Graph 3.1.2




Graph 3.1.3




Graph 3.1.4




Graph 3.1.5




Graph 3.1.6




Graph 3.1.7




Graph 3.1.8




Graph 3.1.9




Graph 3.1.10




Graph 3.1.11




Graph 3.1.12




Graph 3.1.13




Graph 3.1.14




Graph 3.1.15




Graph 3.1.16




Graph 3.1.17




Graph 3.1.18




Graph 3.1.19




Graph 3.1.20




Graph 3.1.21




Graph 3.1.22




Graph 3.1.23




Graph 3.1.24




Graph 3.1.25




Graph 3.1.26




Graph 3.1.27



Graph 3.1.28



Graph 3.1.29



Graph 3.1.30



<b>Date:</b>	February 3 – 5, 2016	<b>Result: Pass</b>
<b>Tested by:</b>	Clay Huff	
<b>Standard:</b>	FCC part 15.247(d)	
<b>Test Point:</b>	Enclosure Sample MEL-024	
<b>Operation mode:</b>	See page 5	
<b>Environmental Conditions:</b>	22.2°C; 23.4%(RH); 98kPa	
<b>Equipment Verification:</b>	<input checked="" type="checkbox"/>	
<b>Note:</b>	Sample MEL-025, Peak readings	

**Table 3.1.3**


Frequency MHz	Antenna		Ant. CF dB1/m	Cable loss dB	Pre-amp Gain (dB)	Peak readings dBµV	Total @ 3m dBµV/m	Limit dBµV/m	Margin dB	Comments
	Polarity	Hts(cm)								
Channel 11 . 2405 MHz										
7210.00	V	105	35.7	5.3	41.0	58.2	58.2	74.0	-15.8	
7210.00	H	100	35.7	5.3	41.0	58.4	58.4	74.0	-15.6	
12022.00	H	100	39.2	6.8	40.4	49.4	54.9	74.0	-19.1	
Channel 19 . 2445 MHz										
7330.00	V	100	36.0	5.3	40.8	59.8	60.4	74.0	-13.6	
7330.00	H	132	36.0	5.3	40.8	59.1	59.6	74.0	-14.4	
12220.00	H	100	39.0	6.9	40.6	51.5	56.8	74.0	-17.2	
Channel 25 . 2475 MHz										
7430.00	V	125	36.2	5.4	40.7	56.3	57.3	74.0	-16.7	
7430.00	H	110	36.2	5.4	40.7	58.1	59.0	74.0	-15.0	




<b>Date:</b>	February 3 – 5, 2016	<b>Result: Pass</b>
<b>Tested by:</b>	Clay Huff	
<b>Standard:</b>	FCC part 15.247(d)	
<b>Test Point:</b>	Enclosure Sample MEL-024	
<b>Operation mode:</b>	See page 5	
<b>Environmental Conditions:</b>	22.2°C; 23.4%(RH); 98kPa	
<b>Equipment Verification:</b>	<input checked="" type="checkbox"/>	
<b>Note:</b>	Sample MEL-025, Average value	

**Table 3.1.4**


Frequency MHz	Antenna		Ant. CF dB1/m	Cable loss dB	Pre-amp Gain (dB)	AVG Reading dBµV	Total @ 3m dBµV/m	Limit dBµV/m	Margin dB	Comments
	Polarity	Hts(cm)								
Channel 11 . 2405 MHz										
2390.00	V	100	28.1	2.9	0.0	10.8	41.8	54.0	-12.2	Bandedge
2390.00	H	103	28.1	2.9	0.0	10.7	41.7	54.0	-12.3	Bandedge
7210.00	V	105	35.7	5.3	41.0	40.2	40.2	54.0	-13.7	
14420.00	V	100	42.3	7.2	40.4	20.3	29.5	54.0	-24.5	
7210.00	H	100	35.7	5.3	41.0	31.2	31.2	54.0	-22.7	
9620.00	H	100	38.0	6.0	40.5	18.9	22.4	54.0	-31.5	
14420.00	H	100	42.3	7.2	40.4	20.3	29.5	54.0	-24.5	
Channel 19 . 2445 MHz										
7330.00	V	100	36.0	5.3	40.8	34.5	35.0	54.0	-19.0	
12220.00	V	100	39.0	6.9	40.6	24.6	29.8	54.0	-24.1	
7330.00	H	132	36.0	5.3	40.8	36.8	37.3	54.0	-16.7	
12220.00	H	100	39.0	6.9	40.6	24.6	29.8	54.0	-24.1	
Channel 25 . 2475 MHz										
2483.50	V	100	28.4	2.9	0.0	11.4	42.7	54.0	-11.3	Bandedge
2483.50	H	100	28.4	2.9	0.0	10.6	41.9	54.0	-12.1	Bandedge
7430.00	V	125	36.2	5.4	40.7	35.6	36.5	54.0	-17.5	
12230.00	V	100	39.0	6.9	40.6	26.8	32.0	54.0	-21.9	
7430.00	H	110	36.2	5.4	40.7	36.4	37.3	54.0	-16.7	
12230.00	H	105	39.0	6.9	40.6	27.4	32.6	54.0	-21.3	




Graph 3.1.31




Graph 3.1.32




**Graph 3.1.33**




**Graph 3.1.34**




Graph 3.1.35




Graph 3.1.36




Graph 3.1.37




Graph 3.1.38




Graph 3.1.39




Graph 3.1.40




Graph 3.1.41




Graph 3.1.42




Graph 3.1.43




Graph 3.1.44




Graph 3.1.45




Graph 3.1.46




**Graph 3.1.47**




**Graph 3.1.48**




**Graph 3.1.49**




**Graph 3.1.50**




Graph 3.1.51




Graph 3.1.52




Graph 3.1.53




Graph 3.1.54




Graph 3.1.55




Graph 3.1.56




**Graph 3.1.57**



**Graph 3.1.58**



Graph 3.1.59



Graph 3.1.60



### 3.2 Receiver/digital device radiated emissions

**Test location:**  OATS  Anechoic Chamber

**Test distance:**  10 meters  3 meters

**Test result:** **Pass**

**Frequency range:** 30MHz-1300MHz

**Max. Emissions margin:** 8.0dB below the limits

**Notes:** The Radiated Emissions test was performed in the Anechoic chamber at 3m measurement distance (see Table 3.2.1 and 3.2.2)  
Graphs 3.2.1 to 3.2.8 show peak of emissions


---




<b>Date:</b>	February 8, 2016	<b>Result: Pass</b>
<b>Tested by:</b>	Clay Huff	
<b>Standard:</b>	FCC Part 15.109, Class B	
<b>Test Point:</b>	Enclosure	
<b>Operation mode:</b>	See page 5	
<b>Environmental Conditions:</b>	21.2°C; 16.3%(RH); 97kPa	
<b>Equipment Verification:</b>	<input checked="" type="checkbox"/>	
<b>Note:</b>	Sample MEL-024	

**Table 3.2.1**


Frequency MHz	Antenna Polarity	Peak Reading dB $\mu$ V	Total C.F. dB1/m	Total at 3m dB $\mu$ V/m	Limit dB $\mu$ V/m	Margin dB
30.187 MHz	V	11.2	20.3	31.4	40.0	-8.6
132.52 MHz	V	17.0	13.5	30.5	43.5	-13.1
997.95 MHz	V	12.6	25.3	37.9	54.0	-16.1
33.315 MHz	H	6.0	18.4	24.4	40.0	-15.6
106.24 MHz	H	7.9	13.0	20.9	43.5	-22.6
992.51 MHz	H	4.2	25.2	29.3	54.0	-24.7




Graph 3.2.1



Graph 3.2.2



Graph 3.2.3




Graph 3.2.4




<b>Date:</b>	February 8, 2016	<b>Result: Pass</b>
<b>Tested by:</b>	Clay Huff	
<b>Standard:</b>	FCC Part 15.109, Class B	
<b>Test Point:</b>	Enclosure	
<b>Operation mode:</b>	See page 5	
<b>Environmental Conditions:</b>	21.2°C; 16.3%(RH); 97kPa	
<b>Equipment Verification:</b>	<input checked="" type="checkbox"/>	
<b>Note:</b>	Sample MEL-025	

**Table 3.2.2**


Frequency MHz	Antenna Polarity	Peak Reading dB $\mu$ V	Total C.F. dB1/m	Total at 3m dB $\mu$ V/m	Limit dB $\mu$ V/m	Margin dB
30.374 MHz	V	11.8	20.2	32.0	40.0	-8.0
128.98 MHz	V	15.6	13.6	29.1	43.5	-14.4
132.52 MHz	V	17.0	13.5	30.4	43.5	-13.1
971.88 MHz	V	12.5	25.0	37.6	54.0	-16.4
30.514 MHz	H	4.7	20.1	24.7	40.0	-15.3
101.96 MHz	H	8.9	12.5	21.4	43.5	-22.1
106.24 MHz	H	7.3	13.0	20.3	43.5	-23.2
989.94 MHz	H	4.6	25.1	29.7	54.0	-24.3




Graph 3.2.5



Graph 3.2.6



Graph 3.2.7



Graph 3.2.8



#### 4.0 TEST EQUIPMENT

DESCRIPTION	MANUFACTURER	MODEL	SERIAL NO.	INTERTEK ID	CAL DUE	USED
Spectrum Analyzer	R & S	FSP 40	100024	12559	01/20/2017	<input checked="" type="checkbox"/>
Spectrum Analyzer	R & S	ESCI	100358	12909	10/20/2016	<input checked="" type="checkbox"/>
Bicono-Log Antenna	Schaffner-Teseq	CBL6112B	2468	9734	01/11/2017	<input checked="" type="checkbox"/>
Horn Antenna	EMCO	3115	9507-4513	9936	07/01/2016	<input checked="" type="checkbox"/>
Waveguide Horn Antenna	EMCO	3116	9904-2423	9705	11/19/2016	<input checked="" type="checkbox"/>
Pre-Amplifier	MITEQ	AMF-5D-00501800-28-13P	1402232	172081	11/19/2016	<input checked="" type="checkbox"/>
Pre-Amplifier	MITEQ	AMF-6F-16002600-25-10P	1222383	MIN-0065	11/19/2016	<input checked="" type="checkbox"/>
System	Quantum Change	TILE! Instrument Control	Ver. 3.4.K.29	15259	VBU	<input checked="" type="checkbox"/>



## 5.0 Revision History

REVISION LEVEL	DATE	REPORT NUMBER	PREPARED	REVIEWED	NOTES
0	02-10-2016	102460119MIN-001	CH	NS	Original Issue
1	03-22-2016	102460119MIN-001	SK <i>SKheya</i>	NS <i>NS</i>	Two Tables with Peak value of spurious emissions were added



Test Setup Photos

