



MRT Technology (Taiwan) Co., Ltd
Phone: +886-3-3288388
Fax: +886-3-3288918
Web: www.mrt-cert.com

Report No.: 2002TW5401-U1
Report Version: 1.0
Issue Date: 2020-03-10

MEASUREMENT REPORT

FCC PART 15.231(a)/ RSS 210

FCC ID: CHQ9050T4

IC: 2968A-9050T4

APPLICANT: RHINE ELECTRONIC CO., LTD.

Application Type: Certification

Product: Transmitter

Model No.: UC9050T4

Brand Name: RHINE

FCC Classification: FCC Part 15 Security/Remote Control Transmitter (DSC)

FCC Rule Part(s): Part 15.231(a)

IC Rule Part(s): RSS 210 Issue 10

Test Procedure(s): ANSI C63.10-2013

Received Date: February 27, 2020

Test Date: March 2 ~ 3, 2020

Tested By : *Peter Syu*

(Peter Syu)



Reviewed By : *Paddy Chen*

(Paddy Chen)



Approved By : *Chenz Ker*

(Chenz Ker)

The test results only relate to the tested sample.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2013. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2002TW5401-U1	1.0	Original Report	2020-03-10	

CONTENTS

Description	Page
1. INTRODUCTION	6
1.1. Scope	6
1.2. MRT Test Location	6
2. PRODUCT INFORMATION	7
2.1. Equipment Description.....	7
2.2. Test Standards	8
2.3. Test Methodology	8
2.4. EUT Setup and Test Mode	9
3. ANTENNA REQUIREMENTS	10
4. TEST EQUIPMENT CALIBRATION DATE	11
5. MEASUREMENT UNCERTAINTY.....	12
6. TEST RESULT	13
6.1. Summary	13
6.2. Radiated Emissions	14
6.2.1. Standard Applicable	14
6.2.2. Test Procedure.....	14
6.2.3. Test Setup.....	15
6.2.4. Test Results	16
6.3. 20dB Bandwidth / 99% Bandwidth	24
6.3.1. Standard Applicable	24
6.3.2. Test Procedure.....	24
6.3.3. Test Setup.....	24
6.3.4. Test Result.....	25
6.4. Transmission Time.....	26
6.4.1. Standard Applicable	26
6.4.2. Test Procedure.....	26
6.4.3. Test Setup.....	26
6.4.4. Test Result.....	27
6.5. Duty Cycle	28
6.5.1. Standard Applicable	28
6.5.2. Test Procedure.....	28
6.5.3. Test Setup.....	28
6.5.4. Test Result.....	29
6.6. AC Conducted Emissions Measurement.....	31

6.6.1.	Test Limit	31
6.6.2.	Test Setup.....	31
6.6.3.	Test Result.....	32
7.	CONCLUSION.....	34

§2.1033 General Information

Applicant	RHINE ELECTRONIC CO., LTD.
Applicant Address	NO. 29, AN HE ROAD, TAN-ZI SHIANG, TAICHUNG COUNTY, 427 Taiwan
Manufacturer	RHINE ELECTRONIC CO., LTD.
Manufacturer Address	NO. 29, AN HE ROAD, TAN-ZI SHIANG, TAICHUNG COUNTY, 427 Taiwan
Factory	KAM SHING ELECTRONIC CO., LTD
Factory Address	The Youth Industrial Administration Park, Chengjing Town, Huiyang city, Guangdong Province China
Test Site	MRT Technology (Taiwan) Co., Ltd
Test Site Address	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)
MRT Registration No.	291082
FCC Rule Part(s)	Part 15.231(a)
Test Device Serial No.	N/A <input type="checkbox"/> Production <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering
FCC Classification	FCC Part 15 Security/Remote Control Transmitter(DSC)

Test Facility / Accreditations

1. MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm.
2. MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada.
3. MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Taiwan, EU and TELEC Rules.


1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name	Transmitter
Model No.	UC9050T4
Frequency Range	433.985 MHz
Type of modulation	ASK
Antenna Type	Monopole

2.2. Test Standards

The following report is prepared on behalf of the **RHINE ELECTRONIC CO., LTD.** in accordance with FCC Part 15, Subpart C, and section 15.231, 15.203, 15.205 and 15.209 of the Federal Communication Commission rules/ IC RSS-Gen 8.8,8.9,8.10 and RSS-210 AnnexA

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission/immunity, should be checked to ensure compliance has been maintained.

2.3. Test Methodology

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013).

Deviation from measurement procedure..........**None**

2.4. EUT Setup and Test Mode

The EUT was operated at continuous transmitting mode that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode	
Mode 1	TX-433.985MHz, Power by Battery
Mode 2	TX-433.985MHz, Power by AC

3. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the **Transmitter** is permanently attached.
- There are no provisions for connection to an external antenna.

Conclusion:

The Transmitter unit complies with the requirement of §15.203.

4. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2020/3/25
Cable	Rosnol	N1C50-RG400-B 1C50-500CM	MRTTWE00013	1 year	2020/6/18
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2020/3/25

Radiated Emissions – AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00001	1 year	2020/6/4
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2020/3/25
Acitive Loop Antenna	Schwarzbeck	FMZB 1519B	MRTTWA00002	1 year	2020/4/29
Broadband Horn antenna	SCHWARZBECK	BBHA 9120D	MRTTWA00003	1 year	2020/4/22
Breitband Hornantenna	Schwarzbeck	BBHA 9170	MRTTWA00004	1 year	2020/4/23
Broadband Amplifier	Schwarzbeck	BBV 9721	MRTTWA00006	1 year	2020/4/24
Broadband Preamplifier	SCHWARZBECK	BBV 9718	MRTTWA00005	1 year	2020/4/24
Cable	HUBERSUHNER	SF106	MRTTWE00010	1 year	2020/4/22
Cable	Rosnol	K1K50-UP0264- K1K50-4M	MRTTWE00012	1 year	2020/6/18

Conducted Test Equipment – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2020/10/2
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2020/7/11
USB Wideband Power Sensor	KEYSIGHT	U2021XA	MRTTWA00015	1 year	2020/3/26

Test Software

Software	Version	Function
e3	9.160520a	EMI Test Software
EMI	V3	EMI Test Software

5. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement – SR2
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): 150kHz~30MHz: 2.42dB
Conducted Measurement– SR1
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): 1.3dB
Radiated Emission Measurement – AC1
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_{c(y)}$): Horizontal: 9K~30MHz: 4.14dB 30MHz~1GHz: 4.22dB 1GHz~40GHz: 4.05dB Vertical: 9K~30MHz: 4.14dB 30MHz~1GHz: 3.37dB 1GHz~40GHz: 4.08dB

6. TEST RESULT

6.1. Summary

Company Name: RHINE ELECTRONIC CO., LTD.

FCC/IC Part Section(s)	Test Description	Test Condition	Test Result
15.203	ANTENNA REQUIREMENTS	--	Pass
15.205,15.209,15.231(b)/ RSS Gen 8.9,8.10 RSS-210 Annex A	Radiated Spurious Emissions		Pass
15.231(c)/ RSS-210 Annex A.1.3	20dB Bandwidth / 99% Bandwidth	Radiated	Pass
15.231(a)/ RSS-210 Annex A.1.1(a)	Transmission Time		Pass
15.231(a)/ RSS-210 Annex A.1.1(a)	Duty Cycle		Pass
15.207 / RSS Gen 8.8	AC Conducted Emissions 150kHz - 30MHz	Line Conducted	Pass

Notes:

- 1) Determining compliance is based on the test results met the regulation limits or requirements declared by clients, and the test results don't take into account the value of measurement uncertainty.
- 2) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 3) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 4) The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.

6.2. Radiated Emissions

6.2.1. Standard Applicable

According to §15.231(b), the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	11,250 to 3,750	1125 to 375
174-260	3,750	375
260-470	13,750 to 12,500	1375 to 1,250
Above 470	12,500	1,250

The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in §15.209, whichever limit permits a higher field strength.

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements start below or at the lowest crystal frequency.

Compliance with the provisions of §15.205 shall be demonstrated using the measurement instrumentation specified in that section.


6.2.2. Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.231(b) and FCC Part 15.209 Limit / RSS-Gen 8.9 and RSS-210 Annex A.1.2.


6.2.3. Test Setup

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.231(b) and FCC Part 15.209 Limit/ RSS-Gen 8.9 and RSS-210 Annex A.1.2.

30MHz ~ 1GHz Test Setup:




1GHz ~ 5GHz Test Setup:



6.2.4. Test Results

EUT	Transmitter	Date of Test	2020-03-02
Factor	VULB 9162	Temp. / Humidity	23°C /58%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	TX- 433.985MHz	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	433.985	58.21	24.66	82.86	-17.97	100.83	100	200	Peak
2	433.985	N/A	N/A	75.42	-5.41	80.83	100	200	Average

Note:

1. **, means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Average factor ($20\log(1/\text{Duty Cycle})$) is 7.54dB,
6. Average Measurement = Peak Measurement - Average factor.

EUT	Transmitter	Date of Test	2020-03-02
Factor	VULB 9162	Temp. / Humidity	23°C /58%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	TX- 433.985MHz	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1 *	433.985	58.23	24.66	82.88	-17.95	100.83	100	90	Peak
2 *	433.985	N/A	N/A	75.44	-5.39	80.83	100	90	Average

Note:

1. **, means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Average factor ($20\log(1/\text{Duty Cycle})$) is 7.54dB,
6. Average Measurement = Peak Measurement - Average factor.

EUT	Transmitter	Date of Test	2020-03-02
Factor	VULB 9162	Temp. / Humidity	23°C /58%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	TX- 433.985MHz, Power by Battery Input	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	216.240	9.29	18.86	28.15	-52.67	80.82	100	400	Peak
2 *	324.880	16.48	22.41	38.89	-7.11	46.00	100	400	Peak
3	542.160	9.36	26.49	35.85	-44.97	80.82	100	400	Peak
4	650.800	5.74	28.32	34.07	-46.75	80.82	100	400	Peak
5	868.080	30.32	31.35	61.67	-19.15	80.82	100	50	Peak
6 *	868.080	N/A	N/A	54.23	-6.59	60.82	100	50	Average
7	976.720	4.92	32.18	37.10	-16.90	54.00	100	400	Peak

Note:

1. **, means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Average factor ($20\log(1/\text{Duty Cycle})$) is 7.54dB,
6. Average Measurement = Peak Measurement - Average factor.

EUT	Transmitter	Date of Test	2020-03-02
Factor	VULB 9162	Temp. / Humidity	23°C /58%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	TX- 433.985MHz, Power by Battery Input	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	244.370	2.81	20.35	23.16	-22.84	46.00	100	400	Peak
2 *	324.880	8.38	22.41	30.79	-15.21	46.00	100	400	Peak
3	542.160	8.85	26.49	35.33	-45.49	80.82	100	400	Peak
4	730.340	4.05	29.58	33.63	-47.19	80.82	100	400	Peak
5	868.080	21.98	31.35	53.33	-27.49	80.82	100	400	Peak
6	976.720	4.70	32.18	36.88	-17.12	54.00	100	400	Peak

Note:

1. **, means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Transmitter	Date of Test	2020-03-02
Factor	VULB 9162	Temp. / Humidity	23°C /58%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	TX-433.985MHz, Power by AC Input	Test Voltage	AV 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	50.370	0.53	21.59	22.13	-58.69	80.82	100	400	Peak
2	101.780	1.05	19.51	20.55	-60.27	80.82	100	400	Peak
3	215.270	8.70	18.82	27.52	-53.30	80.82	100	400	Peak
4 *	328.760	13.81	22.57	36.37	-9.63	46.00	100	400	Peak
5	584.840	8.75	27.23	35.98	-44.84	80.82	100	400	Peak
6	868.060	30.12	31.35	61.47	-19.35	80.82	100	65	Peak
7	868.060	22.67	31.35	54.02	-26.80	60.82	100	65	Average

Note:

1. **, means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Transmitter	Date of Test	2020-03-02
Factor	VULB 9162	Temp. / Humidity	23°C /58%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	TX-433.985MHz, Power by AC Input	Test Voltage	AV 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	53.280	1.31	21.14	22.46	-58.36	80.82	100	400	Peak
2	104.690	0.83	19.23	20.05	-60.77	80.82	100	400	Peak
3	* 245.340	6.00	20.38	26.39	-19.61	46.00	100	400	Peak
4	456.800	7.54	25.02	32.55	-48.27	80.82	100	400	Peak
5	730.340	6.10	29.58	35.68	-45.14	80.82	100	400	Peak
6	868.060	21.82	31.35	53.17	-27.65	80.82	100	400	Peak

Note:

1. **, means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Transmitter	Date of Test	2020-03-03
Factor	BBHA 9120D	Temp. / Humidity	23°C /58%
Polarity	Horizontal	Site / Test Engineer	AC1 / Jay
Test Mode	TX-433.985MHz, Power by Battery Input	Test Voltage	By Battery




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	1301.750	56.06	-6.41	49.65	-24.35	74.00	150	400	Peak
2 *	1736.125	72.94	-5.16	67.79	-13.03	80.82	150	0	Peak
3 *	1736.125	N/A	N/A	60.35	-0.47	60.82	150	0	Average
4	2170.000	62.97	-3.74	59.23	-21.59	80.82	150	400	Peak
5	2604.125	57.97	-2.37	55.60	-25.22	80.82	150	400	Peak
6	3037.625	49.14	-2.80	46.34	-34.48	80.82	150	400	Peak
7	3472.125	43.21	-1.33	41.87	-38.95	80.82	150	400	Peak
8	3906.750	46.27	-0.17	46.11	-27.89	74.00	150	400	Peak
9	4340.000	46.78	1.76	48.54	-25.46	74.00	150	400	Peak

Note:

1. **, means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB) + Cable Loss (dB) - Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Average factor ($20\log(1/\text{Duty Cycle})$) is 7.54dB,
6. Average Measurement = Peak Measurement - Average factor.

EUT	Transmitter	Date of Test	2020-03-03
Factor	BBHA 9120D	Temp. / Humidity	23°C /58%
Polarity	Vertical	Site / Test Engineer	AC1 / Jay
Test Mode	TX-433.985MHz, Power by Battery Input	Test Voltage	By Battery



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	1301.750	54.95	-6.41	48.53	-25.47	74.00	150	400	Peak
2 *	1736.000	70.08	-5.16	64.92	-15.90	80.82	150	70	Peak
3 *	1736.000	N/A	N/A	57.47	-3.35	60.82	150	70	Average
4	2169.875	63.38	-3.74	59.64	-21.18	80.82	150	400	Peak
5	2604.250	55.35	-2.37	52.98	-27.84	80.82	150	400	Peak
6	3037.875	54.82	-2.80	52.02	-28.80	80.82	150	400	Peak
7	3472.000	44.99	-1.33	43.66	-37.16	80.82	150	400	Peak
8	3905.625	47.43	-0.17	47.26	-26.74	74.00	150	400	Peak
9	4339.625	45.29	1.76	47.05	-26.95	74.00	150	400	Peak

Note:

1. **, means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. Average factor ($20\log(1/\text{Duty Cycle})$) is 7.54dB,
6. Average Measurement = Peak Measurement - Average factor.

6.3. 20dB Bandwidth / 99% Bandwidth


6.3.1. Standard Applicable

According to FCC Part 15.231(c), the bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70MHz and below 900MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

6.3.2. Test Procedure

With the EUT's antenna attached, the EUT's 20dB Bandwidth power was received by the test antenna, which was connected to the spectrum analyzer with the START, and STOP frequencies set to the EUT's operation band.

6.3.3. Test Setup



6.3.4. Test Result

Test Frequency (MHz)	Modulation Type	20dB Bandwidth (KHz)	99% Bandwidth (KHz)	Limit (KHz)	Result
433.985	ASK	9.916	28.266	≤ 1085	Pass

Limit = Fundamental Frequency * 0.25%, 433.985 MHz * 0.25% = 1.085 MHz,



6.4. Transmission Time


6.4.1. Standard Applicable

According to FCC 15.231(a)(1), A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

6.4.2. Test Procedure


With the EUT's antenna attached, the EUT's output signal was received by the test antenna, which was connected to the spectrum analyzer. Set the center frequency to 434MHz, then set the spectrum analyzer to Zero Span for the release time reading. During the testing, the switch was released then the EUT automatically deactivated.

6.4.3. Test Setup



6.4.4. Test Result

Test Item	Frequency (MHz)	Measurement (s)	Limit (s)	Result
Transmission Time (T_{on})	433.985	0.26	< 5	Pass



6.5. Duty Cycle


6.5.1. Standard Applicable

According to FCC Part 15.231(b) and 15.35(c), for pulse operation transmitter, the averaging pulsed emissions are calculated by peak value of measured emission plus duty cycle factor.

6.5.2. Test Procedure

With the EUT's antenna attached, the EUT's output signal was received by the test antenna, which was connected to the spectrum analyzer. Set the center frequency to 434MHz, then set the spectrum analyzer to Zero Span for the release time reading. During the testing, the switch was released then the EUT automatically deactivated.

6.5.3. Test Setup




6.5.4. Test Result

Modulation Type	Total Time (T_{on}) (ms)	The duration of one cycle (ms)	Duty Cycle (ms)	Average Factor (dB)
ASK	14.495	34.13	0.42	7.54


Note 1: Duty Cycle = Total Time (T_{on}) / (T_{on} + T_{off}).

$$((780\text{us}*14) + (325\text{us}*11)) / (34.13\text{ms}) = 0.42\text{ms}$$

Note 2: Average Factor = $20*\text{Log}^*(1/\text{Duty Cycle})$.



433.985MHz (T_{on}-Long)



433.985MHz (T_{on}-Short)



6.6. AC Conducted Emissions Measurement


6.6.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 / RSS-Gen Limits		
Frequency (MHz)	QP (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.


Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

6.6.2. Test Setup



6.6.3. Test Result

EUT	Transmitter	Date of Test	2020-03-02
Factor	CE_ENV216-L1 (Filter ON)	Temp. / Humidity	23.1°C /56%
Polarity	Line1	Site / Test Engineer	SR2 / Peter
Test Mode	TX-433.985MHz, Power by AC Input	Test Voltage	AC 120V/60Hz




No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)
1	0.231	-5.18	9.61	4.43	-57.98	62.41	QP
2	0.231	-5.82	9.61	3.79	-48.62	52.41	Average
3	0.424	-6.73	9.60	2.87	-54.49	57.36	QP
4	0.424	-6.97	9.60	2.63	-44.73	47.36	Average
5	0.901	-7.09	9.65	2.55	-53.45	56.00	QP
6	0.901	-7.19	9.65	2.46	-43.54	46.00	Average
7	* 2.404	-6.45	9.69	3.24	-52.76	56.00	QP
8	* 2.404	-6.20	9.69	3.49	-42.51	46.00	Average
9	5.212	-4.81	9.75	4.94	-55.06	60.00	QP
10	5.212	-4.70	9.75	5.05	-44.95	50.00	Average
11	11.210	-4.44	9.89	5.45	-54.55	60.00	QP
12	11.210	-4.83	9.89	5.06	-44.94	50.00	Average

Note:

1. ** means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

EUT	Transmitter	Date of Test	2020-03-02
Factor	CE_ENV216-N (Filter ON)	Temp. / Humidity	23.1°C /56%
Polarity	Neutral	Site / Test Engineer	SR2 / Peter
Test Mode	TX-433.985MHz, Power by AC Input	Test Voltage	AC 120V/60Hz



No	Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Remark (QP/PK/AV)	
1	0.226	-4.97	9.61	4.64	-57.94	62.58	QP	
2	0.226	-5.96	9.61	3.65	-48.93	52.58	Average	
3	0.411	-6.79	9.61	2.82	-54.80	57.63	QP	
4	0.411	-6.84	9.61	2.77	-44.86	47.63	Average	
5	1.018	-6.94	9.66	2.72	-53.28	56.00	QP	
6	1.018	-7.12	9.66	2.54	-43.46	46.00	Average	
7	1.765	-6.65	9.68	3.02	-52.98	56.00	QP	
8	1.765	-6.56	9.68	3.12	-42.88	46.00	Average	
9	*	3.597	-5.38	9.71	4.32	-51.68	56.00	QP
10	*	3.597	-5.30	9.71	4.41	-41.59	46.00	Average
11	11.957	-4.88	9.92	5.04	-54.96	60.00	QP	
12	11.957	-4.73	9.92	5.20	-44.80	50.00	Average	

Note:

1. **, means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).

7. CONCLUSION

The data collected relate only the item(s) tested and show that the **Transmitter** is in compliance with FCC Rules/ IC RSS 210 Annex A1.1.

The End