

FCC/ISED - TEST REPORT

Report Number : **68.760.22.0422.01** Date of Issue: **2022-06-10**

Model : **CPPM1**

Product Type : Camera

Applicant : GoPro, Inc.

Address : 3025 Clearview Way, San Mateo, CA 94402, USA

Manufacturer : GoPro, Inc.

Address : 3025 Clearview Way, San Mateo, CA 94402, USA

Test Result : ☒ **Positive** ☐ **Negative**

Total pages including Appendices : **59**

Any use for advertising purposes must be granted in writing. This technical report may only be quoted in full. This report is the result of a single examination of the object in question and is not generally applicable evaluation of the quality of other products in regular production. For further details, please see testing and certification regulation chapter A-3.4.

1 Table of Contents

1	Table of Contents	2
2	Details about the Test Laboratory	3
3	Description of the Equipment under Test.....	4
4	Summary of Test Standards	5
5	Summary of Test Results.....	6
6	General Remarks.....	7
7	Test Setups.....	8
8	Systems test configuration.....	9
9	Technical Requirement.....	10
9.1	Conducted Emission.....	10
9.2	Conducted output power & EIRP	13
9.3	6dB bandwidth.....	15
9.4	99% bandwidth	20
9.5	Power spectral density.....	25
9.6	Spurious RF conducted emissions	30
9.7	Band edge	43
9.8	Spurious radiated emissions for transmitter.....	47
10	Test Equipment List	58
11	System Measurement Uncertainty	59

2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12&13, Zhiheng Wisdomland Business Park,
Guankou Erlu, Nantou, Nanshan District,
Shenzhen, 518052 China

FCC Designation Number: CN5009

FCC Registration No.: 514049

ISED#: 10320A

Telephone: 86 755 8828 6998
Fax: 86 755 8828 5299

3 Description of the Equipment under Test

Product:	Camera
Model no.:	CPPM1
FCC ID:	CNFCPPM1
IC:	10193A-CPPM1
PMN:	CPPM1
HVIN:	CPPM1
Rating:	3.85VDC
RF Transmission Frequency:	2412MHz-2462MHz for 802.11b/g/n20/n40
No. of Operated Channel:	11
Modulation:	802.11b: BPSK, QPSK, CCK, 802.11g/802.11n20/802.11n40: BPSK, QPSK, 16-QAM, 64-QAM
Antenna Type:	Internal Integrated Metal Antenna
Antenna Gain:	-2.10dBi max for 2.4GHz
Description of the EUT:	The Equipment Under Test (EUT) is a Camera supports 2.4GHz Bluetooth/WIFI, 5GHz WIFI functions.

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2020 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators
RSS-Gen Issue 5, Amendment 2, February 2021	General Requirements and Information for the Certification of Radio Apparatus
RSS-247 Issue 2 February 2017	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSS) and License-Exempt Local Area Network (LE-LAN) Devices

All the test methods were according to KDB558074 D01 v05r02 DTS Measurement Guidance and ANSI C63.10 (2013).

5 Summary of Test Results

Technical Requirements			
FCC Part 15 Subpart C/RSS-247 Issue 2/RSS-Gen Issue 5			
Test Condition		Test Result	Test Site
§15.207 RSS-GEN 8.8	Conducted emission AC power port	Pass	Site 1
§15.247 (b) (3) & RSS-247 5.4(d)	Conducted output power	Pass	Site 1
RSS-247 5.4(d)	Equivalent Isotropic Radiated Power	Pass	Site 1
§15.247(e) RSS-247 5.2(b)	Power spectral density	Pass	Site 1
§15.247(a)(2) RSS-247 5.2(a) & RSS-GEN 6.7	6dB bandwidth	Pass	Site 1
§15.247(a)(1) RSS-247 5.1(b)	20dB Occupied bandwidth	N/A	--
RSS-GEN 6.7	99% Occupied Bandwidth	Pass	Site 1
§15.247(a)(1) RSS-247 5.1(b)	Carrier frequency separation	N/A	--
§15.247(a)(1)(iii) RSS-247 5.1(d)	Number of hopping frequencies	N/A	--
§15.247(a)(1)(iii) RSS-247 5.1(d)	Dwell Time	N/A	--
§15.247(d) RSS-247 5.5	Spurious RF conducted emissions	Pass	Site 1
§15.247(d) RSS-247 5.5	Band edge	Pass	Site 1
§15.247(d) & §15.209 & §15.205 RSS-247 5.5 & RSS- Gen 6.13	Spurious radiated emissions for transmitter	Pass	Site 1
§15.203 RSS-Gen 6.8	Antenna requirement	Pass See note 1	--

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses an Internal Integrated Metal Antenna, which gain is -2.10dBi. In accordance to §15.203 and RSS-Gen 6.8, it is considered sufficiently to comply with the provisions of this section.

6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: CNFCPPM1, complies with Section 15.207, 15.209, 15.205, 15.247 of the FCC Part 15, Subpart C.

This submittal(s) (test report) is intended for IC: 10193A-CPPM1, complies with RSS-247, RSS-GEN.

The Model: CPPM1 supports Bluetooth Low Energy/Bluetooth BDR+EDR /WIFI functions, power by 3.85VDC, 1506mAh supplied by a rechargeable Lithium Ion Battery or 5VDC supplied by USB type C port.

The TX and RX range is 2402MHz-2480MHz for Bluetooth, 2412MHz – 2462MHz for 2.4GHzWIFI, 5180MHz – 5320MHz, 5500MHz – 5720MHz, 5745MHz – 5825MHz for 5GHzWIFI.

This report is for the 2.4GHz WIFI part.

SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: 2022-05-25

Testing Start Date: 2022-05-30

Testing End Date: 2022-06-08

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch -


Reviewed by:

Prepared by:

Tested by:



John Zhi
Project Manager



Myron Yu
Project Engineer




Carry Cai
Test Engineer


7 Test Setups

7.1 Radiated test setups


Below 1GHz




Above 1GHz



7.2 Conducted RF test setups



7.3 AC Power Line Conducted Emission test setups



8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.	S/N
LAPTOP	DELL	LATITUDE 7480	4SWNPH2
USB TYPE C CABLE	GOPRO	0.46M (LENGTH)	--
AC ADAPTER	APPLE	A1401	--

Test Channel information:

Test Mode	Channel (MHz)		
802.11b	CH 1: 2412MHz	CH 6: 2437MHz	CH 11: 2462MHz
802.11g	CH 1: 2412MHz	CH 6: 2437MHz	CH 11: 2462MHz
802.11n20	CH 1: 2412MHz	CH 6: 2437MHz	CH 11: 2462MHz
802.11n40	CH 3: 2422MHz	CH 6: 2437MHz	CH 9: 2452MHz

Test Software information:

Test Software Version	QRCT (V3.0-186.0) from QUALCOMM	
Mode	Packet Type	Data Rate
11b	16	11b LONG 1 Mbps
11g	18.5	11g 6 Mbps
11n HT20	19	MCS0 6.5 Mbps
11n HT40	17	MCS0 13.5 Mbps (40MHz)

9 Technical Requirement

9.1 Conducted Emission

Test Method

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both sides of AC line were checked for maximum conducted interference.
6. The frequency range from 150 kHz to 30 MHz was searched.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively


Limit According to §15.207, conducted emissions limit as below:

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

*Decreasing linearly with logarithm of the frequency

Conducted Emission

Product Type : Camera
 M/N : CPPM1
 Operating Condition : Charging + TX
 Test Specification : Power Line, Live
 Comment : AC 120V/60Hz (External adapter)



Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.202000	43.19	---	63.53	20.33	L1	9.23
0.626000	38.02	---	56.00	17.98	L1	9.20
0.998000	28.06	---	56.00	27.94	L1	9.20
1.950000	29.62	---	56.00	26.38	L1	9.22
4.150000	24.50	---	56.00	31.50	L1	9.28
7.846000	29.88	---	60.00	30.12	L1	9.37

Remark:


Level=Reading Level + Correction Factor

Correction Factor=Cable Loss + LISN Factor

(The Reading Level is recorded by software which is not shown in the sheet)

Conducted Emission

Product Type : Camera
 M/N : CPPM1
 Operating Condition : Charging + TX
 Test Specification : Power Line, Neutral
 Comment : AC 120V/60Hz (External adapter)



Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.150000	47.47	---	66.00	18.53	N	9.40
0.406000	36.11	---	57.73	21.62	N	9.38
0.930000	30.93	---	56.00	25.07	N	9.39
1.982000	29.77	---	56.00	26.23	N	9.42
4.154000	27.95	---	56.00	28.05	N	9.47
8.218000	31.77	---	60.00	28.23	N	9.59

Remark:

Level=Reading Level + Correction Factor

Correction Factor=Cable Loss + LISN Factor

(The Reading Level is recorded by software which is not shown in the sheet)

9.2 Conducted output power & EIRP

Test Method

1. The EUT was placed on 0.8m height table, the RF output of EUT was connected to the power meter by RF cable. The path loss was compensated to the results for each measurement.
2. Setting the highest output power level of the EUT
3. Record the power value.

Limits

According to §15.247 (b) (3) & RSS-247 5.4(d), conducted output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤1	≤30

According to & RSS-247 5.4(d), EIRP limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤4	≤36.2

Test result as below table

802.11B SISO modulation Test Result

Frequency (MHz)	Conducted Output Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Result
Low channel 2412MHz	19.06	-2.10	16.96	Pass
Middle channel 2437MHz	18.73	-2.10	16.63	Pass
High channel 2462MHz	18.44	-2.10	16.34	Pass

802.11G SISO modulation Test Result

Frequency (MHz)	Conducted Output Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Result
Low channel 2412MHz	21.15	-2.10	19.05	Pass
Middle channel 2437MHz	20.81	-2.10	18.71	Pass
High channel 2462MHz	20.75	-2.10	18.65	Pass

802.11N20_SISO modulation Test Result

Frequency (MHz)	Conducted Output Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Result
Low channel 2412MHz	21.35	-2.10	19.25	Pass
Middle channel 2437MHz	21.03	-2.10	18.93	Pass
High channel 2462MHz	20.93	-2.10	18.83	Pass

802.11N40_SISO modulation Test Result

Frequency (MHz)	Conducted Output Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Result
Low channel 2412MHz	19.52	-2.10	17.42	Pass
Middle channel 2437MHz	19.23	-2.10	17.13	Pass
High channel 2462MHz	19.15	-2.10	17.05	Pass

9.3 6dB bandwidth

Test Method

1. Connect EUT test port to spectrum analyzer.
2. Use the following spectrum analyzer settings:
RBW=100K, VBW $\geq$ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
3. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 6 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.
4. Allow the trace to stabilize, record the X dB Bandwidth value.

Limit

Limit [kHz]


≥ 500

Test result

Test Mode	Antenna	Channel [MHz]	DTS BW [MHz]	Limit [MHz]	Verdict
11B	Ant1	2412	7.160	0.5	PASS
		2437	8.160	0.5	PASS
		2462	7.640	0.5	PASS
11G	Ant1	2412	15.200	0.5	PASS
		2437	15.200	0.5	PASS
		2462	15.200	0.5	PASS
11N20SISO	Ant1	2412	15.200	0.5	PASS
		2437	15.200	0.5	PASS
		2462	15.200	0.5	PASS
11N40SISO	Ant1	2422	35.280	0.5	PASS
		2437	35.280	0.5	PASS
		2452	35.280	0.5	PASS


Test Graphs

11B_Ant1_2412




Date: 31.MAY.2022 21:37:53

11B_Ant1_2437




Date: 31.MAY.2022 21:39:50

11B_Ant1_2462




Date: 31.MAY.2022 21:41:25

11G Ant1 2412




Date: 31.MAY.2022 21:43:49

11G Ant1 2437




Date: 31.MAY.2022 21:45:34

11G Ant1 2462




Date: 31.MAY.2022 21:47:30

11N20SISO Ant1 2412




Date: 31.MAY.2022 21:52:44

11N20SISO Ant1 2437




Date: 31.MAY.2022 22:03:14

11N20SISO Ant1 2462




Date: 31.MAY.2022 22:04:56

11N40SISO Ant1 2422




Date: 31.MAY.2022 22:07:14

11N40SISO Ant1 2437



Date: 31.MAY.2022 22:09:32

11N40SISO Ant1 2452



Date: 31.MAY.2022 22:11:35

9.4 99% bandwidth

Test Method

1. Connect EUT test port to spectrum analyzer.
2. Use the following spectrum analyzer settings:
RBW=1% to 5% of the actual occupied, VBW $\geq$ 3RBW, Sweep = auto,
Detector function = peak, Trace = max hold
3. Use the automatic bandwidth measurement capability of an instrument, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.
4. Allow the trace to stabilize, record the X dB Bandwidth value.

Limit

Limit [kHz]


--

Test Result

Test Mode	Antenna	Channel [MHz]	OCB [MHz]	Limit [MHz]	Verdict
11B	Ant1	2412	13.187	---	PASS
		2437	13.147	---	PASS
		2462	13.187	---	PASS
11G	Ant1	2412	16.823	---	PASS
		2437	16.703	---	PASS
		2462	16.703	---	PASS
11N20SISO	Ant1	2412	17.822	---	PASS
		2437	17.742	---	PASS
		2462	17.742	---	PASS
11N40SISO	Ant1	2422	36.204	---	PASS
		2437	36.204	---	PASS
		2452	36.204	---	PASS


Test Graphs

11B_Ant1_2412




Date: 31.MAY.2022 21:38:04

11B_Ant1_2437




Date: 31.MAY.2022 21:40:01

11B_Ant1_2462




Date: 31.MAY.2022 21:41:36

11G Ant1 2412




Date: 31.MAY.2022 21:44:00

11G Ant1 2437




Date: 31.MAY.2022 21:45:45

11G Ant1 2462




Date: 31.MAY.2022 21:47:41

11N20SISO_Ant1_2412




Date: 31.MAY.2022 21:52:55

11N20SISO_Ant1_2437




Date: 31.MAY.2022 22:03:25

11N20SISO_Ant1_2462




Date: 31.MAY.2022 22:05:07

11N40SISO Ant1 2422




Date: 31.MAY.2022 22:07:25

11N40SISO Ant1 2437



Date: 31.MAY.2022 22:09:43

11N40SISO Ant1 2452



Date: 31.MAY.2022 22:11:46

9.5 Power spectral density

Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. The RF output of EUT was connected to the test receiver by RF cable. The path loss was compensated to the results for each measurement.
2. Set analyzer center frequency to DTS channel center frequency. RBW=3kHz, VBW $\geq$ 3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
3. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
4. Repeat above procedures until other frequencies measured were completed.

Limit

Limit [dBm/3KHz]


≤ 8

Test result

Test Mode	Channel [MHz]	Result [dBm/3KHz]	Limit [dBm/3KHz]	Verdict
11B	2412	-3.77	≤ 8	PASS
	2437	-4.86	≤ 8	PASS
	2462	-3.84	≤ 8	PASS
11G	2412	-4.5	≤ 8	PASS
	2437	-4.75	≤ 8	PASS
	2462	-4.22	≤ 8	PASS
11N20SISO	2412	-4.95	≤ 8	PASS
	2437	-5.26	≤ 8	PASS
	2462	-4.81	≤ 8	PASS
11N40SISO	2422	-10.23	≤ 8	PASS
	2437	-10.03	≤ 8	PASS
	2452	-9.62	≤ 8	PASS


Test Graphs

11B_Ant1_2412




Date: 31.MAY.2022 21:38:16

11B_Ant1_2437




Date: 31.MAY.2022 21:40:13

11B_Ant1_2462




Date: 31.MAY.2022 21:41:48

11G Ant1 2412




Date: 31.MAY.2022 21:44:12

11G Ant1 2437




Date: 31.MAY.2022 21:45:57

11G Ant1 2462




Date: 31.MAY.2022 21:47:53

11N20SISO Ant1 2412




Date: 31.MAY.2022 21:53:07

11N20SISO Ant1 2437




Date: 31.MAY.2022 22:03:37

11N20SISO Ant1 2462




Date: 31.MAY.2022 22:05:19

11N40SISO Ant1 2422




Date: 31.MAY.2022 22:07:37

11N40SISO Ant1 2437



Date: 31.MAY.2022 22:09:55

11N40SISO Ant1 2452



Date: 31.MAY.2022 22:11:58

9.6 Spurious RF conducted emissions

Test Method


1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz, VBW ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold
3. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
4. The level displayed must comply with the limit specified in this Section. Submit these plots.
5. Repeat above procedures until all frequencies measured were complete.

Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20


Test Result (Remark: The emissions exceed limit is fundamental signal.)

11B_Ant1_2412_0~Reference




Date: 31.MAY.2022 21:38:31

11B_Ant1_2412_30~1000




Date: 31.MAY.2022 21:38:38

11B_Ant1_2412_1000~26500




Date: 31.MAY.2022 21:38:45

11B Ant1 2437 0~Reference




Date: 31.MAY.2022 21:40:18

11B Ant1 2437 30~1000




Date: 31.MAY.2022 21:40:24

11B Ant1 2437 1000~26500




Date: 31.MAY.2022 21:40:32

11B_Ant1_2462_0~Reference




Date: 31.MAY.2022 21:42:03

11B_Ant1_2462_30~1000




Date: 31.MAY.2022 21:42:09

11B_Ant1_2462_1000~26500




Date: 31.MAY.2022 21:42:17

11G Ant1 2412 0~Reference




Date: 31.MAY.2022 21:44:27

11G Ant1 2412 30~1000




Date: 31.MAY.2022 21:44:33

11G Ant1 2412 1000~26500




Date: 31.MAY.2022 21:44:41

11G_Ant1_2437_0~Reference




Date: 31.MAY.2022 21:46:02

11G_Ant1_2437_30~1000




Date: 31.MAY.2022 21:46:08

11G_Ant1_2437_1000~26500




Date: 31.MAY.2022 21:46:16

11G Ant1 2462 0~Reference




Date: 31 MAY 2022 21:48:08

11G Ant1 2462 30~1000




Date: 31 MAY 2022 21:48:14

11G Ant1 2462 1000~26500




Date: 31 MAY 2022 21:48:22

11N20SISO_Ant1_2412_0~Reference




Date: 31.MAY.2022 21:53:22

11N20SISO_Ant1_2412_30~1000




Date: 31.MAY.2022 21:53:28

11N20SISO_Ant1_2412_1000~26500




Date: 31.MAY.2022 21:53:36

11N20SISO Ant1 2437 0~Reference




Date: 31.MAY.2022 22:03:42

11N20SISO Ant1 2437 30~1000




Date: 31.MAY.2022 22:03:48

11N20SISO Ant1 2437 1000~26500




Date: 31.MAY.2022 22:03:56

11N20SISO_Ant1_2462_0~Reference




Date: 31.MAY.2022 22:05:34

11N20SISO_Ant1_2462_30~1000




Date: 31.MAY.2022 22:05:40

11N20SISO_Ant1_2462_1000~26500




Date: 31.MAY.2022 22:05:48

11N40SISO Ant1 2422 0~Reference




Date: 31 MAY 2022 22:07:52

11N40SISO Ant1 2422 30~1000




Date: 31 MAY 2022 22:07:58

11N40SISO Ant1 2422 1000~26500




Date: 31 MAY 2022 22:08:06

11N40SISO_Ant1_2437_0~Reference




Date: 31.MAY.2022 22:10:00

11N40SISO_Ant1_2437_30~1000




Date: 31.MAY.2022 22:10:06

11N40SISO_Ant1_2437_1000~26500




Date: 31.MAY.2022 22:10:14

11N40SISO Ant1 2452 0~Reference




Date: 31.MAY.2022 22:12:13

11N40SISO Ant1 2452 30~1000



Date: 31.MAY.2022 22:12:19

11N40SISO Ant1 2452 1000~26500



Date: 31.MAY.2022 22:12:27

9.7 Band edge

Test Method


1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz, VBW $\geq$ RBW, Sweep = auto, Detector function = peak, Trace = max hold
3. Allow the trace to stabilize, use the peak and delta measurement to record the result.
The level displayed must comply with the limit specified in this Section.
4. The level displayed must comply with the limit specified in this Section.
5. Repeat the test at the hopping off and hopping on mode, submit all the plots.

Limit:


According to §15.247(d) and RSS-247 5.5, in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a) and RSS-Gen 8.10, must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)) and RSS-Gen.

Frequency Range MHz	Limit (dBc)
30-25000	-20

Test result




11G Ant1 High 2462




Date: 31.MAY.2022 21:48:02

11N20SISO Ant1 Low 2412





Date: 31.MAY.2022 21:53:16

11N20SISO Ant1 High 2462



Date: 31.MAY.2022 22:05:28



9.8 Spurious radiated emissions for transmitter

Test Method

- 1: The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2: The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
- 3: The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4: For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5: Use the following spectrum analyzer settings According to C63.10:

For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious
 RBW = 100 KHz to 120KHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

For Peak unwanted emissions Above 1GHz:

Span = wide enough to capture the peak level of the in-band emission and all spurious
 RBW = 1MHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

Procedures for average unwanted emissions measurements above 1000 MHz

- a) RBW = 1MHz.
- b) VBW \ [3 × RBW].
- c) Detector = RMS (power averaging), if [span / (# of points in sweep)] \ RBW / 2. Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
- d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)
- e) Sweep time = auto.
- f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of 1 / D, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)
- g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
 - 1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is $[10 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.

2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is $[20 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.

3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

Limit

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205 and RSS-GEN 8.10, must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Field Strength dBµV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK


Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.


The only worse case (802.11n20) test result is listed in the report.

Transmitting spurious emission test result as below:

Below 1G:




Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
46.975000	22.04	40.00	17.96	200.0	H	4.0	21.12
126.622778	20.37	43.50	23.13	200.0	H	194.0	15.97
256.495000	23.05	46.00	22.95	200.0	H	205.0	20.28
349.345556	24.56	46.00	21.44	100.0	H	334.0	22.42
490.103333	29.49	46.00	16.51	100.0	H	71.0	25.35
828.094444	38.35	46.00	7.65	200.0	H	163.0	30.59



Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
48.699444	21.82	40.00	18.18	100.0	V	356.0	20.92
98.277222	19.66	43.50	23.84	100.0	V	0.0	18.45
112.827222	24.03	43.50	19.47	100.0	V	238.0	17.63
196.840000	20.46	43.50	23.04	100.0	V	345.0	18.78
344.441667	25.01	46.00	20.99	100.0	V	113.0	22.38
498.456111	29.27	46.00	16.73	100.0	V	0.0	25.48


Low channel 2412MHz



Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2392.857143	55.89	74.00	18.11	150.0	H	259.0	-2.21
6555.500000	42.53	74.00	31.47	150.0	H	329.0	8.81
9648.000000	45.66	74.00	28.34	150.0	H	24.0	12.31

Final Result

Frequency (MHz)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2392.857143	39.61	54.00	14.39	150.0	H	259.0	-2.21




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2393.333333	61.17	74.00	12.83	150.0	V	0.0	-2.21
7231.500000	42.95	74.00	31.05	150.0	V	65.0	8.72
9648.000000	49.87	74.00	24.13	150.0	V	243.0	12.31


Final Result

Frequency (MHz)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2393.333333	38.95	54.00	15.05	150.0	V	0.0	-2.21

Middle channel 2437MHz




Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2347.619048	42.46	74.00	31.54	150.0	H	13.0	-2.36
4545.000000	39.06	74.00	34.94	150.0	H	13.0	3.61
6591.500000	42.11	74.00	31.89	150.0	H	13.0	9.14
9748.500000	48.39	74.00	25.61	150.0	H	1.0	12.50




Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2392.380952	44.86	74.00	29.14	150.0	V	0.0	-2.22
6613.500000	41.70	74.00	32.30	150.0	V	39.0	9.35
9748.000000	49.44	74.00	24.56	150.0	V	123.0	12.50

High channel 2462MHz



Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2379.523810	42.51	74.00	31.49	150.0	H	143.0	-2.27
6571.500000	42.00	74.00	32.00	150.0	H	238.0	8.95
9848.000000	48.46	74.00	25.54	150.0	H	1.0	12.16




Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2390.952381	44.51	74.00	29.49	150.0	V	194.0	-2.22
4920.500000	40.23	74.00	33.77	150.0	V	90.0	5.03
9848.000000	49.93	74.00	24.07	150.0	V	268.0	12.16

Remark:

- (1) Data of measurement within frequency range 18-26GHz are the noise floor or attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so test data does not present in this report,
- (2) These frequencies which exceed the limit are carrier frequency.
- (3) Level= Reading Level + Correction Factor
- (4) Above 1GHz: Corrector factor = Antenna Factor + Cable Loss- Amplifier Gain
Below 1GHz: Corrector factor = Antenna Factor + Cable Loss
(The Reading Level is recorded by software which is not shown in the sheet)

Restricted bands of operation. test result as below:

802.11n20 Modulation 2412MHz



Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Corr. (dB)
2383.780000	48.29	74.00	25.71	150.0	H	155.0	-2.94	---
2390.000000	52.18	74.00	21.82	150.0	H	149.0	-2.93	---
2410.100000	97.61	74.00	-23.61	150.0	H	172.0	-2.89	---

Final Result


Frequency (MHz)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Corr. (dB)
2390.000000	46.77	54.00	7.23	150.0	H	149.0	-2.93	---

Remark:

Level=Reading Level + Correction Factor

Correction Factor=Antenna Factor + Cable Loss – Pre-amplifier

(The Reading Level is recorded by software which is not shown in the sheet)



Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Corr. (dB)
2380.100000	47.42	74.00	26.58	150.0	V	359.0	-2.94	---
2390.000000	52.90	74.00	21.10	150.0	V	0.0	-2.93	---
2410.880000	100.78	74.00	-26.78	150.0	V	359.0	-2.89	---

Final Result

Frequency (MHz)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Corr. (dB)
2390.000000	51.40	54.00	2.60	150.0	V	0.0	-2.93	---


Remark:

Level=Reading Level + Correction Factor

Correction Factor=Antenna Factor + Cable Loss – Pre-amplifier

(The Reading Level is recorded by software which is not shown in the sheet)

802.11n20 Modulation 2462MHz




Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2456.800000	95.80	74.00	-21.80	150.0	H	0.0	-2.73
2483.500000	44.83	74.00	29.17	150.0	H	0.0	-2.60
2500.000000	40.48	74.00	33.52	150.0	H	224.0	-2.51

Remark:

Level=Reading Level + Correction Factor

Correction Factor=Antenna Factor + Cable Loss – Pre-amplifier

(The Reading Level is recorded by software which is not shown in the sheet)



Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2457.860000	97.19	74.00	-23.19	150.0	V	0.0	-2.72
2483.500000	48.13	74.00	25.87	150.0	V	356.0	-2.60
2500.000000	40.70	74.00	33.30	150.0	V	0.0	-2.51

Remark:

Level=Reading Level + Correction Factor

Correction Factor=Antenna Factor + Cable Loss – Pre-amplifier

(The Reading Level is recorded by software which is not shown in the sheet)

10 Test Equipment List

Conducted Emission Test

Description	Manufacturer	Model no.	Equipment ID	Serial no.	Cal interval (year)	Cal. due date
EMI Test Receiver	Rohde & Schwarz	ESR 3	68-4-74-14-001	101782	1	2023-5-27
LISN	Rohde & Schwarz	ENV432	68-4-87-16-001	101318	1	2023-5-27
Attenuator	Shanghai Huaxiang	TS2-26-3	68-4-81-16-003	080928189	1	2023-5-27
Test software	Rohde & Schwarz	EMC32	68-4-90-14-003-A10	Version 9.15.00	N/A	N/A
Shielding Room	TDK	CSR #1	68-4-90-19-004	----	1	2022-11-07

Radiated Emission Test 1#

Description	Manufacturer	Model no.	Equipment ID	Serial no.	Cal interval (year)	Cal. due date
EMI Test Receiver	Rohde & Schwarz	ESR 7	68-4-74-19-001	102176	1	2023-5-27
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	68-4-80-14-002	707	1	2022-7-23
Pre-amplifier	Rohde & Schwarz	SCU 18	68-4-29-14-001	102230	1	2023-5-28
Attenuator	Mini-circuits	UNAT-6+	68-4-81-21-001	15542	1	2023-5-27
3m Semi-anechoic chamber	TDK	SAC-3 #1	68-4-90-14-001	----	2	2023-5-28
Test software	Rohde & Schwarz	EMC32	68-4-90-14-001-A10	Version 10.35.02	N/A	N/A

Radiated Emission Test 2#

Description	Manufacturer	Model no.	Equipment ID	Serial no.	Cal interval (year)	Cal. due date
EMI Test Receiver	Rohde & Schwarz	ESR 26	68-4-74-14-002	101269	1	2023-5-28
Wave Guide Antenna	ETS	3117	68-4-80-19-001	00218954	1	2023-5-9
Pre-amplifier	Rohde & Schwarz	SCU 18F	68-4-29-19-001	100745	1	2023-5-28
Pre-amplifier	Rohde & Schwarz	SCU 18F	68-4-29-19-002	100746	1	2023-5-28
Sideband Horn Antenna	Q-PAR	QWH-SL-18-40-K-SG	68-4-80-14-008	12827	1	2022-7-21
Pre-amplifier	Rohde & Schwarz	SCU 40A	68-4-29-14-002	100432	1	2022-7-27
Attenuator	Mini-circuits	UNAT-6+	68-4-81-21-002	15542	1	2023-5-27
3m Semi-anechoic chamber	TDK	SAC-3 #2	68-4-90-19-006	----	2	2023-5-28
Test software	Rohde & Schwarz	EMC32	68-4-90-19-006-A01	Version 10.35.02	N/A	N/A

RF Conducted Test

Description	Manufacturer	Model no.	Equipment ID	Serial no.	Cal interval (year)	Cal. due date
Signal Analyzer	Rohde & Schwarz	FSV40	68-4-74-14-004	101030	1	2023-5-27

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Conducted Emission 150kHz-30MHz (for test using AMN ENV432)	3.71dB
Uncertainty for Radiated Emission in 3m chamber (68-4-90-14-001)30MHz-1000MHz	Horizontal: 4.68dB; Vertical: 4.65dB;
Uncertainty for Radiated Emission in new 3m chamber (68-4-90-19-006) 1000MHz-18000MHz	Horizontal: 4.76dB; Vertical: 4.75dB;
Uncertainty for Radiated Emission 18000MHz-40000MHz	Horizontal: 4.51dB; Vertical: 4.50dB
Uncertainty for Conducted RF test with TS 8997	RF Power Conducted: 1.27dB Frequency test involved: 0.6×10^{-7} or 1%

Measurement Uncertainty Decision Rule

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2007, clause 4.4.3 and 4.5.1.

---THE END OF REPORT---