



1250 Peterson Dr., Wheeling, IL 60090

Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

FCC Rules and Regulations / Intentional Radiators

Low Power Auxiliary Stations

Part 74, Subpart H, Sections 74.801 - 74.882

Part 74.861 (d) Other than TV Broadcasting

THE FOLLOWING "MEETS" THE ABOVE TEST SPECIFICATION

Formal Name: Wireless Boundary Microphone

Kind of Equipment: Wireless Microphone Transmitter

Test Configuration: Stand Alone (Tested at 3 vdc)

Model Number(s): MX690H5

Model(s) Tested: MX690H5

Serial Number(s): NA

Emission Designator: 120KF3E

Date of Tests: July 5, 12, & 13, 2007

Test Conducted For:
Shure Incorporated
5800 West Touhy Ave.
Niles, Illinois 60714-4608

NOTICE: "This report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government". Please see the "Additional Description of Equipment Under Test" page listed inside of this report.

© Copyright 1983- 2006 D.L.S. Electronic Systems, Inc

COPYRIGHT NOTICE

This report or any portion their of, may not be reproduced or modified in any form without the expressed written consent of D.L.S. Electronic Systems, Inc.



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

SIGNATURE PAGE

Report By:

A handwritten signature in black ink that reads "Aron C. Rowe".

Aron C. Rowe
Test Engineer
EMC-001375-NE

Reviewed By:

A handwritten signature in black ink that reads "William Stumpf".

William Stumpf
OATS Manager

Approved By:

A handwritten signature in black ink that reads "Brian J. Mattson".

Brian Mattson
General Manager

Company Official:

Shure Incorporated



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

TABLE OF CONTENTS

| | | |
|------|---|----|
| i. | Cover Page | 1 |
| ii. | Signature Page | 2 |
| iii. | Table of Contents | 3 |
| iv. | NVLAP Certificate of Accreditation | 5 |
| 1.0 | Summary of Test Report | 6 |
| 2.0 | Introduction | 6 |
| 3.0 | Object | 6 |
| 4.0 | Test Set-Up | 7 |
| 5.0 | Test Equipment | 8 |
| 6.0 | Ambient Measurements | 9 |
| 7.0 | AC Power Line Conducted Emission Measurements | 9 |
| 8.0 | Description of Test Sample | 10 |
| 9.0 | Photo Information and Test Set-Up | 11 |
| 10.0 | Radiated Photos Taken During Testing | 12 |
| 10.0 | RF Conducted Photos Taken During Testing | 13 |
| 11.0 | Results of Tests | 14 |
| 12.0 | Conclusion | 14 |
| | TABLE 1 – EQUIPMENT LIST | 15 |



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

TABLE OF CONTENTS


| | |
|--|----|
| Appendix A – Electric Field Radiated Emissions Test..... | 17 |
| 1.0 Test Set-Up | 18 |
| 2.0 RF Power Output | 18 |
| 2.0 Data taken of the RF Power Output..... | 19 |
| 3.0 RF Power Output Photos Taken During Testing | 23 |
| 4.0 Modulation Characteristics | 24 |
| 4.0 Graph(s) taken of the Modulation Characteristics | 25 |
| 5.0 Occupied Bandwidth..... | 29 |
| 5.0 Data and Graph(s) taken of the 99% Occupied Bandwidth..... | 30 |
| 5.0 Data and Graph(s) taken of the Emission Mask | 34 |
| 6.0 Spurious Emissions At Antenna Terminals | 44 |
| 7.0 Field Strength of Spurious Emission Measurements | 45 |
| 7.0 Radiated Data and Charts taken for Fundamental Emissions using the Substitution Method..... | 47 |
| 7.0 Radiated Data and Graph(s) Taken During Testing for Spurious Emissions | 49 |
| 8.0 Frequency Stability (Temperature) | 59 |
| 9.0 Frequency Stability (Voltage Variation)..... | 59 |
| 8.0 & 9.0 Data Taken During Testing for Frequency Stability Temperature & Voltage Variation | 60 |
| 10.0 Frequency Stability Photos Taken During Testing..... | 62 |



1250 Peterson Dr., Wheeling, IL 60090

Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

United States Department of Commerce
National Institute of Standards and Technology



Certificate of Accreditation to ISO/IEC 17025:2005

NVLAP LAB CODE: 100276-0

D.L.S. Electronic Systems, Inc.
Wheeling, IL

is accredited by the National Voluntary Laboratory Accreditation Program for specific services,
listed on the Scope of Accreditation, for:

ELECTROMAGNETIC COMPATIBILITY AND TELECOMMUNICATIONS

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to Joint ISO/IEC/IAF Communique dated 18 June 2005).



2006-10-01 through 2007-09-30
Effective dates

Jeffrey A. Bruce
For the National Institute of Standards and Technology

NVLAP-01C (REV. 2006-09-13)



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

1.0 SUMMARY OF TEST REPORT

It was found that the Wireless Boundary Microphone, Model Number(s) MX690H5, "meets" the radio interference radiated emission requirements of the FCC "Rules and Regulations", Part 74, Subpart H, Section 74.861 (d), for low power auxiliary stations. The AC Power Line conducted emissions test was not required because the Wireless Boundary Microphone is powered from a D.C. power source. It does not have a line cord to plug into the A.C. power line.

2.0 INTRODUCTION

On July 5, 12, & 13, 2007, a series of radio frequency interference measurements was performed on Wireless Boundary Microphone, Model Number(s) MX690H5, Serial Number: NA. The tests were performed according to the procedures of the FCC as stated in Part 2 - Frequency Allocations and Radio Treaty Matters: General Rules and Regulations, Subpart J, Equipment Authorization Procedures of the Code of Federal Regulations 47. Tests were performed by personnel of D.L.S. Electronic Systems, Inc. who are responsible to Donald L. Sweeney, Senior EMC Engineer.

D.L.S. Electronic Systems, Inc. is a full service EMC/Safety Testing Laboratory accredited to ISO Guide 17025. NVLAP Certificate and Scope can be viewed at <http://www.dlsemc.com/certificate>. Our facilities are registered with the FCC, Industry Canada, and VCCI. All immunity tests were performed by personnel of D.L.S. Electronic Systems, Inc. at the following location(s):

Main Test Facility:
D.L.S. Electronic Systems, Inc.
1250 Peterson Drive
Wheeling, Illinois 60090

3.0 OBJECT

The purpose of this series of tests was to determine if the test sample could meet the radio frequency interference requirements of the FCC "Rules and Regulations", Part 74, Subpart H, Section 74.861 (d), for low power auxiliary stations.



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

4.0 TEST SET-UP

All tests were performed at D.L.S. Electronic Systems, Inc. and set up according to the American National Standards Institute, ANSI C63.4-2003. The AC Power Line conducted tests if required were performed with the test item placed on a non-conductive table (table top equipment), located in the test room. Equipment normally operated on the floor was tested by placing it on the metal ground plane. The ground plane has an electrical isolation layer over its surface approximately 7mm thick. The power line supplied was connected to a dual line impedance stabilization network electrically bonded to the ground plane, located on the floor. The networks were constructed per the requirements of the American National Standards Institute, ANSI C63.4-2003.

All radiated emissions tests were performed with the test item placed on a 80 cm high rotating non-conductive table, located in the test room. Equipment normally operated on the floor was placed on a metal covered turntable, which is flush with the surrounding conducting ground plane. The ground plane has an electrical isolation layer over its surface approximately 7 mm thick. The EUT is separated from the turntable ground plane by a non-conductive layer. The equipment under test was set up according to TIA Standard, TIA-603-C:2004, Section 2.2.12.



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

5.0 TEST EQUIPMENT (Bandwidths and Detector Function)

All preliminary data below 1000 MHz was automatically plotted using the HP Spectrum Analyzer or ESI 26/ESI 40 Fixed Tuned Receiver. The data was taken using Peak, Quasi-Peak or the Average Detector Functions as required. This information was then used to determine the frequencies of maximum emissions. Above 1000 MHz, final data was taken using the Average Detector.

Below 1000 MHz, final data was taken using the HP Spectrum Analyzer and or ESI 26/ESI 40 fixed tuned receiver. These plots were made using the Peak or Quasi-Peak Detector functions, with manual measurements performed on the questionable frequencies using the Quasi-Peak or the Average Detector Function of the Analyzer or ESI 26/ESI 40 Receiver as required. Above 1000 MHz, final data was taken using the Average Detector on the ESI 26/ESI 40 Fixed Tuned Receiver.

The bandwidths shown below are specified by ANSI C63.4-2003.

| Frequency Range | Bandwidth (-6 dB) |
|-------------------|-------------------|
| 10 to 150 kHz | 200 Hz |
| 150 kHz to 30 MHz | 9 kHz |
| 30 MHz to 1 GHz | 120 kHz |
| Above 1 GHz | 1 MHz |

A list of the equipment used can be found in Table 1. All primary equipment was calibrated against known reference standards with a verified traceable path to NIST.



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

6.0 AMBIENT MEASUREMENTS

For emissions measurements, broadband antennas and an EMI Test Receiver with a panoramic spectrum display are used. First the frequency range is scanned and displayed on the test receiver display. Next the scanned frequency range is divided into smaller ranges, and then it is manually tuned through to determine the emissions from the EUT. A headset or loudspeaker is connected to the test receiver's AM/FM demodulated output as an aid in detecting ambient signals and finding frequencies of significant emission from the EUT. If there is any doubt as to the source of the emission, it is further investigated by rotating the EUT, or by disconnecting the power from the EUT.

The EUT is set up in its typical configuration and operated in its various modes. For tabletop systems, cables are manipulated within the range of likely configurations. For floor-standing equipment, the cables are located in the same manner as the user would install them and no further manipulation is made. If the manner of cable installation is not known, or if it changes with each installation, cables or wires for floor-standing equipment shall be manipulated to the extent possible to produce the maximum level of emissions. For each mode of operation, the frequency spectrum is monitored. Variations in antenna height, antenna polarization, EUT azimuth, and cable or wire placement (each variable within bounds specified elsewhere) are explored to produce the emission that has the highest amplitude relative to the limit. These methods are performed to the specifications in ANSI C63.4-2003.

7.0 AC POWER LINE CONDUCTED EMISSION MEASUREMENTS – Part 15.207

The Wireless Boundary Microphone is powered from a D.C. power source and will not at any time be directly plugged into the public utility lines, therefore the AC Power Line conducted emissions test was not performed.



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

8.0 DESCRIPTION OF TEST SAMPLE:

8.1 Description:

The Shure Model MX690 is a uP (microprocessor) controlled frequency agile UHF transmitter operating over the frequency range of 518 to 865 MHz (in nine different frequency bands). The products are identical, with the exception of the frequency components needed for each range. The User Interface includes "mode", "set" and "mute" buttons, and an LCD that displays battery status, group/channel, and transmitter/receiver frequency synchronization. This product is intended for corporate boardroom, educational facilities and fixed installations.

The unit will operate on two "AA" alkaline batteries which are placed in the battery compartment. The unit is turned on by holding the power button (on bottom of EUT) for 3 seconds, the LED around the Push button (on top of EUT) should turn Green.

8.2 PHYSICAL DIMENSIONS OF EQUIPMENT UNDER TEST

Length: 148 mm x 87mm Width: x 43 mm Height:

8.3 LINE FILTER USED:

NA

8.4 INTERNAL CLOCK FREQUENCIES:

Switching Power Supply Frequencies:

NA

Clock Frequencies:

0.32768 MHz & 16 MHz

8.5 DESCRIPTION OF ALL CIRCUIT BOARDS:

1. Printed Circuit Board 1

PN: 190-11080 Rev.01

2. Printed Circuit Board 2

PN: 190A11076 Rev.01



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

9.0 PHOTO INFORMATION AND TEST SET-UP


Item 0 Wireless Boundary Microphone
Model Number: MX690H5, Serial Number: NA



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

10.0 RADIATED PHOTOS TAKEN DURING TESTING






Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

10.0 RF CONDUCTED PHOTOS TAKEN DURING TESTING





Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

11.0 RESULTS OF TESTS

The radio interference emission charts can be seen on the pages at the end of this report. Data sheets indicating the test measurements taken during testing can also be found at the end of this report.

12.0 CONCLUSION

It was found that the Wireless Boundary Microphone, Model Number(s) MX690H5 "meets" the radio interference radiated emission requirements of the FCC "Rules and Regulations", Part 74, Subpart H, Section 74.861 (d), for low power auxiliary stations. The conducted emissions test was not required because the Wireless Boundary Microphone is powered from a D.C. power source. It does not have a line cord to plug into the A.C. power line.



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

TABLE 1 – EQUIPMENT LIST

| Test Equipment | Manufacturer | Model Number | Serial Number | Frequency Range | Cal Due Dates |
|----------------|-----------------|--------------|---------------|------------------|---------------|
| Receiver | Rohde & Schwarz | ESI 26 | 837491/010 | 20 Hz – 26 GHz | 11/07 |
| Receiver | Rohde & Schwarz | ESI 40 | 837808/006 | 20 Hz – 40 GHz | 12/07 |
| Receiver | Rohde & Schwarz | ESI 40 | 837808/005 | 20 Hz – 40 GHz | 12/07 |
| Antenna | EMCO | 3104C | 00054891 | 20 MHz – 200 MHz | 2/08 |
| Antenna | Electrometrics | LPA-25 | 1114 | 200 MHz – 1 GHz | 3/08 |
| Antenna | EMCO | 3104C | 00054892 | 20 MHz – 200 MHz | 3/08 |
| Antenna | Electrometrics | 3146 | 1205 | 200 MHz – 1 GHz | 3/08 |
| Antenna | EMCO | 3104C | 97014785 | 20 MHz – 200 MHz | 2/08 |
| Antenna | EMCO | 3146 | 97024895 | 200 MHz – 1 GHz | 3/08 |
| Antenna | EMCO | 3115 | 2479 | 1 GHz – 18 GHz | 5/08 |
| Antenna | EMCO | 3115 | 99035731 | 1 GHz – 18 GHz | 6/08 |
| Antenna | Rohde & Schwarz | HUF-Z1 | 829381001 | 20 MHz – 1 GHz | 2/08 |
| Antenna | Rohde & Schwarz | HUF-Z1 | 829381005 | 20 MHz – 1 GHz | 8/07 |

All primary equipment is calibrated against known reference standards with a verified traceable path to NIST.



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

TABLE 1 – EQUIPMENT LIST

| Test Equipment | Manufacturer | Model Number | Serial Number | Frequency Range | Cal Due Dates |
|----------------|--------------|------------------|---------------|-----------------|---------------|
| LISN | Solar | 8012-50-R-24-BNC | 8305116 | 10 MHz – 30 MHz | 8/07 |
| LISN | Solar | 8012-50-R-24-BNC | 814548 | 10 MHz – 30 MHz | 8/07 |
| LISN | Solar | 9252-50-R-24-BNC | 961019 | 10 MHz – 30 MHz | 12/07 |
| LISN | Solar | 9252-50-R-24-BNC | 971612 | 10 MHz – 30 MHz | 10/07 |
| LISN | Solar | 9252-50-R-24-BNC | 92710620 | 10 MHz – 30 MHz | 7/08 |

All primary equipment is calibrated against known reference standards with a verified traceable path to NIST.



1250 Peterson Dr., Wheeling, IL 60090

Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

APPENDIX A

TEST PROCEDURE

SUBPART H

LOW POWER AUXILIARY STATIONS



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

1.0 TEST SET-UP

All radiated emission tests were performed at D.L.S. Electronic Systems, Inc. The radiated tests were made with the test item placed on a non-conductive turntable located in the Test Room with the receive antenna placed three or one meter(s) from the device under test.

2.0 RF-POWER OUTPUT – PART 2.1046 and EIA /TIA-603-C:2004, SECTION 2.2.17

As stated in PART 74.861 (d)(1), the RF output power should not exceed 1 watt(s). The RF output of the Wireless Boundary Microphone was connected to a Spectrum Analyzer through suitable attenuation. All cables, connectors, and attenuators were calibrated prior to testing. The RF output power was measured using the following test method:

Actual Measurements Taken:

8.46 dBm Measured output of the transmitter

8.46 dBm equals 0.00701 watt(s)

LIMIT:

Manufacturer's rated output power = 7.9 dBm ± 2 dB

MARGIN:

$1 - 0.00701 = 0.993$ watt(s)



1250 Peterson Dr., Wheeling, IL 60090

Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

APPENDIX A

DATA TAKEN OF THE RF POWER OUTPUT MEASUREMENT

EIA /TIA-603-C:2004, SECTION 2.2.17

FCC Part 74.861(d)(1) & PART 2.1046




Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

Test Date: 07-12-2007
Company: Shure, Inc.
EUT: MX690-H5
Test: Peak Power Output - Conducted
Rule part: FCC Part 74; FCC Part 2.1046
Operator: Craig B
Comment: Channel: 518.2 MHz

Peak Output Power = 7.92 dBm = 6.19 mW






Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

Test Date: 07-12-2007
Company: Shure, Inc.
EUT: MX690-H5
Test: Peak Power Output - Conducted
Rule part: FCC Part 74; FCC Part 2.1046
Operator: Craig B
Comment: Channel: 530.5 MHz

Peak Output Power = 8.46 dBm = 7.01 mW






Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

Test Date: 07-12-2007
Company: Shure, Inc.
EUT: MX690-H5
Test: Peak Power Output - Conducted
Rule part: FCC Part 74; FCC Part 2.1046
Operator: Craig B
Comment: Channel: 541.8 MHz

Peak Output Power = 8.02 dBm = 6.34 mW






Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

3.0 RF POWER OUTPUT PHOTOS TAKEN DURING TESTING



CONDUCTED RF OUTPUT POWER



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

4.0 MODULATION CHARACTERISTICS – PART 2.1047 and EIA /TIA-603-C:2004, SECTION 2.2.3

a. Voice modulated communication equipment.

A curve showing the frequency response of the audio modulating circuit over a range of 50 Hz - 20 kHz ± 3 dB Hz is submitted with this report.

b. Equipment which employs modulation limiting

A family of curves showing the percentage of modulation versus the modulation input voltage with sufficient information showing the modulation limiting capability throughout the range of modulating frequencies and input modulating signal levels employed.



1250 Peterson Dr., Wheeling, IL 60090

Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

APPENDIX A

GRAPH(S) TAKEN SHOWING THE FREQUENCY

RESPONSE OF THE

AUDIO MODULATING CIRCUIT

EIA /TIA-603-C:2004, SECTION 2.2.3


PART 2.1047



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A





Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A





1250 Peterson Dr., Wheeling, IL 60090

Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

APPENDIX A

MX690- H5 #1

Note: Frequency response switch is set to full range setting for these measurements.

Audio Limiting

| LEVEL INPUT | DEVIATION (KHz) AT | | | | |
|-------------|--------------------|-------|--------|---------|---------|
| | 100Hz | 500Hz | 2500Hz | 10000Hz | 15000Hz |
| -70 | 11.92 | 12.26 | 17.46 | 19.19 | 19.03 |
| -60 | 15.10 | 17.48 | 21.40 | 23.18 | 22.80 |
| -50 | 21.18 | 21.84 | 26.12 | 28.67 | 28.24 |
| -40 | 25.43 | 26.96 | 32.73 | 36.14 | 35.56 |
| -30 | 32.07 | 33.93 | 41.50 | 45.66 | 44.97 |
| -20 | 40.61 | 43.11 | 48.76 | 47.97 | 47.34 |
| -10 | 51.62 | 51.40 | 50.10 | 48.92 | 48.19 |

Audio Frequency Response

| UR1 | INPUT : -70dBV |
|----------------|-----------------|
| FREQUENCY (Hz) | DEVIATION (KHz) |
| 20 | 10.67 |
| 50 | 11.88 |
| 100 | 11.64 |
| 500 | 12.82 |
| 1000 | 13.86 |
| 2000 | 16.69 |
| 4000 | 18.73 |
| 5000 | 19.03 |
| 6300 | 19.16 |
| 8000 | 19.11 |
| 10000 | 19.3 |
| 12500 | 19.46 |
| 16000 | 18.97 |
| 20000 | 18.51 |



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

5.0 OCCUPIED BANDWIDTH - PART 2.1049

The occupied bandwidth is that between the lower and upper limits of the signal where the mean power is 99.0% of the total mean power and measured under the following conditions:

For low power auxiliary stations operating in the bands other than those allocated for TV broadcasting, the occupied bandwidth shall not be greater than that necessary for satisfactory transmission and emissions appearing on any discrete frequency outside the authorize band shall be attenuated $43+10 \log^{10}$ (mean output power, in watts) dB below the mean output power of the transmitting unit (device under test).

For low power auxiliary stations operating in the bands allocated for TV broadcasting, any form of modulation may be used. A maximum of ± 75 kHz is permitted when frequency modulation is used. The operating bandwidth shall not exceed 200 kHz.

Carson's Rule:

Section 2.202 (g)

$Bn = 2M + 2DK$, $K=1$

Bn = Bandwidth

$M = 15$ kHz,

M = Maximum Modulating Frequency

$D = 45$ kHz,

D = Peak Deviation

$$\mathbf{Bn = 2(15) + 2(45)(1) = 120 kHz}$$

NOTE:

The emissions mask measurements results were verified by using 2 kHz resolution bandwidth and 2 kHz video bandwidth. The 1.2 kHz was determined by taking 1% of the worst case measurement of 121.8 kHz, which yields 1.2 kHz.



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

DATA AND GRAPH(S) TAKEN OF THE

99% OCCUPIED BANDWIDTH

Part 74.861(d)(3) & PART 2.1049



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478


1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

Test Date: 07-12-2007
Company: Shure, Inc.
EUT: MX690-H5
Test: Occupied Bandwidth; 99% bandwidth
Rule part: FCC Part 74; FCC Part 2.1049
Operator: Craig B

Frequency: 518.2 MHz

99% power bandwidth = 121.8 kHz





Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478


1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

Test Date: 07-12-2007
Company: Shure, Inc.
EUT: MX690-H5
Test: Occupied Bandwidth; 99% bandwidth
Rule part: FCC Part 74; FCC Part 2.1049
Operator: Craig B

Frequency: 530.5 MHz

99% power bandwidth = 120.6 kHz





Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478


1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

Test Date: 07-12-2007
Company: Shure, Inc.
EUT: MX690-H5
Test: Occupied Bandwidth; 99% bandwidth
Rule part: FCC Part 74; FCC Part 2.1049
Operator: Craig B

Frequency: 541.8 MHz

99% power bandwidth = 119.8 kHz



Date: 12.JUL.2007 13:29:29



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

DATA AND GRAPH(S) TAKEN OF THE EMISSION MASK

Part 74.861(d)(3) & PART 2.1049




Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

Test Date: 07-12-2007
Company: Shure, Inc.
EUT: MX690-H5
Test: Emission Mask
Rule Part: FCC Part 74
Operator: Craig B

Nominal Frequency: 518.2 MHz
Unmodulated



Date: 12.JUL.2007 09:15:47




Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

Test Date: 07-12-2007
Company: Shure, Inc.
EUT: MX690-H5
Test: Emission Mask
Rule Part: FCC Part 74
Operator: Craig B

Nominal Frequency: 518.2 MHz
15 kHz 85% modulated



Date: 12.JUL.2007 09:33:06




Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

Test Date: 07-12-2007
Company: Shure, Inc.
EUT: MX690-H5
Test: Emission Mask
Rule Part: FCC Part 74
Operator: Craig B

Nominal Frequency: 518.2 MHz
2500 Hz 16 dB > 50% modulated






Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

Test Date: 07-12-2007
Company: Shure, Inc.
EUT: MX690-H5
Test: Emission Mask
Rule Part: FCC Part 74
Operator: Craig B

Nominal Frequency: 530.5 MHz
Unmodulated



Date: 12.JUL.2007 10:26:23




Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

Test Date: 07-12-2007
Company: Shure, Inc.
EUT: MX690-H5
Test: Emission Mask
Rule Part: FCC Part 74
Operator: Craig B

Nominal Frequency: 530.5 MHz
15 kHz 85% modulated



Date: 12.JUL.2007 10:33:08




Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

Test Date: 07-12-2007
Company: Shure, Inc.
EUT: MX690-H5
Test: Emission Mask
Rule Part: FCC Part 74
Operator: Craig B

Nominal Frequency: 530.5 MHz
2500 Hz 16 dB > 50% modulated



Date: 12.JUL.2007 10:28:01




Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

Test Date: 07-12-2007
Company: Shure, Inc.
EUT: MX690-H5
Test: Emission Mask
Rule Part: FCC Part 74
Operator: Craig B

Nominal Frequency: 541.8 MHz
Unmodulated






Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

Test Date: 07-12-2007
Company: Shure, Inc.
EUT: MX690-H5
Test: Occupied Bandwidth / emission mask
Rule Part: FCC Part 74
Operator: Craig B

Nominal Frequency: 541.8 MHz
15 kHz 85% modulated



Date: 12.JUL.2007 10:39:08




Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

Test Date: 07-12-2007
Company: Shure, Inc.
EUT: MX690-H5
Test: Emission Mask
Rule Part: FCC Part 74
Operator: Craig B

Nominal Frequency: 541.8 MHz
2500 Hz 16 dB > 50% modulated






Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

6.0 SPURIOUS EMISSIONS AT ANTENNA TERMINALS – PART 2.1051 and EIA /TIA-603-C:2004, SECTION 2.2.13

Spurious conducted emissions were measured at the antenna terminals using an artificial load. Plots were made showing the amplitude of each harmonic emission with the equipment operated as specified in 2.989. Measurements were made up to the 10th harmonic of the fundamental. The following setup was used showing placement of the attenuators:



The allowed emissions for transmitters operating in the 518 MHz - 542 MHz bands for Wireless Boundary Microphone equipment are found under Part 74, Section 74.861, Paragraph d-3 for Low Power Auxiliary Stations. This paragraph states the mean power of the emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

- (1) any discrete frequency outside the authorized band shall be attenuated, at least, $43+10\log^{10}$ (mean output power, in watts) dB below the mean output power of the transmitting unit.

NOTE:

The Wireless Boundary Microphone uses a bent Monopole permanently attached to the Flex PCB preventing any connection to the Antenna Port therefore, this test was not run.



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

7.0 FIELD STRENGTH OF SPURIOUS EMISSION MEASUREMENTS – PART 2.1053 and EIA /TIA-603-C:2004, SECTION 2.2.12

Radiated measurements were performed scanning the frequency range from 200 MHz to at least the 10th harmonic of depending upon the fundamental frequency.

For the Wireless Boundary Microphone, the highest fundamental frequency is 704 MHz so the scans were made up to 10000 MHz, to cover the tenth harmonic.

All signals in the frequency range of 30 MHz to 200 MHz were measured with a Biconical Antenna and from 200 MHz to 1000 MHz a Log Periodic Antenna was used as the pickup devices. From 1000 MHz to 10000 MHz, a Double Ridge Horn Antenna was used. The cables and equipment were placed and moved within the range of positions likely to find their maximum emissions. Tests were made in both the horizontal and vertical planes of polarization.

The allowed emissions for transmitters operating in the 518 MHz - 542 MHz bands for Wireless Boundary Microphone are found under Part 74, Section 74.861, Paragraph d-3 for Low Power Auxiliary Stations. This paragraph states that the mean power of the emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:

- (1) any discrete frequency outside the authorized band shall be attenuated, at least, $43+10\log_{10}$ (mean output power, in watts) dB below the mean output power of the transmitting unit.



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

7.0 FIELD STRENGTH OF SPURIOUS EMISSION MEASUREMENTS (CON'T) – PART 2.1053 and EIA /TIA-603-C:2004, SECTION 2.2.12

As stated in Part 74, Section 74.861 (d-1) the limit is 1 Watt in the frequency range 518 MHz – 542 MHz.

To determine the LIMIT for Spurious Emissions the following method was used:

Mean output power in watts:

Manufacturer's rated wattage = **7.9 dBm ± 2 dB Watt(s)**
(See Paragraph 2.0, page 2 of this Appendix)

Free Space Formula

Convert to 10 meter test distance using the Free Space Formula

$$\frac{\sqrt{49.2 * \text{rated wattage}}}{\text{Distance}} = 5.433231\text{E-02} \text{ volts/meter} = 54332.31 \text{ uV/m}$$

$$20 * \text{Log}(54332.31) = 94.70116 \text{ dBuV}$$

Therefore, the Fundamental at three meters equals 94.70116 dBuV,

The emissions must be reduced by:

$$43 + 10 * \text{LOG10}(0.006 \text{ watts}) = 20.78151 \text{ dB}$$

Therefore, the LIMIT at ten meters equals:

94.70116 dBuV extrapolated level for 0.006 watts
-20.78151 dB required reduction below the unmodulated fundamental
73.91965 dBuV maximum spurious emissions allowed



1250 Peterson Dr., Wheeling, IL 60090

Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

APPENDIX A

RADIATED EMISSION DATA & CHARTS TAKEN FOR FUNDAMENTAL EMISSIONS USING THE SUBSTITUTION METHOD

EIA /TIA-603-C:2004, SECTION 2.2.12



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

DLS Electronic Systems, Inc.

Company: Shure, Inc.

Operator: Craig B

Date of test: 07-05-2007

Temperature: 72 deg. F

Humidity: 59% R.H.

Spurious Emissions - ERP - Substitution Method

| Model: MX 690-H5 | | | | | | | | |
|---|--|---|---|------------------------------|----------------------------------|-------------|-------------|---------------------------------|
| Channels: 518.2 MHz, 530.5 MHz, and 541.8 MHz | | | | | | | | |
| Frequency and Polarization (MHz) | Max. Field Strength of EUT @ 3 meters (dBuV/m) | Output of Signal Generator when field strength equals that of EUT (dBm) | Correction factor for cable between Signal Gen. and subst. antenna (dB) | Gain of subst. antenna (dBi) | Strength of emission [ERP] (dBm) | Limit (dBm) | Margin (dB) | Strength of emission [ERP] (mW) |
| 518.2 vertical | 79.3 | -14.0 | 8.0 | 2.15 | -22.0 | 24.0 | 46.0 | 0.01 |
| 518.2 horizontal | 86.3 | -3.6 | 8.0 | 2.15 | -11.6 | 24.0 | 35.6 | 0.07 |
| 530.5 vertical | 79.5 | -11.6 | 8.2 | 2.15 | -19.8 | 24.0 | 43.8 | 0.01 |
| 530.5 horizontal | 86.4 | -4.1 | 8.2 | 2.15 | -12.3 | 24.0 | 36.3 | 0.06 |
| 541.8 vertical | 80.0 | -10.7 | 8.3 | 2.15 | -19.0 | 24.0 | 43.0 | 0.01 |
| 541.8 horizontal | 88.2 | -2.2 | 8.3 | 2.15 | -10.5 | 24.0 | 34.5 | 0.09 |

EIRP = Signal generator output - cable loss + antenna gain

ERP_(ref. to 1/2λ dipole) = Signal generator output - cable loss + antenna gain - 2.15



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

RADIATED EMISSION DATA AND GRAPH(S)

TAKEN FOR

SPURIOUS EMISSION MEASUREMENTS

EIA /TIA-603-C:2004, SECTION 2.2.12

PART 2.1053

Electric Field Strength

EUT: MX 690
Manufacturer: Shure Inc
Operating Condition: 72 deg F; 63% R.H.
Test Site: D.L.S. O.F. Site 3
Operator: Tim O
Test Specification:
Comment: Date: 07-13-2007

TEXT: "Site 3 MidV 10M"


Short Description: Test Set-up Vert30-1000MHz
TEST EQUIPMENT: Receiver --- Rohde&Schwarz ESI 40 SN: 837808/005

Antennas ---
Biconical -- EMCO 3104C SN: 9701-4785
Log Periodic -- EMCO 3146 SN: 9702-4895

Pre-Amp --- Rohde&Schwarz TS-PR10 SN: 032001/005

TEST SET-UP: EUT Measured at 10 Meters with VERTICAL Antenna Polarization

Level [dB μ V/m]



| | | |
|----|------|----------------------|
| | MES | AMX69_F1V_Quasi-Peak |
| ++ | +MES | AMX69_F1V_Peak_List |
| — | LIM | CISPR 22B F QP |

Field Strength QP Limit

MEASUREMENT RESULT: "AMX69_F1V_Final"

7/13/2007 10:56AM

| Frequency MHz | Level dB μ V | Antenna Factor dB μ V/m | System Loss dB | Total Level dB μ V/m | Limit dB μ V/m | Margin dB | Height Ant. m | EuT Angle deg | Final Detector | Comment |
|------------------|---------------------|-----------------------------------|----------------------|--------------------------------|-----------------------|--------------|---------------------|---------------------|-------------------|-------------|
| 85.080000 | 28.93 | 7.18 | -23.4 | 12.7 | 30.0 | 17.3 | 1.00 | 0 | QUASI-PEAK | Noise Floor |
| 165.180000 | 17.06 | 14.12 | -22.7 | 8.5 | 30.0 | 21.5 | 1.00 | 0 | QUASI-PEAK | Noise Floor |
| 322.880000 | 16.56 | 14.03 | -21.1 | 9.5 | 37.0 | 27.5 | 1.00 | 0 | QUASI-PEAK | Noise Floor |

Electric Field Strength

EUT: MX 690
Manufacturer: Shure Inc
Operating Condition: 72 deg F; 63% R.H.
Test Site: D.L.S. O.F. Site 3
Operator: Tim O
Test Specification:
Comment: Date: 07-13-2007

TEXT: "Site 3 MidH 10M"


Short Description: Test Set-up Horz30-1000MHz
TEST EQUIPMENT: Receiver --- Rohde&Schwarz ESI 40 SN: 837808/005

Antennas ---
Biconical -- EMCO 3104C SN: 9701-4785
Log Periodic -- EMCO 3146 SN: 9702-4895

Pre-Amp --- Rohde&Schwarz TS-PR10 SN: 032001/005

TEST SET-UP: EUT Measured at 10 Meters with HORIZONTAL Antenna Polarization

Level [dB μ V/m]



||||| MES AMX69_F1H_Quasi-Peak
+ + +MES AMX69_F1H_Peak_List
— LIM CISPR 22B F QP Limit

Field Strength QP Limit

MEASUREMENT RESULT: "AMX69_F1H_Final"

7/13/2007 10:56AM

| Frequency MHz | Level dB μ V | Antenna Factor dB μ V/m | System Loss dB | Total Level dB μ V/m | Limit dB μ V/m | Margin dB | Height Ant. m | EuT Angle deg | Final Detector | Comment |
|------------------|---------------------|-----------------------------------|----------------------|--------------------------------|-----------------------|--------------|---------------------|---------------------|-------------------|-------------|
| 114.720000 | 18.10 | 12.18 | -23.1 | 7.2 | 30.0 | 22.8 | 3.00 | 0 | QUASI-PEAK | Noise Floor |
| 52.740000 | 20.31 | 10.78 | -24.1 | 7.0 | 30.0 | 23.0 | 3.00 | 0 | QUASI-PEAK | Noise Floor |
| 295.700000 | 16.52 | 13.36 | -21.2 | 8.7 | 37.0 | 28.3 | 3.00 | 0 | QUASI-PEAK | Noise Floor |



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

DLS Electronic Systems, Inc.

Company: Shure, Inc.

Operator: Craig Brandt

Date of test: 07-05-2007

Temperature: 72 deg. F.

Humidity: 59% R.H.

| Radiated Spurious Emissions (e.r.p. substitution method) FCC Part 74; FCC Part 2.1053 | | | | | | | | |
|---|-----------------------------------|--------------------------------|---------------------|--------------|--------------|------------------------------------|-------------------------------|----------------------------------|
| Model: MX690-H5 Transmit Frequency: 518.2 MHz | | | | | | | | |
| Frequency GHz | Field Strength Level dBuV/m | Factor to Convert to dBm | Power ERP dBm | Limit dBm | Margin dB | Receive Antenna Polarization | EUT Antenna Orientation | Receive Antenna Height (m) |
| 1.5546 | 27.48 | 99.9 | -72.42 | -13 | 59.42 | Horizontal | 135 | 1.5 |
| 2.0728 | 29.72 | 100.7 | -70.93 | -13 | 57.93 | Horizontal | 225 | 1.5 |
| 1.5546 | 26.73 | 101.2 | -74.42 | -13 | 61.42 | Vertical | 90 | 1.4 |
| 2.0728 | 34.34 | 99.9 | -65.51 | -13 | 52.51 | Vertical | 0 | 1.2 |



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

DLS Electronic Systems, Inc.

Company: Shure, Inc.

Operator: Craig Brandt

Date of test: 07-05-2007

Temperature: 72 deg. F.

Humidity: 59% R.H.

| Radiated Spurious Emissions (e.r.p. substitution method) FCC Part 74; FCC Part 2.1053 | | | | | | | | |
|---|-----------------------------------|--------------------------------|---------------------|--------------|--------------|------------------------------------|-------------------------------|----------------------------------|
| Model: MX690-H5 Transmit Frequency: 530.5 MHz | | | | | | | | |
| Frequency GHz | Field Strength Level dBuV/m | Factor to Convert to dBm | Power ERP dBm | Limit dBm | Margin dB | Receive Antenna Polarization | EUT Antenna Orientation | Receive Antenna Height (m) |
| 1.5915 | 32.03 | 100.1 | -68.02 | -13 | 55.02 | Horizontal | 45 | 1.2 |
| 2.122 | 30.25 | 100.9 | -70.60 | -13 | 57.60 | Horizontal | 290 | 2.0 |
| 1.5915 | 27.36 | 101.2 | -73.79 | -13 | 60.79 | Vertical | 315 | 1.2 |
| 2.122 | 31.94 | 99.5 | -67.51 | -13 | 54.51 | Vertical | 0 | 1.0 |



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

DLS Electronic Systems, Inc.

Company: Shure, Inc.

Operator: Craig Brandt

Date of test: 07-05-2007

Temperature: 72 deg. F.

Humidity: 59% R.H.

| Radiated Spurious Emissions (e.r.p. substitution method) FCC Part 74; FCC Part 2.1053 | | | | | | | | |
|---|-----------------------------------|--------------------------------|---------------------|--------------|--------------|------------------------------------|-------------------------------|----------------------------------|
| Model: MX690-H5 Transmit Frequency: 541.8 MHz | | | | | | | | |
| Frequency GHz | Field Strength Level dBuV/m | Factor to Convert to dBm | Power ERP dBm | Limit dBm | Margin dB | Receive Antenna Polarization | EUT Antenna Orientation | Receive Antenna Height (m) |
| 1.6254 | 28.91 | 99.9 | -70.94 | -13 | 57.94 | Horizontal | 45 | 1.2 |
| 2.1672 | 29.78 | 101.1 | -71.27 | -13 | 58.27 | Horizontal | 290 | 2.0 |
| 2.709 | 28.82 | 100.2 | -71.33 | -13 | 58.33 | Horizontal | 270 | 1.8 |
| 1.6254 | 27.14 | 100.8 | -73.61 | -13 | 60.61 | Vertical | 315 | 1.2 |
| 2.1672 | 30.54 | 99.2 | -68.61 | -13 | 55.61 | Vertical | 10 | 1.2 |
| 2.709 | 30.01 | 99.6 | -69.54 | -13 | 56.54 | Vertical | 70 | 2.0 |



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

8.0 FREQUENCY STABILITY (TEMPERATURE)– PART 2.1055(a1)

The frequency stability was measured from -30° to +50° centigrade at intervals of 10° centigrade throughout the range. Prior to each frequency measurement, the equipment was left alone for a sufficient period of time (approximately 30 minutes or more) to allow the components of the Wireless Boundary Microphone oscillator circuitry to stabilize.

See the following page for the data taken during testing.

9.0 FREQUENCY STABILITY (VOLTAGE VARIATION)– PART 2.1055(d2)

The frequency stability of Wireless Boundary Microphone was measured by reducing the primary supply voltage to the battery end point specified by the manufacturer.

See the following page for the data taken during testing.



1250 Peterson Dr., Wheeling, IL 60090

Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

APPENDIX A

DATA TAKEN FOR FREQUENCY

STABILITY WHEN VARYING THE TEMPERATURE

AND

PRIMARY SUPPLY VOLTAGE VARIATION

PART 2.1055a(1) & PART 2.1055d(d2)



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

DLS Electronic Systems, Inc.

Company: Shure, Inc.

Operator: Craig B

Date of test: 07-13-2007

Limit = 25.9 kHz (0.005% of 518.2 MHz)

Frequency Stability FCC Part 74; FCC Part 2.1055

| Model | Nominal Frequency (MHz) | Measured Frequency | | | | | | | | | |
|----------|-------------------------|--------------------|---------------|------------|---------------|------------|---------------|------------|---------------|------------|--------------|
| | | +50 deg. C | Error (kHz) | +40 deg. C | Error (kHz) | +30 deg. C | Error (kHz) | +20 deg. C | Error (kHz) | +10 deg. C | Error (kHz) |
| MX690-H5 | 518.200 | 518.196834 | -3.166 | 518.197475 | -2.525 | 518.198357 | -1.643 | 518.199399 | -0.601 | 518.201002 | 1.002 |
| MX690-H5 | 530.500 | 530.496754 | -3.246 | 530.497315 | -2.685 | 530.498597 | -1.403 | 530.499238 | -0.762 | 530.500842 | 0.842 |
| MX690-H5 | 541.800 | 541.796673 | -3.327 | 541.797234 | -2.766 | 541.798357 | -1.643 | 541.799158 | -0.842 | 541.800762 | 0.762 |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |

Frequency Stability FCC Part 74; FCC Part 2.1055

| Model | Nominal Frequency (MHz) | Measured Frequency | | | | | | | | | |
|----------|-------------------------|--------------------|--------------|------------|--------------|------------|--------------|------------|---------------|------------|---------------|
| | | 0 deg. C | Error (kHz) | -10 deg. C | Error (kHz) | -20 deg. C | Error (kHz) | -30 deg. C | Error (kHz) | 2.1 Volts | Error (kHz) |
| MX690-H5 | 518.200 | 518.201162 | 1.162 | 518.201242 | 1.242 | 518.201002 | 1.002 | 518.200120 | 0.120 | 518.199238 | -0.762 |
| MX690-H5 | 530.500 | 530.501242 | 1.242 | 530.501082 | 1.082 | 530.501162 | 1.162 | 530.500601 | 0.601 | 530.499158 | -0.842 |
| MX690-H5 | 541.800 | 541.801323 | 1.323 | 541.801162 | 1.162 | 541.801162 | 1.162 | 541.797555 | -2.445 | 541.799238 | -0.762 |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |



Company: Shure Incorporated
Model Tested: MX690H5
Report Number: 13478

1250 Peterson Dr., Wheeling, IL 60090

APPENDIX A

10.0 FREQUENCY STABILITY PHOTOS TAKEN DURING TESTING

