



Shure SLXD2+

**Measurements of Shure SLXD2+
Handheld Microphone
For Regulatory Approval
G57-variant (470.125 – 551.850 MHz & 552.150-607.875)**

Shure Incorporated
June 18th, 2025

Prepared by
Mark Kenkel, Ph.D.

Table of Contents

1. SLXD2+ – Handheld Transmitter.....	1
1.1 SLXD2+ – UHF antenna for 470.125 - 551.850 & 552.150 – 607.875 MHz	1
2. Appendix	7

Table of Figures

Figure 1 – SLXD2+ G57-variant (470.125 MHz) 3D radiation patterns and scale	1
Figure 2 – SLXD2+ G57-variant (510.000 MHz) 3D radiation patterns and scale	2
Figure 3 – SLXD2+ G57-variant (551.850 MHz) 3D radiation patterns and scale	3
Figure 4 – SLXD2+ G57-variant (552.150 MHz) 3D radiation patterns and scale	4
Figure 5 – SLXD2+ G57-variant (580.000 MHz) 3D radiation patterns and scale	5
Figure 6 – SLXD2+ G57-variant (607.875 MHz) 3D radiation patterns and scale	6
Figure 7 - Antenna reference angles	8
Figure 8 – SLXD2+ UHF Helical Antenna and BLE Helical Antenna RF Connection Block Diagram.....	9

1. SLXD2+ – Handheld Transmitter

1.1 SLXD2+ – UHF antenna for 470.125 - 551.850 & 552.150 – 607.875 MHz

Antenna 3D patterns for:

- Test frequency = 470.125 MHz
- Maximum gain = -1.4 dBi




Figure 1 – SLXD2+ G57-variant (470.125 MHz) 3D radiation patterns and scale

- Test frequency = 510.000 MHz
- Maximum gain = -3.1dBi




Figure 2 – SLXD2+ G57-variant (510.000 MHz) 3D radiation patterns and scale

- Test frequency = 551.850 MHz
- Maximum gain = -3.2 dBi




Figure 3 – SLXD2+ G57-variant (551.850 MHz) 3D radiation patterns and scale

- Test frequency = 552.150MHz
- Maximum gain = -3.2 dBi




Figure 4 – SLXD2+ G57-variant (552.150 MHz) 3D radiation patterns and scale

- Test frequency = 580.000 MHz
- Maximum gain = -1.4 dBi




Figure 5 – SLXD2+ G57-variant (580.000 MHz) 3D radiation patterns and scale

- Test frequency = 607.875 MHz
- Maximum gain = -0.4 dBi




Figure 6 – SLXD2+ G57-variant (607.875 MHz) 3D radiation patterns and scale

2. Appendix

2.1 Supporting Test Equipment List

- E5071C ENA series Vector Network Analyzer 100kHz-8.5GHz
- ets model 2090 multi device controller
- ets lindgren model 3164-10 3164-10 Open Boundary Quad-Ridged Horn 400MHz-10GHz
- ets lindgren model no 3126-1920 precision sleeve dipole 1728-2112MHz
- EMQuest Data Acquisition and Analysis Software v1.12

2.2 Antenna Chamber Diagram and Reference Angles and DUT Pictures




Figure 7– Diagram of Shure antenna chamber. Designed per ETSI EN 300 422-1, section D-1



Figure 8 – Photo of Shure Antenna Test Chamber.





Figure 9 - Antenna reference angles

SLXD2+ Helical UHF and BLE Antenna Structures

**Figure 10 – SLXD2+ UHF Helical Antenna and BLE Helical Antenna RF Connection Block Diagram**