

FCC SAR Exclusion Report

Report No. : SFBCEE-WTW-P20120260

Applicant : Sennheiser electronic GmbH & Co. KG

Address : Am Labor 1, D-30900 Wedemark, Germany

Product Name : CX True Wireless (CX200TW1)

Brand Name : SENNHEISER

FCC ID : DMOCX200TW1L

Model No. : CX200TW1 L

Standards : FCC 47 CFR Part 2 (2.1093), IEEE C95.1:1992, IEEE Std 1528:2013
KDB 865664 D01 v01r04, KDB 865664 D02 v01r02, KDB 447498 D01 v06

Sample Received Date : Feb. 01, 2021

Date of Evaluation : Feb. 22, 2021

Lab Address : No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location : No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City, Taiwan

CERTIFICATION: The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch – Lin Kou Laboratories**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies.

Prepared By :



Shelly Hsueh / Specialist

Approved By :



Gordon Lin / Manager



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1. Summary of Maximum SAR Value	4
2. Description of Equipment Under Test	5
3. SAR Measurement Evaluation	6
3.1 Maximum Output Power.....	6
3.1.1 Maximum Target Conducted Power	6
3.1.2 Measured Conducted Power Result.....	6
3.1.3 Time-Avg. Power calculation.	6
3.2 SAR Testing Exclusions	8
4. Information on the Testing Laboratories.....	9
Appendix A. Photographs of EUT and Setup	
Appendix B. Maximum Target Conducted Power	
Appendix C. Measured Conducted Power Result	

Release Control Record

Issue No.	Reason for Change	Date Issued
SFBCEE-WTW-P20120260	Initial release	Feb. 25, 2021

FCC SAR Exclusion Report

1. Summary of Maximum SAR Value

Equipment Class	Mode	Highest Reported SAR _{1g} (W/kg)
DSS and DTS	Bluetooth	Not Required

Note:

1. The SAR limit (**Head & Body: SAR_{1g} 1.6 W/kg**) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.

2. Description of Equipment Under Test

Test Item Description	True Wireless Earphones
Product Name	CX True Wireless (CX200TW1)
FCC ID	DMOCX200TW1L
Brand Name	SENNHEISER
Model No.	CX200TW1 L
Status of EUT	Engineering Sample
Power Ratings	Left earbud& Right earbud: 3.7Vdc, 55-72mAh (from battery) Charging Case: 5Vdc, 600 mA (from Type-C USB interface) 3.7Vdc, 400-420mAh (from battery)
Operating Temperature range	0°C - +40°C
Modulation Type	BDR & EDR: GFSK, $\pi/4$ DQPSK, 8DPSK BLE: GFSK
Transmission Technology	BDR & EDR: FHSS BLE: DSSS
Technology	Bluetooth
Operating Frequency	2402 - 2480MHz (for Frequency Band: 2400-2483.5MHz)
No. of channels	BDR & EDR: 79 BLE: 40
Channel Spacing	BDR & EDR: 1MHz BLE: 2MHz
Channel Bandwidth	BDR & EDR: 79MHz BLE: 80MHz
Data Transfer Rate	BDR: 1Mbps and EDR: 2Mbps/3Mbps LE 4.0: 1Mbps and LE 5.1: 2Mbps
Maximum Tune-up Conducted Power (Unit: dBm)	Please refer to section 3.1.1 of this report
Antenna Type	Monopole antenna
Antenna Gain	-2.36 dBi
HW Version	Earbuds: V0F Charging case: V0G
SW Version	Earbuds: 0.12.19 Charging case: 20.12.31
Cable supplied	0.25m Shielded USB cable without core

Note:

- The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

3. SAR Measurement Evaluation

3.1 Maximum Output Power

3.1.1 Maximum Target Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Refer to Appendix B.

3.1.2 Measured Conducted Power Result

Refer to Appendix C.

3.1.3 Time-Avg. Power calculation.


The calculation of time-avg. power (Unit: dBm) Including duty cycle.

<The calculated average power with duty cycle>

Mode	Max Tune-up Power	Duty cycle (%)	Calculated Time-Avg. Power
BDR / EDR	8	76.8	6.85
LE 4.0	8.5	61.78	6.41
LE 5.1	8.5	32.64	3.64

FCC SAR Exclusion Report

Time-domain plot for Bluetooth transmission signal




The duty factor of Bluetooth signal has been calculated as following.

$$\text{Duty Factor} = \text{Pulse Width} / \text{Total Period} = 2.88 / 3.75 = 76.80 \%$$

The duty factor of Bluetooth signal has been calculated as following.

$$\text{Duty Factor} = \text{Pulse Width} / \text{Total Period} = 388.0 / 628.0 = 61.78 \%$$



The duty factor of Bluetooth signal has been calculated as following.

$$\text{Duty Factor} = \text{Pulse Width} / \text{Total Period} = 205.0 / 628.0 = 32.64 \%$$

FCC SAR Exclusion Report

3.2 SAR Testing Exclusions

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

- For the test separation distance ≤ 50 mm

$$\frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \sqrt{f_{(\text{GHz})}} \leq 3.0$$

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

- For the test separation distance > 50 mm, and the frequency at 100 MHz to 1500 MHz

$$\left[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times \left(\frac{f_{(\text{MHz})}}{150} \right) \right]_{(\text{mW})}$$

- For the test separation distance > 50 mm, and the frequency at > 1500 MHz to 6 GHz

$$[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times 10]_{(\text{mW})}$$

Mode	Time-Avg. Power (dBm)	Time-Avg. Power (mW)	Left Earbud Ant. to Surface (mm)	Calculated Result	Require SAR Testing?
BDR / EDR	6.85	4.84	8.03	0.95	No
LE 4.0	6.41	4.38	8.03	0.86	No
LE 5.1	3.64	2.31	8.03	0.45	No

Note:

- When separation distance ≤ 50 mm and the calculated result shown in above table is ≤ 3.0 , the SAR testing exclusion is applied.
- When separation distance > 50 mm and the device output power is less than the calculated result (power threshold, mW) shown in above table, the SAR testing exclusion is applied.

Summary:

Since the SAR testing for all device orientations apply SAR test exclusion per KDB 447498, SAR testing for this device is not required.

4. Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Taiwan Huaya Lab:

Add: No. 19, Huaya 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan

Tel: +886-(0)3-318-3232

Fax: +886-(0)3-211-5834

Taiwan Linkou Lab:

Add: No. 47-2, Baodoucuokeng, Linkou Dist., New Taipei City 244, Taiwan

Tel: +886-(0)2-2605-2180

Fax: +886-(0)2-2605-2943

Taiwan Hsinchu Lab1:

Add: E-2, No. 1, Lixing 1st Rd., East Dist., Hsinchu City 300, Taiwan

Tel: +886-(0)3-666-8565

Fax: +886-(0)3-666-8323

Taiwan Hsinchu Lab2:

Add: No. 49, Ln. 206, Wende Rd., Qionglin Township, Hsinchu County 307, Taiwan

Tel: +886-(0)3-512-0595

Fax: +886-(0)3-512-0568

Taiwan Xindian Lab:

Add: B2F., No. 215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan

Tel: +886-(0)2-8914-5882

Fax: +886-(0)2-8914-5840

Email: service.adt@tw.bureauveritas.com

Web Site: <https://ee.bureauveritas.com.tw/BVInternet/Default>

The road map of all our labs can be found in our web site also.

---END---

Appendix A. Photographs of EUT and Setup

Please refer to the attached file (reference no.: SFBCEE-WTW-P20120260)

Appendix B. Maximum Target Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Bluetooth			
Mode	Channel	Frequency	Max Tune-up Power
BDR / EDR	0	2402	8.0
	39	2441	8.0
	78	2480	8.0
LE 4.0	0	2402	8.5
	19	2440	8.5
	39	2480	8.5
LE 5.1	0	2402	8.5
	19	2440	8.5
	39	2480	8.5

Appendix C. Measured Conducted Power Result

The measuring conducted power (Unit: dBm) are shown as below.

Bluetooth			
Mode	Channel	Frequency	Average Power (Left earbud)
BDR / EDR	0	2402	6.76
	39	2441	6.95
	78	2480	6.64
LE 4.0	0	2402	7.26
	19	2440	8.08
	39	2480	7.91
LE 5.1	0	2402	7.28
	19	2440	8.08
	39	2480	7.88