

## FCC Test Report

**Report No.:** RF200618C02-1

**FCC ID:** DMOHD250BT

**Model No.:** HD 250BT

**Received Date:** Jun. 18, 2020

**Test Date:** Jul. 09 ~ Aug. 13, 2020

**Issued Date:** Aug. 17, 2020

**Applicant:** Sennheiser electronic GmbH & Co. KG

**Address:** Am Labor 1, D-30900 Wedemark, Germany

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location:** No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City  
33383, Taiwan

**FCC Registration /  
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

## Table of Contents

|                                                                   |           |
|-------------------------------------------------------------------|-----------|
| <b>Release Control Record .....</b>                               | <b>4</b>  |
| <b>1 Certificate of Conformity .....</b>                          | <b>5</b>  |
| <b>2 Summary of Test Results.....</b>                             | <b>6</b>  |
| 2.1 Measurement Uncertainty.....                                  | 6         |
| 2.2 Modification Record .....                                     | 6         |
| <b>3 General Information .....</b>                                | <b>7</b>  |
| 3.1 General Description of EUT .....                              | 7         |
| 3.2 Description of Test Modes.....                                | 8         |
| 3.2.1 Test Mode Applicability and Tested Channel Detail.....      | 9         |
| 3.3 Duty Cycle of Test Signal .....                               | 11        |
| 3.4 Description of Support Units .....                            | 12        |
| 3.4.1 Configuration of System under Test .....                    | 12        |
| 3.5 General Description of Applied Standards and References ..... | 12        |
| <b>4 Test Types and Results .....</b>                             | <b>14</b> |
| 4.1 Radiated Emission and Bandedge Measurement .....              | 14        |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement .....  | 14        |
| 4.1.2 Test Instruments .....                                      | 15        |
| 4.1.3 Test Procedures.....                                        | 16        |
| 4.1.4 Deviation from Test Standard .....                          | 16        |
| 4.1.5 Test Set Up .....                                           | 17        |
| 4.1.6 EUT Operating Conditions.....                               | 18        |
| 4.1.7 Test Results .....                                          | 19        |
| 4.2 Conducted Emission Measurement.....                           | 29        |
| 4.2.1 Limits of Conducted Emission Measurement .....              | 29        |
| 4.2.2 Test Instruments .....                                      | 29        |
| 4.2.3 Test Procedures.....                                        | 29        |
| 4.2.4 Deviation from Test Standard .....                          | 30        |
| 4.2.5 Test Setup.....                                             | 30        |
| 4.2.6 EUT Operating Conditions.....                               | 30        |
| 4.2.7 Test Results .....                                          | 31        |
| 4.3 6 dB Bandwidth Measurement.....                               | 35        |
| 4.3.1 Limits of 6 dB Bandwidth Measurement.....                   | 35        |
| 4.3.2 Test Setup.....                                             | 35        |
| 4.3.3 Test Instruments .....                                      | 35        |
| 4.3.4 Test Procedure .....                                        | 35        |
| 4.3.5 Deviation from Test Standard .....                          | 35        |
| 4.3.6 EUT Operating Conditions.....                               | 35        |
| 4.3.7 Test Results .....                                          | 36        |
| 4.4 Occupied Bandwidth Measurement.....                           | 38        |
| 4.4.1 Test Setup.....                                             | 38        |
| 4.4.2 Test Instruments .....                                      | 38        |
| 4.4.3 Test Procedure .....                                        | 38        |
| 4.4.4 Deviation from Test Standard .....                          | 38        |
| 4.4.5 EUT Operating Conditions.....                               | 38        |
| 4.4.6 Test Results .....                                          | 39        |
| 4.5 Conducted Output Power Measurement .....                      | 41        |
| 4.5.1 Limits of Conducted Output Power Measurement.....           | 41        |
| 4.5.2 Test Setup.....                                             | 41        |
| 4.5.3 Test Instruments .....                                      | 41        |
| 4.5.4 Test Procedures.....                                        | 41        |
| 4.5.5 Deviation from Test Standard .....                          | 41        |
| 4.5.6 EUT Operating Conditions.....                               | 41        |
| 4.5.7 Test Results .....                                          | 42        |

|          |                                                                 |           |
|----------|-----------------------------------------------------------------|-----------|
| 4.6      | Power Spectral Density Measurement .....                        | 43        |
| 4.6.1    | Limits of Power Spectral Density Measurement.....               | 43        |
| 4.6.2    | Test Setup.....                                                 | 43        |
| 4.6.3    | Test Instruments .....                                          | 43        |
| 4.6.4    | Test Procedure .....                                            | 43        |
| 4.6.5    | Deviation from Test Standard .....                              | 43        |
| 4.6.6    | EUT Operating Condition .....                                   | 43        |
| 4.6.7    | Test Results .....                                              | 44        |
| 4.7      | Conducted Out of Band Emission Measurement .....                | 46        |
| 4.7.1    | Limits of Conducted Out of Band Emission Measurement.....       | 46        |
| 4.7.2    | Test Setup.....                                                 | 46        |
| 4.7.3    | Test Instruments .....                                          | 46        |
| 4.7.4    | Test Procedure .....                                            | 46        |
| 4.7.5    | Deviation from Test Standard .....                              | 46        |
| 4.7.6    | EUT Operating Condition .....                                   | 46        |
| 4.7.7    | Test Results .....                                              | 47        |
| <b>5</b> | <b>Photographs of the Test Configuration.....</b>               | <b>49</b> |
| <b>6</b> | <b>Construction Photos of EUT .....</b>                         | <b>50</b> |
|          | <b>Appendix – Information of the Testing Laboratories .....</b> | <b>51</b> |

### Release Control Record

| Issue No.     | Description      | Date Issued   |
|---------------|------------------|---------------|
| RF200618C02-1 | Original Release | Aug. 17, 2020 |

## 1 Certificate of Conformity

**Product Name:** HD 250BT Wireless

**Brand Name:** SENNHEISER

**Model No.:** HD 250BT

**Sample Status:** Engineering Sample

**Applicant:** Sennheiser electronic GmbH & Co. KG

**Test Date:** Jul. 09 ~ Aug. 13, 2020

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :** Gina Liu, **Date:** Aug. 17, 2020  
Gina Liu / Specialist

**Approved by :** Dylan Chiou, **Date:** Aug. 17, 2020  
Dylan Chiou / Senior Project Engineer

## 2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart C (Section 15.247) |                                |        |                                                                                      |
|------------------------------------------------|--------------------------------|--------|--------------------------------------------------------------------------------------|
| FCC Clause                                     | Test Item                      | Result | Remarks                                                                              |
| 15.207                                         | AC Power Conducted Emission    | Pass   | Meet the requirement of limit.<br>Minimum passing margin is -6.17 dB at 0.46280 MHz. |
| 15.205 & 209                                   | Radiated Emissions             | Pass   | Meet the requirement of limit.<br>Minimum passing margin is -5.2 dB at 2483.50 MHz.  |
| 15.247(d)                                      | Band Edge Measurement          | Pass   | Meet the requirement of limit.                                                       |
| 15.247(d)                                      | Antenna Port Emission          | Pass   | Meet the requirement of limit.                                                       |
| 15.247(a)(2)                                   | 6 dB Bandwidth                 | Pass   | Meet the requirement of limit.                                                       |
| ---                                            | Occupied Bandwidth Measurement | Pass   | Reference only                                                                       |
| 15.247(b)                                      | Conducted Power                | Pass   | Meet the requirement of limit.                                                       |
| 15.247(e)                                      | Power Spectral Density         | Pass   | Meet the requirement of limit.                                                       |
| 15.203                                         | Antenna Requirement            | Pass   | No antenna connector is used.                                                        |

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                        | Frequency          | Expanded Uncertainty (k=2) ( $\pm$ ) |
|------------------------------------|--------------------|--------------------------------------|
| Conducted Emissions at mains ports | 150 kHz ~ 30 MHz   | 2.79 dB                              |
| Radiated Emissions up to 1 GHz     | 9 kHz ~ 30 MHz     | 3.04 dB                              |
|                                    | 30 MHz ~ 200 MHz   | 2.93 dB                              |
|                                    | 200 MHz ~ 1000 MHz | 2.95 dB                              |
| Radiated Emissions above 1 GHz     | 1 GHz ~ 18 GHz     | 2.26 dB                              |
|                                    | 18 GHz ~ 40 GHz    | 1.94 dB                              |

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                                    |                                                                           |
|------------------------------------|---------------------------------------------------------------------------|
| <b>Test Item Description</b>       | On-ear headphones                                                         |
| <b>Product Name</b>                | HD 250BT Wireless                                                         |
| <b>Brand Name</b>                  | SENNHEISER                                                                |
| <b>Model No.</b>                   | HD 250BT                                                                  |
| <b>Status of EUT</b>               | Engineering Sample                                                        |
| <b>Power Rating</b>                | 5Vdc, 120 mA (from Type-C USB interface)<br>3.7Vdc, 190mAh (from battery) |
| <b>Operating Temperature range</b> | 0°C - +40°C                                                               |
| <b>Modulation Type</b>             | GFSK                                                                      |
| <b>Transmission Technology</b>     | DSSS                                                                      |
| <b>Technology</b>                  | Bluetooth                                                                 |
| <b>Operating Frequency</b>         | 2402 ~ 2480 MHz<br>(for Frequency Band: 2400-2483.5MHz)                   |
| <b>Number of Channel</b>           | 40                                                                        |
| <b>Channel Spacing</b>             | 2MHz                                                                      |
| <b>Channel Bandwidth</b>           | 80MHz                                                                     |
| <b>Data Transfer Rate</b>          | LE 4.0: 1 Mbps<br>LE 5.0: 2 Mbps                                          |
| <b>Antenna Type</b>                | PCB antenna                                                               |
| <b>Antenna Gain</b>                | 1.43 dBi                                                                  |
| <b>Maximum Output Power</b>        | LE 4.0: 2.443 mW<br>LE 5.0: 2.449 mW                                      |
| <b>HW Version</b>                  | V3.0                                                                      |
| <b>SW Version</b>                  | V2.4.3                                                                    |
| <b>Cable Supplied</b>              | 0.5m shielded USB cable without core                                      |

Note:

1. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.
2. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or User's Manual.

### 3.2 Description of Test Modes

40 channels are provided to this EUT:

| Channel | Freq. (MHz) | Channel | Freq. (MHz) | Channel | Freq. (MHz) | Channel | Freq. (MHz) |
|---------|-------------|---------|-------------|---------|-------------|---------|-------------|
| 0       | 2402        | 10      | 2422        | 20      | 2442        | 30      | 2462        |
| 1       | 2404        | 11      | 2424        | 21      | 2444        | 31      | 2464        |
| 2       | 2406        | 12      | 2426        | 22      | 2446        | 32      | 2466        |
| 3       | 2408        | 13      | 2428        | 23      | 2448        | 33      | 2468        |
| 4       | 2410        | 14      | 2430        | 24      | 2450        | 34      | 2470        |
| 5       | 2412        | 15      | 2432        | 25      | 2452        | 35      | 2472        |
| 6       | 2414        | 16      | 2434        | 26      | 2454        | 36      | 2474        |
| 7       | 2416        | 17      | 2436        | 27      | 2456        | 37      | 2476        |
| 8       | 2418        | 18      | 2438        | 28      | 2458        | 38      | 2478        |
| 9       | 2420        | 19      | 2440        | 29      | 2460        | 39      | 2480        |

### 3.2.1 Test Mode Applicability and Tested Channel Detail

<LE 4.0>

| EUT Configure Mode | Applicable To |       |     |      | Description                     |
|--------------------|---------------|-------|-----|------|---------------------------------|
|                    | RE≥1G         | RE<1G | PLC | APCM |                                 |
| A                  | √             | -     | -   | √    | EUT charging Notebook (Cable 1) |

Where **RE≥1G**: Radiated Emission above 1 GHz

**RE<1G**: Radiated Emission below 1 GHz

**PLC**: Power Line Conducted Emission

**APCM**: Antenna Port Conducted Measurement

**Note:** The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.

**Note:** “-” means no effect.

#### **Radiated Emission Test (Above 1 GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type | Data Rate (Mbps) |
|--------------------|-------------------|----------------|-----------------|------------------|
| A                  | 0 to 39           | 0, 19, 39      | GFSK            | 1                |

#### **Antenna Port Conducted Measurement:**

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type | Data Rate (Mbps) |
|--------------------|-------------------|----------------|-----------------|------------------|
| A                  | 0 to 39           | 0, 19, 39      | GFSK            | 1                |

### <LE 5.0>

| EUT Configure Mode | Applicable To |       |     |      | Description                     |
|--------------------|---------------|-------|-----|------|---------------------------------|
|                    | RE≥1G         | RE<1G | PLC | APCM |                                 |
| A                  | √             | √     | √   | √    | EUT charging Notebook (Cable 1) |
| B                  | -             | √     | √   | -    | EUT charging adapter (Cable 2)  |

Where **RE≥1G**: Radiated Emission above 1 GHz **RE<1G**: Radiated Emission below 1 GHz  
**PLC**: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

**Note:** The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.  
**Note:** "-" means no effect.

### Radiated Emission Test (Above 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type | Data Rate (Mbps) |
|--------------------|-------------------|----------------|-----------------|------------------|
| A                  | 0 to 39           | 0, 19, 39      | GFSK            | 2                |

### Radiated Emission Test (Below 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type | Data Rate (Mbps) |
|--------------------|-------------------|----------------|-----------------|------------------|
| A, B               | 0 to 39           | 39             | GFSK            | 2                |

### Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type | Data Rate (Mbps) |
|--------------------|-------------------|----------------|-----------------|------------------|
| A, B               | 0 to 39           | 39             | GFSK            | 2                |

### Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT Configure Mode | Available Channel | Tested Channel | Modulation Type | Data Rate (Mbps) |
|--------------------|-------------------|----------------|-----------------|------------------|
| A                  | 0 to 39           | 0, 19, 39      | GFSK            | 2                |

### Test Condition:


| Applicable To | Environmental Conditions | Input Power    | Tested by  |
|---------------|--------------------------|----------------|------------|
| RE $\geq$ 1G  | 23 deg. C, 65 % RH       | 120 Vac, 60 Hz | Adair Peng |
| RE $<$ 1G     | 23 deg. C, 65 % RH       | 120 Vac, 60 Hz | Adair Peng |
| PLC           | 23 deg. C, 67 % RH       | 120 Vac, 60 Hz | Adair Peng |
| APCM          | 25 deg. C, 65 % RH       | 120 Vac, 60 Hz | Ivan Tseng |

### 3.3 Duty Cycle of Test Signal

Duty cycle of test signal is < 98 %, duty factor shall be considered.


#### <LE 4.0>

Duty cycle =  $0.411/0.616 = 0.667$ , Duty factor =  $10 * \log(1/0.667) = 1.76$



#### <LE 5.0>

Duty cycle =  $0.2554/0.6271 = 0.407$ , Duty factor =  $10 * \log(1/0.407) = 3.90$



### 3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| No. | Product  | Brand  | Model No.  | Serial No.      | FCC ID    |
|-----|----------|--------|------------|-----------------|-----------|
| A.  | Notebook | ASUS   | X571G      | L1N0CX017583018 | PD99560NG |
| B.  | Adapter  | LITEON | PA-1050-39 | N/A             | N/A       |


| No. | Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks          |
|-----|--------------|------|------------|--------------------|--------------|------------------|
| 1.  | USB Cable    | 1    | 1.0        | Y                  | 0            | Provided by Lab  |
| 2.  | USB Cable    | 1    | 0.5        | Y                  | 0            | Accessory of EUT |

Note:


1. All power cords of the above support units are non-shielded (1.8m).
2. Item 2 USB Cable only for charging.

#### 3.4.1 Configuration of System under Test

Mode A



Mode B



### 3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

#### Test Standard:

##### **FCC Part 15, Subpart C (15.247)**

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

#### References Test Guidance:

##### **KDB 558074 D01 15.247 Meas Guidance v05r02**

All test items have been performed as a reference to the above KDB test guidance.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F (kHz)                      | 300                           |
| 0.490 ~ 1.705     | 24000/F (kHz)                     | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

**Note:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

#### 4.1.2 Test Instruments

| Description & Manufacturer                | Model No.                             | Serial No.                      | Date of Calibration | Due Date of Calibration |
|-------------------------------------------|---------------------------------------|---------------------------------|---------------------|-------------------------|
| Test Receiver<br>ROHDE & SCHWARZ          | ESR3                                  | 102579                          | Jul. 07, 2020       | Jul. 06, 2021           |
| Spectrum Analyzer<br>ROHDE & SCHWARZ      | FSP40                                 | 100269                          | Jun. 09, 2020       | Jun. 08, 2021           |
| Spectrum Analyzer<br>ROHDE & SCHWARZ      | FSV40                                 | 100980                          | Apr. 20, 2020       | Apr. 19, 2021           |
| BILOG Antenna<br>SCHWARZBECK              | VULB9168                              | 9168-171                        | Nov. 11, 2019       | Nov. 10, 2020           |
| HORN Antenna<br>SCHWARZBECK               | 9120D                                 | 209                             | Nov. 24, 2019       | Nov. 23, 2020           |
| HORN Antenna<br>SCHWARZBECK               | BBHA 9170                             | BBHA9170241                     | Nov. 24, 2019       | Nov. 23, 2020           |
| Preamplifier<br>Agilent<br>(Below 1GHz)   | 8447D                                 | 2944A10738                      | Aug. 20, 2019       | Aug. 19, 2020           |
| Preamplifier<br>Agilent<br>(Above 1GHz)   | 8449B                                 | 3008A02465                      | Mar. 23, 2020       | Mar. 22, 2021           |
| RF Coaxial Cable<br>WOKEN<br>With 5dB PAD | 8D-FB                                 | Cable-CH3-01                    | Aug. 20, 2019       | Aug. 19, 2020           |
| RF signal cable<br>HUBER+SUHNER           | SUCOFLEX 104                          | Cable-CH3-03<br>(223653/4)      | Aug. 20, 2019       | Aug. 19, 2020           |
| RF signal cable<br>HUBER+SUHNER&<br>EMCI  | SUCOFLEX<br>104&EMC104-SM-<br>SM-8000 | Cable-CH3-03<br>(309224+170907) | Aug. 20, 2019       | Aug. 19, 2020           |
| Software<br>BV ADT                        | ADT_Radiated_<br>V7.6.15.9.5          | NA                              | NA                  | NA                      |
| Antenna Tower<br>inn-co GmbH              | MA 4000                               | 013303                          | NA                  | NA                      |
| Antenna Tower Controller<br>BV ADT        | AT100                                 | AT93021702                      | NA                  | NA                      |
| Turn Table<br>BV ADT                      | TT100                                 | TT93021702                      | NA                  | NA                      |
| Turn Table Controller<br>BV ADT           | SC100                                 | SC93021702                      | NA                  | NA                      |
| Boresight Antenna Fixture                 | FBA-01                                | FBA-SIP01                       | NA                  | NA                      |
| High Speed Peak Power<br>Meter            | ML2495A                               | 1012010                         | Sep. 04, 2019       | Sep. 03, 2020           |
| Power Sensor                              | MA2411B                               | 1315050                         | Sep. 04, 2019       | Sep. 03, 2020           |

Note: 1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.  
2. The test was performed in HwaYa Chamber 3.

#### 4.1.3 Test Procedures

##### **For Radiated Emission below 30 MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

##### **Note:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.

##### **For Radiated Emission above 30 MHz**

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

##### **Note:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) or Peak detection (PK) at frequency below 1 GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle  $< 98\%$ ) or 10 Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1 GHz. (BT LE 4.0: RBW = 1 MHz, VBW = 3 kHz; BT LE 5.0: RBW = 1 MHz, VBW = 10 kHz)
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Set Up


##### <Radiated Emission below 30 MHz>



##### <Radiated Emission 30 MHz to 1 GHz>



### <Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Set the EUT under transmission condition continuously at specific channel frequency.

#### 4.1.7 Test Results

##### Above 1 GHz Data:

<LE 4.0>

|                        |                |                                     |               |
|------------------------|----------------|-------------------------------------|---------------|
| <b>CHANNEL</b>         | TX Channel 0   | <b>DETECTOR<br/>FUNCTION</b>        | Peak (PK)     |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz   |                                     | Average (AV)  |
| <b>INPUT POWER</b>     | 120 Vac, 60 Hz | <b>ENVIRONMENTAL<br/>CONDITIONS</b> | 23 °C, 65% RH |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 58.7 PK                       | 74.0              | -15.3          | 1.22 H                   | 154                        | 26.4                   | 32.3                           |
| 2                                                   | 2390.00        | 47.0 AV                       | 54.0              | -7.0           | 1.22 H                   | 154                        | 14.7                   | 32.3                           |
| 3                                                   | *2402.00       | 100.8 PK                      |                   |                | 1.22 H                   | 154                        | 68.5                   | 32.3                           |
| 4                                                   | *2402.00       | 99.1 AV                       |                   |                | 1.22 H                   | 154                        | 66.8                   | 32.3                           |
| 5                                                   | 4804.00        | 49.0 PK                       | 74.0              | -25.0          | 1.31 H                   | 110                        | 45.9                   | 3.1                            |
| 6                                                   | 4804.00        | 38.9 AV                       | 54.0              | -15.1          | 1.31 H                   | 110                        | 35.8                   | 3.1                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 58.9 PK                       | 74.0              | -15.1          | 1.53 V                   | 168                        | 26.6                   | 32.3                           |
| 2                                                   | 2390.00        | 47.2 AV                       | 54.0              | -6.8           | 1.53 V                   | 168                        | 14.9                   | 32.3                           |
| 3                                                   | *2402.00       | 102.7 PK                      |                   |                | 1.53 V                   | 168                        | 70.4                   | 32.3                           |
| 4                                                   | *2402.00       | 100.4 AV                      |                   |                | 1.53 V                   | 168                        | 68.1                   | 32.3                           |
| 5                                                   | 4804.00        | 49.0 PK                       | 74.0              | -25.0          | 1.02 V                   | 274                        | 45.9                   | 3.1                            |
| 6                                                   | 4804.00        | 39.0 AV                       | 54.0              | -15.0          | 1.02 V                   | 274                        | 35.9                   | 3.1                            |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

|                        |                |                                     |               |
|------------------------|----------------|-------------------------------------|---------------|
| <b>CHANNEL</b>         | TX Channel 19  | <b>DETECTOR<br/>FUNCTION</b>        | Peak (PK)     |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz   |                                     | Average (AV)  |
| <b>INPUT POWER</b>     | 120 Vac, 60 Hz | <b>ENVIRONMENTAL<br/>CONDITIONS</b> | 23 °C, 65% RH |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2440.00       | 99.4 PK                       |                   |                | 1.35 H                   | 161                        | 67.1                   | 32.3                           |
| 2                                                   | *2440.00       | 98.7 AV                       |                   |                | 1.35 H                   | 161                        | 66.4                   | 32.3                           |
| 3                                                   | 4880.00        | 48.4 PK                       | 74.0              | -25.6          | 1.39 H                   | 118                        | 45.4                   | 3.0                            |
| 4                                                   | 4880.00        | 37.2 AV                       | 54.0              | -16.8          | 1.39 H                   | 118                        | 34.2                   | 3.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2440.00       | 101.3 PK                      |                   |                | 1.51 V                   | 174                        | 69.0                   | 32.3                           |
| 2                                                   | *2440.00       | 99.9 AV                       |                   |                | 1.51 V                   | 174                        | 67.6                   | 32.3                           |
| 3                                                   | 4880.00        | 48.5 PK                       | 74.0              | -25.5          | 1.01 V                   | 268                        | 45.5                   | 3.0                            |
| 4                                                   | 4880.00        | 37.3 AV                       | 54.0              | -16.7          | 1.01 V                   | 268                        | 34.3                   | 3.0                            |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

|                        |                |                                 |               |
|------------------------|----------------|---------------------------------|---------------|
| <b>CHANNEL</b>         | TX Channel 39  | <b>DETECTOR FUNCTION</b>        | Peak (PK)     |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz   |                                 | Average (AV)  |
| <b>INPUT POWER</b>     | 120 Vac, 60 Hz | <b>ENVIRONMENTAL CONDITIONS</b> | 23 °C, 65% RH |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | *2480.00    | 100.7 PK                |                |             | 1.28 H             | 159                  | 68.3             | 32.4                     |
| 2                                                   | *2480.00    | 98.8 AV                 |                |             | 1.28 H             | 159                  | 66.4             | 32.4                     |
| 3                                                   | 2483.50     | 59.6 PK                 | 74.0           | -14.4       | 1.28 H             | 159                  | 27.2             | 32.4                     |
| 4                                                   | 2483.50     | 47.1 AV                 | 54.0           | -6.9        | 1.28 H             | 159                  | 14.7             | 32.4                     |
| 5                                                   | 4960.00     | 47.1 PK                 | 74.0           | -26.9       | 1.27 H             | 107                  | 43.8             | 3.3                      |
| 6                                                   | 4960.00     | 36.2 AV                 | 54.0           | -17.8       | 1.27 H             | 107                  | 32.9             | 3.3                      |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | *2480.00    | 102.5 PK                |                |             | 1.40 V             | 172                  | 70.1             | 32.4                     |
| 2                                                   | *2480.00    | 100.2 AV                |                |             | 1.40 V             | 172                  | 67.8             | 32.4                     |
| 3                                                   | 2483.50     | 59.8 PK                 | 74.0           | -14.2       | 1.40 V             | 172                  | 27.4             | 32.4                     |
| 4                                                   | 2483.50     | 47.4 AV                 | 54.0           | -6.6        | 1.40 V             | 172                  | 15.0             | 32.4                     |
| 5                                                   | 4960.00     | 47.4 PK                 | 74.0           | -26.6       | 1.01 V             | 267                  | 44.1             | 3.3                      |
| 6                                                   | 4960.00     | 36.3 AV                 | 54.0           | -17.7       | 1.01 V             | 267                  | 33.0             | 3.3                      |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

<LE 5.0>

|                        |                |                                     |               |
|------------------------|----------------|-------------------------------------|---------------|
| <b>CHANNEL</b>         | TX Channel 0   | <b>DETECTOR<br/>FUNCTION</b>        | Peak (PK)     |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz   |                                     | Average (AV)  |
| <b>INPUT POWER</b>     | 120 Vac, 60 Hz | <b>ENVIRONMENTAL<br/>CONDITIONS</b> | 23 °C, 65% RH |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 2390.00        | 58.8 PK                       | 74.0              | -15.2          | 1.41 H                   | 153                        | 26.5                   | 32.3                           |
| 2   | 2390.00        | 47.3 AV                       | 54.0              | -6.7           | 1.41 H                   | 153                        | 15.0                   | 32.3                           |
| 3   | *2402.00       | 100.4 PK                      |                   |                | 1.41 H                   | 153                        | 68.1                   | 32.3                           |
| 4   | *2402.00       | 97.3 AV                       |                   |                | 1.41 H                   | 153                        | 65.0                   | 32.3                           |
| 5   | 4804.00        | 47.7 PK                       | 74.0              | -26.3          | 1.48 H                   | 120                        | 44.6                   | 3.1                            |
| 6   | 4804.00        | 37.1 AV                       | 54.0              | -16.9          | 1.48 H                   | 120                        | 34.0                   | 3.1                            |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 2390.00        | 59.0 PK                       | 74.0              | -15.0          | 1.56 V                   | 171                        | 26.7                   | 32.3                           |
| 2   | 2390.00        | 47.5 AV                       | 54.0              | -6.5           | 1.56 V                   | 171                        | 15.2                   | 32.3                           |
| 3   | *2402.00       | 102.2 PK                      |                   |                | 1.56 V                   | 171                        | 69.9                   | 32.3                           |
| 4   | *2402.00       | 98.6 AV                       |                   |                | 1.56 V                   | 171                        | 66.3                   | 32.3                           |
| 5   | 4804.00        | 47.9 PK                       | 74.0              | -26.1          | 1.01 V                   | 265                        | 44.8                   | 3.1                            |
| 6   | 4804.00        | 37.3 AV                       | 54.0              | -16.7          | 1.01 V                   | 265                        | 34.2                   | 3.1                            |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

|                        |                |                                     |               |
|------------------------|----------------|-------------------------------------|---------------|
| <b>CHANNEL</b>         | TX Channel 19  | <b>DETECTOR<br/>FUNCTION</b>        | Peak (PK)     |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz   |                                     | Average (AV)  |
| <b>INPUT POWER</b>     | 120 Vac, 60 Hz | <b>ENVIRONMENTAL<br/>CONDITIONS</b> | 23 °C, 65% RH |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2440.00       | 99.6 PK                       |                   |                | 1.32 H                   | 156                        | 67.3                   | 32.3                           |
| 2                                                   | *2440.00       | 97.0 AV                       |                   |                | 1.32 H                   | 156                        | 64.7                   | 32.3                           |
| 3                                                   | 4880.00        | 47.3 PK                       | 74.0              | -26.7          | 1.39 H                   | 120                        | 44.3                   | 3.0                            |
| 4                                                   | 4880.00        | 36.7 AV                       | 54.0              | -17.3          | 1.39 H                   | 120                        | 33.7                   | 3.0                            |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2440.00       | 101.4 PK                      |                   |                | 1.47 V                   | 173                        | 69.1                   | 32.3                           |
| 2                                                   | *2440.00       | 98.3 AV                       |                   |                | 1.47 V                   | 173                        | 66.0                   | 32.3                           |
| 3                                                   | 4880.00        | 47.4 PK                       | 74.0              | -26.6          | 1.00 V                   | 265                        | 44.4                   | 3.0                            |
| 4                                                   | 4880.00        | 36.8 AV                       | 54.0              | -17.2          | 1.00 V                   | 265                        | 33.8                   | 3.0                            |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

|                        |                |                                 |               |
|------------------------|----------------|---------------------------------|---------------|
| <b>CHANNEL</b>         | TX Channel 39  | <b>DETECTOR FUNCTION</b>        | Peak (PK)     |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz   |                                 | Average (AV)  |
| <b>INPUT POWER</b>     | 120 Vac, 60 Hz | <b>ENVIRONMENTAL CONDITIONS</b> | 23 °C, 65% RH |

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1   | *2480.00    | 99.6 PK                 |                |             | 1.28 H             | 161                  | 67.2             | 32.4                     |
| 2   | *2480.00    | 96.1 AV                 |                |             | 1.28 H             | 161                  | 63.7             | 32.4                     |
| 3   | 2483.50     | 59.9 PK                 | 74.0           | -14.1       | 1.28 H             | 161                  | 27.5             | 32.4                     |
| 4   | 2483.50     | 48.4 AV                 | 54.0           | -5.6        | 1.28 H             | 161                  | 16.0             | 32.4                     |
| 5   | 4960.00     | 47.5 PK                 | 74.0           | -26.5       | 1.39 H             | 117                  | 44.2             | 3.3                      |
| 6   | 4960.00     | 36.0 AV                 | 54.0           | -18.0       | 1.39 H             | 117                  | 32.7             | 3.3                      |

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1   | *2480.00    | 101.3 PK                |                |             | 1.40 V             | 175                  | 68.9             | 32.4                     |
| 2   | *2480.00    | 97.6 AV                 |                |             | 1.40 V             | 175                  | 65.2             | 32.4                     |
| 3   | 2483.50     | 60.2 PK                 | 74.0           | -13.8       | 1.40 V             | 175                  | 27.8             | 32.4                     |
| 4   | 2483.50     | 48.8 AV                 | 54.0           | -5.2        | 1.40 V             | 175                  | 16.4             | 32.4                     |
| 5   | 4960.00     | 47.7 PK                 | 74.0           | -26.3       | 1.03 V             | 267                  | 44.4             | 3.3                      |
| 6   | 4960.00     | 36.2 AV                 | 54.0           | -17.8       | 1.03 V             | 267                  | 32.9             | 3.3                      |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency.

### 30 MHz ~ 1 GHz Worst-Case Data:

<LE 5.0>


#### Mode A

|                        |                |                                 |                 |
|------------------------|----------------|---------------------------------|-----------------|
| <b>CHANNEL</b>         | TX Channel 39  | <b>DETECTOR FUNCTION</b>        | Quasi-Peak (QP) |
| <b>FREQUENCY RANGE</b> | 30MHz ~ 1GHz   |                                 |                 |
| <b>INPUT POWER</b>     | 120 Vac, 60 Hz | <b>ENVIRONMENTAL CONDITIONS</b> | 23 °C, 65% RH   |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 138.25      | 29.4 QP                 | 43.5           | -14.1       | 2.00 H             | 328                  | 38.6             | -9.2                     |
| 2                                                   | 164.96      | 28.1 QP                 | 43.5           | -15.4       | 1.00 H             | 279                  | 36.8             | -8.7                     |
| 3                                                   | 183.23      | 26.6 QP                 | 43.5           | -16.9       | 1.00 H             | 186                  | 36.8             | -10.2                    |
| 4                                                   | 250.71      | 26.9 QP                 | 46.0           | -19.1       | 1.00 H             | 246                  | 36.4             | -9.5                     |
| 5                                                   | 395.51      | 31.5 QP                 | 46.0           | -14.5       | 1.00 H             | 16                   | 36.1             | -4.6                     |
| 6                                                   | 585.29      | 32.3 QP                 | 46.0           | -13.7       | 1.51 H             | 95                   | 31.7             | 0.6                      |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.




|                 |                |                             |                 |
|-----------------|----------------|-----------------------------|-----------------|
| CHANNEL         | TX Channel 39  | DETECTOR<br>FUNCTION        | Quasi-Peak (QP) |
| FREQUENCY RANGE | 30MHz ~ 1GHz   |                             |                 |
| INPUT POWER     | 120 Vac, 60 Hz | ENVIORNMENTAL<br>CONDITIONS | 23 °C, 65% RH   |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                               | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                 | 30.00          | 32.1 QP                       | 40.0              | -7.9           | 1.00 V                   | 235                        | 42.5                   | -10.4                          |
| 2                                                 | 121.38         | 30.6 QP                       | 43.5              | -12.9          | 1.00 V                   | 268                        | 41.4                   | -10.8                          |
| 3                                                 | 134.03         | 30.3 QP                       | 43.5              | -13.2          | 1.00 V                   | 103                        | 39.8                   | -9.5                           |
| 4                                                 | 164.96         | 29.3 QP                       | 43.5              | -14.2          | 1.00 V                   | 206                        | 38.0                   | -8.7                           |
| 5                                                 | 184.64         | 29.6 QP                       | 43.5              | -13.9          | 1.00 V                   | 6                          | 40.1                   | -10.5                          |
| 6                                                 | 557.17         | 35.1 QP                       | 46.0              | -10.9          | 1.49 V                   | 247                        | 35.4                   | -0.3                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.



## Mode B


|                        |                |                                 |                 |
|------------------------|----------------|---------------------------------|-----------------|
| <b>CHANNEL</b>         | TX Channel 39  | <b>DETECTOR FUNCTION</b>        | Quasi-Peak (QP) |
| <b>FREQUENCY RANGE</b> | 30MHz ~ 1GHz   |                                 |                 |
| <b>INPUT POWER</b>     | 120 Vac, 60 Hz | <b>ENVIRONMENTAL CONDITIONS</b> | 23 °C, 65% RH   |

### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| NO. | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
|-----|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1   | 30.00       | 28.4 QP                 | 40.0           | -11.6       | 1.00 H             | 304                  | 38.8             | -10.4                    |
| 2   | 66.55       | 27.2 QP                 | 40.0           | -12.8       | 1.51 H             | 337                  | 37.2             | -10.0                    |
| 3   | 82.01       | 21.5 QP                 | 40.0           | -18.5       | 2.00 H             | 259                  | 35.1             | -13.6                    |
| 4   | 107.32      | 20.9 QP                 | 43.5           | -22.6       | 2.00 H             | 82                   | 33.0             | -12.1                    |
| 5   | 171.99      | 21.2 QP                 | 43.5           | -22.3       | 1.00 H             | 264                  | 30.3             | -9.1                     |
| 6   | 540.30      | 30.4 QP                 | 46.0           | -15.6       | 1.00 H             | 206                  | 31.1             | -0.7                     |

### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




|                        |                |                                 |                 |
|------------------------|----------------|---------------------------------|-----------------|
| <b>CHANNEL</b>         | TX Channel 39  | <b>DETECTOR FUNCTION</b>        | Quasi-Peak (QP) |
| <b>FREQUENCY RANGE</b> | 30MHz ~ 1GHz   |                                 |                 |
| <b>INPUT POWER</b>     | 120 Vac, 60 Hz | <b>ENVIRONMENTAL CONDITIONS</b> | 23 °C, 65% RH   |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|---------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                               | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                 | 30.00       | 29.0 QP                 | 40.0           | -11.0       | 1.00 V             | 196                  | 39.4             | -10.4                    |
| 2                                                 | 66.55       | 27.4 QP                 | 40.0           | -12.6       | 1.99 V             | 348                  | 37.4             | -10.0                    |
| 3                                                 | 107.32      | 27.6 QP                 | 43.5           | -15.9       | 1.00 V             | 162                  | 39.7             | -12.1                    |
| 4                                                 | 134.03      | 29.2 QP                 | 43.5           | -14.3       | 1.49 V             | 57                   | 38.7             | -9.5                     |
| 5                                                 | 486.88      | 27.4 QP                 | 46.0           | -18.6       | 1.99 V             | 1                    | 29.2             | -1.8                     |
| 6                                                 | 673.86      | 30.9 QP                 | 46.0           | -15.1       | 1.49 V             | 17                   | 29.2             | 1.7                      |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

| Frequency (MHz) | Conducted Limit (dBuV) |         |
|-----------------|------------------------|---------|
|                 | Quasi-Peak             | Average |
| 0.15 - 0.5      | 66 - 56                | 56 - 46 |
| 0.50 - 5.0      | 56                     | 46      |
| 5.0 - 30.0      | 60                     | 50      |

Note: 1. The lower limit shall apply at the transition frequencies.  
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

### 4.2.2 Test Instruments

| Description & Manufacturer              | Model No.                | Serial No.     | Date of Calibration | Due Date of Calibration |
|-----------------------------------------|--------------------------|----------------|---------------------|-------------------------|
| Test Receiver<br>ROHDE & SCHWARZ        | ESCI                     | 100613         | Dec. 11, 2019       | Dec. 10, 2020           |
| RF signal cable<br>Woken                | 5D-FB                    | Cable-cond1-01 | Sep. 05, 2019       | Sep. 04, 2020           |
| LISN<br>ROHDE & SCHWARZ<br>(EUT)        | ENV216                   | 101826         | Feb. 20, 2020       | Feb. 19, 2021           |
| LISN<br>ROHDE & SCHWARZ<br>(Peripheral) | ESH3-Z5                  | 100311         | Aug. 22, 2019       | Aug. 21, 2020           |
| Software<br>ADT                         | BV ADT_Cond_<br>V7.3.7.4 | NA             | NA                  | NA                      |

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.  
 2. The test was performed in HwaYa Shielded Room 1.  
 3. The VCCI Site Registration No. is C-12040.

### 4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

**Note:** The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz - 30 MHz.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



**Note: 1.**Support units were connected to second LISN.

**2.**Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

#### 4.2.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Set the EUT under transmission condition continuously at specific channel frequency.

#### 4.2.7 Test Results

#### CONDUCTED WORST-CASE DATA


<LE 5.0>

|                 |                |                                          |                                      |
|-----------------|----------------|------------------------------------------|--------------------------------------|
| Frequency Range | 150kHz ~ 30MHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP) / Average (AV), 9kHz |
| Input Power     | 120Vac, 60Hz   | Environmental Conditions                 | 23°C, 67%RH                          |
| Tested by       | Adair Peng     | Test Date                                | 2020/7/9                             |
| Test Mode       | Mode A         |                                          |                                      |

| Phase Of Power : Line (L) |                 |                        |                      |       |                       |       |              |       |             |        |
|---------------------------|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
| No                        | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |       | Emission Level (dBuV) |       | Limit (dBuV) |       | Margin (dB) |        |
|                           |                 |                        | Q.P.                 | AV.   | Q.P.                  | AV.   | Q.P.         | AV.   | Q.P.        | AV.    |
| 1                         | 0.25948         | 9.63                   | 25.99                | 16.16 | 35.62                 | 25.79 | 61.45        | 51.45 | -25.83      | -25.66 |
| 2                         | 0.44716         | 9.65                   | 35.52                | 19.26 | 45.17                 | 28.91 | 56.93        | 46.93 | -11.76      | -18.02 |
| 3                         | 0.59965         | 9.66                   | 34.71                | 20.06 | 44.37                 | 29.72 | 56.00        | 46.00 | -11.63      | -16.28 |
| 4                         | 0.74432         | 9.67                   | 35.29                | 17.44 | 44.96                 | 27.11 | 56.00        | 46.00 | -11.04      | -18.89 |
| 5                         | 1.18615         | 9.69                   | 28.29                | 16.99 | 37.98                 | 26.68 | 56.00        | 46.00 | -18.02      | -19.32 |
| 6                         | 15.20350        | 9.90                   | 31.54                | 20.64 | 41.44                 | 30.54 | 60.00        | 50.00 | -18.56      | -19.46 |

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




|                 |                |                                          |                                      |
|-----------------|----------------|------------------------------------------|--------------------------------------|
| Frequency Range | 150kHz ~ 30MHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP) / Average (AV), 9kHz |
| Input Power     | 120Vac, 60Hz   | Environmental Conditions                 | 23°C, 67%RH                          |
| Tested by       | Adair Peng     | Test Date                                | 2020/7/9                             |
| Test Mode       | Mode A         |                                          |                                      |

| Phase Of Power : Neutral (N) |                 |                        |                      |       |                       |       |              |       |             |        |
|------------------------------|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
| No                           | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |       | Emission Level (dBuV) |       | Limit (dBuV) |       | Margin (dB) |        |
|                              |                 |                        | Q.P.                 | AV.   | Q.P.                  | AV.   | Q.P.         | AV.   | Q.P.        | AV.    |
| 1                            | 0.37678         | 9.67                   | 35.60                | 23.26 | 45.27                 | 32.93 | 58.35        | 48.35 | -13.08      | -15.42 |
| 2                            | 0.45107         | 9.67                   | 35.84                | 20.55 | 45.51                 | 30.22 | 56.86        | 46.86 | -11.35      | -16.64 |
| 3                            | 0.61138         | 9.68                   | 36.43                | 25.06 | 46.11                 | 34.74 | 56.00        | 46.00 | -9.89       | -11.26 |
| 4                            | 0.75605         | 9.69                   | 35.47                | 17.34 | 45.16                 | 27.03 | 56.00        | 46.00 | -10.84      | -18.97 |
| 5                            | 1.18608         | 9.71                   | 28.96                | 17.38 | 38.67                 | 27.09 | 56.00        | 46.00 | -17.33      | -18.91 |
| 6                            | 15.18395        | 9.98                   | 29.64                | 18.48 | 39.62                 | 28.46 | 60.00        | 50.00 | -20.38      | -21.54 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




|                 |                |                                          |                                      |
|-----------------|----------------|------------------------------------------|--------------------------------------|
| Frequency Range | 150kHz ~ 30MHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP) / Average (AV), 9kHz |
| Input Power     | 120Vac, 60Hz   | Environmental Conditions                 | 23°C, 67%RH                          |
| Tested by       | Adair Peng     | Test Date                                | 2020/7/9                             |
| Test Mode       | Mode B         |                                          |                                      |

| Phase Of Power : Line (L) |                 |                        |                      |       |                       |       |              |       |             |        |
|---------------------------|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
| No                        | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |       | Emission Level (dBuV) |       | Limit (dBuV) |       | Margin (dB) |        |
|                           |                 |                        | Q.P.                 | AV.   | Q.P.                  | AV.   | Q.P.         | AV.   | Q.P.        | AV.    |
| 1                         | 0.15782         | 9.63                   | 29.24                | 16.62 | 38.87                 | 26.25 | 65.58        | 55.58 | -26.71      | -29.33 |
| 2                         | 0.18519         | 9.62                   | 28.37                | 14.25 | 37.99                 | 23.87 | 64.25        | 54.25 | -26.26      | -30.38 |
| 3                         | 0.46280         | 9.65                   | 29.32                | 26.66 | 38.97                 | 36.31 | 56.64        | 46.64 | -17.67      | -10.33 |
| 4                         | 1.06885         | 9.68                   | 14.15                | 7.51  | 23.83                 | 17.19 | 56.00        | 46.00 | -32.17      | -28.81 |
| 5                         | 5.53016         | 9.81                   | 12.70                | 6.49  | 22.51                 | 16.30 | 60.00        | 50.00 | -37.49      | -33.70 |
| 6                         | 21.71756        | 9.91                   | 13.02                | 5.16  | 22.93                 | 15.07 | 60.00        | 50.00 | -37.07      | -34.93 |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




|                 |                |                                          |                                      |
|-----------------|----------------|------------------------------------------|--------------------------------------|
| Frequency Range | 150kHz ~ 30MHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP) / Average (AV), 9kHz |
| Input Power     | 120Vac, 60Hz   | Environmental Conditions                 | 23°C, 67%RH                          |
| Tested by       | Adair Peng     | Test Date                                | 2020/7/9                             |
| Test Mode       | Mode B         |                                          |                                      |

| Phase Of Power : Neutral (N) |                 |                        |                      |              |                       |              |              |              |               |              |
|------------------------------|-----------------|------------------------|----------------------|--------------|-----------------------|--------------|--------------|--------------|---------------|--------------|
| No                           | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |              | Emission Level (dBuV) |              | Limit (dBuV) |              | Margin (dB)   |              |
|                              |                 |                        | Q.P.                 | AV.          | Q.P.                  | AV.          | Q.P.         | AV.          | Q.P.          | AV.          |
| 1                            | 0.15391         | 9.66                   | 28.45                | 15.88        | 38.11                 | 25.54        | 65.79        | 55.79        | -27.68        | -30.25       |
| 2                            | <b>0.46280</b>  | <b>9.67</b>            | <b>30.87</b>         | <b>30.80</b> | <b>40.54</b>          | <b>40.47</b> | <b>56.64</b> | <b>46.64</b> | <b>-16.10</b> | <b>-6.17</b> |
| 3                            | 0.77169         | 9.69                   | 17.57                | 13.23        | 27.26                 | 22.92        | 56.00        | 46.00        | -28.74        | -23.08       |
| 4                            | 1.10795         | 9.71                   | 16.85                | 12.82        | 26.56                 | 22.53        | 56.00        | 46.00        | -29.44        | -23.47       |
| 5                            | 4.67387         | 9.83                   | 16.74                | 6.71         | 26.57                 | 16.54        | 56.00        | 46.00        | -29.43        | -29.46       |
| 6                            | 20.86518        | 10.03                  | 10.45                | 3.51         | 20.48                 | 13.54        | 60.00        | 50.00        | -39.52        | -36.46       |

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




### 4.3 6 dB Bandwidth Measurement

#### 4.3.1 Limits of 6 dB Bandwidth Measurement

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

- Set resolution bandwidth (RBW) = 100 kHz
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 4.3.5 Deviation from Test Standard

No deviation.


#### 4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.3.7 Test Results


<LE 4.0>

| Channel | Frequency (MHz) | 6 dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|----------------------|---------------------|-------------|
| 0       | 2402            | 0.73                 | 0.5                 | Pass        |
| 19      | 2440            | 0.73                 | 0.5                 | Pass        |
| 39      | 2480            | 0.73                 | 0.5                 | Pass        |




<LE 5.0>

| Channel | Frequency (MHz) | 6 dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|----------------------|---------------------|-------------|
| 0       | 2402            | 1.26                 | 0.5                 | Pass        |
| 19      | 2440            | 1.27                 | 0.5                 | Pass        |
| 39      | 2480            | 1.27                 | 0.5                 | Pass        |



## 4.4 Occupied Bandwidth Measurement

### 4.4.1 Test Setup



### 4.4.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.4.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1 % to 5 % of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to sampling. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

### 4.4.4 Deviation from Test Standard

No deviation.


### 4.4.5 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.4.6 Test Results


<LE 4.0>

| Channel | Frequency (MHz) | Occupied Bandwidth (MHz) | Pass / Fail |
|---------|-----------------|--------------------------|-------------|
| 0       | 2402            | 1.03                     | Pass        |
| 19      | 2440            | 1.03                     | Pass        |
| 39      | 2480            | 1.03                     | Pass        |



<LE 5.0>

| Channel | Frequency (MHz) | Occupied Bandwidth (MHz) | Pass / Fail |
|---------|-----------------|--------------------------|-------------|
| 0       | 2402            | 2.05                     | Pass        |
| 19      | 2440            | 2.05                     | Pass        |
| 39      | 2480            | 2.05                     | Pass        |




## 4.5 Conducted Output Power Measurement

### 4.5.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

### 4.5.5 Deviation from Test Standard

No deviation.

### 4.5.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.5.7 Test Results

##### <LE 4.0>

| Channel | Freq. (MHz) | Peak Power |       | Average Power |       | Power Limit<br>(mW) | Pass / Fail |
|---------|-------------|------------|-------|---------------|-------|---------------------|-------------|
|         |             | (mW)       | (dBm) | (mW)          | (dBm) |                     |             |
| 0       | 2402        | 2.193      | 3.41  | 2.163         | 3.35  | 1000                | Pass        |
| 19      | 2440        | 2.323      | 3.66  | 2.301         | 3.62  | 1000                | Pass        |
| 39      | 2480        | 2.443      | 3.88  | 2.415         | 3.83  | 1000                | Pass        |

##### <LE 5.0>


| Channel | Freq. (MHz) | Peak Power |       | Average Power |       | Power Limit<br>(mW) | Pass / Fail |
|---------|-------------|------------|-------|---------------|-------|---------------------|-------------|
|         |             | (mW)       | (dBm) | (mW)          | (dBm) |                     |             |
| 0       | 2402        | 2.218      | 3.46  | 2.188         | 3.40  | 1000                | Pass        |
| 19      | 2440        | 2.371      | 3.75  | 2.344         | 3.70  | 1000                | Pass        |
| 39      | 2480        | 2.449      | 3.89  | 2.443         | 3.88  | 1000                | Pass        |

## 4.6 Power Spectral Density Measurement

### 4.6.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### 4.6.2 Test Setup



### 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 Test Procedure

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d. Set the VBW  $\geq 3 \times \text{RBW}$ .
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.

### 4.6.5 Deviation from Test Standard

No deviation.


### 4.6.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.6.7 Test Results


<LE 4.0>

| Channel | Frequency (MHz) | PSD (dBm/3 kHz) | Limit (dBm/3 kHz) | Pass / Fail |
|---------|-----------------|-----------------|-------------------|-------------|
| 0       | 2402            | -11.18          | 8                 | Pass        |
| 19      | 2440            | -10.78          | 8                 | Pass        |
| 39      | 2480            | -10.67          | 8                 | Pass        |



<LE 5.0>

| Channel | Frequency (MHz) | PSD (dBm/3 kHz) | Limit (dBm/3 kHz) | Pass / Fail |
|---------|-----------------|-----------------|-------------------|-------------|
| 0       | 2402            | -13.95          | 8                 | Pass        |
| 19      | 2440            | -13.60          | 8                 | Pass        |
| 39      | 2480            | -13.38          | 8                 | Pass        |




## 4.7 Conducted Out of Band Emission Measurement

### 4.7.1 Limits of Conducted Out of Band Emission Measurement

Below -20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

### 4.7.2 Test Setup



### 4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.7.4 Test Procedure

#### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

#### MEASUREMENT PROCEDURE OOBE

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

### 4.7.5 Deviation from Test Standard

No deviation.


### 4.7.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.7.7 Test Results



The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20 dB offset below D1. It shows compliance with the requirement.

<LE 4.0>





<LE 5.0>



### Ch 0




### Ch 19




### Ch 39



### Ch 0 Band Edge



### Ch 39 Band Edge



## 5 Photographs of the Test Configuration

Please refer to the attached file (Reference no.: 200618C02 (TSup photo)).

## 6 Construction Photos of EUT

Please refer to the attached file (200618C02 (EUT photo))

## Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---