



RF EXPOSURE REPORT

REPORT NO.: SA980708L01

MODEL NO.: HDR170, HDR180

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Sennheiser electronic GmbH & Co.KG

ADDRESS: Am Labor 1, D-30900 Wedemark Postfach 100
264, D-30892 Wedemark, Germany

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan,
R.O.C.



No evaluation required if power is below this threshold:

| F(GHz) | mW |
|--------|-------|
| Low | 2.403 |
| High | 2.478 |

Maximum measured transmitter power:

| Pout (dBm) | Pout (mW) |
|-----------------|-----------|
| Conducted Power | 8.860 |
| EIRP Power | 13.510 |

***Note:** The antenna is Inverted F antenna with 4.65dBi gain

Threshold for no SAR evaluation is 24.61mW

Transmitter power is 22.44mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold