



NVLAP LAB CODE 200707-0



FCC PART 15.231

MEASUREMENT AND TEST REPORT

For

PRIMATRONIX LTD

Unit 1, 21/F QPL Industrial Bldg, 126-140 Texaco Road,
Tsuen Wan NT, Hong Kong

FCC ID: DYFSH200

Report Type: Original Report	Product Type: Activator (Remote Controller)
Test Engineer: <u>Thomas Zhang</u>	<i>Thomas Zhang</i>
Report Number: <u>RSZ10030905</u>	
Report Date: <u>2010-04-21</u>	
Reviewed By: <u>EMC Engineer</u>	<i>Merry Zhao</i>
Prepared By:	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, NIST, or any agency of the Federal Government.
* This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "*" (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION.....3

 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)3

 EUT PHOTOGRAPH3

 OBJECTIVE3

 RELATED SUBMITTAL(S)/GRANT(S).....4

 TEST METHODOLOGY4

 TEST FACILITY4

SYSTEM TEST CONFIGURATION.....5

 JUSTIFICATION5

 SPECIAL ACCESSORIES.....5

 EQUIPMENT MODIFICATIONS5

 EXTERNAL I/O CABLE.....5

 CONFIGURATION OF TEST SETUP5

 BLOCK DIAGRAM OF TEST SETUP5

SUMMARY OF TEST RESULTS6

FCC §15.203 - ANTENNA REQUIREMENT.....7

 STANDARD APPLICABLE7

FCC §15.205, §15.209 & §15.231(B) - RADIATED EMISSIONS8

 MEASUREMENT UNCERTAINTY.....8

 EUT SETUP8

 EMI TEST RECEIVER SETUP.....8

 TEST EQUIPMENT LIST AND DETAILS.....9

 TEST PROCEDURE9

 APPLICABLE STANDARD9

 CORRECTED AMPLITUDE & MARGIN CALCULATION9

 TEST RESULTS SUMMARY10

 TEST DATA10

FCC §15.231(A) - DEACTIVATION TESTING12

 REQUIREMENT12

 EUT SETUP12

 TEST EQUIPMENT LIST AND DETAILS.....12

 TEST PROCEDURE13

 TEST DATA13

FCC §15.231(C) – 20 DB BANDWIDTH TESTING14

 REQUIREMENT14

 TEST EQUIPMENT LIST AND DETAILS.....14

 TEST PROCEDURE14

 TEST DATA14

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The PRIMATRONIX LTD's product, model: STEPHEAR (FCC ID: DYFSH200) or the "EUT" as referred to in this report is a remote controller of Navigation and Information Reference Point System, which measures approximately 6.0 cm L x 4.0 cm W x 1.8 cm H, rated input voltage: 3.7V 200mAh battery.

EUT specification:

Frequency: 433.57 MHz \pm 120 kHz;

Modulation: FSK;

** All measurement and test data in this report was gathered from production sample serial number: 1003029 (Assigned by BAEL, Shenzhen). The EUT was received on 2010-03-09.*

EUT Photograph



Objective

This document is a test report based on the Electromagnetic Interference (EMI) tests performed on the EUT. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4-2003.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.231 rules.

Related Submittal(s)/Grant(s)

No Related Submittals

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4 - 2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 21, 2007. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



NVLAP LAB CODE 200707-0

The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

Special Accessories

The special accessories were provided by Bay Area Compliance Laboratories Corp. (Shenzhen).

Equipment Modifications

No modifications were made to the unit tested.


External I/O Cable

Configuration of Test Setup



EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliant
§15.207(a)	Conducted Emissions	N/A
§15.205, §15.209, §15.35(c), §15.231(b)	Radiated Emissions	Compliant
§15.231(a)	Deactivation Testing	Compliant
§15.231(c)	20 dB Band Width Testing	Compliant

Note: N/A, the device operates with battery only.

FCC §15.203 - ANTENNA REQUIREMENT

Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Result: Compliant.

The EUT has a printed loop antenna on PCB; it is permanently attached to the PCB. The maximum gain is -12 dBi, Please refer to the EUT internal photos.


FCC §15.205, §15.209 & §15.231(b) - RADIATED EMISSIONS

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emission measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is ± 4.0 dB.

EUT Setup



The radiated emission tests were performed in the 3 meters chamber B test site, using the setup accordance with the ANSI C63.4 - 2003. The specification used was the FCC 15.205 § 15.209 and 15.231.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 5 GHz.

During the radiated emission test, the test receiver was set with the following configurations:

<i>Frequency Range</i>	<i>RBW</i>	<i>Video B/W</i>	<i>Detector</i>
30MHz – 1000 MHz	100 kHz	300 kHz	QP
1000 MHz – 5 GHz	1 MHz	3 MHz	PK
1000 MHz – 5 GHz	1 MHz	10 Hz	AV

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447D	2944A09795	2009-11-15	2010-11-15
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2009-11-24	2010-11-24
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2010-03-11	2011-03-11
HP	Amplifier	8449B	3008A00277	2009-09-12	2010-09-11
Sunol Sciences	Horn Antenna	DRH-118	A052604	2009-05-05	2010-05-04

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Peak and Average detection mode.

Applicable Standard

According to FCC §15.231(b), the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field Strength of Fundamental (Microvolts /meter)	Field Strength of spurious emissions ((Microvolts /meter)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	1,250 to 3,370 *	125 to 375 *
174-260	3,750	375
260-470	3,750 to 12,500*	375 to 1,250*
Above 470	12,500	1,250

*Linear interpolations.

The above field strength limits are specified at a distance of 3-meters the tighter limits apply at the band edges.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 5.8 dB means the emission is 5.8 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.205, §15.209 §15.231 (b), with the worst margin reading of:

30-1000 MHz:

15.17 dB at **433.57 MHz** in the **Vertical** polarization.

Above 1 GHz:

11.97 dB at **1300.71 MHz** in the **Horizontal** polarization

Test Data

Environmental Conditions


Temperature:	22 ° C
Relative Humidity:	50 %
ATM Pressure:	100.9 kPa

The testing was performed by Thomas Zhang on 2009-04-03 and 2010-04-07.

Test Mode: Transmitting

Frequency (MHz)	S.A. Reading (dBµV/m)	Detector (PK/AV)	Direction (Degree)	Test Antenna			Cable Loss (dB)	Pre-Amp. (dB)	Cord. Amp. (dBµV/m)	FCC Part 15.231(b)/15.209		
				Height (m)	Polar (H/V)	Factor (dB)				Limit (dBµV/m)	Margin (dB)	Remarks
30-1000 MHz												
433.57	75.36	AV	293	1.55	V	14.5	1.73	25.96	65.63	80.8	15.17	Fund.
867.14	41.64	AV	327	1.91	V	19.9	3.86	25.64	39.76	60.8	21.04	Harmonic
433.57	65.79	AV	76	1.11	H	14.5	1.73	25.96	56.06	80.8	24.74	Fund.
867.14	37.68	AV	360	1.00	H	19.9	3.86	25.64	35.8	60.8	25.00	Harmonic
433.57	79.12	PK	293	1.55	V	14.5	1.73	25.96	69.39	100.8	31.41	Fund.
867.14	47.30	PK	327	1.91	V	19.9	3.86	25.64	45.42	80.8	35.38	Harmonic
433.57	69.3	PK	76	1.11	H	14.5	1.73	25.96	59.57	100.8	41.23	Fund.
867.14	41.2	PK	360	1.00	H	19.9	3.86	25.64	39.32	80.8	41.48	Harmonic
1-5 GHz												
1300.71	44.56	AV	176	1.70	H	26.7	5.37	34.6	42.03	54	11.97	Harmonic
1300.71	43.79	AV	176	1.70	H	26.7	5.37	34.6	41.26	54	12.74	Harmonic
1734.28	42.16	AV	235	1.51	V	28.8	5.99	34.2	42.75	60.8	18.05	Harmonic
1734.28	42.34	AV	90	1.61	H	28.3	5.99	34.2	42.43	60.8	18.37	Harmonic
1300.71	48.65	PK	176	1.70	H	26.7	5.37	34.6	46.12	74	27.88	Harmonic
1300.71	48.65	PK	176	1.70	H	26.7	5.37	34.6	46.12	74	27.88	Harmonic
1734.28	46.39	PK	235	1.51	V	28.8	5.99	34.2	46.98	80.8	33.82	Harmonic
1734.28	46.26	PK	90	1.61	H	28.3	5.99	34.2	46.35	80.8	34.45	Harmonic

Duty Cycle =100%, Duty Cycle Factor =20 log (Duty Cycle) =0 dB




Date: 3.APR.2010 12:22:25

FCC §15.231(a) - DEACTIVATION TESTING

Requirement

Per FCC §15.231(a)(1), a manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

EUT Setup



The deactivation test was performed in the 3 meters chamber B test site, using the setup accordance with the ANSI C63.4 - 2003. The specification used was the FCC 15.231(a) limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2009-11-24	2010-11-24
HP	Amplifier	8447E	1937A01046	2009-08-02	2010-08-02
Sunol Sciences	Bilog Antenna	JB1	A040904-2	2009-05-05	2010-05-04

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

Test Procedure

1. Place the EUT in the chamber and set it in transmitting mode.
2. Set center frequency of spectrum analyzer=operating frequency.
3. Set the spectrum analyzer as RBW=100 kHz, VBW=300 kHz, Span=0Hz.
4. Repeat above procedures until all frequency measured was complete.

Test Data


Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	56 %
ATM Pressure:	103.2 kPa

The testing was performed by Thomas Zhang on 2010-04-07.

Test Mode: Transmitting

Test Result: Compliant, please refer to following plot



Date: 7.APR.2010 00:30:13

FCC §15.231(c) – 20 dB BANDWIDTH TESTING

Requirement

Per 15.231(c), The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2009-11-24	2010-11-24
HP	Amplifier	8447E	1937A01046	2009-08-02	2010-08-02
Sunol Sciences	Bilog Antenna	JB1	A040904-2	2009-05-05	2010-05-04

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed per the NVLAP requirements, traceable to NIST.

Test Procedure

With the EUT's antenna attached, the waveform was received by the test antenna which was connected to the spectrum analyzer, plot the 20 dB bandwidth.

Test Data

Environmental Conditions

Temperature:	25 ° C
Relative Humidity:	56 %
ATM Pressure:	100.9 kPa

The testing was performed by Thomas Zhang on 2010-04-03.


Test Mode: Transmitting

Please refer to following table and plot.

Channel Frequency (MHz)	20 dB Bandwidth (kHz)	Limit (kHz)	Result
433.57	180.0	1083.9	Pass

Note: Limit = 0.25% * Center Frequency = 0.25% * 433.57 MHz = 1.0839 MHz = 1083.9 kHz
20 dB Bandwidth = 180.0 kHz < 1083.9 kHz

20 dB Bandwidth



Date: 3.APR.2010 13:39:51

***** END OF REPORT *****