

FCC SAR TEST REPORT

FCC ID : E2K-RTL8852BE
Equipment : 11ax RTL8852BE Combo module
Brand Name : REALTEK
Model Name : RTL8852BE
PMN : 11ax RTL8852BE Combo module
Applicant : Dell Inc.
One Dell Way Round Rock, TX 78682, USA
Manufacturer : Dell Inc.
One Dell Way Round Rock, TX 78682, USA
Standard : FCC 47 CFR Part 2 (2.1093)

The product was installed into Portable Computer (Brand Name DELL, Model Name: P168G) during test.

The product was received on Nov. 01, 2022 and testing was started from Dec. 02, 2022 and completed on Dec. 03, 2022. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample provide by manufacturer and the test data has been evaluated in accordance with the test procedures given in 47 CFR Part 2.1093 and FCC KDB and has been pass the FCC requirement.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager



Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan



Table of Contents

1. Statement of Compliance	4
2. Guidance Applied.....	4
3. Equipment Under Test (EUT) Information.....	5
3.1 General Information	5
3.2 Sensor Triggering angle and power verification	7
4. RF Exposure Limits.....	10
4.1 Uncontrolled Environment.....	10
4.2 Controlled Environment.....	10
5. Specific Absorption Rate (SAR).....	11
5.1 Introduction	11
5.2 SAR Definition.....	11
6. System Description and Setup	12
6.1 Test Site Location.....	12
6.2 E-Field Probe	13
6.3 Data Acquisition Electronics (DAE)	13
6.4 Phantom.....	14
6.5 Device Holder.....	15
7. Measurement Procedures	16
7.1 Spatial Peak SAR Evaluation.....	16
7.2 Power Reference Measurement.....	17
7.3 Area Scan	17
7.4 Zoom Scan.....	18
7.5 Volume Scan Procedures.....	18
7.6 Power Drift Monitoring.....	18
8. Test Equipment List.....	19
9. System Verification	20
9.1 Tissue Verification	20
9.2 System Performance Check Results.....	20
10. RF Exposure Positions	21
10.1 SAR Testing for Tablet.....	21
11. WiFi/Bluetooth Output Power (Unit: dBm)	22
12. Antenna Location	32
13. SAR Test Results	35
13.1 Body SAR	36
13.2 Repeated SAR Measurement	37
14. Simultaneous Transmission Analysis	38
14.1 Body Exposure Conditions	38
14.2 SPLSR Evaluation and Analysis.....	38
15. Uncertainty Assessment	39
16. References.....	39
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	

History of this test report

Report No.	Version	Description	Issued Date
FA2N0319	01	Initial issue of report	Dec. 29, 2022

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) for Dell Inc., 11ax RTL8852BE Combo module, RTL8852BE, are as follows.

Equipment Class	Frequency Band		Highest SAR Summary	Highest Simultaneous Transmission 1g SAR (W/kg)
			Body (Separation 0mm)	
			1g SAR (W/kg)	
DTS	WLAN	2.4GHz WLAN	0.82	1.32
NII		5GHz WLAN	0.95	0.95
DSS	2.4GHz Band	Bluetooth	0.18	0.49
Date of Testing:			2022/12/2 ~ 2022/12/3	

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation and the FCC designation No. TW3786 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications

Reviewed by: Jason Wang
Report Producer: Daisy Peng

2. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards, the below KDB standard may not including in the TAF code without accreditation.

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 616217 D04 SAR for laptop and tablets v01r02

3. Equipment Under Test (EUT) Information

3.1 General Information

Product Feature & Specification	
Equipment Name	11ax RTL8852BE Combo module
Brand Name	REALTEK
Model Name	RTL8852BE
PMN	11ax RTL8852BE Combo module
FCC ID	E2K-RTL8852BE
Wireless Technology and Frequency Range	WLAN 2.4 GHz Band: 2400 MHz ~ 2483.5 MHz WLAN 5.2 GHz Band: 5150 MHz ~ 5250 MHz WLAN 5.3 GHz Band: 5250 MHz ~ 5350 MHz WLAN 5.6 GHz Band: 5470 MHz ~ 5725 MHz WLAN 5.8 GHz Band: 5725 MHz ~ 5850 MHz WLAN 5.8 GHz UNII4 Band: 5850 MHz ~ 5895 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz
Mode	WLAN: 802.11a/b/g/n/ac/ax HT20/HT40/VHT20/VHT40/VHT80/HE20/HE40/HE80 Bluetooth BR/EDR/LE
Remark: 1. This device has two antenna vendors; RF exposure evaluation selects Auden as the main test, Speed will spot check worst case found in Auden. 2. This device is convertible type notebook PC, and there have Laptop and Tablet two usage way, when end user is used different mode which the device will according current mode to limit different maximum power.	

Host Information	
Equipment Name	Portable Computer
Brand Name	DELL
Model Name	P168G
EUT Stage	Identical Prototype

Tablet Mode									
Antenna Information									
1	Ant. Type	PIFA			2	Ant. Type	PIFA		
	Model No.	81EABW15.G19				Model No.	81EABW15.G20		
	Peak Gain (dBi)			Peak Gain (dBi)					
	2400~2483.5MHz	2	5470~5725MHz	2.76		2400~2483.5MHz	1.03	5470~5725MHz	0.98
	5150~5250MHz	2.25	5725~5850MHz	1.7		5150~5250MHz	1.93	5725~5850MHz	1.05
	5250~5350MHz	1.4	5925~7125MHz	2.91		5250~5350MHz	2.53	5925~7125MHz	2.4
Antenna Information									
1	Ant. Type	PIFA			2	Ant. Type	PIFA		
	Model No.	F-0G-FS-6139-001				Model No.	F-0G-FS-6139-002		
	Peak Gain (dBi)			Peak Gain (dBi)					
	2400~2483.5MHz	2	5470~5725MHz	2.76		2400~2483.5MHz	1.03	5470~5725MHz	0.98
	5150~5250MHz	2.25	5725~5850MHz	1.7		5150~5250MHz	1.93	5725~5850MHz	1.05
	5250~5350MHz	1.4	5925~7125MHz	2.91		5250~5350MHz	2.53	5925~7125MHz	2.4

Laptop Mode									
Antenna Information									
1	Ant. Type	PIFA			2	Ant. Type	PIFA		
	Model No.	81EABW15.G19				Model No.	81EABW15.G20		
	Peak Gain (dBi)			Peak Gain (dBi)					
	2400~2483.5MHz	2.62	5470~5725MHz	3.38		2400~2483.5MHz	2.03	5470~5725MHz	3.69
	5150~5250MHz	1.46	5725~5850MHz	3.74		5150~5250MHz	1.98	5725~5850MHz	3.21
	5250~5350MHz	1.45	5850~5895MHz	3.98		5250~5350MHz	2.61	5925~7125MHz	3.98
*Antenna Information									
1	Ant. Type	PIFA			2	Ant. Type	PIFA		
	Model No.	F-0G-FS-6139-001				Model No.	F-0G-FS-6139-002		
	Peak Gain (dBi)			Peak Gain (dBi)					
	2400~2483.5MHz	2.62	5470~5725MHz	3.38		2400~2483.5MHz	2.03	5470~5725MHz	3.69
	5150~5250MHz	1.46	5725~5850MHz	3.74		5150~5250MHz	1.98	5725~5850MHz	3.21
	5250~5350MHz	1.45	5850~5895MHz	3.98		5250~5350MHz	2.61	5925~7125MHz	3.98

3.2 Sensor Triggering angle and power verification

General Note:

- The following guidance should be applied to laptops/tablets that use Hall Effect or gravity sensors to detect lid angle for the purpose of power reduction:

Step 1: With the lid is in closed mode (0 degrees), open the screen in 10 degree steps until laptop mode is obtained
Step 2: Lower the screen 5 degrees. Closed mode should be reobtained. If not keep lowering in 5 degree steps
Step 3: Open the screen in 1 degree steps until laptop mode is reobtained
Step 4: Continue opening the screen in 1 degree steps until at least 5 degrees past where laptop mode was obtained
Step 5: Then continue opening the screen in 10 degree steps until tablet mode is obtained
Step 6: Power measurements should be taken at each step
Step 7: Reverse this procedure going from tablet mode back down to closed mode

when the screen angle is from 0 degree to 360 degree														
Screen angle (degree) v.s. power	Wireless		WLAN Ant 1						WLAN Ant 2					
	Band		2.4GHz WLAN	5.2GHz WLAN	5.3GHz WLAN	5.5GHz WLAN	5.8GHz WLAN	5.9GHz WLAN	2.4GHz WLAN	5.2GHz WLAN	5.3GHz WLAN	5.5GHz WLAN	5.8GHz WLAN	5.9GHz WLAN
	Lid Close	0	Standby	Standby	Standby	Standby	Standby	Standby	Standby	Standby	Standby	Standby	Standby	Standby
Notebook	1	17.4	13.9	14.0	14.0	13.3	13.2	17.7	13.9	13.7	13.8	13.3	13.2	
	2	17.5	13.8	13.8	13.7	13.4	13.2	17.3	13.7	14.0	14.1	13.2	13.4	
	3	17.5	13.6	14.1	14.0	13.1	13.5	17.7	14.0	13.7	14.1	13.2	13.5	
	4	17.7	13.8	13.7	13.8	13.4	13.1	17.3	13.8	14.0	13.6	13.5	13.6	
	5	17.4	13.7	13.8	13.9	13.1	13.3	17.5	13.6	13.9	13.9	13.4	13.3	
	10	17.5	13.8	13.9	14.0	13.2	13.4	17.5	13.8	13.7	13.7	13.4	13.4	
	20	17.5	13.7	13.8	14.0	13.5	13.5	17.5	13.8	14.0	14.0	13.3	13.4	
	30	17.2	13.9	13.6	13.7	13.4	13.1	17.2	13.9	13.9	14.0	13.3	13.3	
	40	17.3	13.6	13.9	13.9	13.3	13.3	17.3	13.8	14.0	13.8	13.3	13.2	
	50	17.5	13.7	13.7	14.0	13.1	13.6	17.3	14.0	14.0	13.9	13.4	13.3	
	60	17.4	13.8	13.9	13.7	13.2	13.3	17.5	13.8	14.0	13.9	13.4	13.5	
	70	17.6	14.0	13.9	13.8	13.4	13.1	17.3	14.1	14.1	13.7	13.4	13.6	
	80	17.3	13.9	13.9	14.1	13.1	13.5	17.4	13.8	13.6	13.7	13.5	13.5	
	90	17.6	13.8	13.7	13.7	13.5	13.3	17.6	13.8	14.1	13.6	13.2	13.5	
	100	17.6	13.8	13.9	13.6	13.1	13.2	17.6	13.6	13.6	13.8	13.5	13.4	
	110	17.7	13.9	13.9	13.8	13.1	13.3	17.5	14.0	13.8	14.0	13.6	13.5	
	120	17.4	14.1	14.0	13.9	13.1	13.1	17.3	13.7	13.7	13.9	13.6	13.4	
	130	17.7	13.8	13.8	13.8	13.6	13.2	17.4	14.0	14.1	14.0	13.2	13.4	
	140	17.6	14.1	13.9	13.6	13.5	13.3	17.6	14.0	13.8	13.9	13.5	13.3	
	150	17.4	13.8	13.9	14.1	13.6	13.6	17.6	13.6	14.0	13.9	13.4	13.4	
	160	17.5	13.7	13.6	14.0	13.5	13.2	17.2	13.8	14.0	13.8	13.6	13.5	
	170	17.5	14.1	13.9	14.1	13.1	13.3	17.3	14.0	13.6	13.9	13.6	13.5	
	180	17.5	14.0	13.6	14.1	13.2	13.5	17.4	13.9	13.9	13.7	13.2	13.1	
	185	17.5	14.2	14.6	14.6	13.3	13.3	17.5	14.4	14.5	14.6	13.4	13.5	
	186	17.4	13.9	14.0	14.1	13.1	13.2	17.7	14.0	13.7	13.7	13.5	13.1	
	187	17.6	13.8	13.6	13.7	13.2	13.5	17.2	13.7	14.0	14.0	13.2	13.3	
	188	17.4	13.8	14.0	13.9	13.2	13.4	17.5	14.0	13.8	14.0	13.4	13.1	
	189	17.3	14.0	13.9	13.6	13.1	13.1	17.7	13.8	13.8	14.1	13.4	13.4	
	190	17.6	14.1	13.8	13.6	13.3	13.3	17.5	14.0	13.7	13.7	13.3	13.3	
Tablet Mode	191	15.7	10.2	10.6	10.2	10.3	10.4	15.6	10.6	10.7	10.3	10.2	10.3	
	192	15.3	10.4	10.4	10.7	10.5	10.4	15.5	10.4	10.6	10.5	10.5	10.4	
	193	15.5	10.5	10.6	10.3	10.7	10.3	15.5	10.4	10.6	10.5	10.6	10.7	
	194	15.4	10.5	10.2	10.6	10.7	10.5	15.7	10.7	10.6	10.5	10.3	10.5	
	195	15.5	10.2	10.2	10.7	10.3	10.4	15.4	10.6	10.7	10.4	10.6	10.5	
	200	15.5	10.4	10.6	10.6	10.4	10.7	15.4	10.7	10.3	10.3	10.4	10.7	
	205	15.4	10.6	10.2	10.6	10.3	10.6	15.4	10.5	10.5	10.4	10.3	10.5	
	210	15.7	10.4	10.3	10.6	10.4	10.4	15.5	10.5	10.3	10.4	10.7	10.2	
	220	15.6	10.4	10.6	10.4	10.2	10.3	15.7	10.3	10.5	10.5	10.6	10.6	
	230	15.4	10.4	10.7	10.5	10.4	10.6	15.5	10.4	10.3	10.3	10.7	10.6	
240	15.6	10.2	10.3	10.6	10.4	10.3	15.3	10.3	10.4	10.2	10.4	10.6		



FCC SAR TEST REPORT

Report No. : FA2N0319

250	15.6	10.6	10.7	10.5	10.3	10.3	15.3	10.3	10.5	10.4	10.7	10.2
260	15.3	10.4	10.3	10.7	10.6	10.2	15.6	10.3	10.2	10.4	10.3	10.5
270	15.5	10.4	10.6	10.3	10.5	10.5	15.4	10.3	10.3	10.5	10.3	10.6
280	15.6	10.6	10.6	10.6	10.2	10.5	15.3	10.6	10.2	10.7	10.3	10.4
290	15.4	10.3	10.2	10.3	10.2	10.4	15.5	10.3	10.7	10.5	10.4	10.7
300	15.6	10.7	10.5	10.4	10.6	10.7	15.7	10.6	10.5	10.6	10.3	10.7
310	15.5	10.3	10.2	10.4	10.4	10.3	15.4	10.5	10.4	10.7	10.6	10.3
320	15.4	10.3	10.3	10.2	10.2	10.6	15.6	10.4	10.3	10.3	10.4	10.5
330	15.4	10.3	10.2	10.6	10.2	10.6	15.6	10.6	10.5	10.2	10.6	10.5
340	15.5	10.2	10.5	10.4	10.5	10.3	15.6	10.6	10.4	10.5	10.6	10.7
350	15.6	10.4	10.2	10.5	10.7	10.5	15.3	10.2	10.4	10.6	10.3	10.4
360	15.4	10.6	10.2	10.4	10.7	10.7	15.4	10.7	10.6	10.5	10.7	10.4

when the screen angle is from 0 degree to 360 degree														
Screen angle (degree) v.s. power	Wireless		WLAN Ant 1						WLAN Ant 2					
	Band		2.4GHz WLAN	5.2GHz WLAN	5.3GHz WLAN	5.5GHz WLAN	5.8GHz WLAN	5.9GHz WLAN	2.4GHz WLAN	5.2GHz WLAN	5.3GHz WLAN	5.5GHz WLAN	5.8GHz WLAN	5.9GHz WLAN
Tablet Mode	360	15.5	10.6	10.2	10.3	10.6	10.7	15.3	10.4	10.3	10.2	10.5	10.6	
	350	15.5	10.3	10.5	10.6	10.3	10.6	15.2	10.4	10.6	10.3	10.6	10.4	
	340	15.3	10.5	10.7	10.3	10.5	10.4	15.6	10.3	10.2	10.4	10.7	10.6	
	330	15.5	10.5	10.2	10.3	10.2	10.6	15.6	10.2	10.5	10.3	10.7	10.5	
	320	15.5	10.6	10.2	10.4	10.7	10.6	15.4	10.5	10.5	10.5	10.6	10.4	
	310	15.7	10.3	10.4	10.6	10.4	10.6	15.3	10.3	10.5	10.3	10.2	10.3	
	300	15.4	10.4	10.3	10.2	10.6	10.5	15.3	10.3	10.5	10.3	10.3	10.7	
	290	15.3	10.3	10.3	10.6	10.6	10.3	15.4	10.5	10.3	10.5	10.7	10.6	
	280	15.2	10.3	10.6	10.2	10.3	10.4	15.2	10.4	10.5	10.7	10.5	10.7	
	270	15.5	10.5	10.6	10.5	10.7	10.5	15.7	10.6	10.7	10.4	10.4	10.3	
	260	15.3	10.2	10.4	10.3	10.4	10.3	15.4	10.5	10.3	10.4	10.4	10.6	
	250	15.6	10.3	10.3	10.6	10.2	10.5	15.4	10.3	10.6	10.2	10.6	10.3	
	240	15.5	10.6	10.2	10.6	10.3	10.5	15.7	10.6	10.3	10.3	10.3	10.2	
	230	15.4	10.3	10.2	10.7	10.4	10.4	15.2	10.3	10.6	10.6	10.3	10.4	
	220	15.3	10.2	10.5	10.6	10.3	10.6	15.7	10.5	10.6	10.3	10.6	10.5	
	210	15.6	10.3	10.3	10.3	10.6	10.6	15.5	10.3	10.3	10.2	10.3	10.3	
	200	15.5	10.3	10.3	10.7	10.5	10.4	15.3	10.3	10.3	10.5	10.6	10.2	
	195	15.7	10.3	10.4	10.3	10.2	10.7	15.2	10.5	10.5	10.6	10.4	10.4	
	194	15.5	10.4	10.4	10.7	10.4	10.5	15.2	10.3	10.3	10.7	10.5	10.4	
	193	15.3	10.2	10.2	10.4	10.4	10.7	15.4	10.4	10.4	10.5	10.5	10.2	
	192	15.7	10.3	10.4	10.3	10.3	10.6	15.5	10.6	10.3	10.5	10.2	10.4	
	191	15.5	10.6	10.2	10.3	10.2	10.6	15.2	10.6	10.3	10.4	10.6	10.7	
	190	15.6	10.5	10.7	10.7	10.4	10.3	15.2	10.4	10.3	10.7	10.6	10.3	
	Notebook	189	17.5	13.7	13.7	13.9	13.4	13.6	17.3	14.2	13.7	14.1	13.2	13.5
		188	17.4	13.9	14.1	13.8	13.4	13.5	17.5	14.0	13.7	13.8	13.3	13.4
		187	17.6	13.9	14.1	14.2	13.3	13.4	17.7	14.2	13.8	14.1	13.3	13.5
		186	17.5	14.2	14.1	14.0	13.4	13.2	17.6	14.2	13.9	14.1	13.3	13.1
		185	17.3	13.9	14.1	14.0	13.5	13.4	17.5	13.7	14.1	13.9	13.5	13.4
		180	17.5	13.9	13.9	14.1	13.4	13.2	17.3	13.8	13.8	13.9	13.6	13.4
		175	17.6	13.9	13.8	14.0	13.2	13.3	17.7	14.1	13.9	13.7	13.1	13.4
		170	17.4	13.8	13.8	13.8	13.4	13.4	17.6	14.0	13.8	14.2	13.5	13.3
		160	17.3	13.8	14.2	14.0	13.2	13.2	17.6	14.2	13.8	13.8	13.4	13.3
		150	17.3	13.8	14.2	13.7	13.3	13.1	17.4	13.8	13.9	14.2	13.2	13.4
		140	17.3	14.0	14.0	14.1	13.5	13.5	17.5	14.1	13.9	13.9	13.6	13.3
		130	17.7	13.8	14.2	13.8	13.3	13.2	17.3	13.9	14.2	13.8	13.6	13.3
		120	17.7	13.8	13.8	13.8	13.5	13.2	17.4	13.8	14.1	14.2	13.3	13.5
110		17.4	13.7	14.0	14.0	13.5	13.4	17.7	14.2	13.8	14.2	13.4	13.4	
100		17.4	13.9	14.2	14.0	13.4	13.5	17.5	14.2	14.0	14.0	13.4	13.2	
90		17.5	14.0	13.9	13.8	13.6	13.3	17.7	13.8	13.7	14.0	13.3	13.3	



FCC SAR TEST REPORT

Report No. : FA2N0319

		80	17.2	13.7	13.8	14.2	13.6	13.3	17.6	13.7	13.7	14.2	13.1	13.3
		70	17.2	13.9	14.2	13.9	13.3	13.2	17.6	13.7	14.1	13.8	13.4	13.2
		60	17.7	13.8	14.1	13.7	13.3	13.3	17.7	14.0	13.9	13.8	13.3	13.3
		50	17.3	14.0	13.9	13.8	13.5	13.2	17.5	13.7	14.0	14.0	13.4	13.1
		40	17.4	14.1	14.0	13.8	13.3	13.4	17.4	14.1	14.1	13.9	13.6	13.4
		30	17.3	14.2	14.0	13.8	13.3	13.4	17.4	13.9	14.1	13.7	13.4	13.4
		20	17.4	13.9	14.2	13.8	13.5	13.1	17.3	14.0	14.0	14.1	13.5	13.3
		10	17.6	13.8	14.2	13.7	13.4	13.5	17.3	13.9	14.0	14.2	13.4	13.5
		5	17.7	14.0	14.0	13.9	13.6	13.4	17.6	13.7	14.0	14.1	13.5	13.1
		4	17.5	13.9	13.7	13.8	13.3	13.2	17.3	13.7	14.0	14.1	13.3	13.3
		3	17.5	13.9	14.0	13.9	13.3	13.5	17.4	13.8	14.1	13.7	13.5	13.5
		2	17.5	13.7	14.0	14.0	13.6	13.5	17.2	14.0	13.7	14.1	13.6	13.2
		1	17.3	13.8	13.7	13.8	13.4	13.2	17.3	14.0	13.9	14.2	13.5	13.2
	Lid Close	0	Standby	Standby	Standby	Standby	Standby	Standby	Standby	Standby	Standby	Standby	Standby	Standby

4. RF Exposure Limits

4.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

4.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

5. Specific Absorption Rate (SAR)

5.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

5.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

6. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- The DASY system in SAR Configuration is shown above
- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running windows software and the DASY software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

6.1 Test Site Location

The SAR measurement facilities used to collect data are within both Sporton Lab list below test site location are accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190 and 3786) and the FCC designation No. TW1190 and TW3786 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test.

Test Site	EMC & Wireless Communications Laboratory		Wensan Laboratory		
Test Site Location	TW1190 No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan		TW3786 No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan		
Test Site No.	SAR01-HY	SAR03-HY	SAR08-HY	SAR09-HY	SAR15-HY
	SAR04-HY	SAR05-HY	SAR11-HY	SAR12-HY	SAR16-HY
	SAR06-HY	SAR10-HY	SAR13-HY	SAR14-HY	SAR17-HY

6.2 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

6.3 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.1 Photo of DAE

6.4 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

6.5 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

7. Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

7.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

7.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

7.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

7.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

7.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

8. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	2450MHz System Validation Kit	D2450V2	806	Mar. 24, 2022	Mar. 23, 2023
SPEAG	5GHz System Validation Kit	D5GHzV2	1128	Nov. 23, 2022	Nov. 22, 2023
SPEAG	5GHz System Validation Kit	D5GHzV2	1171	Apr. 20, 2021	Apr. 18, 2023
SPEAG	Data Acquisition Electronics	DAE4	376	Oct. 19, 2022	Oct. 18, 2023
SPEAG	Data Acquisition Electronics	DAE4	699	Feb. 24, 2022	Feb. 23, 2023
SPEAG	Dosimetric E-Field Probe	EX3DV4	3728	Mar. 02, 2022	Mar. 01, 2023
SPEAG	Dosimetric E-Field Probe	EX3DV4	7625	Jan. 27, 2022	Jan. 26, 2023
RCPTWN	Thermometer	HTC-1	TM685-1	Jun. 27, 2022	Jun. 26, 2023
RCPTWN	Thermometer	HTC-1	TM560-2	Mar. 15, 2022	Mar. 14, 2023
R&S	BT Base Station	CBT	100815	Feb. 24, 2022	Feb. 23, 2023
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Anritsu	Signal Generator	MG3710A	6201502524	Oct. 12, 2022	Oct. 11, 2023
Keysight	ENA Network Analyzer	E5071C	MY46104758	Sep. 22, 2022	Sep. 21, 2023
SPEAG	Dielectric Probe Kit	DAK-3.5	1126	Sep. 28, 2022	Sep. 27, 2023
LINE SEIKI	Digital Thermometer	DTM3000-spezial	3252	Jul. 25, 2022	Jul. 24, 2023
Anritsu	Power Meter	ML2495A	1419002	Aug. 16, 2022	Aug. 15, 2023
Anritsu	Power Meter	ML2495A	1804003	Oct. 17, 2022	Oct. 16, 2023
Anritsu	Power Sensor	MA2411B	1726150	Oct. 17, 2022	Oct. 16, 2023
Anritsu	Power Sensor	MA2411B	1911334	Jun. 22, 2022	Jun. 21, 2023
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jul. 21, 2022	Jul. 20, 2023
Anritsu	Spectrum Analyzer	N9010A	MY53470118	Jan. 12, 2022	Jan. 11, 2023
Mini-Circuits	Power Amplifier	ZVE-8G+	6418	Oct. 14, 2022	Oct. 13, 2023
Mini-Circuits	Power Amplifier	ZVE-8G+	479102029	Sep. 15, 2022	Sep. 14, 2023
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005-3	N/A	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.
2. The dipole calibration interval can be extended to 3 years with justification according to KDB 865664 D01. The dipoles are also not physically damaged, or repaired during the interval. The justification data in appendix C can be found which the return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration for each dipole.

9. System Verification

9.1 Tissue Verification

The tissue dielectric parameters of tissue-equivalent media used for SAR measurements must be characterized within a temperature range of 18°C to 25°C, measured with calibrated instruments and apparatuses, such as network analyzers and temperature probes. The temperature of the tissue-equivalent medium during SAR measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized. The tissue dielectric measurement system must be calibrated before use. The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements.

The liquid tissue depth was at least 15cm in the phantom for all SAR testing

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
2450	22.6	1.803	39.246	1.80	39.20	0.17	0.12	± 5	2022/12/2
5250	22.3	4.651	36.994	4.71	35.95	-1.25	2.90	± 5	2022/12/3
5600	22.3	5.024	36.459	5.07	35.50	-0.91	2.70	± 5	2022/12/3
5750	22.3	5.171	36.282	5.22	35.35	-0.94	2.64	± 5	2022/12/3
5850	22.3	5.283	36.125	5.32	35.25	-0.70	2.48	± 5	2022/12/3

9.2 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)	Test Site
2022/12/2	2450	50	D2450V2-806	EX3DV4 - SN3728	DAE4 Sn699	2.470	52.700	49.4	-6.26	SAR14
2022/12/3	5250	50	D5GHzV2-1128-5250	EX3DV4 - SN7625	DAE4 Sn376	3.600	80.000	72	-10.00	SAR13
2022/12/3	5600	50	D5GHzV2-1128-5600	EX3DV4 - SN7625	DAE4 Sn376	3.960	82.400	79.2	-3.88	SAR13
2022/12/3	5750	50	D5GHzV2-1128-5750	EX3DV4 - SN7625	DAE4 Sn376	3.770	79.100	75.4	-4.68	SAR13
2022/12/3	5850	100	D5GHzV2-1171-5850	EX3DV4 - SN7625	DAE4 Sn376	8.310	82.300	83.1	0.97	SAR13




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo



10. RF Exposure Positions

10.1 SAR Testing for Tablet

This device can be used also in full sized tablet exposure conditions, due to its size. Per FCC KDB 616217, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom. The SAR exclusion threshold in KDB 447498 D01v06 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent tablet edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.

11. WiFi/Bluetooth Output Power (Unit: dBm)

General Note:

1. For each antenna, transmit power in SISO operation is larger than (or equal to) the power in MIMO operation, RF exposure compliance of MIMO mode can be deduced from the compliance simultaneous transmission of antennas operating in SISO mode.
2. Per KDB 248227 D01v02r02, the simultaneous SAR provisions in KDB publication 447498 should be applied to determine simultaneous transmission SAR test exclusion for WiFi MIMO. If the sum of 1g single transmission chain SAR measurements is $< 1.6\text{W/kg}$ and SAR peak to location ratio ≤ 0.04 , no additional SAR measurements for MIMO.
3. The maximum output power specified for production units are determined for all applicable 802.11 transmission modes in each standalone and aggregated frequency band. Maximum output power is measured for the highest maximum output power configuration(s) in each frequency band according to the default power measurement procedures. For "Not required", SAR Test reduction was applied from KDB 248227 guidance, Sec. 2.1, b), 1) when the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, additional output power measurements were not necessary.
4. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
5. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
6. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
7. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures. 18 The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is $\leq 0.4\text{ W/kg}$, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is $> 0.4\text{ W/kg}$, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is $\leq 0.8\text{ W/kg}$ or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is $> 0.8\text{ W/kg}$, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is $\leq 1.2\text{ W/kg}$ or all required channels are tested.
8. Per 201904 TCBC workshops, General principles of FCC KDB Publication 248227 D01 can be applied to determine the SAR Initial Test Configurations and test reduction for 802.11ax SAR testing. For the table below the 802.11ax maximum power is SU (non-OFDMA), and the SU maximum power also higher than RU (OFDMA)
9. In applying the test guidance, the IEEE 802.11 mode with the maximum output power (out of all modes) should be considered for testing
10. For modes with the same maximum output power, the guidance from section 5.3.2 a) of FCC KDB Publication 248227 D01 should be applied, with 802.11ax being considered as the highest 802.11 mode for the appropriate frequency bands
11. When SAR testing for 802.11ax is required
 - a. If the maximum output power is highest for OFDMA scenarios, choose the tone size with the maximum number of tones and the highest maximum output power
 - b. Otherwise, consider the fully allocated channel for SAR testing
 - c. When SAR testing is required on RU sizes less than the fully allocated channel, use the RU number closest to the middle of the channel, choosing the higher RU number when two RUs are equidistant to the middle of the channel

<Tablet Mode>

2.4GHz WLAN				Ant 1			Ant 2			Ant 1+2			
2.4GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	
	802.11b 1Mbps	1	2412	17.00	17.00	99.80	16.90	17.00	99.80	No Required	20.00	No Required	
		6	2437	16.80	17.00		17.00	20.00					
		11	2462	16.80	17.00		17.00	20.00					
		12	2467	15.30	15.50		15.50	18.50					
		13	2472	11.70	12.00		11.70	12.00			15.00		
	802.11g 6Mbps	1	2412	No Required	17.00	No Required	No Required	17.00	No Required		20.00		
		6	2437		17.00			17.00			20.00		
		11	2462		17.00			17.00			20.00		
		12	2467		13.00			13.00			16.00		
		13	2472		12.00			12.00			15.00		
	802.11ac-VHT20 MCS0	1	2412		16.00			16.00			19.00		
		6	2437		17.00			17.00			20.00		
		11	2462		16.00			16.00			19.00		
		12	2467		13.00			13.00			16.00		
		13	2472		12.00			12.00			15.00		
	802.11ac-VHT40 MCS0	3	2422		15.00			15.00			18.00		
		6	2437		17.00			17.00			20.00		
		9	2452		15.00			15.00			18.00		
		10	2457		12.00			12.00			15.00		
	802.11ac-VHT40 MCS0	11	2462		11.00			11.00			14.00		
		802.11ax-HE20 MCS0	1		2412			16.00			16.00		19.00
			6		2437			17.00			17.00		20.00
			11		2462			16.50			16.50		19.50
			12		2467			13.50			13.50		16.50
	13		2472		12.00			12.00			15.00		
	802.11ax-HE40 MCS0	3	2422		15.00			15.00			18.00		
		6	2437		17.00			17.00			20.00		
9		2452	15.00		15.00			18.00					
10		2457	12.50		12.50			15.50					
11		2462	11.00		11.00			14.00					

<Laptop Mode>

2.4GHz WLAN				Ant 1			Ant 2			Ant 1+2		
2.4GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11b 1Mbps	1	2412	18.60	19.00	99.80	18.90	19.00	99.80	No Required	22.00	No Required
		6	2437	18.60	19.00		18.60	19.00			22.00	
		11	2462	18.70	19.00		18.60	19.00			22.00	
		12	2467	15.30	15.50		15.50	15.50			18.50	
		13	2472	11.70	12.00		11.70	12.00			15.00	
	802.11g 6Mbps	1	2412	No Required	17.00	No Required	No Required	17.00	No Required		20.00	
		6	2437		19.00			19.00			22.00	
		11	2462		17.00			17.00			20.00	
		12	2467		13.00			13.00			16.00	
		13	2472		12.00			12.00			15.00	
	802.11ac-VHT20 MCS0	1	2412		16.00			16.00			19.00	
		6	2437		19.00			19.00			22.00	
		11	2462		16.00			16.00			19.00	
		12	2467		13.00			13.00			16.00	
		13	2472		12.00			12.00			15.00	
	802.11ac-VHT40 MCS0	3	2422		15.00			15.00			18.00	
		6	2437		18.00			18.00			21.00	
		9	2452		15.00			15.00			18.00	
		10	2457		12.00			12.00			15.00	
		11	2462		11.00			11.00			14.00	
	802.11ax-HE20 MCS0	1	2412		16.00			16.00			19.00	
		6	2437		19.00			19.00			22.00	
		11	2462		16.50			16.50			19.50	
		12	2467		13.50			13.50			16.50	
		13	2472		12.00			12.00			15.00	
	802.11ax-HE40 MCS0	3	2422		15.00			15.00			18.00	
		6	2437		18.50			18.50			21.50	
9		2452	15.00		15.00			18.00				
10		2457	12.50		12.50			15.50				
11		2462	11.00		11.00			14.00				



<Tablet Mode>

5.2GHz WLAN				Ant 1			Ant 2			Ant 1+2		
	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.2GHz WLAN	802.11a 6Mbps	36	5180	No Required	12.00	No Required	No Required	12.00	No Required	No Required	15.00	No Required
		40	5200		12.00			15.00				
		44	5220		12.00			15.00				
		48	5240		12.00			15.00				
	802.11n-HT20 MCS0	36	5180		12.00			15.00				
		40	5200		12.00			15.00				
		44	5220		12.00			15.00				
		48	5240		12.00			15.00				
	802.11n-HT40 MCS0	38	5190		12.00			15.00				
		46	5230		12.00			15.00				
	802.11ac-VHT20 MCS0	36	5180		12.00			15.00				
		40	5200		12.00			15.00				
		44	5220		12.00			15.00				
		48	5240		12.00			15.00				
	802.11ac-VHT40 MCS0	38	5190		12.00			15.00				
		46	5230		12.00			15.00				
	802.11ac-VHT80 MCS0	42	5210		12.00			15.00				
	802.11ax-HE20 MCS0	36	5180		12.00			15.00				
		40	5200		12.00			15.00				
		44	5220		12.00			15.00				
		48	5240		12.00			15.00				
	802.11ax-HE40 MCS0	38	5190		12.00			15.00				
		46	5230		12.00			15.00				
	802.11ax-HE80 MCS0	42	5210		12.00			15.00				

5.3GHz WLAN				Ant 1			Ant 2			Ant 1+2		
	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.3GHz WLAN	802.11a 6Mbps	52	5260	No Required	12.00	No Required	No Required	12.00	No Required	No Required	15.00	No Required
		56	5280		12.00			15.00				
		60	5300		12.00			15.00				
		64	5320		12.00			15.00				
	802.11n-HT20 MCS0	52	5260		12.00			15.00				
		56	5280		12.00			15.00				
		60	5300		12.00			15.00				
		64	5320		12.00			15.00				
	802.11n-HT40 MCS0	54	5270		12.00			15.00				
		62	5310		12.00			15.00				
	802.11ac-VHT20 MCS0	52	5260		12.00			15.00				
		56	5280		12.00			15.00				
		60	5300		12.00			15.00				
		64	5320		12.00			15.00				
	802.11ac-VHT40 MCS0	54	5270		12.00			15.00				
		62	5310		12.00			15.00				
	802.11ac-VHT80 MCS0	58	5290		11.60			12.00			95.60	
	802.11ax-HE20 MCS0	52	5260	No Required	12.00	No Required	No Required	12.00	No Required	15.00		
		56	5280		12.00			15.00				
		60	5300		12.00			15.00				
		64	5320		12.00			15.00				
	802.11ax-HE40 MCS0	54	5270		12.00			15.00				
		62	5310		12.00			15.00				
	802.11ax-HE80 MCS0	58	5290		12.00			15.00				

5.5GHz WLAN				Ant 1			Ant 2			Ant 1+2		
	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.5GHz WLAN	802.11a 6Mbps	100	5500	No Required	12.00	No Required	No Required	12.00	No Required	No Required	15.00	No Required
		116	5580		12.00			15.00				
		124	5620		12.00			15.00				
		132	5660		12.00			15.00				
		144	5720		12.00			15.00				
	802.11n-HT20 MCS0	100	5500		12.00			15.00				
		116	5580		12.00			15.00				
		124	5620		12.00			15.00				
		132	5660		12.00			15.00				
		144	5720		12.00			15.00				
	802.11n-HT40 MCS0	102	5510		12.00			15.00				
		110	5550		12.00			15.00				
		126	5630		12.00			15.00				
		134	5670		12.00			15.00				
		142	5710		12.00			15.00				
	802.11ac-VHT20 MCS0	100	5500		12.00			15.00				
		116	5580		12.00			15.00				
		124	5620		12.00			15.00				
		132	5660		12.00			15.00				
		144	5720		12.00			15.00				
	802.11ac-VHT40 MCS0	102	5510		12.00			15.00				
		110	5550		12.00			15.00				
		126	5630		12.00			15.00				
		134	5670		12.00			15.00				
		142	5710		12.00			15.00				
	802.11ac-VHT80 MCS0	106	5530	11.50	12.00	95.60	12.00	12.00	95.60	15.00		
		122	5610	11.70	12.00		11.90	12.00		15.00		
		138	5690	11.50	12.00		11.90	12.00		15.00		
	802.11ax-HE20 MCS0	100	5500	No Required	12.00	No Required	No Required	12.00	No Required	15.00		
		116	5580		12.00			15.00				
		124	5620		12.00			15.00				
		132	5660		12.00			15.00				
		144	5720		12.00			15.00				
	802.11ax-HE40 MCS0	102	5510		12.00			15.00				
		110	5550		12.00			15.00				
		126	5630		12.00			15.00				
		134	5670		12.00			15.00				
		142	5710		12.00			15.00				
	802.11ax-HE80 MCS0	106	5530		12.00			15.00				
		122	5610		12.00			15.00				
		138	5690		12.00			15.00				

5.8GHz WLAN				Ant 1			Ant 2			Ant 1+2		
	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.8GHz WLAN	802.11a 6Mbps	149	5745	No Required	12.00	No Required	No Required	12.00	No Required	No Required	16.00	No Required
		157	5785		12.00			12.00			16.00	
		165	5825		12.00			12.00			16.00	
	802.11n-HT20 MCS0	149	5745		12.00			12.00			16.00	
		157	5785		12.00			12.00			16.00	
		165	5825		12.00			12.00			16.00	
	802.11n-HT40 MCS0	151	5755	11.70	12.00	97.70	11.90	12.00	97.70		16.00	
		159	5795	11.80	12.00		11.90	12.00			16.00	
	802.11ac-VHT20 MCS0	149	5745	No Required	12.00	No Required	No Required	12.00	No Required		16.00	
		157	5785		12.00			12.00			16.00	
		165	5825		12.00			12.00			16.00	
	802.11ac-VHT40 MCS0	151	5755		12.00			12.00			16.00	
		159	5795		12.00			12.00		16.00		
	802.11ac-VHT80 MCS0	155	5775	11.80	12.00	95.60	12.00	12.00	95.60	16.00		
	802.11ax-HE20 MCS0	149	5745	No Required	12.00	No Required	No Required	12.00	No Required	16.00		
		157	5785		12.00			12.00		16.00		
		165	5825		12.00			12.00		16.00		
	802.11ax-HE40 MCS0	151	5755		12.00			12.00		16.00		
		159	5795		12.00			12.00		16.00		
	802.11ax-HE80 MCS0	155	5775					12.00			12.00	

5.8GHz WLAN (UNII-4)				Ant 1			Ant 2			Ant 1+2		
	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.8GHz WLAN (UNII-4)	802.11a 6Mbps	169	5845	No Required	12.00	No Required	No Required	12.00	No Required	No Required	15.00	No Required
		173	5865		12.00			12.00			15.00	
		177	5885		12.00			12.00			15.00	
	802.11n-HT20 MCS0	169	5845		12.00			12.00			15.00	
		173	5865		12.00			12.00			15.00	
		177	5885		12.00			12.00			15.00	
	802.11n-HT40 MCS0	167	5835		12.00			12.00			15.00	
		175	5875		12.00			12.00			15.00	
	802.11ac-VHT20 MCS0	169	5845		12.00			12.00			15.00	
		173	5865		12.00			12.00			15.00	
		177	5885		12.00			12.00			15.00	
	802.11ac-VHT40 MCS0	167	5835		12.00			12.00			15.00	
		175	5875		12.00			12.00			15.00	
	802.11ac-VHT80 MCS0	171	5855	11.70	12.00	95.60	11.70	12.00	95.60	15.00		
	802.11ax-HE20 MCS0	169	5845	No Required	12.00	No Required	No Required	12.00	No Required	15.00		
		173	5865		12.00			12.00		15.00		
		177	5885		12.00			12.00		15.00		
	802.11ax-HE40 MCS0	167	5835		12.00			12.00		15.00		
		175	5875		12.00			12.00		15.00		
	802.11ax-HE80 MCS0	171	5855		12.00			12.00		15.00		



<Laptop Mode>

<WLAN 5GHz>

5.2GHz WLAN				Ant 1			Ant 2			Ant 1+2		
5.2GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	36	5180	No Required	15.00	No Required	No Required	15.00	No Required	No Required	18.00	No Required
		40	5200		15.00			15.00			18.00	
		44	5220		15.00			15.00			18.00	
		48	5240		15.00			15.00			18.00	
	802.11n-HT20 MCS0	36	5180		15.00			15.00			18.00	
		40	5200		15.00			15.00			18.00	
		44	5220		15.00			15.00			18.00	
		48	5240		15.00			15.00			18.00	
	802.11n-HT40 MCS0	38	5190		15.00			15.00			18.00	
		46	5230		15.00			15.00			18.00	
	802.11ac-VHT20 MCS0	36	5180		15.00			15.00			18.00	
		40	5200		15.00			15.00			18.00	
		44	5220		15.00			15.00			18.00	
		48	5240		15.00			15.00			18.00	
	802.11ac-VHT40 MCS0	38	5190		15.00			15.00			18.00	
		46	5230		15.00			15.00			18.00	
	802.11ac-VHT80 MCS0	42	5210		15.00			15.00			18.00	
		36	5180		15.00			15.00			18.00	
	802.11ax-HE20 MCS0	40	5200		15.00			15.00			18.00	
		44	5220		15.00			15.00			18.00	
		48	5240		15.00			15.00			18.00	
		38	5190		15.00			15.00			18.00	
	802.11ax-HE40 MCS0	46	5230		15.00			15.00			18.00	
		42	5210		15.00			15.00			18.00	
	802.11ax-HE80 MCS0	42	5210		15.00			15.00			18.00	

5.3GHz WLAN				Ant 1			Ant 2			Ant 1+2		
5.3GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	52	5260	No Required	15.00	No Required	No Required	15.00	No Required	No Required	18.00	No Required
		56	5280		15.00			15.00			18.00	
		60	5300		15.00			15.00			18.00	
		64	5320		15.00			15.00			18.00	
	802.11n-HT20 MCS0	52	5260		15.00			15.00			18.00	
		56	5280		15.00			15.00			18.00	
		60	5300		15.00			15.00			18.00	
		64	5320		15.00			15.00			18.00	
	802.11n-HT40 MCS0	54	5270		15.00			15.00			18.00	
		62	5310		15.00			15.00			18.00	
	802.11ac-VHT20 MCS0	52	5260		15.00			15.00			18.00	
		56	5280		15.00			15.00			18.00	
		60	5300		15.00			15.00			18.00	
		64	5320		15.00			15.00			18.00	
	802.11ac-VHT40 MCS0	54	5270		15.00			15.00			18.00	
		62	5310		15.00			15.00			18.00	
	802.11ac-VHT80 MCS0	58	5290	14.60	15.00	95.60	15.00	15.00	95.60		18.00	
	802.11ax-HE20 MCS0	52	5260	No Required	15.00	No Required	No Required	15.00	No Required	No Required	18.00	No Required
		56	5280		15.00			15.00			18.00	
		60	5300		15.00			15.00			18.00	
		64	5320		15.00			15.00			18.00	
	802.11ax-HE40 MCS0	54	5270		15.00			15.00			18.00	
		62	5310		15.00			15.00			18.00	
	802.11ax-HE80 MCS0	58	5290		15.00			15.00			18.00	

5.5GHz WLAN				Ant 1			Ant 2			Ant 1+2		
5.5GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	100	5500	No Required	15.00	No Required	No Required	15.00	No Required	No Required	18.00	No Required
		116	5580		15.00			18.00				
		124	5620		15.00			18.00				
		132	5660		15.00			18.00				
		144	5720		15.00			18.00				
	802.11n-HT20 MCS0	100	5500		15.00			15.00			18.00	
		116	5580		15.00			15.00			18.00	
		124	5620		15.00			15.00			18.00	
		132	5660		15.00			15.00			18.00	
		144	5720		15.00			15.00			18.00	
	802.11n-HT40 MCS0	102	5510		15.00			15.00			18.00	
		110	5550		15.00			15.00			18.00	
		126	5630		15.00			15.00			18.00	
		134	5670		15.00			15.00			18.00	
		142	5710		15.00			15.00			18.00	
	802.11ac-VHT20 MCS0	100	5500		15.00			15.00			18.00	
		116	5580		15.00			15.00			18.00	
		124	5620		15.00			15.00			18.00	
		132	5660		15.00			15.00			18.00	
		144	5720		15.00			15.00			18.00	
	802.11ac-VHT40 MCS0	102	5510		15.00			15.00			18.00	
		110	5550		15.00			15.00			18.00	
		126	5630		15.00			15.00			18.00	
		134	5670		15.00			15.00			18.00	
		142	5710		15.00			15.00			18.00	
	802.11ac-VHT80 MCS0	106	5530	14.70	15.00	95.60	14.90	15.00	95.60	18.00		
		122	5610	14.90	15.00		15.00	18.00				
		138	5690	14.60	15.00		14.70	15.00		18.00		
	802.11ax-HE20 MCS0	100	5500	No Required	15.00	No Required	No Required	15.00	No Required	18.00		
116		5580	15.00		15.00			18.00				
124		5620	15.00		15.00			18.00				
132		5660	15.00		15.00			18.00				
144		5720	15.00		15.00			18.00				
802.11ax-HE40 MCS0	102	5510	15.00		15.00			18.00				
	110	5550	15.00		15.00			18.00				
	126	5630	15.00		15.00			18.00				
	134	5670	15.00		15.00			18.00				
	142	5710	15.00		15.00			18.00				
802.11ax-HE80 MCS0	106	5530	15.00		15.00			18.00				
	122	5610	15.00		15.00			18.00				
	138	5690	15.00		15.00			18.00				

5.8GHz WLAN				Ant 1			Ant 2			Ant 1+2						
5.8GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %				
	802.11a 6Mbps	149	5745	No Required	15.00	No Required	No Required	15.00	No Required	No Required	18.00	No Required				
		157	5785		15.00			18.00								
		165	5825		15.00			18.00								
	802.11n-HT20 MCS0	149	5745		15.00			15.00			18.00					
		157	5785		15.00			15.00			18.00					
		165	5825		15.00			15.00			18.00					
	802.11n-HT40 MCS0	151	5755		15.00			15.00			18.00					
		159	5795		15.00			15.00			18.00					
	802.11ac-VHT20 MCS0	149	5745		15.00			15.00			18.00					
		157	5785		15.00			15.00			18.00					
		165	5825		15.00			15.00			18.00					
	802.11ac-VHT40 MCS0	151	5755		15.00			15.00			18.00					
		159	5795		15.00			15.00			18.00					
	802.11ac-VHT80 MCS0	155	5775		14.80			15.00			95.60		14.90	15.00	95.60	18.00
	802.11ax-HE20 MCS0	149	5745		No Required			15.00			No Required		No Required	15.00	No Required	18.00
		157	5785					15.00						18.00		
		165	5825					15.00						18.00		
	802.11ax-HE40 MCS0	151	5755					15.00						15.00		18.00
		159	5795					15.00						15.00		18.00
	802.11ax-HE80 MCS0	155	5775					15.00						15.00		18.00

5.8GHz WLAN (UNII-4)				Ant 1			Ant 2			Ant 1+2						
5.8GHz WLAN (UNII-4)	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %				
	802.11a 6Mbps	169	5845	No Required	15.00	No Required	No Required	15.00	No Required	No Required	18.00	No Required				
		173	5865		15.00			18.00								
		177	5885		15.00			18.00								
	802.11n-HT20 MCS0	169	5845		15.00			15.00			18.00					
		173	5865		15.00			15.00			18.00					
		177	5885		15.00			15.00			18.00					
	802.11n-HT40 MCS0	167	5835		15.00			15.00			18.00					
		175	5875		15.00			15.00			18.00					
	802.11ac-VHT20 MCS0	169	5845		15.00			15.00			18.00					
		173	5865		15.00			15.00			18.00					
		177	5885		15.00			15.00			18.00					
	802.11ac-VHT40 MCS0	167	5835		15.00			15.00			18.00					
		175	5875		15.00			15.00			18.00					
	802.11ac-VHT80 MCS0	171	5855		14.80			15.00			95.60		15.00	15.00	95.60	18.00
	802.11ax-HE20 MCS0	169	5845		No Required			15.00			No Required		No Required	15.00	No Required	18.00
		173	5865					15.00						15.00		18.00
		177	5885					15.00						15.00		18.00
	802.11ax-HE40 MCS0	167	5835					15.00						15.00		18.00
		175	5875					15.00						15.00		18.00
	802.11ax-HE80 MCS0	171	5855					15.00						15.00		18.00


<2.4GHz Bluetooth>

Mode	Channel	Frequency (MHz)	Average power (dBm)		
			1Mbps	2Mbps	3Mbps
BR / EDR	CH 00	2402	12.3	No Required	No Required
	CH 39	2441	12.2		
	CH 78	2480	12.3		
Tune-up Limit			12.5	10	10

Mode	Channel	Frequency (MHz)	Average power (dBm)	
			1Mbps	2Mbps
LE	CH 00	2402	No Required	No Required
	CH 19	2440		
	CH 39	2480		
Tune-up Limit			12.5	12.5


General Note:

- For 2.4GHz Bluetooth SAR testing was selected 1Mbps due to its highest average power and duty cycle is 100% considered in SAR testing, and the duty cycle would be scaled to theoretical 83.3% in reported SAR calculation.



12. Antenna Location


<For Tablet>



The separation distance for antenna to edge :

Antenna	To Edge1 (mm)	To Edge2 (mm)	To Edge3 (mm)	To Edge4 (mm)
WLAN Antenna 1	52.39	290.43	127.40	< 5
WLAN/BT Antenna 2	52.39	< 5	127.40	290.43

<For Laptop>



The separation distance for antenna to edge :

Antenna	To Bottom of Laptop (mm)
WLAN Antenna 1	< 5
WLAN/BT Antenna 2	< 5

<SAR test exclusion table>
General Note:

1. The below table, when the distance is < 50 mm exclusion threshold is "Ratio", when the distance is > 50 mm exclusion threshold is "mW"
2. Maximum power is the source-based time-average power and represents the maximum RF output power among production units
3. Per KDB 447498 D01v06, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
4. Per KDB 447498 D01v06, standalone SAR test exclusion threshold is applied; If the test separation distance is < 5mm, 5mm is used to determine SAR exclusion threshold.
5. Per KDB 447498 D01v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$
 - f(GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison
6. Per KDB 447498 D01v06, at 100 MHz to 6 GHz and for *test separation distances* > 50 mm, the SAR test exclusion threshold is determined according to the following
 - a) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · (f(MHz)/150)] mW, at 100 MHz to 1500 MHz
 - b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · 10] mW at > 1500 MHz and ≤ 6 GHz

<For Tablet>

Exposure Position	Wireless Interface	BT ANT 2	2.4GHz WLAN ANT 1	2.4GHz WLAN ANT 2	5GHz WLAN ANT 1	5GHz WLAN ANT 2
	Calculated Frequency (MHz)	2480	2472	2472	5825	5825
	Maximum power (dBm)	12.5	17.0	17.0	12.0	12.0
	Maximum rated power(mW)	17.78	50.12	50.12	15.85	15.85
Bottom Face	Separation distance(mm)	5.0	5.0	5.0	5.0	5.0
	exclusion threshold	5.6	15.8	15.8	7.7	7.7
	Testing required?	Yes	Yes	Yes	Yes	Yes
Edge 1	Separation distance(mm)	52.39	52.39	52.39	52.39	52.39
	exclusion threshold	119.0	119.0	119.0	86.0	86.0
	Testing required?	No	No	No	No	No
Edge 2	Separation distance(mm)	5.00	290.43	5.00	290.43	5.00
	exclusion threshold	5.6	2500.0	15.8	2466.0	7.7
	Testing required?	Yes	No	Yes	No	Yes
Edge 3	Separation distance(mm)	127.40	127.40	127.40	127.40	127.40
	exclusion threshold	869.0	869.0	869.0	836.0	836.0
	Testing required?	No	No	No	No	No
Edge 4	Separation distance(mm)	290.43	5.00	290.43	5.00	290.43
	exclusion threshold	2500.0	15.8	2500.0	7.7	2466.0
	Testing required?	No	Yes	No	Yes	No

<For Laptop>

Exposure Position	Wireless Interface	BT ANT 2	2.4GHz WLAN ANT 1	2.4GHz WLAN ANT 2	5GHz WLAN ANT 1	5GHz WLAN ANT 2
	Calculated Frequency (MHz)	2480	2472	2472	5825	5825
	Maximum power (dBm)	12.5	19.0	19.0	15.0	15.0
	Maximum rated power(mW)	17.78	79.43	79.43	31.62	31.62
Bottom of Laptop	Separation distance(mm)	5.00	5.00	5.00	5.00	5.00
	exclusion threshold	5.6	25.0	25.0	15.3	15.3
	Testing required?	Yes	Yes	Yes	Yes	Yes

13. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. Per KDB 248227 D01v02r02, WLAN5.2GHz SAR testing is not required when the WLAN5.3GHz band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for WLAN5.2GHz band.
3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. For WLAN SAR testing was performed on single antenna RF power in SISO mode is larger or equal to the single antenna RF power in MIMO mode, and for RF exposure assessment of MIMO mode simultaneous transmission exclusion analysis was performed with SAR test results of each antenna in SISO mode.
6. Per KDB 248227 D01v02r02, the simultaneous SAR provisions in KDB publication 447498 should be applied to determine simultaneous transmission SAR test exclusion for WiFi MIMO. If the sum of 1g single transmission chain SAR measurements is < 1.6 W/kg and SAR peak to location ratio ≤ 0.04 , no additional SAR measurements for MIMO.
7. For determination of the scaling factor for report SAR of MIMO mode, if the hot spots are separated the scaling factors are individually determined from each transmit chain. If the hot spots are not spatially separated, the scaling factor is determined from the worst number of each transmit chain
8. During SAR testing the WLAN transmission was verified using a spectrum analyzer.

**13.1 Body SAR****<WLAN SAR>**

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna Vendor	Configuration (Tablet / Laptop)	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
01	WLAN2.4GHz	802.11b 1Mbps	Bottom of Laptop	0mm	WNC	Laptop	Ant 1	11	2462	18.70	19.00	1.072	99.8	1.002	0.17	0.350	0.376
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	WNC	Tablet	Ant 1	1	2412	17.00	17.00	1.000	99.8	1.002	-0.13	0.822	0.824
	WLAN2.4GHz	802.11b 1Mbps	Edge 4	0mm	WNC	Tablet	Ant 1	1	2412	17.00	17.00	1.000	99.8	1.002	0.04	0.622	0.623
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	WNC	Tablet	Ant 1	6	2437	16.80	17.00	1.047	99.8	1.002	0.15	0.629	0.660
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	WNC	Tablet	Ant 1	11	2462	16.80	17.00	1.047	99.8	1.002	-0.14	0.674	0.707
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	Speed	Tablet	Ant 1	1	2412	17.00	17.00	1.000	99.8	1.002	-0.12	0.521	0.522
	WLAN2.4GHz	802.11b 1Mbps	Bottom of Laptop	0mm	WNC	Laptop	Ant 2	1	2412	18.90	19.00	1.023	99.8	1.002	0.15	0.132	0.135
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	WNC	Tablet	Ant 2	6	2437	17.00	17.00	1.000	99.8	1.002	-0.06	0.495	0.496
	WLAN2.4GHz	802.11b 1Mbps	Edge 2	0mm	WNC	Tablet	Ant 2	6	2437	17.00	17.00	1.000	99.8	1.002	-0.04	0.311	0.312
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	WNC	Tablet	Ant 2	1	2412	16.90	17.00	1.023	99.8	1.002	0.18	0.457	0.469
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	WNC	Tablet	Ant 2	11	2462	17.00	17.00	1.000	99.8	1.002	-0.04	0.489	0.490
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	Speed	Tablet	Ant 2	6	2437	17.00	17.00	1.000	99.8	1.002	-0.15	0.487	0.488
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom of Laptop	0mm	WNC	Laptop	Ant 1	58	5290	14.60	15.00	1.096	95.6	1.046	0.16	0.125	0.143
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	WNC	Tablet	Ant 1	58	5290	11.60	12.00	1.096	95.6	1.046	0.03	0.617	0.708
	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 4	0mm	WNC	Tablet	Ant 1	58	5290	11.60	12.00	1.096	95.6	1.046	-0.15	0.116	0.133
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Speed	Tablet	Ant 1	58	5290	11.60	12.00	1.096	95.6	1.046	-0.16	0.561	0.643
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom of Laptop	0mm	WNC	Laptop	Ant 2	58	5290	15.00	15.00	1.000	95.6	1.046	-0.05	0.062	0.065
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	WNC	Tablet	Ant 2	58	5290	11.80	12.00	1.047	95.6	1.046	-0.09	0.352	0.386
	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 2	0mm	WNC	Tablet	Ant 2	58	5290	11.80	12.00	1.047	95.6	1.046	0.15	0.073	0.080
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Speed	Tablet	Ant 2	58	5290	11.80	12.00	1.047	95.6	1.046	0	0.345	0.378
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom of Laptop	0mm	WNC	Laptop	Ant 1	122	5610	14.90	15.00	1.023	95.6	1.046	-0.06	0.244	0.261
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	WNC	Tablet	Ant 1	122	5610	11.70	12.00	1.072	95.6	1.046	0.04	0.617	0.692
	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 4	0mm	WNC	Tablet	Ant 1	122	5610	11.70	12.00	1.072	95.6	1.046	0.02	0.253	0.284
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	WNC	Tablet	Ant 1	106	5530	11.50	12.00	1.122	95.6	1.046	0.07	0.624	0.732
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	WNC	Tablet	Ant 1	138	5690	11.50	12.00	1.122	95.6	1.046	-0.08	0.745	0.874
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Speed	Tablet	Ant 1	138	5690	11.50	12.00	1.122	95.6	1.046	0.18	0.582	0.683
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom of Laptop	0mm	WNC	Laptop	Ant 2	122	5610	15.00	15.00	1.000	95.6	1.046	0.09	0.077	0.081
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	WNC	Tablet	Ant 2	106	5530	12.00	12.00	1.000	95.6	1.046	-0.16	0.476	0.498
	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 2	0mm	WNC	Tablet	Ant 2	106	5530	12.00	12.00	1.000	95.6	1.046	-0.04	0.158	0.165
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	WNC	Tablet	Ant 2	122	5610	11.90	12.00	1.023	95.6	1.046	0.04	0.370	0.396
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	WNC	Tablet	Ant 2	138	5690	11.90	12.00	1.023	95.6	1.046	-0.06	0.601	0.643
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Speed	Tablet	Ant 2	138	5690	11.90	12.00	1.023	95.6	1.046	-0.05	0.435	0.466
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom of Laptop	0mm	WNC	Laptop	Ant 1	155	5775	14.80	15.00	1.047	95.6	1.046	0.04	0.304	0.333
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	WNC	Tablet	Ant 1	155	5775	11.80	12.00	1.047	95.6	1.046	0.08	0.868	0.951
	WLAN5GHz	802.11n-HT40 MCS0	Bottom Face	0mm	WNC	Tablet	Ant 1	151	5755	11.70	12.00	1.072	97.7	1.024	0.03	0.667	0.732
	WLAN5GHz	802.11n-HT40 MCS0	Bottom Face	0mm	WNC	Tablet	Ant 1	159	5795	11.80	12.00	1.047	97.7	1.024	-0.1	0.590	0.633
	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 4	0mm	WNC	Tablet	Ant 1	155	5775	11.80	12.00	1.047	95.6	1.046	-0.05	0.372	0.407
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Speed	Tablet	Ant 1	155	5775	11.80	12.00	1.047	95.6	1.046	0.02	0.431	0.472
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom of Laptop	0mm	WNC	Laptop	Ant 2	155	5775	14.90	15.00	1.023	95.6	1.046	-0.01	0.099	0.106
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	WNC	Tablet	Ant 2	155	5775	12.00	12.00	1.000	95.6	1.046	-0.07	0.602	0.630
	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 2	0mm	WNC	Tablet	Ant 2	155	5775	12.00	12.00	1.000	95.6	1.046	0.11	0.109	0.114
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Speed	Tablet	Ant 2	155	5775	12.00	12.00	1.000	95.6	1.046	-0.04	0.636	0.665
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom of Laptop	0mm	WNC	Laptop	Ant 1	171	5855	14.80	15.00	1.047	95.6	1.046	0.01	0.179	0.196
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	WNC	Tablet	Ant 1	171	5855	11.70	12.00	1.072	95.6	1.046	-0.03	0.582	0.652
	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 4	0mm	WNC	Tablet	Ant 1	171	5855	11.70	12.00	1.072	95.6	1.046	-0.13	0.331	0.371
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Speed	Tablet	Ant 1	171	5855	11.70	12.00	1.072	95.6	1.046	-0.04	0.368	0.412
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom of Laptop	0mm	WNC	Laptop	Ant 2	171	5855	15.00	15.00	1.000	95.6	1.046	0.03	0.085	0.089
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	WNC	Tablet	Ant 2	171	5855	11.70	12.00	1.072	95.6	1.046	0.05	0.479	0.537
	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 2	0mm	WNC	Tablet	Ant 2	171	5855	11.70	12.00	1.072	95.6	1.046	-0.14	0.099	0.111
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Speed	Tablet	Ant 2	171	5855	11.70	12.00	1.072	95.6	1.046	-0.18	0.517	0.579

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna Vendor	Configuration (Tablet / Laptop)	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
06	Bluetooth	1Mbps	Bottom of Laptop	0mm	WNC	Laptop	Ant 2	0	2402	12.30	12.50	1.047	100	1.000	-0.16	0.044	0.046
	Bluetooth	1Mbps	Bottom Face	0mm	WNC	Tablet	Ant 2	0	2402	12.30	12.50	1.047	100	1.000	-0.04	0.168	0.176
	Bluetooth	1Mbps	Edge 2	0mm	WNC	Tablet	Ant 2	0	2402	12.30	12.50	1.047	100	1.000	-0.14	0.104	0.109
	Bluetooth	1Mbps	Bottom Face	0mm	WNC	Tablet	Ant 2	39	2441	12.20	12.50	1.072	100	1.000	-0.08	0.154	0.165
	Bluetooth	1Mbps	Bottom Face	0mm	WNC	Tablet	Ant 2	78	2480	12.30	12.50	1.047	100	1.000	-0.03	0.165	0.173
	Bluetooth	1Mbps	Bottom Face	0mm	Speed	Tablet	Ant 2	0	2402	12.30	12.50	1.047	100	1.000	-0.09	0.162	0.170

13.2 Repeated SAR Measurement

No.	Band	Mode	Test Position	Gap (mm)	Antenna Vendor	Configuration (Tablet / Laptop)	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	WNC	Tablet	Ant 1	1	2412	17.00	17.00	1.000	99.8	1.002	0.01	0.774	-	0.776
2nd	WLAN2.4GHz	802.11b 1Mbps	Edge 4	0mm	WNC	Tablet	Ant 1	1	2412	17.00	17.00	1.000	99.8	1.002	0.04	0.622	1.24	0.623
1st	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	WNC	Tablet	Ant 1	155	5775	11.80	12.00	1.047	95.6	1.046	0.08	0.868	-	0.951
2nd	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	WNC	Tablet	Ant 1	155	5775	11.80	12.00	1.047	95.6	1.046	-0.05	0.824	1.05	0.903

General Note:

- Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8\text{W/kg}$.
- Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR $< 1.45\text{W/kg}$, only one repeated measurement is required.
- The ratio is the difference in percentage between original and repeated *measured SAR*.
- All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

14. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Body
1.	WLAN2.4GHz Ant 1 + WLAN2.4GHz Ant 2	Yes
2.	WLAN5GHz Ant 1 + WLAN5GHz Ant 2 + Bluetooth Ant 2	Yes

General Note:

- The worst case WLAN reported SAR for each configuration was used for SAR summation. Therefore, the following summations represent the absolute worst cases for simultaneous transmission with WLAN.
- WLAN RF exposure assessment of MIMO mode simultaneous transmission exclusion analysis was performed with SAR test results of each antenna in SISO mode. Therefore SPLSR calculation was choose worst case with SAR test results of each antenna in SISO mode perform evaluation.
- The Scaled SAR summation is calculated based on the same configuration and test position.
- Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - Scalar SAR summation $< 1.6\text{W/kg}$.
 - $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - Simultaneously transmission SAR measurement, and the reported multi-band SAR $< 1.6\text{W/kg}$.
 - The SPLSR calculated results please refer to section 14.2.

14.1 Body Exposure Conditions

Exposure Position	1	2	3	4	5	1+2 Summed 1g SAR (W/kg)	3+4+5 Summed 1g SAR (W/kg)	SPLSR	Case No
	WLAN2.4GHz Ant 1 1g SAR (W/kg)	WLAN2.4GHz Ant 2 1g SAR (W/kg)	WLAN5GHz Ant 1 1g SAR (W/kg)	WLAN5GHz Ant 2 1g SAR (W/kg)	Bluetooth Ant 2 1g SAR (W/kg)				
Bottom of Laptop at 0mm	0.376	0.135	0.333	0.106	0.046	0.511	0.485		
Bottom Face at 0mm	0.824	0.496	0.951	0.665	0.176	1.320	1.792	0.01	Case 1
Edge 2 at 0mm		0.312		0.165	0.109	0.312	0.274		
Edge 4 at 0mm	0.623		0.407			0.623	0.407		

14.2 SPLSR Evaluation and Analysis

General Note:

- Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneously transmitting antenna. When the sum of 1-g or 10-g SAR of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit, SAR test exclusion applies to that simultaneous transmission configuration. Therefore, the adjacent transmit antennas will be summed first, and then the SPLSR calculation will be evaluated with the farther transmitted antennas.
- $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\text{min. separation distance, mm})$. If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
- The minimum distance between transmit ant 1 and 2 is 274.9mm and using for SPLRS analysis.

Case 1	Band	Position	SAR (W/kg)	Gap (mm)	Minimum distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
	WLAN5GHz Ant 1	Bottom Face	0.951	0mm	274.9	1.79	0.01	Not required
	WLAN5GHz Ant 2+ BT Ant 2		0.841	0mm				

Test Engineer : Sing Lim

15. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg. Therefore, the measurement uncertainty table is not required in this report.

Declaration of Conformity:

The test results with all measurement uncertainty excluded is presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

16. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 616217 D04 v01r02, "SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers", Oct 2015
- [8] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [9] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.