



# Certification Report on

## Specific Absorption Rate (SAR)Body Europe

### Experimental Analysis

**Intel Corporation**

**X300**

**Test Date: December 2003**



ITLB-Dell PROTO3 (ST)-H 802.11b/g Mini-PCI Card, Type 3A (FCC)-4089

51 Spectrum Way Nepean ON K2R 1E6  
Tel: (613) 820-2730 Fax: (613) 820-4161  
email: [info@aprel.com](mailto:info@aprel.com)

**Applicant Name:** Intel Corporation

**Applicant Address:** Intel Corporation  
Evening Creek Drive,  
San Diego CA, 92128

**FCC ID:** E2K24GBRL



**Project Number:** Dell PROTO3 (ST)-H 802.11b/g Mini-PCI Card, Type 3A (FCC)-4089

**Test/Analysis Date:** 29<sup>th</sup> December 2003

<b>DUT Type</b>	Laptop computer with 802.11b/g WLAN
<b>Model Number</b>	WM3A2200BG
<b>Project Name</b>	Dell Blade-II
<b>Received Status</b>	Pre-Production Model
<b>DUT Serial Number</b>	KR-03Y639-36521-34S-Z224
<b>Experimental/Compliance</b>	Compliance
<b>Tx Frequency</b>	2412MHz to 2462MHz
<b>Max Tx Power</b>	(802.11b 17.4dB) (802.11g 16.5db)
<b>Conservative Averaged SAR (RF Exposure)</b>	802.11b 1.46 W/kg 802.11g 0.93 W/kg

We the undersigned of APREL Laboratories, located at 51 Spectrum Way, Ottawa, Ontario, Canada, K2R-1E6, on the date indicated attest that the Device Under Test as detailed within this test report has been tested and found to be compliant with the Uncontrolled Environment RF exposure rules and regulations as defined by the methodologies, procedures, and standards as described in this document.

APREL Laboratories are an ISO 17025 accredited facility.

Stuart Nicol, Date  
Director Product Development

Jay Sarkar, Date  
Director Standards & Certification

Dr Jacek J. Wojcik, Date  
P. Engineer



Project number: ITLB-Dell-4089  
FCC ID: ID:E2K24GBRL

51 Spectrum Way  
Nepean, Ontario  
Canada K2R 1E6  
© 2004 APREL Laboratories

AL-065

Page 1 of 54



Tel: (613) 820-2730  
Fax: (613) 820-4161  
Info@aprel.com  
www.aprel.com

## Table of Contents

<b>1.0</b>	<b>Introduction</b>	<b>3</b>
<b>2.0</b>	<b>Applicable Documents</b>	<b>3</b>
<b>3.0</b>	<b>ALSAS-10U System Description</b>	<b>4</b>
<b>3.1</b>	<b>Applications</b>	<b>5</b>
<b>3.2</b>	<b>Visualisation and reporting</b>	<b>5</b>
<b>3.3</b>	<b>Field scans</b>	<b>5</b>
<b>3.3.1</b>	<b>Area Scans</b>	<b>5</b>
<b>3.3.2</b>	<b>Zoom Scan (Cube Scan Averaging)</b>	<b>6</b>
<b>3.4</b>	<b>Operator settings</b>	<b>6</b>
<b>3.5</b>	<b>ALSAS-10U Interpolation and Extrapolation Uncertainty</b>	<b>6</b>
<b>4.0</b>	<b>ALSAS-10U Hardware</b>	<b>7</b>
<b>4.1</b>	<b>Isotropic E-Field Probe</b>	<b>7</b>
<b>4.2</b>	<b>Isotropic E-Field Probe Specification</b>	<b>8</b>
<b>4.3</b>	<b>Boundary Detection Unit and Probe Mounting Device</b>	<b>8</b>
<b>4.4</b>	<b>Daq-Paq (Analog to Digital Electronics)</b>	<b>8</b>
<b>4.5</b>	<b>Axis Articulated Robot</b>	<b>9</b>
<b>4.6</b>	<b>ALSAS Universal Workstation</b>	<b>9</b>
<b>4.7</b>	<b>Universal Device Positioner</b>	<b>10</b>
<b>4.8</b>	<b>Phantom Types</b>	<b>11</b>
<b>4.8.1</b>	<b>APREL SAM Phantoms</b>	<b>11</b>
<b>4.8.2</b>	<b>APREL Laboratories Universal Phantom</b>	<b>12</b>
<b>4.9</b>	<b>Validation Dipoles</b>	<b>13</b>
<b>5.0</b>	<b>Tissue Simulation Fluid</b>	<b>14</b>
<b>5.1</b>	<b>Tissue Calibration Procedure Using a Coaxial Probe</b>	<b>15</b>
<b>5.2</b>	<b>Tissue Calibration Results</b>	<b>15</b>
<b>6.0</b>	<b>System Validation</b>	<b>16</b>
<b>6.1</b>	<b>Experimental Results Summary</b>	<b>17</b>
<b>6.2</b>	<b>SAR Measurement Procedure</b>	<b>17</b>
<b>6.3</b>	<b>SAR Exposure Limits</b>	<b>17</b>
<b>6.4</b>	<b>Equipment List</b>	<b>18</b>
<b>6.5</b>	<b>SAR Measurement Results</b>	<b>19</b>
<b>7.0</b>	<b>Measurement Uncertainty</b>	<b>22</b>
<b>Appendix A</b>	<b>SAR Plots</b>	<b>23</b>
<b>Appendix B</b>	<b>Probe Calibration Certificate</b>	<b>34</b>
<b>Appendix C</b>	<b>Dipole Calibration Certificate</b>	<b>45</b>

## 1.0 Introduction

Tests were conducted at APREL Laboratories within the ISO 17025 accredited SAR facility to establish the conservative exposure value associated with the Device Under Test as detailed within this test report. Assessments were made in line with the guidelines contained in the reference documents. The method used for assessment was the ALSAS-10U (APREL Laboratories SAR Assessment System-10 Universal). All practices along with standards and scientific methodologies which have been utilized during the assessment of the Device Under Test (DUT) are detailed within this test report.

APREL Laboratories employees currently hold senior and executive positions in multiple international standards organizations, including IEC, IEEE, among others, and work closely with several national regulators, including the FCC. Through the IEC, we have a liaison with CENELEC, and informal links to other national and international standards organizations.

## 2.0 Applicable Documents

EN-50371 TITLE "Generic Standard to Demonstrate the Compliance of low power electronic and electrical apparatus with the basic restrictions related to human exposure to electromagnetic fields (10MHz-300GHz) general public"

2) DIRECTIVE 1999/5/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 1999 on radio equipment and telecommunications terminal equipment and the mutual recognition of their conformity

ANSI/IEEE C95.1-1999, IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

FCC 96-326, Guidelines for Evaluating the Environmental Effects of Radio-Frequency Radiation.

ANSI/IEEE C95.3-1992, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields – RF and Microwave.

OET Bulletin 65 (Edition 97-01) Supplement C (Edition 01-01), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radio Frequency Electromagnetic Fields".

IEEE 1528 "Recommended Practice for Determining the Peak Spatial Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communication Devices: Experimental Techniques."

### 3.0 ALSAS-10U System Description

**APREL Laboratories ALSAS-10-U (APREL Laboratories SAR Assessment System)** is fully optimized for the dosimetric evaluation of a broad range of wireless transceivers and antennas. It is an easy-to-use development and compliance tool, which provides excellent application flexibility. Developed in line with the latest methodologies it is fully compliant with the technical and scientific requirements of IEEE 1528, IEC 62209, CENELEC, ARIB, ACA, and the Federal Communications Commission. The system comprises of a six axes articulated robot which utilizes a dedicated controller.

ALSAS-10U has been developed with a strong engineering focus, and with custom modular software/hardware for the broadest range of applications, including dosimetry research and measurements in various Phantoms – SAM Phantom, UniPhantom™ Universal Phantom, Universal Flat Phantom and others.

Free space E-Field measurements of mobile devices and base station antennas can also be executed using ALSAS. With the current ALSAS configuration, several phantoms and setups can be arranged around the system – and since the phantoms are designed to be light and easy to move for interchanging between test frequencies.

ALSAS-10U has been developed using the latest methodologies and FDTD modeling to provide a platform which is repeatable with minimum uncertainty.

The ongoing commitment from APREL Laboratories to the field of Dosimetric research and development will ensure that the ALSAS-10-U measurement system can easily be upgraded to accommodate changes to wireless technologies, and scientific methodologies.



### 3.1 Applications

Predefined measurement procedures compliant with the guidelines of CENELEC, IEEE, IEC, FCC, etc are utilized during the assessment for the device. Automatic detection for all SAR maxima are embedded within the core architecture for the system, ensuring that peak locations used for centering the zoom scan are within a 1mm resolution and a 0.05mm repeatable position. A little less than 10 min per device position measurement completion time, (depending of DUT size) ensures minimum power drift during the assessment. No user interaction is required during the measurement processes: area scan, evaluation of cube maximal search, fine cube measurements and device power drift measurement. System operation range currently available up-to 6 GHz in simulated tissue.

ALSAS-10U can be used for all analog and digital devices, including wideband, spread spectrum and pulsed systems, etc.: handsets, handhelds, wireless data, electronic article surveillance, accessories, wireless access points, WLAN, cordless, radio, etc.

### 3.2 Visualisation and reporting

2/3D isoline distribution, scatter graphics, polar graphics, and vector reproduction. Device representation and phantom visualization in 2/3D graphics with measurement data overlaid (in color plot format). Freely configurable output graphic formats with automatic title, data and legend generation which includes all relevant information relating to the measurement process. Uncertainty analysis and budget calculated and reported drawing on active device drift assessment, and tissue simulation values.

### 3.3 Field scans

ALSAS-10U can provide multiple scan types including Measurements along lines (X, Y, Z), multiple planes, curved surfaces, volumes in free space or restricted volumes (phantoms). Cube measurements with surface extrapolation and spatial SAR evaluation for 1g and/or 10g. Time measurements (source power drift). Probe rotation measurements (isotropy) and many others in line with the requirements of any given standard or procedure.

#### 3.3.1 Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 10mm<sup>2</sup> step integral, with 1mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.

### 3.3.2 Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the ALSAS-10U software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1 000 kg/m<sup>3</sup> is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1 g cube is 10mm, with the side length of the 10 g cube 21.5mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the centre of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 5x5x8 (8mmx8mmx5mm) providing a volume of 32mm in the X & Y axis, and 35mm in the Z axis.

### 3.4 Operator settings

Multiple access levels (password protected) for parametric modifications/test scenarios in line with selected standards, including the FCC. Any number of predefined settings (probes, phantoms, liquids, devices, measurement procedures, etc.) can be stored for future use and repeatable assessments.

### 3.5 ALSAS-10U Interpolation and Extrapolation Uncertainty

The overall uncertainty for the methodology and algorithms used during the SAR calculation was evaluated using the data from IEEE 1528 based on the example f3 algorithm:

$$f_3(x, y, z) = A \frac{a^2}{\frac{a^2}{4} + x'^2 + y'^2} \cdot \left( e^{-\frac{2z}{a}} + \frac{a^2}{2(a + 2z)^2} \right)$$

## 4.0 ALSAS-10U Hardware


The ALSAS-10U comprises of hardware designed exclusively by APREL Laboratories based on methodologies presented in IEEE 1528, IEC 62209, CENELEC and FCC supplement C OET bulletin 65.

### 4.1 Isotropic E-Field Probe

The isotropic E-Field probe used by APREL Laboratories, has been fully calibrated and assessed for isotropicity, and boundary effect within a controlled environment. Depending on the frequency for which the probe is calibrated the method utilized for calibration will change. APREL Laboratories utilize a number of methods for calibrating probes, and these are outlined in the table below.

Calibration Frequency (MHz)	Air Calibration	Tissue Calibration
300	TEM Cell	Temperature
450	TEM Cell	Temperature
835	TEM Cell	Temperature
900	TEM Cell	Temperature
1800	TEM Cell	Temperature
1900	TEM Cell	Temperature
2450	Waveguide	Temperature
5200	Waveguide	Waveguide
5800	Waveguide	Waveguide

The APREL Laboratories E-Field probe utilizes a triangular sensor arrangement as detailed in the diagram below.



SAR is assessed with a calibrated probe which moves at a default height of 5mm from the centre of the diode, which is mounted to the sensor, to the phantom surface (in the Z Axis). The 5mm offset height has been selected so as to minimize any resultant boundary effect due to the probe being in close proximity to the phantom surface.

The following algorithm is an example of the function used by the system for linearization of the output from the probe when measuring complex modulation schemes.

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

## 4.2 Isotropic E-Field Probe Specification

<b>Calibration in Air</b>	Frequency Dependent Below 2GHz Calibration in air performed in a TEM Cell Above 2GHz Calibration in air performed in waveguide
<b>Sensitivity</b>	0.70 $\mu$ V/(V/m) <sup>2</sup> to 0.85 $\mu$ V/(V/m) <sup>2</sup>
<b>Dynamic Range</b>	0.01 W/kg to 100 W/kg
<b>Isotropic Response</b>	Better than 0.2dB
<b>Diode Compression Point (DCP)</b>	Calibrated for Specific Frequency
<b>Probe Tip Radius</b>	<5mm
<b>Sensor Offset</b>	1.56 (+/-0.02mm)
<b>Probe Length</b>	290mm
<b>Video Bandwidth</b>	@ 500 Hz: 1 dB @ 1.02 KHz: 3 dB
<b>Boundary Effect</b>	Less than 2% for distances greater than 2.4mm
<b>Spatial Resolution</b>	Diameter less than 5mm Compliant with Standards

## 4.3 Boundary Detection Unit and Probe Mounting Device

ALSAS-10U incorporates a boundary detection unit with a sensitivity of 0.05mm for detecting all types of surfaces. The robust design allows for detection during probe tilt (probe normalize) exercises, and utilizes a second stage emergency stop. The signal electronics are fed directly into the robot controller for high accuracy surface detection in lateral and axial detection modes (X, Y, & Z).

The probe is mounted directly onto the Boundary Detection unit for accurate tooling and displacement calculations controlled by the robot kinematics. The probe is connect to an isolated probe interconnect where the output stage of the probe is fed directly into the amplifier stage of the Daq-Paq.

## 4.4 Daq-Paq (Analog to Digital Electronics)

ALSAS-10U incorporates a fully calibrated Daq-Paq (analog to digital conversion system) which has a 4 channel input stage, sent via a 2 stage auto-set amplifier module. The input signal is amplified accordingly so as to offer a dynamic range from 5 $\mu$ V to 800mV. Integration of the fields measured is carried out at board level utilizing a Co-Processor which then sends the measured fields down into the main computational module in digitized form via an RS232 communications port. Probe linearization and duty cycle compensation is carried out within the main Daq-Paq module.

<b>ADC</b>	12 Bit
<b>Amplifier Range</b>	20mV to 200mV and 150mV to 800mV
<b>Field Integration</b>	Local Co-Processor utilizing proprietary integration algorithms
<b>Number of Input Channels</b>	4 in total 3 dedicated and 1 spare
<b>Communication</b>	Packet data via RS232

#### 4.5 Axis Articulated Robot



ALSAS-10U utilizes a six axis articulated robot, which is controlled using a Pentium based real-time movement controller. The movement kinematics engine utilizes proprietary (Thermo CRS) interpolation and extrapolation algorithms, which allow full freedom of movement for each of the six joints within the working envelope. Utilization of joint 6 allows for full probe rotation with a tolerance better than 0.05mm around the central axis.

<b>Robot/Controller Manufacturer</b>	Thermo CRS
<b>Number of Axis</b>	Six independently controlled axis
<b>Positioning Repeatability</b>	0.05mm
<b>Controller Type</b>	Single phase Pentium based C500C
<b>Robot Reach</b>	710mm
<b>Communication</b>	RS232 and LAN compatible

#### 4.6 ALSAS Universal Workstation

ALSAS Universal workstation was developed with a strong engineering focus taking into consideration flexibility and engineering needs, and the necessity to have integrated system which will allow for repeatability and fast adaptability. ALSAS workstation technology is stable and robust in structure, but at the same time flexible so that users can do calibration, testing and measurements using different types of phantoms with one set up, which significantly speeds up the measurement process.

The workstation incorporates a modular structure which can be easily adapted to specific engineering requirements and needs. Phantoms which are self contained modular units are easily located, removable and swappable. Three fully configurable shelves allow for setting up of a test device in a way which can either utilize the APREL Laboratories device positioner, or custom designed units. When using the modular shelf for positioning of a device, additional loading characteristics have been avoided.

The workstation has been constructed entirely out of composite wood and Canadian maple, with all metallic fasteners kept at a compliant distance from the Device under test.

#### 4.7 Universal Device Positioner



The APREL Laboratories universal device positioner has been developed so as to allow complete freedom of movement of the DUT. Developed to hold a DUT in a free-space scenario any additional loading attributable to the material used in the construction of the positioner has been eliminated. Repeatability has been enhanced through the linear scales which form the design used to indicate positioning for any given test scenario in all major axes. A 15° tilt indicator has been included for the aid of cheek to tilt movements for head SAR analysis. Overall uncertainty for measurements have been reduced due to the design of the Universal device positioner, which allows positioning of a device in as near to a free-space scenario as possible, and by providing the means for complete repeatability.




<b>Length</b>	201mm
<b>Width</b>	140mm
<b>Height</b>	222mm
<b>Weight</b>	1.95kg
<b>Number of Axis</b>	6 axis freedom of movement
<b>Translation Along MB Line</b>	+/- 76.2mm
<b>Translation Along NF Line</b>	+/- 38.1mm
<b>Translation Along Z Axis</b>	+/- 25.4mm (expandable to 500mm)
<b>Rotation Around MB Line (yaw)</b>	+/- 10°
<b>Rotation Around NF Line (pitch)</b>	+/- 30°
<b>Rotation Around Z Axis (roll)</b>	360° full circle
<b>Minimum Grip Range</b>	0mm
<b>Maximum Grip</b>	152mm
<b>Maximum Distance from Device to Positioner Material</b>	40mm
<b>Tilt Movement</b>	Full movement with predefined 15° guide

## 4.8 Phantom Types

The ALSAS-10U has been designed so as to allow the integration of multiple phantom types. This includes but is not limited to the APREL Laboratories SAM Phantoms fully compliant with IEEE 1528, Universal Phantom, and Universal Flat.

### 4.8.1 APREL SAM Phantoms

The APREL Laboratories SAM phantoms have been designed so as to aid repeatability and positioning for any DUT. Developed using the IEEE SAM CAD file they are fully compliant with the requirements for both IEEE 1528 and FCC Supplement C. Both the left and right SAM phantoms are interchangeable, transparent and include the IEEE 1528 grid with visible NF and MB lines.



<b>Compliant Standards</b>	IEEE-1528, IEC 62209, CENELEC, and others
<b>Manufacturing Process</b>	Injection molded
<b>Material</b>	Composite urethane
<b>Manufacturing Tolerance</b>	+/- 0.2mm
<b>Frame Material</b>	Corian
<b>Tissue Simulation Volume</b>	7 ltr with 15cm tissue
<b>Thickness</b>	2mm nominally 6mm at NF/MB intersection
<b>Loss Tangent</b>	<0.05
<b>Relative Permittivity</b>	<5
<b>Resistant to Solvents</b>	Resistant to all solvents detailed in IEEE 1528
<b>Load Deflection</b>	<1mm with sugar water compositions

#### 4.8.2 APREL Laboratories Universal Phantom



The APREL Laboratories Universal Phantom has been developed as an engineering tool for both compliance and development. It is also used on the ALSAS-10U as a system validation phantom. The unique design allows repeatable measurements for all devices, including handsets, PDA units, laptop computers, and validation dipoles. The APREL Laboratories Universal Phantom has been fully validated both experimentally from 800MHz to 6GHz and numerically using XFDTD numerical software. The shell thickness is 2mm overall, with a 4mm spacer located at the NF/MB intersection providing an overall


thickness of 6mm in line with the requirements of IEEE-1528. The design allows for fast and accurate measurements, of handsets, by allowing the conservative SAR to be evaluated at on frequency for both left and right head experiments in one measurement. The phantom is surrounded by a Corian frame, which adds additional support and load bearing characteristics.

<b>Compliant Standards</b>	IEEE-1528, IEC 62209, CENELEC, and others
<b>Frequency Range</b>	800MHz to 6GHz
<b>Material</b>	Vivac
<b>Manufacturing Tolerance</b>	+/- 0.2mm
<b>Frame Material</b>	Corian
<b>Tissue Simulation Volume</b>	8 ltr with 15cm tissue
<b>Thickness</b>	2mm nominally 6mm at NF/MB intersection
<b>Loss Tangent</b>	<0.05
<b>Relative Permittivity</b>	<5
<b>Resistant to Solvents</b>	Resistant to all solvents detailed in IEEE 1528
<b>Load Deflection</b>	<1% Length with sugar water compositions
<b>Dimensions</b>	Length 220mm x breadth 170mm

#### 4.9 Validation Dipoles

APREL Laboratories utilize dipoles based on the IEEE-1528 standard, and have ensured that they comply with mechanical and electrical specifications in line with the requirements of both IEEE and FCC Supplement C. the table below provides details for the mechanical and electrical specifications for the dipoles used by APREL Laboratories.

Body validation target numbers have been derived using XFDTD numerical software, and validated experimentally.



APREL Laboratories have developed high frequency dipoles based on current scientific research carried both experimentally and numerically here at the APREL Laboratories site. Mechanical and electrical parameters for the dipoles have been established using experimental and numerical techniques, and target SAR values have been established following IEC methodologies. The results of the experimental and numerical research have been published and released for peer review.

Frequency (MHz)	<i>L</i> (mm)	<i>h</i> (mm)	<i>d</i> (mm)
300	396.0	250.0	6.0
450	270.0	166.7	6.0
835	161.0	89.8	3.6
900	149.0	83.3	3.6
1450	89.1	51.7	3.6
1800	72.0	41.7	3.6
1900	68.0	39.5	3.6
2000	64.5	37.5	3.6
2450	51.5	30.4	3.6
3000	41.5	25.0	3.6
5200	X	X	X
5800	X	X	x

## 5.0 Tissue Simulation Fluid

Tissue simulation fluids in the frequency range of 450MHz to 2450MHz are based on IEEE-1528 and FCC Supplement C guidelines. All fluids meet the dielectric specifications as outlined in the above standards (within allowable tolerances) and are calibrated on a regular basis, to maintain stability. The recipes used along with the dielectric target values are included in the table below.

Ingredients (% Weight)	450 MHz Head	835 MHz Head	915 MHz Head	1900 MHz Head	2450 MHz Head
<b>Water</b>	38.56	41.45	41.05	54.9	62.7
<b>Salt</b>	3.95	1.45	1.35	0.18	0.5
<b>Sugar</b>	56.32	56.0	56.5	x	x
<b>HEC</b>	0.98	1.0	1.0	x	x
<b>Bactericide</b>	0.19	0.1	0.1	0.1	X
<b>Triton-X</b>	X	X	X	X	36.8
<b>DGBE</b>	X	X	X	44.92	x
<b><math>\epsilon^r</math></b>	43.42	42.54	42.0	39.9	39.8
<b><math>\delta</math></b>	0.85	0.91	1.0	1.42	1.88

Ingredients (% Weight)	450 MHz Body	835 MHz Body	915 MHz Body	1900 MHz Body	2450 MHz Body
<b>Water</b>	51.16	52.4	56.0	40.4	73.2
<b>Salt</b>	1.49	1.4	0.76	0.5	0.04
<b>Sugar</b>	46.78	45.0	41.76	58.0	X
<b>HEC</b>	0.52	1.0	1.21	1.0	X
<b>Bactericide</b>	0.05	0.1	0.27	0.1	X
<b>Triton-X</b>	X	X	X	X	X
<b>DGBE</b>	X	X	X	X	26.7
<b><math>\epsilon^r</math></b>	58.0	56.1	56.8	54.0	52.5
<b><math>\delta</math></b>	0.83	0.95	1.07	1.45	1.78

NOTE. Recipes are based on those presented in FCC Supplement C Page 36.

For frequencies above 2450MHz recipes are presented in a separate appendix.

## 5.1 Tissue Calibration Procedure Using a Coaxial Probe

The VNA (Vector Network Analyzer) is configured and calibrated for the frequency of the simulated tissue which has to be assessed. The Coaxial probe is then calibrated in line with the tissue frequency using an open, short, and De-Ionized water routine. The sample of simulated tissue is placed into a non-metallic container for use during the calibration. The temperature of the simulated tissue sample is measured. The probe head is then completely immersed in the simulated tissue sample (the probe is held in place using a non metallic probe holder). The simulated tissue sample is then measured to assess the permittivity and conductivity.

## 5.2 Tissue Calibration Results




Tissue used during the SAR assessment is calibrated prior to use in the measurement process. APREL Laboratories use the co-axial probe method for all tissue calibration exercises. Tissue which is being used over a period of 24 hours is re-calibrated to ensure that no change to the dielectric properties will affect the SAR measurement process. The table below provides details of the results from the tissue equivalent dielectric calibration.

Calibrated By	Calibration Date	Frequency MHz	Tissue Type	Epsilon ( $\epsilon'$ )	Sigma ( $\delta$ )
Y. Chen	29-12-03	2450	Body	50.60	2.03

## 6.0 System Validation

ALSAS-10U is fully validated prior to the SAR assessment of the DUT following methodologies presented in IEEE-1528 section 8. The system is validated using tissue which has been calibrated within a 24 hour period. When the measurement process exceeds a 24 hour period a secondary system validation is executed and the results presented within this test report. The graphic plots resulting from the system validation are included in Appendix A SAR plots.



Date	Validation Frequency (MHZ)	Dipole Separation Distance mm	Power W	Dipole	SAR 1g W/kg	Target 1g W/kg	Delta %
29-12-03	2450	10	1.0	AL-CD10	54.1	52.4	3.4

Currently no standards are in place for validating a system while using body tissue. APREL Laboratories have conducted research using XFDTD to assess the target validation numbers while using body tissue. It should be noted that the target validation numbers presented in IEEE-1528 have been derived using FDTD methodologies.

## 6.1 Experimental Results Summary

The results for each experimental assessment are contained within this section. Where any deviation has been made from the given procedures contained within IEEE-1528 or FCC Supplement C this has been described accordingly.

## 6.2 SAR Measurement Procedure

The ALSAS-10U calculates SAR using the following equation,

$$SAR = \frac{\sigma |E|^2}{\rho}$$

$\sigma$ : represents the simulated tissue conductivity

$\rho$ : represents the tissue density

The DUT is set to transmit at the required power in line with product specification, at each frequency relating to the LOW, MID, and HIGH channel settings.

Pre-scans are made on the device to establish the location for the transmitting antenna, using a large area scan in either air or tissue simulation fluid.

The DUT is placed against the Universal Phantom where the maximum area scan dimensions are larger than the physical size of the resonating antenna. When the scan size is not large enough to cover the peak SAR distribution, it is modified by either extending the area scan size in both the X and Y directions, or the device is shifted within the predefined area.

The area scan is then run to establish the peak SAR location (interpolated resolution set at 1mm<sup>2</sup>) which is then used to orient the center of the zoom scan. The zoom scan is then executed and the 1g and 10g averages are derived from the zoom scan volume (interpolated resolution set at 1mm<sup>3</sup>).

## 6.3 SAR Exposure Limits

SAR assessments have been made in line with the requirements of IEEE-1528, FCC Supplement C, and comply with ANSI/IEEE C95.1-1992 "Uncontrolled Environments" limits. These limits apply to a location which is deemed as "Uncontrolled Environment" which can be described as a situation where the general public may be exposed to an RF source with no prior knowledge or control over their exposure.

Type of Exposure	Uncontrolled Environment Limit
Spatial Peak SAR (1g cube tissue for brain or body)	<b>1.60 W/kg</b>
Spatial Average SAR (whole body)	<b>0.08 W/kg</b>
Spatial Peak SAR (10g for hands, feet, ankles and wrist)	<b>4.00 W/kg</b>

## 6.4 Equipment List


APREL Laboratories utilize the following equipment.

Equipment Description	Asset/Serial Number	Calibration Due Date
ALSAS-10U		Prior to Test
Boundary Detection Unit		
Daq-Paq		
Pentium 4 Workstation		Not Required
Signal Generator		
Gigatronics Power Meter		
Gigatronics Broad Band Power Sensor		
HP-Directional Coupler		
APREL Laboratories 800-4200MHz 12W Amplifier		
APREL Laboratories 2450MHz Validation Dipole		
APREL Laboratories E-020 E-Field Probe		
40MHz -20GHz VNA		
TRL Calibration Kit		
APREL Laboratories Coaxial Probe (Dielectric Probe Kit)		
APREL Laboratories Universal Phantom		
APREL Laboratories SAM Phantom LHS		
APREL Laboratories SAM Phantom RHS		
APREL Laboratories 15mm Dipole Separation Kit		
APREL Laboratories 10mm Dipole Separation Kit		

## 6.5 SAR Measurement Results

DELL Blade-II X300

Intel PRO/Wireless 802.11b/g Mini-PCI type 3B WLAN Adapter



<b>Power</b>	17.4dB (bmode) 16.5dB(gmode)
<b>DUT Position</b>	Top Right
<b>Separation</b>	0mm
<b>Antenna Type</b>	Internal
<b>Antenna Manufacturer</b>	Hitachi
<b>Antenna Location</b>	Top right hand side of LCD
<b>Power Mode</b>	Mains A/C
<b>Tx Frequency</b>	2412-2462MHz
<b>Duty Cycle</b>	100%
<b>Epsilon</b>	50.60
<b>Sigma</b>	2.03
<b>Tissue Depth</b>	15cm
<b>Phantom Type</b>	Universal
<b>DUT Workstation Location</b>	Centre
<b>Device Positioner</b>	HESET1
<b>Test Date</b>	23-12-03
<b>Test Engineer</b>	R-Kuleba

Mode	Channel	Frequency MHz	1g SAR W/kg
801.11b	1	2412	1.13
802.11b	6	2437	0.86
802.11b	12	2462	0.89
<hr/>			
802.11g	1	2412	0.79
802.11g	6	2437	0.68
802.11g	12	2462	0.60

SAR Limit	Conservative Measured SAR
1.6 W/kg 1gram Average Maximum	1.13 W/kg 1gram Average

**SAR Plot for Conservative SAR Included in Appendix A.**

DELL Blade-II X300  
Intel PRO/Wireless 802.11b/g Mini-PCI type 3B WLAN Adapter



<b>Power</b>	17.4dB (bmode) 16.5dB (gmode)
<b>DUT Position</b>	Top right LCD open
<b>Separation</b>	0mm
<b>Antenna Type</b>	Internal
<b>Antenna Manufacturer</b>	Hitachi Corp
<b>Antenna Location</b>	Top right hand side of LCD
<b>Power Mode</b>	Mains A/C
<b>Tx Frequency</b>	2412-2462MHz
<b>Duty Cycle</b>	100%
<b>Epsilon</b>	50.60
<b>Sigma</b>	2.03
<b>Tissue Depth</b>	15cm
<b>Phantom Type</b>	Universal
<b>DUT Workstation Location</b>	Centre
<b>Device Positioner</b>	HESET1
<b>Test Date</b>	23-12-03
<b>Test Engineer</b>	R-Kuleba

Mode	Channel	Frequency MHz	1g SAR W/kg
801.11b	1	2412	1.45
802.11b	6	2437	1.22
802.11b	12	2462	1.35
<hr/>			
802.11g	1	2412	1.36
802.11g	6	2437	1.21
802.11g	12	2462	1.25

SAR Limit	Conservative Measured SAR
1.6 W/kg 1gram Average Maximum	1.45 W/kg 1gram Average

**SAR Plot for Conservative SAR Included in Appendix A.**

DELL Blade-II X300  
Intel PRO/Wireless 802.11b/g Mini-PCI type 3B WLAN Adapter

<b>Power</b>	17.4dB (bmode) 16.5dB (gmode)
<b>DUT Position</b>	Front right LCD Closed
<b>Separation</b>	0mm
<b>Antenna Type</b>	Internal
<b>Antenna Manufacturer</b>	Hitachi Corp
<b>Antenna Location</b>	Top right hand side of LCD
<b>Power Mode</b>	Mains A/C
<b>Tx Frequency</b>	2412-2462MHz
<b>Duty Cycle</b>	100%
<b>Epsilon</b>	50.60
<b>Sigma</b>	2.03
<b>Tissue Depth</b>	15cm
<b>Phantom Type</b>	Universal
<b>DUT Workstation Location</b>	Centre
<b>Device Positioner</b>	HESET1
<b>Test Date</b>	23-12-03
<b>Test Engineer</b>	R-Kuleba

Mode	Channel	Frequency MHz	1g SAR W/kg
801.11b	1	2412	0.67
802.11b	6	2437	0.57
802.11b	12	2462	0.56
<hr/>			
802.11g	1	2412	0.41
802.11g	6	2437	0.34
802.11g	12	2462	0.37

SAR Limit	Conservative Measured SAR
1.6 W/kg 1gram Average Maximum	0.67 W/kg 1gram Average

## SAR Plot for Conservative SAR Included in Appendix A.

## 7.0 Measurement Uncertainty

SAR measurement uncertainty has been calculated using the uncertainty table below, based on that which is presented in IEEE-1528.

Source of Uncertainty	Description (Annex)	Tolerance Value	Probability Distribution	Divisor	$c_i^1 (1-g)$	$c_i^1 (10-g)$	Standard Uncertainty (1-g)	Standard Uncertainty (10-g)	$v_i^2$ or $v_{eff}$
<b>Measurement System</b>									
Probe Calibration	E1.1	3.5	normal	1	1	1	3.5	3.5	8
Axial Isotropy	E1.2	3.7	rectangular	$\sqrt{3}$	$(1-cp)^{1/2}$	$(1-cp)^{1/2}$	1.5	1.5	8
Hemispherical Isotropy	E1.2	10.9	rectangular	$\sqrt{3}$	$\sqrt{cp}$	$\sqrt{cp}$	4.4	4.4	8
Boundary Effect	E1.3	1.0	rectangular	$\sqrt{3}$	1	1	0.6	0.6	8
Linearity	E1.4	4.7	rectangular	$\sqrt{3}$	1	1	2.7	2.7	8
Detection Limit	E1.5	1.0	rectangular	$\sqrt{3}$	1	1	0.6	0.6	8
Readout Electronics	E1.6	1.0	normal	1	1	1	1.0	1.0	8
Response Time	E1.7	0.8	rectangular	$\sqrt{3}$	1	1	0.5	0.5	8
Integration Time	E1.8	1.7	rectangular	$\sqrt{3}$	1	1	1.0	1.0	8
RF Ambient Condition	E5.1	3.0	rectangular	$\sqrt{3}$	1	1	1.7	1.7	8
Probe Positioner Mech. Restrictions	E5.2	0.4	rectangular	$\sqrt{3}$	1	1	0.2	0.2	8
Probe Positioning with respect to Phantom Shell	E5.3	2.9	rectangular	$\sqrt{3}$	1	1	1.7	1.7	8
Extrapolation and Integration	E4.2	3.7	rectangular	$\sqrt{3}$	1	1	2.1	2.1	$\infty$
Test Sample Positioning	E3.1.3	4.0	normal	1	1	1	4.0	4.0	11
Device Holder Uncertainty	E3.1.2	2.0	normal	1	1	1	2.0	2.0	8
Drift of Output Power	Section 6.6.2	0.0	rectangular	$\sqrt{3}$	1	1	0.0	0.0	8
<b>Phantom and Setup</b>									
Phantom Uncertainty (shape and thickness tolerance)	E2.1	3.4	rectangular	$\sqrt{3}$	1	1	2.0	2.0	$\infty$
Liquid Conductivity (target)	E2.2	4.0	rectangular	$\sqrt{3}$	0.7	0.5	1.3	0.9	$\infty$
Liquid Conductivity (meas.)	E2.2	2.0	rectangular	$\sqrt{3}$	0.7	0.5	0.8	0.6	$\infty$
Liquid Permittivity (target)	E2.2	4.1	rectangular	$\sqrt{3}$	0.6	0.5	1.4	1.2	$\infty$
Liquid Permittivity (meas.)	E2.2	2.0	rectangular	$\sqrt{3}$	0.6	0.5	0.7	0.6	$\infty$
<b>Combined Uncertainty</b>									
Combined Uncertainty (coverage factor = 2)	Normal (k=2)			RSS			9.0	8.9	$\infty$
					18.0	17.8	$\infty$		

## Appendix A SAR Plots



**SAR Data Report**

Start : 29-Dec-2003 02:33:52 PM  
 End : 29-Dec-2003 02:41:47 PM  
 Scanning time : 475 secs

**Product Data**

Device Name : DELL-Blade II\_Hitachi\_01\_2412  
 Device Serial No. : PN 5N793  
 Device Model : Blade II  
 Device Type : Other  
 Device Frequency : 2412.00 MHz  
 Max. Transmit Power : 0.055 W  
 Drift Time : 60 min(s)  
 Device Length : 0 mm  
 Device Width : 0 mm  
 Device Depth : 0 mm  
 Device Orientation : Touch  
 Antenna Type : Internal  
 Device Power at ERP-Start : 0.05  
 Device Power At ERP-Finish: 0.07  
 Device Drift : 0.02

**Measurement Data**

Phantom Name : APREL-Uni  
 Phantom Type : Uni-Phantom  
 Phantom Size : 280 x 280 x 200  
 Phantom Serial No. : Default  
 Phantom Location : Center  
 Phantom Description : test  
 Tissue Type : Body  
 Tissue Serial No. : Lab1  
 Tissue Frequency : 2450.00 MHz  
 Tissue Calibration Date : 16-Dec-2003  
 Tissue Dielectric : 50.60 F/m  
 Tissue Conductivity : 2.03 S/m  
 Tissue Density : 1000.00 kg/cu. m  
 Crest Factor : 1.00

**Probe Data**

Probe Name : APREL Lab Probe  
 Probe Model : E020  
 Probe Type : E-Field Triangle  
 Probe Serial No. : 209  
 Probe Frequency : 2450.00 MHz  
 Tissue Type : Body  
 Calibrated Dielectric : 50.60 F/m  
 Calibrated Conductivity : 2.03 S/m  
 Probe Offset : 2.44 mm  
 Conversion Factor : 4.60  
 Diode Compression Pt : 98.00 mV  
 Probe Sensitivity : 0.72 0.72 0.72  $\mu$ V/(V/sq. m)

Project number: ITLB-Dell-4089

FCC ID: ID:E2K24GBRL

51 Spectrum Way

Nepean, Ontario

Canada K2R 1E6

© 2004 APREL Laboratories


Page 24 of 54



AL-065

This report shall not be reproduced, except in full, without written approval of APREL Laboratories

Tel: (613) 820-2730  
 Fax: (613) 820-4161  
 Info@aprel.com  
 www.aprel.com



1 gram SAR Value

: X = -2.50 Y = 39.70 Z = 3 Value = 1.13 W/kg

10 gram SAR Value


: X = -2.50 Y = 39.70 Z = 3 Value = 0.49 W/kg

Area Scan Peak SAR

: 1.44

Zoom Scan Peak SAR

: 2.79



**SAR Data Report**

Start : 29-Dec-2003 03:59:49 PM  
 End : 29-Dec-2003 04:07:42 PM  
 Scanning time : 473 secs

**Product Data**

Device Name : DELL-Blade II\_Hitachi\_04\_2412-top  
 Device Serial No. : PN 5N793  
 Device Model : Blade II  
 Device Type : Other  
 Device Frequency : 2412.00 MHz  
 Max. Transmit Power : 0.045 W  
 Drift Time : 60 min(s)  
 Device Length : 0 mm  
 Device Width : 0 mm  
 Device Depth : 0 mm  
 Device Orientation : Touch  
 Antenna Type : Internal  
 Device Power at ERP-Start : 0.03  
 Device Power At ERP-Finish: 0.04  
 Device Drift : 0.01

**Measurement Data**

Phantom Name : APREL-Uni  
 Phantom Type : Uni-Phantom  
 Phantom Size : 280 x 280 x 200  
 Phantom Serial No. : Default  
 Phantom Location : Center  
 Phantom Description : test  
 Tissue Type : Body  
 Tissue Serial No. : Lab1  
 Tissue Frequency : 2450.00 MHz  
 Tissue Calibration Date : 16-Dec-2003  
 Tissue Dielectric : 50.60 F/m  
 Tissue Conductivity : 2.03 S/m  
 Tissue Density : 1000.00 kg/cu. m  
 Crest Factor : 1.00

**Probe Data**

Probe Name : APREL Lab Probe  
 Probe Model : E020  
 Probe Type : E-Field Triangle  
 Probe Serial No. : 209  
 Probe Frequency : 2450.00 MHz  
 Tissue Type : Body  
 Calibrated Dielectric : 50.60 F/m  
 Calibrated Conductivity : 2.03 S/m  
 Probe Offset : 2.44 mm  
 Conversion Factor : 4.60  
 Diode Compression Pt : 98.00 mV  
 Probe Sensitivity : 0.72 0.72 0.72  $\mu$ V/(V/sq. m)

Project number: ITLB-Dell-4089

FCC ID: ID:E2K24GBRL

51 Spectrum Way

Nepean, Ontario

Canada K2R 1E6

© 2004 APREL Laboratories


Page 26 of 54




AL-065

This report shall not be reproduced, except in full, without written approval of APREL Laboratories

Tel: (613) 820-2730  
 Fax: (613) 820-4161  
 Info@aprel.com  
 www.aprel.com



1 gram SAR Value : X = -2.50 Y = 39.70 Z = 3.3 Value = 0.74 W/kg  
10 gram SAR Value : X = -2.50 Y = 39.70 Z = 3.3 Value = 0.31 W/kg  
Area Scan Peak SAR : 0.84  
Zoom Scan Peak SAR : 1.85SAR Data Report



Project number: ITLB-Dell-4089  
FCC ID: ID: E2K24GBRL

51 Spectrum Way  
Nepean, Ontario  
Canada K2R 1E6  
© 2004 APREL Laboratories

AL-065



This report shall not be reproduced, except in full, without written approval of APREL Laboratories

Page 27 of 54

Tel: (613) 820-2730  
Fax: (613) 820-4161  
Info@aprel.com  
www.aprel.com

**SAR Data Report**

Start : 30-Dec-2003 02:31:52 PM  
 End : 30-Dec-2003 02:40:45 PM  
 Scanning time : 533 secs

**Product Data**

Device Name : Dell\_Blade II\_Hitachi\_09  
 Device Serial No. : PN 5N793  
 Device Model : Blade II  
 Device Type : Other  
 Device Frequency : 2412.00 MHz  
 Max. Transmit Power : 0.055 W  
 Drift Time : 60 min(s)  
 Device Length : 0 mm  
 Device Width : 0 mm  
 Device Depth : 0 mm  
 Device Orientation : Touch  
 Antenna Type : Internal  
 Device Power at ERP-Start : 0.20  
 Device Power At ERP-Finish: 0.19  
 Device Drift : 0.01

**Measurement Data**

Phantom Name : APREL-Uni  
 Phantom Type : Uni-Phantom  
 Phantom Size : 280 x 280 x 200  
 Phantom Serial No. : Default  
 Phantom Location : Center  
 Phantom Description : test  
 Tissue Type : Body  
 Tissue Serial No. : Lab1  
 Tissue Frequency : 2450.00 MHz  
 Tissue Calibration Date : 16-Dec-2003  
 Tissue Dielectric : 50.60 F/m  
 Tissue Conductivity : 2.03 S/m  
 Tissue Density : 1000.00 kg/cu. m  
 Crest Factor : 1.00

**Probe Data**

Probe Name : APREL Lab Probe  
 Probe Model : E020  
 Probe Type : E-Field Triangle  
 Probe Serial No. : 209  
 Probe Frequency : 2450.00 MHz  
 Tissue Type : Body  
 Calibrated Dielectric : 50.60 F/m  
 Calibrated Conductivity : 2.03 S/m  
 Probe Offset : 2.44 mm  
 Conversion Factor : 4.60  
 Diode Compression Pt : 98.00 mV  
 Probe Sensitivity : 0.72 0.72 0.72  $\mu$ V/(V/sq. m)

Project number: ITLB-Dell-4089

FCC ID: ID:E2K24GBRL

51 Spectrum Way

Nepean, Ontario

Canada K2R 1E6

© 2004 APREL Laboratories


Page 28 of 54



AL-065


This report shall not be reproduced, except in full, without written approval of APREL Laboratories

Tel: (613) 820-2730  
 Fax: (613) 820-4161  
 Info@aprel.com  
 www.aprel.com



1 gram SAR Value  
10 gram SAR Value  
Area Scan Peak SAR

: X = 12.80 Y = 5.00 Z = 3.3 Value = 0.67 W/kg  
: X = 12.80 Y = 5.00 Z = 3.3 Value = 0.32 W/kg  
: 0.86



Project number: ITLB-Dell-4089  
FCC ID: ID: E2K24GBRL

51 Spectrum Way  
Nepean, Ontario  
Canada K2R 1E6  
© 2004 APREL Laboratories

AL-065



This report shall not be reproduced, except in full, without written approval of APREL Laboratories

Page 29 of 54

Tel: (613) 820-2730  
Fax: (613) 820-4161  
Info@aprel.com  
www.aprel.com

**SAR Data Report**

Start : 30-Dec-2003 11:33:39 PM  
 End : 30-Dec-2003 11:43:08 PM  
 Scanning time : 569 secs

**Product Data**

Device Name : DELL-Blade II\_Hitachi\_23b\_2412\_LCD-open  
 Device Serial No. : PN 5N793  
 Device Model : Blade II  
 Device Type : Other  
 Device Frequency : 2412.00 MHz  
 Max. Transmit Power : 0.055 W  
 Drift Time : 60 min(s)  
 Device Length : 0 mm  
 Device Width : 0 mm  
 Device Depth : 0 mm  
 Device Orientation : Touch  
 Antenna Type : Internal  
 Device Power at ERP-Start : 0.18  
 Device Power At ERP-Finish: 0.18  
 Device Drift : 0.00

**Measurement Data**

Phantom Name : APREL-Uni  
 Phantom Type : Uni-Phantom  
 Phantom Size : 280 x 280 x 200  
 Phantom Serial No. : Default  
 Phantom Location : Center  
 Phantom Description : test  
 Tissue Type : Body  
 Tissue Serial No. : Lab1  
 Tissue Frequency : 2450.00 MHz  
 Tissue Calibration Date : 16-Dec-2003  
 Tissue Dielectric : 50.60 F/m  
 Tissue Conductivity : 2.03 S/m  
 Tissue Density : 1000.00 kg/cu. m  
 Crest Factor : 1.00

**Probe Data**

Probe Name : APREL Lab Probe  
 Probe Model : E020  
 Probe Type : E-Field Triangle  
 Probe Serial No. : 209  
 Probe Frequency : 2450.00 MHz  
 Tissue Type : Body  
 Calibrated Dielectric : 50.60 F/m  
 Calibrated Conductivity : 2.03 S/m  
 Probe Offset : 2.44 mm  
 Conversion Factor : 4.60  
 Diode Compression Pt : 98.00 mV  
 Probe Sensitivity : 0.72 0.72 0.72  $\mu$ V/(V/sq. m)

Project number: ITLB-Dell-4089

FCC ID: ID:E2K24GBRL

51 Spectrum Way  
 Nepean, Ontario  
 Canada K2R 1E6  
 © 2004 APREL Laboratories


AL-065




This report shall not be reproduced, except in full, without written approval of APREL Laboratories

Page 30 of 54

Tel: (613) 820-2730  
 Fax: (613) 820-4161  
 Info@aprel.com  
 www.aprel.com



1 gram SAR Value : X = 18.30 Y = -44.30 Z = 3.6 Value = 1.45 W/kg  
10 gram SAR Value : X = 18.30 Y = -44.30 Z = 3.6 Value = 0.62 W/kg  
Area Scan Peak SAR : 1.76  
Zoom Scan Peak SAR : 4.02



Project number: ITLB-Dell-4089  
FCC ID: ID: E2K24GBRL

51 Spectrum Way  
Nepean, Ontario  
Canada K2R 1E6  
© 2004 APREL Laboratories

AL-065



This report shall not be reproduced, except in full, without written approval of APREL Laboratories

Page 31 of 54

Tel: (613) 820-2730  
Fax: (613) 820-4161  
Info@aprel.com  
www.aprel.com

**SAR Data Report**

Start : 31-Dec-2003 01:12:21 AM  
 End : 31-Dec-2003 01:21:57 AM  
 Scanning time : 576 secs

**Product Data**

Device Name : DELL-Blade II\_Hitachi\_25B\_2412\_top-open-  
 Device Serial No. : PN 5N793  
 Device Model : Blade II  
 Device Type : Other  
 Device Frequency : 2412.00 MHz  
 Max. Transmit Power : 0.055 W  
 Drift Time : 60 min(s)  
 Device Length : 0 mm  
 Device Width : 0 mm  
 Device Depth : 0 mm  
 Device Orientation : Touch  
 Antenna Type : Internal  
 Device Power at ERP-Start : 0.16  
 Device Power At ERP-Finish: 0.17  
 Device Drift : 0.01

**Measurement Data**

Phantom Name : APREL-Uni  
 Phantom Type : Uni-Phantom  
 Phantom Size : 280 x 280 x 200  
 Phantom Serial No. : Default  
 Phantom Location : Center  
 Phantom Description : test  
 Tissue Type : Body  
 Tissue Serial No. : Lab1  
 Tissue Frequency : 2450.00 MHz  
 Tissue Calibration Date : 16-Dec-2003  
 Tissue Dielectric : 50.60 F/m  
 Tissue Conductivity : 2.03 S/m  
 Tissue Density : 1000.00 kg/cu. m  
 Crest Factor : 1.00

**Probe Data**

Probe Name : APREL Lab Probe  
 Probe Model : E020  
 Probe Type : E-Field Triangle  
 Probe Serial No. : 209  
 Probe Frequency : 2450.00 MHz  
 Tissue Type : Body  
 Calibrated Dielectric : 50.60 F/m  
 Calibrated Conductivity : 2.03 S/m  
 Probe Offset : 2.44 mm  
 Conversion Factor : 4.60  
 Diode Compression Pt : 98.00 mV  
 Probe Sensitivity : 0.72 0.72 0.72  $\mu$ V/(V/sq. m)

Project number: ITLB-Dell-4089

FCC ID: ID:E2K24GBRL


51 Spectrum Way  
 Nepean, Ontario  
 Canada K2R 1E6  
 © 2004 APREL Laboratories

AL-065

Page 32 of 54



Tel: (613) 820-2730  
 Fax: (613) 820-4161  
 Info@aprel.com  
 www.aprel.com



1 gram SAR Value

: X = -12.70 Y = -25.20 Z = 2.6 Value = 1.27 W/kg

10 gram SAR Value


: X = -12.70 Y = -25.20 Z = 2.6 Value = 0.54 W/kg

Area Scan Peak SAR

: 1.40

Zoom Scan Peak SAR

: 3.19



**Appendix B**  
**Probe Calibration Certificate**

Project number: ITLB-Dell-4089  
FCC ID: ID:E2K24GBRL

51 Spectrum Way  
Nepean, Ontario  
Canada K2R 1E6  
© 2004 APREL Laboratories

AL-065



This report shall not be reproduced, except in full, without written approval of APREL Laboratories

Page 34 of 54

Tel: (613) 820-2730  
Fax: (613) 820-4161  
Info@aprel.com  
www.aprel.com

**NCL CALIBRATION LABORATORIES**

Calibration File No.: CP-339

Client.: APREL

**C E R T I F I C A T E   O F   C A L I B R A T I O N**

It is certified that the equipment identified below has been calibrated in the  
**NCL CALIBRATION LABORATORIES** by qualified personnel following recognized  
procedures and using transfer standards traceable to NRC/NIST.

Equipment: Miniature Isotropic RF Probe 2450 MHz

Manufacturer: APREL Laboratories

Model No.: E-020

Serial No.: 209

**BODY Calibration**

Calibration Procedure: SSI/DRB-TP-D01-032-E020

Project No: Internal

Calibrated: 3<sup>rd</sup> November 2003

Released on: 4<sup>th</sup> November 2003

This Calibration Certificate is Incomplete Unless Accompanied with the Calibration  
Results Summary

Released By: \_\_\_\_\_

**NCL CALIBRATION LABORATORIES**

51 SPECTRUM WAY  
NEPEAN, ONTARIO  
CANADA K2R 1E6

Division of APREL Lab.  
TEL: (613) 820-4988  
FAX: (613) 820-4161

Project number: ITLB-Dell-4089  
FCC ID: ID:E2K24GBRL

51 Spectrum Way  
Nepean, Ontario  
Canada K2R 1E6  
© 2004 APREL Laboratories

AL-065



This report shall not be reproduced, except in full, without written approval of APREL Laboratories

Page 35 of 54

Tel: (613) 820-2730  
Fax: (613) 820-4161  
Info@aprel.com  
www.aprel.com

## Introduction

This Calibration Report reproduces the results of the calibration performed in line with the SSI/DRB-TP-D01-032-E020 E-Field Probe Calibration Procedure. The results contained within this report are for APREL E-Field Probe E-020 209.

## References

SSI/DRB-TP-D01-032-E020 E-Field Probe Calibration Procedure

IEEE 1528 "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques"

SSI-TP-011 Tissue Calibration Procedure

## Conditions

Probe 209 was a new probe taken from stock prior to calibration.

**Ambient Temperature of the Laboratory:** 22 °C +/- 0.5°C  
**Temperature of the Tissue:** 21 °C +/- 0.5°C



**Calibration Results Summary**

**Probe Type:** E-Field Probe E-020  
**Serial Number:** 209  
**Frequency:** 2450 MHz  
**Sensor Offset:** 1.56 mm  
**Sensor Length:** 2.5 mm  
**Tip Enclosure:** Ertalyte\*  
**Tip Diameter:** 5 mm  
**Tip Length:** 60 mm  
**Total Length:** 290 mm

\*Resistive to recommended tissue recipes per IEEE-1528

Sensitivity in Air

**Channel X:** 0.72  $\mu$ V/(V/m)<sup>2</sup>  
**Channel Y:** 0.72  $\mu$ V/(V/m)<sup>2</sup>  
**Channel Z:** 0.72  $\mu$ V/(V/m)<sup>2</sup>  
**Diode Compression Point:** 98 mV

## Sensitivity in Body Tissue

**Frequency:** 2450 MHz

**Epsilon:** 50.6 (+/-5%)      **Sigma:** 1.98 S/m (+/-10%)

### ConvF

**Channel X:** 4.60

**Channel Y:** 4.60

**Channel Z:** 4.60


Tissue sensitivity values were calculated using the load impedance of the APREL Laboratories Daq-Paq.



### Boundary Effect:

Uncertainty resulting from the boundary effect is less than 2% for the distance between the tip of the probe and the tissue boundary, when less than 2.4mm.

### Spatial Resolution:

The measured probe tip diameter is 5 mm (+/- 0.01 mm) and therefore meets the requirements of SSI/DRB-TP-D01-032 for spatial resolution.

**Receiving Pattern 2450 MHz (Air)**

**Isotropy Error 2450 MHz (Air)****Isotropicity:**

0.10 dB


Project number: ITLB-Dell-4089  
FCC ID: ID:E2K24GBRL51 Spectrum Way  
Nepean, Ontario  
Canada K2R 1E6  
© 2004 APREL Laboratories

AL-065

This report shall not be reproduced, except in full, without written approval of APREL Laboratories


Page 40 of 54

Tel: (613) 820-2730  
Fax: (613) 820-4161  
Info@aprel.com  
www.aprel.com

**Dynamic Range**

## Video Bandwidth

Probe Frequency Characteristics



**Video Bandwidth at 500 Hz** 1 dB  
**Video Bandwidth at 1.02 KHz:** 3 dB

## Conversion Factor Uncertainty Assessment

**Frequency:** 2450MHz

**Epsilon:** 50.6 (+/-5%)      **Sigma:** 1.98 S/m (+/-10%)

### ConvF

**Channel X:** 4.60 7%(K=2)

**Channel Y:** 4.60 7%(K=2)

**Channel Z:** 4.60 7%(K=2)

To minimize the uncertainty calculation all tissue sensitivity values were calculated using a load impedance of 5 MΩ.

### Boundary Effect:

For a distance of 2.4mm the evaluated uncertainty (increase in the probe sensitivity) is less than 2%.



## Test Equipment

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2003.



**Appendix C**  
**Dipole Calibration Certificate**

Project number: ITLB-Dell-4089  
FCC ID: ID:E2K24GBRL

51 Spectrum Way  
Nepean, Ontario  
Canada K2R 1E6  
© 2004 APREL Laboratories

AL-065



This report shall not be reproduced, except in full, without written approval of APREL Laboratories

Page 45 of 54

Tel: (613) 820-2730  
Fax: (613) 820-4161  
Info@aprel.com  
www.aprel.com

**NCL CALIBRATION LABORATORIES**

Calibration File No: DC-0265  
Project Number: Internal

**C E R T I F I C A T E   O F   C A L I B R A T I O N**

It is certified that the equipment identified below has been calibrated in the  
**NCL CALIBRATION LABORATORIES** by qualified personnel following recognized  
procedures and using transfer standards traceable to NRC/NIST.

APREL Validation Dipole

Manufacturer: APREL Laboratories  
Part number: D-2450-S-1  
Frequency: 2.45 GHz  
Serial No: ALCD-10

Customer: APREL

Calibrated: 15 November 2003  
Released on: 14 November 2003

Released By: \_\_\_\_\_

**NCL CALIBRATION LABORATORIES**

51 SPECTRUM WAY  
NEPEAN, ONTARIO  
CANADA K2R 1E6

Division of APREL Lab.  
TEL: (613) 820-4988  
FAX: (613) 820-4161

Project number: ITLB-Dell-4089  
FCC ID: ID: E2K24GBRL

51 Spectrum Way  
Nepean, Ontario  
Canada K2R 1E6  
© 2004 APREL Laboratories

AL-065



This report shall not be reproduced, except in full, without written approval of APREL Laboratories

Page 46 of 54  
Tel: (613) 820-2730  
Fax: (613) 820-4161  
Info@aprel.com  
www.aprel.com

## Calibration Results Summary

The following results relate the Calibrated Dipole and should be used as a quick reference for the user.

### Mechanical Dimensions


**Length:** 51.7 mm  
**Height:** 30.8 mm

### Electrical Specification

**SWR:** 1.181U  
**Return Loss:** -21.4 dB  
**Impedance:** 46.175

### System Validation Results

Frequency	1 Gram	10 Gram	Peak
2.45 GHz	52.45	22.91	102.91



## Introduction

This Calibration Report has been produced in line with the SSI Dipole Calibration Procedure SSI-TP-018. The results contained within this report are for Validation Dipole ALCD-10 at 2.45 GHz. The calibration routine consisted of a three-step process. Step 1 was a mechanical verification of the dipole to ensure that it meets the IEEE mechanical specification. Step 2 was an Electrical Calibration for the Validation Dipole, where the SWR, Impedance, and the Return loss were assessed. Step 3 involved a System Validation using the ALIDX-500, along with the APREL Reference E-010 130 MHz to 26 GHz E-Field Probe Serial Number 163.

## References

SSI-TP-018 Dipole Calibration Procedure

SSI-TP-016 Tissue Calibration Procedure

IEEE 1528 *DRAFT* "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques"

## Conditions

Dipole ALCD-10 was a new Dipole taken from stock prior to calibration.

**Ambient Temperature of the Laboratory:** 24 °C +/- 0.5°C

**Temperature of the Tissue:** 20 °C +/- 0.5°C



## Dipole Calibration Results

### Mechanical Verification

IEEE Length	IEEE Height	Measured Length	Measured Height
51.5 mm	30.4 mm	51.7 mm	30.8 mm


### Tissue Validation


Head Tissue 2450 MHz	Measured
Dielectric constant, $\epsilon_r$	39.2
Conductivity, $\sigma$ [S/m]	1.82
Tissue Conversion Factor,	4.61

**Electrical Calibration**

Test	Result	IEEE Value
S11 R/L	-21.4	-21 dB
SWR	1.181U	-
Impedance	46.175 Ω	

The Following Graphs are the results as displayed on the Vector Network Analyzer.

**S11 Parameter Return Loss**

**SWR****S11 FORWARD REFLECTION**


CH 1 - S11  
REFERENCE PLANE  
5.1160 mm

MARKER 2  
2.411000 GHz  
1.049 U

MARKER TO MAX  
MARKER TO MIN

1 2.450000 GHz  
1.181 U


MARKER READOUT  
FUNCTIONS

**Smith Chart Dipole Impedance**

**System Validation Results Using the Electrically Calibrated Dipole**

Frequency	1 Gram	10 Gram	Peak Above Feed Point
2.45 GHz	52.45	22.91	102.91

The following Graphic Plot is the splined measurement result for the course scan.



## Test Equipment

The test equipment used during Probe Calibration, manufacturer, model number and, current calibration status are listed and located on the main APREL server R:\NCL\Calibration Equipment\Instrument List May 2003