



AEGIS LABS INC.



Class II Permissive Change
Test Report
And Application for Grant of Equipment Authorization

Pertaining To:

EUT	FCC ID:
Inspiron 630m Notebook Computer, MN: PP19L	E2K5HCKT

Configuration
Tested with an Intel PRO/Wireless 2915ABG Network Connection, MN: WM3A2915ABG
With a set of Wistron NeWeb Corp. Antennas

MEASUREMENTS PERFORMED IN ACCORDANCE WITH

Regulatory Standard(s)
47 CFR Part 15, Subpart C Section 15.247

Test Method:

ANSI C63.4: 2003 American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz



Certificate Number: 1111.01

APPLICANT:

Dell Computer Corporation
One Dell Way
Round Rock, TX 78682

Contact(s): Mr. Jason Limoges

	REPORT BODY	APPENDICES	TOTAL PAGES
		A	

PREPARED BY:

Aegis Labs, Inc.
22431 Antonio Parkway B160-417
Rancho S. Margarita, CA 92688

Agent(s): Mr. Steve Kuiper
Mr. Rick Candelas
Mr. Johnny Candelas
Test Report #: INTEL-050912F
Test Report Revision: None

The contents of this report shall not be reproduced except in full, without the written approval of Aegis Labs, Inc.

Page 1 of 18

Report Number: INTEL-050912F

FCC ID: E2K5HCKT



AEGIS LABS INC.

TABLE OF CONTENTS

SECTION	TITLE	PAGE
	COVER SHEET.....	01
	TABLE OF CONTENTS.....	02
1.0	CERTIFICATION OF TEST DATA.....	03
2.0	SUMMARY OF TEST RESULTS.....	06
3.0	ADMINISTRATIVE DATA AND TEST DESCRIPTION.....	07
4.0	DESCRIPTION OF EUT.....	08
4.1	EUT Description.....	08
4.1.1	Channel Number and Frequencies.....	09
4.2	EUT Configuration.....	10
4.3	List of EUT Sub-Assemblies and Host Equipment.....	11
4.4	I/O Cabling Diagram and Description.....	12
5.0	TEST EQUIPMENT AND TEST SETUPS.....	13
5.1	AC Power Line Conducted Emissions.....	13
5.2	Spurious Radiated Emissions.....	14
5.3	Conducted Emissions At The Antenna Port.....	14
5.4	Test and Measurement Equipment Used.....	15
6.0	SAMPLE CALCULATIONS.....	16
7.0	MODIFICATIONS AND RECOMMENDATIONS.....	18

APPENDICES

A

Test Data

Page 2 of 18
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

1.0 CERTIFICATION OF TEST DATA

Aegis Labs, Inc. operates as both a Nevada and California Corporation with no organizational or financial relationship with any company, institution, or private individual.

Testing and engineering functions provided by Aegis Labs are furnished through the use of part-time, full-time or consulting engineers with the appropriate qualifications to carry out their duties. The intended purpose of this test report is to describe the measurement procedure and to determine whether the equipment under test "EUT" complies with both the conducted and radiated limits. Limits for emissions testing are described under Subpart C of Part 15 of the FCC rules.

The data, data evaluation and equipment configuration represented herein are a true and accurate representation of the Equipment Under Test (EUT) under the requirements specified in the emissions standard as described below. The test results contained in this report are only representative of the test sample tested as described in Section 3.0 of this report. Certification of the EUT is required as a prerequisite to marketing as defined in Part 2 of the FCC Rules.

Prepared By:



Johnny Candelas
Staff Engineer
Aegis Labs, Inc.

10/05/05
Date:


Reviewed By:



Rick Candelas
Lab Manager
Aegis Labs, Inc.

10/05/05
Date:

Report Approved By:



Steve J. Kuiper
Quality Assurance Manager
Aegis Labs, Inc.

10/05/05
Date:



AEGIS LABS INC.

2.0 SUMMARY OF TEST RESULTS

The test results provided within this report, indicate that the EUT has been found to be in **COMPLIANCE** with the test specifications based upon the following RF compliance standards:

Pass/Fail determination is based upon the nominal values of the test data.

802.11a Mode (5745-5825 MHz)

EMISSIONS STANDARD			
FCC Part 15 Section	Description	Results	Comments
15.247(a)(2)	The minimum 6dB bandwidth shall be at least 500 kHz.	PASSED	5745 MHz = 16.42 MHz 5785 MHz = 16.50 MHz 5825 MHz = 16.50 MHz
15.247(b)(1)	The maximum peak output power of the intentional radiator shall not exceed 1 watt.	PASSED	5745 MHz = 21.20 dBm = 131.83 mW 5785 MHz = 20.80 dBm = 120.23 mW 5825 MHz = 20.60 dBm = 114.82 mW
15.247(b)(4)	The intentional radiator shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the FCC guidelines per Section 1.1307(b)(1).	PASSED	Refer to MPE Calculations
15.247(c)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.	PASSED	See Data Sheets
15.247(c)	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.	PASSED	See Data Sheets
15.247(d)	The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	PASSED	5745 MHz = -13.17 dB 5785 MHz = -11.67 dB 5825 MHz = -12.00 dB
15.207	AC Conducted Emissions	PASSED	See Data Sheet
15.209	Radiated Emissions (30-1000 MHz)	PASSED	See Data Sheet



AEGIS LABS INC.

2.0 Summary of Test Results (Continued)

The test results provided within this report, indicate that the EUT has been found to be in **COMPLIANCE** with the test specifications based upon the following RF compliance standards:

Pass/Fail determination is based upon the nominal values of the test data.

802.11b Mode (2412-2462 MHz)

EMISSIONS STANDARD			
FCC Part 15 Section	Description	Results	Comments
15.247(a)(2)	The minimum 6dB bandwidth shall be at least 500 kHz.	PASSED	2412 MHz = 10.00 MHz 2437 MHz = 10.00 MHz 2462 MHz = 10.08 MHz
15.247(b)(1)	The maximum peak output power of the intentional radiator shall not exceed 1 watt.	PASSED	2412 MHz = 17.13 dBm = 51.64 mW 2437 MHz = 19.21 dBm = 83.37 mW 2462 MHz = 19.18 dBm = 82.79 mW
15.247(b)(4)	The intentional radiator shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the FCC guidelines per Section 1.1307(b)(1).	PASSED	Refer to MPE Calculations
15.247(c)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.	PASSED	See Data Sheets
15.247(c)	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.	PASSED	See Data Sheets
15.247(d)	The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	PASSED	2412 MHz = -9.00 dB 2437 MHz = -7.00 dB 2462 MHz = -7.67 dB
15.207	AC Conducted Emissions	PASSED	See Data Sheet
15.209	Radiated Emissions (30-1000 MHz)	PASSED	See Data Sheet



AEGIS LABS INC.

2.0 Summary of Test Results (Continued)

The test results provided within this report, indicate that the EUT has been found to be in **COMPLIANCE** with the test specifications based upon the following RF compliance standards:

Pass/Fail determination is based upon the nominal values of the test data.

802.11g Mode (2412-2462 MHz)

EMISSIONS STANDARD

FCC Part 15 Section	Description	Results	Comments
15.247(a)(2)	The minimum 6dB bandwidth shall be at least 500 kHz.	PASSED	2412 MHz = 16.50 MHz 2437 MHz = 16.58 MHz 2462 MHz = 15.67 MHz
15.247(b)(1)	The maximum peak output power of the intentional radiator shall not exceed 1 watt.	PASSED	2412 MHz = 24.12 dBm = 258.23 mW 2437 MHz = 23.96 dBm = 248.89 mW 2462 MHz = 23.87 dBm = 243.78 mW
15.247(b)(4)	The intentional radiator shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the FCC guidelines per Section 1.1307(b)(1).	PASSED	Refer to MPE Calculations
15.247(c)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.	PASSED	See Data Sheets
15.247(c)	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.	PASSED	See Data Sheets
15.247(d)	The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	PASSED	2412 MHz = -11.50 dB 2437 MHz = -11.17 dB 2462 MHz = -10.83 dB
15.207	AC Conducted Emissions	PASSED	See Data Sheet
15.209	Radiated Emissions (30-1000 MHz)	PASSED	See Data Sheet



AEGIS LABS INC.

3.0 ADMINISTRATIVE DATA AND TEST DESCRIPTION

DEVICE TESTED:	ITE Type: Inspiron 630m Notebook Computer Model Number(s): PP19L Serial Number: 0454774 FCC ID: E2K5HCKT
TEST DATE (S):	September 13 - 20, 2005
DATE EUT RECEIVED:	September 12, 2005
ORIGIN OF TEST SAMPLE (S):	Production Unit
RESPONSIBLE PARTY:	Dell Computer Corporation One Dell Way Round Rock, TX 78682
CLIENT CONTACT:	Mr. Jason Limoges
MANUFACTURER:	Dell Computer Corporation
TEST LOCATION:	Aegis Labs, Inc. 32231 Trabuco Creek Road Trabuco Canyon, CA 92678 Conducted Site #2 Radiated Site #2
A2LA CERTIFICATE:	1111.01, Valid through February 28, 2006
PURPOSE OF TEST:	To demonstrate compliance with the relevant standards described in Section 2.0 of this report.
TEST (S) PERFORMED:	Refer to Table in Section 2.0 of this report.

All calibration vendors were responsible for certifying Aegis Labs, Inc. test equipment as per the manufacturer's specifications and that the equipment is calibrated using instruments and standards where the accuracy is traceable to the National Institute of Standards and Technology (NIST). Calibration of all test equipment conforms to ANSI/NCSL Z540-1 and ISO 10012-1 and/or ISO/IEC Guide 17025 compliance (Additionally, other pertinent test equipment will carry MIL-STD-45662A). All calibration documents are on file with Aegis Labs, Inc., with copies provided upon request.

Page 7 of 18
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

4.0 DESCRIPTION OF EUT

4.1 EUT Description

Equipment Under Test (EUT)

Trade Name:	Inspiron 630m Notebook Computer
Model Number:	PP19L tested with an Intel PRO/Wireless 2915ABG Network Connection, MN: WM3A2915ABG
Frequency Range:	802.11a = 5745 – 5825 MHz 802.11b/g = 2412 – 2462MHz
Type of Transmission:	Direct Sequence Spread Spectrum
Transfer Rate:	1/5.5/11 Mbps for 802.11b mode 6/36/54 Mbps for 802.11g and 802.11a modes
Number of Channels:	802.11a mode (5725-5850 MHz) = 5 802.11b mode (2400-2483.5 MHz) = 11 802.11g mode (2400-2483.5 MHz) = 11
Modulation Type:	DBPSK, DQPSK, CCK, OFDM
Antenna Type:	<u>Wistron NeWeb Corp.:</u> PIFA (Main/Aux)
Antenna Gain (See Note 2):	<u>Wistron NeWeb Corp.:</u> 2.4 GHz = 1.30 (Main), 1.38 (Aux) dBi 5 GHz = 1.49 (Main), 1.05 (Aux) dBi
Transmit Output Power:	21 dBm (Typical) for 802.11a mode 17 - 19 dBm (Typical) for 802.11b mode 24 dBm (Typical) for 802.11g mode Please see Appendix A (Data Sheets) for actual output power.
Power Supply:	3.3VDC from computer MPCI slot.
Number of External Test Ports Exercised:	2 Antenna Ports (1 Main & 1 Auxiliary)

The Inspiron | 630m Notebook Computer was tested with an Intel PRO/Wireless 2915ABG Network Connection as an embedded 2.4 GHz Wireless Local Area Network Mini-PCI adapter. The Mini-PCI Type 3A form factor is designed for notebook computer systems where overall thickness must be kept to an absolute minimum and connect to antennas internal to the notebook computer. It is capable of a data rate of up to 52 Mbps.

NOTE 1: For a more detailed description, please refer to the manufacturer's specifications or User's Manual.

NOTE 2: The EUT was tested with a set of antennas. (Refer to the antenna specifications exhibits).



AEGIS LABS INC.

4.1.1 Channel Number and Frequencies

802.11a Mode		802.11b Mode		802.11g Mode	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	1	2412	1	2412
153	5765	2	2417	2	2417
157	5785	3	2422	3	2422
161	5805	4	2427	4	2427
165	5825	5	2432	5	2432
		6	2437	6	2437
		7	2442	7	2442
		8	2447	8	2447
		9	2452	9	2452
		10	2457	10	2457
		11	2462	11	2462

Page 9 of 18
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

4.2 EUT Configuration

The EUT was tested with an Intel PRO/Wireless 2915ABG Network Connection installed in its mini PCI slot and was connected to a set of Wistron NeWeb Corp. triple band antennas via its main and auxiliary antenna ports. Data can be found in Appendix A.

For conducted emissions at the AC mains port and radiated emissions, the EUT was connected to a Dell monitor and Logitech mouse via its video and USB ports respectively.

The low, middle, and high channels were tested in 802.11a, b, & g modes. Also, the EUT was tested once transmitting from the MAIN antenna port and once transmitting from the AUX antenna port. The EUT was placed in either continuous transmit or continuous receive mode by a program provided by the manufacturer (*CRTU Version 3.2.15.0000*).

Page 10 of 18
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

4.3 List of EUT, Sub-Assemblies, and Host Equipment

LIST OF EUT AND SUB-ASSEMBLIES

Equipment Name	Manufacturer	Model Number	Serial Number
Inspiron 630m Notebook Computer	Dell Computer Corporation	PP19L	0454774
EUT Sub-Assemblies			
Intel PRO/Wireless 2915ABG Network Connection	Intel Corporation	WM3A2915ABG	MY-0C6952-12462-4A7-00YL
Auxiliary Triple Band Antenna	Wistron NeWeb Corp.	EDM-A	N/A
Main Triple Band Antenna	Wistron NeWeb Corp.	EDM-A	N/A

HOST EQUIPMENT LIST


Equipment Name	Manufacturer	Model Number	Serial Number
Monitor	Compaq	610	712BC060B526
Mouse	Logitech	Y-BF37	MCTZ5200581
Keyboard	Logitech	M-BJ58	PMA32715049

NOTE: All the power cords of the above support equipment are standard non-shielded, 1.8 meters long.



AEGIS LABS INC.

4.4 I/O Cabling Diagram and Description



- Cable 1: This is a 6-foot braid and foil shielded round cable connecting the host computer with the monitor. It has metallic DB-15 type connector at the computer end and is hardwired to the monitor. The cable is bundled to a length of one meter and the shield of the cable is grounded to the chassis of both devices via the connector shells.
- Cable 2: This is a 6-foot braid and foil shielded round cable connecting the host computer to the keyboard. It has a metallic 6-pin mini din type connector at the computer end and is hardwired to the keyboard. The shield of the cable is grounded to the chassis of the computer via the connector shell.
- Cable 3: This is a 6-foot braid and foil shielded round cable connecting the host computer to the mouse. It has a metallic 6-pin mini din type connector at the computer end and is hardwired to the mouse. The shield of the cable is grounded to the chassis of the computer via the connector shell.



AEGIS LABS INC.

5.0 TEST EQUIPMENT AND TEST SETUPS

The test equipment settings and functions are selected using the guidance of ANSI C63.4: 2003. All test equipment setups and operations during conducted and radiated emissions testing are in accordance with this reference document.

5.1 AC Power Line Conducted Emissions

During conducted emissions measurements, a spectrum analyzer was used as the measuring instrument along with a preselector and quasi-peak detector. A 10 dB attenuation pad was used for the protection of the spectrum analyzer input stage. The conducted emissions from the EUT in the frequency range from 150 kHz to 30 MHz were captured for graphical display through the use of automated LABVIEW EMI measurement software. All graphical readings were measured in the “Peak” mode only to reduce testing time. Upon completion of the graphical scan, the test lab personnel performed the conducted measurement scan manually using the spectrum analyzer front panel keys. All peak measurements coming within 3 dB of the limit line were “Averaged” and/or “Quasi-Peaked” and denoted appropriately in the EXCEL spreadsheet.

The Equipment Under Test (EUT) was configured as a system with peripherals connected, so that at least one interface port of each type is connected to one external peripheral when tested for conducted emissions according to ANSI C63.4: 2003. Excess power cord length was wrapped in a bundle 30 to 40 centimeters in length near the center of the cord. The EUT was tested in a tabletop configuration.

The emission readings for Line 1 and Line 2 are highlighted on the data sheets in Appendix A. The graphical scans only reflects peak readings while the tabulated data sheets reflect peak, average, and/or quasi-peak readings which ever applies.



AEGIS LABS INC.

5.2 Spurious Radiated Emissions

A spectrum analyzer was used as the measuring instrumentation along with a preselector and quasi-peak-detector. The pre-amplifiers were used to increase the sensitivity of the instrument. The spectrum analyzer was used in the peak detector mode with the “max-hold” feature activated and in Positive Peak mode. In this mode, the spectrum analyzer records the highest measured reading over all the sweeps. The quasi-peak detector was used only for those readings, which are marked accordingly in the data sheet. The effective measurement bandwidth used for the radiated emissions test was 120 kHz for (30 MHz- 1000 MHz). The spectrum analyzer operated such that the modulation of the signal was filtered out to set the analyzer in linear mode. For testing beyond 1000 MHz a spectrum analyzer capable of taking reading above 1000 MHz was connected to the high frequency amplifier, where these measurement readings were taken with the transducer placed at a 3-meter test distance from the EUT.

The Open Area Test Sites (OATS) was used for radiated emission testing. These test sites are designed according to ANSI C63.4: 2003 and ANSI C63.7: 1992 guidelines. The Measurements were conducted in accordance with ANSI C63.4: 2003 and ANSI C63.7: 1992 requirements.

Broadband biconical, log periodic, and horn antennas were used as transducers during the measurement reading phase. The frequency spans were wide (30 MHz-88 MHz, 88 MHz- 216 MHz, 216 MHz- 300 MHz, and 300 MHz- 1000 MHz). After 1000 MHz the horn antenna was used to measure emissions. The emission readings in both horizontal and vertical polarities are highlighted on the data sheets in Appendix A.

5.3 Conducted Emissions at the Antenna Port

A spectrum analyzer or power meter was used as the measuring instrumentation along with an attenuator and/or filter connected to the EUT antenna port. The attenuator and filters are used to ensure that the front end of the measurement instrument is not overloaded by the fundamental transmission. The instruments recorded the measured readings with the bandwidths (video and resolution) set in accordance with the FCC Rules and regulations.

For the power out measurements in 802.11b and 802.11g modes a peak power meter was used along with a peak power sensor with a wide enough bandwidth to capture the entire fundamental transmission. For 802.11a mode a spectrum analyzer with “Channel Power Measurement” function was used to measure the peak output power.

The measured readings are on the data sheets in Appendix A.



AEGIS LABS INC.

5.4 Test and Measurement Equipment Used

TEST EQUIPMENT USED					
Equipment Name	Manufacturer	Model Number	Serial Number	Calibration Due Date	Calibration Cycle
Spectrum Analyzer	Agilent	8564EC	4046A00387	08/15/06	1 Year
Preamp	Miteq	JS42-01001800-25-10P	815980	07/21/06	1 Year
2.4 GHz Notch Filter	Micro-Tronics	BRM50702-02	003	04/21/06	1 Year
5.15-5.35 GHz Notch Filter	Microwave Circuits	N0452502	3173-01	06/27/06	1 Year
5.725-5.850 GHz Notch Filter	Microwave Circuits	N0257881	3173-01	06/27/06	1 Year
Horn Antenna	EMCO	3115	2230	02/06/06	1 Year
Antenna - 18-26.5 GHz Pre-amplified Horn	Aegis Labs, Inc.	H042	SLK-35-3W	11/04/05	1 Year
Antenna - 26.5-40 GHz Pre-amplified Horn	Aegis Labs, Inc.	H028	GM1260-10	11/04/05	1 Year
Cable	Semflex	60637	S1L29BFS1348	04/11/06	1 Year
Temperature/Humidity Monitor	Dickson	TH550	7255185	N/A	N/A
Power Meter	Anritsu	ML2487A	6K00001785	04/12/06	1 Year
Wide Bandwidth Sensor	Anritsu	MA2491A	31193	04/12/06	1 Year
12dB Attenuator	Narda	4779-12	203	08/06/06	1 Year
Antenna - Biconical	EMCO	3110	9108-1421	05/17/06	1 Year
Antenna - Log Periodic	EMCO	3148	4947	05/11/06	1 Year
LISN (EUT)	FCC	FCC-LISN-50-25-2	9931	02/06/06	1 Year
LISN (Access)	Com-Power	LI-200	12019	07/05/07	1 Year
LISN (Access)	Com-Power	LI-200	12018	07/05/07	1 Year



AEGIS LABS INC.

6.0 SAMPLE CALCULATIONS

If a preamplifier is used during the Radiated Emissions Testing, it is required that the amplifier gain be subtracted from the Spectrum Analyzer (Meter) Reading. In addition, a correction factor for the antenna, cable and a distance factor, if any, must be applied to the Meter Reading before a true field strength reading can be obtained. In the Automatic Mode of A.R.M.S. measurements, these considerations are automatically presented as a part of the printout. In the case of manual measurements and for greater efficiency and convenience, usage of the calibration correction factors in the Appendices is necessary to calculate the Corrected Meter Reading. These correlation factors for each meter reading shall be modified to reflect these correlation factors at each frequency value so that the meter readings can be compared directly to the modified specification limit. This modified specification limit is referred to as the "Corrected Meter Reading Limit" (CML).

The equation shall be derived in the following manner:

$$\text{Corrected Meter Reading} = \text{Meter Reading} + F + C - G - D$$

Where, F = Antenna Factor

C = Cable Factor

G = Amplifier Gain

D = Distance Factor

Therefore, the equation for determining the Corrected Meter Reading Limit (CML) is:

$$\text{CML} = \text{Specification Limit} - F - C + G + D$$

For the manual mode of measurement, a table of corrected meter reading limits shall be used to permit immediate comparison of the meter reading to determine if the measured emission amplitude exceeded the specification limit at that specific frequency. There shall be two calculation sheets done, one for three meter and one for ten-meter measurement distances, where applicable. The correction factors for the antenna and the amplifier gain are attached in the Appendices.



AEGIS LABS INC.

6.0 Sample Calculations (Continued)

Peak Transmit Power Output:

A correction factor for the cable must be applied to the Conducted Power before a true power reading can be obtained. This is referred to as the “Corrected Power” (CP).

The equation shall be derived in the following manner:

Corrected Power Reading = Conducted Power Reading + C

Where, C = Cable Factor

The conducted power is taken in units of dBm. To obtain units of mW the following equation is used:

$$mW = 10^{(dBm/10)}$$



AEGIS LABS INC.

7.0 MODIFICATIONS AND RECOMMENDATIONS

No modifications were made to the EUT.

*Page 18 of 18
Report Number: INTEL-050912F
FCC ID: E2K5HCKT*



AEGIS LABS INC.

APPENDIX A

TEST DATA

*Page 1 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT*



AEGIS LABS INC.

AC POWER LINE CONDUCTED EMISSIONS TEST RESULTS

CLIENT:	Dell Computer Corporation	DATE:	09/20/05
EUT:	Inspiron 630m Notebook Computer	PROJECT NUMBER:	INTEL-050915
MODEL NUMBER:	PP19L	TEST ENGINEER:	JC
SERIAL NUMBER:	0454774	SITE #:	2
CONFIGURATION:	Tested with an Intel PRO/Wireless 2200BG Network Connection installed in its mini PCI slot and connected to a set of Wistron NeWeb Corp. antennas.	TEMPERATURE:	22 C
		HUMIDITY:	59% RH
		TIME:	3:00 PM

Standard:	FCC CFR 47, Part 15.207
Description:	AC Power Line Conducted Emissions
Results:	Passes the conducted limits by -0.68 @ 0.560 MHz

Conducted Limits		
Frequency (MHz)	Quasi-Peak Limit (dBuV)	Average Limit (dBuV)
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

NOTE: During preliminary scans, there wasn't any difference which channel or data rate was used with the EUT; therefore only Channel 1 at a data rate of 1 Mbps was used for final testing. Also, the scan was only done with the Wistron NeWeb Corp. set of antennas.


Page 2 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AC Power Line Conducted Emissions Test Results (Continued)

AEGIS LABS INC.

CONDUCTED EMISSIONS – LINE 1						
Freq. (MHz)	Meter Reading (dBuV)	Detector (PK/QP/AV)	Average Limit (dBuV)	Average Delta (dB)	Quasi-Peak Limit (dBuV)	Quasi-Peak Delta (dB)
0.1500	54.90	PK	56.00	-1.10	66.00	-11.10
0.1600	49.26	PK	55.71	-6.45	65.71	-16.45
0.1700	48.46	PK	55.43	-6.97	65.43	-16.97
0.4800	53.55	PK	46.57	6.98	56.57	-3.02
0.4800	45.20	AV	46.57	-1.37	56.57	-11.37
0.5600	49.15	PK	46.00	3.15	56.00	-6.85
0.5600	44.91	AV	46.00	-1.09	56.00	-11.09
0.6300	48.87	PK	46.00	2.87	56.00	-7.13
0.6300	37.84	AV	46.00	-8.16	56.00	-18.16



RBW = 100 kHz, VBW = 100 kHz

Page 3 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT




AC Power Line Conducted Emissions Test Results (Continued)

AEGIS LABS INC.

CONDUCTED EMISSIONS - LINE 2						
Freq. (MHz)	Meter Reading (dB _u V)	Detector (PK/QP/AV)	Average Limit (dB _u V)	Average Delta (dB)	Quasi-Peak Limit (dB _u V)	Quasi-Peak Delta (dB)
0.1700	50.97	PK	55.43	-4.46	65.43	-14.46
0.1900	48.59	PK	54.86	-6.27	64.86	-16.27
0.2200	48.82	PK	54.00	-5.18	64.00	-15.18
0.4800	54.03	PK	46.57	7.46	56.57	-2.54
0.4800	42.72	AV	46.57	-3.85	56.57	-13.85
0.5600	49.71	PK	46.00	3.71	56.00	-6.29
0.5600	45.32	AV	46.00	-0.68	56.00	-10.68
0.6400	49.12	PK	46.00	3.12	56.00	-6.88
0.6400	42.92	AV	46.00	-3.08	56.00	-13.08

14:12:18 SEP 20, 2005
14:52:53 APR 14, 2003 11:58:46 SEP 23, 2004

ACTV DET: PEAK
MEAS DET: PEAK QP AVG
MKR 480 kHz
54.03 dB_uV



RBW = 100 kHz, VBW = 100 kHz

Page 4 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

SPURIOUS RADIATED EMISSIONS TEST RESULTS

CLIENT:	Dell Computer Corporation	DATE:	09/20/05
EUT:	Inspiron 630m Notebook Computer	PROJECT NUMBER:	INTEL-050915
MODEL NUMBER:	PP19L	TEST ENGINEER:	JC
SERIAL NUMBER:	0454774	SITE #:	2
CONFIGURATION:	Tested with an Intel PRO/Wireless 2200BG Network Connection installed in its mini PCI slot and connected to a set of Wistron NeWeb Corp. antennas.	TEMPERATURE:	19 C
		HUMIDITY:	66% RH
		TIME:	7:20 AM

Standard:	FCC Pt. 15.209
Description:	Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in Sec. 15.209.
Results:	Passes the radiated limits by -4.90@ 36.14 MHz (Vertical antenna polarization)

Radiated Limits	
Frequency (MHz)	Quasi-Peak Limit (dBuV) @ 10m
30-88	40
88-216	43.5
216-960	46
960-1000	54

NOTE 1: During preliminary scans, there wasn't any difference which channel or data rate was used with the EUT; therefore only Channel 1 at a data rate of 1 Mbps was used for final testing. Also, the scan was only done with the Wistron NeWeb Corp. set of antennas.

NOTE 2: RBW/VBW = 1 MHz

Page 5 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Peak, Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	10 Meter Distance Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
38.93	4.86	400	225			0.98	15.92	10.46	32.22	40.00	-7.78
83.95	9.83	400	135			1.44	7.31	10.46	29.04	40.00	-10.96
110.23	9.41	400	225			1.70	11.83	10.46	33.40	43.50	-10.10
174.97	4.80	400	180			2.08	16.20	10.46	28.74	43.50	-14.76
249.99	10.59	375	225			2.80	17.50	10.46	30.76	46.00	-15.24
283.41	6.72	350	225			2.83	19.23	10.46	39.25	46.00	-6.75
300.01	9.18	300	315			2.90	13.50	10.46	36.04	46.00	-9.96
375.02	7.09	300	270			3.35	14.80	10.46	35.70	46.00	-10.30
386.05	6.69	275	225			3.42	14.84	10.46	35.41	46.00	-10.59
431.98	7.20	300	180			3.63	15.45	10.46	36.74	46.00	-9.26

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Peak, Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	10 Meter Distance Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
36.14	8.15	100	315			0.92	15.57	10.46	35.10	40.00	-4.90
110.20	9.52	100	225			1.70	10.63	10.46	32.31	43.50	-11.19
175.01	6.86	100	180			2.08	16.35	10.46	35.75	43.50	-7.75
228.03	5.90	100	315	6.06	Q	2.54	17.62	10.46	36.68	46.00	-9.32
250.01	7.42	100	270			2.80	18.50	10.46	31.76	46.00	-14.24
300.04	9.44	100	180			2.90	14.50	10.46	37.30	46.00	-8.70
353.87	6.57	100	135			3.22	15.25	10.46	35.51	46.00	-10.49
386.02	9.37	100	180			3.42	15.79	10.46	39.04	46.00	-6.96

NOTE: The measurements were taken at 10 meters and extrapolated to 3 meters.

NOTE 2: The measurements are Peak readings unless otherwise specified.

Page 6 of 72 (Appendix A)
 Report Number: INTEL-050912F
 FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

CLIENT:	Dell Computer Corporation	DATE:	09/13/05
EUT:	Inspiron 630m Notebook Computer	PROJECT NUMBER:	INTEL-050912
MODEL NUMBER:	PP19L	TEST ENGINEER:	JC/BM
SERIAL NUMBER:	0454774	SITE #:	2
CONFIGURATION:	Tested with an Intel PRO/Wireless 2915ABG Network Connection installed in its mini PCI slot and connected to a set of Wistron NeWeb Corp. antennas in 802.11a (5745-5825 MHz) mode.	TEMPERATURE:	20 C
		HUMIDITY:	52% RH
		TIME:	4:30 PM

Standard:	FCC CFR 47, Part 15.247(c)
Description:	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.
Results:	Passes (See Data Sheets)

Unwanted Spurious Emissions Limits			
Frequency (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m) (Emissions in the restricted bands)	Field Strength (dBm/MHz) (Emissions outside the restricted bands)
Above 960	500	54.00 (Average) 74.00 (Peak)	< -20 dBc

Page 7 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Fundamental Measurements in 802.11a mode (5745-5825 MHz)

Channels 149, 157, & 169

Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas

Aegis Labs, Inc. File #: INTEL-050912-06

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)		Note
5745.00	65.67	100	180				4.75	35.05	105.46	
5745.00				54.17	A		4.75	35.05	93.96	
5785.00	63.67	100	135				4.77	35.07	103.51	
5785.00				52.06	A		4.77	35.07	91.90	
5825.00	64.00	100	180				4.78	35.10	103.88	
5825.00				52.87	A		4.78	35.10	92.75	

RADIATED EMISSIONS – Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)		Note
5745.00	69.33	100	135				4.75	34.85	108.92	
5745.00				58.24	A		4.75	34.85	97.83	
5785.00	66.17	100	180				4.77	34.87	105.81	
5785.00				54.90	A		4.77	34.87	94.54	
5825.00	66.50	100	180				4.78	34.90	106.18	
5825.00				55.24	A		4.78	34.90	94.92	

Page 8 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Band Edge Field Strength Measurements in 802.11a mode (5745-5825 MHz)
Channels 149, 157, & 169
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050912-06

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note	
5725.00	35.17	100	180				4.74	35.04	74.94	85.46	-10.52	Ch. 149
5850.00	29.83	100	180				4.79	35.11	69.73	83.88	-14.14	Ch. 165

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note	
5725.00	36.00	100	135				4.74	34.84	75.57	88.92	-13.35	Ch. 149
5850.00	30.83	100	180				4.79	34.91	70.53	86.18	-15.64	Ch. 165



Page 9 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)

Test Date	Data	Test Eng.
09/13/05	5.745 GHz band edge PEAK (Horizontal Antenna Polarity) (INTEL-050912-06e05)	JC
	<p>*ATTEN 0dB RL 97.0dBμV 10dB/ MKR 35.17dBμV 5.72500GHz</p> 	
	<p>CENTER 5.74500GHz SPAN 50.00MHz *RBW 1.0MHz *VBW 1.0MHz SWP 50.0ms</p>	
Test Date	Data	Test Eng.
09/13/05	5.825 GHz band edge PEAK (Horizontal Antenna Polarity) (INTEL-050912-06e06)	JC
	<p>*ATTEN 0dB RL 97.0dBμV 10dB/ MKR 29.83dBμV 5.85000GHz</p> 	
	<p>CENTER 5.82500GHz SPAN 50.00MHz *RBW 1.0MHz *VBW 1.0MHz SWP 50.0ms</p>	



Page 10 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)

Test Date	Data	Test Eng.
09/13/05	5.745 GHz band edge PEAK (Vertical Antenna Polarity) (INTEL-050912-06e07)	JC
	<p>*ATTEN 0dB RL 97.0dBμV 10dB/ MKR 36.00dBμV 5.72500GHz</p>  <p>D</p> <p>CENTER 5.74500GHz SPAN 50.00MHz *RBW 1.0MHz *VBW 1.0MHz SWP 50.0ms</p>	
09/13/05	5.825 GHz band edge PEAK (Vertical Antenna Polarity) (INTEL-050912-06e08)	JC
	<p>*ATTEN 0dB RL 97.0dBμV 10dB/ MKR 30.83dBμV 5.85000GHz</p>  <p>D</p> <p>CENTER 5.82500GHz SPAN 50.00MHz *RBW 1.0MHz *VBW 1.0MHz SWP 50.0ms</p>	

Page 11 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11a mode (5745-5825 MHz)

Channels 149, 157, & 169

Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas

Aegis Labs, Inc. File #: INTEL-050912-08

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note
3830.00	56.67	100	180		46.75	3.84	32.46	46.22	74.00	-27.78	Ch. 149
3830.00				49.60	A	46.75	3.84	32.46	39.15	54.00	-14.85
7660.00	57.67	100	180		45.56	5.51	37.34	54.95	74.00	-19.05	
7660.00				53.32	A	45.56	5.51	37.34	50.60	54.00	-3.40
11490.00	50.33	100	135		44.97	6.87	39.49	51.72	74.00	-22.29	
11490.00				38.08	A	44.97	6.87	39.49	39.47	54.00	-14.54
15319.89	49.33	100	135		44.72	7.96	39.96	52.54	85.46	-32.92	
3856.66	56.67	100	180		46.74	3.86	32.53	46.31	74.00	-27.69	Ch. 157
3856.66				49.83	A	46.74	3.86	32.53	39.47	54.00	-14.53
7713.33	56.17	100	180		45.52	5.53	37.58	53.76	74.00	-20.24	
7713.33				50.56	A	45.52	5.53	37.58	48.15	54.00	-5.85
11569.98	50.67	100	135		44.97	6.89	39.53	52.12	74.00	-21.88	
11569.98				37.93	A	44.97	6.89	39.53	39.38	54.00	-14.62
15426.58	49.67	100	135		44.63	7.98	39.45	52.48	74.00	-21.52	
15426.58				37.46		44.63	7.98	39.45	40.27	54.00	-13.73
3883.34	58.83	100	180		46.73	3.87	32.60	48.56	74.00	-25.44	Ch. 165
3883.34				54.04	A	46.73	3.87	32.60	43.77	54.00	-10.23
7766.66	55.50	100	180		45.48	5.55	37.83	53.39	83.88	-30.49	
11650.00	50.67	100	135		44.96	6.92	39.56	52.18	74.00	-21.82	
11650.00				38.67	A	44.96	6.92	39.56	40.18	54.00	-13.82
15533.23	49.33	100	135		44.56	8.00	39.08	51.85	74.00	-22.15	
15533.23				37.71	A	44.56	8.00	39.08	40.23	54.00	-13.77

Page 12 of 72 (Appendix A)

Report Number: INTEL-050912F

FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note
3830.00	54.50	100	270		46.75	3.84	32.46	44.05	74.00	-29.95	Ch. 149
3830.00				46.45	A	46.75	3.84	32.46	36.00	54.00	-18.00
7660.00	58.33	100	135		45.56	5.51	37.37	55.64	74.00	-18.36	
7660.00				53.58	A	45.56	5.51	37.37	50.89	54.00	-3.11
11490.00	50.17	100	135		44.97	6.87	39.49	51.56	74.00	-22.44	
11490.00				38.17	A	44.97	6.87	39.49	39.56	54.00	-14.44
3856.66	54.50	125	90		46.74	3.86	32.53	44.14	74.00	-29.86	Ch. 157
3856.66				44.54	A	46.74	3.86	32.53	34.18	54.00	-19.82
7713.33	56.67	100	135		45.52	5.53	37.62	54.30	74.00	-19.70	
7713.33				51.81	A	45.52	5.53	37.62	49.44	54.00	-4.56
11569.98	50.33	100	135		44.97	6.89	39.54	51.80	74.00	-22.20	
11569.98				37.77	A	44.97	6.89	39.54	39.24	54.00	-14.76
3883.33	56.83	125	225		46.74	3.87	32.60	46.56	74.00	-27.44	Ch. 165
3883.33				50.15	A	46.74	3.87	32.60	39.88	54.00	-14.12
7766.66	57.00	100	180		45.48	5.55	37.88	54.94	86.18	-31.24	
11650.00	50.17	100	135		44.96	6.92	39.59	51.71	74.00	-22.29	
11650.00				38.40	A	44.96	6.92	39.59	39.94	54.00	-14.06

Page 13 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11a mode (5745-5825 MHz)

Channels 149, 157, & 169

Continuous RX at MAIN Antenna port with Wistron NeWeb Corp. Antennas

Aegis Labs, Inc. File #: INTEL-050912-08

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) + = FAIL	Note
3830.00	53.83	100	180		46.75	3.84	32.46	43.38	80.00	-36.62	Ch. 149
3830.00				44.34	A	46.75	3.84	32.46	33.89	60.00	-26.11
7660.00	51.33	100	135		45.56	5.51	37.34	48.61	80.00	-31.39	
7660.00				38.89	A	45.56	5.51	37.34	36.17	60.00	-23.83
11489.92	50.17	100	135		44.97	6.87	39.49	51.55	80.00	-28.45	
11489.92				37.37	A	44.97	6.87	39.49	38.75	60.00	-21.25
3856.62	54.00	100	45		46.74	3.86	32.53	43.64	80.00	-36.36	Ch. 157
3856.62				42.68	A	46.74	3.86	32.53	32.32	60.00	-27.68
7713.32	50.67	100	135		45.52	5.53	37.58	48.26	80.00	-31.74	
7713.32				38.44	A	45.52	5.53	37.58	36.03	60.00	-23.97
11569.92	49.33	100	135		44.97	6.89	39.53	50.78	80.00	-29.22	
11569.92				37.37	A	44.97	6.89	39.53	38.82	60.00	-21.18
3883.34	55.17	100	135		46.73	3.87	32.60	44.90	80.00	-35.10	Ch. 165
3883.34				47.21	A	46.73	3.87	32.60	36.94	60.00	-23.06
7766.62	52.33	100	90		45.48	5.55	37.83	50.22	80.00	-29.78	
7766.62				39.97	A	45.48	5.55	37.83	37.86	60.00	-22.14
11649.94	50.83	100	135		44.96	6.92	39.56	52.34	80.00	-27.66	
11649.94				37.82	A	44.96	6.92	39.56	39.33	60.00	-20.67

Page 14 of 72 (Appendix A)

Report Number: INTEL-050912F

FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note
3830.00	54.00	100	225		46.75	3.84	32.46	43.55	80.00	-36.45	Ch. 149
3830.00				45.40	A	46.75	3.84	32.46	34.95	60.00	-25.05
7660.00	51.67	100	225		45.56	5.51	37.37	48.98	80.00	-31.02	
7660.00				41.01	A	45.56	5.51	37.37	38.32	60.00	-21.68
11489.96	49.83	100	135		44.97	6.87	39.49	51.22	80.00	-28.78	
11489.96				37.46	A	44.97	6.87	39.49	38.85	60.00	-21.15
3856.65	52.50	100	225		46.74	3.86	32.53	42.14	80.00	-37.86	Ch. 157
3856.65				39.18	A	46.74	3.86	32.53	28.82	60.00	-31.18
7713.29	51.00	100	180		45.52	5.53	37.62	48.63	80.00	-31.37	
7713.29				40.63	A	45.52	5.53	37.62	38.26	60.00	-21.74
11569.91	50.33	100	135		44.97	6.89	39.54	51.80	80.00	-28.20	
11569.91				37.90	A	44.97	6.89	39.54	39.37	60.00	-20.63
3883.35	55.17	100	225		46.73	3.87	32.60	44.90	80.00	-35.10	Ch. 165
3883.35				46.47	A	46.73	3.87	32.60	36.20	60.00	-23.80
7766.63	50.50	100	225		45.48	5.55	37.88	48.44	80.00	-31.56	
7766.63				40.11	A	45.48	5.55	37.88	38.05	60.00	-21.95
11649.97	51.00	100	180		44.96	6.92	39.59	52.54	80.00	-27.46	
11649.97				38.56	A	44.96	6.92	39.59	40.10	60.00	-19.90

Page 15 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

CLIENT:	Dell Computer Corporation	DATE:	09/13/05
EUT:	Inspiron 630m Notebook Computer	PROJECT NUMBER:	INTEL-050912
MODEL NUMBER:	PP19L	TEST ENGINEER:	JC/BM
SERIAL NUMBER:	0454774	SITE #:	2
CONFIGURATION:	Tested with an Intel PRO/Wireless 2915ABG Network Connection installed in its mini PCI slot and connected to a set of Wistron NeWeb Corp. antennas in 802.11b (2412-2462 MHz) mode.	TEMPERATURE:	20 C
		HUMIDITY:	52% RH
		TIME:	4:30 PM

Standard:	FCC CFR 47, Part 15.247(c)
Description:	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.
Results:	Passes (See Data Sheets)

Unwanted Spurious Emissions Limits			
Frequency (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m) (Emissions in the restricted bands)	Field Strength (dBm/MHz) (Emissions outside the restricted bands)
Above 960	500	54.00 (Average) 74.00 (Peak)	< -20 dBc

Page 16 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Fundamental Measurements in 802.11b mode (2412-2462 MHz)

Channels 1, 6, & 11

Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas

Aegis Labs, Inc. File #: INTEL-050912-06

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)		Note
2412.00	71.33	100	135			3.02	29.22	103.58		Ch. 1
2412.00				63.21	A	3.02	29.22	95.46		
2437.00	73.33	100	135			3.04	29.27	105.64		Ch. 6
2437.00				64.79	A	3.04	29.27	97.10		
2462.00	71.50	100	135			3.06	29.32	103.88		Ch. 11
2462.00				63.28	A	3.06	29.32	95.66		

RADIATED EMISSIONS – Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)		Note
2412.00	74.00	125	135			3.02	29.42	106.45		Ch. 1
2412.00				65.13	A	3.02	29.42	97.58		
2437.00	76.00	125	135			3.04	29.47	108.51		Ch. 6
2437.00				68.08	A	3.04	29.47	100.59		
2462.00	73.83	100	180			3.06	29.52	106.41		Ch. 11
2462.00				65.03	A	3.06	29.52	97.61		

NOTE: Fundamental signals measured to calculate the band edge field strengths using the “Marker Delta Method”.

Page 17 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



Spurious Radiated Emissions Test Results (Continued)

AEGIS LABS INC.

Band Edge Field Strength Measurements in 802.11b mode (2412-2462 MHz)

Channels 1, 6, & 11

Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas

Aegis Labs, Inc. File #: INTEL-050912-06

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) + = FAIL	Note
2390.00								49.08	74.00	-24.92	Ch. 1
2390.00								33.96	54.00	-20.04	
2387.00								51.08	74.00	-22.92	
2387.00								35.96	54.00	-18.04	
2400.00	38.00	100	135			3.02	29.20	70.22	83.58	-13.36	
2483.50								52.21	74.00	-21.79	Ch. 11
2483.50								38.00	54.00	-16.00	
2487.00								55.21	74.00	-18.79	
2487.00								40.33	54.00	-13.67	

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) + = FAIL	Note
2390.00								51.95	74.00	-22.05	Ch. 1
2390.00								36.08	54.00	-17.92	
2387.00								53.95	74.00	-20.05	
2387.00								38.08	54.00	-15.92	
2400.00	39.33	125	135			3.02	29.40	71.75	86.45	-14.70	
2483.50								54.74	74.00	-19.26	Ch. 11
2483.50								39.95	54.00	-14.05	
2487.00								57.74	74.00	-16.26	
2487.00								42.28	54.00	-11.72	

NOTE: The "Band Edge Field Strength" was calculated using the "Fundamental" and "Conducted Band Edge" measurements per the "Marker-Delta Method" with the following formula:

$$BE = Fm - \Delta m$$

Where

BE = Band Edge Field Strength

Fm = Measured Fundamental (Peak or Average)

Δm = Measured Conducted Band Edge Delta (Peak or Average)

Page 18 of 72 (Appendix A)

Report Number: INTEL-050912F

FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)

Test Date	Data	Test Eng.
09/13/05	2.412 GHz band edge PEAK DELTA (INTEL-050912-02a01)	JC
	*ATTEN 30dB RL 20. 0dBm 10dB/ △MKR 52. 50dB 25. 8MHz	
	CENTER 2.3900GHz SPAN 100.0MHz *RBW 1.0MHz *VBW 1.0MHz SWP 50.0ms	
Test Date	Data	Test Eng.
09/13/05	2.412 GHz band edge AVERAGE DELTA (INTEL-050912-02a02)	JC
	*ATTEN 30dB RL 20. 0dBm 10dB/ △MKR 59. 50dB 23. 5MHz	
	CENTER 2.3900GHz SPAN 100.0MHz *RBW 1.0MHz *VBW 10Hz SWP 37.0sec	



Page 19 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)

Test Date	Data	Test Eng.
09/13/05	2.462 GHz band edge PEAK DELTA (INTEL-050912-02a03)	JC
	<p>*ATTEN 30dB RL 20. 0dBm 10dB/</p> <p>△MKR 48. 67dB -25. 5MHz</p>  <p>CENTER 2.4835GHz SPAN 100.0MHz *RBW 1.0MHz *VBW 1.0MHz SWP 50.0ms</p>	
09/13/05	2.462 GHz band edge AVERAGE DELTA (INTEL-050912-02a04)	JC
	<p>*ATTEN 30dB RL 20. 0dBm 10dB/</p> <p>△MKR 55. 33dB -25. 5MHz</p>  <p>CENTER 2.4835GHz SPAN 100.0MHz *RBW 1.0MHz *VBW 10Hz SWP 37.0sec</p>	

Page 20 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11b mode (2412-2462 MHz)

Channels 1, 6, & 11

Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas

Aegis Labs, Inc. File #: INTEL-050912-07

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	1 Meter Distance Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note
2312.00	31.50	100	135		9.54	1.97	29.02	52.95	74.00	-21.05	Ch. 1
2312.00				14.86	A	9.54	1.97	29.02	36.31	54.00	-17.69
2336.00	32.67	100	135		9.54	1.98	29.07	54.18	74.00	-19.82	Ch. 6
2336.00				21.54	A	9.54	1.98	29.07	43.05	54.00	-10.95
2358.66	32.33	100	135		9.54	1.99	29.12	53.90	74.00	-20.10	Ch. 11
2358.66				19.11	A	9.54	1.99	29.12	40.68	54.00	-13.32

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	1 Meter Distance Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note
2312.00	30.50	100	135		9.54	1.97	29.22	52.15	74.00	-21.85	Ch. 1
2312.00				13.17	A	9.54	1.97	29.22	34.82	54.00	-19.18
2336.00	32.33	100	180		9.54	1.98	29.27	54.04	74.00	-19.96	Ch. 6
2336.00				20.28	A	9.54	1.98	29.27	41.99	54.00	-12.01
2358.66	32.33	100	135		9.54	1.99	29.32	54.10	74.00	-19.90	Ch. 11
2358.66				15.94	A	9.54	1.99	29.32	37.71	54.00	-16.29

NOTE: These spurious emissions measurements were taken without a preamp at a distance on 1 meter to avoid saturating the preamp and analyzer because the signals were close to the fundamental frequency. The readings were extrapolated to 1 meter.

Page 21 of 72 (Appendix A)

Report Number: INTEL-050912F

FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11b mode (2412-2462 MHz)

Channels 1, 6, & 11

Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas

Aegis Labs, Inc. File #: INTEL-050912-08

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note
3216.01	51.67	100	135		46.82	3.51	30.98	39.34	83.58	-44.24	Ch. 1
4824.00	55.17	100	135		46.57	4.35	34.10	47.06	74.00	-26.94	
4824.00				46.15	A	46.57	4.35	34.10	38.04	54.00	-15.96
6431.97	55.67	100	135		46.54	5.03	35.37	49.53	83.58	-34.05	
9648.01	50.67	100	135		44.78	6.19	38.11	50.18	83.58	-33.40	
12864.03	50.17	100	135		45.23	7.21	40.27	52.43	83.58	-31.15	
3249.32	53.00	100	135		46.82	3.53	31.05	40.76	85.64	-44.88	Ch. 6
4873.99	53.67	100	180		46.57	4.37	34.27	45.74	74.00	-28.26	
4873.99				43.37	A	46.57	4.37	34.27	35.44	54.00	-18.56
6498.69	55.33	100	135		46.51	5.06	35.40	49.28	85.64	-36.36	
9747.96	50.50	100	135		44.80	6.23	38.25	50.17	85.64	-35.47	
12997.37	53.67	100	135		45.32	7.25	40.59	56.19	85.64	-29.45	
3282.67	54.33	100	135		46.82	3.55	31.12	42.17	83.88	-41.71	Ch. 11
4924.00	52.83	100	180		46.58	4.40	34.44	45.09	74.00	-28.91	
4924.00				41.62	A	46.58	4.40	34.44	33.88	54.00	-20.12
6565.34	54.67	100	315		46.47	5.08	35.62	48.91	83.88	-34.97	
9848.01	51.00	100	135		44.83	6.27	38.39	50.83	83.88	-33.05	
13130.67	49.83	100	135		45.37	7.32	40.65	52.43	83.88	-31.45	

Page 22 of 72 (Appendix A)

Report Number: INTEL-050912F

FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note
3216.00	52.83	100	315		46.82	3.51	31.09	40.61	86.45	-45.84	Ch. 1
4823.96	56.50	100	135		46.57	4.35	34.07	48.36	74.00	-25.64	
4823.96				49.29	A	46.57	4.35	34.07	41.15	54.00	-12.85
6431.95	56.50	100	135		46.54	5.03	35.35	50.34	86.45	-36.11	
9647.97	49.83	100	135		44.78	6.19	38.17	49.40	86.45	-37.05	
12864.01	50.50	100	135		45.23	7.21	40.27	52.76	86.45	-33.69	
3249.32	53.50	100	135		46.82	3.53	31.15	41.36	88.51	-47.15	Ch. 6
4874.01	54.00	100	135		46.57	4.37	34.22	46.02	74.00	-27.98	
4874.01				41.67	A	46.57	4.37	34.22	33.69	54.00	-20.31
6498.66	58.00	100	180		46.51	5.06	35.40	51.95	88.51	-36.56	
9748.04	50.17	135	180		44.80	6.23	38.35	49.94	88.51	-38.57	
12997.35	49.67	100	135		45.32	7.25	40.59	52.19	88.51	-36.32	
3282.66	56.33	100	315		46.82	3.55	31.21	44.26	86.41	-42.15	Ch. 11
4924.00	53.33	100	0		46.58	4.40	34.37	45.52	74.00	-28.48	
4924.00				40.92	A	46.58	4.40	34.37	33.11	54.00	-20.89
6565.32	57.33	100	225		46.47	5.08	35.60	51.54	86.41	-34.87	
9847.96	50.00	100	135		44.83	6.27	38.53	49.97	86.41	-36.44	
13130.63	49.17	100	135		45.37	7.32	40.68	51.79	86.41	-34.62	

Page 23 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11b mode (2412-2462 MHz)

Channels 1, 6, & 11

Continuous RX at MAIN Antenna port with Wistron NeWeb Corp. Antennas

Aegis Labs, Inc. File #: INTEL-050912-08

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB)	Note
											+=FAIL
3216.02	55.83	100	135		46.82	3.51	30.98	43.50	80.00	-36.50	Ch. 1
3216.02				43.10	A	46.82	3.51	30.98	30.77	60.00	-29.23
6432.00	56.00	100	135		46.54	5.03	35.37	49.86	80.00	-30.14	
6432.00				47.32	A	46.54	5.03	35.37	41.18	60.00	-18.82
9648.03	50.50	100	135		44.78	6.19	38.11	50.01	80.00	-29.99	
9648.03				38.20	A	44.78	6.19	38.11	37.71	60.00	-22.29
3249.32	52.50	100	135		46.82	3.53	31.05	40.26	80.00	-39.74	Ch. 6
3249.32				40.83	A	46.82	3.53	31.05	28.59	60.00	-31.41
6498.70	54.67	100	270		46.51	5.06	35.40	48.62	80.00	-31.38	
6498.70				47.19	A	46.51	5.06	35.40	41.14	60.00	-18.86
9747.99	49.00	100	135		44.80	6.23	38.25	48.67	80.00	-31.33	
9747.99				36.03	A	44.80	6.23	38.25	35.70	60.00	-24.30
3282.66	53.00	100	135		46.82	3.55	31.12	40.84	80.00	-39.16	Ch. 11
3282.66				40.68	A	46.82	3.55	31.12	28.52	60.00	-31.48
6565.32	54.83	100	180		46.47	5.08	35.62	49.07	80.00	-30.93	
6565.32				46.69	A	46.47	5.08	35.62	40.93	60.00	-19.07
9848.01	49.50	100	135		44.83	6.27	38.39	49.33	80.00	-30.67	
9848.01				36.31	A	44.83	6.27	38.39	36.14	60.00	-23.86

Page 24 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note
3216.00	52.67	100	135		46.82	3.51	31.09	40.45	80.00	-39.55	Ch. 1
3216.00				41.54	A	46.82	3.51	31.09	29.32	60.00	-30.68
6432.03	55.17	100	225		46.54	5.03	35.35	49.01	80.00	-30.99	
6432.03				46.10	A	46.54	5.03	35.35	39.94	60.00	-20.06
9648.02	50.00	100	135		44.78	6.19	38.17	49.57	80.00	-30.43	
9648.02				38.00	A	44.78	6.19	38.17	37.57	60.00	-22.43
3249.32	53.00	100	135		46.82	3.53	31.15	40.86	80.00	-39.14	Ch. 6
3249.32				41.86	A	46.82	3.53	31.15	29.72	60.00	-30.28
6498.67	56.50	100	180		46.51	5.06	35.40	50.45	80.00	-29.55	
6498.67				50.80	A	46.51	5.06	35.40	44.75	60.00	-15.25
9747.96	48.67	100	135		44.80	6.23	38.35	48.44	80.00	-31.56	
9747.96				36.78	A	44.80	6.23	38.35	36.55	60.00	-23.45
3282.67	53.83	100	45		46.82	3.55	31.21	41.76	80.00	-38.24	Ch. 11
3282.67				42.73	A	46.82	3.55	31.21	30.66	60.00	-29.34
6565.37	56.83	100	180		46.47	5.08	35.60	51.04	80.00	-28.96	
6565.37				50.50	A	46.47	5.08	35.60	44.71	60.00	-15.29
9847.98	49.50	100	135		44.83	6.27	38.53	49.47	80.00	-30.53	
9847.98				37.10	A	44.83	6.27	38.53	37.07	60.00	-22.93

Page 25 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

CLIENT:	Dell Computer Corporation	DATE:	09/13/05
EUT:	Inspiron 630m Notebook Computer	PROJECT NUMBER:	INTEL-050912
MODEL NUMBER:	PP19L	TEST ENGINEER:	JC/BM
SERIAL NUMBER:	0454774	SITE #:	2
CONFIGURATION:	Tested with an Intel PRO/Wireless 2915ABG Network Connection installed in its mini PCI slot and connected to a set of Wistron NeWeb Corp. antennas in 802.11g (2412-2462 MHz) mode.	TEMPERATURE:	20 C
		HUMIDITY:	52% RH
		TIME:	4:30 PM

Standard:	FCC CFR 47, Part 15.247(c)
Description:	Radiated emissions, which fall in the restricted bands, as defined in Sec. 15.205(a), must also comply with the radiated emission limits specified in Sec. 15.209(a). All others must be < -20dBc.
Results:	Passes (See Data Sheets)

Unwanted Spurious Emissions Limits			
Frequency (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m) (Emissions in the restricted bands)	Field Strength (dBm/MHz) (Emissions outside the restricted bands)
Above 960	500	54.00 (Average) 74.00 (Peak)	< -20 dBc

Page 26 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Fundamental Measurements in 802.11g mode (2412-2462 MHz)

Channels 1, 6, & 11

Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas

Aegis Labs, Inc. File #: INTEL-050912-06

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)		Note
2412.00	74.67	100	135			3.02	29.22	106.92		Ch. 1
2412.00				63.78	A	3.02	29.22	96.03		
2437.00	74.50	100	135			3.04	29.27	106.81		Ch. 6
2437.00				62.99	A	3.04	29.27	95.30		
2462.00	74.17	175	135			3.06	29.32	106.55		Ch. 11
2462.00				63.61	A	3.06	29.32	95.99		

RADIATED EMISSIONS – Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)		Note
2412.00	77.00	100	135			3.02	29.42	109.45		Ch. 1
2412.00				65.31	A	3.02	29.42	97.76		
2437.00	77.17	125	135			3.04	29.47	109.68		Ch. 6
2437.00				65.36	A	3.04	29.47	97.87		
2462.00	74.83	100	135			3.06	29.52	107.41		Ch. 11
2462.00				64.13	A	3.06	29.52	96.71		

NOTE: Fundamental signals measured to calculate the band edge field strengths using the “Marker Delta Method”.

Page 27 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Band Edge Field Strength Measurements in 802.11g mode (2412-2462 MHz)
Channels 1, 6, & 11
Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas
Aegis Labs, Inc. File #: INTEL-050912-06

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note
2390.00								64.09	74.00	-9.91	Ch. 1
2390.00								50.19	54.00	-3.81	
2400.00	49.50	100	135			3.02	29.20	81.72	86.92	-5.20	
2483.50								66.05	74.00	-7.95	Ch. 11
2483.50								47.99	54.00	-6.01	

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note
2390.00								66.62	74.00	-7.38	Ch. 1
2390.00								51.92	54.00	-2.08	
2400.00	51.83	100	135			3.02	29.40	84.25	89.45	-5.20	
2483.50								66.91	74.00	-7.09	Ch. 11
2483.50								48.71	54.00	-5.29	

NOTE: The “Band Edge Field Strength” was calculated using the “Fundamental” and “Conducted Band Edge” measurements per the “Marker-Delta Method” with the following formula:

$$BE = Fm - \Delta m$$

Where

BE = Band Edge Field Strength

Fm = Measured Fundamental (Peak or Average)

Δm = Measured Conducted Band Edge Delta (Peak or Average)

Page 28 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)

Test Date	Data	Test Eng.
09/13/05	2.412 GHz band edge PEAK DELTA (INTEL-050912-03a01)	JC
	*ATTEN 30dB RL 20. 0dBm 10dB/ △MKR 42. 83dB 16. 8MHz	
	CENTER 2.3900GHz *RBW 1.0MHz *VBW 1.0MHz SPAN 100.0MHz SWP 50.0ms	
Test Date	Data	Test Eng.
09/13/05	2.412 GHz band edge AVERAGE DELTA (INTEL-050912-03a02)	JC
	*ATTEN 30dB RL 20. 0dBm 10dB/ △MKR 45. 84dB 20. 7MHz	
	CENTER 2.3900GHz *RBW 1.0MHz *VBW 10Hz SPAN 100.0MHz SWP 37.0sec	



Page 29 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)

Test Date	Data	Test Eng.
09/13/05	2.462 GHz band edge PEAK DELTA (INTEL-050912-03a03)	JC
	<p>*ATTEN 30dB RL 20. 0dBm 10dB/</p> <p>△MKR 40. 50dB -26. 3MHz</p>  <p>CENTER 2.4835GHz SPAN 100.0MHz *RBW 1.0MHz *VBW 1.0MHz SWP 50.0ms</p>	
09/13/05	2.462 GHz band edge AVERAGE DELTA (INTEL-050912-03a04)	JC
	<p>*ATTEN 30dB RL 20. 0dBm 10dB/</p> <p>△MKR 48. 00dB -22. 8MHz</p>  <p>CENTER 2.4835GHz SPAN 100.0MHz *RBW 1.0MHz *VBW 10Hz SWP 37.0sec</p>	

Page 30 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11g mode (2412-2462 MHz)

Channels 1, 6, & 11

Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas

Aegis Labs, Inc. File #: INTEL-050912-07

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	1 Meter Distance Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note
2312.00	31.50	100	135		9.54	1.97	29.02	52.95	74.00	-21.05	Ch. 1
2312.00				18.59	A	9.54	1.97	29.02	40.04	54.00	-13.96
2336.00	32.50	100	180		9.54	1.98	29.07	54.01	74.00	-19.99	Ch. 6
2336.00				20.86	A	9.54	1.98	29.07	42.37	54.00	-11.63
2358.66	31.83	100	135		9.54	1.99	29.12	53.40	74.00	-20.60	Ch. 11
2358.66				18.48	A	9.54	1.99	29.12	40.05	54.00	-13.95

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	1 Meter Distance Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note
2312.00	31.33	100	135		9.54	1.97	29.22	52.98	74.00	-21.02	Ch. 1
2312.00				16.44	A	9.54	1.97	29.22	38.09	54.00	-15.91
2336.00	32.50	100	135		9.54	1.98	29.27	54.21	74.00	-19.79	Ch. 6
2336.00				20.95	A	9.54	1.98	29.27	42.66	54.00	-11.34
2358.66	32.00	100	135		9.54	1.99	29.32	53.77	74.00	-20.23	Ch. 11
2358.66				18.48	A	9.54	1.99	29.32	40.25	54.00	-13.75

NOTE: These spurious emissions measurements were taken without a preamp at a distance on 1 meter to avoid saturating the preamp and analyzer because the signals were close to the fundamental frequency. The readings were extrapolated to 1 meter.

Page 31 of 72 (Appendix A)

Report Number: INTEL-050912F

FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11g mode (2412-2462 MHz)

Channels 1, 6, & 11

Continuous TX at MAIN Antenna port with Wistron NeWeb Corp. Antennas

Aegis Labs, Inc. File #: INTEL-050912-08

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note
3216.00	54.00	100	225		46.82	3.51	30.98	41.67	86.92	-45.25	Ch. 1
4824.20	59.83	100	135		46.57	4.35	34.10	51.72	74.00	-22.28	
4824.20				45.69	A	46.57	4.35	34.10	37.58	54.00	-16.42
6432.05	56.67	100	180		46.54	5.03	35.37	50.53	86.92	-36.39	
9647.97	51.00	100	135		44.78	6.19	38.11	50.51	86.92	-36.41	
12864.05	51.00	100	135		45.23	7.21	40.27	53.26	86.92	-33.66	
3249.37	54.00	100	135		46.82	3.53	31.05	41.76	86.81	-45.05	Ch. 6
4874.06	52.67	100	135		46.57	4.37	34.27	44.74	74.00	-29.26	
4874.06				39.90	A	46.57	4.37	34.27	31.97	54.00	-22.03
6498.69	56.67	150	180		46.51	5.06	35.40	50.62	86.81	-36.19	
9748.09	49.50	100	135		44.80	6.23	38.25	49.17	86.81	-37.64	
12997.35	49.83	100	135		45.32	7.25	40.59	52.35	86.81	-34.46	
3282.68	53.00	100	135		46.82	3.55	31.12	40.84	86.55	-45.71	Ch. 11
4923.82	52.50	100	135		46.58	4.40	34.44	44.76	74.00	-29.24	
4923.82				39.53	A	46.58	4.40	34.44	31.79	54.00	-22.21
6565.42	54.17	100	135		46.47	5.08	35.62	48.41	86.55	-38.14	
9847.97	53.17	100	135		44.83	6.27	38.39	53.00	86.55	-33.55	
13130.70	50.33	100	135		45.37	7.32	40.65	52.93	86.55	-33.62	

Page 32 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note
3216.01	52.83	100	315		46.82	3.51	31.09	40.61	89.45	-48.84	Ch. 1
4823.97	57.50	100	135		46.57	4.35	34.07	49.36	74.00	-24.64	
4823.97				44.50	A	46.57	4.35	34.07	36.36	54.00	-17.64
6431.99	57.83	100	135		46.54	5.03	35.35	51.67	89.45	-37.78	
9648.08	50.33	100	135		44.78	6.19	38.17	49.90	89.45	-39.55	
12863.98	50.83	100	135		45.23	7.21	40.27	53.09	89.45	-36.36	
3249.35	55.17	100	315		46.82	3.53	31.15	43.03	89.68	-46.65	Ch. 6
4874.03	52.17	100	135		46.57	4.37	34.22	44.19	74.00	-29.81	
4874.03				34.00	A	46.57	4.37	34.22	26.02	54.00	-27.98
6498.67	58.50	100	180		46.51	5.06	35.40	52.45	89.68	-37.23	
9748.00	50.50	100	135		44.80	6.23	38.35	50.27	89.68	-39.41	
12997.35	50.50	100	135		45.32	7.25	40.59	53.02	89.68	-36.66	
3282.65	55.33	100	315		46.82	3.55	31.21	43.26	87.41	-44.15	Ch. 11
4924.01	52.17	100	135		46.58	4.40	34.37	44.36	74.00	-29.64	
4924.01				39.39	A	46.58	4.40	34.37	31.58	54.00	-22.42
6565.34	56.00	100	225		46.47	5.08	35.60	50.21	87.41	-37.20	
9848.03	50.83	100	135		44.83	6.27	38.53	50.80	87.41	-36.61	
13130.62	49.67	100	135		45.37	7.32	40.68	52.29	87.41	-35.12	

Page 33 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11g mode (2412-2462 MHz)

Channels 1, 6, & 11

Continuous RX at MAIN Antenna port with Wistron NeWeb Corp. Antennas

Aegis Labs, Inc. File #: INTEL-050912-08

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note
3215.99	53.00	100	135		46.82	3.51	30.98	40.67	80.00	-39.33	Ch. 1
3215.99				40.38	A	46.82	3.51	30.98	28.05	60.00	-31.95
6431.98	54.17	100	135		46.54	5.03	35.37	48.03	80.00	-31.97	
6431.98				45.01	A	46.54	5.03	35.37	38.87	60.00	-21.13
9648.00	49.00	100	135		44.78	6.19	38.11	48.51	80.00	-31.49	
9648.00				37.19	A	44.78	6.19	38.11	36.70	60.00	-23.30
3249.32	52.83	100	135		46.82	3.53	31.05	40.59	80.00	-39.41	Ch. 6
3249.32				41.12	A	46.82	3.53	31.05	28.88	60.00	-31.12
6498.67	55.00	100	270		46.51	5.06	35.40	48.95	80.00	-31.05	
6498.67				46.73	A	46.51	5.06	35.40	40.68	60.00	-19.32
9748.03	49.67	100	135		44.80	6.23	38.25	49.34	80.00	-30.66	
9748.03				36.92	A	44.80	6.23	38.25	36.59	60.00	-23.41
3282.66	53.17	100	135		46.82	3.55	31.12	41.01	80.00	-38.99	Ch. 11
3282.66				40.89	A	46.82	3.55	31.12	28.73	60.00	-31.27
6565.32	54.33	100	180		46.47	5.08	35.62	48.57	80.00	-31.43	
6565.32				45.69	A	46.47	5.08	35.62	39.93	60.00	-20.07
9848.03	49.17	100	135		44.83	6.27	38.39	49.00	80.00	-31.00	
9848.03				37.28	A	44.83	6.27	38.39	37.11	60.00	-22.89

Page 34 of 72 (Appendix A)

Report Number: INTEL-050912F

FCC ID: E2K5HCKT



AEGIS LABS INC.

Spurious Radiated Emissions Test Results (Continued)

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL	Note
3216.00	52.17	100	135		46.82	3.51	31.09	39.95	80.00	-40.05	Ch. 1
3216.00				41.01	A	46.82	3.51	31.09	28.79	60.00	-31.21
6432.00	57.17	100	180		46.54	5.03	35.35	51.01	80.00	-28.99	
6432.00				50.92	A	46.54	5.03	35.35	44.76	60.00	-15.24
9648.00	49.33	100	135		44.78	6.19	38.17	48.90	80.00	-31.10	
9648.00				37.24	A	44.78	6.19	38.17	36.81	60.00	-23.19
3249.33	53.00	100	135		46.82	3.53	31.15	40.86	80.00	-39.14	Ch. 6
3249.33				41.67	A	46.82	3.53	31.15	29.53	60.00	-30.47
6498.69	57.00	100	180		46.51	5.06	35.40	50.95	80.00	-29.05	
6498.69				50.86	A	46.51	5.06	35.40	44.81	60.00	-15.19
9748.03	49.67	100	135		44.80	6.23	38.35	49.44	80.00	-30.56	
9748.03				36.13	A	44.80	6.23	38.35	35.90	60.00	-24.10
3282.67	53.00	100	135		46.82	3.55	31.21	40.93	80.00	-39.07	Ch. 11
3282.67				41.67	A	46.82	3.55	31.21	29.60	60.00	-30.40
6565.34	55.67	125	180		46.47	5.08	35.60	49.88	80.00	-30.12	
6565.34				49.77	A	46.47	5.08	35.60	43.98	60.00	-16.02
9848.04	49.83	100	135		44.83	6.27	38.53	49.80	80.00	-30.20	
9848.04				37.24	A	44.83	6.27	38.53	37.21	60.00	-22.79

Page 35 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

PEAK TRANSMIT POWER

CLIENT:	Dell Computer Corporation	DATE:	09/13/05
EUT:	Inspiron 630m Notebook Computer	PROJECT NUMBER:	INTEL-050912
MODEL NUMBER:	PP19L	TEST ENGINEER:	JC
SERIAL NUMBER:	0454774	SITE #:	2
CONFIGURATION:	Tested with an Intel PRO/Wireless 2915ABG Network Connection installed in its mini PCI slot.	TEMPERATURE:	18 C
		HUMIDITY:	56% RH
		TIME:	10:00 AM

Standard:	FCC CFR 47, Part 15.247(b)(1)
Description:	The maximum peak output power of the intentional radiator shall not exceed 1 watt.
Results:	See Data Sheet

Peak Transmit Power Limits

Frequency (MHz)	Output Power (W)
5725-5850	1
2412-2462	1

Page 36 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Peak Transmit Power (Continued)

Mode	Channel	Frequency (MHz)	Rate (Mbps)	Average Power (dBm)	Average Power (mW)	Peak Power (dBm)	Peak Power (mW)
802.11a	149	5745	6	15.61	36.39	21.20	131.83
802.11a	157	5785	6	15.02	31.77	20.80	120.23
802.11a	165	5825	6	14.91	30.97	20.60	114.82
802.11b	1	2412	1	15.25	33.50	17.13	51.64
802.11b	6	2437	1	17.18	52.24	19.21	83.37
802.11b	11	2462	1	17.08	51.05	19.18	82.79
802.11g	1	2412	6	15.63	36.56	24.12	258.23
802.11g	6	2437	6	15.56	35.97	23.96	248.89
802.11g	11	2462	6	15.52	35.65	23.87	243.78

NOTE: The output power measurement is conducted.

Page 37 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

6 dB EMISSIONS BANDWIDTH

CLIENT:	Dell Computer Corporation	DATE:	09/13/05
EUT:	Inspiron 630m Notebook Computer	PROJECT NUMBER:	INTEL-050912
MODEL NUMBER:	PP19L	TEST ENGINEER:	JC
SERIAL NUMBER:	0454774	SITE #:	2
CONFIGURATION:	Tested with an Intel PRO/Wireless 2915ABG Network Connection installed in its mini PCI slot.	TEMPERATURE:	21 C
		HUMIDITY:	47% RH
		TIME:	11:05 AM

Standard:	FCC CFR 47, Part 15.247(a)(2)
Description:	The minimum 6dB bandwidth shall be at least 500 kHz.
Results:	See Data Sheets



Page 38 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

6 dB Emissions Bandwidth (Continued)

802.11a Mode

Test Date	Data	Test Eng.
09/14/05	5.745 GHz (INTEL-050912-05a1)	JC
	*ATTEN 30dB RL 20. 0dBm 10dB/ ΔMKR -.33dB 16. 42MHz	
		
	CENTER 5.74500GHz SPAN 50.00MHz *RBW 100kHz *VBW 300kHz SWP 50.0ms	
Test Date	Data	Test Eng.
09/14/05	5.785 GHz (INTEL-050912-05a2)	JC
	*ATTEN 30dB RL 20. 0dBm 10dB/ ΔMKR 1.17dB 16. 50MHz	
		
	CENTER 5.78500GHz SPAN 50.00MHz *RBW 100kHz *VBW 300kHz SWP 50.0ms	


Page 39 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



6 dB Emissions Bandwidth (Continued)

AEGIS LABS INC.

802.11a Mode



Page 40 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

6 dB Emissions Bandwidth (Continued)

802.11b Mode

Test Date	Data	Test Eng.
09/13/05	2.412 GHz (INTEL-050912-02b1)	JC
 *ATTEN 30dB RL 20. 0dBm	10dB/ △MKR .17dB 10. 00MHz	

D

CENTER 2.41200GHz SPAN 50.00MHz

*RBW 100kHz *VBW 300kHz SWP 50.0ms

Test Date	Data	Test Eng.
09/13/05	2.437 GHz (INTEL-050912-02b2)	JC
 *ATTEN 30dB RL 20. 0dBm	10dB/ △MKR 0dB 10. 00MHz	

D

CENTER 2.43700GHz SPAN 50.00MHz

*RBW 100kHz *VBW 300kHz SWP 50.0ms


Page 41 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



6 dB Emissions Bandwidth (Continued)

AEGIS LABS INC.

802.11b Mode





Page 42 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

6 dB Emissions Bandwidth (Continued)

802.11g Mode

Test Date	Data	Test Eng.
09/13/05	2.412 GHz (INTEL-050912-03b1)	JC
<p>*ATTEN 20dB RL 10. 0dBm 10dB/ ΔMKR 0dB 16. 50MHz</p>  <p>D</p> <p>CENTER 2.41200GHz SPAN 50.00MHz *RBW 100kHz *VBW 300kHz SWP 50.0ms</p>		
Test Date	Data	Test Eng.
09/13/05	2.437 GHz (INTEL-050912-03b2)	JC
<p>*ATTEN 20dB RL 10. 0dBm 10dB/ ΔMKR -.50dB 16. 58MHz</p>  <p>D</p> <p>CENTER 2.43700GHz SPAN 50.00MHz *RBW 100kHz *VBW 300kHz SWP 50.0ms</p>		


Page 43 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

6 dB Emissions Bandwidth (Continued)

802.11g Mode



Page 44 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

PEAK POWER SPECTRAL DENSITY

CLIENT:	Dell Computer Corporation	DATE:	09/13/05
EUT:	Inspiron 630m Notebook Computer	PROJECT NUMBER:	INTEL-050912
MODEL NUMBER:	PP19L	TEST ENGINEER:	JC
SERIAL NUMBER:	0454774	SITE #:	2
CONFIGURATION:	Tested with an Intel PRO/Wireless 2915ABG Network Connection installed in its mini PCI slot.	TEMPERATURE:	21 C
		HUMIDITY:	47% RH
		TIME:	11:05 AM

Standard:	FCC CFR 47, Part 15.247(d)
Description:	The peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
Results:	See Data Sheets

Peak Power Spectral Density Limits

Frequency (MHz)	Limit (dBm)
5725-5850	8
2412-2462	8

Page 45 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Peak Power Spectral Density (Continued)

802.11a Mode

Test Date	Data	Test Eng.
09/14/05	5.745 GHz (INTEL-050912-05c1)	JC
<p>*ATTEN 20dB RL 10. 0dBm 10dB/</p> <p>MKR -13. 17dBm 5.745303GHz</p> <p>CENTER 5.745000GHz SPAN 1.500MHz *RBW 3.0kHz *VBW 3.0kHz *SWP 500sec</p>		

Test Date	Data	Test Eng.
09/14/05	5.785 GHz (INTEL-050912-05c2)	JC
<p>*ATTEN 20dB RL 10. 0dBm 10dB/</p> <p>MKR -11. 67dBm 5.785300GHz</p> <p>CENTER 5.785000GHz SPAN 1.500MHz *RBW 3.0kHz *VBW 3.0kHz *SWP 500sec</p>		


Page 46 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



Peak Power Spectral Density (Continued)

AEGIS LABS INC.

802.11a Mode





Page 47 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Peak Power Spectral Density (Continued)

802.11b Mode

Test Date	Data	Test Eng.
09/13/05	2.412 GHz (INTEL-050912-02d1)	JC
	*ATTEN 20dB RL 10.0dBm 10dB/ MKR -9.00dBm 2.411315GHz	
		
	CENTER 2.412000GHz SPAN 1.500MHz *RBW 3.0kHz *VBW 3.0kHz *SWP 500sec	
Test Date	Data	Test Eng.
09/13/05	2.437 GHz (INTEL-050912-02d2)	JC
	*ATTEN 20dB RL 10.0dBm 10dB/ MKR -7.00dBm 2.436315GHz	
		
	CENTER 2.437000GHz SPAN 1.500MHz *RBW 3.0kHz *VBW 3.0kHz *SWP 500sec	


Page 48 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



Peak Power Spectral Density (Continued)

AEGIS LABS INC.

802.11b Mode



Page 49 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



Peak Power Spectral Density (Continued)

AEGIS LABS INC.

802.11g Mode

Test Date	Data	Test Eng.
09/13/05	2.412 GHz (INTEL-050912-03d1)	JC
	<p>*ATTEN 20dB RL 10. 0dBm 10dB/</p> <p>MKR -11. 50dBm 2.412313GHz</p> <p>CENTER 2.412000GHz SPAN 1.500MHz *RBW 3.0kHz *VBW 3.0kHz *SWP 500sec</p>	


Page 50 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Peak Power Spectral Density (Continued)

802.11g Mode



Page 51 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

CONDUCTED OUT OF BAND EMISSIONS

CLIENT:	Dell Computer Corporation	DATE:	09/13/05
EUT:	Inspiron 630m Notebook Computer	PROJECT NUMBER:	INTEL-050912
MODEL NUMBER:	PP19L	TEST ENGINEER:	JC
SERIAL NUMBER:	0454774	SITE #:	2
CONFIGURATION:	Tested with an Intel PRO/Wireless 2915ABG Network Connection installed in its mini PCI slot.	TEMPERATURE:	21 C
		HUMIDITY:	47% RH
		TIME:	11:05 AM

Standard:	FCC CFR 47, Part 15.247(c)
Description:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.


Page 52 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT




AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11a Mode

Test Date	Data	Test Eng.
09/14/05	5.745 GHz (INTEL-050912-05d01)	JC
	<p>*ATTEN 20dB RL 10.0dBm 10dB/</p> <p>MKR -65.00dBm 691.2MHz</p>  <p>START 30.0MHz STOP 1.0000GHz *RBW 100kHz *VBW 300kHz SWP 540ms</p>	

Test Date	Data	Test Eng.
09/14/05	5.745 GHz (INTEL-050912-05d02)	JC
	<p>*ATTEN 20dB RL 10.0dBm 10dB/</p> <p>MKR -54.83dBm 3.827GHz</p>  <p>START 1.000GHz STOP 5.000GHz *RBW 100kHz *VBW 300kHz SWP 2.20sec</p>	



Page 53 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11a Mode

Test Date	Data	Test Eng.
09/14/05	5.745 GHz (INTEL-050912-05d03)	JC
*ATTEN 20dB RL 10. 0d Bm	MKR -42. 17d Bm 5. 500GHz	
		
	START 5. 000GHz *RBW 100kHz	STOP 10. 000GHz *VBW 300kHz
		SWP 2.80sec
Test Date	Data	Test Eng.
09/14/05	5.745 GHz (INTEL-050912-05d04)	JC
*ATTEN 20dB RL 10. 0d Bm	MKR -59. 50d Bm 14. 17GHz	
		
	START 10. 00GHz *RBW 100kHz	STOP 20. 00GHz *VBW 300kHz
		SWP 5.50sec


Page 54 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT




AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11a Mode

Test Date	Data	Test Eng.
09/14/05	5.745 GHz (INTEL-050912-05d05)	JC
<p>*ATTEN 20dB RL 10. 0dBm 10dB/</p> <p>MKR -52. 17dBm 36. 57GHz</p>  <p>D</p> <p>START 20. 00GHz STOP 40. 00GHz *RBW 100kHz *VBW 300kHz SWP 11. 0sec</p>		

Test Date	Data	Test Eng.
09/14/05	5.785 GHz (INTEL-050912-05d06)	JC
<p>*ATTEN 20dB RL 10. 0dBm 10dB/</p> <p>MKR -65. 00dBm 618. 5MHz</p>  <p>D</p> <p>START 30. 0MHz STOP 1. 0000GHz *RBW 100kHz *VBW 300kHz SWP 540ms</p>		

Page 55 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11a Mode

Test Date	Data	Test Eng.
09/14/05	5.785 GHz (INTEL-050912-05d07)	JC
<p>*ATTEN 20dB RL 10.0dBm 10dB/</p> <p>MKR -51.33dBm 3.853GHz</p> <p>START 1.000GHz STOP 5.000GHz *RBW 100kHz *VBW 300kHz SWP 2.20sec</p>		

Test Date	Data	Test Eng.
09/14/05	5.785 GHz (INTEL-050912-05d08)	JC
<p>*ATTEN 20dB RL 10.0dBm 10dB/</p> <p>MKR -42.83dBm 5.542GHz</p> <p>START 5.000GHz STOP 10.000GHz *RBW 100kHz *VBW 300kHz SWP 2.80sec</p>		


Page 56 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT




AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11a Mode

Test Date	Data	Test Eng.
09/14/05	5.785 GHz (INTEL-050912-05d09)	JC
<p>*ATTEN 20dB RL 10. 0dBm 10dB/ MKR -60. 17dBm 16. 73GHz</p>  <p>START 10.00GHz STOP 20.00GHz *RBW 100kHz *VBW 300kHz SWP 5.50sec</p>		

Test Date	Data	Test Eng.
09/14/05	5.785 GHz (INTEL-050912-05d10)	JC
<p>*ATTEN 20dB RL 10. 0dBm 10dB/ MKR -51. 50dBm 36. 73GHz</p>  <p>START 20.00GHz STOP 40.00GHz *RBW 100kHz *VBW 300kHz SWP 11.0sec</p>		

Page 57 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT




AEGIS LABS INC.


Conducted Out Of Band Emissions (Continued)

802.11a Mode

Test Date	Data	Test Eng.
09/14/05	5.825 GHz (INTEL-050912-05d11)	JC



Test Date	Data	Test Eng.
09/14/05	5.825 GHz (INTEL-050912-05d12)	JC




Page 58 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT




AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11a Mode

Test Date	Data	Test Eng.
09/14/05	5.825 GHz (INTEL-050912-05d13)	JC
<p>*ATTEN 20dB RL 10.0dBm 10dB/</p> <p>MKR -43.50dBm 7.767GHz</p>  <p>START 5.000GHz STOP 10.000GHz *RBW 100kHz *VBW 300kHz SWP 2.80sec</p>		

Test Date	Data	Test Eng.
09/14/05	5.825 GHz (INTEL-050912-05d14)	JC
<p>*ATTEN 20dB RL 10.0dBm 10dB/</p> <p>MKR -59.50dBm 19.57GHz</p>  <p>START 10.00GHz STOP 20.00GHz *RBW 100kHz *VBW 300kHz SWP 5.50sec</p>		


Page 59 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11a Mode



Page 60 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11b Mode

Test Date	Data	Test Eng.
09/13/05	2.412 GHz (INTEL-050912-02e01)	JC
*ATTEN 20dB RL 10. 0d Bm	MKR -55. 50d Bm 457MHz	

Figure showing a spectrum analysis plot for 802.11b mode. The plot shows a single sharp peak at 457 MHz, which is the measured marker (MKR) frequency. The plot is on a grid with a 10 dB/10 MHz scale. The x-axis is labeled with START 30MHz and STOP 2.000GHz, and the y-axis is labeled with *RBW 100kHz and *VBW 300kHz. The sweep width (SWP) is 1.10sec.

Test Date	Data	Test Eng.
09/13/05	2.412 GHz (INTEL-050912-02e02)	JC
*ATTEN 20dB RL 10. 0d Bm	MKR -49. 67d Bm 2.307GHz	

Figure showing a spectrum analysis plot for 802.11b mode. The plot shows a single sharp peak at 2.307 GHz, which is the measured marker (MKR) frequency. The plot is on a grid with a 10 dB/10 MHz scale. The x-axis is labeled with START 2.000GHz and STOP 10.000GHz, and the y-axis is labeled with *RBW 100kHz and *VBW 300kHz. The sweep width (SWP) is 4.40sec.


Page 61 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT




AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11b Mode

Test Date	Data	Test Eng.
09/13/05	2.412 GHz (INTEL-050912-02e03)	JC
<p>*ATTEN 20dB RL 10.0dBm 10dB/</p> <p>MKR -59.00dBm 13.43GHz</p>  <p>START 10.00GHz STOP 20.00GHz *RBW 100kHz *VBW 300kHz SWP 5.50sec</p>		

Test Date	Data	Test Eng.
09/13/05	2.412 GHz (INTEL-050912-02e04)	JC
<p>*ATTEN 20dB RL 10.0dBm 10dB/</p> <p>MKR -54.83dBm 24.58GHz</p>  <p>START 20.00GHz STOP 26.00GHz *RBW 100kHz *VBW 300kHz SWP 3.30sec</p>		

Page 62 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11b Mode

Test Date	Data	Test Eng.
09/13/05	2.437 GHz (INTEL-050912-02e05)	JC
*ATTEN 20dB RL 10. 0d Bm	MKR -50. 00d Bm 483MHz	

Graph showing conducted out-of-band emissions in 802.11b mode. The plot shows a single sharp peak at 483 MHz, which is well below the 2.437 GHz operating frequency. The plot is on a grid with a 10 dB/10 MHz scale.

START 30MHz STOP 2.000GHz
*RBW 100kHz *VBW 300kHz SWP 1.10sec

Test Date	Data	Test Eng.
09/13/05	2.437 GHz (INTEL-050912-02e06)	JC
*ATTEN 20dB RL 10. 0d Bm	MKR -46. 83d Bm 2.333GHz	

Graph showing conducted out-of-band emissions in 802.11b mode. The plot shows a single sharp peak at 2.333 GHz, which is well below the 2.437 GHz operating frequency. The plot is on a grid with a 10 dB/10 MHz scale.

START 2.000GHz STOP 10.000GHz
*RBW 100kHz *VBW 300kHz SWP 4.40sec

Page 63 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11b Mode

Test Date	Data	Test Eng.
09/13/05	2.437 GHz (INTEL-050912-02e07)	JC
<p>*ATTEN 20dB RL 10. 0dBm 10dB/</p> <p>MKR -59. 00dBm 14. 18GHz</p> <p>START 10.00GHz STOP 20.00GHz *RBW 100kHz *VBW 300kHz SWP 5.50sec</p>		

Test Date	Data	Test Eng.
09/13/05	2.437 GHz (INTEL-050912-02e08)	JC
<p>*ATTEN 20dB RL 10. 0dBm 10dB/</p> <p>MKR -55. 00dBm 25. 470GHz</p> <p>START 20.000GHz STOP 26.000GHz *RBW 100kHz *VBW 300kHz SWP 3.30sec</p>		

Page 64 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT




AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11b Mode

Test Date	Data	Test Eng.
09/13/05	2.462 GHz (INTEL-050912-02e09)	JC
<p>*ATTEN 20dB RL 10. 0dBm 10dB/</p> <p>MKR -51. 17dBm 509MHz</p>  <p>START 30MHz STOP 2.000GHz *RBW 100kHz *VBW 300kHz SWP 1.10sec</p>		

Test Date	Data	Test Eng.
09/13/05	2.462 GHz (INTEL-050912-02e10)	JC
<p>*ATTEN 20dB RL 10. 0dBm 10dB/</p> <p>MKR -50. 50dBm 2.347GHz</p>  <p>START 2.000GHz STOP 10.000GHz *RBW 100kHz *VBW 300kHz SWP 4.40sec</p>		

Page 65 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT




AEGIS LABS INC.


Conducted Out Of Band Emissions (Continued)

802.11b Mode

Test Date	Data	Test Eng.
09/13/05	2.462 GHz (INTEL-050912-02e11)	JC



Test Date	Data	Test Eng.
09/13/05	2.462 GHz (INTEL-050912-02e12)	JC



Page 66 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11g Mode

Test Date	Data	Test Eng.
09/13/05	2.412 GHz (INTEL-050912-03e01)	JC
<p>*ATTEN 20dB RL 10.0dBm 10dB/</p> <p>MKR -63.00dBm 460MHz</p> <p>START 30MHz STOP 2.000GHz *RBW 100kHz *VBW 300kHz SWP 1.10sec</p>		

Test Date	Data	Test Eng.
09/13/05	2.412 GHz (INTEL-050912-03e02)	JC
<p>*ATTEN 20dB RL 10.0dBm 10dB/</p> <p>MKR -47.67dBm 2.507GHz</p> <p>START 2.000GHz STOP 10.000GHz *RBW 100kHz *VBW 300kHz SWP 4.40sec</p>		


Page 67 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT




AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11g Mode

Test Date	Data	Test Eng.
09/13/05	2.412 GHz (INTEL-050912-03e03)	JC
<p>*ATTEN 20dB RL 10.0dBm 10dB/</p> <p>MKR -59.50dBm 13.38GHz</p>  <p>D</p> <p>START 10.00GHz STOP 20.00GHz *RBW 100kHz *VBW 300kHz SWP 5.50sec</p>		

Test Date	Data	Test Eng.
09/13/05	2.412 GHz (INTEL-050912-03e04)	JC
<p>*ATTEN 20dB RL 10.0dBm 10dB/</p> <p>MKR -54.83dBm 24.54GHz</p>  <p>D</p> <p>START 20.00GHz STOP 26.00GHz *RBW 100kHz *VBW 300kHz SWP 3.30sec</p>		

Page 68 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT




AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11g Mode

Test Date	Data	Test Eng.
09/13/05	2.437 GHz (INTEL-050912-03e05)	JC


*ATTEN 20dB MKR -59.67dB
RL 10.0dBm 10dB/ 483MHz



START 30MHz STOP 2.000GHz
*RBW 100kHz *UBW 300kHz SWP 1.10sec

Test Date	Data	Test Eng.
09/13/05	2.437 GHz (INTEL-050912-03e06)	JC

*ATTEN 20dB MKR -47.00dBm
RL 10.0dBm 10dB/ 2.333GHz



START 2.000GHz STOP 10.000GHz
*RBW 100kHz *UWB 300kHz SWP 4.40sec

Page 69 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT




AEGIS LABS INC.


Conducted Out Of Band Emissions (Continued)

802.11g Mode

Test Date	Data	Test Eng.
09/13/05	2.437 GHz (INTEL-050912-03e07)	JC



Test Date	Data	Test Eng.
09/13/05	2.437 GHz (INTEL-i050912-03e08)	JC



Page 70 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11g Mode

Test Date	Data	Test Eng.
09/13/05	2.462 GHz (INTEL-050912-03e09)	JC
<p>*ATTEN 20dB RL 10.0dBm 10dB/</p> <p>MKR -61.50dBm 506MHz</p> <p>START 30MHz STOP 2.000GHz *RBW 100kHz *VBW 300kHz SWP 1.10sec</p>		

Test Date	Data	Test Eng.
09/13/05	2.462 GHz (INTEL-050912-03e10)	JC
<p>*ATTEN 20dB RL 10.0dBm 10dB/</p> <p>MKR -50.00dBm 2.347GHz</p> <p>START 2.000GHz STOP 10.000GHz *RBW 100kHz *VBW 300kHz SWP 4.40sec</p>		


Page 71 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT




AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)

802.11g Mode

Test Date	Data	Test Eng.
09/13/05	2.462 GHz (INTEL-050912-03e11)	JC
<p>*ATTEN 20dB RL 10. 0dBm 10dB/</p> <p>MKR -59. 50dBm 13. 33GHz</p>  <p>START 10. 00GHz STOP 20. 00GHz *RBW 100kHz *VBW 300kHz SWP 5.50sec</p>		

Test Date	Data	Test Eng.
09/13/05	2.462 GHz (INTEL-050912-03e12)	JC
<p>*ATTEN 20dB RL 10. 0dBm 10dB/</p> <p>MKR -54. 33dBm 25. 41GHz</p>  <p>START 20. 000GHz STOP 26. 000GHz *RBW 100kHz *VBW 300kHz SWP 3.30sec</p>		

Page 72 of 72 (Appendix A)
Report Number: INTEL-050912F
FCC ID: E2K5HCKT