



AEGIS LABS INC.

Class II Permissive Change
Test Report
And Application for Grant of Equipment Authorization

Pertaining To:

Equipment Under Test	FCC ID:
XPS M2010 Notebook Computer, MN: PP03X	E2KWM3945ABG

Configuration
Tested with an Intel PRO/Wireless 3945ABG Network Connection, MN: WM3945ABG

MEASUREMENTS PERFORMED IN ACCORDANCE WITH

Regulatory Standard(s)
47 CFR Part 15, Subpart E Section 15.407 (UNII Devices)
Test Method: ANSI C63.4: 2003 American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz



Certificate Number: 1111.01

APPLICANT:

Dell Computer Corporation
One Dell Way
Round Rock, TX 78682

Contact(s): Mr. Jason Limoges

PREPARED BY:

Aegis Labs, Inc.
22431 Antonio Parkway B160-417
Rancho S. Margarita, CA 92688

Agent(s): Mr. Steve Kuiper
Mr. Rick Candelas
Mr. Johnny Candelas

Test Report #: INTEL-060408F
Test Report Revision: None

	REPORT BODY	APPENDICES	TOTAL PAGES
		<i>A</i>	
PAGES	16	48	64

The contents of this report shall not be reproduced except in full, without the written approval of Aegis Labs, Inc.

Page 1 of 16
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG



TABLE OF CONTENTS

SECTION	TITLE	PAGE
	COVER SHEET.....	01
	TABLE OF CONTENTS.....	02
1.0	CERTIFICATION OF TEST DATA.....	03
2.0	SUMMARY OF TEST RESULTS.....	04
3.0	ADMINISTRATIVE DATA AND TEST DESCRIPTION.....	06
4.0	DESCRIPTION OF EUT.....	07
4.1	EUT Description.....	07
4.2	EUT Configuration.....	08
4.3	List of EUT Sub-Assemblies and Host Equipment.....	09
4.4	I/O Cabling Diagram and Description.....	10
5.0	TEST EQUIPMENT AND TEST SETUPS.....	11
5.1	AC Power Line Conducted Emissions.....	11
5.2	Spurious Radiated Emissions.....	12
5.3	Conducted Emissions At The Antenna Port.....	12
5.4	Test and Measurement Equipment Used.....	13
6.0	SAMPLE CALCULATIONS.....	14
7.0	MODIFICATIONS AND RECOMMENDATIONS.....	16

APPENDICES

A	Test Data
----------	-----------



Aegis Labs, Inc. operates as both a Nevada and California Corporation with no organizational or financial relationship with any company, institution, or private individual.

Testing and engineering functions provided by Aegis Labs are furnished through the use of part-time, full-time or consulting engineers with the appropriate qualifications to carry out their duties. The intended purpose of this test report is to describe the measurement procedure and to determine whether the equipment under test “EUT” complies with both the conducted and radiated limits. Limits for emissions testing are described under Subpart E of Part 15 of the FCC rules for Unlicensed National Information Infrastructure (UNII) Devices.

The data, data evaluation and equipment configuration represented herein are a true and accurate representation of the Equipment Under Test (EUT) under the requirements specified in the emissions standard as described below. The test results contained in this report are only representative of the test sample tested as described in Section 3.0 of this report. Certification of the EUT is required as a prerequisite to marketing as defined in Part 2 of the FCC Rules.

Report Reviewed By:

 04/14/06
Rick Candelas Date:
Lab Manager
Aegis Labs, Inc.

Report Approved By:

 **04/14/06**
Steve J. Kuiper **Date:**
Quality Assurance Manager
Aegis Labs, Inc.



2.0 SUMMARY OF TEST RESULTS

The test results provided within this report, indicate that the EUT has been found to be in **COMPLIANCE** with the test specifications based upon the following RF compliance standards:

Pass/Fail determination is based upon the nominal values of the test data.

EMISSIONS STANDARD			
FCC Part 15 Section	Description	Results	Comments
Operation in the 5.15-5.25 GHz Band			
15.407(d)	Any UNII device shall use a transmitting antenna that is an integral part of the device.	PASSED	The antenna will be integral when installed in a notebook computer
15.407(e)	UNII devices will be restricted to indoor operations.	PASSED	Refer to "User's Manual" Exhibit
15.407(a)(1)	26dB emissions bandwidth in MHz.	N/A	5.18 GHz = 23.50 MHz
15.407(a)(1)	Peak transmit power shall not exceed the lesser of 50mW or 4dBm+10logB (where B = 26dB emissions bandwidth).	PASSED	5.18 GHz = 16.60dBm (45.71mW) 5.24 GHz = 16.70dBm (46.77mW)
15.407(a)(1)	The peak power spectral density shall not exceed 4dBm in any 1MHz band.	PASSED	5.18 GHz = 1.93dBm
15.407(a)(1)	Peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the transmitting antenna exceeds 6dBi.	N/A	All antennas tested have less than 6dBi antenna gain (Please see the antenna data sheets)
15.407(b)(6) 15.209	Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in Section 15.209.	PASSED	See Data Sheets
15.407(b)(1)	All emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27dBm/MHz.	PASSED	See Data Sheets
Operation in the 5.25-5.35 GHz Band			
15.407(a)(2)	26dB emissions bandwidth in MHz.	N/A	5.26 GHz = 23.58 MHz 5.32 GHz = 24.25 MHz
15.407(a)(2)	Peak transmit power shall not exceed the lesser of 250mW or 11dBm+10logB (where B = 26dB emissions bandwidth).	PASSED	5.26 GHz = 18.50dBm (70.79mW) 5.32 GHz = 18.30dBm (67.61mW)
15.407(a)(2)	The peak power spectral density shall not exceed 11dBm in any 1MHz band.	PASSED	5.26 GHz = 2.60dBm 5.32 GHz = 2.12dBm
15.407(a)(2)	Peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the transmitting antenna exceeds 6dBi.	N/A	All antennas tested have less than 6dBi antenna gain (Please see the antenna data sheets)
15.407(b)(6) 15.209	Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in Section 15.209.	PASSED	See Data Sheets
15.407(b)(2)	All emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27dBm/MHz. Must meet all applicable technical requirements for operating in the 5.15-5.25 GHz band.	PASSED	See Data Sheets



2.0 SUMMARY OF TEST RESULTS (Continued)

EMISSIONS STANDARD			
FCC Part 15 Section	Description	Results	Comments
General Requirements For All Bands			
15.407(a)(6)	The ratio of the peak excursion of the modulation envelope to the peak transmit power shall not exceed 13dB across any 1 MHz bandwidth or the emissions bandwidth whichever is less.	PASSED	5.18 GHz = 5.00 dB 5.26 GHz = 5.33 dB 5.32 GHz = 5.16 dB
15.407(f)	Radio frequency radiation exposure requirement.	PASSED	Refer to MPE Calculations Exhibit
15.407(b)(6) 15.207	UNII devices using AC power line are required to comply with the conducted limits set forth in Section 15.207.	PASSED	See Data Sheets



3.0 ADMINISTRATIVE DATA AND TEST DESCRIPTION

DEVICE TESTED:	ITE Type: XPS M2010 Notebook Computer Model Number(s): PP03X Serial Number: 2029658000002 FCC ID: E2KWM3945ABG
TEST DATE(S):	April 07-13, 2006
DATE EUT RECEIVED:	April 07, 2006
ORIGIN OF TEST SAMPLE(S):	Production Unit
RESPONSIBLE PARTY:	Dell Computer Corporation One Dell Way Round Rock, TX 78682
CLIENT CONTACT:	Mr. Jason Limoges
MANUFACTURER:	Dell Computer Corporation
TEST LOCATION:	Aegis Labs, Inc. 32231 Trabuco Creek Road Trabuco Canyon, CA 92678 Conducted Site #2 Radiated Site #2
A2LA CERTIFICATE:	1111.01, Valid through April 30, 2006
PURPOSE OF TEST:	To demonstrate compliance with the relevant standards described in Section 2.0 of this report.
TEST(S) PERFORMED:	Refer to Table in Section 2.0 of this report.

All calibration vendors were responsible for certifying Aegis Labs, Inc. test equipment as per the manufacturer's specifications and that the equipment is calibrated using instruments and standards where the accuracy is traceable to the National Institute of Standards and Technology (NIST). Calibration of all test equipment conforms to ANSI/NCSL Z540-1 and ISO 10012-1 and/or ISO/IEC Guide 17025 compliance (Additionally, other pertinent test equipment will carry MIL-STD-45662A). All calibration documents are on file with Aegis Labs, Inc., with copies provided upon request.



4.0 DESCRIPTION OF EUT

4.1 EUT Description

Equipment Under Test (EUT)		
Trade Name:	XPS M2010 Notebook Computer	
Model Number:	PP03X tested with an Intel PRO/Wireless 3945ABG Network Connection, MN: WM3945ABG	
Frequency Range:	5.15-5.35 GHz	
Enclosure:	The EUT contains it's own shield made of aluminum approximately 2.5cm wide by 2cm deep by 2mm high.	
Transfer Rate:	6/36/52 Mbps	
Antenna Type:	<u>Amphenol:</u> FR4, Dipole Antenna (Main/Aux)	<u>Hitachi:</u> Monopole (Main/Aux)
Antenna Gain (See Note 2):	<u>Amphenol:</u> 5 GHz = 2.36 dBi	<u>Hitachi:</u> 5 GHz = 2.10 dBi
Transmit Output Power:	16 dBm (Typical) for 5.15-5.25 GHz 18 dBm (Typical) for 5.25-5.35 GHz Please see Appendix A (Data Sheets) for actual output power.	
Power Supply:	3.3VDC from computer MPCIE slot.	
Number of External Test Ports Exercised:	2 Antenna Ports (1 Main & 1 Auxiliary)	

The XPS | M2010 Notebook Computer was tested with an Intel PRO/Wireless 3945ABG Network Connection, operating in the 2.4 GHz and 5 GHz spectrum. The Mini-PCI-E form factor is designed to meet the space and size requirements for thin and light notebook PCs. It is capable of a data rate of up to 52 Mbps.

NOTE 1: For a more detailed description, please refer to the manufacture's specifications or User's Manual.

NOTE 2: Refer to the antenna specifications for a further description of the antennas. Antennas will be professionally installed inside the laptop computer by the laptop vendor.



4.2 EUT Configuration

The EUT was tested with an Intel PRO/Wireless 3945ABG Network Connection installed in its Mini PCI-E slot and was connected to a set of Amphenol & Hitachi multi-band antennas via its main and auxiliary antenna ports. Data can be found in Appendix A.

For conducted emissions at the AC mains port and radiated emissions, the EUT was connected to a Logitech keyboard, and mouse via its USB ports.

The low, middle, and high channels were tested in 802.11a, b, & g modes. Also, the EUT was tested once transmitting from the MAIN antenna port and once transmitting from the AUX antenna port. The EUT was placed in either continuous transmit or continuous receive mode by a program provided by the manufacturer (*GRTT Version 1.1.1*).



4.3 List of EUT, Sub-Assemblies, and Host Equipment


LIST OF EUT AND SUB-ASSEMBLIES			
Equipment Name	Manufacturer	Model Number	Serial Number
XPS M2010 Notebook Computer	Dell Computer Corporation	PP03X	2029658000002
EUT Sub-Assemblies			
Intel PRO/Wireless 3945ABG Network Connection	Intel Corporation	WM3945ABG	001302256F72
Main Multi Band Antenna	Amphenol	EAX20	N/A
Auxiliary Multi Band Antenna	Amphenol	EAX20	N/A
Main Multi Band Antenna	Hitachi Cable, Ltd	HMT02-DL01	N/A
Auxiliary Multi Band Antenna	Hitachi Cable, Ltd	HMT02-DL01	N/A

HOST EQUIPMENT LIST			
Equipment Name	Manufacturer	Model Number	Serial Number
Keyboard	Logitech	Y-BF37	MCTZ5200581
Mouse	Logitech	M-BJ58	LZE14759424

NOTE: All the power cords of the above support equipment are standard non-shielded, 1.8 meters long.



4.4 I/O Cabling Diagram and Description



- Cable 1: This is a 6-foot braid and foil shielded round cable connecting the host computer to the keyboard. It has a metallic 6-pin mini din type connector at the computer end and is hardwired to the keyboard. The shield of the cable is grounded to the chassis of the computer via the connector shell.
- Cable 2: This is a 6-foot braid and foil shielded round cable connecting the host computer to the mouse. It has a metallic 6-pin mini din type connector at the computer end and is hardwired to the mouse. The shield of the cable is grounded to the chassis of the computer via the connector shell.



5.0 TEST EQUIPMENT AND TEST SETUPS

The test equipment settings and functions are selected using the guidance of ANSI C63.4-2003. All test equipment setups and operations during conducted and radiated emissions testing are in accordance with this reference document.

5.1 AC Power Line Conducted Emissions

During conducted emissions measurements, a spectrum analyzer was used as the measuring instrument along with a preselector and quasi-peak detector. A 10 dB attenuation pad was used for the protection of the spectrum analyzer input stage. The conducted emissions from the EUT in the frequency range from 150 kHz to 30 MHz were captured for graphical display through the use of automated LABVIEW EMI measurement software. All graphical readings were measured in the “Peak” mode only to reduce testing time. Upon completion of the graphical scan, the test lab personnel performed the conducted measurement scan manually using the spectrum analyzer front panel keys. All peak measurements coming within 3 dB of the limit line were “Averaged” and/or “Quasi-Peaked” and denoted appropriately in the EXCEL spreadsheet.

The Equipment Under Test (EUT) was configured as a system with peripherals connected, so that at least one interface port of each type is connected to one external peripheral when tested for conducted emissions according to ANSI C63.4: 2003. Excess power cord length was wrapped in a bundle 30 to 40 centimeters in length near the center of the cord. The EUT was tested in a tabletop configuration.

The emission readings for Line 1 and Line 2 are highlighted on the data sheets in Appendix A. The graphical scans only reflects peak readings while the tabulated data sheets reflect peak, average, and/or quasi-peak readings which ever applies.



5.2 Spurious Radiated Emissions

A spectrum analyzer was used as the measuring instrumentation along with a preselector and quasi-peak-detector. The pre-amplifiers were used to increase the sensitivity of the instrument. The spectrum analyzer was used in the peak detector mode with the “max-hold” feature activated and in Positive Peak mode. In this mode, the spectrum analyzer records the highest measured reading over all the sweeps. The quasi-peak detector was used only for those readings, which are marked accordingly in the data sheet. The effective measurement bandwidth used for the radiated emissions test was 120 kHz for (30 MHz- 1000 MHz). The spectrum analyzer operated such that the modulation of the signal was filtered out to set the analyzer in linear mode. For testing beyond 1000 MHz a spectrum analyzer capable of taking reading above 1000 MHz was connected to the high frequency amplifier, where these measurement readings were taken with the transducer placed at a 3-meter test distance from the EUT.

The Open Area Test Sites (OATS) was used for radiated emission testing. These test sites are designed according to ANSI C63.4: 2003 and ANSI C63.7: 1992 guidelines. The Measurements were conducted in accordance with ANSI C63.4: 2003 and ANSI C63.7: 1992 requirements.

Broadband biconical, log periodic, and horn antennas were used as transducers during the measurement reading phase. The frequency spans were wide (30 MHz-88 MHz, 88 MHz- 216 MHz, 216 MHz- 300 MHz, and 300 MHz- 1000 MHz). After 1000 MHz the horn antenna was used to measure emissions. The emission readings in both horizontal and vertical polarities are highlighted on the data sheets in Appendix A.

5.3 Conducted Emissions at the Antenna Port

A spectrum analyzer or power meter was used as the measuring instrumentation along with an attenuator and/or filter connected to the EUT antenna port. The attenuator and filters are used to ensure that the front end of the measurement instrument is not overloaded by the fundamental transmission. . The instruments recorded the measured readings with the bandwidths (video and resolution) set in accordance with the FCC Rules and regulations.

The measured readings are on the data sheets in Appendix A.



5.4 Test and Measurement Equipment Used

TEST EQUIPMENT USED					
Equipment Name	Manufacturer	Model Number	Serial Number	Calibration Due Date	Calibration Cycle
Spectrum Analyzer	Agilent	8564EC	4046A00387	08/15/06	1 Year
Preamp	Miteq	JS42-01001800-25-10P	815980	07/21/06	1 Year
2.4 GHz Notch Filter	Micro-Tronics	BRM50702-02	003	04/21/06	1 Year
5.15-5.35 GHz Notch Filter	Microwave Circuits	N0452502	3173-01	06/27/06	1 Year
5.725-5.850 GHz Notch Filter	Microwave Circuits	N0257881	3173-01	06/27/06	1 Year
Horn Antenna	EMCO	3115	2230	02/06/07	1 Year
Antenna - 18-26.5 GHz Pre-amplified Horn	Aegis Labs, Inc.	H042	SLK-35-3W	02/08/07	1 Year
Antenna - 26.5-40 GHz Pre-amplified Horn	Aegis Labs, Inc.	H028	GM1260-10	02/08/07	1 Year
Cable	Semflex	X116BFSX10216	546	12/14/06	1 Year
Temperature/Humidity Monitor	Dickson	TH550	7255185	N/A	N/A
Power Meter	Anritsu	ML2487A	6K00001785	04/12/07	1 Year
Wide Bandwidth Sensor	Anritsu	MA2491A	31193	04/12/07	1 Year
12dB Attenuator	Narda	4779-12	203	08/06/06	1 Year
EMI Receiver - RF Section	Hewlett Packard	8546A	3737A00407	09/02/06	1 Year
EMI Receiver - RF Filter Section	Hewlett Packard	85460A	3704A00399	09/02/06	1 Year
Antenna - Biconical	EMCO	3110	9108-1421	05/17/06	1 Year
Antenna - Log Periodic	EMCO	3148	47943	05/23/06	1 Year
EUT LISN	Solar	9252-50-R-24-BNC	961025	03/30/08	2 Year
Accessory LISN	Solar	9252-50-R-24-BNC	961024	07/05/07	2 Year
10dB Attenuator	Radiall	R412710000	Lot:9624	07/09/06	1 Year
Spectrum Analyzer	Rohde & Schwarz	FSP 40	100205	08/15/06	1 Year



6.0 SAMPLE CALCULATIONS

If a preamplifier is used during the Radiated Emissions Testing, it is required that the amplifier gain be subtracted from the Spectrum Analyzer (Meter) Reading. In addition, a correction factor for the antenna, cable and a distance factor, if any, must be applied to the Meter Reading before a true field strength reading can be obtained. In the Automatic Mode of A.R.M.S. measurements, these considerations are automatically presented as a part of the printout. In the case of manual measurements and for greater efficiency and convenience, usage of the calibration correction factors in the Appendices is necessary to calculate the Corrected Meter Reading. These correlation factors for each meter reading, shall be modified to reflect these correlation factors at each frequency value so that the meter readings can be compared directly to the modified specification limit. This modified specification limit is referred to as the "Corrected Meter Reading Limit" (CML).

The equation shall be derived in the following manner:

$$\text{Corrected Meter Reading} = \text{Meter Reading} + F + C - G - D$$

Where, F = Antenna Factor

C = Cable Factor

G = Amplifier Gain

D = Distance Factor

Therefore, the equation for determining the Corrected Meter Reading Limit (CML) is:

$$\text{CML} = \text{Specification Limit} - F - C + G + D$$

For the manual mode of measurement, a table of corrected meter reading limits shall be used to permit immediate comparison of the meter reading to determine if the measured emission amplitude exceeded the specification limit at that specific frequency. There shall be two calculation sheets done, one for three meter and one for ten-meter measurement distances, where applicable. The correction factors for the antenna and the amplifier gain are attached in the Appendices.



6.0 Sample Calculations (Continued)

Peak Transmit Power Output:

A correction factor for the cable must be applied to the Conducted Power before a true power reading can be obtained. This is referred to as the “Corrected Power” (CP).

The equation shall be derived in the following manner:

$$\text{Corrected Power Reading} = \text{Conducted Power Reading} + C$$

Where, C = Cable Factor

The conducted power is taken in units of dBm. To obtain units of mW the following equation is used:

$$\text{mW} = 10^{(\text{dBm}/10)}$$



7.0 MODIFICATIONS AND RECOMMENDATIONS

No modifications were made to the EUT.



AEGIS LABS INC.

APPENDIX A

TEST DATA

Page 1 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG

**AC POWER LINE CONDUCTED EMISSIONS TEST RESULTS**

CLIENT:	Dell Computer Corporation	DATE:	04/11/06
EUT:	XPS M2010 Notebook Computer	PROJECT NUMBER:	INTEL-060407
MODEL NUMBER:	PP03X	TEST ENGINEER:	JC
SERIAL NUMBER:	2029658000002	SITE #:	1
CONFIGURATION:	Tested with an Intel PRO/Wireless 3945ABG Network Connection installed in its mini PCI-E slot.	TEMPERATURE:	18 C
		HUMIDITY:	52% RH
		TIME:	1:30 PM

Standard:	FCC CFR 47, 15.407(b)(6) 15.207
Description:	U-NII devices using an AC power line are required to comply with the conducted limits set forth in Sec. 15.207.
Results:	Passes the conducted limits by -12.96 @ 0.1500 MHz

Conducted Limits		
Frequency (MHz)	Quasi-Peak Limit (dBuV)	Average Limit (dBuV)
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50


*Decreases with the logarithm of the frequency.

NOTE: During preliminary scans, there wasn't any difference which mode, channel, or data rate was used with the EUT; therefore only 802.11b mode at Channel 1 with a data rate of 1 Mbps was used for final testing.



AC Power Line Conducted Emissions Test Results (Continued)

CONDUCTED EMISSIONS – LINE 1						
Freq. (MHz)	Meter Reading (dBuV)	Detector (PK/QP/AV)	Average Limit (dBuV)	Average Delta(dB)	Quasi-Peak Limit (dBuV)	Quasi-Peak Delta(dB)
0.1500	42.95	PK	56.00	-13.05	66.00	-23.05
0.1700	39.27	PK	55.43	-16.16	65.43	-26.16
0.3100	33.43	PK	51.43	-18.00	61.43	-28.00
0.3500	31.97	PK	50.28	-18.31	60.28	-28.31
1.2300	31.83	PK	46.00	-14.17	56.00	-24.17
13.0000	34.03	PK	50.00	-15.97	60.00	-25.97






AEGIS LABS INC.

AC Power Line Conducted Emissions Test Results (Continued)

CONDUCTED EMISSIONS - LINE 2						
Freq. (MHz)	Meter Reading (dBuV)	Detector (PK/QP/AV)	Average Limit (dBuV)	Average Delta(dB)	Quasi-Peak Limit (dBuV)	Quasi-Peak Delta(dB)
0.1500	43.04	PK	56.00	-12.96	66.00	-22.96
0.4000	28.97	PK	48.86	-19.89	58.86	-29.89
0.7000	29.02	PK	46.00	-16.98	56.00	-26.98
1.3000	28.55	PK	46.00	-17.45	56.00	-27.45
1.7200	28.85	PK	46.00	-17.15	56.00	-27.15
12.2800	33.45	PK	50.00	-16.55	60.00	-26.55



Page 4 of 48 (Appendix A)
 Report Number: INTEL-060408F
 FCC ID: E2KWM3945ABG

**SPURIOUS RADIATED EMISSIONS TEST RESULTS**

CLIENT:	Dell Computer Corporation	DATE:	04/12/06
EUT:	XPS M2010 Notebook Computer	PROJECT NUMBER:	INTEL-060407
MODEL NUMBER:	PP03X	TEST ENGINEER:	BM
SERIAL NUMBER:	2029658000002	SITE #:	1
CONFIGURATION:	Tested with an Intel PRO/Wireless 3945ABG Network Connection installed in its mini PCI-E slot.	TEMPERATURE:	13 C
		HUMIDITY:	71% RH
		TIME:	9:00 PM

Standard:	FCC CFR 47, Part 15.407(b)(6) 15.209
Description:	Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in Sec. 15.209. (Using CISPR22 Class B Limits)
Results:	Passes the radiated limits by -3.57 @ 602.31 MHz (Vertical antenna polarization)

Radiated Limits	
Frequency (MHz)	Quasi-Peak Limit (dBuV)
30-88	40
88-216	43.52
216-960	46.02
960-1000	54

NOTE: During preliminary scans, there wasn't any difference which mode, channel, or data rate was used with the EUT; therefore only 802.11b mode at Channel 1 with a data rate of 1 Mbps was used for final testing.

**SPURIOUS RADIATED EMISSIONS TEST RESULTS**

RADIATED EMISSIONS - Horizontal Antenna Polarization											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>10 Meter Distance Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
33.25	4.40	400	0			0.92	17.63	10.46	33.40	40.00	-6.60
49.84	5.30	400	0			1.07	11.86	10.46	28.69	40.00	-11.31
80.02	10.65	400	45			1.45	6.60	10.46	29.16	40.00	-10.84
112.88	11.03	400	135			1.82	12.20	10.46	24.48	43.50	-19.02
200.01	5.81	400	225			2.37	16.90	10.46	35.54	43.50	-7.96
243.99	7.38	400	315			2.53	17.45	10.46	37.83	46.00	-8.17
249.98	9.27	400	180			2.55	17.50	10.46	39.78	46.00	-6.22
450.22	9.55	400	45			3.37	17.21	10.46	40.59	46.00	-5.41
559.74	8.85	400	45			3.85	19.19	10.46	42.36	46.00	-3.64
614.32	6.86	400	315			4.07	19.73	10.46	41.12	46.00	-4.88
727.73	8.89	400	135	4.67	Q	4.30	22.53	10.46	41.97	46.00	-4.03

**SPURIOUS RADIATED EMISSIONS TEST RESULTS**

RADIATED EMISSIONS - Vertical Antenna Polarization											
<i>Freq. (MHz)</i>	<i>Meter Reading (dBuV)</i>	<i>Antenna Height (cm)</i>	<i>Azimuth (degrees)</i>	<i>Quasi pk or AVG (dBuV)</i>		<i>Cable Factor (dB)</i>	<i>Ant. Factor (dB)</i>	<i>10 Meter Distance Factor (dB)</i>	<i>Corrected Reading (dBuV)</i>	<i>Limits (dBuV)</i>	<i>Diff (dB) +=FAIL</i>
44.30	7.05	100	315			1.02	12.55	10.46	31.08	40.00	-8.92
112.90	14.79	100	180			1.82	11.04	10.46	38.11	43.50	-5.39
144.00	14.88	100	135	8.55	Q	2.06	14.34	10.46	35.41	43.50	-8.09
146.96	10.51	100	180			2.10	14.52	10.46	37.59	43.50	-5.91
162.52	10.61	100	45			2.28	14.65	10.46	38.00	43.50	-5.50
168.00	10.34	100	0			2.32	15.64	10.46	38.76	43.50	-4.74
244.10	8.70	100	225			2.53	18.26	10.46	39.96	46.00	-6.04
250.00	9.04	100	135			2.55	18.50	10.46	40.55	46.00	-5.45
333.29	6.83	100	0			2.93	15.40	10.46	35.62	46.00	-10.38
400.00	7.49	100	45			3.19	16.00	10.46	37.14	46.00	-8.86
450.22	7.69	100	315			3.37	17.40	10.46	38.92	46.00	-7.08
596.35	5.63	100	180			4.00	19.50	10.46	39.59	46.00	-6.41
602.31	8.40	100	45			4.03	19.55	10.46	42.43	46.00	-3.57

NOTE: The measurements were taken at 10 meters and extrapolated to 3 meters.



AEGIS LABS INC.

***Dell Greenland with
Amphenol Antennas
TEST DATA***

*Page 8 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG*



Spurious Radiated Emissions Test Results (Continued)

CLIENT:	Dell Computer Corporation	DATE:	04/07/06
EUT:	XPS M2010 Notebook Computer	PROJECT NUMBER:	INTEL-060407
MODEL NUMBER:	PP03X	TEST ENGINEER:	BM/JC
SERIAL NUMBER:	2029658000002	SITE #:	2
CONFIGURATION:	Tested with an Intel PRO/Wireless 3945ABG Network Connection installed in its mini PCI-E slot and connected to a set of Amphenol antennas in 802.11a (5150-5350 MHz) mode.	TEMPERATURE:	12 C
		HUMIDITY:	74% RH
		TIME:	6:00 PM

Standard:	FCC CFR 47, Part 15.407(b)(7)
Description:	The provisions of Sec. 15.205 apply to intentional radiators operating under this section.
Results:	Passes (See Data Sheets)

Unwanted Spurious Emissions Limits			
Frequency (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m) (Emissions in the restricted bands)	Field Strength (dBm/MHz) (Emissions outside the restricted bands)
Above 960	500	54.00 (Average) 74.00 (Peak)	EIRP < -27dBm/MHz (68.3dBuV/m)



Spurious Radiated Emissions Test Results (Continued)

Fundamental Measurements in 802.11a mode (5150-5350 MHz)
Channels 36, 48, 52, & 64
Continuous TX at MAIN Antenna port with Amphenol Antennas
Aegis Labs, Inc. File #: INTEL-060407-06

RADIATED EMISSIONS - Horizontal Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
5180.00	68.17	100	225				4.73	34.77	107.67		
5180.00				60.16	A		4.73	34.77	99.66		
5240.00	67.67	100	225				4.76	34.80	107.23		
5240.00				59.46	A		4.76	34.80	99.02		
5260.00	68.33	100	225				4.77	34.80	107.90		
5260.00				59.93	A		4.77	34.80	99.50		
5320.00	67.33	100	225				4.80	34.83	106.96		
5320.00				59.11	A		4.80	34.83	98.74		

RADIATED EMISSIONS – Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
5180.00	66.00	150	270				4.73	34.64	105.37		
5180.00				57.88	A		4.73	34.64	97.25		
5240.00	67.50	100	0				4.76	34.65	106.91		
5240.00				59.11	A		4.76	34.65	98.52		
5260.00	67.67	100	225				4.77	34.65	107.09		
5260.00				59.29	A		4.77	34.65	98.71		
5320.00	66.00	125	270				4.80	34.66	105.46		
5320.00				57.96	A		4.80	34.66	97.42		

NOTE: Fundamental signals measured to calculate the band edge field strengths using the “Marker Delta Method”.



Spurious Radiated Emissions Test Results (Continued)

*Band Edge Field Strength Calculations in 802.11a mode (5150-5350 MHz)
Channels 36 & 64
Continuous TX at MAIN Antenna port with Amphenol Antennas
Aegis Labs, Inc. File #: INTEL-060407-06*

RADIATED EMISSIONS - Horizontal Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamplifier Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
5150.00									64.34	74.00	-9.66
5150.00					A				51.32	54.00	-2.68
5350.00									65.13	74.00	-8.87
5350.00					A				50.58	54.00	-3.42
5352.50									66.29	74.00	-7.71
5352.50					A				48.91	54.00	-5.09

RADIATED EMISSIONS – Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamplifier Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
5150.00									62.04	74.00	-11.96
5150.00					A				48.91	54.00	-5.09
5350.00									63.63	74.00	-10.37
5350.00					A				49.26	54.00	-4.74
5352.50									64.79	74.00	-9.21
5352.50					A				47.59	54.00	-6.41

NOTE: The “Band Edge Field Strength” was calculated using the “Fundamental” and “Conducted Band Edge” measurements per the “Marker-Delta Method” with the following formula:

$$BE = F_m - \Delta m$$

Where

BE = Band Edge Field Strength


F_m = Measured Fundamental (Peak or Average)

Δ_m = Measured Conducted Band Edge Delta (Peak or Average)



Spurious Radiated Emissions Test Results (Continued)


Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)





Spurious Radiated Emissions Test Results (Continued)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)





Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11a mode (5150-5350 MHz)**Channels 36, 52, & 64****Continuous TX at MAIN Antenna port with Amphenol Antennas****Aegis Labs, Inc. File #: INTEL-060407-08****RADIATED EMISSIONS - Horizontal Antenna Polarization**

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 36 (5.18 GHz)											
3453.33	53.33	100	225			46.84	3.84	31.50	41.83	68.00	-26.17
10360.01	54.50	100	45			45.00	6.86	38.60	54.96	68.00	-13.04
EUT in Continuous Transmit Mode on Channel 52 (5.26 GHz)											
3506.66	53.00	100	135			46.85	3.87	31.62	41.64	68.00	-26.36
10520.00	53.67	100	315			45.05	6.93	38.61	54.16	68.00	-13.84
EUT in Continuous Transmit Mode on Channel 64 (5.32 GHz)											
3546.66	52.83	100	225			46.84	3.90	31.72	41.61	68.00	-26.39
10639.98	50.83	100	225			45.02	6.96	38.68	51.46	74.00	-22.54
10639.98				38.59	A	45.02	6.96	38.68	39.22	54.00	-14.78

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 36 (5.18 GHz)											
3453.33	53.50	100	135			46.84	3.84	31.52	42.01	68.00	-25.99
10360.02	57.83	100	225			45.00	6.86	38.80	58.49	68.00	-9.51
EUT in Continuous Transmit Mode on Channel 52 (5.26 GHz)											
3506.66	53.33	100	135			46.85	3.87	31.62	41.97	68.00	-26.03
10520.00	55.50	100	180			45.05	6.93	38.82	56.20	68.00	-11.80
EUT in Continuous Transmit Mode on Channel 64 (5.32 GHz)											
3546.66	53.00	100	225			46.84	3.90	31.72	41.78	68.00	-26.22
10639.98	51.33	100	225			45.02	6.96	38.91	52.18	74.00	-21.82
10639.98				28.97	A	45.02	6.96	38.91	29.82	54.00	-24.18



Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11a mode (5150-5350 MHz)**Channels 36, 52, & 64****Continuous TX at MAIN Antenna port with Amphenol Antennas****Aegis Labs, Inc. File #: INTEL-060407-09****RADIATED EMISSIONS - Horizontal Antenna Polarization**

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Cable Factor (dB)	Antenna/ Preamp Factor (dB)	Corrected Reading (dBuV/m)	Limits (dBuV/m)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 36 (5.18 GHz)										
20720.00	38.67	100	180			10.07	-3.36	45.38	74.00	-28.62
20720.00				24.66	A	10.07	-3.36	31.37	54.00	-22.63
EUT in Continuous Transmit Mode on Channel 52 (5.26 GHz)										
21040.00	39.33	100	180			10.20	-3.33	46.20	74.00	-27.80
21040.00				25.13	A	10.20	-3.33	32.00	54.00	-22.00
EUT in Continuous Transmit Mode on Channel 64 (5.32 GHz)										
21280.00	38.83	100	180			10.22	-3.38	45.67	74.00	-28.33
21280.00				26.10	A	10.22	-3.38	32.94	54.00	-21.06

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Cable Factor (dB)	Antenna/ Preamp Factor (dB)	Corrected Reading (dBuV/m)	Limits (dBuV/m)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 36 (5.18 GHz)										
20720.00	39.83	100	225			10.07	-3.29	46.62	74.00	-27.39
20720.00				24.90	A	10.07	-3.29	31.69	54.00	-22.32
EUT in Continuous Transmit Mode on Channel 52 (5.26 GHz)										
21040.00	38.50	100	225			10.20	-3.28	45.42	74.00	-28.58
21040.00				25.57	A	10.20	-3.28	32.49	54.00	-21.51
EUT in Continuous Transmit Mode on Channel 64 (5.32 GHz)										
21280.00	39.33	100	180			10.22	-3.24	46.32	74.00	-27.68
21280.00				25.89	A	10.22	-3.24	32.88	54.00	-21.12



Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11a mode (5150-5350 MHz)**Channels 36, 52, & 64****Continuous RX at MAIN Antenna port with Amphenol Antennas****Aegis Labs, Inc. File #: INTEL-060407-08****RADIATED EMISSIONS - Horizontal Antenna Polarization**

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 36 (5.18 GHz)											
3453.33	54.00	100	135			46.84	3.84	31.50	42.50	74.00	-31.50
3453.33				41.43	A	46.84	3.84	31.50	29.93	54.00	-24.07
EUT in Continuous Transmit Mode on Channel 52 (5.26 GHz)											
3506.66	52.83	100	135			46.85	3.87	31.62	41.47	74.00	-32.53
3506.66				41.21	A	46.85	3.87	31.62	29.85	54.00	-24.15
EUT in Continuous Transmit Mode on Channel 64 (5.32 GHz)											
3546.66	53.33	100	135			46.84	3.90	31.72	42.11	74.00	-31.89
3546.66				41.04	A	46.84	3.90	31.72	29.82	54.00	-24.18

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 36 (5.18 GHz)											
3453.33	53.67	100	135			46.84	3.84	31.52	42.18	74.00	-31.82
3453.33				41.09	A	46.84	3.84	31.52	29.60	54.00	-24.40
EUT in Continuous Transmit Mode on Channel 52 (5.26 GHz)											
3506.68	53.67	100	135			46.85	3.87	31.62	42.31	74.00	-31.69
3506.68				41.21	A	46.85	3.87	31.62	29.85	54.00	-24.15
EUT in Continuous Transmit Mode on Channel 64 (5.32 GHz)											
3546.66	53.50	125	135			46.84	3.90	31.72	42.28	74.00	-31.72
3546.66				40.68	A	46.84	3.90	31.72	29.46	54.00	-24.54



AEGIS LABS INC.

***Dell Greenland with
Hitachi Antennas
TEST DATA***

*Page 17 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG*



Spurious Radiated Emissions Test Results (Continued)

CLIENT:	Dell Computer Corporation	DATE:	04/12/06
EUT:	XPS M2010 Notebook Computer	PROJECT NUMBER:	INTEL-060407
MODEL NUMBER:	PP03X	TEST ENGINEER:	BM/JC
SERIAL NUMBER:	2029658100029	SITE #:	2
CONFIGURATION:	Tested with an Intel PRO/Wireless 3945ABG Network Connection installed in its mini PCI-E slot and connected to a set of Hitachi antennas in 802.11a (5150-5350 MHz) mode.	TEMPERATURE:	16 C
		HUMIDITY:	54% RH
		TIME:	9:15 AM

Standard:	FCC CFR 47, Part 15.407(b)(7)
Description:	The provisions of Sec. 15.205 apply to intentional radiators operating under this section.
Results:	Passes (See Data Sheets)

Unwanted Spurious Emissions Limits			
Frequency (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m) (Emissions in the restricted bands)	Field Strength (dBm/MHz) (Emissions outside the restricted bands)
Above 960	500	54.00 (Average) 74.00 (Peak)	EIRP < -27dBm/MHz (68.3dBuV/m)



Spurious Radiated Emissions Test Results (Continued)

Fundamental Measurements in 802.11a mode (5150-5350 MHz)
Channels 36, 48, 52, & 64
Continuous TX at MAIN Antenna port with Hitachi Antennas
Aegis Labs, Inc. File #: INTEL-060407-13

RADIATED EMISSIONS - Horizontal Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
5180.00	68.33	100	225				4.73	34.77	107.83		
5180.00				59.90	A		4.73	34.77	99.40		
5240.00	67.67	100	225				4.76	34.80	107.23		
5240.00				59.39	A		4.76	34.80	98.95		
5260.00	68.00	100	225				4.77	34.80	107.57		
5260.00				59.67	A		4.77	34.80	99.24		
5320.00	67.17	100	225				4.80	34.83	106.80		
5320.00				59.25	A		4.80	34.83	98.88		

RADIATED EMISSIONS – Vertical Antenna Polarization											
Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
5180.00	67.50	100	180				4.73	34.64	106.87		
5180.00				59.15	A		4.73	34.64	98.52		
5240.00	67.67	100	180				4.76	34.65	107.08		
5240.00				59.27	A		4.76	34.65	98.68		
5260.00	67.83	100	180				4.77	34.65	107.25		
5260.00				59.32	A		4.77	34.65	98.74		
5320.00	66.67	100	180				4.80	34.66	106.13		
5320.00				58.14	A		4.80	34.66	97.60		

NOTE: Fundamental signals measured to calculate the band edge field strengths using the “Marker Delta Method”.



Spurious Radiated Emissions Test Results (Continued)

Band Edge Field Strength Calculations in 802.11a mode (5150-5350 MHz)
Channels 36 & 64
Continuous TX at MAIN Antenna port with Hitachi Antennas
Aegis Labs, Inc. File #: INTEL-060407-13

RADIATED EMISSIONS - Horizontal Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
5150.00								64.50	74.00	-9.50
5150.00					A			51.06	54.00	-2.94
5350.00								64.97	74.00	-9.03
5350.00					A			50.72	54.00	-3.28
5352.50								66.13	74.00	-7.87
5352.50					A			49.05	54.00	-4.95

RADIATED EMISSIONS – Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
5150.00								63.54	74.00	-10.46
5150.00					A			50.18	54.00	-3.82
5350.00								64.30	74.00	-9.70
5350.00					A			49.44	54.00	-4.56
5352.50								65.46	74.00	-8.54
5352.50					A			47.77	54.00	-6.23

NOTE: The “Band Edge Field Strength” was calculated using the “Fundamental” and “Conducted Band Edge” measurements per the “Marker-Delta Method” with the following formula:

$$BE = F_m - \Delta m$$

Where

BE = Band Edge Field Strength


F_m = Measured Fundamental (Peak or Average)

Δ_m = Measured Conducted Band Edge Delta (Peak or Average)



Spurious Radiated Emissions Test Results (Continued)


Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)





Spurious Radiated Emissions Test Results (Continued)

Plots Showing Out-Of-Band Emissions (Peak RBW=VBW=1MHz; Average RBW = 1MHz, VBW = 10Hz)





Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11a mode (5150-5350 MHz)**Channels 36, 52, & 64****Continuous TX at MAIN Antenna port with Hitachi Antennas****Aegis Labs, Inc. File #: INTEL-060407-15****RADIATED EMISSIONS - Horizontal Antenna Polarization**

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 36 (5.18 GHz)										
3453.33	53.50	100	180			46.84	3.84	31.50	42.00	68.00 -26.00
10360.01	50.83	100	225			45.00	6.86	38.60	51.29	68.00 -16.71
EUT in Continuous Transmit Mode on Channel 52 (5.26 GHz)										
3506.66	53.33	100	180			46.85	3.87	31.62	41.97	68.00 -26.03
10520.00	50.50	100	225			45.05	6.93	38.61	50.99	68.00 -17.01
EUT in Continuous Transmit Mode on Channel 64 (5.32 GHz)										
3546.66	53.33	100	225			46.84	3.90	31.72	42.11	68.00 -25.89
10639.98	51.17	100	225			45.02	6.96	38.68	51.80	74.00 -22.20
10639.98				38.89	A	45.02	6.96	38.68	39.52	54.00 -14.48

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)	Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 36 (5.18 GHz)										
3453.33	53.67	100	180			46.84	3.84	31.52	42.18	68.00 -25.82
10360.02	52.00	100	180			45.00	6.86	38.80	52.66	68.00 -15.34
EUT in Continuous Transmit Mode on Channel 52 (5.26 GHz)										
3506.66	54.33	100	225			46.85	3.87	31.62	42.97	68.00 -25.03
10520.00	51.67	100	270			45.05	6.93	38.82	52.37	68.00 -15.63
EUT in Continuous Transmit Mode on Channel 64 (5.32 GHz)										
3546.66	54.17	100	225			46.84	3.90	31.72	42.95	68.00 -25.05
10639.98	51.83	100	225			45.02	6.96	38.91	52.68	74.00 -21.32
10639.98				39.18	A	45.02	6.96	38.91	40.03	54.00 -13.97



Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11a mode (5150-5350 MHz)*Channels 36, 52, & 64***Continuous TX at MAIN Antenna port with Hitachi Antennas***Aegis Labs, Inc. File #: INTEL-060407-16***RADIATED EMISSIONS - Horizontal Antenna Polarization**

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Cable Factor (dB)	Antenna/ Preamp Factor (dB)	Corrected Reading (dBuV/m)	Limits (dBuV/m)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 36 (5.18 GHz)										
20720.00	37.17	100	180			10.07	-3.36	43.88	74.00	-30.12
20720.00				24.42	A	10.07	-3.36	31.13	54.00	-22.87
EUT in Continuous Transmit Mode on Channel 52 (5.26 GHz)										
21040.00	38.50	100	180			10.20	-3.33	45.37	74.00	-28.63
21040.00				25.52	A	10.20	-3.33	32.39	54.00	-21.61
EUT in Continuous Transmit Mode on Channel 64 (5.32 GHz)										
21280.00	38.50	100	180			10.22	-3.38	45.34	74.00	-28.66
21280.00				25.35	A	10.22	-3.38	32.19	54.00	-21.81

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Cable Factor (dB)	Antenna/ Preamp Factor (dB)	Corrected Reading (dBuV/m)	Limits (dBuV/m)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 36 (5.18 GHz)										
20720.00	38.17	100	180			10.07	-3.29	44.96	74.00	-29.05
20720.00				24.78	A	10.07	-3.29	31.57	54.00	-22.44
EUT in Continuous Transmit Mode on Channel 52 (5.26 GHz)										
21040.00	38.00	100	180			10.20	-3.28	44.92	74.00	-29.08
21040.00				25.19	A	10.20	-3.28	32.11	54.00	-21.89
EUT in Continuous Transmit Mode on Channel 64 (5.32 GHz)										
21280.00	39.50	100	180			10.22	-3.24	46.49	74.00	-27.51
21280.00				26.44	A	10.22	-3.24	33.43	54.00	-20.57



Spurious Radiated Emissions Test Results (Continued)

Spurious Emissions Measurements in 802.11a mode (5150-5350 MHz)**Channels 36, 52, & 64****Continuous RX at MAIN Antenna port with Hitachi Antennas****Aegis Labs, Inc. File #: INTEL-060407-15****RADIATED EMISSIONS - Horizontal Antenna Polarization**

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 36 (5.18 GHz)											
3453.33	53.00	100	135			46.84	3.84	31.50	41.50	74.00	-32.50
3453.33				40.71	A	46.84	3.84	31.50	29.21	54.00	-24.79
EUT in Continuous Transmit Mode on Channel 52 (5.26 GHz)											
3506.66	53.17	125	135			46.85	3.87	31.62	41.81	74.00	-32.19
3506.66				40.85	A	46.85	3.87	31.62	29.49	54.00	-24.51
EUT in Continuous Transmit Mode on Channel 64 (5.32 GHz)											
3546.66	53.50	100	135			46.84	3.90	31.72	42.28	74.00	-31.72
3546.66				41.23	A	46.84	3.90	31.72	30.01	54.00	-23.99

RADIATED EMISSIONS - Vertical Antenna Polarization

Freq. (MHz)	Meter Reading (dBuV)	Antenna Height (cm)	Azimuth (degrees)	Quasi pk or AVG (dBuV)		Preamp Factor (dB)	Cable Factor (dB)	Ant. Factor (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Diff (dB) +=FAIL
EUT in Continuous Transmit Mode on Channel 36 (5.18 GHz)											
3453.33	53.17	100	135			46.84	3.84	31.52	41.68	74.00	-32.32
3453.33				40.84	A	46.84	3.84	31.52	29.35	54.00	-24.65
EUT in Continuous Transmit Mode on Channel 52 (5.26 GHz)											
3506.68	53.33	100	135			46.85	3.87	31.62	41.97	74.00	-32.03
3506.68				41.66	A	46.85	3.87	31.62	30.30	54.00	-23.70
EUT in Continuous Transmit Mode on Channel 64 (5.32 GHz)											
3546.66	53.67	100	135			46.84	3.90	31.72	42.45	74.00	-31.55
3546.66				41.97	A	46.84	3.90	31.72	30.75	54.00	-23.25

**PEAK TRANSMIT POWER**

CLIENT:	Dell Computer Corporation	DATE:	04/10/06
EUT:	XPS M2010 Notebook Computer	PROJECT NUMBER:	INTEL-060407
MODEL NUMBER:	PP03X	TEST ENGINEER:	BM/JC
SERIAL NUMBER:	2029658000002	SITE #:	2
CONFIGURATION:	Tested with an Intel PRO/Wireless 3945ABG Network Connection installed in its mini PCI-E slot.	TEMPERATURE:	15 C
		HUMIDITY:	64% RH
		TIME:	9:00 AM

Standard:	FCC CFR 47, Part 15.407(a)(1) & 15.407(a)(2)
Description:	For the band 5.15-5.25 GHz, the peak transmit power over the frequency band of operation shall not exceed the lesser of 50 mW or 4 dBm + 10logB, where B is the 26-dB emission bandwidth in MHz. For the band 5.25-5.35 GHz, the peak transmit power over the frequency band of operation shall not exceed the lesser of 250 mW or 11 dBm + 10logB, where B is the 26-dB emission bandwidth in MHz.
Results:	See Data Sheet

Peak Transmit Power Limits		
Frequency (MHz)	Output Power (mW)	Output Power (Note 1)
5150-5250	50 (17 dBm)	4 dBm + 10logB = 17.71 dBm @ 5180 MHz
5250-5350	250 (24 dBm)	11 dBm + 10logB = 24.73 dBm @ 5260 MHz 11 dBm + 10logB = 24.85 dBm @ 5320 MHz

Note 1: Calculated using the 26-dB emissions bandwidth measurements.



Peak Transmit Power (Continued)

Mode	Channel	Frequency (MHz)	Rate (Mbps)	Average Power (dBm)	Average Power (mW)	Peak Power (dBm)	Peak Power (mW)
802.11a	36	5180	6	16.08	40.55	16.60	45.71
802.11a	48	5240	6	16.19	41.59	16.70	46.77
802.11a	52	5260	6	17.30	53.70	18.50	70.79
802.11a	64	5320	6	17.11	51.40	18.30	67.61

Note: Power was measured conducted.

**CONDUCTED BAND EDGE EMISSIONS TEST RESULTS**

CLIENT:	Dell Computer Corporation	DATE:	04/11/06
EUT:	XPS M2010 Notebook Computer	PROJECT NUMBER:	INTEL-060407
MODEL NUMBER:	PP03X	TEST ENGINEER:	JC
SERIAL NUMBER:	2029658000002	SITE #:	2
CONFIGURATION:	Tested with an Intel PRO/Wireless 3945ABG Network Connection installed in its mini PCI-E slot.	TEMPERATURE:	17 C
		HUMIDITY:	50% RH
		TIME:	9:10 AM

Standard:	FCC CFR 47, Part 15.407(b)(2)
Description:	For transmitters operating in the 5.25-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5.25-5.35 GHz band that generate emissions in the 5.15-5.25 GHz band must meet all applicable technical requirements for operation in the 5.15-5.25 GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5.15-5.25 GHz band.
Results:	Passes (See Data Sheets)

Unwanted Spurious Emissions Limits


Frequency (MHz)	Field Strength (dBm/MHz) (Emissions outside the restricted bands)
5250-5350	EIRP < -27dBm/MHz (68.3dBuV/m)

<i>Freq. (MHz)</i>	<i>Power Spec Den. Reading (dBm/MHz)</i>	<i>Antenna Gain (dBi)</i>	<i>Corrected Reading (dBm/MHz)</i>	<i>Limits (dBm/MHz)</i>	<i>Diff (dB) +=FAIL</i>	<i>Comments</i>
With Amphenol Antenna Gain at 5 GHz						
5250.00	-31.10	2.36	-28.74	-27.00	-1.74	Tx @ 5240 MHz
5250.00	-30.60	2.36	-28.24	-27.00	-1.24	Tx @ 5260 MHz
With Hitachi Antenna Gain at 5 GHz						
5250.00	-31.10	2.10	-29.00	-27.00	-2.00	Tx @ 5240 MHz
5250.00	-30.60	2.10	-28.50	-27.00	-1.50	Tx @ 5260 MHz



Conducted Band Edge Emissions Test Results (Continued)

Plots Showing Power Spectral Densities





AEGIS LABS INC.

26-dB EMISSIONS BANDWIDTH

CLIENT:	Dell Computer Corporation	DATE:	04/11/06
EUT:	XPS M2010 Notebook Computer	PROJECT NUMBER:	INTEL-060407
MODEL NUMBER:	PP03X	TEST ENGINEER:	JC
SERIAL NUMBER:	2029658000002	SITE #:	2
CONFIGURATION:	Tested with an Intel PRO/Wireless 3945ABG Network Connection installed in its mini PCI-E slot.	TEMPERATURE:	17 C
		HUMIDITY:	50% RH
		TIME:	9:10 AM


Standard:	FCC CFR 47, Part 15.407(a)(1) & 15.407(a)(2)
Description:	26-dB emission bandwidth in MHz
Results:	See Data Sheets

Page 30 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG



AEGIS LABS INC.

26-dB Emissions Bandwidth (Continued)




Page 31 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG



AEGIS LABS INC.

26-dB Emissions Bandwidth (Continued)



Page 32 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG

**PEAK POWER SPECTRAL DENSITY**

CLIENT:	Dell Computer Corporation	DATE:	04/11/06
EUT:	XPS M2010 Notebook Computer	PROJECT NUMBER:	INTEL-060407
MODEL NUMBER:	PP03X	TEST ENGINEER:	JC
SERIAL NUMBER:	2029658000002	SITE #:	2
CONFIGURATION:	Tested with an Intel PRO/Wireless 3945ABG Network Connection installed in its mini PCI-E slot.	TEMPERATURE:	17 C
		HUMIDITY:	50% RH
		TIME:	9:10 AM

Standard:	FCC CFR 47, Part 15.407(a)(1) & 15.407(a)(2)
Description:	For the band 5.15-5.25 GHz, the peak power spectral density shall not exceed 4 dBm in any 1-MHz band
	For the band 5.2 5-5.35 GHz, the peak power spectral density shall not exceed 11 dBm in any 1-MHz band
Results:	See Data Sheets


Peak Power Spectral Density Limits	
Frequency (MHz)	Limit (dBm)
5150-5250	4
5250-5350	11

Using “Method 2” of the FCC Public Notice (DA 02-2138)



AEGIS LABS INC.

Peak Power Spectral Density (Continued)




Page 34 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG



AEGIS LABS INC.

Peak Power Spectral Density (Continued)




Page 35 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG



AEGIS LABS INC.

Peak Power Spectral Density (Continued)



Page 36 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG

**PEAK EXCURSION**

CLIENT:	Dell Computer Corporation	DATE:	04/11/06
EUT:	XPS M2010 Notebook Computer	PROJECT NUMBER:	INTEL-060407
MODEL NUMBER:	PP03X	TEST ENGINEER:	JC
SERIAL NUMBER:	2029658000002	SITE #:	2
CONFIGURATION:	Tested with an Intel PRO/Wireless 3945ABG Network Connection installed in its mini PCI-E slot.	TEMPERATURE:	17 C
		HUMIDITY:	50% RH
		TIME:	9:10 AM


Standard:	FCC CFR 47, Part 15.407(a)(6)
Description:	The ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the peak transmit power shall not exceed 13 dB across any 1 MHz bandwidth or the emission bandwidth whichever is less.
Results:	See Data Sheets

Peak Excursion Limits	
Frequency (MHz)	Limit (dB)
5150-5350	13



AEGIS LABS INC.

Peak Excursion (Continued)




Page 38 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG



AEGIS LABS INC.

Peak Excursion (Continued)



Page 39 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG

**CONDUCTED OUT OF BAND EMISSIONS**


CLIENT:	Dell Computer Corporation	DATE:	04/11/06
EUT:	XPS M2010 Notebook Computer	PROJECT NUMBER:	INTEL-060407
MODEL NUMBER:	PP03X	TEST ENGINEER:	JC
SERIAL NUMBER:	2029658000002	SITE #:	2
CONFIGURATION:	Tested with an Intel PRO/Wireless 3945ABG Network Connection installed in its mini PCI-E slot.	TEMPERATURE:	17 C
		HUMIDITY:	50% RH
		TIME:	9:10 AM

Standard:	FCC CFR 47, Part 15.407(b)(1) and 15.407(b)(2)
Description:	For transmitters operating in the 5.15-5.25 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. For transmitters operating in the 5.25-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5.25-5.35 GHz band that generate emissions in the 5.15-5.25 GHz band must meet all applicable technical requirements for operation in the 5.15-5.25 GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5.15-5.25 GHz band.



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)




Page 41 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)





Page 42 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)



Test Date	Data	Test Eng.
04/11/06	5.18 GHz (INTEL-060407-04e5)	JC
*ATTEN 10dB RL 12.0dBm 10dB/ MKR -40.67dBm 36.87GHz  START 20.00GHz STOP 40.00GHz *RBW 1.0MHz *VBW 1.0MHz SWP 400ms 		
Test Date	Data	Test Eng.
04/11/06	5.26 GHz (INTEL-060407-04e06)	JC
*ATTEN 10dB RL 12.0dBm 10dB/ MKR -54.17dBm 597.5MHz  START 30.0MHz STOP 1.0000GHz *RBW 1.0MHz *VBW 1.0MHz SWP 50.0ms 		

Page 43 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)


Test Date	Data	Test Eng.
04/11/06	5.26 GHz (INTEL-060407-04e07)	JC
*ATTEN 10dB RL 12.0dBm 10dB/ MKR -43.67dBm 5.045GHz  START 1.000GHz STOP 5.150GHz *RBW 1.0MHz *VBW 1.0MHz SWP 83.0ms 		
Test Date	Data	Test Eng.
04/11/06	5.26 GHz (INTEL-060407-04e08)	JC
*ATTEN 10dB RL 12.0dBm 10dB/ MKR -45.67dBm 5.435GHz  START 5.350GHz STOP 10.000GHz *RBW 1.0MHz *VBW 1.0MHz SWP 93.0ms 		

Page 44 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)





Page 45 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)


Test Date	Data	Test Eng.
04/11/06	5.32 GHz (INTEL-060407-04e11)	JC
*ATTEN 10dB RL 12.0dBm 10dB/ MKR -54.50dBm 332.3MHz  START 30.0MHz STOP 1.0000GHz *RBW 1.0MHz *VBW 1.0MHz SWP 50.0ms 		
Test Date	Data	Test Eng.
04/11/06	5.32 GHz (INTEL-060407-04e12)	JC
*ATTEN 10dB RL 12.0dBm 10dB/ MKR -42.17dBm 5.123GHz  START 1.000GHz STOP 5.250GHz *RBW 1.0MHz *VBW 1.0MHz SWP 85.0ms 		

Page 46 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG



AEGIS LABS INC.

Conducted Out Of Band Emissions (Continued)



Page 47 of 48 (Appendix A)
Report Number: INTEL-060408F
FCC ID: E2KWM3945ABG



Conducted Out Of Band Emissions (Continued)

