

According to Appendix B of 447498 D04 Interim General RF Exposure Guidance v01, the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula.

P_{th} is given by:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

The separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz.

P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distances (cm).

Limbs SAR

Tx Interface	Frequency (GHz)	Output Power		Antenna Gain (dBi)	ERP (dBm)	ERP Threshold (mW)	Separation Distances (cm)	P_{th} (mW)	Exemption result
		dBm	mW						
SRD2.4G	2.405	3.5	2	2.84	4.19	2.62	0.5	6.96	-EXEMPT-
BLE	2.402	3.5	2	3.11	4.46	2.79	0.5	6.97	-EXEMPT-

Note:

1. The SRD2.4G tune up power referred the AVG power of the test report **TMWK2506002446KR** for SAR test exclusion purpose.
2. The BLE tune up power referred the AVG power of the test report **TMWK2506002444KR** for SAR test exclusion purpose.