

# **FCC RF EXPOSURE REPORT**

**FCC ID: EMOB67**

**Project No. : 1605C137**  
**Equipment : Bluetooth Speaker**  
**Test Model : Ni-B67RP**  
**Serial Model : Ni-B67LN, Wi-B67GD, Wi-B67PY**  
**Applicant : SDI TECHNOLOGIES INC.**  
**Address : 1299 Main Street, Rahway, NJ 07065, U.S.A**

**According: : FCC Guidelines for Human Exposure IEEE C95.1**

**B T L I N C .**

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.  
TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

Table for Filed Antenna

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	Printed	N/A	0

## GENERAL CONCLUSION:

Maximum measured transmitter power:

OutputPower (dBm)	Output Power (mW)	Limit (mW)
2.18	1.65	10

According to FCC KDB447498 V06, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and  $\leq 50$  mm

The maximum measured output peak power of this EUT is 1.65mW, less than 10mW at 5mm distance.

**Conclusion: No SAR evaluation required since transmitter power is below FCC threshold**