

FCC RF EXPOSURE REPORT

FCC ID: EMOIBT18

Project No. : 1512C056

**Equipment : BT Alarm Clock Speaker with Speakerphone
and USB charging**

**Model : iBT18, iBT18X, iBT18XC ("X"= a to Z; denote
as color of cabinet)**

Applicant : SDI TECHNOLOGIES INC.

Address : 1299 Main Street, Rahway, NJ 07065, U.S.A

**According: : FCC Guidelines for Human Exposure IEEE
C95.1**

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

Table for Filed Antenna

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	PIFA	N/A	0

GENERAL CONCULSION:

Maximum measured transmitter power:

Output Power (dBm)	Output Power (mW)	Limit (mW)
5.65	3.7	10

According to FCC KDB447498 V05, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and \leq 50 mm

The maximum measured output peak power of this EUT is 3.7mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold