

RF EXPOSURE Test Report

Product: Wireless Triple Mag Charging Travel
Clock

Trade Mark: iHome

Model Number: iWW7B.EXv25

FCC ID: EMOIWW7A

Prepared for

SDI Technologies Inc.

1299 Main St. Rahway, New Jersey United States 07065

Prepared by

Shenzhen HongBiao Certification& Testing Co., Ltd

Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan
Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen,
China

Tel.: +86-755-2998 9321 Fax.: +86-755-2998 5110

Website: <http://www.sz-hongbiao.com>

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	DESCRIPTION OF EUT	5
1.2	TEST MODE.....	5
1.3	TEST SETUP	6
1.4	ANCILLARY EQUIPMENT	6
2	TEST FACILITIES AND ACCREDITATIONS	7
2.1	TEST LABORATORY	7
2.2	ENVIRONMENTAL CONDITIONS	7
2.3	MEASUREMENT UNCERTAINTY	7
2.4	TEST SOFTWARE	7
3	LIST OF TEST EQUIPMENT	8
4	RF EXPOSURE.....	9
4.1	MAXIMUM PERMISSIBLE EXPOSURE	9
4.1.1.	<i>Limit</i>	9
4.1.2.	<i>Test Procedures</i>	9
4.1.3.	<i>Test Setup</i>	9
4.1.4.	<i>Test Result</i>	9
5	PHOTOGRAPHS OF THE TEST SETUP.....	12

TEST RESULT CERTIFICATION

Applicant's Name..... : SDI Technologies Inc.

Address : 1299 Main St. Rahway, New Jersey United States 07065

Manufacturer's Name : SDI Technologies Inc.

Address : 1299 Main St. Rahway, New Jersey United States 07065

Product description

Product name : Wireless Triple Mag Charging Travel Clock

Model Number : iWW7B.EXv25

Standards : FCC CFR 47 PART 1 , 1.1310

Test procedure..... : KDB 680106 D01 Wireless Power Transfer v04


This device described above has been tested by Shenzhen HongBiao Certification& Testing Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the EMC requirements. And it is applicable only to the tested sample identified in the report.

Date of Test:

Date (s) of performance of tests: July 21, 2025~ Aug. 01, 2025

Test Result.....: **Pass**

Testing Engineer :




(Z o e S u)

Technical Manager :



(G a r y L u)

Authorized Signatory :



(L e o S u)

[illegible]

1 General Description

1.1 Description of EUT

Product name:	Wireless Triple Mag Charging Travel Clock
Model name:	iWW7B.EXv25
Series Model:	iWW7X
Different of series model:	All the models are the same circuit and module, except the model No.. iWW7X (X could be single or multiple digits by any alphabets and punctuation marks denoting different year version, buyers and cabinet colors)
Operation frequency:	Phone: 110.5kHz-205kHz, 360kHz Airpods: 110.5kHz-205kHz Watch: 328kHz
Operational mode:	Wireless charging
Modulation type:	ASK
Antenna type:	Coil Antenna
Hardware version:	V1.0
Software version:	V1.0
Battery:	N/A
Power supply:	Input: DC 9V/3A Wireless Output(Phone): 15W Max Wireless Output(Airpods): 5W Max Wireless Output(Watch): 2.5W Max
Adapter information:	Model: SG-PA34MU Input: 100-240V~ 50/60Hz 1.0A MAX Output: QC2.0: 5.0V=3.0A, 9.0V=3.0A, 12.0V=2.5A, 20.0V=1.75A QC3.0: 3.6V-9.0V=3.0A, 9.1V-120V=2.5A, 12.1V-15.8V=2.0A(35.0W MAX)

1.2 Test Mode

Pretest Test Mode	Description of Mode
1	AC/DC adapter+Wireless Output (Phone:5W+ Airpods:5W+Watch:2.5W)
2	AC/DC adapter+Wireless Output (Phone:7.5W+ Airpods:5W+Watch:2.5W)
3	AC/DC adapter+Wireless Output (Phone:10W+ Airpods:5W+Watch:2.5W)

4	AC/DC adapter+Wireless Output (Phone:15W+ Airpods:5W+Watch:2.5W)
---	---

1.3 Test Setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

1.4 Ancillary Equipment

Equipment	Model	S/N	Manufacturer
Phone	iPhone 16pro	HMV3W3W19W	Apple Inc
Airpods	A2031	H04F3NS0LX2Y	Apple Inc.
Watch	A2859	M69PQQ7J2T	Apple Inc.

2 Test Facilities and Accreditations

2.1 Test Laboratory

Test Site	Shenzhen HongBiao Certification& Testing Co., Ltd
Test Site Location	Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen, China
Telephone:	(86-755) 2998 9321
Fax:	(86-755) 2998 5110
FCC Registration No.:	CN1341
A2LA Certificate No.:	6765.01

2.2 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C~35°C
Relative Humidity:	20%~75%
Air Pressure:	98kPa~101kPa

2.3 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

The data and results quoted in this document are true and accurate values, and uncertainties are not involved in the calculations.

In addition, components and mass production processes that are similar to testing equipment may introduce additional deviations, and the manufacturer is solely responsible for the continued compliance of the equipment.

Measurement Frequency Range	U, (dB)	Note
RF frequency	2×10^{-5}	
E-field	± 2.5 dB	
H-field	± 4.2 dB	
Temperature	± 1 degree	
Humidity	± 5 %	

2.4 Test Software

Software name	Manufacturer	Model	Version
EHP200-TS	Narda	EHP-200A	Rel 1.95

3 List of Test Equipment

Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E073	Electric and Magnetic Field Analyzer	Narda	EHP-200A	180ZX11013	2025-05-10	2026-05-09

Note: the calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

4 RF Exposure

4.1 Maximum Permissible Exposure

4.1.1. Limit

Frequency range(MHz)	Electric field strength(V/m)	Magnetic field strength(A/m)	Power density(mW/cm2)	Averaging time(minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0 6	6
300-1500	/	/	f/300	6
1500-100000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100000	/	/	1	30

f = frequency in MHz * = Plane-wave equivalent power density


4.1.2. Test Procedures

E and H-field measurements should be made with the center of the probe at a distance of 20 cm surrounding the device and 20 cm above the top surface of the primary/client pair.

These measurements should be repeated for three different client battery levels, 1%, 50%, and 99%.

Record the test results.

4.1.3. Test Setup



4.1.4. Test Result

Test condition: Mode 3 operating mode with client device (1 %, 50%, 99% battery status of client device)

Maximum permissible Exposure (Phone: 110.5kHz-205kHz+ AirPods: 110.5kHz-205kHz+Watch: 328kHz)				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<1%	Top	20	1.0482	0.0456
<1%	Left	20	0.4724	0.0454
<1%	Right	20	0.6268	0.0454
<1%	Front	20	0.6362	0.0470
<1%	Back	20	0.4347	0.0557
Limit			614	1.63
Margin Limit (%)			0.17%	3.42%

Maximum permissible Exposure (Phone: 110.5kHz-205kHz+ AirPods: 110.5kHz-205kHz+Watch: 328kHz)				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<50%	Top	20	1.0475	0.0449
<50%	Left	20	0.4716	0.0446
<50%	Right	20	0.6260	0.0445
<50%	Front	20	0.6354	0.0461
<50%	Back	20	0.4341	0.0548
Limit			614	1.63
Margin Limit (%)			0.17%	3.36%

Maximum permissible Exposure (Phone: 110.5kHz-205kHz+ AirPods: 110.5kHz-205kHz+Watch: 328kHz)				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<99%	Top	20	1.0467	0.0440
<99%	Left	20	0.4708	0.0438
<99%	Right	20	0.6253	0.0437
<99%	Front	20	0.6345	0.0454
<99%	Back	20	0.4337	0.0540
Limit			614	1.63
Margin Limit (%)			0.17%	3.31%

Test condition: Mode 4 operating mode with client device (1 %, 50%, 99% battery status of client device)

Maximum permissible Exposure (Phone: 360kHz+Airpods: 110.5kHz-205kHz+Watch: 328kHz)				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<1%	Top	20	2.7586	0.0470
<1%	Left	20	1.2168	0.0501
<1%	Right	20	1.0336	0.0456
<1%	Front	20	1.6560	0.0554
<1%	Back	20	0.7352	0.0454
Limit			614	1.63
Margin Limit (%)			0.45%	3.40%

Maximum permissible Exposure (Phone: 360kHz+Airpods: 110.5kHz-205kHz+Watch: 328kHz)				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<50%	Top	20	2.7580	0.0461
<50%	Left	20	1.2161	0.0495
<50%	Right	20	1.0328	0.0448
<50%	Front	20	1.6553	0.0545
<50%	Back	20	0.7347	0.0445
Limit			614	1.63
Margin Limit (%)			0.45%	3.34%

Maximum permissible Exposure (Phone: 360kHz+Airpods: 110.5kHz-205kHz+Watch: 328kHz)				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<99%	Top	20	2.7572	0.0452
<99%	Left	20	1.2155	0.0484
<99%	Right	20	1.0319	0.0440
<99%	Front	20	1.6545	0.0534
<99%	Back	20	0.7341	0.0436
Limit			614	1.63
Margin Limit (%)			0.45%	3.28%

5 Photographs of the Test Setup

MPE



***** END OF REPORT *****