

SDI Technologies Inc.

Application
For
Certification
(FCC ID: EMOT150)

Superheterodyne Receiver

WO# 0101086

DY/sc

March 1, 2001

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report shall not be reproduced except in full without prior authorization from Intertek Testing Services Hong Kong Limited

Intertek Testing Services Hong Kong Ltd.
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2745 8306

FCC ID: EMOT150

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report shall not be reproduced except in full without prior authorization from Intertek Testing Services Hong Kong Limited
- For Terms And Conditions of the services, it can be provided upon request.

Intertek Testing Services Hong Kong Ltd.
2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2713 8888 Fax: (852) 2745 8306

INTERTEK TESTING SERVICES

LIST OF EXHIBITS

INTRODUCTION

| | |
|-------------------|---------------------------|
| <i>EXHIBIT 1:</i> | General Description |
| <i>EXHIBIT 2:</i> | System Test Configuration |
| <i>EXHIBIT 3:</i> | Emission Results |
| <i>EXHIBIT 4:</i> | Equipment Photographs |
| <i>EXHIBIT 5:</i> | Product Labelling |
| <i>EXHIBIT 6:</i> | Technical Specifications |
| <i>EXHIBIT 7:</i> | Instruction Manual |
| <i>EXHIBIT 8:</i> | Miscellaneous Information |

INTERTEK TESTING SERVICES

MEASUREMENT/TECHNICAL REPORT

**SDI Technologies Inc. - MODEL: TIMEX T-150'X'
FCC ID: EMOT150**

This report concerns (check one): Original Grant Class II Change

Equipment Type: Superheterodyne Receiver (example: computer, printer, modem, etc.)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes No

If yes, defer until: _____
date

Company Name agrees to notify the Commission by: _____
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes No

If no, assumed Part 15, Subpart B for unintentional radiator - the new 47 CFR [10-1-96 Edition] provision.

Report prepared by:

Daniel Yau
Intertek Testing Services
Hong Kong Ltd.
2/F., Garment Centre,
576, Castle Peak Road,
Kowloon, Hong Kong
Phone: 852-2173-8542
Fax: 852-2371-0914

INTERTEK TESTING SERVICES

Table of Contents

| | |
|--|----|
| 1.0 General Description | 2 |
| 1.1 Product Description..... | 2 |
| 1.2 Related Submittal(s) Grants..... | 2 |
| 1.3 Test Methodology..... | 3 |
| 1.4 Test Facility | 3 |
| 2.0 System Test Configuration | 5 |
| 2.1 Justification..... | 5 |
| 2.2 EUT Exercising Software | 5 |
| 2.3 Special Accessories | 5 |
| 2.4 Equipment Modification..... | 6 |
| 2.5 Support Equipment List and Description | 6 |
| 3.0 Emission Results | 8 |
| 3.1 Field Strength Calculation | 9 |
| 3.1 Field Strength Calculation (cont'd) | 10 |
| 3.2 Radiated Emission Configuration Photograph | 11 |
| 3.3 Radiated Emission Data | 12 |
| 3.4 Conducted emission Configuration Photograph..... | 15 |
| 3.5 Conducted Emission Data | 17 |
| 4.0 Equipment Photographs | 19 |
| 5.0 Product Labelling | 21 |
| 6.0 Technical Specifications | 23 |
| 7.0 Instruction Manual | 25 |
| 8.0 Miscellaneous Information | 27 |
| 8.1 Discussion of Pulse Desensitization | 28 |
| 8.2 Calculation of Average Factor | 29 |
| 8.3 Emissions Test Procedures | 30 |
| 8.3 Emissions Test Procedures (cont'd)..... | 31 |

INTERTEK TESTING SERVICES

List of attached file

| Exhibit type | File Description | filename |
|-----------------------|--------------------------------|--|
| Cover Letter | Letter of Agency | letter.pdf |
| Test Report | Test Report | report.doc |
| Operation Description | Technical Description | descri.pdf |
| Test Setup Photo | Radiated Emission | radiated1.jpg, radiated2.jpg |
| Test Setup Photo | Conducted Emission | conduct1.jpg, conduct2.jpg, conduct3.jpg |
| Test Report | Conducted Emission Test Result | conduct.pdf |
| External Photo | External Photo | ophoto1.jpg, ophoto2.jpg, ophoto3.jpg |
| Internal Photo | Internal Photo | iphoto1.jpg, iphoto2.jpg, iphoto3.jpg, iphoto4.jpg, iphoto5.jpg. |
| Block Diagram | Block Diagram | block.pdf |
| Schematics | Circuit Diagram | circuit.pdf |
| ID Label/Location | Label Artwork and Location | label.pdf |
| User Manual | User Manual | manual.pdf |

INTERTEK TESTING SERVICES

EXHIBIT 1

GENERAL DESCRIPTION

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The equipment under test (EUT) is a weather band radio with nature sound and alarm clock function. The operating frequency of the weather band is from 162.40 to 162.55 MHz. The EUT is powered by 120V AC/DC adaptor or three 'AA' size batteries. At the front panel of the EUT, it consists of four nature sound buttons, time setting and weather band on/off buttons, and the weather band channels selector and volume control knob are located at the side panel. This EUT is designed to receive the weather information broadcasting from local weather band stations. And, the nature sound function is mainly for relaxation purpose.

For electronic filing, the brief circuit description is saved with filename: descri.pdf

1.2 Related Submittal(s) Grants

This is a single application for certification of a receiver.

INTERTEK TESTING SERVICES

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (1992). Radiated measurement was performed in an Open Area Test Site and Conducted Emission measurement was performed in Shield Room. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. For each scan, the procedure for maximizing emissions in Appendices D and E were followed. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

EXHIBIT 2

SYSTEM TEST CONFIGURATION

INTERTEK TESTING SERVICES

2.0 System Test Configuration

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSIC63.4 (1992).

The EUT is powered by 120VAC/DC adaptor or three 'AA' size batteries.

The unit was placed in the center of the turntable. For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. The step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

2.2 EUT Exercising Software

There was no special software to exercise the device. Once the weather band function is turned on, it received the weather information from weather broadcast station continuously.

2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

INTERTEK TESTING SERVICES

2.4 Equipment Modification

Any modifications installed previous to testing by SDI Technologies Inc. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services.

2.5 Support Equipment List and Description

AC/DC Adaptor

Model: U060035D

Input: AC 120V

Output: DC 6V 350mA

(Provided by client)

All the items listed under section 2.0 of this report are:


Confirmed by:

Daniel Yau

Technical Manager - Home Entertainment Electronics

Intertek Testing Services Hong Kong Ltd.

Agent for SDI Technologies Inc.



Signature

March 1, 2001
Date

EXHIBIT 3

EMISSION RESULTS

INTERTEK TESTING SERVICES

3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

INTERTEK TESTING SERVICES

3.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in dB μ V/m

RA = Receiver Amplitude (including preamplifier) in dB μ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

INTERTEK TESTING SERVICES

3.1 Field Strength Calculation (cont'd)

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$AV = -10 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V/m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm} [(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \text{ } \mu\text{V/m}$$

INTERTEK TESTING SERVICES

3.2 Radiated Emission Configuration Photograph

**Worst Case Radiated Emission
at
404.116 MHz**

For electronic filing, the front view and back view of the test configuration photographs are saved with filename: radiated1.jpg and radiated2.jpg respectively.

INTERTEK TESTING SERVICES

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 6.7 dB margin

TEST PERSONNEL:



Signature

Prudence S. M. Poon, Compliance Engineer
Typed/Printed Name

March 1, 2001
Date

INTERTEK TESTING SERVICES

Company: SDI Technologies Inc.

Date of Test: February 19, 2001

Model: TIMEX T-150'X'

Operating mode: Weather Band

Table 1
Radiated Emissions

| Polarity | Frequency (MHz) | Reading (dB μ V/m) | Antenna Factor (dB) | Pre-Amp (dB) | Net at 3m (dB μ V/m) | Limit at 3m (dB μ V/m) | Margin (dB) |
|----------|--------------------|---------------------------|---------------------------|-----------------|--------------------------------|----------------------------------|----------------|
| V | 81.046 | 32.9 | 6.7 | 16.0 | 23.6 | 40.0 | -16.4 |
| H | 129.678 | 28.5 | 12.6 | 16.0 | 25.1 | 43.5 | -18.4 |
| H | 145.890 | 29.1 | 11.6 | 16.0 | 24.7 | 43.5 | -18.8 |
| H | 162.087 | 37.5 | 13.1 | 16.0 | 34.6 | 43.5 | -8.9 |
| H | 178.017 | 25.4 | 15.5 | 16.0 | 24.9 | 43.5 | -18.6 |
| H | 194.514 | 26.5 | 17.1 | 16.0 | 27.6 | 43.5 | -15.9 |
| H | 210.881 | 31.0 | 11.8 | 16.0 | 26.8 | 43.5 | -16.7 |
| H | 243.135 | 27.0 | 11.4 | 16.0 | 22.4 | 46.0 | -23.6 |
| H | 307.984 | 26.5 | 14.3 | 16.0 | 24.8 | 46.0 | -21.2 |
| H | 324.179 | 26.7 | 14.3 | 16.0 | 25.0 | 46.0 | -21.0 |
| H | 358.314 | 31.5 | 14.9 | 16.0 | 30.4 | 46.0 | -15.6 |
| H | 372.318 | 38.0 | 14.9 | 16.0 | 36.9 | 46.0 | -9.1 |
| H | 394.386 | 39.3 | 15.4 | 16.0 | 38.7 | 46.0 | -7.3 |
| H | 404.116 | 39.3 | 15.9 | 16.0 | 39.2 | 46.0 | -6.8 |
| H | 465.332 | 22.4 | 16.8 | 16.0 | 23.2 | 46.0 | -22.8 |

NOTES: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna and average detector are used for the emission over 1000MHz.

The corresponding limit as per 15.109 is based on Quasi peak detector data for frequencies below 1000 MHz and average detector data for frequencies over 1000 MHz.

INTERTEK TESTING SERVICES

Test Engineer: Prudence S. M. Poon

Company: SDI Technologies Inc.

Date of Test: February 19, 2001

Model: TIMEX T-150'X'

Operating mode: Sound mode

Table 2
Radiated Emissions

| Polarity | Frequency (MHz) | Reading (dB μ V/m) | Antenna Factor (dB) | Pre-Amp Gain (dB) | Net at 3m (dB μ V/m) | Limit at 3m (dB μ V/m) | Margin (dB) |
|----------|--------------------|---------------------------|---------------------------|-------------------------|--------------------------------|----------------------------------|----------------|
| V | 81.046 | 32.9 | 6.7 | 16.0 | 23.6 | 40.0 | -16.4 |
| H | 129.678 | 30.2 | 12.6 | 16.0 | 26.8 | 43.5 | -16.7 |
| H | 145.890 | 28.7 | 11.6 | 16.0 | 24.3 | 43.5 | -19.2 |
| H | 162.087 | 37.9 | 13.1 | 16.0 | 35.0 | 43.5 | -8.5 |
| H | 178.017 | 25.6 | 15.5 | 16.0 | 25.1 | 43.5 | -18.4 |
| H | 194.514 | 26.9 | 17.1 | 16.0 | 28.0 | 43.5 | -15.5 |
| H | 210.881 | 30.1 | 11.8 | 16.0 | 25.9 | 43.5 | -17.6 |
| H | 243.135 | 27.6 | 11.4 | 16.0 | 23.0 | 46.0 | -23.0 |
| H | 307.984 | 25.6 | 14.3 | 16.0 | 23.9 | 46.0 | -22.1 |
| H | 324.179 | 26.0 | 14.3 | 16.0 | 24.3 | 46.0 | -21.7 |
| H | 358.314 | 31.7 | 14.9 | 16.0 | 30.6 | 46.0 | -15.4 |
| H | 372.318 | 37.3 | 14.9 | 16.0 | 36.2 | 46.0 | -9.8 |
| H | 394.386 | 38.6 | 15.4 | 16.0 | 38.0 | 46.0 | -8.0 |
| H | 404.116 | 39.4 | 15.9 | 16.0 | 39.3 | 46.0 | -6.7 |
| H | 465.332 | 22.4 | 16.8 | 16.0 | 23.2 | 46.0 | -22.8 |

NOTES:

1. Peak Detector Data unless otherwise stated.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna and average detector are used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

The corresponding limit as per 15.109 is based on Quasi peak detector data for frequencies below 1000 MHz and average detector data for frequencies over 1000 MHz.

Test Engineer: Prudence S. M. Poon

INTERTEK TESTING SERVICES

3.4 Conducted Emission Configuration Photograph

**Worst Case Conducted Emission
at
16.200 MHz**

For electronic filing, the front view, rear view and side view of the test configuration photographs are saved with filename: conduct1.jpg, conduct2.jpg and conduct3.jpg.

INTERTEK TESTING SERVICES

Company: SDI Technologies Inc.

Date of Test: February 19, 2001

Model: TIMEX T-150'X'

Worst case operating model: weather band

Conducted Emissions Section 15.107 Requirements

For Electronic filing, the conducted emission test result is saved with filename: conduct.pdf

INTERTEK TESTING SERVICES

3.5 Conducted Emission Data

For electronic filing, the graph and data table of conducted emission are saved with filename: conduct.pdf. The data table lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgement: Passed by 18.6 dB margin

* Peak Detector Data Unless otherwise stated.

TEST PERSONNEL:



Signature

Prudence S. M. Poon, Compliance Engineer
Typed/Printed Name

March 1, 2001
Date

EXHIBIT 4

EQUIPMENT PHOTOGRAPHS

INTERTEK TESTING SERVICES

4.0 Equipment Photographs

For electronic filing, photographs of the tested EUT are saved with filename: ophoto1.jpg to ophoto3.jpg for external photo, and iphoto1.jpg to iphoto5.jpg for internal photo.

EXHIBIT 5

PRODUCT LABELLING

INTERTEK TESTING SERVICES

5.0 Product Labelling

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

EXHIBIT 6

TECHNICAL SPECIFICATIONS

INTERTEK TESTING SERVICES

6.0 Technical Specifications

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

EXHIBIT 7

INSTRUCTION MANUAL

INTERTEK TESTING SERVICES

7.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

EXHIBIT 8

MISCELLANEOUS INFORMATION

INTERTEK TESTING SERVICES

8.0 Miscellaneous Information

This miscellaneous information includes details of the test procedure and calculation of factors such as pulse desensitization and averaging factor.

INTERTEK TESTING SERVICES

8.1 Discussion of Pulse Desensitization

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

This device is a superheterodyne receiver. The emission are continuous, and no desensitization of the measurement equipment occurs.

INTERTEK TESTING SERVICES

8.2 Calculation of Average Factor

This device is a superheterodyne receiver.

It is not necessary to apply average factor to the measurement results.

INTERTEK TESTING SERVICES

8.3 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of Superheterodyne Receivers operating under the Part 15, Subpart B rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 - 1992.

The equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the groundplane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.2.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 450 kHz to 30 MHz.

INTERTEK TESTING SERVICES

8.3 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 - 1992.

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Measurements are normally conducted at a measurement distance of three meters. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.