VM5251-2 Full Color Video Monitor BC

VM5251



## vtech User's manual

### CONGRATULATIONS

♣ WHAT'S IN THE BOX







TECHNICAL SPECIFICATIONS



## IMPORTANT SAFETY INSTRUCTIONS

- Continue

  The continue of the product of a continue of the con

Electromagnetic fields (EMF)
This VTech product complies with all standards regarding electromagnetic fields (EMF). If handled properly and a his instruction in this user's manual, the product it take to be used bleed on scientific evidence available boday.

# CONNECT AND CHARGE THE BATTERY



ATTERS MICHARDS 

Be bittery can set find with the property of the property of the bittery of th

## BEFORE USE

O CAUTION

In the harding practices, make one the general only in more particularly, make a property of the harding practices, make the particular of the three particular only high problem falses, shown the particular of the three particular only the particular of the particular of

1. If you believe how believe him to state your NEW on your parent with. The sort NEW of You and you want to the sort of the NOTE you want to the sort of the NOTE you want to the NOTE of you want to the NOTE of your favour, make the parent would use to the NOTE of your favour, make the parent would not be the NOTE of You want to the You want to the

## USING THE BABY MONITOR

• Frest W. ② or ③ v. Q. co. the parent unit at any time when viewin For baby unit.
The baby unit speaker volume determines the fulley volume and transmitted from parent unit. It can be adjusted in the parent unit.
1. Prices MRNU when the parent unit is die.
2. Prices WRNU when the parent unit is die.
2. Prices WRNU when the parent unit is die.
3. Prices V. A. or A. Concor Volume and CAM. then prices ELECT.
3. Prices V. A. or A. Concor Volume and Volume level, Level 1 is the John MRNU when the WRNU when the Volume and V







Adjust LCD brightness
You can charge the brightness of the parent unit screen from Level 1 to Level 5. The LCD
brightness pripare to Level 5. The LCD
brightness pripare to Level 3. The LCD
brightness pripare to LCD the parent unit side.
1. Prices MIND when the parent unit side.
1. Prices VIA 1 to Chost LCD, their prices SELECT.
4. Prices VIA to Choste The desired level of brightness, then prices SELECT to confirm youlded from the Choste The Choste

## Turn on and off the dim mode

ressen on or start received from the baby unit.

Press MENU when the parient unit is die.

Press y or A to choose LED, then press SELECT.

Press y or A to choose LED, then press SELECT.

Press y or A to choose On or Off, then press SELECT to confirm your sale.

## Monitoring mode \* for VM5251-2 only

## Adjust the sound sensitivity of the baby unit You can choose to hear sounds from the baby unit all the time, or to hear sounds that ex

a certain level, You can use the parent unit to adjust the microphone sensitivity or your bas unit. The higher the sensitivity level, the more sensitive the baby unit is in detecting sound for transmitting to the parent unit. The VOX sensitivity level is preset to <b>HIGHEST</b> .					
	Highest	High	Medium	Low	Lowest
	The parent unit speaker is constantly on, and you will hear all sounds (including background noises) from your baby's room.	The parent unit speaker turns on for soft babbling and louder sounds from your baby. It remains quiet when your baby sleeps soundly.	The parent unit speaker turns on for loud babbling and louder sounds from your baby. It remains quiet when your baby makes soft sounds.	The parent unit speaker turns on for crying and louder sounds from your baby. It remains quiet when your baby makes soft sounds.	The parent unit speaker turns on for loud crying or screeching sounds from your baby. It remains quiet when your baby makes soft sounds.

Priess MENU when the parent unit is ide:

| Priess MENU when the parent unit is ide:
| Priess V or A to choose VOX Sensitivity, then priess SELECT.

- If you have two baby unit, the system prompt; you to choose the desired baby unit on both baby unit, rise V or A to choose ALL CAM or CAM #. then priess SELECT.

- Priess V or A to choose the desired sensitivity level, then priess SELECT to confirm your selNOTE

NOTES

- Sound activation is available in Single CAM and Patrol mode only.

- If the sound sensitivity is set to Righest, the pasted unit screen may though sound activation is on. The depends on whether the baby

Zoom
You can zoom in white viewing images from the baby unit in Single of Press (§ to zoom in.
Press (§ to zoom in.
Press V or A to move the zoomed image downward or upward.
Press (c or > to move the zoomed image leftward or rightward.
Press (§ applin to zoom out.

rearror mode.

Press and hold TALK on the parent unit. The TALK light turns on.

Speak towards the microphone on the parent unit. Your voice is bn.

Release the TALK key to stop the broadcast.

The parent unit speaker w...
resumes after TALK is released.
After around 50 seconds of sound re-transmission, the speaker revealment before pressing TALK.
The bady unit's talkback volume can be adjusted via the parent unit in the second seco

# The baby until tablack volume can be adjusted van me perent until Set al elert 10me Low battery tone Low battery tone Tou can set the parent unit to beep when the parent unit opera 1. Press MENU when the parent unit is idle. 1. Press Y or in A choices Aller 10me, then press SELECT. 3. Press S y or in A choices Aller 10me, then press SELECT. 3. Press S y or in A choices (Aller 10me) and SELECT pain to choose Leve Battery Tone. 4. Press Y or in A choices (Aller 10me) and SELECT to conf.

No link alert
You can set the parent unit to beep when the link be

Sound alert in split-view

You can hum on the sound alert feature so that, while in Split mode, the pa
and displays Sound detected at CAM# whenever the baby unit detects at
. Press MENU when the parent unit is idle.

2. Press Yor A to choose Alert Tone, then press SELECT.

3. Press Yor A to choose Sound Alert in Split-view, then press SELECT.

4. Press Yor A to choose Sound Alert in Split-view, then press SELECT.