

FCC Test Report

for

RF Laser Mouse

Trade Name : Forward
Model Number : FDM-71UL1
FCC ID : F4Z4K3FDM-71UL1
Report Number : RF-T013-0612-178
Date of Receipt : January 3, 2007
Date of Report : January 12, 2007

Prepared for

Forward Electronics Co., LTD.

No.393, Chung Cheng Rd. Sec.1, San-Hsia Town, Taipei Hsien, Taiwan, 237, R.O.C.

Prepared by



Central Research Technology Co. EMC Test Laboratory

11, Lane 41, Fushuen St., Jungshan Chiu, Taipei, Taiwan, 104, R.O.C.

This report shall not be reproduced, except in full, without the written approval of Central Research Technology Co.. It may be duplicated completely in its entirety for legal use with the permission of the applicant. It should not be used to claim product endorsement by any U.S. government agency. The test result in the report applies only to the sample tested.

Certification of Compliance

Equipment under Test : RF Laser Mouse
Model No. : FDM-71UL1
FCC ID : F4Z4K3FDM-71UL1
Manufacturer : Forward Electronics Co., LTD.
Applicant : Forward Electronics Co., LTD.
Address : No.393, Chung Cheng Rd. Sec.1, San-Hsia Town, Taipei
Hsien, Taiwan, 237, R.O.C.
Applicable Standards : 47 CFR part 15, Subpart C
Date of Testing : January 8~9, 2007
Deviation : N/A
Condition of Test Sample : Prototype



We, **Central Research Technology Co.**, hereby certify that one sample of the designated product was tested in our facility during the period mentioned above. The test records, data evaluation and Equipment Under Test (EUT) configurations shown in the present report are true and accurate representation of the measurements of the sample's RF characteristics under the conditions herein specified.

The test results show that the EUT as described in the present report is in compliance with the requirements set forth in the standards mentioned above and apply to the tested sample identified in the present report only. The test report shall not be reproduced, except in its entirety, without the written approval of Central Research Technology Co.

PREPARED BY : Cathy Chen, DATE : Jan. 12, 2007
(Cathy Chen/ Technical Manager)

APPROVED BY : J. Y. Shih, DATE : Jan. 12, 2007
(Tsun-Yu Shih/Laboratory Head)

Contents

1. General Description	4
1.1 General Description of EUT.....	4
1.2 Test Methodology	4
1.3 Applied standards	5
1.4 The Support Units	8
1.5 Layout of the Setup.....	8
1.6 Test Facility	9
1.7 Measurement Uncertainty.....	11
2. Field strength of Fundamental	12
2.1 Limits for Field strength of Fundamental.....	12
2.2 Test Instruments	13
2.3 Test Procedures	14
2.4 Test Configurations.....	15
2.5 Test Results	16
3. Radiated Emission Measurement	21
3.1 Limit for Radiated Emission Measurement.....	21
3.2 Test Instruments	22
3.3 Test Procedures	23
3.4 Test Configuration	24
3.5 Test Results	25
Band Edge	25
Radiated Emission Measurement	29

Attachment 1 – Photographs of the Test Configurations

Attachment 2 – External Photographs of EUT

Attachment 3 – Internal Photographs of EUT

1. General Description

1.1 General Description of EUT

Equipment under Test : RF Laser Mouse

Model No. : FDM-71UL1

Power in : 1.5Vdc

Test Voltage : 1.5Vdc (Battery*1)

Manufacturer : Forward Electronics Co., LTD.

Channel Numbers : 8

Frequency Range : 2414MHz~2470MHz

Fundamental Frequency : 2414, 2420, 2424, 2430, 2452, 2456, 2462, 2470 MHz

Modulation : GFSK

Function Description :

The EUT is used to transmit control command only. Please refer to the user's manual for the details.

1.2 Test Methodology

For this E.U.T., the radiated emissions measurement performed according to the procedures illustrated in ANSI C63.4 and other required were illustrated in separate sections of this test report for detail.

1.3 Applied standards

(1) Field strength of Fundamental

According to 15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field Strength of Fundamental (mV/m)	Field Strength of Harmonics (uV/m)
902 – 928 MHz	50	500
2400 – 2483.5 MHz	50	500
5725 – 5875 MHz	50	500
24.0 – 24.25 GHz	250	2500

(2) Radiation emission

According to 15.249(d), Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

(3) Radiated emission limits, general requirements.

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

(4) Restricted Band

Frequency(MHz)	Frequency(MHz)	Frequency(MHz)	Frequency(GHz)
0.090 - 0.110	16.420 – 16.423	399.9 – 410.0	4.50 – 5.15
10.495 - 0.505	16.69475 – 16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 41.28	25.50 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.50 – 38.25	1435.0 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73.0 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108.00 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.90 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500.0	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2655 - 2900	22.01 – 23.12
8.41425 – 8.41475	162.0125 – 167.1700	3260 – 3267	23.6 – 24.0
12.290 – 12.293	167.72 – 173.20	3332 – 3339	31.2 – 31.8
12.51975 – 12.52025	240 – 285	3345.8 – 3358.0	36.43 – 36.5
12.57675 – 12.57725	322.0 – 335.4	3600 - 4400	(2)
13.36 – 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

1.4 The Support Units

No.	Cable	Length	Shielded	Ferrite Core	Shielded Backshell	Supported by lab.	Note
N/A	*	*	*	*	*	*	*

1.5 Layout of the Setup

Transmitter

Connecting Cables :

No.	Cable	Length	Shielded	Ferrite Core	Shielded Backshell	Supported by lab.	Note
N/A	*	*	*	*	*	*	*

Justification:

For both conducted and radiated emission below 1GHz, the system was configured for typical fashion as a customer could normal use it.

For radiated emission, measurement of radiated emission from digital circuit is performed with normal transmitting.

1.6 Test Facility

Test Facility

The test facility used for evaluating the conformance of the EUT with each standard in the present report meets what required in CISPR16-1-4, CISPR16-2-3 and ANSI C63.4.

Test Room	Type of Test Room	Descriptions
☐ TR1	10m semi-anechoic chamber (23m×14m×9m)	Complying with the NSA requirements in documents CISPR 22 and ANSI C63.4. For the radiated emission measurement.
☐ TR10	3m semi-anechoic chamber (9m × 6m × 6m)	
☒ TR11	3m semi-anechoic chamber (9m × 6m × 6m)	
☐ TR4	Shielding Room (5m×3m×3m)	For the RF conducted emission measurement.
☐ TR5	Shielding Room (8m×5m×4m)	For the conducted emission measurement.

Test Laboratory Competence Information

Central Research Technology Co. has been accredited/filed/authorized by the agencies listed in the following table.

Certificate	Nation	Agency	Code	Mark
Accreditation Certificate	USA	NVLAP	200575-0	ISO/IEC 17025
	R.O.C. (Taiwan)	TAF	0905	ISO/IEC 17025
	R.O.C. (Taiwan)	BSMI	SL2-IN-E-0033,SL2-IS-E-0033,SL2-A1-E-0033	ISO/IEC 17025
Site Filing Document	USA	FCC	474046, TW-1021	Test facility list & NSA Data
	Canada	IC	4699A	Test facility list & NSA Data
	Japan	VCCI	R-1527,C-1609,T-131	Test facility list & NSA Data
Authorization Certificate	Norway	Nemko	ELA 212	ISO/IEC 17025

The copy of each certificate can be downloaded from our web site: www.crc-lab.com

1.7 Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$. The values are less than $U_{cisp\text{r}}$ in table 1 of CISPR 16-4-2 and which are shown as below.

Test Item	Measurement Uncertainty
Radiated Emission: (30MHz~200MHz)	Horizontal: 3.3dB ; Vertical: 3.4dB
Radiated Emission: (200MHz~1GHz)	Horizontal: 3.7dB ; Vertical: 3.7dB
Radiated Emission: (above 1GHz)	Horizontal: 4.4 dB ; Vertical: 4.4 dB

2. Field strength of Fundamental

Result: PASS

2.1 Limits for Field strength of Fundamental

Fundamental Frequency	Peak	Average
☐ 902 – 928 MHz	500mV/m (114dBuV/m)	50mV/m (94dBuV/m)
☒ 2400 – 2483.5 MHz	500 mV/m (114dBuV/m)	50 mV/m (94dBuV/m)
☐ 5725 – 5875 MHz	500 mV/m (114dBuV/m)	50 mV/m (94dBuV/m)
☐ 24.0 – 24.25 GHz	2500 mV/m (128dBuV/m)	250 mV/m (108dBuV/m)

2.2 Test Instruments

Test Site and Equipment	Manufacturer	Model No./ Serial No.	Last Calibration Date	Calibration Due Date
Semi-anechoic Chamber	ETS.LINDGREN	TR11/13455	June 13, 2006	June 13, 2007
Spectrum Analyzer	Agilent	E4405B/ MY45106706	March 9, 2006	March 9, 2007
Antenna	EMCO	3117/ 57408	Feb. 9, 2006	Feb. 9, 2007
Pre-amplifier	MITEQ	J S4-00101800- 28-5A/ 742229	Aug. 1, 2006	Aug. 1, 2007

Note :

1. The calibrations are traceable to NML/ROC.
2. NCR:No Calibration Required

Instrument Setting

RBW	VBW	Detector	Trace	Comment
1MHz	3MHz	Peak	Maxhold	


Climatic Condition

Ambient Temperature : 27°C ; Relative Humidity : 68%

2.3 Test Procedures

- a. The EUT was set up per the test configuration figured in the next section of this chapter to simulate the typical usage per the user's manual.
- b. If the EUT is desktop equipment, it was placed on a wooden table with a height of 0.8 meters above the reference ground plane in the semi-anechoic chamber. If the EUT is floor-standing equipment, it was placed on a non-conducted support with a height of 12 mm above the reference ground plane in the semi-anechoic chamber.
- c. The EUT was set at 3m away from the interference receiving antenna.
- d. Rapidly sweep the signal in the test frequency range by using the spectrum through the Maximum-peak detector.
- e. Rotate the EUT from 0° to 360° and position the receiving antenna at heights from 1 to 4 meters above the reference ground plane continuously to determine the fundamental frequency and frequencies associated with higher emission levels and record them.
- f. Then measure each frequency found from step e. by using the spectrum with rotating the EUT and positioning the receiving antenna height to determine the maximum level.
- g. Finely tune the antenna and turntable around the recorded position of each frequency found from step f.
- h. For measurement of frequency below 1000MHz, set the receiver detector to be Quasi-Peak per CISPR 16-1 to find out the maximum level occurred.
- i. For measurement of frequency above 1000MHz, set the spectrum detector to be Peak or Average to find out the maximum level occurred, if any.
- j. Record the frequency and polarization of the receiving antenna and compare the maximum level with the required limit.
- k. Change the receiving antenna to another polarization to measure radiated emission by following step d. to j. again.
- l. If the peak emission level measured from step e. is 10dB lower than the limit specified, then the emission values presented will be the peak value only. Otherwise, accurate Q.P. value will be measured and presented.

2.4 Test Configurations



2.5 Test Results

Test Mode : Transmitter

Test Distance : 3m

Tester : Bill

Frequency (MHz)	Polarization	Reading Data (dBuV)		Correction Factor (dB/m)	Output Field Strength (dBμV/m)		Limit (dBμV/m)		Margin (dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
2412	V	74.38	54.38	-1.18	73.20	53.20	113.98	93.98	40.78	40.78
	H	88.49	68.49	-1.18	87.31	67.31	113.98	93.98	26.67	26.67
2452	V	75.17	55.17	-1.10	74.07	54.07	113.98	93.98	39.91	39.91
	H	87.27	67.27	-1.10	86.17	66.17	113.98	93.98	27.81	27.81
2470	V	73.98	53.98	-1.12	72.86	52.86	113.98	93.98	41.12	41.12
	H	86.86	66.86	-1.12	85.74	65.74	113.98	93.98	28.24	28.24

Note :

1. Correction Factor (dB/m) = Cable Loss + Antenna Factor – Gain of Preamplifier
2. Output Field Strength (dBuV/m) = Reading Data + Correction Factor
3. Margin (dB) = Limit – Output Field Strength
4. The average value of fundamental frequency is:

Average = Peak value + 20log(Duty cycle)


Where the duty factor is calculated from following formula:

$$20\log(\text{Duty Cycle}) = 20\log \frac{0.48}{14.8} < -20\text{dB}$$


please see page 20 for plotted duty cycle.

2414MHz

Vertical Polarization




Horizontal Polarization




2452MHz

Vertical Polarization




Horizontal Polarization




2470MHz



Vertical Polarization



Horizontal Polarization



Duty Cycle



3. Radiated Emission Measurement

Result: PASS

3.1 Limit for Radiated Emission Measurement

Limit for Harmonics Radiation Emission Measurement

Fundamental Frequency	Field Strength of Harmonics
☐ 902 – 928 MHz	500 uV/m (54dBuV/m)
☒ 2400 – 2483.5 MHz	500 uV/m (54dBuV/m)
☐ 5725 – 5875 MHz	500 uV/m (54dBuV/m)
☐ 24.0 – 24.25 GHz	2500 uV/m(68dBuV/m)

Limit for Other Emissions except Harmonics

Frequency (MHz)	Quasi-peak (dBμV/m)	
30 to 88	40	
88 to 216	43.5	
216 to 960	46	
960 to 1000	54	
Frequency (MHz)	Peak (dBμV/m)	Average (dBμV/m)
Above 1000	74	54
Note 1- The lower limit shall apply at the transition frequency.		
Note 2- Additional provisions may be required for cases where interference occurs.		

3.2 Test Instruments

Test Site and Equipment	Manufacturer	Model No./ Serial No.	Last Calibration Date	Calibration Due Date
Semi-anechoic Chamber	ETS.LINDGREN	TR11/13455	June 13, 2006	June 13, 2007
Test Receiver	R&S	ESCI/ 100316	Feb. 1, 2006	Feb. 1, 2007
Spectrum Analyzer	Agilent	E4405B/ MY45106706	March 9, 2006	March 9, 2007
Antenna	EMCO	3142C/ 35035	Aug. 14, 2006	Aug. 14, 2007
Antenna	EMCO	3117/ 57408	Feb. 9, 2006	Feb. 9, 2007
Antenna	EMCO	3116/ 20533	Dec. 13, 2006	Dec. 13, 2007
Pre-amplifier	MITEQ	JS4-00101800-28-5A/742229	Aug. 1, 2006	Aug. 1, 2007
Pre-amplifier	MITEQ	JS4-18002600-30-5A / 741923	Aug. 1, 2006	Aug. 1, 2007
Pre-amplifier	Mini Circuit	ZKL-2/ 008	May 4, 2006	May 4, 2007

Note :

1. The calibrations are traceable to NML/ROC.
2. NCR:No Calibration Required

Instrument Setting

RBW	VBW	Detector	Trace	Comment
120kHz	N/A	Quasi-Peak	Maxhold	Below 1GHz
1MHz	1MHz	Peak	Maxhold	Above 1GHz Peak
1MHz	10Hz	Peak	Maxhold	Above 1GHz Average

Climatic Condition


Ambient Temperature : 27°C ; Relative Humidity : 68%

3.3 Test Procedures


- a. The EUT was set up per the test configuration figured in the next section of this chapter to simulate the typical usage per the user's manual.
- b. If the EUT is desktop equipment, it was placed on a wooden table with a height of 0.8 meters above the reference ground plane in the semi-anechoic chamber. If the EUT is floor-standing equipment, it was placed on a non-conducted support with a height of 12 mm above the reference ground plane in the semi-anechoic chamber.
- c. The EUT was set at 3m away from the interference receiving antenna.
- d. Rapidly sweep the signal in the test frequency range by using the spectrum through the Maximum-peak detector.
- e. Rotate the EUT from 0° to 360° and position the receiving antenna at heights from 1 to 4 meters above the reference ground plane continuously to determine the fundamental frequency and frequencies associated with higher emission levels and record them.
- f. Then measure each frequency found from step e. by using the spectrum with rotating the EUT and positioning the receiving antenna height to determine the maximum level.
- g. Finely tune the antenna and turntable around the recorded position of each frequency found from step f.
- h. For measurement of frequency below 1000MHz, set the receiver detector to be Quasi-Peak per CISPR 16-1 to find out the maximum level occurred.
- i. For measurement of frequency above 1000MHz, set the spectrum detector to be Peak or Average to find out the maximum level occurred, if any.
- j. Record the frequency and polarization of the receiving antenna and compare the maximum level with the required limit.
- k. Change the receiving antenna to another polarization to measure radiated emission by following step d. to j. again.
- l. If the peak emission level measured from step e. is 10dB lower than the limit specified, then the emission values presented will be the peak value only. Otherwise, accurate Q.P. value will be measured and presented.

3.4 Test Configuration

Radiated Emission Measurement below 1000MHz



Radiated Emission Measurement above 1000MHz



3.5 Test Results

Band Edge

Test Mode : Transmitter

Test Distance : 3m


Tester : Bill

Test Range	Polarization	Frequency (MHz)	Reading Data (dBUV)		Correction Factor (dB/m)	Emission (dBUV/m)		Limit (dBUV/m)		Margin (dB)	
			PK.	AV.		PK.	AV.	PK.	AV.	PK.	AV.
Lowest	V	2391.75	46.36	*	-1.25	45.11	*	74	54	28.89	*
	H	2391.75	57.25	31.27	-1.25	56.00	30.02	74	54	18.00	23.98
Highest	V	2494.39	44.78	*	-1.18	43.60	*	74	54	30.40	*
	H	2493.61	56.28	31.23	-1.17	55.11	30.06	74	54	18.89	23.94


Note:

1. Correction Factor (dB/m) = Cable Loss + Antenna Factor – Gain of Preamplifier
2. Emission Level (dBUV/m) = Reading Data + Correction Factor
3. Margin (dB) = Limit – Emission Level
4. “*”: The emission is too low to be measured.


Lowest Channel, Vertical, Peak




Lowest Channel, Horizontal, Peak




Lowest Channel, Horizontal, Average




Highest Channel, Vertical, Peak



Highest Channel, Horizontal, Peak



Highest Channel, Horizontal, Average




Radiated Emission Measurement

Below 1000MHz

Test Mode : 2414MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Vertical Frequency Range : 30MHz~300MHz




Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.
3. Q.P is abbreviation of quasi-peak.

Test Mode : 2414MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Vertical Frequency Range : 300MHz~1000MHz




Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.
3. Q.P is abbreviation of quasi-peak.

Test Mode : 2414MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Horizontal Frequency Range : 30MHz~300MHz




Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.
3. Q.P is abbreviation of quasi-peak.

Test Mode : 2414MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Horizontal Frequency Range : 300MHz~1000MHz




Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.
3. Q.P is abbreviation of quasi-peak.

Test Mode : 2452MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Vertical Frequency Range : 30MHz~300MHz




Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.
3. Q.P is abbreviation of quasi-peak.

Test Mode : 2452MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Vertical Frequency Range : 300MHz~1000MHz




Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.
3. Q.P is abbreviation of quasi-peak.

Test Mode : 2452MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Horizontal Frequency Range : 30MHz~300MHz




Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.
3. Q.P is abbreviation of quasi-peak.

Test Mode : 2452MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Horizontal Frequency Range : 300MHz~1000MHz




Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.
3. Q.P is abbreviation of quasi-peak.

Test Mode : 2470MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Vertical Frequency Range : 30MHz~300MHz




Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.
3. Q.P is abbreviation of quasi-peak.

Test Mode : 2470MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Vertical Frequency Range : 300MHz~1000MHz




Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.
3. Q.P is abbreviation of quasi-peak.

Test Mode : 2470MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Horizontal Frequency Range : 30MHz~300MHz




Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.
3. Q.P is abbreviation of quasi-peak.

Test Mode : 2470MHz, Transmitter


Test Distance : 3m Tester : Bill

Polarization : Horizontal Frequency Range : 300MHz~1000MHz



Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.
3. Q.P is abbreviation of quasi-peak.
4. “*”: The emission is too low to be measured.


Above 1000MHz**Test Mode : 2414MHz, Transmitter****Test Distance : 3m Tester : Bill****Polarization : Vertical Frequency Range : 1GHz ~ 4GHz****Note:**

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.

Test Mode : 2414MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Vertical Frequency Range : 4GHz ~ 8GHz



	Freq	Level	Factor	Read	Limit	Over	Ant	Table	Pol/Phase	Remark
				Level	Line	Limit	Pos	Pos		
	MHz	dBuV/m	dB/m	dBuV	dBuV/m	dB	cm	deg		
1	4828.000	47.29	4.07	43.22	74.00	-26.71	---	---	VERTICAL	Peak

Note:


1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.

No signal can be detected from 8GHz to 25GHz, so the graphs are omitted above 8GHz.

Test Mode : 2414MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Horizontal Frequency Range : 1GHz ~ 4GHz



	Freq	Level	Factor	Read Level	Limit Line	Over Limit	Ant Pos	Table Pos	Pol/Phase	Remark
	MHz	dBuV/m	dB/m	dBuV	dBuV/m	dB	cm	deg		
1	2337.740	30.31	-1.45	31.76	54.00	-23.69	---	191	HORIZONTAL	Average
2	2338.000	53.51	-1.45	54.96	74.00	-20.49	---	---	HORIZONTAL	Peak
3	2716.000	49.67	-0.47	50.14	74.00	-24.33	---	---	HORIZONTAL	Peak


Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.

Test Mode : 2414MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Horizontal Frequency Range : 4GHz ~ 8GHz



	Freq	Level	Factor	Read	Limit	Over	Ant	Table	Pol/Phase	Remark
				Level	Line	Limit				
	MHz	dBuV/m	dB/m	dBuV	dBuV/m	dB	cm	deg		
1	4828.000	49.93	4.07	45.86	74.00	-24.07	---	---	HORIZONTAL	Peak

Note:


1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.

No signal can be detected from 8GHz to 25GHz, so the graphs are omitted above 8GHz.

Test Mode : 2452MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Vertical Frequency Range : 1GHz ~ 4GHz




Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.

Test Mode : 2452MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Vertical Frequency Range : 4GHz ~ 8GHz



	Freq	Level	Factor	Read	Limit	Over	Ant	Table	Pol/Phase	Remark
				Level	Line	Limit				
	MHz	dBuV/m	dB/m	dBuV	dBuV/m	dB	cm	deg		
1	4904.000	48.92	4.52	44.40	74.00	-25.08	---	---	VERTICAL	

Note:


1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.

No signal can be detected from 8GHz to 25GHz, so the graphs are omitted above 8GHz.

Test Mode : 2452MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Horizontal Frequency Range : 1GHz ~ 4GHz




	Freq	Level	Factor	Read Level	Limit Line	Over Limit	Ant Pos	Table Pos	Pol/Phase	Remark
	MHz	dBuV/m	dB/m	dBuV	dBuV/m	dB	cm	deg		
1	2389.000	49.93	-1.27	51.20	74.00	-24.07	---	---	HORIZONTAL	Peak
2 !	2716.000	56.20	-0.47	56.67	74.00	-17.80	---	---	HORIZONTAL	Peak
3	2716.305	31.91	-0.47	32.38	54.00	-22.09	---	258	HORIZONTAL	Average

Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.

Test Mode : 2452MHz, Transmitter
Test Distance : 3m Tester : Bill
Polarization : Horizontal Frequency Range : 4GHz ~ 8GHz



	Freq	Level	Factor	Read	Limit	Over	Ant	Table	Pol/Phase	Remark
				Level	Line	Limit		Pos		
	MHz	dBuV/m	dB/m	dBuV	dBuV/m	dB	cm	deg		
1	4903.780	27.91	4.52	23.39	54.00	-26.09	---	279	HORIZONTAL	Average
2	4904.000	52.14	4.52	47.62	74.00	-21.86	---	---	HORIZONTAL	Peak


- Note:
- 1. Emission Level = reading value + correction factor.
 - 2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.

No signal can be detected from 8GHz to 25GHz, so the graphs are omitted above 8GHz.

Test Mode : 2470MHz, Transmitter

Test Distance : 3m Tester : Bill


Polarization : Vertical Frequency Range : 1GHz ~ 4GHz



Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.

Test Mode : 2470MHz, Transmitter
Test Distance : 3m Tester : Bill
Polarization : Vertical Frequency Range : 4GHz ~ 8GHz



	Freq	Level	Factor	Read	Limit	Over	Ant	Table	Pol/Phase	Remark
				Level	Line	Limit				
	MHz	dBuV/m	dB/m	dBuV	dBuV/m	dB	cm	deg		
1	4940.000	49.67	4.45	45.22	74.00	-24.33	---	---	VERTICAL	Peak


- Note:
- 1. Emission Level = reading value + correction factor.
 - 2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.

No signal can be detected from 8GHz to 25GHz, so the graphs are omitted above 8GHz.

Test Mode : 2470MHz, Transmitter

Test Distance : 3m Tester : Bill

Polarization : Horizontal Frequency Range : 1GHz ~ 4GHz




	Freq	Level	Factor	Read Level	Limit Line	Over Limit	Ant Pos	Table Pos	Pol/Phase	Remark
	MHz	dBuV/m	dB/m	dBuV	dBuV/m	dB	cm	deg		
1 !	2506.000	59.62	-1.14	60.76	74.00	-14.38	---	---	HORIZONTAL	Peak
2	2507.040	29.94	-1.12	31.06	54.00	-24.06	---	277	HORIZONTAL	Average
3 !	2572.000	56.45	-0.78	57.23	74.00	-17.55	---	---	HORIZONTAL	Peak
4	2572.125	30.55	-0.78	31.33	54.00	-23.45	---	290	HORIZONTAL	Average

Note:

1. Emission Level = reading value + correction factor.
2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.

Test Mode : 2470MHz, Transmitter
Test Distance : 3m Tester : Bill
Polarization : Horizontal Frequency Range : 4GHz ~ 8GHz



	Freq	Level	Factor	Read			Ant	Table		Remark
				Level	Limit	Over		Pos	Pos	
	MHz	dBuV/m	dB/m	dBuV	dBuV/m	dB	cm	deg		
1	4939.725	28.61	4.45	24.16	54.00	-25.39	---	302	HORIZONTAL	Average
2 !	4940.000	54.99	4.45	50.54	74.00	-19.01	---	---	HORIZONTAL	Peak

- Note:
- 1. Emission Level = reading value + correction factor.
 - 2. Correction factor = cable loss + antenna factor – gain of pre-amplifier.

No signal can be detected from 8GHz to 25GHz, so the graphs are omitted above 8GHz.