



## FCC RADIO TEST REPORT

Applicant's company	<b>Buffalo Inc.</b>
Applicant Address	Akamon-dori Bldg 30-20, Ohsu 3-chome Naka-ku, Nagoya 460-8315 Japan
FCC ID	<b>FDI-09101695-0</b>

Product Name	1. Wireless AC1300 / N900 Gigabit Dual Band Router 2. Wireless AC1300 / N450 Gigabit Dual Band Media Bridge
Brand Name	Buffalo Inc.
Model Name	WZR-D1800H / WLI-H4-D1300
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	5745~5850MHz
Received Date	Mar. 26, 2012
Final Test Date	May 02, 2012
Submission Type	Class II Change
Multiple Listing	Please refer to section 3.7

### Statement

**Test result included is only for the IEEE 802.11n, and IEEE 802.11a (5725 ~ 5850MHz) of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



## Table of Contents

<b>1. CERTIFICATE OF COMPLIANCE.....</b>	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>3. GENERAL INFORMATION.....</b>	<b>3</b>
3.1. Product Details .....	3
3.2. Accessories .....	4
3.3. Table for Filed Antenna .....	5
3.4. Table for Carrier Frequencies .....	6
3.5. Table for Test Modes .....	6
3.6. Table for Testing Locations .....	7
3.7. Table for Class II Change & Multiple Listing .....	7
3.8. Table for Supporting Units.....	8
3.9. Table for Parameters of Test Software Setting .....	9
3.10. Test Configurations .....	10
<b>4. TEST RESULT .....</b>	<b>13</b>
4.1. AC Power Line Conducted Emissions Measurement.....	13
4.2. Conducted Output Power Measurement.....	17
4.3. Power Spectral Density Measurement.....	26
4.4. 6dB Spectrum Bandwidth Measurement.....	36
4.5. Radiated Emissions Measurement.....	41
4.6. Band Edge Emissions Measurement .....	56
4.7. Antenna Requirements.....	61
<b>5. LIST OF MEASURING EQUIPMENTS .....</b>	<b>62</b>
<b>6. TEST LOCATION.....</b>	<b>64</b>
<b>7. TAF CERTIFICATE OF ACCREDITATION .....</b>	<b>65</b>
<b>APPENDIX A. PHOTOGRAPHS OF EUT .....</b>	<b>A1 ~ A61</b>
<b>APPENDIX B. TEST PHOTOS .....</b>	<b>B1 ~ B6</b>
<b>APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE.....</b>	<b>C1 ~ C3</b>



### History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR232630	Rev. 01	Initial issue of report	Apr. 18, 2012
FR232630-01	Rev. 01	Add 5GHz Band 4 test data for Class II Change	May 08, 2012

## 1. CERTIFICATE OF COMPLIANCE

**Product Name** : 1. **Wireless AC1300 / N900 Gigabit Dual Band Router**  
2. **Wireless AC1300 / N450 Gigabit Dual Band Media Bridge**  
**Brand Name** : **Buffalo Inc.**  
**Model Name** : **WZR-D1800H / WLI-H4-D1300**  
**Applicant** : **Buffalo Inc.**  
**Test Rule Part(s)** : **47 CFR FCC Part 15 Subpart C § 15.247**

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Mar. 26, 2012 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



**Jordan Hsiao**

**SPORTON INTERNATIONAL INC.**

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	17.25 dB
4.2	15.247(b)(3)	Conducted Output Power	Complies	4.85 dB
4.3	15.247(e)	Power Spectral Density	Complies	24.66 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	5.13 dB
4.6	15.247(d)	Band Edge Emissions	Complies	-
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5 × 10 <sup>-8</sup>	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1GHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

### 3. GENERAL INFORMATION

#### 3.1. Product Details

##### IEEE 802.11n/ac

Items	Description
Product Type	WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	For 802.11n: OFDM (BPSK / QPSK / 16QAM / 64QAM) For 802.11ac: OFDM (BPSK/QPSK/16QAM/64QAM/256QAM)
Frequency Range	5745~5850MHz
Channel Number	10 for 20MHz bandwidth ; 4 for 40MHz bandwidth 1 for 80MHz bandwidth
Channel Band Width (99%)	MCS0 (20MHz): 17.68 MHz ; MCS0 (40MHz): 36.00 MHz MCS0 (80MHz): 75.60 MHz
Conducted Output Power	MCS0 (20MHz): 22.46 dBm ; MCS0 (40MHz): 21.69 dBm MCS0 (80MHz): 22.37 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

##### IEEE 802.11a

Items	Description
Product Type	802.11a :WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Frequency Range	5745~5850MHz
Channel Number	5
Channel Band Width (99%)	11a: 16.56 MHz
Conducted Output Power	11a: 22.66 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

**Antenna & Band width**

Antenna	Single (TX)			Two (TX)			Three (TX)		
	20 MHz	40 MHz	80 MHz	20 MHz	40 MHz	80 MHz	20 MHz	40 MHz	80 MHz
IEEE 802.11a	X	X	X	X	X	X	V	X	X
IEEE 802.11n	X	X	X	X	X	X	V	V	X
IEEE 802.11ac	X	X	X	X	X	X	X	X	V

**IEEE 802. 11a, 11n and 11ac Spec.**

Worst Modulation Used for Conformance Testing				
Power Level		1		
IEEE 802.11 Protocol	Number of Transmit Chains (N <sub>TX</sub> )	Data Rate / MCS	Worst Data Rate / MCS	Worst Modulation Mode
a	3	6-54 Mbps	6Mbps	11A5.2G-20M
n (HT20)	3	MCS 0-15	MCS 0	11N5.2G-20M
n (HT40)	3	MCS 0-15	MCS 0	11N5.2G-40M
ac (VHT80)	3	MCS 0-9	MCS 0-Nss1	11AC5.2G-80M

Note 1: IEEE Std. 802.11-2007 modulation consists of IEEE Std. 802.11a-1999.

Note 2: IEEE Std. 802.11n-2009 modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40. Worst modulation mode of Guard Interval (GI) is 400ns.

Note 3: draft IEEE Std. 802.11ac-2012 modulation consists of VHT20, VHT40, VHT80 and VHT160. Then EUT support VHT80. (VHT: Very High Throughput).

Note 4: Modulation modes consist of 11A5.2G-20M, 11A5.3G-20M, 11A5.6G-20M, 11N5.2G-20M, 11N5.3G-20M, 11N5.6G-20M, 11N5.2G-40M, 11N5.3G-40M, 11N5.6G-40M, 11AC5.2G-80M, 11AC5.3G-80M, 11AC5.6G-80M:

11A: IEEE 802.11a, 11N: IEEE 802.11n, 11AC: IEEE 802.11ac. 5.2G: 5.15-5.25 GHz band, 5.3G: 5.25-5.35 GHz band, 5.6G: 5.47-5.725 GHz band.

20M/40M/80M: Channel Bandwidth 20MHz/40MHz/80MHz

**3.2. Accessories**

Power	Brand	Model	Rating
Adapter	Asian Power Devices Inc.	WA-36A12	INPUT: 100-240V, 50-60Hz, 0.9A Max. OUTPUT: 12V, 3A
Others			
Plug *1			
Cradle *1			

### 3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Remark
1	Arcadyan	WG9116A33-J6-R0A	PCB Antenna & MIFA	I-PEX	3.83	TX/RX
2	Arcadyan	WG9116A33-J6-R0A	PCB Antenna & MIFA	I-PEX	2.37	TX/RX
3	Arcadyan	WG9116A33-J6-R0A	PCB Antenna & MIFA	I-PEX	4.80	TX/RX

Note: The EUT has three antennas

**For IEEE 802.11a mode (3TX/3RX)**


Ant. 1, Ant. 2 and Ant. 3 could transmit/receive simultaneously.

**For IEEE 802.11n mode (3TX/3RX)**

Ant. 1, Ant. 2 and Ant. 3 could transmit/receive simultaneously.

**For IEEE 802.11ac mode (3TX/3RX):**

Ant. 1, Ant. 2, Ant. 3 could transmit/receive simultaneously.





### 3.4. Table for Carrier Frequencies

There are three bandwidth systems for IEEE 802.11n.

For 20MHz bandwidth systems, use Channel 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 151, 159.

For 80MHz bandwidth systems, use Channel 155.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz Band 4	149	5745 MHz	157	5785 MHz
	151	5755 MHz	159	5795 MHz
	153	5765 MHz	161	5805 MHz
	155	5775 MHz	165	5825 MHz

### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	-
Conducted Output Power Power Spectral Density	20MHz	MCS0	149/157/165	1/2/3/1+2+3
	40MHz	MCS0	151/159	1/2/3/1+2+3
	80MHz	MCS0	155	1/2/3/1+2+3
	11a	BPSK 6 Mbps	149/157/165	1/2/3/1+2+3
6dB Spectrum Bandwidth	20MHz	MCS0	149/157/165	1+2+3
	40MHz	MCS0	151/159	1+2+3
	80MHz	MCS0	155	1/2/3/1+2+3
	11a	BPSK 6 Mbps	149/157/165	1+2+3
Radiated Emissions Below 1GHz	CTX	Auto	-	-
Radiated Emissions Above 1GHz	20MHz	MCS0	149/157/165	1+2+3
	40MHz	MCS0	151/159	1+2+3
	80MHz	MCS0	155	1/2/3/1+2+3
	11a	BPSK 6 Mbps	149/157/165	1+2+3
Band Edge Emissions	20MHz	MCS0	149/157/165	1+2+3
	40MHz	MCS0	151/159	1+2+3
	80MHz	MCS0	155	1/2/1+2
	11a	BPSK 6 Mbps	149/157/165	1+2+3

The following test modes were performed for all tests:

**For Conducted Emission test:**

Normal Link

**For Radiated Emission test:**

Mode 1. Put EUT upright.

Mode 2. Put EUT lying.

<30MHz ~ 1GHz>

Mode 1 generated the worst test result, so it was recorded in this report.

<Above 1GHz>

Mode 1 generated the worst test result, so it was recorded in this report.

### 3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D	-
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

### 3.7. Table for Class II Change & Multiple Listing

The model names in the following table are all refer to the identical product.

Product Name	Model Name	WLAN Mode	USB Port	WAN Port	Description
Wireless AC1300/N900 Gigabit Dual Band Router	WZR-D1800H	Master	V	V	-
Wireless AC1300/N450 Gigabit Dual Band Media Bridge	WLI-H4-D1300	Client	X	X	It is lack of components as below: D20/SW3/FB1/C49/U5/L1/TV S1/C66/R91

Note: The configuration of Wireless AC1300/N900 Gigabit Dual Band Router (Master) is more complex than Wireless AC1300/N450 Gigabit Dual Band Media Bridge, so it was selected to perform the test.

This product is an extension of original one reported under Sporton project number: FR232630

Below is the table for the change of the product with respect to the original one.

Modifications	Description	Performance Checking
Add 5GHz Band 4	Perform 802.11n, 802.11ac and 802.11a test data.	1. Conducted Output Power Measurement 2. Power Spectral Density Measurement 3. 6dB Spectrum Bandwidth Measurement 4. Radiated Emissions Measurement 5. Band Edge Emissions Measurement

### 3.8. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Flash Disk	Silicon	I-Series	DoC
Notebook	DELL	M1330	E2K4965AGNM
Notebook	DELL	D420	E2K24GBRL
Notebook	DELL	D400	QDS-BRCM1005-D
Notebook	DELL	D400	QDS-BRCM1005-D

### 3.9. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### Power Parameters of IEEE 802.11n MCS0 20MHz

Test Software Version	Manual Tool Version 0.0.0.9		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS0 20MHz	68	68	68

#### Power Parameters of IEEE 802.11n MCS0 40MHz

Test Software Version	Manual Tool Version 0.0.0.9	
Frequency	5755 MHz	5795 MHz
MCS0 40MHz	64	64

#### Power Parameters of IEEE 802.11ac MCS0 80MHz

Test Software Version	Manual Tool Version 0.0.0.9
Frequency	5775 MHz
MCS0 40MHz	68

#### Power Parameters of IEEE 802.11a


Test Software Version	Manual Tool Version 0.0.0.9		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	68	68	68

During the test, "Manual Tool Version 0.0.0.9" under WIN XP was executed the test program to control the EUT continuously transmit RF signal.

### 3.10. Test Configurations


#### 3.10.1. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz




Item	Connection	Shield	Length
1	Power cable	No	1.5M
2	RJ-45 cable*3	No	1M
3	RJ-45 cable	No	10M
4	RJ-45 cable	No	10M

Test Configuration: above 1GHz



Item	Connection	Shield	Length
1	Power cable	No	1.5M
2	Console cable	No	1.5M
3	RJ-45 cable	No	1M

### 3.10.2. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shield	Length
1	Power cable	No	1.5M
2	RJ-45 cable*3	No	1M
3	RJ-45 cable	No	10M
4	RJ-45 cable	No	10M

## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.


Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.



#### 4.1.4. Test Setup Layout



#### LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50  $\Omega$ . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

#### 4.1.5. Test Deviation


There is no deviation with the original standard.

#### 4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


#### 4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	22°C	Humidity	57%
Test Engineer	Kane Liu	Phase	Line
Configuration	Normal Link		



	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.15650	48.40	-17.25	65.65	48.13	0.07	0.20	QP
2	0.15650	36.24	-19.41	55.65	35.97	0.07	0.20	AVERAGE
3	0.18056	44.27	-20.19	64.46	44.01	0.06	0.20	QP
4	0.18056	31.46	-23.00	54.46	31.20	0.06	0.20	AVERAGE
5	0.19969	38.76	-24.86	63.62	38.51	0.05	0.20	QP
6	0.19969	27.36	-26.26	53.62	27.11	0.05	0.20	AVERAGE
7	0.27152	34.35	-26.72	61.07	34.11	0.04	0.20	QP
8	0.27152	25.25	-25.82	51.07	25.01	0.04	0.20	AVERAGE
9	5.836	19.05	-30.95	50.00	18.55	0.20	0.30	AVERAGE
10	5.836	26.07	-33.93	60.00	25.57	0.20	0.30	QP
11	16.573	25.84	-24.16	50.00	24.76	0.65	0.43	AVERAGE
12	16.573	33.52	-26.48	60.00	32.44	0.65	0.43	QP

Temperature	22°C	Humidity	57%
Test Engineer	Kane Liu	Phase	Neutral
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15567	37.26	-18.43	55.69	36.96	0.10	0.20	AVERAGE
2	0.15567	48.21	-17.48	65.69	47.91	0.10	0.20	QP
3	0.17961	33.22	-21.28	54.50	32.93	0.09	0.20	AVERAGE
4	0.17961	44.38	-20.12	64.50	44.09	0.09	0.20	QP
5	0.20396	42.27	-21.18	63.45	41.99	0.08	0.20	QP
6	0.20396	31.17	-22.28	53.45	30.89	0.08	0.20	AVERAGE
7	0.27009	27.86	-23.26	51.12	27.58	0.08	0.20	AVERAGE
8	0.27009	34.95	-26.17	61.12	34.67	0.08	0.20	QP
9	7.526	22.33	-27.67	50.00	21.62	0.31	0.40	AVERAGE
10	7.526	28.79	-31.21	60.00	28.08	0.31	0.40	QP
11	16.398	32.71	-27.29	60.00	31.64	0.65	0.42	QP
12	16.398	25.07	-24.93	50.00	24.00	0.65	0.42	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

## 4.2. Conducted Output Power Measurement

### 4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1MHz
VB	3MHz
Detector	RMS
Trace	Average 100
Sweep Time	Auto

### 4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Test was performed in accordance with Measurement of Digital Transmission Systems Operating under Section 15.247 March 23, 2005.
3. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of Conducted Output Power

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Allen Liu	<b>Configurations</b>	IEEE 802.11n
<b>Test Date</b>	May 02, 2012		

##### Configuration IEEE 802.11n MCS0 20MHz

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3			
149	5745 MHz	17.88	17.49	17.68	22.46	30.00	<b>Complies</b>
157	5785 MHz	17.89	17.51	17.60	22.44	30.00	<b>Complies</b>
165	5825 MHz	17.90	17.32	17.53	22.36	30.00	<b>Complies</b>

##### Configuration IEEE 802.11n MCS0 40MHz

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3			
151	5755 MHz	16.95	16.89	16.91	21.69	30.00	<b>Complies</b>
159	5795 MHz	16.97	16.25	16.26	21.28	30.00	<b>Complies</b>

##### Configuration IEEE 802.11ac MCS0 80MHz

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3			
155	5775 MHz	17.82	17.49	17.48	22.37	30.00	<b>Complies</b>

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Allen Liu	<b>Configurations</b>	IEEE 802.11a
<b>Test Date</b>	May 02, 2012		


**Configuration IEEE 802.11a**

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3			
149	5745 MHz	17.96	17.86	17.84	22.66	27.51	<b>Complies</b>
157	5785 MHz	18.00	17.65	17.57	22.52	27.51	<b>Complies</b>
165	5825 MHz	18.07	17.33	17.44	22.40	27.51	<b>Complies</b>

NOTE Directional gain =  $10 \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N]$  dBi


=8.49dBi > 6dBi, so the conducted power limit =30-(8.49-6)=27.51dBm.

**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 20MHz / 5745 MHz / ANT. 1**




Date: 2.MAY.2012 18:22:47

**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 20MHz / 5745 MHz/ ANT. 2**




Date: 2.MAY.2012 18:22:17

**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 20MHz / 5745 MHz/ ANT. 3**




**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 40MHz / 5755 MHz/ ANT. 1**






**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 40MHz / 5755 MHz/ ANT. 2**




Date: 2.MAY.2012 18:13:57

**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 40MHz / 5755 MHz/ ANT. 3**




Date: 2.MAY.2012 18:14:35


**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 80MHz / 5775 MHz/ ANT. 1**



**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 80MHz / 5775 MHz/ ANT. 2**




**Conducted Output Power Plot on Configuration IEEE 802.11n MCS0 80MHz / 5775 MHz/ ANT. 3**




Date: 2.MAY.2012 18:03:24

**Conducted Output Power Plot on Configuration IEEE 802.11a / 5745 MHz/ ANT. 1**




Date: 2.MAY.2012 18:33:09

**Conducted Output Power Plot on Configuration IEEE 802.11a / 5745 MHz/ ANT. 2**



Date: 2.MAY.2012 18:33:40

**Conducted Output Power Plot on Configuration IEEE 802.11a / 5745 MHz/ ANT. 3**



Date: 2.MAY.2012 18:34:11

### 4.3. Power Spectral Density Measurement

#### 4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the analyzer span to 5-30% greater than the EBW.
RB	100 kHz
VB	300 kHz
Detector	RMS
Trace	Single Sweep
Sweep Time	$\geq 10 \times (\text{number of measurement points in sweep}) \times (\text{transmission symbol period})$ .

#### 4.3.3. Test Procedures

1. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
2. Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span/RBW}$  (use of a greater number of measurement points than this minimum requirement is recommended).
3. Use the peak marker function to determine the maximum level in any 100 kHz band segment within the fundamental EBW.
4. Scale the observed power level to an equivalent level in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where:  $\text{BWCF} = 10\log(3 \text{ kHz}/100 \text{ kHz} = -15.2 \text{ dB})$ .
5. The resulting PSD level must be  $\leq 8 \text{ dBm}$ .
6. When measuring power spectral density with multiple antenna systems, add every result of the values by mathematic formula.

#### 4.3.4. Test Setup Layout



#### 4.3.5. Test Deviation

There is no deviation with the original standard.

#### 4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.3.7. Test Result of Power Spectral Density

Temperature	25°C	Humidity	56%
Test Engineer	Allen Liu	Configurations	IEEE 802.11n

##### Configuration IEEE 802.11n MCS0 20MHz

Channel	Frequency	Power Density (dBm/100kHz)			Total Power Density (dBm/100k Hz)	BWCF factor (100KHz to 3KHz)	Total Power Density (dBm/3kHz)	Max. Limit (dBm/3kH )	Result
		Ant. 1	Ant. 2	Ant. 3					
149	5745 MHz	-6.19	-6.19	-6.24	-1.44	-15.23	-16.66	8.00	Complies
157	5785 MHz	-6.25	-6.77	-6.81	-1.83	-15.23	-17.06	8.00	Complies
165	5825 MHz	-6.25	-6.91	-7.19	-1.99	-15.23	-17.22	8.00	Complies

##### Configuration IEEE 802.11n MCS0 40MHz

Channel	Frequency	Power Density (dBm/100kHz)			Total Power Density (dBm/100k Hz)	BWCF factor (100KHz to 3KHz)	Total Power Density (dBm/3kHz )	Max. Limit (dBm/3kHz )	Result
		Ant. 1	Ant. 2	Ant. 3					
151	5755 MHz	-9.97	-9.89	-10.30	-5.28	-15.23	-20.51	8.00	Complies
159	5795 MHz	-9.78	-10.58	-10.36	-5.46	-15.23	-20.68	8.00	Complies

##### Configuration IEEE 802.11ac MCS0 80MHz

Channel	Frequency	Power Density (dBm/100kHz)			Total Power Density (dBm/100k Hz)	BWCF factor (100KHz to 3KHz)	Total Power Density (dBm/3kHz )	Max. Limit (dBm/3kHz )	Result
		Ant. 1	Ant. 2	Ant. 3					
155	5775 MHz	-12.42	-12.37	-12.57	-7.68	-15.23	-22.91	8.00	Complies

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Benson Peng	<b>Configurations</b>	IEEE 802.11a

**Configuration IEEE 802.11a**

Channel	Frequency	Power Density (dBm/100kHz)			Total Power Density (dBm/100k Hz)	BWCF factor (100KHz to 3KHz)	Total Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3					
149	5745 MHz	-6.65	-7.04	-7.39	-2.24	-15.23	-17.47	5.51	<b>Complies</b>
157	5785 MHz	-6.55	-7.56	-7.93	-2.54	-15.23	-17.76	5.51	<b>Complies</b>
165	5825 MHz	-6.75	-7.64	-7.99	-2.66	-15.23	-17.89	5.51	<b>Complies</b>

Note: Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N]$  dBi


=8.49dBi > 6dBi, so the conducted power limit =8-(8.49-6)=5.51dBm.

All the test values were listed in the report.

For plots, only the channel with maximum results was shown.




**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 / 5745 MHz**




Date: 2.MAY.2012 12:12:46

**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 2 / 5745 MHz**




Date: 2.MAY.2012 12:11:57

**Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 3 / 5745 MHz**




Date: 2.MAY.2012 12:10:40

**Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 / 5755 MHz**




Date: 2.MAY.2012 12:18:41

### Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 2 / 5755 MHz




Date: 2.MAY.2012 12:18:04

### Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 3 / 5755 MHz




Date: 2.MAY.2012 12:17:20

**Power Density Plot on Configuration IEEE 802.11n MCS0 8MHz / Ant. 1 / 5775 MHz**




Date: 2.MAY.2012 12:23:40

**Power Density Plot on Configuration IEEE 802.11n MCS0 8MHz / Ant. 2 / 5775 MHz**




Date: 2.MAY.2012 12:23:07

### Power Density Plot on Configuration IEEE 802.11n MCS0 8MHz / Ant. 3 / 5775 MHz




Date: 2.MAY.2012 12:22:32

### Power Density Plot on Configuration IEEE 802.11a / Ant. 1 / 5745 MHz




Date: 2.MAY.2012 11:51:18

**Power Density Plot on Configuration IEEE 802.11a / Ant. 2 / 5745 MHz**



Date: 2.MAY.2012 11:53:05

**Power Density Plot on Configuration IEEE 802.11a / Ant. 3 / 5745 MHz**



Date: 2.MAY.2012 11:54:19

#### 4.4. 6dB Spectrum Bandwidth Measurement

##### 4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

##### 4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

##### 4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

##### 4.4.4. Test Setup Layout



##### 4.4.5. Test Deviation

There is no deviation with the original standard.

##### 4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.4.7. Test Result of 6dB Spectrum Bandwidth

<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Allen Liu	<b>Configurations</b>	IEEE 802.11n

##### Configuration IEEE 802.11n MCS0 20MHz / Ant. 1+ Ant. 2 + Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.64	17.68	500	<b>Complies</b>
157	5785 MHz	16.32	17.68	500	<b>Complies</b>
165	5825 MHz	16.68	17.64	500	<b>Complies</b>

##### Configuration IEEE 802.11n MCS0 40MHz / Ant. 1+ Ant. 2 + Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	35.20	36.00	500	<b>Complies</b>
159	5795 MHz	35.12	36.00	500	<b>Complies</b>

##### Configuration IEEE 802.11n MCS0 80MHz / Ant. 1+ Ant. 2 + Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
155	5775 MHz	75.80	75.60	500	<b>Complies</b>




<b>Temperature</b>	25°C	<b>Humidity</b>	56%
<b>Test Engineer</b>	Benson Peng	<b>Configurations</b>	IEEE 802.11a

**Configuration IEEE 802.11a / Ant. 1+ Ant. 2+ Ant. 3**


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.32	16.56	500	<b>Complies</b>
157	5785 MHz	16.36	16.52	500	<b>Complies</b>
165	5825 MHz	15.76	16.48	500	<b>Complies</b>

### 6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5785 MHz




Date: 2.MAY.2012 11:32:02

### 6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5795 MHz




Date: 2.MAY.2012 11:34:05

### 6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 80MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5775 MHz



Date: 2.MAY.2012 11:36:37

### 6 dB Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1+ Ant. 2+ Ant. 3 / 5825 MHz



Date: 2.MAY.2012 11:30:53

## 4.5. Radiated Emissions Measurement

### 4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1GHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 3MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1GHz / RB 120kHz for QP

#### 4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.5.4. Test Setup Layout

For Radiated Emissions below 1GHz



For Radiated Emissions above 1GHz



#### 4.5.5. Test Deviation

There is no deviation with the original standard.

#### 4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.5.7. Results of Radiated Emissions (9kHz~30MHz)

<b>Temperature</b>	25°C	<b>Humidity</b>	57%
<b>Test Engineer</b>	Magic Lai	<b>Configurations</b>	Normal Link
<b>Test Date</b>	Apr. 12, 2012		

<b>Freq. (MHz)</b>	<b>Level (dBuV)</b>	<b>Over Limit (dB)</b>	<b>Limit Line (dBuV)</b>	<b>Remark</b>
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

#### 4.5.8. Results of Radiated Emissions (30MHz~1GHz)

Temperature	25°C	Humidity	57%
Test Engineer	Magic Lai	Configurations	Normal Link


##### Horizontal



	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	223.03	32.99	46.00	-13.01	47.48	1.79	10.77	27.05	Peak	100	0	HORIZONTAL
2	330.70	34.17	46.00	-11.83	44.93	2.16	14.20	27.12	Peak	100	0	HORIZONTAL
3	375.32	35.60	46.00	-10.40	45.38	2.25	15.40	27.43	Peak	100	0	HORIZONTAL
4	625.58	38.82	46.00	-7.18	44.99	3.05	18.85	28.07	Peak	100	0	HORIZONTAL
5	875.84	37.98	46.00	-8.02	41.58	3.50	20.35	27.45	Peak	100	0	HORIZONTAL
6	960.23	39.28	54.00	-14.72	41.83	3.62	20.99	27.16	Peak	100	0	HORIZONTAL



**Vertical**



	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	56.19	34.17	40.00	-5.83	53.68	0.80	7.47	27.78	Peak	400	0	VERTICAL
2	94.99	35.54	43.50	-7.96	52.08	1.10	9.98	27.62	Peak	400	0	VERTICAL
3	146.40	34.77	43.50	-8.73	48.68	1.43	12.03	27.37	Peak	400	0	VERTICAL
4	375.32	33.46	46.00	-12.54	43.24	2.25	15.40	27.43	Peak	400	0	VERTICAL
5	625.58	40.87	46.00	-5.13	47.04	3.05	18.85	28.07	Peak	400	0	VERTICAL
6	960.23	41.84	54.00	-12.16	44.39	3.62	20.99	27.16	Peak	400	0	VERTICAL

**Note:**

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

#### 4.5.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

<b>Temperature</b>	25°C	<b>Humidity</b>	60%
<b>Test Engineer</b>	Serway Lee	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz CH 149 / Ant. 1 + Ant. 2 + Ant. 3
<b>Test Date</b>	Apr. 27, 2012		

##### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11487.81	59.57	74.00	-14.43	45.22	9.93	39.50	35.08	Peak	102	145	HORIZONTAL
2	11488.00	44.76	54.00	-9.24	30.41	9.93	39.50	35.08	Average	102	145	HORIZONTAL

##### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11484.49	56.10	74.00	-17.90	41.76	9.92	39.50	35.08	Peak	120	142	VERTICAL
2	11489.74	42.75	54.00	-11.25	28.40	9.93	39.50	35.08	Average	120	142	VERTICAL



<b>Temperature</b>	25°C	<b>Humidity</b>	60%
<b>Test Engineer</b>	Serway Lee	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz CH 157 / Ant. 1 + Ant. 2 + Ant. 3
<b>Test Date</b>	Apr. 27, 2012		

**Horizontal**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11568.20	45.34	54.00	-8.66	31.01	9.95	39.47	35.09	Average	101	146	HORIZONTAL
2	11568.46	59.82	74.00	-14.18	45.49	9.95	39.47	35.09	Peak	101	146	HORIZONTAL

**Vertical**

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11570.07	42.87	54.00	-11.13	28.54	9.95	39.47	35.09	Average	116	143	VERTICAL
2	11570.40	57.94	74.00	-16.06	43.61	9.95	39.47	35.09	Peak	116	143	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	60%
<b>Test Engineer</b>	Serway Lee	<b>Configurations</b>	IEEE 802.11n MCS0 20MHz CH 165 / Ant. 1 + Ant. 2 + Ant. 3
<b>Test Date</b>	Apr. 27, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11648.29	45.85	54.00	-8.15	31.50	9.98	39.44	35.07	Average	100	145	HORIZONTAL
2	11648.48	61.84	74.00	-12.16	47.49	9.98	39.44	35.07	Peak	100	145	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11647.20	43.88	54.00	-10.12	29.53	9.98	39.44	35.07	Average	116	141	VERTICAL
2	11647.32	59.88	74.00	-14.12	45.53	9.98	39.44	35.07	Peak	116	141	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	60%
<b>Test Engineer</b>	Serway Lee	<b>Configurations</b>	IEEE 802.11n MCS0 40MHz CH 151 / Ant. 1 + Ant. 2 + Ant. 3
<b>Test Date</b>	Apr. 27, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11510.04	56.14	74.00	-17.86	41.81	9.93	39.50	35.10	Peak	104	138	HORIZONTAL
2	11510.39	41.95	54.00	-12.05	27.62	9.93	39.50	35.10	Average	104	138	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11510.37	41.11	54.00	-12.89	26.78	9.93	39.50	35.10	Average	100	186	VERTICAL
2	11510.46	55.41	74.00	-18.59	41.08	9.93	39.50	35.10	Peak	100	186	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	60%
<b>Test Engineer</b>	Serway Lee	<b>Configurations</b>	IEEE 802.11n MCS0 40MHz CH 159 / Ant. 1 + Ant. 2 + Ant. 3
<b>Test Date</b>	Apr. 27, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11583.08	42.09	54.00	-11.91	27.75	9.95	39.47	35.08	Average	101	144	HORIZONTAL
2	11588.01	55.66	74.00	-18.34	41.31	9.96	39.47	35.08	Peak	101	144	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11580.03	54.26	74.00	-19.74	39.92	9.95	39.47	35.08	Peak	121	277	VERTICAL
2	11580.96	40.66	54.00	-13.34	26.32	9.95	39.47	35.08	Average	121	277	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	60%
<b>Test Engineer</b>	Serway Lee	<b>Configurations</b>	IEEE 802.11n MCS0 80MHz CH 155/ Ant. 1 + Ant. 2 + Ant. 3
<b>Test Date</b>	Apr. 27, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11540.00	55.72	74.00	-18.28	41.38	9.94	39.49	35.09	Peak	100	117	HORIZONTAL
2	11543.27	43.14	54.00	-10.86	28.80	9.94	39.49	35.09	Average	100	117	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11541.22	42.33	54.00	-11.67	27.99	9.94	39.49	35.09	Average	100	212	VERTICAL
2	11552.08	54.86	74.00	-19.14	40.53	9.94	39.48	35.09	Peak	100	212	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	60%
<b>Test Engineer</b>	Serway Lee	<b>Configurations</b>	IEEE 802.11a CH 149 / Ant. 1 + Ant.2 + Ant. 3
<b>Test Date</b>	Apr. 27, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11492.34	44.71	54.00	-9.29	30.36	9.93	39.50	35.08	Average	105	149	HORIZONTAL
2	11492.63	60.03	74.00	-13.97	45.68	9.93	39.50	35.08	Peak	105	149	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11489.71	41.44	54.00	-12.56	27.09	9.93	39.50	35.08	Average	100	299	VERTICAL
2	11490.16	55.07	74.00	-18.93	40.72	9.93	39.50	35.08	Peak	100	299	VERTICAL



<b>Temperature</b>	25°C	<b>Humidity</b>	60%
<b>Test Engineer</b>	Serway Lee	<b>Configurations</b>	IEEE 802.11a CH 157 / Ant. 1 + Ant.2 + Ant. 3
<b>Test Date</b>	Apr. 27, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11572.34	60.78	74.00	-13.22	46.44	9.95	39.47	35.08	Peak	101	150	HORIZONTAL
2	11572.41	45.28	54.00	-8.72	30.94	9.95	39.47	35.08	Average	101	150	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11569.94	56.09	74.00	-17.91	41.76	9.95	39.47	35.09	Peak	120	139	VERTICAL
2	11570.00	42.67	54.00	-11.33	28.34	9.95	39.47	35.09	Average	120	139	VERTICAL

<b>Temperature</b>	25°C	<b>Humidity</b>	60%
<b>Test Engineer</b>	Serway Lee	<b>Configurations</b>	IEEE 802.11a CH 165 / Ant. 1 + Ant.2 + Ant. 3
<b>Test Date</b>	Apr. 27, 2012		

### Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11652.85	60.07	74.00	-13.93	45.72	9.98	39.44	35.07	Peak	101	144	HORIZONTAL
2	11653.08	45.98	54.00	-8.02	31.63	9.98	39.44	35.07	Average	101	144	HORIZONTAL

### Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11580.03	54.26	74.00	-19.74	39.92	9.95	39.47	35.08	Peak	121	277	VERTICAL
2	11580.96	40.66	54.00	-13.34	26.32	9.95	39.47	35.08	Average	121	277	VERTICAL

### Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 4.6. Band Edge Emissions Measurement

### 4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

### 4.6.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

### 4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

### 4.6.5. Test Deviation


There is no deviation with the original standard.

### 4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


### 4.6.7. Test Result of Outband Emissions

#### Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5745 MHz




Date: 2.MAY.2012 21:04:09

#### Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5825 MHz




Date: 2.MAY.2012 21:00:55

**Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5755 MHz**




Date: 2.MAY.2012 21:07:47

**Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5795 MHz**




Date: 2.MAY.2012 21:06:23

**Band Edge Plot on Configuration IEEE 802.11n MCS0 80MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5775 MHz**




Date: 2.MAY.2012 21:17:27

**Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3 / 5745 MHz**



Date: 2.MAY.2012 20:57:09

**Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3 / 5825 MHz**



Date: 2.MAY.2012 20:58:55

## **4.7. Antenna Requirements**

### **4.7.1. Limit**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### **4.7.2. Antenna Connector Construction**

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.



## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Sep. 14, 2011	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 14, 2011	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9K ~ 30MHz	Nov. 30, 2011	Conduction (CO01-CB)
PULSE LIMITER	R&S	ESH3-Z2	100430	9K-30MHz	Feb. 03, 2012	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	0.15MHz~30MHz	Dec. 4, 2011	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Jan. 11, 2012	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 25, 2011	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 22, 2011	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 17, 2011	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 29, 2011	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 29, 2011	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100056	9KHz~40GHz	Nov. 03, 2011	Radiation (03CH01-CB))
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 20, 2012	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Sep. 09, 2010*	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N/A	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N/A	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2011	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz – 26.5 GHz	Nov. 17, 2011	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz – 26.5 GHz	Nov. 17, 2011	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 17, 2011	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 17, 2011	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9KHz~40GHz	Sep. 26, 2011	Conducted (TH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	May 20, 2011	Conducted (TH01-CB)
Thermo-Hygro Meter	N/A	HC 520	#1	15~70 degree	Nov. 02, 2011	Conducted (TH01-CB)
Signal Generator	R&S	SMR40	100302	10MHz-40GHz	Nov. 22, 2011	Conducted (TH01-CB)
RF Power Divider	HP	11636A	00306	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Power Splitter	Anaren	44100	1839	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Power Splitter	Anaren	42100	17930	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-12	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-13	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Nov. 01, 2011	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Nov. 01, 2011	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

Note: “\*\*” Calibration Interval of instruments listed above is two years.

## 6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

## 7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-110702

財團法人全國認證基金會  
Taiwan Accreditation Foundation

### Certificate of Accreditation

This is to certify that

**Sporton International Inc.**  
**EMC & Wireless Communications Laboratory**  
No.52, Hwa Ya 1st Road, Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,  
Taiwan, R.O.C.

**is accredited in respect of laboratory**

<b>Accreditation Criteria</b>	: ISO/IEC 17025:2005
<b>Accreditation Number</b>	: 1190
<b>Originally Accredited</b>	: December 15, 2003
<b>Effective Period</b>	: January 10, 2010 to January 09, 2013
<b>Accredited Scope</b>	: Testing Field, see described in the Appendix
<b>Specific Accreditation Program</b>	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities

  
Jay-San Chen  
President, Taiwan Accreditation Foundation  
Date : July 02, 2011

P1, total 22 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix