

FCC RADIO TEST REPORT

Applicant's company	BUFFALO INC.
Applicant Address	4-15, Shibata Hondori, Minami-ku, Nagoya 457-8520, Japan
FCC ID	FDI-09102030-0
Manufacturer's company	Cameo Communications, Inc.
Manufacturer Address	No.42 Sec. 6, Mincyuan E. Rd., Neihu District, Taipei City 114, Taiwan

Product Name	EWC USB adapter
Brand Name	BUFFALO INC.
Model Name	WLI-U2-G300N
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Receive Date	Aug. 28, 2006
Final Test Date	Oct. 11, 2006
Submission Type	Original Equipment



Statement

Test result included is only for the Draft n part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Lab Code: 200079-0

Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	4
3.3. Table for Filed Antenna.....	5
3.4. Table for Carrier Frequencies	5
3.5. Table for Test Modes	6
3.6. Table for Testing Locations.....	6
3.7. Table for Supporting Units	6
3.8. Table for Parameters of Test Software Setting	7
3.9. Test Configurations	8
4. TEST RESULT	11
4.1. AC Power Line Conducted Emissions Measurement.....	11
4.2. Maximum Peak Output Power Measurement	18
4.3. Power Spectral Density Measurement	20
4.4. 6dB Spectrum Bandwidth Measurement	28
4.5. Radiated Emissions Measurement	36
4.6. Band Edge Emissions Measurement	72
4.7. Antenna Requirements	85
5. LIST OF MEASURING EQUIPMENTS	86
6. TEST LOCATION.....	88
7. NVLAP CERTIFICATE OF ACCREDITATION	89
APPENDIX A. PHOTOGRAPHS OF EUT.....	A1 ~ A7
APPENDIX B. TEST PHOTOS.....	B1 ~ B9
APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE.....	C1 ~C4

History of This Test Report

Original Issue Date: Oct. 19, 2006

Report No.: FR682817AA

☒ No additional attachment.

☐ Additional attachment were issued as following record:

Attachment No.	Issue Date	Description



1. CERTIFICATE OF COMPLIANCE

Product Name : EWC USB adapter
Brand Name : BUFFALO INC.
Model Name : WLI-U2-G300N
Applicant : BUFFALO INC.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sportow International as requested by the applicant to evaluate the EMC performance of the product sample received on Aug. 28, 2006 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

Sharon Jiang 20.10.06

Prepared By:

Sharon Jiang / Specialist

Steven Lu 20.10.06

Tested By:

Steven Lu / Engineer

Wayne Hsu 20.10.06

Reviewed By:

Wayne Hsu

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	12.68 dB
4.2	15.247(b)(3)	Maximum Peak Conducted Output Power	Complies	13.6 dB
4.3	15.247(e)	Power Spectral Density	Complies	24.05 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	2.01 dB
4.6	15.247(d)	Band Edge Emissions	Complies	3.28 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	$\pm 2.26\text{dB}$	Confidence levels of 95%
Maximum Peak Conducted Output Power	$\pm 0.5\text{dB}$	Confidence levels of 95%
Power Spectral Density	$\pm 0.71\text{dB}$	Confidence levels of 95%
6dB Spectrum Bandwidth	$\pm 6.25 \times 10^{-7}$	Confidence levels of 95%
Radiated Emissions/ Band Edge Emissions	$\pm 3.72\text{dB}$	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From Host system
Modulation	see the below table for Draft n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for Draft n
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11 for 20MHz bandwidth ; 7 for 40MHz bandwidth
Channel Band Width (99%)	MCS8 (20MHz) : 17.72 MHz MCS8 (40MHz) : 36.32 MHz
Conducted Output Power	MCS8(20MHz) : 16.40 dBm MCS8 (40MHz) : 16.33 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna & Band width

Antenna	Single (TX)		Two (TX)	
Band width Mode	20 MHz	40 MHz	20 MHz	40 MHz
Draft n	V	V	V	V

Draft n spec

MCS Index	Nss	Modulation	R	NBPSC	NCBPS		NDBPS		Datarate(Mbps)			
									800nsGI		400nsGI	
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5	7.200	15
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0	14.400	30
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5	21.700	45
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0	28.900	60
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0	43.300	90
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0	57.800	120
6	1	64-QAM	3/4	6	312	648	234	486	58.5	121.5	65.000	135
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0	72.200	150
8	2	BPSK	1/2	1	104	216	52	108	13.0	27.0	14.444	30
9	2	QPSK	1/2	2	208	432	104	216	26.0	54.0	28.889	60
10	2	QPSK	3/4	2	208	432	156	324	39.0	81.0	43.333	90
11	2	16-QAM	1/2	4	416	864	208	432	52.0	108.0	57.778	120
12	2	16-QAM	3/4	4	416	864	312	648	78.0	162.0	86.667	180
13	2	64-QAM	2/3	6	624	1296	416	864	104.0	216.0	115.556	240
14	2	64-QAM	3/4	6	624	1296	468	972	117.0	243.0	130.000	270
15	2	64-QAM	5/6	6	624	1296	520	1080	130.0	270.0	144.444	300

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

3.2. Accessories

USB Cable	Cable Lenth
1	0.5m, Shielded
2	2m, Shielded (with Core)

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
A	SmartAnt	CAM04-050060	Dipole Antenna	UFL	2.00
B	SmartAnt	CAM04-050060	Dipole Antenna	UFL	2.00

3.4. Table for Carrier Frequencies

There are two bandwidth systems for Draft n.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

For both 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz		

For Draft n, the two TX Ant. A & Ant. B could transmit simultaneously.

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Channel	Antenna	USB Cable
AC Power Line Conducted Emissions	Normal Link	6	A+B	1 / 2
6dB Spectrum Bandwidth	MCS8/20MHz	1/6/11	A / A+B	NA
	MCS8/40MHz	3/6/9	A / A+B	NA
Maximum Peak Conducted Output Power Power Spectral Density	MCS8/20MHz	1/6/11	A / A+B	NA
	MCS8/40MHz	3/6/9	A / A+B	NA
Radiated Emissions 9kHz~1GHz	11n /BPSK	6	A / A+B	1 / 2
Radiated Emissions 1GHz~10 th Harmonic	MCS8/20MHz	1/6/11	A / A+B	2
	MCS8/40MHz	3/6/9	A / A+B	2
Band Edge Emissions	MCS8/20MHz	1/11	A / A+B	2
	MCS8/40MHz	3/9	A / A+B	2

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
CO04-HY	Conduction	Hwa Ya	101377	IC 4088	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D505	E2K24GBRL
Printer	EPSON	LQ-300	DOC
Modem	ACEEX	DM-1414	IFAXDM1414
AP	3COM	AP2750	O9C-AP2750

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of Draft n MCS8 20MHz Ant. A

Test Software Version	DutApiClient_Usb		
Frequency	2412 MHz	2437 MHz	2462 MHz
Draft n Ant. A	4C	4B	4B

Power Parameters of Draft n MCS8 20MHz Ant. A + Ant. B

Test Software Version	DutApiClient_Usb		
Frequency	2412 MHz	2437 MHz	2462 MHz
Draft n Ant. A	4C	4B	4B
Draft n Ant. B	4D	4C	4C

Power Parameters of Draft n MCS8 40MHz Ant. A

Test Software Version	DutApiClient_Usb		
Frequency	2422 MHz	2437 MHz	2452 MHz
Draft n Ant. A	4E	4D	4D

Power Parameters of Draft n MCS8 40MHz Ant. A + Ant. B

Test Software Version	DutApiClient_Usb		
Frequency	2422 MHz	2437 MHz	2452 MHz
Draft n Ant. A	4E	4D	4D
Draft n Ant. B	50	4F	4F

An executive program, EMCTEST.EXE under WIN XP, which generates a complete line of continuously repeating " H " pattern was used as the test software.

The program was executed as follows:

Turn on the power of all equipment.

The NB sends " H " messages to the panel, and the panel displays " H " patterns on the screen.

The NB sends " H " messages to the printer, then the printer prints them on the paper.

The NB sends " H " messages to the modem.

At the same time, the following programs were executed:

Executed "ping.exe" to link with the remote workstation to receive and transmit data by WLAN.


Executed " DutApiClient_Usb " to control the EUT continuously transmit RF signal.

3.9. Test Configurations

3.9.1. Radiation Emissions Test Configuration


USB Cable 1

Test Configuration: 9KHz~1GHz




3.9.2. AC Power Line Conduction Emissions Test Configuration

USB Cable 1



WLAN AP

USB Cable 2



WLAN AP

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



1. If cables, which hang closer than 40 cm to the horizontal metal groundplane, cannot be shortened to appropriate length, the excess shall be folded back and forth forming a bundle 30 cm to 40 cm long.
2. Excess mains cord shall be bundled in the centre or shortened to appropriate length.
3. EUT is connected to one artificial mains network (AMN). All AMNs and ISNs may alternatively be connected to a vertical reference plane or metal wall.
4. All other units of a system are powered from a second AMN. A multiple outlet strip can be used for multiple mains cords.
5. AMN and ISN are 80 cm from the EUT and at least 80 cm from other units and other metal planes.
6. Mains cords and signal cables shall be positioned for their entire lengths, as far as possible, at 40 cm from the vertical reference plane.
7. Cables of hand operated devices, such as keyboards, mice, etc. shall be placed as for normal usage.
8. Peripherals shall be placed at a distance of 10 cm from each other and from the controller, except for the monitor which, if this is an acceptable installation practice, shall be placed directly on the top of the controller.
9. I/O signal cable intended for external connection.
10. The end of the I/O signal cables which are not connected to an AE may be terminated, if required, using correct terminating impedance.
11. If used, the current probe shall be placed at 0,1 m from the ISN.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	24°C	Humidity	58%
Test Engineer	Leo Hung	Phase	Line
Configuration	Normal Link / USB Cable 1		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15403	42.20	-23.58	65.78	39.96	2.04	0.20	QP
2	0.15403	29.13	-26.65	55.78	26.89	2.04	0.20	AVERAGE
3	0.18152	42.67	-21.74	64.42	40.88	1.59	0.20	QP
4	0.18152	29.74	-24.67	54.42	27.95	1.59	0.20	AVERAGE
5	0.19344	40.63	-23.26	63.89	39.26	1.17	0.20	QP
6	0.19344	25.81	-28.08	53.89	24.44	1.17	0.20	AVERAGE
7	1.991	35.19	-20.81	56.00	34.69	0.30	0.20	QP
8	1.991	24.85	-21.15	46.00	24.35	0.30	0.20	AVERAGE
9	2.055	28.73	-17.27	46.00	28.23	0.30	0.20	AVERAGE
10	2.055	36.40	-19.60	56.00	35.90	0.30	0.20	QP
11	9.913	32.79	-17.21	50.00	32.19	0.30	0.30	AVERAGE
12	9.913	38.11	-21.89	60.00	37.51	0.30	0.30	QP

Temperature	24°C	Humidity	64%
Test Engineer	Leo Hung	Phase	Neutral
Configuration	Normal Link / USB Cable 1		




	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.15160	43.53	-22.38	65.91	41.43	1.90	0.20	QP
2	0.15160	28.29	-27.62	55.91	26.19	1.90	0.20	AVERAGE
3	0.17678	42.90	-21.74	64.64	41.14	1.56	0.20	QP
4	0.17678	30.95	-23.69	54.64	29.19	1.56	0.20	AVERAGE
5	0.19969	40.70	-22.92	63.62	39.30	1.20	0.20	QP
6	0.19969	24.43	-29.19	53.62	23.03	1.20	0.20	AVERAGE
7	1.918	23.73	-22.27	46.00	23.33	0.21	0.19	AVERAGE
8	1.918	35.17	-20.83	56.00	34.77	0.21	0.19	QP
9	2.133	25.54	-20.46	46.00	25.11	0.23	0.20	AVERAGE
10	2.133	35.16	-20.84	56.00	34.73	0.23	0.20	QP
11	4.006	34.03	-21.97	56.00	33.43	0.30	0.30	QP
12	4.006	25.95	-20.05	46.00	25.35	0.30	0.30	AVERAGE

Note:


Level = Read Level + LISN Factor + Cable Loss.

Temperature	24°C	Humidity	58%
Test Engineer	Leo Hung	Phase	Line
Configuration	Normal Link / USB Cable 2		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15650	52.97	-12.68	65.65	50.70	2.07	0.20	QP
2	0.15650	36.34	-19.31	55.65	34.07	2.07	0.20	AVERAGE
3	0.17584	33.29	-21.39	54.68	31.31	1.78	0.20	AVERAGE
4	0.17584	48.54	-16.14	64.68	46.56	1.78	0.20	QP
5	0.21620	27.85	-25.12	52.96	26.51	1.14	0.20	AVERAGE
6	0.21620	43.48	-19.49	62.96	42.14	1.14	0.20	QP
7	2.055	40.23	-15.77	56.00	39.73	0.30	0.20	QP
8	2.055	30.23	-15.77	46.00	29.73	0.30	0.20	AVERAGE
9	4.070	38.57	-17.43	56.00	37.88	0.39	0.30	QP
10	4.070	31.34	-14.66	46.00	30.65	0.39	0.30	AVERAGE
11	5.744	29.12	-20.88	50.00	28.52	0.30	0.30	AVERAGE
12	5.744	37.56	-22.44	60.00	36.96	0.30	0.30	QP

Temperature	24°C	Humidity	64%
Test Engineer	Leo Hung	Phase	Neutral
Configuration	Normal Link / USB Cable 2		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.16589	46.88	-18.28	65.16	44.90	1.78	0.20	QP
2	0.16589	31.86	-23.30	55.16	29.88	1.78	0.20	AVERAGE
3	0.19863	37.07	-26.60	63.67	35.69	1.18	0.20	QP
4	0.19863	20.39	-33.28	53.67	19.01	1.18	0.20	AVERAGE
5	0.24682	39.92	-21.94	61.86	38.89	0.83	0.20	QP
6	0.24682	29.21	-22.65	51.86	28.18	0.83	0.20	AVERAGE
7	2.077	39.86	-16.14	56.00	39.44	0.22	0.20	QP
8	2.077	30.60	-15.40	46.00	30.18	0.22	0.20	AVERAGE
9	4.027	37.52	-18.48	56.00	36.92	0.30	0.30	QP
10	4.027	29.80	-16.20	46.00	29.20	0.30	0.30	AVERAGE
11	10.125	36.39	-23.61	60.00	35.77	0.30	0.32	QP
12	10.125	30.95	-19.05	50.00	30.33	0.30	0.32	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Peak Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Peak Sensor	NRV-Z32 (model 04)

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Peak Output Power

Temperature	24°C	Humidity	58%
Test Engineer	Leo Hung	Configurations	Draft n

Configuration Draft n MCS8 20MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	13.4	30.00	Complies
6	2437 MHz	13.52	30.00	Complies
11	2462 MHz	13.22	30.00	Complies

Configuration Draft n MCS8 20MHz Ant. A + Ant. B

Channel	Frequency	Ant. A Port (dBm)	Ant. B Port (dBm)	Combination Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	13.4	13.3	16.36	30.00	Complies
6	2437 MHz	13.52	13.27	16.40	30.00	Complies
11	2462 MHz	13.22	13.17	16.20	30.00	Complies

Configuration Draft n MCS8 40MHz Ant. A

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	13.25	30.00	Complies
6	2437 MHz	13.34	30.00	Complies
9	2452 MHz	13.47	30.00	Complies

Configuration Draft n MCS8 40MHz Ant. A + Ant. B

Channel	Frequency	Ant. A Port (dBm)	Ant. B Port (dBm)	Combination Conducted Power (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	13.25	13.12	16.19	30.00	Complies
6	2437 MHz	13.34	13.24	16.30	30.00	Complies
9	2452 MHz	13.47	13.17	16.33	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	24°C	Humidity	58%
Test Engineer	Leo Hung	Configurations	Draft n

Configuration Draft n MCS8 20MHz Ant. A

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-18.91	8.00	Complies
6	2437 MHz	-19.51	8.00	Complies
11	2462 MHz	-20.5	8.00	Complies

Configuration Draft n MCS8 20MHz Ant. A + Ant. B

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-16.8	8.00	Complies
6	2437 MHz	-16.36	8.00	Complies
11	2462 MHz	-16.8	8.00	Complies


Configuration Draft n MCS8 40MHz Ant. A

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	-21.18	8.00	Complies
6	2437 MHz	-20.93	8.00	Complies
9	2452 MHz	-21.31	8.00	Complies

Configuration Draft n MCS8 40MHz Ant. Ant. A + Ant. B


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
3	2422 MHz	-16.43	8.00	Complies
6	2437 MHz	-16.66	8.00	Complies
9	2452 MHz	-16.05	8.00	Complies

Power Density Plot on Configuration Drafft n MCS8 20MHz Ant. A / 2412 MHz




Date: 3.OCT.2006 09:13:16

Power Density Plot on Configuration Drafft n MCS8 20MHz Ant. A / 2437 MHz




Date: 3.OCT.2006 09:14:36

Power Density Plot on Configuration Drafft n MCS8 20MHz Ant. A / 2462 MHz




Date: 3.OCT.2006 09:15:32

Power Density Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. B / 2412 MHz




Date: 3.OCT.2006 08:22:18

Power Density Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. B / 2437 MHz




Date: 3.OCT.2006 08:22:57

Power Density Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. B/ 2462 MHz




Date: 3.OCT.2006 08:21:55

Power Density Plot on Configuration Drafft n MCS8 40MHz Ant. A / 2422 MHz




Date: 3.OCT.2006 09:19:55

Power Density Plot on Configuration Drafft n MCS8 40MHz Ant. A / 2437 MHz




Date: 3.OCT.2006 09:25:11

Power Density Plot on Configuration Drafft n MCS8 40MHz Ant. A / 2452 MHz




Date: 3.OCT.2006 09:26:13

Power Density Plot on Configuration Drafft n MCS8 40MHz Ant. A + Ant. B/ 2422 MHz




Date: 3.OCT.2006 07:56:03

Power Density Plot on Configuration Drafft n MCS8 40MHz Ant. A + Ant. B / 2437 MHz



Date: 3.OCT.2006 08:02:50

Power Density Plot on Configuration Drafft n MCS8 40MHz Ant. A + Ant. B / 2452 MHz



Date: 3.OCT.2006 08:09:37

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the Spectrum Analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	24°C	Humidity	58%
Test Engineer	Leo Hung	Configurations	Draft n

Configuration Draft n MCS8 20MHz Ant. A

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	17.8	17.72	500	Complies
6	2437 MHz	17.8	17.72	500	Complies
11	2462 MHz	17.8	17.72	500	Complies

Configuration Draft n MCS8 20MHz Ant. A + Ant. B

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.44	17.08	500	Complies
6	2437 MHz	16.48	16.96	500	Complies
11	2462 MHz	16.68	17.04	500	Complies


Configuration Draft n MCS8 40MHz Ant. A

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	36.56	36.32	500	Complies
6	2437 MHz	36.56	36.24	500	Complies
9	2452 MHz	36.56	36.24	500	Complies

Configuration Draft n MCS8 40MHz Ant. A + Ant. B


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	36.16	36.24	500	Complies
6	2437 MHz	36.24	36.16	500	Complies
9	2452 MHz	36.08	36.16	500	Complies

6 dB Bandwidth Plot on Configuration Draft n MCS8 20MHz Ant. A / 2412 MHz




Date: 3.OCT.2006 09:12:51

6 dB Bandwidth Plot on Configuration Draft n MCS8 20MHz Ant. A / 2437 MHz




Date: 3.OCT.2006 09:14:20

6 dB Bandwidth Plot on Configuration Draft n MCS8 20MHz Ant. A / 2462 MHz




Date: 3.OCT.2006 09:15:16

6 dB Bandwidth Plot on Configuration Draft n MCS8 20MHz Ant. A + Ant. B / 2412 MHz




Date: 3.OCT.2006 08:14:14

6 dB Bandwidth Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. B / 2437 MHz




Date: 3.OCT.2006 08:18:51

6 dB Bandwidth Plot on Configuration Drafft n MCS8 20MHz Ant. A + Ant. B / 2462 MHz




Date: 3.OCT.2006 08:19:49

6 dB Bandwidth Plot on Configuration Draft n MCS8 40MHz Ant. A / 2422 MHz




Date: 3.OCT.2006 09:19:29

6 dB Bandwidth Plot on Configuration Draft n MCS8 40MHz Ant. A / 2437 MHz




Date: 3.OCT.2006 09:24:10

6 dB Bandwidth Plot on Configuration Draft n MCS8 40MHz Ant. A / 2452 MHz




Date: 3.OCT.2006 09:25:48

6 dB Bandwidth Plot on Configuration Draft n MCS8 40MHz Ant. A + Ant. B / 2422 MHz




Date: 3.OCT.2006 07:54:38

6 dB Bandwidth Plot on Configuration Draft n MCS8 40MHz Ant. A + Ant. B / 2437 MHz



Date: 3.OCT.2006 08:04:13

6 dB Bandwidth Plot on Configuration Draft n MCS8 40MHz Ant. A + Ant. B / 2452 MHz



Date: 3.OCT.2006 08:07:17

4.5. Radiated Emissions Measurement

4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1000KHz / 1000KHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	23°C	Humidity	60%
Test Engineer	Jordan Hsiao	Configurations	Draft n Ch 6 40MHz Ant. A + Ant. B / USB Cable 2

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	23°C	Humidity	60%
Test Engineer	Jordan Hsiao	Configurations	Draft n 40MHz Ch 6 Ant. A / USB Cable 1

Vertical



	Freq	Level	Over	Limit	Read	Cable	Preamp		Ant	TableAntenna
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Remark	Pos	Pos Factor
			dB	dBuV/m	dBuV	dB	dB		cm	deg dB/m
1 @	31.940	36.31	-3.69	40.00	48.39	0.93	31.67	Peak	---	18.66
2 @	90.140	34.38	-9.12	43.50	55.09	1.43	31.55	Peak	---	9.40
3 @	198.780	35.97	-7.53	43.50	55.28	2.00	31.45	Peak	---	10.14
4 @	388.900	41.06	-4.94	46.00	53.17	2.63	31.08	Peak	---	16.34
5 @	514.030	39.00	-7.00	46.00	48.44	3.27	30.89	Peak	---	18.17
6 @	599.390	41.21	-4.79	46.00	49.76	3.10	30.75	Peak	---	19.10

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1 ☐	31.940	36.08	-3.92	40.00	48.16	0.93	31.67	Peak	---	---	18.66
2 ☐	90.140	32.18	-11.32	43.50	52.90	1.43	31.55	Peak	---	---	9.40
3 ☐	113.420	33.64	-9.86	43.50	51.04	1.50	31.74	Peak	---	---	12.84
4 ☐	256.980	34.51	-11.49	46.00	49.73	2.46	31.35	Peak	---	---	13.67
5 ☐	385.990	37.40	-8.60	46.00	49.60	2.62	31.09	Peak	---	---	16.27
6 ☐	599.390	36.71	-9.29	46.00	45.26	3.10	30.75	Peak	---	---	19.10

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.




Temperature	23°C	Humidity	60%
Test Engineer	Jordan Hsiao	Configurations	Draft n 40MHz Ch 6 Ant. A / USB Cable 2

Vertical



	Freq	Level	Over	Limit	Read	Cable	Preamp	Remark	Ant	TableAntenna	
			Limit	Line	Level	Loss	Factor		Pos	Pos	Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1 @	31.940	36.24	-3.76	40.00	48.32	0.93	31.67	Peak	---	---	18.66
2 @	87.230	32.80	-7.20	40.00	54.11	1.45	31.63	Peak	---	---	8.86
3 @	385.990	39.32	-6.68	46.00	51.52	2.62	31.09	Peak	---	---	16.27
4 @	451.950	37.34	-8.66	46.00	48.12	2.92	30.92	Peak	---	---	17.23
5 @	517.910	38.56	-7.44	46.00	47.91	3.26	30.87	Peak	---	---	18.25
6 @	599.390	38.97	-7.03	46.00	47.53	3.10	30.75	Peak	---	---	19.10
7 @	749.740	36.95	-9.05	46.00	43.02	3.90	30.27	Peak	---	---	20.30

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1	31.940	36.16	-3.84	40.00	48.24	0.93	31.67	Peak	---	---	18.66
2	148.340	33.65	-9.85	43.50	52.05	1.83	31.54	Peak	---	---	11.31
3	256.980	37.72	-8.28	46.00	52.94	2.46	31.35	Peak	---	---	13.67
4	385.990	37.64	-8.36	46.00	49.84	2.62	31.09	Peak	---	---	16.27
5	450.980	33.80	-12.20	46.00	44.59	2.92	30.92	Peak	---	---	17.21
6	599.390	33.53	-12.47	46.00	42.08	3.10	30.75	Peak	---	---	19.10

Note:


The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


Temperature	23°C	Humidity	60%
Test Engineer	Jordan Hsiao	Configurations	Draft n 40MHz Ch 6 Ant. A+ Ant. B / USB Cable 1

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	TableAntenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1	31.940	35.59	-4.41	40.00	47.67	0.93	31.67	Peak	---	---	18.66
2	90.140	34.39	-9.11	43.50	55.11	1.43	31.55	Peak	---	---	9.40
3	141.550	36.42	-7.08	43.50	54.59	1.70	31.56	Peak	---	---	11.69
4	388.900	39.36	-6.64	46.00	51.46	2.63	31.08	Peak	---	---	16.34
5	450.980	39.95	-6.05	46.00	50.75	2.92	30.92	Peak	---	---	17.21
6	516.940	40.11	-5.89	46.00	49.49	3.27	30.88	Peak	---	---	18.23
7	598.420	39.73	-6.27	46.00	48.29	3.10	30.75	Peak	---	---	19.09

Horizontal



	Freq	Level	Over	Limit	Read	Cable	Preamp		Ant	TableAntenna
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Remark	Pos	Pos Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg dB/m
1	31.940	36.07	-3.93	40.00	48.15	0.93	31.67	Peak	---	18.66
2	90.140	32.59	-10.91	43.50	53.31	1.43	31.55	Peak	---	9.40
3	113.420	33.04	-10.46	43.50	50.45	1.50	31.74	Peak	---	12.84
4	257.950	33.16	-12.84	46.00	48.24	2.48	31.35	Peak	---	13.78
5	388.900	37.78	-8.22	46.00	49.88	2.63	31.08	Peak	---	16.34
6	517.910	36.24	-9.76	46.00	45.59	3.26	30.87	Peak	---	18.25
7	595.510	35.95	-10.05	46.00	44.51	3.11	30.75	Peak	---	19.08

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Pol. : V is Vertical Polarization ; H is Horizontal Polarization.


Temperature	23°C	Humidity	60%
Test Engineer	Jordan Hsiao	Configurations	Draft n 40MHz Ch 6 Ant. A+ Ant. B / USB Cable 2

Vertical



	Freq	Level	Over	Limit	Read	Cable	Preamp		Ant	TableAntenna
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Remark	Pos	Pos Factor
			dB	dBuV/m	dBuV	dB	dB		cm	deg dB/m
1 @	31.940	36.23	-3.77	40.00	48.31	0.93	31.67	Peak	---	18.66
2 @	113.420	33.21	-10.29	43.50	50.62	1.50	31.74	Peak	---	12.84
3 @	388.900	38.70	-7.30	46.00	50.80	2.63	31.08	Peak	---	16.34
4 @	498.510	37.74	-8.26	46.00	47.52	3.28	30.94	Peak	---	17.87
5 @	516.940	40.21	-5.79	46.00	49.59	3.27	30.88	Peak	---	18.23
6 @	595.510	40.26	-5.74	46.00	48.82	3.11	30.75	Peak	---	19.08

Horizontal



	Freq	Level	Over	Limit	Read	Cable	Preamp		Ant	Table	Antenna
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Remark	Pos	Pos	Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1	31.940	36.38	-3.62	40.00	48.46	0.93	31.67	Peak	---	---	18.66
2	136.700	38.79	-4.71	43.50	56.68	1.70	31.60	Peak	---	---	12.01
3	257.950	36.26	-9.74	46.00	51.34	2.48	31.35	Peak	---	---	13.78
4	388.900	35.25	-10.75	46.00	47.35	2.63	31.08	Peak	---	---	16.34
5	450.980	34.49	-11.51	46.00	45.28	2.92	30.92	Peak	---	---	17.21
6	595.510	38.40	-7.60	46.00	46.96	3.11	30.75	Peak	---	---	19.08

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Pol. : V is Vertical Polarization ; H is Horizontal Polarization.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)


Temperature	23°C	Humidity	60%
Test Engineer	Jordan Hsiao	Configurations	Draft n MCS8 20MHz Ch 1 Ant. A / USB Cable 2

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1	2279.890	58.09	-15.91	74.00	62.53	2.69	35.04	PEAK	100	252	27.91
2	2280.070	49.40	-4.60	54.00	53.84	2.69	35.04	AVERAGE	100	252	27.91


Horizontal



	Freq	Level	Over	Limit	Read	Cable	Preamp		Ant	TableAntenna
			Limit	Line	Level	Loss	Factor	Remark	Pos	Pos Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg dB/m
1	2279.910	52.82	-21.18	74.00	57.26	2.69	35.04	PEAK	100	166 27.91
2	2280.030	44.21	-9.79	54.00	48.65	2.69	35.04	AVERAGE	100	166 27.91


Temperature	23°C	Humidity	60%
Test Engineer	Jordan Hsiao	Configurations	Draft n MCS8 20MHz Ch 6 Ant. A / USB Cable 2

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1	2280.030	50.50	-3.50	54.00	54.94	2.69	35.04	AVERAGE	100	14	27.91
2	2280.050	59.64	-14.36	74.00	64.09	2.69	35.04	PEAK	100	14	27.91


Horizontal



	Freq	Level	Over	Limit	Read	Cable	Preamp		Ant	Table	Antenna
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Remark	Pos	Pos	Factor
			dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1	2279.640	54.34	-19.66	74.00	58.79	2.69	35.04	PEAK	100	151	27.91
2	2280.050	45.28	-8.72	54.00	49.72	2.69	35.04	AVERAGE	100	151	27.91


Temperature	24°C	Humidity	64%
Test Engineer	Jordan Hsiao	Configurations	Draft n MCS8 20MHz Ch11 Ant. A / USB Cable 2

Vertical



	Freq	Level	Over	Limit	Read	Cable	Preamp		Ant	Table	Antenna
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Remark	Pos	Pos	Factor
			dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1	2279.900	61.08	-12.92	74.00	65.53	2.69	35.04	PEAK	100	27	27.91
2	2280.070	51.99	-2.01	54.00	56.43	2.69	35.04	AVERAGE	100	27	27.91


Horizontal



	Freq	Level	Over	Limit	Read	Cable	Preamp		Ant	Table	Antenna
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Remark	Pos	Pos	Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1	2279.830	56.37	-17.63	74.00	60.82	2.69	35.04	PEAK	100	164	27.91
2	2280.050	46.85	-7.15	54.00	51.29	2.69	35.04	AVERAGE	100	164	27.91


Temperature	23°C	Humidity	60%
Test Engineer	Jordan Hsiao	Configurations	Draft n MCS8 20MHz Ch 1 Ant. A + Ant. B / USB Cable 2

Vertical



	Freq	Level	Over	Limit	Read	Cable	Preamp		Ant	Table	Antenna
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	Remark	Pos	Pos	Factor
			dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1	2280.020	49.59	-4.41	54.00	54.03	2.69	35.04	AVERAGE	100	26	27.91
2	2280.160	60.12	-13.88	74.00	64.56	2.69	35.04	PEAK	100	26	27.91


Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	TableAntenna Pos	Antenna Factor
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB	dB		cm	deg	dB/m
1	2280.060	44.60	-9.40	54.00	49.04	2.69	35.04	AVERAGE	100	162	27.91
2	2280.460	53.54	-20.46	74.00	57.98	2.69	35.04	PEAK	100	162	27.91


Temperature	23°C	Humidity	60%
Test Engineer	Jordan Hsiao	Configurations	Draft n MCS8 20MHz Ch 6 Ant. A + Ant. B / USB Cable 2

Vertical



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1 @	2280.070	49.18	-4.82	54.00	53.63	2.69	35.04	AVERAGE	100	14	27.91
2 @	2280.160	59.05	-14.95	74.00	63.50	2.69	35.04	PEAK	100	14	27.91

Horizontal



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Antenna Pos	Antenna Factor
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB		cm	deg	dB/m
1	2280.030	44.45	-9.55	54.00	48.90	2.69	35.04	AVERAGE	100	151	27.91
2	2280.310	53.85	-20.15	74.00	58.30	2.69	35.04	PEAK	100	151	27.91