



FCC Test Report

Equipment : 11n/a&11n/g/b Concurrent Smart model /
11n/a,11n/g/b Single Smart model

Brand Name : BUFFALO

Model No. : WAPS-APG600H/WAPS-AG300H

FCC ID : FDI000000004

Standard : 47 CFR FCC Part 15.247

Frequency Range : 5725 MHz – 5850 MHz

Applicant : Buffalo Inc.

Manufacturer : AKAMONDORI Bldg, 30-20, Ohsu 3-chome,
Naka-ku, Nagoya,460-8315, Japan

The product sample received on Jun. 27, 2012 and completely tested on Aug. 01, 2012. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2009 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Wayne Hsu / Assistant Manager





Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Accessories	8
1.3	Support Equipment.....	8
1.4	Testing Applied Standards	8
1.5	Testing Location Information.....	9
1.6	Measurement Uncertainty	9
2	TEST CONFIGURATION OF EUT	10
2.1	The Worst Case Modulation Configuration	10
2.2	Test Channel Frequencies Configuration.....	10
2.3	The Worst Case Power Setting Parameter	11
2.4	The Worst Case Measurement Configuration.....	12
2.5	Test Setup Diagram	14
3	TRANSMITTER TEST RESULT	16
3.1	AC Power-line Conducted Emissions	16
3.2	6dB Bandwidth	19
3.3	RF Output Power.....	22
3.4	Power Spectral Density	28
3.5	Transmitter Radiated Bandedge Emissions.....	32
3.6	Transmitter Radiated Unwanted Emissions	39
4	TEST EQUIPMENT AND CALIBRATION DATA.....	61
5	CERTIFICATION OF TAF ACCREDITATION.....	63
APPENDIX A. TEST PHOTOS		A7
APPENDIX B. PHOTOGRAPHS OF EUT		B21



Summary of Test Result

Conformance Test Specifications					
Report Clause	Ref. Std. Clause	Description	Measured	Limit	Result
1.1.2	15.203	Antenna Requirement	Antenna connector mechanism complied	FCC 15.203	Complied
3.1	15.207	AC Power-line Conducted Emissions	0.72MHz: 28.24dBuV (17.76dB) - AV 27.89dBuV (28.11dB) - QP	FCC 15.207	Complied
3.2	15.247(a)	6dB Bandwidth	6dB Bandwidth [MHz] 5745-5825MHz(20M): 17.44 5755-5795MHz(40M): 35.28	≥500kHz	Complied
3.3	15.247(b)	RF Output Power (Maximum Peak Conducted Output Power)	Power [dBm] 5745-5825MHz: 22.45 5755-5795MHz: 22.64	Power [dBm] 5745-5825MHz: 30 5755-5795MHz: 30	Complied
3.4	15.247(d)	Power Spectral Density	PSD [dBm/3kHz] 5745-5825MHz: -14.86 5755-5795MHz: -17.57	PSD [dBm/3kHz] 5745-5825MHz: 8 5755-5795MHz: 8	Complied
3.5	15.247(c)	Transmitter Radiated Bandedge Emissions	Non-Restricted Bands: 5720.60MHz: 22.45dB Bandedge emissions not fall in restricted bands.	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied
3.6	15.247(c)	Transmitter Radiated Unwanted Emissions	Restricted Bands [dBuV/m at 1m]: 43.58MHz: 36.85 (Margin 3.15dB) - PK	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied



Revision History



1 General Description

1.1 Information

1.1.1 RF General Information

RF General Information				
Frequency Range (MHz)	IEEE Std. 802.11 Protocol	Ch. Frequency (MHz)	Channel Number	RF Output Power (dBm)
5725-5850	a	5745-5825	149-165 [5]	22.19
5725-5850	n (HT20)	5745-5825	149-165 [5]	22.45
5725-5850	n (HT40)	5755-5795	151-159 [2]	22.64

Note 1: IEEE Std. 802.11-2007 modulation consists of IEEE Std. 802.11a-1999.
Note 2: IEEE Std. 802.11n-2009 modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40.
Note 3: RF output power specifies that Maximum Peak Conducted Output Power.

Transmitter Chains & Receiver Chains Information					
IEEE Std. 802.11 Protocol	Number of Transmit Chains (N_{TX})	Number of Receive Chains (N_{RX})	Correlation Signals with Multiple N_{TX}	99% Emission Bandwidth (MHz)	Co-location
a	2	2	Correlated	16.47	Yes
n (HT20)	2	2	Uncorrelated	17.49	Yes
n (HT40)	2	2	Uncorrelated	36.18	Yes

Note 1: Co-location, Co-location is generally defined as simultaneously transmitting (co-transmitting) antennas within 20 cm of each other. (i.e., EUT has simultaneously co-transmitting that operating 2.4GHz and 5GHz.)



1.1.2 Antenna Information

Antenna Category	
<input type="checkbox"/>	Equipment placed on the market without antennas
<input type="checkbox"/>	Integral antenna (antenna permanently attached)
	<input type="checkbox"/> Temporary RF connector provided
	<input type="checkbox"/> No temporary RF connector provided Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path.
<input checked="" type="checkbox"/>	External antenna (dedicated antennas)
	<input type="checkbox"/> Single power level with corresponding antenna(s). Power Level (PL): 1
	<input checked="" type="checkbox"/> Multiple power level and corresponding antenna(s). Power Level (PL): 1~2
	<input type="checkbox"/> No RF connector provided
	<input type="checkbox"/> Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path.
	<input type="checkbox"/> RF connector provided
	<input type="checkbox"/> Unique antenna connector. (e.g., MMCX, U.FL, IPX, and RP-SMA, RP-N type...)
	<input type="checkbox"/> Standard antenna connector. (e.g., SMA, N, BNC, and TNC type...)

Antenna General Information								
Antenna Port (Total 2 Port)				2(TX/RX)				
Maximum RF Output Power Level (PL)				1				
Transmit Chains Power Distribution				<input checked="" type="checkbox"/> symmetrical distribution <input type="checkbox"/> asymmetrical distribution				
Ant. No.	PL	Ant. Port [Ant No. X connect to Ant. Port Y]	Ant. Cat.	Ant. Type	G _{ANT} (dBi)	DG (dBi) [correlated] N _{TX} = 1	DG (dBi) [uncorrelated] N _{TX} = 2	
1	1	1	Internal	Dipole	2.89	5.9	2.89	
2	1	2	Internal	Dipole	2.89			

Note 1: For all transmitter outputs with equal antenna gains, directional gain is to be computed as follows:
Any transmit signals are correlated, Directional Gain (DG) = $G_{ANT} + 10 \log(N)$ dBi
All transmit signals are completely uncorrelated, Directional Gain (DG) = G_{ANT}

Note 2: For all transmitter outputs with unequal antenna gains, directional gain is to be computed as follows:
Any transmit signals are correlated, Directional Gain (DG) = $10 \log[(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10})^2 / N]$ dBi
All transmit signals are completely uncorrelated, Directional Gain (DG) = $10 \log[(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10})/N]$ dBi



1.1.3 Type of EUT

Identify EUT	
EUT Serial Number	N/A
Presentation of Equipment	<input type="checkbox"/> Production ; <input checked="" type="checkbox"/> Pre-Production ; <input type="checkbox"/> Prototype
Type of EUT	
<input checked="" type="checkbox"/> Stand-alone	
<input type="checkbox"/> Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.: ...	
<input type="checkbox"/> Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.: ...	
<input type="checkbox"/> Other:	

1.1.4 Test Signal Duty Cycle

Operated Mode for Worst Duty Cycle		
<input type="checkbox"/> Operated normally mode for worst duty cycle		
<input checked="" type="checkbox"/> Operated test mode for worst duty cycle		
Test Signal Duty Cycle (x)	Power Duty Factor [dB] – (10 log 1/x)	Voltage Duty Factor [dB] – (20 log 1/x)
<input checked="" type="checkbox"/> 100% - IEEE 802.11a	0	0
<input checked="" type="checkbox"/> 100% - IEEE 802.11n (HT20)	0	0
<input checked="" type="checkbox"/> 100% - IEEE 802.11n (HT40)	0	0

1.1.5 EUT Operational Condition

Supply Voltage	<input checked="" type="checkbox"/> AC mains	<input type="checkbox"/> DC	
Type of DC Source	<input checked="" type="checkbox"/> Internal DC supply	<input type="checkbox"/> External DC adapter	<input type="checkbox"/> Battery



1.2 Accessories

Accessories Information				
AC Adapter	Brand Name	APD	Model Name	DA-48P12
	Power Rating	I/P: 100-240V~、50-60Hz、1.2AMax ; O/P: 12V 4A		

Note: Regarding to more detail and other information, please refer to user manual.

1.3 Support Equipment

Support Equipment - Conducted Emissions				
No.	Equipment	Brand Name	Model Name	Serial No.
1	USB Flash 1	TDK	16G	N/A
2	USB Flash 2	LITEON	2G	N/A
3	Notebook	DELL	E5520	DoC
4	iPod	Apple	A1199	DoC
5	USB Mouse	Microsoft	1113	DoC
6	Notebook (Remote Workstation)	DELL	VOSTRO 3350	DoC
7	POE (Remote Workstation)	D-Link	DWL-P200	DoC

Support Equipment - Radiated Emissions				
No.	Equipment	Brand Name	Model Name	Serial No.
1	USB Flash 1	TDK	16G	N/A
2	USB Flash 2	LITEON	2G	N/A
3	Notebook	DELL	E5520	DoC
4	USB Mouse	Microsoft	1113	DoC
5	iPod	Apple	A1199	DoC
6	Notebook (Remote Workstation)	DELL	E5520	DOC
7	POE (Remote Workstation)	D-Link	DWL-P200	DoC

1.4 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR FCC Part 15
- ANSI C63.10-2009
- FCC KDB 558074 - Guidance for Performing Compliance Measurements on DTS
- FCC KDB 662911 - Emissions Testing of Transmitters with Multiple Outputs
- FCC KDB 412172 - Guidelines for Determining the ERP and EIRP



1.5 Testing Location Information

Testing Location				
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C	TEL : 886-3-327-3456	FAX : 886-3-327-0973
Test Condition		Test Site No.	Test Engineer	Test Environment
Conducted Emission		CO01-HY	David	25.9°C / 53.6%
RF Conducted		TH01-HY	Ian	24.6°C / 44%
Radiated Emission		03CH02-HY	Hsiao	24.1°C / 64%
				28-Jun-12~17-Jul-12

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty			
Test Item	Uncertainty	Limit	
AC power-line conducted emissions	±2.26 dB	N/A	
Emission bandwidth, 6dB bandwidth	±1.42 %	N/A	
RF output power, conducted	±0.63 dB	N/A	
Power density, conducted	±0.81 dB	N/A	
Unwanted emissions, conducted	30 – 1000 MHz	±0.51 dB	N/A
	1 – 18 GHz	±0.67 dB	N/A
	18 – 40 GHz	±0.83 dB	N/A
	40 – 200 GHz	N/A	N/A
All emissions, radiated	30 – 1000 MHz	± 2.54 dB	N/A
	1 – 18 GHz	±3.59 dB	N/A
	18 – 40 GHz	±3.82 dB	N/A
	40 – 200 GHz	N/A	N/A
Temperature	±0.8 °C	N/A	
Humidity	±3 %	N/A	
DC and low frequency voltages	±3 %	N/A	
Time	±1.42 %	N/A	
Duty Cycle	±1.42 %	N/A	



2 Test Configuration of EUT

2.1 The Worst Case Modulation Configuration

Worst Modulation Used for Conformance Testing						
Power Level		1				
IEEE 802.11 Protocol	Number of Transmit Chains (N_{TX})	Data Rate / MCS	Worst Data Rate / MCS	Worst Modulation Mode	RF Output Power (dBm)	Power Spectral Density (dBm/3kHz)
a	2	6-54 Mbps	6Mbps	11A5.8G-20M	22.19	-15.80
n (HT20)	2	MCS 0-15	MCS 8	11N5.8G-20M	22.45	-14.86
n (HT40)	2	MCS 0-15	MCS 8	11N5.8G-40M	22.64	-17.57

Note 1: IEEE Std. 802.11-2007 modulation consists of IEEE Std. 802.11a-1999.

Note 2: IEEE Std. 802.11n-2009 modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40. Worst modulation mode of Guard Interval (GI) is 400ns.

Note 3: Modulation modes consist of 11A5.8-G-20M, 11N5.8G-20M, 11N5.8G-40M:
11A5.8G: IEEE 802.11a (5.8GHz Band), 11N5.8G: IEEE 802.11n (5.8GHz Band)
20M/40M: Channel Bandwidth 20MHz/40MHz

Note 4: RF output power specifies that Maximum Peak Conducted Output Power.

2.2 Test Channel Frequencies Configuration

Test Channel Frequencies Configuration		
IEEE 802.11 Protocol	Worst Modulation Mode	Test Channel Frequencies (MHz) – FX (Frequencies Abbreviations)
a	11A5.8G-20M	5745-(F1), 5785-(F2), 5825-(F3)
n (HT20)	11N5.8G-20M	5745-(F1), 5785-(F2), 5825-(F3)
n (HT40)	11N5.8G-40M	5755-(F4), 5795-(F5)

Note 1: Modulation modes consist of 11A5.8-G-20M, 11N5.8G-20M, 11N5.8G-40M:
11A5.8G: IEEE 802.11a (5.8GHz Band), 11N5.8G: IEEE 802.11n (5.8GHz Band)
20M/40M: Channel Bandwidth 20MHz/40MHz



2.3 The Worst Case Power Setting Parameter

The Worst Case Power Setting Parameter					
Power Level		1			
Test Software Version		RT 3883 QA_1.0.4.5			
Worst Modulation Mode	Number of Transmit Chains (N _{TX})	Frequency (MHz)	Power Setting	Worst Data Rate / MCS	RF Output Power (dBm)
11A5.8G-20M	2	5745	13,11	6 Mbps	21.95
11A5.8G-20M	2	5785	15,14	6 Mbps	21.99
11A5.8G-20M	2	5825	17,18	6 Mbps	22.19
11N5.8G-20M	2	5745	14,12	MCS 8	22.35
11N5.8G-20M	2	5785	16,15	MCS 8	22.45
11N5.8G-20M	2	5825	17,18	MCS 8	22.34
11N5.8G-40M	2	5755	16,14	MCS 8	22.64
11N5.8G-40M	2	5795	16,16	MCS 8	22.46

Note 1: Modulation modes consist of 11A5.8-G-20M, 11N5.8G-20M, 11N5.8G-40M:
11A5.8G: IEEE 802.11a (5.8GHz Band), 11N5.8G: IEEE 802.11n (5.8GHz Band)
20M/40M: Channel Bandwidth 20MHz/40MHz

Note 2: RF output power specifies that Maximum Peak Conducted Output Power.



2.4 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests				
Tests Item	AC power-line conducted emissions			
Condition	AC power-line conducted measurement for line and neutral			
Operating Mode	Operating Mode Description	Worst Modulation Mode	Test Freq.	Power Level
1	Normal TX + Adapter Mode	11N5.8G-20M	F2	1
2	Normal TX + POE Mode	11N5.8G-40M	F5	1

For operating mode 1 is the worst case and it was record in this test report.

The Worst Case Mode for Following Conformance Tests				
Tests Item	RF Output Power Power Spectral Density 6dB Bandwidth			
Test Condition	Conducted measurement at transmit chains			
Worst Modulation Mode	Number of Transmit Chains (N_{TX})	Worst Data Rate / MCS	Test Frequency	Power Level
11A5.8G-20M	2	6Mbps	F1, F2, F3	1
11N5.8G-20M	2	MCS 8	F1, F2, F3	1
11N5.8G-40M	2	MCS 8	F4, F5	1


The Worst Case Mode for Following Conformance Tests				
Tests Item	Transmitter Radiated Bandedge Emissions			
Test Condition	Radiated measurement			
Worst Modulation Mode	Number of Transmit Chains (N_{TX})	Worst Data Rate / MCS	Test Frequency	Power Level
11A5.8G-20M	2	6Mbps	F1, F3	1
11N5.8G-20M	2	MCS 8	F1, F3	1
11N5.8G-40M	2	MCS 8	F4, F5	1





The Worst Case Mode for Following Conformance Tests						
Tests Item	Transmitter Radiated Unwanted Emissions					
Test Condition	Radiated measurement					
User Position	<input checked="" type="checkbox"/> EUT will be placed in fixed position.					
	<input type="checkbox"/> EUT will be placed in mobile position and operating multiple positions. EUT shall be performed two or three orthogonal planes.					
	<input type="checkbox"/> EUT will be a hand-held or body-worn battery-powered devices and operating multiple positions. EUT shall be performed two or three orthogonal planes.					
Operating Mode < 1GHz	<input checked="" type="checkbox"/> 1. Normal TX + Adapter Mode					
	<input checked="" type="checkbox"/> 2. Normal TX + POE Mode					
Worst Modulation Mode	Number of Transmit Chains (N _{TX})	Worst Data Rate / MCS	Test Frequency	Power Level	Ant No.	Worst Orthogonal Planes of EUT
11A5.8G-20M	2	6Mbps	F1, F2, F3	1	1,2	X Plane
11N5.8G-20M	2	MCS 8	F1, F2, F3	1	1,2	X Plane
11N5.8G-40M	2	MCS 8	F4, F5	1	1,2	X Plane
Orthogonal Planes of EUT	X Plane		Y Plane		Z Plane	

For operating mode 1 is the worst case and it was record in this test report.

2.5 Test Setup Diagram





3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures


Test Method
<input checked="" type="checkbox"/> Refer as ANSI C63.10-2009, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup






3.1.5 Test Result of AC Power-line Conducted Emissions



Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)





3.2 6dB Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit
Systems using digital modulation techniques:
<input checked="" type="checkbox"/> 6 dB bandwidth \geq 500 kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> For the emission bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 5.1.1 Option 1 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as FCC KDB 558074, clause 5.1.2 Option 2 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.
<input checked="" type="checkbox"/> For conducted measurement.
<input type="checkbox"/> The EUT supports single transmit chain and measurements performed on this transmit chain.
<input checked="" type="checkbox"/> The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input checked="" type="checkbox"/> The EUT supports multiple transmit chains using options given below:
<input type="checkbox"/> Option 1: Multiple transmit chains measurements need to be performed on one of the active transmit chains (antenna outputs). All measurement had be performed on transmit chains 1.
<input checked="" type="checkbox"/> Option 2: Multiple transmit chains measurements need to be performed on each transmit chains individually (antenna outputs). All measurement had be performed on all transmit chains.
<input type="checkbox"/> Option 3: A power splitter/combiner shall be used to combine all the transmit chains (antenna outputs) into a single test point and record a single test point EBW.
<input type="checkbox"/> For radiated measurement. The equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted power level.

3.2.4 Test Setup





3.2.5 Test Result of Emission Bandwidth


Emission Bandwidth Result										
Power Level	1		Emission Bandwidth (MHz)							
Modulation Mode	N _{TX}	Freq. (MHz)	99% Bandwidth				6dB Bandwidth			
			Chain-Port 1	Chain-Port 2	-	-	Chain-Port 1	Chain-Port 2	-	-
11A5.8G-20M	2	5745	16.47	16.31	-	-	16.42	16.08	-	-
11A5.8G-20M	2	5785	16.41	16.47	-	-	16.26	16.36	-	-
11A5.8G-20M	2	5825	16.39	16.37	-	-	16.36	16.28	-	-
11N5.8G-20M	2	5745	17.49	17.45	-	-	17.44	17.04	-	-
11N5.8G-20M	2	5785	17.43	17.29	-	-	17.12	16.54	-	-
11N5.8G-20M	2	5825	17.41	17.37	-	-	17.06	16.84	-	-
11N5.8G-40M	2	5755	35.38	36.18	-	-	34.32	33.92	-	-
11N5.8G-40M	2	5795	35.78	35.74	-	-	33.80	35.28	-	-
Limit			N/A				≥500 kHz			
Result			Complied							

Note 1: N_{TX} = Number of Transmit Chains




Worst Emission Bandwidth Plots


11A5.8G-20M – F1 [Port 1]



11N5.8G-20M – F1 [Port 1]



11N5.8G-40M – F5 [Port 2]





3.3 RF Output Power

3.3.1 RF Output Power Limit

RF Output Power Limit	
Maximum Peak Conducted Output Power or Maximum Conducted Output Power Limit	
<input type="checkbox"/> 902-928 MHz Band:	<input type="checkbox"/> If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W) <input type="checkbox"/> If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
<input type="checkbox"/> 2400-2483.5 MHz Band:	<input type="checkbox"/> If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W) <input type="checkbox"/> Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm <input type="checkbox"/> Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm <input type="checkbox"/> Smart antenna system (SAS): <input type="checkbox"/> Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm <input type="checkbox"/> Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm <input type="checkbox"/> Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm
<input checked="" type="checkbox"/> 5725-5850 MHz Band:	<input checked="" type="checkbox"/> If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W) <input type="checkbox"/> Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm <input type="checkbox"/> Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30$ dBm
e.i.r.p. Power Limit:	
<input type="checkbox"/> 902-928 MHz Band: $P_{eirp} \leq 36$ dBm (4 W)	
<input type="checkbox"/> 2400-2483.5 MHz Band	
	<input type="checkbox"/> Point-to-multipoint systems (P2M): $P_{eirp} \leq 36$ dBm (4 W)
	<input type="checkbox"/> Point-to-point systems (P2P): $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX}])$ dBm
	<input type="checkbox"/> Smart antenna system (SAS)
	<input type="checkbox"/> Single beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	<input type="checkbox"/> Overlap beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	<input type="checkbox"/> Aggregate power on all beams: $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX} + 8])$ dBm
<input checked="" type="checkbox"/> 5725-5850 MHz Band	
	<input checked="" type="checkbox"/> Point-to-multipoint systems (P2M): $P_{eirp} \leq 36$ dBm (4 W)
	<input type="checkbox"/> Point-to-point systems (P2P): N/A
P_{Out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi. P_{eirp} = e.i.r.p. Power in dBm.	



3.3.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method			
<input checked="" type="checkbox"/> Maximum Peak Conducted Output Power	<input type="checkbox"/> Refer as FCC KDB 558074, clause 5.2.1.1 Option 1 (RBW \geq EBW method). <input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 5.2.1.2 Option 2 (integrated band power method). <input type="checkbox"/> Refer as ANSI C63.10, clause 6.10.2.1 a) for peak power meter. <input type="checkbox"/> Refer as ANSI C63.10, clause 6.10.2.1 a) for spectrum analyzer - (RBW \geq EBW). <input type="checkbox"/> Refer as ANSI C63.10, clause 6.10.2.1 b) for spectrum analyzer - BW correction factor.		
<input checked="" type="checkbox"/> Maximum Conducted (Average) Output Power	<input type="checkbox"/> Refer as FCC KDB 558074, clause 5.2.2.1 Option 1 (RMS detection with slow sweep speed). <input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 5.2.2.2 Option 2 (spectral trace averaging). <input type="checkbox"/> Refer as ANSI C63.10, clause 6.10.3.1 for spectrum analyzer - Method 1 (trace averaging). <input type="checkbox"/> Refer as ANSI C63.10, clause 6.10.3.2 for spectrum analyzer - Method 2 (zero-span averaging). <input type="checkbox"/> Refer as ANSI C63.10, clause 6.10.3.2 for spectrum analyzer - Method 3 (band power max-hold).		
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 2 for conducted measurement.	<input type="checkbox"/> The EUT supports single transmit chain and measurements performed on this transmit chain. <input checked="" type="checkbox"/> The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case. <input checked="" type="checkbox"/> For conducted measurements on devices with multiple transmit chains: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them. <input checked="" type="checkbox"/> If multiple transmit chains, EIRP calculation could be following as methods: <table border="0"><tr><td><input type="checkbox"/> Method 1: $EIRP_1 = P_1 + G_{ANT1}$; $EIRP_2 = P_2 + G_{ANT2}$; ... $EIRP_n = P_n + G_{ANTn}$ $EIRP_{total} = EIRP_1 + EIRP_2 + \dots + EIRP_n$ (calculated in linear unit [mW] and transfer to log unit [dBm])</td></tr><tr><td><input checked="" type="checkbox"/> Method 2: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$</td></tr></table>	<input type="checkbox"/> Method 1: $EIRP_1 = P_1 + G_{ANT1}$; $EIRP_2 = P_2 + G_{ANT2}$; ... $EIRP_n = P_n + G_{ANTn}$ $EIRP_{total} = EIRP_1 + EIRP_2 + \dots + EIRP_n$ (calculated in linear unit [mW] and transfer to log unit [dBm])	<input checked="" type="checkbox"/> Method 2: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$
<input type="checkbox"/> Method 1: $EIRP_1 = P_1 + G_{ANT1}$; $EIRP_2 = P_2 + G_{ANT2}$; ... $EIRP_n = P_n + G_{ANTn}$ $EIRP_{total} = EIRP_1 + EIRP_2 + \dots + EIRP_n$ (calculated in linear unit [mW] and transfer to log unit [dBm])			
<input checked="" type="checkbox"/> Method 2: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$			
<input type="checkbox"/> Refer as FCC KDB 558074, clause 2 for radiated measurement.			



3.3.4 Test Setup





3.3.5 Test Result of Maximum Peak Conducted Output Power

Maximum Peak Conducted Output Power Result											
Power Level		1	RF Output Power (dBm)								
Directional Gain (dBi)		5.9									
Modulation Mode	N _{TX}	Freq. (MHz)	Chain-Port 1	Chain-Port 2	-	-	Sum Chain	Power Limit	EIRP Power	EIRP Limit	
11A5.8G-20M	2	5745	18.87	19.00	-	-	21.95	30.0	27.85	36.0	
11A5.8G-20M	2	5785	18.84	19.11	-	-	21.99	30.0	27.89	36.0	
11A5.8G-20M	2	5825	19.16	19.20	-	-	22.19	30.0	28.09	36.0	
Result			Complied								

Note 1: N_{TX} = Number of Transmit Chains

Maximum Peak Conducted Output Power Result											
Power Level		1	RF Output Power (dBm)								
Directional Gain (dBi)		2.89									
Modulation Mode	N _{TX}	Freq. (MHz)	Chain-Port 1	Chain-Port 2	-	-	Sum Chain	Power Limit	EIRP Power	EIRP Limit	
11N5.8G-20M	2	5745	19.03	19.63	-	-	22.35	30.0	25.24	36.0	
11N5.8G-20M	2	5785	19.37	19.51	-	-	22.45	30.0	25.34	36.0	
11N5.8G-20M	2	5825	19.28	19.37	-	-	22.34	30.0	25.23	36.0	
Result			Complied								

Note 1: N_{TX} = Number of Transmit Chains

Maximum Peak Conducted Output Power Result											
Power Level		1	RF Output Power (dBm)								
Directional Gain (dBi)		2.89									
Modulation Mode	N _{TX}	Freq. (MHz)	Chain-Port 1	Chain-Port 2	-	-	Sum Chain	Power Limit	EIRP Power	EIRP Limit	
11N5.8G-40M	2	5755	19.56	19.70	-	-	22.64	30.0	25.53	36.0	
11N5.8G-40M	2	5825	19.31	19.59	-	-	22.46	30.0	25.35	36.0	
Result			Complied								

Note 1: N_{TX} = Number of Transmit Chains



3.3.6 Test Result of Maximum Conducted (Average) Output Power

Maximum Conducted (Average) Output Power Result											
Power Level		1	RF Output Power (dBm)								
Directional Gain (dBi)		5.9									
Modulation Mode	N _{TX}	Freq. (MHz)	Chain-Port 1	Chain-Port 2	-	-	Sum Chain	Power Limit	EIRP Power	EIRP Limit	
11A5.8G-20M	2	5745	11.14	11.37	-	-	14.27	30.0	20.17	36.0	
11A5.8G-20M	2	5785	11.15	11.38	-	-	14.28	30.0	20.18	36.0	
11A5.8G-20M	2	5825	11.50	11.57	-	-	14.55	30.0	20.45	36.0	
Result			Complied								


Note 1: N_{TX} = Number of Transmit Chains

Maximum Conducted (Average) Output Power Result											
Power Level		1	RF Output Power (dBm)								
Directional Gain (dBi)		2.89									
Modulation Mode	N _{TX}	Freq. (MHz)	Chain-Port 1	Chain-Port 2	-	-	Sum Chain	Power Limit	EIRP Power	EIRP Limit	
11N5.8G-20M	2	5745	11.16	11.47	-	-	14.33	30.0	17.22	36.0	
11N5.8G-20M	2	5785	11.44	11.42	-	-	14.44	30.0	17.33	36.0	
11N5.8G-20M	2	5825	11.40	11.34	-	-	14.38	30.0	17.27	36.0	
Result			Complied								

Note 1: N_{TX} = Number of Transmit Chains

Maximum Conducted (Average) Output Power Result											
Power Level		1	RF Output Power (dBm)								
Directional Gain (dBi)		2.89									
Modulation Mode	N _{TX}	Freq. (MHz)	Chain-Port 1	Chain-Port 2	-	-	Sum Chain	Power Limit	EIRP Power	EIRP Limit	
11N5.8G-40M	2	5755	11.56	11.54	-	-	14.56	30.0	17.45	36.0	
11N5.8G-40M	2	5795	11.32	11.46	-	-	14.40	30.0	17.29	36.0	
Result			Complied								

Note 1: N_{TX} = Number of Transmit Chains





3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

Power Spectral Density Limit
<input checked="" type="checkbox"/> Power Spectral Density (PSD) $\leq 8 \text{ dBm/3kHz}$

3.4.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> Power spectral density procedures that the same method as used to determine the conducted output power shall be used to determine the power spectral density. In addition, the use of a peak PSD procedure will always result in a "worst-case" measured level for comparison to the limit. Therefore, whenever the DTS bandwidth exceeds 500 kHz, it is acceptable to utilize the peak PSD procedure to demonstrate compliance to the PSD limit, regardless of how the fundamental output power was measured. For the power spectral density shall be measured using below options:
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 5.3.1 Option 1 (peak PSD; BWCF=-15.2dB).
<input type="checkbox"/> Refer as FCC KDB 558074, clause 5.3.2 Option 2 (average PSD; BWCF=-15.2dB).
<input type="checkbox"/> Refer as ANSI C63.10, clause 6.11.2.3 for PSD for DTS - (RBW=3kHz; sweep=100s).
<input type="checkbox"/> Refer as ANSI C63.10, clause 6.11.2.4 for Alternative PSD for DTS - (RBW=3kHz; average=100)
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 2 for conducted measurement.
<input type="checkbox"/> The EUT supports single transmit chain and measurements performed on this transmit chain.
<input checked="" type="checkbox"/> The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input checked="" type="checkbox"/> The EUT supports multiple transmit chains using options given below:
<input checked="" type="checkbox"/> Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the N_{TX} output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace. The new data trace samples added 100 kHz segment and found the highest value of each 100 kHz segments. Add the bandwidth correction factor (BWCF) adjusting in power spectral density per 3kHz.
<input type="checkbox"/> Option 2: Measure and add $10 \log(N)$ dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with $10 \log(N)$. Or each transmit chains shall be add $10 \log(N)$ to compared with the limit.
<input type="checkbox"/> Refer as FCC KDB 558074, clause 2 for radiated measurement.



3.4.4 Test Setup



3.4.5 Test Result of Power Spectral Density

Power Spectral Density Result							
Power Level		1	Power Spectral Density (dBm/3kHz)				
Directional Gain (dBi)		5.9					
Modulation Mode	N _{TX}	Freq. (MHz)	Sum All Chains	-	-	-	PSD Limit
11A5.8G-20M	2	5745	-15.80	-	-	-	8
11A5.8G-20M	2	5785	-16.20	-	-	-	8
11A5.8G-20M	2	5825	-15.90	-	-	-	8
Result		Complied					

Note 1: N_{TX} = Number of Transmit Chains
Note 2: PPSD [dBm/MHz] = sum each transmit chains by bin-to-bin PPSD [dBm/MHz]

Power Spectral Density Result							
Power Level		1	Power Spectral Density (dBm/3kHz)				
Directional Gain (dBi)		2.89					
Modulation Mode	N _{TX}	Freq. (MHz)	Sum All Chains	-	-	-	PSD Limit
11N5.8G-20M	2	5745	-15.23	-	-	-	8
11N5.8G-20M	2	5785	-14.86	-	-	-	8
11N5.8G-20M	2	5825	-15.05	-	-	-	8
Result		Complied					

Note 1: N_{TX} = Number of Transmit Chains
Note 2: PPSD [dBm/MHz] = sum each transmit chains by bin-to-bin PPSD [dBm/MHz]




Power Spectral Density Result							
Power Level		1	Power Spectral Density (dBm/3kHz)				
Directional Gain (dBi)		2.89					
Modulation Mode	N _{TX}	Freq. (MHz)	Sum All Chains	-	-	-	PSD Limit
11N5.8G-40M	2	5755	-17.57	-	-	-	8
11N5.8G-40M	2	5795	-18.62	-	-	-	8
Result		Complied					

Note 1: N_{TX} = Number of Transmit Chains
Note 2: PPSD [dBm/MHz] = sum each transmit chains by bin-to-bin PPSD [dBm/MHz]




Worst Power Spectral Density Plots


11A5.8G-20M – F1 [Sum All Chains]



11N5.8G-20M – F2 [Sum All Chains]




11N5.8G-40M – F4 [Sum All Chains]



3.5 Transmitter Radiated Bandedge Emissions

3.5.1 Transmitter Radiated Bandedge Emissions Limit



3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.




3.5.3 Test Procedures

Test Method – General Information	
<input checked="" type="checkbox"/>	The average emission levels shall be measured in [duty cycle \geq 98 or duty factor].
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.9.2.2 bandedge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.
<input checked="" type="checkbox"/>	For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 5.4.1 for unwanted emissions into non-restricted bands.	
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 5.4.2 for unwanted emissions into restricted bands.	
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 5.4.2.2.1 Option 1 (Power Averaging).
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 5.4.2.2.2 Option 2 (Trace Averaging).
	<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced VBW) - Duty cycle \geq 98%.
	<input type="checkbox"/> Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions.
	<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 5.4.2.2.1.1 measurement procedure peak limit.
	<input type="checkbox"/> Refer as ANSI C63.10, clause 4.2.3.2.2 measurement procedure peak limit.
<input checked="" type="checkbox"/>	For the transmitter bandedge emissions shall be measured using following options below:
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 5.4.2.2.4 for narrower resolution bandwidth using the band power and summing the spectral levels (i.e., 100 kHz or 1 MHz).
	<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.9.2 for band-edge testing.
	<input type="checkbox"/> Refer as ANSI C63.10, clause 6.9.3 for marker-delta method for band-edge measurements.

**Test Method**

<input checked="" type="checkbox"/> Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements). Measurements in the bandedge are typically made at a closer distance 1m, because the instrumentation noise floor is typically close to the radiated emission limit.
<input type="checkbox"/> Refer as FCC KDB 558074, clause 2 for conducted measurement. <ul style="list-style-type: none"><input type="checkbox"/> For unwanted emissions into non-restricted bands (relative emission limits).<input type="checkbox"/> For conducted measurements on devices with multiple transmit chains: Refer as FCC KDB 662911, when testing out-of-band and spurious emissions against relative emission limits, tests may be performed on each output individually without summing or adding 10 log(N) if the measurements are made relative to the in-band emissions on the individual outputs.<input type="checkbox"/> For unwanted emissions into restricted bands. Test conducted spurious emissions and radiated by the cabinet with the antenna connector(s) terminated by a specified load (cabinet radiation).<ul style="list-style-type: none"><input type="checkbox"/> Refer as FCC KDB 558074, clause 5.4.2.2.1 unwanted emissions in restricted bands on frequencies \leq 1000 MHz<input type="checkbox"/> Refer as FCC KDB 558074, clause 5.4.2.2.2 unwanted emissions in restricted bands on frequencies $>$ 1000 MHz<input type="checkbox"/> For conducted measurements on devices with multiple transmit chains using options given below:<ul style="list-style-type: none"><input type="checkbox"/> Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, out-of-band and spurious emission measurement. The trace data for each transmit chain has to be individually recorded and each transmit chain trace data shall be added and compared with the limit.<input type="checkbox"/> Option 2: Measure and add 10 log(N) dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with 10 log(N). Or each transmit chains shall be add 10 log(N) to compared with the limit.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 2 for radiated measurement. <ul style="list-style-type: none"><input type="checkbox"/> Refer as ANSI C63.10, clause 6.4 for radiated emissions from below 30 MHz.<input type="checkbox"/> Refer as ANSI C63.10, clause 6.5 for radiated emissions from 30 MHz to 1000 MHz.<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.5 for radiated emissions from above 1 GHz.

3.5.4 Test Setup





3.5.5 Test Result of Transmitter Radiated Bandedge Emissions

Transmitter Radiated Bandedge Emissions Result									
Power Level	1	Gain (dBi)	5.9	Non-restricted Band Emissions					
Modulation	11A5.8G-20M								
Non-restricted Band (MHz)	N _{TX}	Test Ch. Freq. (MHz)	In-band PSD [i] (dBuV/100kHz)	NBE Freq. (MHz)	Out-band PSD [o] (dBuV/100kHz)	[i] – [o] (dB)	Limit (dB)	Level Type	Pol. note 1
5460-5725	2	5745	111.10	5724.97	79.04	31.06	20	PK	V
5850-7250	2	5825	110.60	5852.13	69.85	40.75	20	PK	V
Low Band				Up Band					

Note 1: Measurement worst emissions of receive antenna polarization: H (Horizontal) or V (Vertical)



Transmitter Radiated Bandedge Emissions Result									
Power Level	1	Gain (dBi)	2.89	Non-restricted Band Emissions					
Modulation	11N5.8G-20M								
Non-restricted Band (MHz)	N _{TX}	Test Ch. Freq. (MHz)	In-band PSD [i] (dBuV /100kHz)	NBE Freq. (MHz)	Out-band PSD [o] (dBuV /100kHz)	[i] – [o] (dB)	Limit (dB)	Level Type	Pol. note 1
5460-5725	2	5745	112.05	5724.69	84.49	27.56	20	PK	V
5850-7250	2	5825	109.09	5851.47	70.53	38.56	20	PK	V
Low Band					Up Band				

Note 1: Measurement worst emissions of receive antenna polarization: H (Horizontal) or V (Vertical)



Transmitter Radiated Bandedge Emissions Result									
Power Level	1	Gain (dBi)	2.89	Non-restricted Band Emissions					
Modulation	11N5.8G-40M								
Non-restricted Band (MHz)	N _{TX}	Test Ch. Freq. (MHz)	In-band PSD [i] (dBuV /100kHz)	NBE Freq. (MHz)	Out-band PSD [o] (dBuV /100kHz)	[i] – [o] (dB)	Limit (dB)	Level Type	Pol. note 1
5460-5725	2	5755	109.29	5720.60	86.84	22.45	20	PK	V
5850-7250	2	5795	107.31	5853.70	69.44	37.87	20	PK	V
Low Band					Up Band				

Note 1: Measurement worst emissions of receive antenna polarization: H (Horizontal) or V (Vertical)



3.6 Transmitter Radiated Unwanted Emissions

3.6.1 Transmitter Radiated Unwanted Emissions Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Average output power procedure	30

Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.

3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.




3.6.3 Test Procedures

Test Method – General Information	
<input checked="" type="checkbox"/>	Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).
<input checked="" type="checkbox"/>	Measurements in the frequency range 5 GHz - 10GHz are typically made at a closer distance 1m, because the instrumentation noise floor is typically close to the radiated emission limit.
<input checked="" type="checkbox"/>	Measurements in the frequency range 10 GHz - 18GHz are typically made at a closer distance 1m, because the instrumentation noise floor is typically close to the radiated emission limit.
<input checked="" type="checkbox"/>	Measurements in the frequency range above 18 GHz - 40GHz are typically made at a closer distance 0.5m, because the instrumentation noise floor is typically close to the radiated emission limit.
<input checked="" type="checkbox"/>	The average emission levels shall be measured in [duty cycle \geq 98 or duty factor].
<input checked="" type="checkbox"/>	For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 5.4.1 for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 5.4.2 for unwanted emissions into restricted bands.
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 5.4.2.2.1 Option 1 (Power Averaging).
	<input type="checkbox"/> Refer as FCC KDB 558074, clause 5.4.2.2.2 Option 2 (Trace Averaging).
	<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced VBW) – Duty \geq 98%.
	<input type="checkbox"/> Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions.
	<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 5.4.2.2.1.1 measurement procedure peak limit.
	<input type="checkbox"/> Refer as ANSI C63.10, clause 4.2.3.2.2 measurement procedure peak limit.



Test Method	
<input type="checkbox"/> Refer as FCC KDB 558074, clause 2 for conducted measurement.	
<input type="checkbox"/>	<input type="checkbox"/> For unwanted emissions into non-restricted bands (relative emission limits). <input type="checkbox"/> For conducted measurements on devices with multiple transmit chains: Refer as FCC KDB 662911, when testing out-of-band and spurious emissions against relative emission limits, tests may be performed on each output individually without summing or adding 10 log(N) if the measurements are made relative to the in-band emissions on the individual outputs.
<input type="checkbox"/>	<input type="checkbox"/> For unwanted emissions into restricted bands. Test conducted spurious emissions and radiated by the cabinet with the antenna connector(s) terminated by a specified load (cabinet radiation).
<input type="checkbox"/>	<input type="checkbox"/> Refer as FCC KDB 558074, clause 5.4.2.2.1 unwanted emissions in restricted bands on frequencies \leq 1000 MHz <input type="checkbox"/> Refer as FCC KDB 558074, clause 5.4.2.2.2 unwanted emissions in restricted bands on frequencies $>$ 1000 MHz <input type="checkbox"/> For conducted measurements on devices with multiple transmit chains using options given below: <input type="checkbox"/> Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, out-of-band and spurious emission measurement. The trace data for each transmit chain has to be individually recorded and each transmit chain trace data shall be added and compared with the limit. <input type="checkbox"/> Option 2: Measure and add 10 log(N) dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with 10 log(N). Or each transmit chains shall be add 10 log(N) to compared with the limit.
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> For radiated measurement.
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.4 for radiated emissions from below 30 MHz. <input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.5 for radiated emissions from 30 MHz to 1000 MHz. <input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.5 for radiated emissions from above 1 GHz.


3.6.4 Test Setup





3.6.5 Test Result of Transmitter Radiated Unwanted Emissions (Below 1GHz)

Transmitter Radiated Unwanted Emissions (Below 1GHz)			
Modulation Mode	11N2.4G-20M	Test Freq. (FX)	F2
Operating Mode	1	Polarization	V
Operating Function	Normal TX + Adapter Mode		



Freq	Level	Over	Limit	Read	Antenna	Cable Preamp			Ant	Table
		Limit	Line	Level	Factor	Loss	Factor	Remark		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1. @ 43.580	36.85	-3.15	40.00	51.37	12.27	1.09	27.88	Peak	---	---
2 137.670	31.55	-11.95	43.50	45.07	12.18	1.98	27.68	Peak	---	---
3 249.220	37.28	-8.72	46.00	48.83	12.97	2.77	27.29	Peak	---	---
4 374.350	34.63	-11.37	46.00	44.17	14.86	3.29	27.69	Peak	---	---
5 498.510	36.69	-9.31	46.00	43.97	17.26	3.82	28.36	Peak	---	---
6 625.580	36.40	-9.60	46.00	40.65	19.84	4.32	28.41	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)



Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation Mode	11N2.4G-20M	Test Freq. (FX)	F2
Operating Mode	1	Polarization	H
Operating Function	Normal TX + Adapter Mode		



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant Pos	Table Pos
		Limit	Line	Antenna	Cable	Loss	Factor		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 40.670	34.18	-5.82	40.00	48.02	13.01	1.05	27.90	Peak	---
2 249.220	36.87	-9.13	46.00	48.42	12.97	2.77	27.29	Peak	---
3 268.620	24.81	-21.19	46.00	35.94	13.26	2.85	27.24	Peak	---
4 374.350	37.83	-8.17	46.00	47.37	14.86	3.29	27.69	Peak	---
5 498.510	38.96	-7.04	46.00	46.24	17.26	3.82	28.36	Peak	---
6 831.220	39.59	-6.41	46.00	42.24	20.19	4.99	27.83	Peak	---


Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)



3.6.6 Test Result of Transmitter Radiated Unwanted Emissions (Above 1GHz)





Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11A5.8G-20M	Test Freq. (FX)	F1							
Operating Function	Transmit	Polarization	H							
Level (dBuV/m)			Date: 2012-07-17							
Freq	Level	Over Limit	Limit	Read Line	Antenna Level	Cable Factor	Preamp	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 8837.000	48.78			41.48	36.50	6.09	35.29	Peak	---	---
2 11490.000	55.09	-8.45	63.54	44.29	38.89	6.63	34.72	PK	---	---
3 17235.000	60.03			43.85	41.61	8.55	33.98	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For un-restricted bands, unwanted emissions (item 1 and 3) shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11A5.8G-20M	Test Freq. (FX)	F2						
Operating Function	Transmit	Polarization	V						
Level (dBuV/m)			Date: 2012-07-17						
Freq	Level	Over Limit	Line	Read	Antenna	Cable	Preamp	Int	Table
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	Pos	Pos
								cm	deg
1 8914.000	48.38			41.00	36.55	6.13	35.30 Peak	---	---
2 11570.000	61.68	-21.86	83.54	50.87	38.94	6.63	34.76 Peak	---	---
3 11570.000	50.28	-13.26	63.54	39.47	38.94	6.63	34.76 Average	---	---
4 17355.000	65.05			48.97	41.56	8.50	33.98 Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)


Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For un-restricted bands, unwanted emissions (item 1 and 4) shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11A5.8G-20M	Test Freq. (FX)	F2
Operating Function	Transmit	Polarization	H



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table
		Limit	Line	Level	Factor	Cable	Preamp			
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	8683.000	47.44			40.28	36.41	6.02	35.27 Peak	---	---
2	811570.000	53.48	-10.06	63.54	42.67	38.94	6.63	34.76 PK	---	---
3	17355.000	59.19			43.11	41.56	8.50	33.98 Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For un-restricted bands, unwanted emissions (item 3 and 4) shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11A5.8G-20M	Test Freq. (FX)	F3						
Operating Function	Transmit	Polarization	V						
Level (dBuV/m)			Date: 2012-07-17						
Freq	Level	Over Limit	Line	Read	Antenna	Cable	Preamp	Ant	Table
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	Pos	Pos
								cm	deg
1	8914.000	47.79		40.41	36.55	6.13	35.30	Peak	---
2	11650.000	61.77	-21.77	83.54	50.96	38.98	6.64	34.81	Peak
3	11650.000	49.91	-13.63	63.54	39.10	38.98	6.64	34.81	Average
4	17475.000	61.54		45.57	41.51	8.44	33.98	Peak	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For un-restricted bands, unwanted emissions (item 1 and 4) shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11A5.8G-20M	Test Freq. (FX)	F3						
Operating Function	Transmit	Polarization	H						
Level (dBuV/m)			Date: 2012-07-17						
Frequency (MHz)									
Freq	Level	Over Limit	Limit	Read Line	Antenna	Cable	Preamp	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 8980.000	48.04			40.62	36.58	6.16	35.32 Peak	---	---
2 11650.000	52.96	-10.58	63.54	42.15	38.98	6.64	34.81 PK	---	---
3 17475.000	59.70			43.73	41.51	8.44	33.98 Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For un-restricted bands, unwanted emissions (item 1 and 3) shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11N5.8G-20M	Test Freq. (FX)	F1						
Operating Function	Transmit	Polarization	V						
Level (dBuV/m)			Date: 2012-06-28						
Freq	Level	Over Limit	Line	Read	Antenna	Cable	Preamp	Ant	Table
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	Pos	Pos
1	8573.000	48.83		41.77	36.34	5.97	35.25	Peak	---
2	11490.000	64.43	-19.11	83.54	53.63	38.89	6.63	34.72	Peak
3	11490.000	53.35	-10.19	63.54	42.55	38.89	6.63	34.72	Average
4	17235.000	64.74		48.56	41.61	8.55	33.98	Peak	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For un-restricted bands, unwanted emissions (item 1 and 4) shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11N5.8G-20M	Test Freq. (FX)	F1						
Operating Function	Transmit	Polarization	H						
Level (dBuV/m)			Date: 2012-06-28						
									
Freq	Level	Over Limit	Line	Read	Antenna	Cable	Preamp	Ant	Table
MHz	dBuV/m	dB	dBuV/m	dBuV	Level Factor	Loss	Factor	Pos	Pos
								cm	deg
1	8606.000	48.14		41.05	36.36	5.99	35.26 Peak	---	---
2	11490.000	57.47	-6.07	63.54	46.67	38.89	6.63	34.72 PK	---
3	17235.000	59.64			43.46	41.61	8.55	33.98 Peak	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For un-restricted bands, unwanted emissions (item 1 and 3) shall be attenuated by at least 20 dB relative to the maximum measured in-band level.




Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11N5.8G-20M	Test Freq. (FX)	F2
Operating Function	Transmit	Polarization	V
<p>Graph showing Transmitter Radiated Unwanted Emissions (Above 1GHz) with Level (dBuV/m) on the Y-axis (0 to 130) and Frequency (MHz) on the X-axis (1000 to 40000). The graph displays four measurement points (1, 2, 3, 4) and two limit lines: FCC-B-1M (red) and FCC-B-1M-AV (blue). The measurement points are located at approximately 8705.000 MHz (Level ~48.41 dB), 11570.000 MHz (Level ~63.51 dB), 11570.000 MHz (Level ~52.91 dB), and 17355.000 MHz (Level ~64.62 dB). The FCC-B-1M limit is at ~65 dB, and the FCC-B-1M-AV limit is at ~20 dB below the FCC-B-1M limit.</p>			

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For un-restricted bands, unwanted emissions (item 1 and 4) shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)


Modulation Mode	11N5.8G-20M		Test Freq. (FX)	F2					
Operating Function	Transmit		Polarization	H					
Level (dBuV/m)					Date: 2012-06-28				
									
Freq	Level	Over Limit	Line	Read	Antenna	Cable	Preamp	Ant	Table
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	Pos	Pos
1 8826.000	49.37			42.08	36.49	6.09	35.29 Peak	---	---
2 11570.000	55.91	-7.63	63.54	45.10	38.94	6.63	34.76 PK	---	---
3 17355.000	60.21			44.13	41.56	8.50	33.98 Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
Note 4: For un-restricted bands, unwanted emissions (item 1 and 3) shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11N5.8G-20M	Test Freq. (FX)	F3
Operating Function	Transmit	Polarization	V



Freq	Level	Over	Limit	Read		Antenna			Cable		Preamp		Ant	Table
		Limit	Line	Level	Factor	Loss	Factor	Remark	Pos	Pos				
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg				
1 8705.000	48.41			41.22	36.42	6.04	35.27	Peak	---	---				
2 11650.000	59.67	-3.87	63.54	48.86	38.98	6.64	34.81	PK	---	---				
3 17475.000	61.70			45.73	41.51	8.44	33.98	Peak	---	---				

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For un-restricted bands, unwanted emissions (item 1 and 3) shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11N5.8G-20M	Test Freq. (FX)	F3						
Operating Function	Transmit	Polarization	H						
Level (dBuV/m)			Date: 2012-06-28						
Freq	Level	Over Limit	Line	Read	Antenna	Cable	Preamp	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 8661.000	48.55			41.40	36.40	6.01	35.26 Peak	---	---
2 11650.000	53.28	-10.26	63.54	42.47	38.98	6.64	34.81 PK	---	---
3 17475.000	59.75			43.78	41.51	8.44	33.98 Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For un-restricted bands, unwanted emissions (item 1 and 3) shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11N5.8G-40M	Test Freq. (FX)	F4
Operating Function	Transmit	Polarization	V
			Date: 2012-06-28

Freq	Level	Over Limit	Limit	Read		Antenna	Cable	Preamp	Ant	Table
				Line	Factor					
MHz	dBuV/m		dB	dBuV/m		dBuV	dB/m	dB	dB	cm
1 8694.000	48.63			41.46		36.42	6.02	35.27	Peak	---
2 11510.000	61.40	-22.14	83.54	50.59		38.90	6.63	34.72	Peak	---
3 11510.000	50.29	-13.25	63.54	39.48		38.90	6.63	34.72	Average	---
4 17265.000	63.12			46.97		41.59	8.54	33.98	Peak	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For un-restricted bands, unwanted emissions (item 1 and 4) shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11N5.8G-40M	Test Freq. (FX)	F4						
Operating Function	Transmit	Polarization	H						
Level (dBuV/m)			Date: 2012-06-28						
									
Freq	Level	Over Limit	Line	Read	Antenna	Cable	Preamp	Ant	Table
MHz	dBuV/m	dB	dBuV/m	Line	Level Factor	Loss Factor	Remark	Pos	Pos
					dBuV	dB/m		cm	deg
1	8837.000	48.52			41.22	36.50	6.09 35.29 Peak	---	---
2	11510.000	55.17	-8.37	63.54	44.36	38.90	6.63 34.72 PK	---	---
3	17265.000	60.19			44.04	41.59	8.54 33.98 Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For un-restricted bands, unwanted emissions (item 1 and 3) shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)





Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11N5.8G-40M	Test Freq. (FX)	F5						
Operating Function	Transmit	Polarization	H						
Level (dB _{UV} /m)			Date: 2012-06-28						
Frequency (MHz)									
Reported By:									
Freq	Level	Over Limit	Limit	Read Line	Antenna	Cable	Preamp	Ant Pos	Table Pos
MHz	dB _{UV} /m	dB	dB _{UV} /m	dB _{UV}	dB/m	dB	dB	cm	deg
1	8573.000	48.32	-----	41.26	36.34	5.97	35.25 Peak	---	---
2	11590.000	52.08	-11.46	63.54	41.26	38.95	6.63 34.76 PK	---	---
3	17385.000	58.69			42.64	41.55	8.48 33.98 Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For un-restricted bands, unwanted emissions (item 1 and 3) shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9 kHz ~ 2.75 GHz	Mar. 23, 2012	Conduction (CO04-HY)
LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	8127-477	9kHz – 30MHz	Feb. 08, 2012	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9 kHz ~ 30 MHz	Apr. 20, 2012	Conduction (CO04-HY)
RF Cable-CON	HUBER+SUHNER	RG213/U	CB049	9 kHz ~ 30 MHz	Apr. 25, 2012	Conduction (CO04-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP 40	100305	9 KHz ~ 40 GHz	Feb. 21, 2012	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-SP-SD	MAA1112-007	-20~100°C	Dec. 07, 2011	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100302	10MHz ~ 40GHz	Nov. 22, 2011	Conducted (TH01-HY)
Power Sensor	Anritsu	MA2411B	1027452	300MHz ~ 40GHz	Jan. 12, 2012	Conducted (TH01-HY)
Power Meter	Anritsu	ML2495A	1124009	300MHz ~ 40GHz	Jan. 12, 2012	Conducted (TH01-HY)
RF Cable-1m	Jye Bao	RG142	CB034-1m	20 MHz ~ 7 GHz	Dec. 03, 2011	Conducted (TH01-HY)
RF Cable-2m	Jye Bao	RG142	CB035-2m	20 MHz ~ 1 GHz	Dec. 03, 2011	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Jun. 09, 2011*	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is two year.

**FCC RADIO TEST REPORT**

Report No. : FR262610-02AI

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP40	100004	9kHz ~ 40GHz	Feb. 01, 2012	Radiation (03CH02-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	30MHz ~ 1GHz 3m	May 10, 2012	Radiation (03CH02-HY)
Amplifier	Agilent	8447D	2944A11146	100kHz ~ 1.3GHz	Jul. 25, 2011	Radiation (03CH02-HY)
Amplifier	Agilent	8449B	3008A02120	1GHz ~ 26.5GHz	Apr. 23 2012	Radiation (03CH02-HY)
Horn Antenna	ETS-LINDGREN	3117	00091920	1GHz ~ 18GHz	Nov. 15, 2011	Radiation (03CH02-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30MHz ~ 1GHz	Nov. 11, 2011	Radiation (03CH02-HY)
RF Cable-high	SUHNER	SUCOFLEX106	03CH02-HY	1GHz ~ 40GHz	Mar. 06, 2012	Radiation (03CH02-HY)
Bilog Antenna	SCHAFFNER	CBL61128	2723	30MHz ~ 2GHz	Oct. 22, 2011	Radiation (03CH02-HY)
Turn Table	HD	DS 420	420/649/00	0~ 360 degree	N/A	Radiation (03CH02-HY)
Antenna Mast	HD	MA 240	240/559/00	1 ~ 4 m	N/A	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Sep. 09, 2010*	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is two year.



5 Certification of TAF Accreditation



Certificate No. : L1190-120405

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sportun International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria : ISO/IEC 17025:2005
Accreditation Number : 1190
Originally Accredited : December 15, 2003
Effective Period : January 10, 2010 to January 09, 2013
Accredited Scope : Testing Field, see described in the Appendix
Specific Accreditation Program : Accreditation Program for Designated Testing Laboratory
for Commodities Inspection
Accreditation Program for Telecommunication Equipment
Testing Laboratory
Accreditation Program for BSMI Mutual Recognition
Arrangement with Foreign Authorities

Jay-San Chen
President, Taiwan Accreditation Foundation
Date: April 05, 2012

P1, total 24 pages