



Co-location Report



1 TEST RESULT

1.1 Radiated Emissions Measurement

1.1.1 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

1.1.2 Measuring Instruments and Setting

Please refer to section 2 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP




1.1.3 Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

1.1.4 Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);
Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

1.1.5 Test Deviation

There is no deviation with the original standard.


1.1.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.




1.1.7 Results of Radiated Emissions (30MHz~1GHz)

Final Test Date	Mar.18, 2013	Test Site No.	03CH05-HY
Temperature	25°C	Humidity	65%
Test Engineer	Daniel Hsu	Configuration	2.4GHz 11g + 5GHz 11a

Horizontal

Freq MHz	Level dBuV/m	Over Limit		Read Line	Antenna Level Factor	Cable Loss dB	Preamp Factor	A/Pos cm	T/Pos deg	Remark
		Limit dB	Line dBuV/m							
1	148.34	37.92	-5.58	43.50	56.73	11.17	1.27	31.25	---	---
2	249.22	36.03	-9.97	46.00	52.81	12.51	1.61	30.90	---	Peak
3	334.58	32.62	-13.38	46.00	47.84	13.94	1.92	31.08	---	Peak
4	499.48	32.49	-13.51	46.00	42.54	18.09	2.44	30.58	---	Peak
5	668.26	33.50	-12.50	46.00	40.85	20.28	2.52	30.15	---	Peak
6	811.82	39.50	-6.50	46.00	44.15	22.27	2.86	29.78	---	Peak

**Vertical**

Freq MHz	Level dBuV/m	Over	Limit	Read	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Limit	Line	Level	Factor	dB/m	dB	dB	cm	
1	148.34	38.01	-5.49	43.50	56.82	11.17	1.27	31.25	---	--- Peak
2	249.22	35.83	-10.17	46.00	52.61	12.51	1.61	30.90	---	--- Peak
3	334.58	32.68	-13.32	46.00	47.90	13.94	1.92	31.08	---	--- Peak
4	482.99	34.89	-11.11	46.00	45.50	17.76	2.31	30.68	---	--- Peak
5	665.35	32.88	-13.12	46.00	40.22	20.25	2.55	30.14	---	--- Peak
6	805.03	41.68	-4.32	46.00	46.48	22.15	2.85	29.80	---	--- Peak

Note:


The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



Final Test Date	Mar.15, 2013	Test Site No.	03CH05-HY
Temperature	25°C	Humidity	65%
Test Engineer	Daniel Hsu	Configuration	2.4GHz 11g + 5GHz 11n HT20

Horizontal

Freq MHz	Level dBuV/m	Over Limit	Read Line	Antenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark
		Limit dB							
1	148.34	37.34	-6.16	43.50	56.15	11.17	1.27	31.25	---
2	239.52	36.28	-9.72	46.00	54.22	11.34	1.67	30.95	---
3	334.58	33.10	-12.90	46.00	48.32	13.94	1.92	31.08	---
4	499.48	32.41	-13.59	46.00	42.46	18.09	2.44	30.58	---
5	667.29	32.19	-13.81	46.00	39.54	20.27	2.53	30.15	---
6	805.03	42.18	-3.82	46.00	46.98	22.15	2.85	29.80	---

**Vertical**

Freq MHz	Level dBuV/m	Over Limit		Read Line Level dBuV	Antenna Factor dB/m	Cable Loss dB	Preamp Factor dB	A/Pos cm	T/Pos deg	Remark
		Limit dB	Line dBuV/m							
1	111.48	36.28	-7.22	43.50	55.27	11.38	1.15	31.52	---	--- Peak
2	148.34	33.12	-10.38	43.50	51.93	11.17	1.27	31.25	---	--- Peak
3	482.99	42.16	-3.84	46.00	52.77	17.76	2.31	30.68	---	--- Peak
4	531.49	32.45	-13.55	46.00	42.60	18.44	2.30	30.89	---	--- Peak
5	818.61	36.90	-9.10	46.00	41.27	22.54	2.85	29.76	---	--- Peak
6	918.52	29.78	-16.22	46.00	32.95	23.86	3.01	30.04	---	--- Peak

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

1.1.8 Results for Radiated Emissions (1GHz~10th Harmonic)


Final Test Date	Mar.15, 2013	Test Site No.	03CH05-HY
Temperature	25°C	Humidity	65%
Test Engineer	Daniel Hsu	Configuration	2.4GHz 11g + 5GHz 11a

Horizontal



Freq MHz	Level dBuV/m	Over Limit		Read Line Level Factor	Antenna Level Factor	Cable Loss dB	Preamp Factor	A/Pos cm	T/Pos deg	Remark
		Limit dB	Line dBuV/m							
1	3856.00	44.53	-9.47	54.00	40.33	33.20	5.89	34.89	---	Average
2	3856.00	50.25	-23.75	74.00	46.05	33.20	5.89	34.89	---	Peak
3	4874.00	49.56	-4.44	54.00	43.73	34.27	6.53	34.97	---	Average
4	4874.00	60.95	-13.05	74.00	55.12	34.27	6.53	34.97	---	Peak
5	7311.00	46.11	-7.89	54.00	36.69	36.04	8.40	35.02	---	Average
6	7311.00	60.23	-13.77	74.00	50.81	36.04	8.40	35.02	---	Peak
7	7500.00	38.02	-15.98	54.00	28.36	36.00	8.76	35.10	---	Average
8	7500.00	50.81	-23.19	74.00	41.15	36.00	8.76	35.10	---	Peak
9	7713.00	51.24	-2.76	54.00	41.46	36.04	8.80	35.06	---	Average
10	7713.00	56.35	-17.65	74.00	46.57	36.04	8.80	35.06	---	Peak
11	11570.00	51.89	-2.11	54.00	37.84	38.56	10.39	34.90	---	Average
12	11570.00	64.45	-9.55	74.00	50.40	38.56	10.39	34.90	---	Peak

Note: The items 2, 3 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

**Vertical**

	Freq	Level	Over Limit	Limit	Read	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	3856.00	48.31	-5.69	54.00	44.11	33.20	5.89	34.89	---	---	Average
2	3856.00	53.42	-20.58	74.00	49.22	33.20	5.89	34.89	---	---	Peak
3	4874.00	41.96	-12.04	54.00	36.13	34.27	6.53	34.97	---	---	Average
4	4874.00	54.48	-19.52	74.00	48.65	34.27	6.53	34.97	---	---	Peak
5	7311.00	44.36	-9.64	54.00	34.94	36.04	8.40	35.02	---	---	Average
6	7311.00	57.41	-16.59	74.00	47.99	36.04	8.40	35.02	---	---	Peak
7	7500.00	37.68	-16.32	54.00	28.02	36.00	8.76	35.10	---	---	Average
8	7500.00	50.92	-23.08	74.00	41.26	36.00	8.76	35.10	---	---	Peak
9	7713.00	49.81	-4.19	54.00	40.03	36.04	8.80	35.06	---	---	Average
10	7713.00	55.23	-18.77	74.00	45.45	36.04	8.80	35.06	---	---	Peak
11	11570.00	49.01	-4.99	54.00	34.96	38.56	10.39	34.90	---	---	Average
12	11570.00	62.84	-11.16	74.00	48.79	38.56	10.39	34.90	---	---	Peak

Note: The items 2, 3 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.


The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



Final Test Date	Mar.15, 2013	Test Site No.	03CH05-HY
Temperature	25°C	Humidity	65%
Test Engineer	Daniel Hsu	Configuration	2.4G 11g + 5GHz 11n HT20

Horizontal

Freq MHz	Level dBuV/m	Over Limit		Read Line dBuV	Antenna Factor	Cable Loss dB	Preamp Factor	A/Pos cm	T/Pos deg	Remark
		Limit dB	Line dBuV/m							
1 3466.00	45.23	-23.07	68.30	42.47	32.71	5.68	35.63	---	---	Peak
2 4874.00	48.36	-5.64	54.00	42.53	34.27	6.53	34.97	---	---	Average
3 4874.00	60.86	-13.14	74.00	55.03	34.27	6.53	34.97	---	---	Peak
4 6933.00	52.84	-15.46	68.30	43.88	36.09	7.80	34.93	---	---	Peak
5 7311.00	45.93	-8.07	54.00	36.51	36.04	8.40	35.02	---	---	Average
6 7311.00	60.11	-13.89	74.00	50.69	36.04	8.40	35.02	---	---	Peak
7 7500.00	37.96	-16.04	54.00	28.30	36.00	8.76	35.10	---	---	Average
8 7500.00	50.62	-23.38	74.00	40.96	36.00	8.76	35.10	---	---	Peak
9 10400.00	55.72	-12.58	68.30	43.62	37.74	9.76	35.40	---	---	Peak

**Vertical**

Freq MHz	Level dBuV/m	Over	Limit	Read	Antenna	Cable	Preamp	A/Pos	T/Pos	Remark
		Limit	Line	Level	Factor	dB	dB	cm	deg	
1 3466.00	42.45	-25.85	68.30	39.69	32.71	5.68	35.63	---	---	Peak
2 4874.00	41.96	-12.04	54.00	36.13	34.27	6.53	34.97	---	---	Average
3 4874.00	54.48	-19.52	74.00	48.65	34.27	6.53	34.97	---	---	Peak
4 6933.00	52.63	-15.67	68.30	43.67	36.09	7.80	34.93	---	---	Peak
5 7311.00	44.32	-9.68	54.00	34.90	36.04	8.40	35.02	---	---	Average
6 7311.00	57.26	-16.74	74.00	47.84	36.04	8.40	35.02	---	---	Peak
7 7500.00	37.68	-16.32	54.00	28.02	36.00	8.76	35.10	---	---	Average
8 7500.00	50.91	-23.09	74.00	41.25	36.00	8.76	35.10	---	---	Peak
9 10400.00	54.49	-13.81	68.30	42.39	37.74	9.76	35.40	---	---	Peak

Note: The items 2, 3 and 4 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions.

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



2 LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP	100055	9Kz – 40GHz	Jun. 06, 2012	Radiation (03CH05-HY)
Receiver	R&S	ESIB26	100337	20Hz – 26.5GHz	Jun.21, 2012	Radiation (03CH05-HY)
3m Semi Anechoic Chamber	TDK	SAC-3M	03CH05-HY	30 MHz - 1 GHz 3m	N/A	Radiation (03CH05-HY)
Amplifier	COM-POWER	PA-103	161050	1 MHz ~ 1 GHz	Mar. 20, 2012	Radiation (03CH05-HY)
Amplifier	Agilent	8449B	3008A02665	1GHz – 26.5 GHz	Aug. 28, 2012	Radiation (03CH05-HY)
Horn Antenna	ETS-LINDGREN	3117	66584	1GHz~18GHz	Aug. 09, 2012	Radiation (03CH05-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15GHz ~ 40GHz	Jan. 08, 2013	Radiation (03CH05-HY)
RF Cable-R03m	Jye Bao	RG142	03CH05-HY	30 MHz - 1 GHz	Oct. 14, 2012	Radiation (03CH05-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX104	03CH05-HY	1GHz~40GHz	Oct. 14, 2012	Radiation (03CH05-HY)
Bilog Antenna	SCHAFFNER	CBL6111C	2725	30 MHz - 1 GHz	Oct. 06, 2012	Radiation (03CH05-HY)
Turn Table	HD	HD100	420/611	0 - 360 degree	N/A	Radiation (03CH05-HY)
Antenna Mast	HD	HD100	240/666	1 m - 4 m	N/A	Radiation (03CH05-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	R&S	HFH2-Z2	860004/0001	9 kHz - 30 MHz	Jul. 03, 2012*	Radiation (03CH05-HY)
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5GHz ~ 40GHz	Apr. 19, 2011	Radiation (03CH05-HY)

Note: Calibration Interval of instruments listed above is two year.



3 TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei 221, Taiwan, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C TEL : 886-3-327-3456 FAX : 886-3-327-0973
LINKOU	ADD : No. 30-2, Dingfu Vil., Linkou Dist., New Taipei City 244, Taiwan, R.O.C. TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei 114, Taiwan, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei 235, Taiwan, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085