

FCC RADIO TEST REPORT

Applicant's company	BUFFALO INC.
Applicant Address	Akamon-dori Bldg 30-20, Ohsu 3-chome Naka-ku, Nagoya 460-8315 Japan
FCC ID	FDI000000014
Manufacturer's company	BUFFALO INC.
Manufacturer Address	Akamon-dori Bldg 30-20, Ohsu 3-chome Naka-ku, Nagoya 460-8315 Japan

Product Name	AirStation
Brand Name	BUFFALO INC.
Model No.	WZR-900DHP
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Received Date	Feb. 07, 2013
Final Test Date	Apr. 11, 2013
Submission Type	Original Equipment



Statement

Test result included is only for the IEEE 802.11n, IEEE 802.11b/g part and IEEE 802.11a (5725 ~ 5850MHz) of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009**,

47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v02 and KDB 662911 D01 v01r02.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.

Table of Contents

1. CERTIFICATE OF COMPLIANCE.....	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION.....	3
3.1. Product Details	3
3.2. Accessories	5
3.3. Table for Filed Antenna	6
3.4. Table for Carrier Frequencies	7
3.5. Table for Test Modes	8
3.6. Table for Testing Locations.....	10
3.7. Table for Supporting Units	10
3.8. Table for Parameters of Test Software Setting	11
3.9. EUT Operation during Test.....	11
3.10. Duty Cycle.....	12
3.11. Test Configurations.....	16
4. TEST RESULT.....	19
4.1. AC Power Line Conducted Emissions Measurement	19
4.2. Maximum Conducted Output Power Measurement.....	23
4.3. Power Spectral Density Measurement.....	26
4.4. 6dB Spectrum Bandwidth Measurement	34
4.5. Radiated Emissions Measurement.....	41
4.6. Emissions Measurement.....	67
4.7. Antenna Requirements	94
5. LIST OF MEASURING EQUIPMENTS	95
6. TEST LOCATION.....	97
APPENDIX A. PHOTOGRAPHS OF EUT.....	A1 ~ A22
APPENDIX B. TEST PHOTOS	B1 ~ B5
APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE	C1 ~ C3
APPENDIX D. CO-LOCATION REPORT	D1 ~ D3


History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR311723-01AA	Rev. 01	Initial issue of report	May 02, 2013

1. CERTIFICATE OF COMPLIANCE

Product Name : AirStation
Brand Name : BUFFALO INC.
Model No. : WZR-900DHP
Applicant : BUFFALO INC.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Feb. 07, 2013 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	14.50 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	0.80 dB
4.3	15.247(e)	Power Spectral Density	Complies	1.49 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.02 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.04 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n

Items	Description
Product Type	WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	For 2.4GHz Band: 11 for 20MHz bandwidth ; 7 for 40MHz bandwidth For 5GHz Band: 5 for 20MHz bandwidth ; 2 for 40MHz bandwidth
Channel Band Width (99%)	For 2.4GHz Band: MCS0 (20MHz): 17.20 MHz ; MCS0 (40MHz): 36.00 MHz For 5GHz Band: MCS0 (20MHz): 17.60 MHz ; MCS0 (40MHz): 36.32 MHz
Maximum Conducted Output Power	For 2.4GHz Band: MCS0 (20MHz): 27.01 dBm ; MCS0 (40MHz): 23.11 dBm For 5GHz Band: MCS0 (20MHz): 28.09 dBm ; MCS0 (40MHz): 27.65 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

802.11a/b/g

Items	Description
Product Type	WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From Power Adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11a/g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	11b/g: 11 ; 11a: 5
Channel Band Width (99%)	11b: 10.24 MHz ; 11g: 16.40 MHz ; 11a: 16.56 MHz
Maximum Conducted Output Power	11b: 29.20 dBm ; 11g: 26.82 dBm ; 11a: 25.84 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna & Band width

Antenna	Three (TX)	
Band width Mode	20 MHz	40 MHz
802.11a	V	X
802.11b	V	X
802.11g	V	X
802.11n	V	V

802.11n spec

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	3	MCS 0-23
802.11n (HT40)	3	MCS 0-23
Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40. Note 2: Modulation modes consist of below configuration: HT20/HT40: IEEE 802.11n		

3.2. Accessories

Power	Brand Holder	Model	Rating
Adapter 1	Asian Power Devices Inc.	WA-36A12	INPUT: 100~240Vac, 50-60Hz, 0.9A Max OUTPUT: 12Vdc, 3A
Adapter 2	Asian Power Devices Inc.	WA-36A12U	INPUT: 100~240Vac, 50-60Hz, 0.9A Max OUTPUT: 12Vdc, 3A
Others			
Cradle*1, Plug of Adapter 1*1			

Note: The difference between Adapter 1 and Adapter 2 is only different plug, so only Adapter 1 (Model No. WA-36A12) was selected to test and recorded in the report as a result.

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	
					2.4GHz	5GHz
1	Airgain	N2420SS	PCB Antenna	I-PEX	2.19	-
2	Airgain	N2420SS	PCB Antenna	I-PEX	2.19	-
3	Airgain	N2420SS	PCB Antenna	I-PEX	1.97	-
4	Airgain	N5x20B	PCB Antenna	I-PEX	-	2.48
5	Airgain	N5x20B	PCB Antenna	I-PEX	-	2.60
6	Airgain	N5x20B	PCB Antenna	I-PEX	-	2.46

Note: The EUT has six antennas

<For 2.4GHz Band>


For IEEE 802.11b/g/n mode (3TX/3RX)

Ant. 1, Ant. 2 and Ant. 3 could transmit/receive simultaneously.

<For 5GHz Band>

For IEEE 802.11a/n mode (3TX/3RX):

Ant. 4, Ant. 5 and Ant. 6 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

For 2.4GHz Band:

For IEEE 802.11b/g, use Channel 1~Channel 11.

There are two bandwidth systems for IEEE 802.11n.

For both 20MHz bandwidth systems, use Channel 1~Channel 11.

For both 40MHz bandwidth systems, use Channel 3~Channel 9.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

For 5GHz Band:

For IEEE 802.11a, use Channel 149, 153, 157, 161, 165.

There are two bandwidth systems for IEEE 802.11n.

For 20MHz bandwidth systems, use Channel 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 151, 159.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz Band 4	149	5745 MHz	157	5785 MHz
	151	5755 MHz	159	5795 MHz
	153	5765 MHz	161	5805 MHz
	165	5825 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

For 2.4GHz Band

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	-
Maximum Conducted Output Power	11n 20MHz	MCS0	1/6/11	1+2+3
	11n 40MHz	MCS0	3/6/9	1+2+3
	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
Power Spectral Density	11n 20MHz	MCS0	1/6/11	1, 2, 3
	11n 40MHz	MCS0	3/6/9	1, 2, 3
	11b/CCK	1 Mbps	1/6/11	1, 2, 3
	11g/BPSK	6 Mbps	1/6/11	1, 2, 3
6dB Spectrum Bandwidth	11n 20MHz	MCS0	1/6/11	1+2+3
	11n 40MHz	MCS0	3/6/9	1+2+3
	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
Radiated Emissions Below 1GHz	Normal Link	Auto	-	-
Radiated Emissions Above 1GHz	11n 20MHz	MCS0	1/6/11	1+2+3
	11n 40MHz	MCS0	3/6/9	1+2+3
	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3
Band Edge Emissions	11n 20MHz	MCS0	1/6/11	1+2+3
	11n 40MHz	MCS0	3/6/9	1+2+3
	11b/CCK	1 Mbps	1/6/11	1+2+3
	11g/BPSK	6 Mbps	1/6/11	1+2+3

For 5GHz Band

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	-
Maximum Conducted Output Power	11n 20MHz	MCS0	149/157/165	4+5+6
	11n 40MHz	MCS0	151/159	4+5+6
	11a/BPSK	6 Mbps	149/157/165	4+5+6
Power Spectral Density	11n 20MHz	MCS0	149/157/165	4+5+6
	11n 40MHz	MCS0	151/159	4+5+6
	11a/BPSK	6 Mbps	149/157/165	4+5+6
6dB Spectrum Bandwidth	11n 20MHz	MCS0	149/157/165	4+5+6
	11n 40MHz	MCS0	151/159	4+5+6
	11a/BPSK	6 Mbps	149/157/165	4+5+6
Radiated Emissions Below 1GHz	Normal Link	Auto	-	-
Radiated Emissions Above 1GHz	11n 20MHz	MCS0	149/157/165	4+5+6
	11n 40MHz	MCS0	151/159	4+5+6
	11a/BPSK	6 Mbps	149/157/165	4+5+6
Band Edge Emissions	11n 20MHz	MCS0	149/157/165	4+5+6
	11n 40MHz	MCS0	151/159	4+5+6
	11a/BPSK	6 Mbps	149/157/165	4+5+6

The following test modes were performed for all tests:

<For MPE and Co-location Test>:

The EUT could be applied with 2.4GHz WLAN function and 5GHz WLAN function; therefore Maximum Permissible Exposure (Please refer to Appendix C) and Co-location (please refer to Appendix D) tests are added for simultaneously transmit between 2.4GHz WLAN function and 5GHz WLAN function.

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

Test Site No. 03CH01-CB and CO01-CB

Support Unit	Brand	Model	FCC ID
Hard Disk	WD	WDBACY5000AWT	DoC
Notebook	DELL	E6220	QDS-BRCM1049LE
Notebook	DELL	E6220	QDS-BRCM1049LE
Notebook	DELL	E6430	QDS-BRCM1049LE
Notebook	DELL	E6430	QDS-BRCM1049LE

Test Site No. TH01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6220	QDS-BRCM1049LE

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

For 2.4GHz Band

Power Parameters of IEEE 802.11n MCS0 20MHz / Ant. 1+ Ant. 2+ Ant. 3

Test Software Version	Manual Tool Version : 1.0.0.10		
Frequency	2412 MHz	2437 MHz	2462 MHz
MCS0 20MHz	55	92	64

Power Parameters of IEEE 802.11n MCS0 40MHz / Ant. 1+ Ant. 2+ Ant. 3

Test Software Version	Manual Tool Version : 1.0.0.10		
Frequency	2422 MHz	2437 MHz	2452 MHz
MCS0 40MHz	43	70	51

Power Parameters of IEEE 802.11b/g / Ant. 1+ Ant. 2+ Ant. 3

Test Software Version	Manual Tool Version : 1.0.0.10		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	90	100	86
IEEE 802.11g	59	90	62

For 5GHz Band

Power Parameters of IEEE 802.11n MCS0 20MHz / Ant. 4+ Ant. 5+ Ant. 6

Test Software Version	Manual Tool Version : 1.0.0.10		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS0 20MHz	90	79	79

Power Parameters of IEEE 802.11n MCS0 40MHz / Ant. 4+ Ant. 5+ Ant. 6

Test Software Version	Manual Tool Version : 1.0.0.10		
Frequency	5755 MHz	5795 MHz	
MCS0 40MHz	89	77	

Power Parameters of IEEE 802.11a / Ant. 4+ Ant. 5+ Ant. 6


Test Software Version	Manual Tool Version : 1.0.0.10		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	89	79	79

3.9. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

3.10. Duty Cycle


IEEE 802.11n MCS0 20MHz / For 2.4GHz Band




IEEE 802.11n MCS0 40MHz / For 2.4GHz Band




IEEE 802.11n MCS0 20MHz / For 5GHz Band



IEEE 802.11n MCS0 40MHz / For 5GHz Band




IEEE 802.11b



Date: 9.APR.2013 14:08:25

IEEE 802.11g



Date: 9.APR.2013 14:09:06



RBW 1 MHz Delta 0.71
 VBW 1 MHz -43.60 dB
 Ref 20 dBm Att 30 dB SWT 5 ms 0.00000 ms

Sacker 1 (T1)
 -5.16 dBm
 Delta 1 (T1)
 1.14 dB

Center 5.18 GHz 500 ps/


1.2K
 CLRWR

894
 100

Date: 6.MAR.2013 07:13:09

3.11. Test Configurations


3.11.1. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shield	Length
1	Power cable	No	1.5m
2	RJ-45 cable*3	No	1m
3	RJ-45 cable	No	10m
4	RJ-45 cable	No	10m
5	USB cable	No	0.5m


3.11.2. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz



Item	Connection	Shield	Length
1	Power cable	No	1.5m
2	RJ-45 cable*3	No	1m
3	RJ-45 cable	No	10m
4	RJ-45 cable	No	10m
5	USB cable	No	0.5m

Test Configuration: above 1GHz



Item	Connection	Shield	Length
1	Power cable	No	1.5m
2	RJ-45 cable	No	10m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	24°C	Humidity	60%
Test Engineer	Justin Chiu	Phase	Line
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15403	50.12	-15.66	65.78	49.78	0.16	0.18	QP
2	0.15403	38.55	-17.23	55.78	38.21	0.16	0.18	AVERAGE
3	0.17584	45.90	-18.78	64.68	45.56	0.15	0.19	QP
4	0.17584	33.95	-20.73	54.68	33.61	0.15	0.19	AVERAGE
5	0.39344	32.93	-25.06	57.99	32.58	0.15	0.20	QP
6	0.39344	31.50	-16.49	47.99	31.15	0.15	0.20	AVERAGE
7	2.346	14.21	-31.79	46.00	13.78	0.20	0.24	AVERAGE
8	2.346	22.52	-33.48	56.00	22.09	0.20	0.24	QP
9	4.315	32.55	-23.45	56.00	32.02	0.23	0.31	QP
10	4.315	24.07	-21.93	46.00	23.54	0.23	0.31	AVERAGE
11	12.716	16.95	-33.05	50.00	16.17	0.38	0.40	AVERAGE
12	12.716	25.10	-34.90	60.00	24.32	0.38	0.40	QP

Temperature	24°C	Humidity	60%
Test Engineer	Justin Chiu	Phase	Neutral
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15321	41.32	-14.50	55.82	41.06	0.08	0.18	AVERAGE
2	0.15321	50.74	-15.08	65.82	50.48	0.08	0.18	QP
3	0.17584	45.97	-18.71	64.68	45.70	0.08	0.19	QP
4	0.17584	35.49	-19.19	54.68	35.22	0.08	0.19	AVERAGE
5	0.23910	31.16	-20.97	52.13	30.88	0.08	0.20	AVERAGE
6	0.23910	37.50	-24.63	62.13	37.22	0.08	0.20	QP
7	2.358	26.80	-29.20	56.00	26.45	0.11	0.24	QP
8	2.358	23.86	-22.14	46.00	23.51	0.11	0.24	AVERAGE
9	4.407	22.31	-23.69	46.00	21.86	0.14	0.31	AVERAGE
10	4.407	33.00	-23.00	56.00	32.55	0.14	0.31	QP
11	12.582	25.79	-34.21	60.00	25.11	0.28	0.40	QP
12	12.582	20.25	-29.75	50.00	19.57	0.28	0.40	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter output power.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

4.2.3. Test Procedures

1. Test procedures refer KDB558074 v01 r02 section 8.2.3 option 3.
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	23°C	Humidity	63%
Test Engineer	Benson Peng	Configurations	IEEE 802.11n
Test Date	Apr. 11, 2013		

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Ant. 1+ Ant. 2+ Ant. 3

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3			
1	2412 MHz	13.98	14.12	14.15	18.86	30.00	Complies
6	2437 MHz	21.82	22.32	22.54	27.01	30.00	Complies
11	2462 MHz	16.23	16.39	16.40	21.11	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz / Ant. 1+ Ant. 2+ Ant. 3

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3			
3	2422 MHz	10.72	10.29	10.43	15.25	30.00	Complies
6	2437 MHz	18.08	18.31	18.62	23.11	30.00	Complies
9	2452 MHz	13.83	13.62	13.67	18.48	30.00	Complies

For 5GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Ant. 4+ Ant. 5+ Ant. 6

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 4	Ant. 5	Ant. 6			
149	5745 MHz	23.78	22.98	23.15	28.09	30.00	Complies
157	5785 MHz	21.43	20.44	20.55	25.60	30.00	Complies
165	5825 MHz	21.36	20.24	20.37	25.46	30.00	Complies

Configuration IEEE 802.11n MCS0 40MHz / Ant. 4+ Ant. 5+ Ant. 6

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 4	Ant. 5	Ant. 6			
151	5755 MHz	22.81	22.84	22.97	27.65	30.00	Complies
159	5795 MHz	20.53	20.17	20.39	25.14	30.00	Complies

Temperature	23°C	Humidity	63%
Test Engineer	Benson Peng	Configurations	IEEE 802.11a/b/g
Test Date	Apr. 11, 2013		

Configuration IEEE 802.11b / Ant. 1+ Ant. 2+ Ant. 3

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3			
1	2412 MHz	21.48	22.09	22.19	26.70	30.00	Complies
6	2437 MHz	24.06	24.51	24.70	29.20	30.00	Complies
11	2462 MHz	20.66	21.15	21.23	25.79	30.00	Complies

Configuration IEEE 802.11g / Ant. 1+ Ant. 2+ Ant. 3

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 1	Ant. 2	Ant. 3			
1	2412 MHz	14.70	15.11	15.09	19.74	30.00	Complies
6	2437 MHz	21.73	22.05	22.34	26.82	30.00	Complies
11	2462 MHz	15.64	16.06	16.03	20.69	30.00	Complies

Configuration IEEE 802.11a / Ant. 4+ Ant. 5+ Ant. 6

Channel	Frequency	Conducted Power (dBm)			Total Conducted Power (dBm)	Max. Limit (dBm)	Result
		Ant. 4	Ant. 5	Ant. 6			
149	5745 MHz	23.14	22.89	22.76	27.70	30.00	Complies
157	5785 MHz	21.36	20.42	20.52	25.56	30.00	Complies
165	5825 MHz	21.35	20.29	21.46	25.84	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RB	≥ 3 kHz
VB	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.3.3. Test Procedures

1. Test procedures refer KDB 558074 v01 r02 section 9.1 option 1 & KDB662911 D01 Multiple Transmitter Output v01r02 section In-Band Power Spectral Density (PSD) Measurements option (2) Measure and add $10 \log(\text{NANT})$ dB.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be ≤ 8 dBm.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	23°C	Humidity	63%
Test Engineer	Benson Peng	Configurations	IEEE 802.11n

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Ant. 1, Ant. 2, Ant. 3

Channel	Frequency	Power Density (dBm/3kHz)			Single Port Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3		
1	2412 MHz	-11.25	-11.14	-11.36	3.23	Complies
6	2437 MHz	-4.16	-3.71	-3.48	3.23	Complies
11	2462 MHz	-10.34	-9.37	-9.67	3.23	Complies

Note: PSD Limit = 8dBm/3KHz $-(10\log(3)) = 3.23\text{dBm/3KHz}$.

Configuration IEEE 802.11n MCS0 40MHz / Ant. 1, Ant. 2, Ant. 3

Channel	Frequency	Power Density (dBm/3kHz)			Single Port Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3		
3	2422 MHz	-17.45	-18.33	-17.80	3.23	Complies
6	2437 MHz	-10.17	-9.15	-9.90	3.23	Complies
9	2452 MHz	-15.50	-14.81	-14.77	3.23	Complies

Note: PSD Limit = 8dBm/3KHz $-(10\log(3)) = 3.23\text{dBm/3KHz}$.

For 5GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Ant. 4, Ant. 5, Ant. 6

Channel	Frequency	Power Density (dBm/3kHz)			Single Port Limit (dBm/3kHz)	Result
		Ant. 4	Ant. 5	Ant. 6		
149	5745 MHz	-2.45	-1.08	-1.61	3.23	Complies
157	5785 MHz	-4.98	-4.64	-4.61	3.23	Complies
165	5825 MHz	-4.75	-4.54	-4.82	3.23	Complies

Note: PSD Limit = 8dBm/3KHz $-(10\log(3)) = 3.23\text{dBm/3KHz}$.

Configuration IEEE 802.11n MCS0 40MHz / Ant. 4, Ant. 5, Ant. 6

Channel	Frequency	Power Density (dBm/3kHz)			Single Port Limit (dBm/3kHz)	Result
		Ant. 4	Ant. 5	Ant. 6		
151	5755 MHz	-4.64	-5.01	-4.55	3.23	Complies
159	5795 MHz	-6.86	-6.65	-7.23	3.23	Complies

Note: PSD Limit = 8dBm/3KHz $-(10\log(3)) = 3.23\text{dBm/3KHz}$.

Temperature	23°C	Humidity	63%
Test Engineer	Benson Peng	Configurations	IEEE 802.11a/b/g

Configuration IEEE 802.11b / Ant. 1, Ant. 2, Ant. 3

Channel	Frequency	Power Density (dBm/3kHz)			Single Port Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3		
1	2412 MHz	-2.28	-1.74	-1.88	3.23	Complies
6	2437 MHz	0.32	1.74	1.55	3.23	Complies
11	2462 MHz	-2.70	-1.94	-2.17	3.23	Complies

Note: PSD Limit = 8dBm/3KHz $-(10\log(3)) = 3.23\text{dBm/3KHz}$.

Configuration IEEE 802.11g / Ant. 1, Ant. 2, Ant. 3

Channel	Frequency	Power Density (dBm/3kHz)			Single Port Limit (dBm/3kHz)	Result
		Ant. 1	Ant. 2	Ant. 3		
1	2412 MHz	-10.88	-10.40	-10.55	3.23	Complies
6	2437 MHz	-4.21	-3.74	-3.30	3.23	Complies
11	2462 MHz	-11.06	-10.21	-10.51	3.23	Complies

Note: PSD Limit = 8dBm/3KHz $-(10\log(3)) = 3.23\text{dBm/3KHz}$.

Configuration IEEE 802.11a / Ant. 4, Ant. 5, Ant. 6

Channel	Frequency	Power Density (dBm/3kHz)			Single Port Limit (dBm/3kHz)	Result
		Ant. 4	Ant. 5	Ant. 6		
149	5745 MHz	-2.00	-1.93	-2.15	3.23	Complies
157	5785 MHz	-4.42	-3.92	-4.05	3.23	Complies
165	5825 MHz	-4.51	-3.81	-4.05	3.23	Complies

Note: PSD Limit = 8dBm/3KHz $-(10\log(3)) = 3.23\text{dBm/3KHz}$.

Note: All the test values were listed in the report.

For plots, only the channel with maximum results was shown.



Ref 20 dBm *Att 30 dB Marker 1 [T1] -3.48 dBm
 *RBW 3 kHz *VBW 30 kHz SWT 3.4 s 2.435380000 GHz

20 Offset 1.5 dB

1. PF
 MAX4

Center 2.437 GHz 3 MHz/ Span 30 MHz

Ref 20 dBm *Att 30 dB Marker 1 [T1] -9.15 dBm
 RBW 3 kHz VBW 30 kHz SWT 6.8 s 2.437600000 GHz


20 Offset 1.5 dB

1. PR
 12.241

Center 2.437 GHz 6 MHz/ Span 60 MHz


Issued Date : May 02, 2013

Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 5 / 5745 MHz




Date: 9.APR.2013 16:54:11

Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 6 / 5755 MHz




Date: 9.APR.2013 17:01:44

Power Density Plot on Configuration IEEE 802.11b / Ant. 2 / 2437 MHz



Date: 9.APR.2013 14:42:13

Power Density Plot on Configuration IEEE 802.11g / Ant. 3 / 2437 MHz



Date: 9.APR.2013 14:48:58



Ref 20 dBm *Att 30 dB *RBW 3 kHz *VBW 30 kHz SWT 3.4 s Marker 1 [T1] -1.93 dBm 5.750280000 GHz

20 Offset 12.5 dB

1. PF MAXdB

Center 5.745 GHz 3 MHz/ Span 30 MHz

Date: 9.APR.2013 16:47:51

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	1-5 % or DTS BW, not exceed 100KHz
VB	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 5.1.1 EBW Measurement Procedure
3. Multiple antenna system was performed in accordance with KDB 662911 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	23°C	Humidity	63%
Test Engineer	Benson Peng	Configurations	IEEE 802.11n

For 2.4GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Ant. 1+ Ant. 2+ Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	15.36	17.20	500	Complies
6	2437 MHz	15.12	17.12	500	Complies
11	2462 MHz	15.04	17.20	500	Complies

Configuration IEEE 802.11n MCS0 40MHz / Ant. 1+ Ant. 2+ Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
3	2422 MHz	31.36	36.00	500	Complies
6	2437 MHz	31.36	35.84	500	Complies
9	2452 MHz	31.36	35.52	500	Complies

For 5GHz Band

Configuration IEEE 802.11n MCS0 20MHz / Ant. 4+ Ant. 5+ Ant. 6

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	15.68	17.60	500	Complies
157	5785 MHz	16.40	17.60	500	Complies
165	5825 MHz	16.32	17.52	500	Complies

Configuration IEEE 802.11n MCS0 40MHz / Ant. 4+ Ant. 5+ Ant. 6

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	35.84	36.32	500	Complies
159	5795 MHz	35.84	36.32	500	Complies

Temperature	23°C	Humidity	63%
Test Engineer	Benson Peng	Configurations	IEEE 802.11a/b/g

Configuration IEEE 802.11b / Ant. 1+ Ant. 2+ Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	8.08	10.16	500	Complies
6	2437 MHz	8.48	10.24	500	Complies
11	2462 MHz	9.12	10.08	500	Complies

Configuration IEEE 802.11g / Ant. 1+ Ant. 2+ Ant. 3

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	15.04	16.40	500	Complies
6	2437 MHz	15.12	16.40	500	Complies
11	2462 MHz	15.04	16.40	500	Complies


Configuration IEEE 802.11a / Ant. 4+ Ant. 5+ Ant. 6

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	15.84	16.56	500	Complies
157	5785 MHz	15.12	16.56	500	Complies
165	5825 MHz	14.88	16.56	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 1+ Ant. 2+ Ant. 3 / 2462 MHz




Date: 9.APR.2013 14:24:58

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 1+ Ant. 2+ Ant. 3 / 2437 MHz




Date: 9.APR.2013 14:26:07

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / Ant. 4+ Ant. 5+ Ant. 6 / 5745 MHz




Date: 9.APR.2013 15:52:34

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / Ant. 4+ Ant. 5+ Ant. 6 / 5755MHz




Date: 9.APR.2013 15:35:07

6 dB Bandwidth Plot on Configuration IEEE 802.11b / Ant. 1+ Ant. 2+ Ant. 3 / 2412 MHz




Date: 9.APR.2013 14:19:30

6 dB Bandwidth Plot on Configuration IEEE 802.11g / Ant. 1+ Ant. 2+ Ant. 3 / 2462 MHz



Date: 9.APR.2013 14:21:34

6 dB Bandwidth Plot on Configuration IEEE 802.11a / Ant. 4+ Ant. 5+ Ant. 6 / 5825 MHz



Date: 9.APR.2013 15:51:30

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 1GHz



For radiated emissions above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	Normal Link
Test Date	Mar. 21, 2013		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	Normal Link

Horizontal



	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Preamp Factor	A/Pos	T/Pos	Pol/Phase	Remark	F.
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	101.78	26.40	43.50	-17.10	46.25	1.19	10.56	31.60	300	342	HORIZONTAL Peak	
2	172.59	22.12	43.50	-21.38	43.18	1.59	8.87	31.52	200	92	HORIZONTAL Peak	
3	375.32	28.64	46.00	-17.36	42.70	2.44	14.93	31.43	100	153	HORIZONTAL Peak	
4 pp	533.43	35.41	46.00	-10.59	46.17	2.90	17.72	31.38	150	34	HORIZONTAL Peak	
5	596.48	34.73	46.00	-11.27	44.45	3.11	18.40	31.23	150	284	HORIZONTAL Peak	
6	960.23	36.13	54.00	-17.87	42.07	4.10	21.05	31.09	100	321	HORIZONTAL Peak	

Vertical



		Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	A/Pos	T/Pos	Pol/Phase	Remark	F.
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg			
1	qp	42.61	34.87	40.00	-5.13	55.19	0.77	10.76	31.85	100	5	VERTICAL	QP	
2	!	68.80	34.04	40.00	-5.96	59.67	0.99	5.18	31.80	100	41	VERTICAL	Peak	
3	!	533.43	40.08	46.00	-5.92	50.84	2.90	17.72	31.38	100	290	VERTICAL	Peak	
4		725.49	37.39	46.00	-8.61	45.77	3.46	19.43	31.27	100	102	VERTICAL	Peak	
5	pp	853.53	41.89	46.00	-4.11	49.01	3.82	20.26	31.20	150	268	VERTICAL	Peak	
6		960.23	44.99	54.00	-9.01	50.93	4.10	21.05	31.09	125	255	VERTICAL	Peak	

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz Ch 1 / Ant. 1+ Ant. 2+ Ant. 3
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	2239.95	40.47	54.00	-13.53	45.60	2.14	27.83	35.10	Average	126	245	HORIZONTAL
2	2240.40	51.55	74.00	-22.45	56.68	2.14	27.83	35.10	Peak	126	245	HORIZONTAL
3	4827.91	29.06	54.00	-24.94	27.72	3.31	33.06	35.03	Average	100	292	HORIZONTAL
4	4828.04	41.79	74.00	-32.21	40.45	3.31	33.06	35.03	Peak	100	292	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	2239.94	41.77	54.00	-12.23	46.90	2.14	27.83	35.10	Average	114	288	VERTICAL
2	2239.98	53.52	74.00	-20.48	58.65	2.14	27.83	35.10	Peak	114	288	VERTICAL
3	4816.34	28.99	54.00	-25.01	27.70	3.31	33.02	35.04	Average	100	219	VERTICAL
4	4818.17	41.99	74.00	-32.01	40.69	3.31	33.02	35.03	Peak	100	219	VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz Ch 6 / Ant. 1+ Ant. 2+ Ant. 3
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2239.58	60.12	74.00	-13.88	65.25	2.14	27.83	35.10 Peak	133	263	HORIZONTAL
2	2240.03	48.22	54.00	-5.78	53.35	2.14	27.83	35.10 Average	133	263	HORIZONTAL
3	4868.65	42.63	74.00	-31.37	41.21	3.33	33.12	35.03 Peak	100	64	HORIZONTAL
4	4883.52	29.29	54.00	-24.71	27.83	3.33	33.16	35.03 Average	100	64	HORIZONTAL
5	7313.21	45.03	74.00	-28.97	40.41	4.06	35.96	35.40 Peak	100	138	HORIZONTAL
6	7314.14	32.62	54.00	-21.38	28.00	4.06	35.96	35.40 Average	100	138	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2238.69	61.66	74.00	-12.34	66.79	2.14	27.83	35.10 Peak	118	287	VERTICAL
2	2239.97	50.30	54.00	-3.70	55.43	2.14	27.83	35.10 Average	118	287	VERTICAL
3	4875.80	29.18	54.00	-24.82	27.72	3.33	33.16	35.03 Average	100	37	VERTICAL
4	4877.43	42.00	74.00	-32.00	40.54	3.33	33.16	35.03 Peak	100	37	VERTICAL
5	7304.24	45.19	74.00	-28.81	40.61	4.06	35.92	35.40 Peak	100	291	VERTICAL
6	7307.44	32.64	54.00	-21.36	28.02	4.06	35.96	35.40 Average	100	291	VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz Ch 11 / Ant. 1+ Ant. 2+ Ant. 3
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	2239.95	41.98	54.00	-12.02	47.11	2.14	27.83	35.10	Average	153	271	HORIZONTAL
2	2240.92	54.62	74.00	-19.38	59.75	2.14	27.83	35.10	Peak	153	271	HORIZONTAL
3	4933.46	41.81	74.00	-32.19	40.21	3.35	33.26	35.01	Peak	100	84	HORIZONTAL
4	4933.81	29.62	54.00	-24.38	28.02	3.35	33.26	35.01	Average	100	84	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	2239.58	55.36	74.00	-18.64	60.49	2.14	27.83	35.10	Peak	111	288	VERTICAL
2	2239.94	43.56	54.00	-10.44	48.69	2.14	27.83	35.10	Average	111	288	VERTICAL
3	4931.95	29.80	54.00	-24.20	28.20	3.35	33.26	35.01	Average	100	212	VERTICAL
4	4933.26	42.22	74.00	-31.78	40.62	3.35	33.26	35.01	Peak	100	212	VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 40MHz Ch 3 / Ant. 1+ Ant. 2+ Ant. 3
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
			Line	Limit	Level	Loss	Factor	Factor	Remark			Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2240.01	40.87	54.00	-13.13	46.00	2.14	27.83	35.10	Average	100	251	HORIZONTAL
2	2240.12	48.43	74.00	-25.57	53.56	2.14	27.83	35.10	Peak	100	251	HORIZONTAL
3	4852.69	41.55	74.00	-32.45	40.17	3.32	33.09	35.03	Peak	100	301	HORIZONTAL
4	4853.07	28.81	54.00	-25.19	27.43	3.32	33.09	35.03	Average	100	301	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
			Line	Limit	Level	Loss	Factor	Factor	Remark			Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2239.80	52.64	74.00	-21.36	57.77	2.14	27.83	35.10	Peak	156	318	VERTICAL
2	2239.95	42.81	54.00	-11.19	47.94	2.14	27.83	35.10	Average	156	318	VERTICAL
3	4834.03	40.75	74.00	-33.25	39.41	3.31	33.06	35.03	Peak	100	164	VERTICAL
4	4841.60	28.76	54.00	-25.24	27.38	3.32	33.09	35.03	Average	100	164	VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 40MHz Ch 6 / Ant. 1+ Ant. 2+ Ant. 3
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
			Line	Limit	Level	Loss	Factor	Factor	Remark			Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2239.96	46.88	54.00	-7.12	52.01	2.14	27.83	35.10	Average	127	264	HORIZONTAL
2	2240.22	56.70	74.00	-17.30	61.83	2.14	27.83	35.10	Peak	127	264	HORIZONTAL
3	4880.17	29.30	54.00	-24.70	27.84	3.33	33.16	35.03	Average	100	303	HORIZONTAL
4	4885.30	41.77	74.00	-32.23	40.31	3.33	33.16	35.03	Peak	100	303	HORIZONTAL
5	7308.31	32.55	54.00	-21.45	27.93	4.06	35.96	35.40	Average	100	19	HORIZONTAL
6	7314.85	44.64	74.00	-29.36	40.02	4.06	35.96	35.40	Peak	100	19	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
			Line	Limit	Level	Loss	Factor	Factor	Remark			Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2239.98	48.88	54.00	-5.12	54.01	2.14	27.83	35.10	Average	156	323	VERTICAL
2	2240.01	57.52	74.00	-16.48	62.65	2.14	27.83	35.10	Peak	156	323	VERTICAL
3	4852.61	41.38	74.00	-32.62	40.00	3.32	33.09	35.03	Peak	100	105	VERTICAL
4	4880.25	29.27	54.00	-24.73	27.81	3.33	33.16	35.03	Average	100	105	VERTICAL
5	7302.35	32.48	54.00	-21.52	27.90	4.06	35.92	35.40	Average	100	345	VERTICAL
6	7317.67	45.55	74.00	-28.45	40.93	4.06	35.96	35.40	Peak	100	345	VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 40MHz Ch 9 / Ant. 1+ Ant. 2+ Ant. 3
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2239.98	43.73	54.00	-10.27	48.86	2.14	27.83	35.10	Average	100	250 HORIZONTAL
2	2240.00	52.24	74.00	-21.76	57.37	2.14	27.83	35.10	Peak	100	250 HORIZONTAL
3	4899.71	29.38	54.00	-24.62	27.87	3.34	33.19	35.02	Average	100	46 HORIZONTAL
4	4913.68	42.26	74.00	-31.74	40.71	3.34	33.23	35.02	Peak	100	46 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2239.80	53.98	74.00	-20.02	59.11	2.14	27.83	35.10	Peak	100	287 VERTICAL
2	2239.98	44.57	54.00	-9.43	49.70	2.14	27.83	35.10	Average	100	287 VERTICAL
3	4900.44	29.56	54.00	-24.44	28.05	3.34	33.19	35.02	Average	100	126 VERTICAL
4	4912.01	41.55	74.00	-32.45	40.00	3.34	33.23	35.02	Peak	100	126 VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz CH 149 / Ant. 4+ Ant. 5+ Ant. 6
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg
1	5386.96	66.88	74.00	-7.12	64.37	3.50	34.09	35.08	Peak	148	196 HORIZONTAL
2	5392.73	53.96	54.00	-0.04	51.45	3.50	34.09	35.08	Average	148	196 HORIZONTAL
3	11491.36	40.57	54.00	-13.43	31.96	5.11	38.78	35.28	Average	100	298 HORIZONTAL
4	11491.68	54.15	74.00	-19.85	45.54	5.11	38.78	35.28	Peak	100	298 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg
1	5415.81	65.41	74.00	-8.59	62.86	3.51	34.12	35.08	Peak	115	10 VERTICAL
2	5418.69	52.63	54.00	-1.37	50.05	3.51	34.15	35.08	Average	115	10 VERTICAL
3	11489.84	51.46	74.00	-22.54	42.85	5.11	38.78	35.28	Peak	100	90 VERTICAL
4	11491.12	38.49	54.00	-15.51	29.88	5.11	38.78	35.28	Average	100	90 VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz CH 157 / Ant. 4+ Ant. 5+ Ant. 6
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	5394.01	52.83	54.00	-1.17	50.32	3.50	34.09	35.08	Average	144	196 HORIZONTAL
2	5442.41	65.98	74.00	-8.02	63.38	3.52	34.17	35.09	Peak	144	196 HORIZONTAL
3	11571.67	38.35	54.00	-15.65	29.68	5.14	38.83	35.30	Average	100	295 HORIZONTAL
4	11571.67	52.21	74.00	-21.79	43.54	5.14	38.83	35.30	Peak	100	295 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	5395.30	66.86	74.00	-7.14	64.35	3.50	34.09	35.08	Peak	127	18 VERTICAL
2	5399.78	53.96	54.00	-0.04	51.41	3.51	34.12	35.08	Average	127	18 VERTICAL
3	11570.06	36.98	54.00	-17.02	28.31	5.14	38.83	35.30	Average	100	148 VERTICAL
4	11572.50	49.93	74.00	-24.07	41.26	5.14	38.83	35.30	Peak	100	148 VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz CH 165 / Ant. 4+ Ant. 5+ Ant. 6
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	5397.54	63.82	74.00	-10.18	61.31	3.50	34.09	35.08	Peak	100	221	HORIZONTAL
2	5405.23	51.26	54.00	-2.74	48.71	3.51	34.12	35.08	Average	100	221	HORIZONTAL
3	11647.82	52.10	74.00	-21.90	43.38	5.16	38.86	35.30	Peak	100	53	HORIZONTAL
4	11648.69	39.00	54.00	-15.00	30.28	5.16	38.86	35.30	Average	100	53	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	5392.73	65.77	74.00	-8.23	63.26	3.50	34.09	35.08	Peak	126	354	VERTICAL
2	5416.45	53.71	54.00	-0.29	51.13	3.51	34.15	35.08	Average	126	354	VERTICAL
3	11650.54	37.10	54.00	-16.90	28.38	5.16	38.86	35.30	Average	100	143	VERTICAL
4	11656.60	49.51	74.00	-24.49	40.79	5.16	38.86	35.30	Peak	100	143	VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 40MHz CH 151 / Ant. 4+ Ant. 5+ Ant. 6
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	5373.50	66.89	74.00	-7.11	64.40	3.50	34.06	35.07	Peak	152	197 HORIZONTAL
2	5399.78	53.87	54.00	-0.13	51.32	3.51	34.12	35.08	Average	152	197 HORIZONTAL
3	11506.47	39.04	54.00	-14.96	30.41	5.12	38.79	35.28	Average	100	294 HORIZONTAL
4	11506.79	52.51	74.00	-21.49	43.88	5.12	38.79	35.28	Peak	100	294 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	5395.94	52.22	54.00	-1.78	49.71	3.50	34.09	35.08	Average	101	16 VERTICAL
2	5398.82	65.57	74.00	-8.43	63.05	3.51	34.09	35.08	Peak	101	16 VERTICAL
3	11510.16	37.64	54.00	-16.36	29.01	5.12	38.79	35.28	Average	100	124 VERTICAL
4	11514.01	49.25	74.00	-24.75	40.62	5.12	38.79	35.28	Peak	100	124 VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 40MHz CH 159 / Ant. 4+ Ant. 5+ Ant. 6
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	5393.37	66.96	74.00	-7.04	64.45	3.50	34.09	35.08	Peak	145	196 HORIZONTAL
2	5398.50	53.19	54.00	-0.81	50.68	3.50	34.09	35.08	Average	145	196 HORIZONTAL
3	11590.00	37.95	54.00	-16.05	29.28	5.14	38.83	35.30	Average	100	248 HORIZONTAL
4	11590.80	49.87	74.00	-24.13	41.20	5.14	38.83	35.30	Peak	100	248 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	5405.87	66.59	74.00	-7.41	64.04	3.51	34.12	35.08	Peak	115	11 VERTICAL
2	5419.01	53.68	54.00	-0.32	51.10	3.51	34.15	35.08	Average	115	11 VERTICAL
3	11575.18	36.69	54.00	-17.31	28.02	5.14	38.83	35.30	Average	100	181 VERTICAL
4	11605.54	48.34	74.00	-25.66	39.65	5.15	38.84	35.30	Peak	100	181 VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11b CH 1 / Ant. 1+ Ant. 2+ Ant. 3
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2239.99	47.49	54.00	-6.51	52.62	2.14	27.83	35.10	Average	123	269	HORIZONTAL
2	2240.09	59.98	74.00	-14.02	65.11	2.14	27.83	35.10	Peak	123	269	HORIZONTAL
3	2331.97	52.44	54.00	-1.56	57.30	2.18	28.06	35.10	Average	117	274	HORIZONTAL
4	2332.23	63.03	74.00	-10.97	67.89	2.18	28.06	35.10	Peak	117	274	HORIZONTAL
5	4815.76	41.41	74.00	-32.59	40.12	3.31	33.02	35.04	Peak	100	206	HORIZONTAL
6	4823.90	29.39	54.00	-24.61	28.05	3.31	33.06	35.03	Average	100	206	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2239.98	49.13	54.00	-4.87	54.26	2.14	27.83	35.10	Average	100	288	VERTICAL
2	2240.45	61.82	74.00	-12.18	66.95	2.14	27.83	35.10	Peak	100	288	VERTICAL
3	2331.85	60.33	74.00	-13.67	65.19	2.18	28.06	35.10	Peak	110	287	VERTICAL
4	2331.97	50.50	54.00	-3.50	55.36	2.18	28.06	35.10	Average	110	287	VERTICAL
5	4818.23	41.04	74.00	-32.96	39.74	3.31	33.02	35.03	Peak	100	338	VERTICAL
6	4823.97	29.39	54.00	-24.61	28.05	3.31	33.06	35.03	Average	100	338	VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11b CH 6 / Ant. 1+ Ant. 2+ Ant. 3
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2239.94	51.45	54.00	-2.55	56.58	2.14	27.83	35.10 Average	128	272	HORIZONTAL
2	2240.79	64.36	74.00	-9.64	69.49	2.14	27.83	35.10 Peak	128	272	HORIZONTAL
3	2356.81	63.99	74.00	-10.01	68.80	2.19	28.10	35.10 Peak	120	242	HORIZONTAL
4	2357.00	53.65	54.00	-0.35	58.46	2.19	28.10	35.10 Average	120	242	HORIZONTAL
5	4873.97	30.90	54.00	-23.10	29.44	3.33	33.16	35.03 Average	100	200	HORIZONTAL
6	4880.99	41.42	74.00	-32.58	39.96	3.33	33.16	35.03 Peak	100	200	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2238.60	65.35	74.00	-8.65	70.48	2.14	27.83	35.10 Peak	100	287	VERTICAL
2	2239.99	52.32	54.00	-1.68	57.45	2.14	27.83	35.10 Average	100	287	VERTICAL
3	2356.87	61.91	74.00	-12.09	66.72	2.19	28.10	35.10 Peak	105	285	VERTICAL
4	2356.97	52.08	54.00	-1.92	56.89	2.19	28.10	35.10 Average	105	285	VERTICAL
5	4872.11	41.46	74.00	-32.54	40.00	3.33	33.16	35.03 Peak	100	77	VERTICAL
6	4873.94	30.36	54.00	-23.64	28.90	3.33	33.16	35.03 Average	100	77	VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11b CH 11 / Ant. 1+ Ant. 2+ Ant. 3
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2240.00	47.67	54.00	-6.33	52.80	2.14	27.83	35.10	Average	127	269	HORIZONTAL
2	2240.12	60.91	74.00	-13.09	66.04	2.14	27.83	35.10	Peak	127	269	HORIZONTAL
3	4931.08	41.75	74.00	-32.25	40.15	3.35	33.26	35.01	Peak	100	81	HORIZONTAL
4	4932.56	29.71	54.00	-24.29	28.11	3.35	33.26	35.01	Average	100	81	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2239.90	61.21	74.00	-12.79	66.34	2.14	27.83	35.10	Peak	100	287	VERTICAL
2	2240.02	48.91	54.00	-5.09	54.04	2.14	27.83	35.10	Average	100	287	VERTICAL
3	4923.02	42.79	74.00	-31.21	41.19	3.35	33.26	35.01	Peak	100	233	VERTICAL
4	4923.97	30.03	54.00	-23.97	28.43	3.35	33.26	35.01	Average	100	233	VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11g CH 1 / Ant. 1+ Ant. 2+ Ant. 3
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	2240.06	40.29	54.00	-13.71	45.42	2.14	27.83	35.10	Average	122	272	HORIZONTAL
2	2240.42	52.45	74.00	-21.55	57.58	2.14	27.83	35.10	Peak	122	272	HORIZONTAL
3	4816.63	28.85	54.00	-25.15	27.56	3.31	33.02	35.04	Average	100	182	HORIZONTAL
4	4817.78	41.24	74.00	-32.76	39.94	3.31	33.02	35.03	Peak	100	182	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	2238.32	54.72	74.00	-19.28	59.85	2.14	27.83	35.10	Peak	114	287	VERTICAL
2	2239.97	42.76	54.00	-11.24	47.89	2.14	27.83	35.10	Average	114	287	VERTICAL
3	4815.99	28.91	54.00	-25.09	27.62	3.31	33.02	35.04	Average	100	106	VERTICAL
4	4818.62	41.74	74.00	-32.26	40.44	3.31	33.02	35.03	Peak	100	106	VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11g CH 6 / Ant. 1+ Ant. 2+ Ant. 3
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2440.11	48.52	54.00	-5.48	53.10	2.23	28.29	35.10	Average	129	266	HORIZONTAL
2	2440.36	61.82	74.00	-12.18	66.40	2.23	28.29	35.10	Peak	129	266	HORIZONTAL
3	4870.25	41.44	74.00	-32.56	40.02	3.33	33.12	35.03	Peak	100	142	HORIZONTAL
4	4878.33	29.25	54.00	-24.75	27.79	3.33	33.16	35.03	Average	100	142	HORIZONTAL
5	7309.14	45.50	74.00	-28.50	40.88	4.06	35.96	35.40	Peak	100	214	HORIZONTAL
6	7315.65	32.63	54.00	-21.37	28.01	4.06	35.96	35.40	Average	100	214	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2440.32	50.82	54.00	-3.18	55.40	2.23	28.29	35.10	Average	114	286	VERTICAL
2	2440.32	62.22	74.00	-11.78	66.80	2.23	28.29	35.10	Peak	114	286	VERTICAL
3	4868.55	41.66	74.00	-32.34	40.24	3.33	33.12	35.03	Peak	100	53	VERTICAL
4	4879.22	30.01	54.00	-23.99	28.55	3.33	33.16	35.03	Average	100	53	VERTICAL
5	7310.74	46.30	74.00	-27.70	41.68	4.06	35.96	35.40	Peak	100	240	VERTICAL
6	7313.72	32.64	54.00	-21.36	28.02	4.06	35.96	35.40	Average	100	240	VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11g CH 11 / Ant. 1+ Ant. 2+ Ant. 3
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	2239.98	40.69	54.00	-13.31	45.82	2.14	27.83	35.10	Average	100	250	HORIZONTAL
2	2240.06	50.77	74.00	-23.23	55.90	2.14	27.83	35.10	Peak	100	250	HORIZONTAL
3	4929.32	42.09	74.00	-31.91	40.49	3.35	33.26	35.01	Peak	100	45	HORIZONTAL
4	4933.97	29.68	54.00	-24.32	28.08	3.35	33.26	35.01	Average	100	45	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	2239.99	43.07	54.00	-10.93	48.20	2.14	27.83	35.10	Average	100	287	VERTICAL
2	2241.15	54.73	74.00	-19.27	59.86	2.14	27.83	35.10	Peak	100	287	VERTICAL
3	4931.47	42.99	74.00	-31.01	41.39	3.35	33.26	35.01	Peak	100	167	VERTICAL
4	4932.78	29.80	54.00	-24.20	28.20	3.35	33.26	35.01	Average	100	167	VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11a CH 149 / Ant. 4+ Ant. 5+ Ant. 6
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	5379.23	53.17	54.00	-0.83	50.69	3.50	34.06	35.08	Average	100	196	HORIZONTAL
2	5384.04	66.96	74.00	-7.04	64.45	3.50	34.09	35.08	Peak	100	196	HORIZONTAL
3	11488.40	41.39	54.00	-12.61	32.78	5.11	38.78	35.28	Average	100	298	HORIZONTAL
4	11498.30	55.27	74.00	-18.73	46.65	5.12	38.78	35.28	Peak	100	298	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	5395.58	52.38	54.00	-1.62	49.87	3.50	34.09	35.08	Average	101	18	VERTICAL
2	5400.06	65.49	74.00	-8.51	62.94	3.51	34.12	35.08	Peak	101	18	VERTICAL
3	11489.62	39.62	54.00	-14.38	31.01	5.11	38.78	35.28	Average	100	284	VERTICAL
4	11490.51	52.37	74.00	-21.63	43.76	5.11	38.78	35.28	Peak	100	284	VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11a CH 157 / Ant. 4+ Ant. 5+ Ant. 6
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss Factor	Factor	Remark	cm	deg	Pol/Phase
1	5405.19	53.92	54.00	-0.08	51.37	3.51	34.12	35.08 Average	100	221	HORIZONTAL
2	5407.12	66.22	74.00	-7.78	63.67	3.51	34.12	35.08 Peak	100	221	HORIZONTAL
3	11567.85	39.23	54.00	-14.77	30.57	5.13	38.83	35.30 Average	100	294	HORIZONTAL
4	11568.49	53.86	74.00	-20.14	45.20	5.13	38.83	35.30 Peak	100	294	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss Factor	Factor	Remark	cm	deg	Pol/Phase
1	5411.28	53.98	54.00	-0.02	51.43	3.51	34.12	35.08 Average	113	17	VERTICAL
2	5411.92	66.70	74.00	-7.30	64.15	3.51	34.12	35.08 Peak	113	17	VERTICAL
3	11568.30	51.50	74.00	-22.50	42.84	5.13	38.83	35.30 Peak	100	284	VERTICAL
4	11569.74	37.56	54.00	-16.44	28.90	5.13	38.83	35.30 Average	100	284	VERTICAL

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11a CH 165 / Ant. 4+ Ant. 5+ Ant. 6
Test Date	Mar. 27, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5407.15	50.31	54.00	-3.69	47.76	3.51	34.12	35.08	Average	100	360	HORIZONTAL
2	5414.85	62.51	74.00	-11.49	59.96	3.51	34.12	35.08	Peak	100	360	HORIZONTAL
3	11648.01	38.18	54.00	-15.82	29.46	5.16	38.86	35.30	Average	100	291	HORIZONTAL
4	11648.56	52.12	74.00	-21.88	43.40	5.16	38.86	35.30	Peak	100	291	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5395.94	53.35	54.00	-0.65	50.84	3.50	34.09	35.08	Average	100	17	VERTICAL
2	5409.40	65.92	74.00	-8.08	63.37	3.51	34.12	35.08	Peak	100	17	VERTICAL
3	11642.76	50.64	74.00	-23.36	41.92	5.16	38.86	35.30	Peak	100	183	VERTICAL
4	11648.81	37.16	54.00	-16.84	28.44	5.16	38.86	35.30	Average	100	183	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Emissions Measurement

4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 kHz / 300 kHz for Peak

4.6.3. Test Procedures

For Radiated band edges Measurement:

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around band edges.

For Conducted Out of Band Emission Measurement:

1. Test was performed in accordance with KDB 558074 v02 Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure
2. The conducted emission test is performed on each TX port of operating mode without summing or adding 10log (N) since the limit is relative emission limit.
Only worst data of each operating mode is presented.

4.6.4. Test Setup Layout

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Conducted Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.4.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 20MHz Ch 1, 6, 11 / Ant. 1+ Ant. 2+ Ant. 3
Test Date	Mar. 27, 2013		

Channel 1

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg
1	2390.00	53.44	54.00	-0.56	23.05	2.22	28.17	0.00	Average	140	295 HORIZONTAL
2	2390.00	67.13	74.00	-6.87	36.74	2.22	28.17	0.00	Peak	140	295 HORIZONTAL
3	2405.91	111.81			81.38	2.22	28.21	0.00	Peak	140	295 HORIZONTAL
4	2410.88	101.07			70.64	2.22	28.21	0.00	Average	140	295 HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg
1	2239.20	64.61	74.00	-9.39	34.64	2.14	27.83	0.00	Peak	113	288 VERTICAL
2	2240.00	53.78	54.00	-0.22	23.81	2.14	27.83	0.00	Average	113	288 VERTICAL
3	2432.19	101.77			71.29	2.23	28.25	0.00	Average	113	288 VERTICAL
4	2432.19	113.35			82.87	2.23	28.25	0.00	Peak	113	288 VERTICAL
5	2483.50	48.50	54.00	-5.50	17.87	2.26	28.37	0.00	Average	113	288 VERTICAL
6	2488.31	61.41	74.00	-12.59	30.74	2.26	28.41	0.00	Peak	113	288 VERTICAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 11

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg
1	2466.65	99.75			69.16	2.26	28.33	0.00	Average	100	287 VERTICAL
2	2468.25	111.84			81.21	2.26	28.37	0.00	Peak	100	287 VERTICAL
3	2483.50	53.96	54.00	-0.04	23.33	2.26	28.37	0.00	Average	100	287 VERTICAL
4	2484.30	66.73	74.00	-7.27	36.10	2.26	28.37	0.00	Peak	100	287 VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11n MCS0 40MHz Ch 3, 6, 9 / Ant. 1+ Ant. 2+ Ant. 3
Test Date	Mar. 27, 2013		

Channel 3

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2385.51	53.86	54.00	-0.14	23.48	2.21	28.17	0.00	Average	139	300 HORIZONTAL
2	2386.15	66.48	74.00	-7.52	36.10	2.21	28.17	0.00	Peak	139	300 HORIZONTAL
3	2410.14	106.61	---	---	76.18	2.22	28.21	0.00	Peak	139	300 HORIZONTAL
4	2410.78	94.38			63.95	2.22	28.21	0.00	Average	139	300 HORIZONTAL

Item 3, 4 are the fundamental frequency at 2422 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2388.40	66.98	74.00	-7.02	36.60	2.21	28.17	0.00	Peak	144	137 HORIZONTAL
2	2389.36	53.64	54.00	-0.36	23.26	2.21	28.17	0.00	Average	144	137 HORIZONTAL
3	2438.28	112.84			82.32	2.23	28.29	0.00	Peak	144	137 HORIZONTAL
4	2438.60	101.52			71.00	2.23	28.29	0.00	Average	144	137 HORIZONTAL
5	2483.50	51.85	54.00	-2.15	21.21	2.26	28.38	0.00	Average	144	137 HORIZONTAL
6	2483.50	66.95	74.00	-7.05	36.31	2.26	28.38	0.00	Peak	144	137 HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437MHz.

Channel 9

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg
			dBuV/m	dB	dBuV	dB	dB/m	dB			Pol/Phase
1	2434.69	106.75	---	---	76.23	2.23	28.29	0.00	Peak	101	286 VERTICAL
2	2449.44	95.13			64.60	2.24	28.29	0.00	Average	101	286 VERTICAL
3	2487.03	53.70	54.00	-0.30	23.03	2.26	28.41	0.00	Average	101	286 VERTICAL
4	2489.91	65.92	74.00	-8.08	35.25	2.26	28.41	0.00	Peak	101	286 VERTICAL

Item 1, 2 are the fundamental frequency at 2452 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11b CH 1, 6, 11 / Ant. 1+ Ant. 2+ Ant. 3
Test Date	Mar. 27, 2013		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2390.00	53.92	54.00	-0.08	23.53	2.22	28.17	0.00	Average	100	284	VERTICAL
2	2390.00	61.73	74.00	-12.27	31.34	2.22	28.17	0.00	Peak	100	284	VERTICAL
3	2411.04	116.71			86.28	2.22	28.21	0.00	Peak	100	284	VERTICAL
4	2411.20	112.95			82.52	2.22	28.21	0.00	Average	100	284	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2352.80	63.03	74.00	-10.97	32.74	2.19	28.10	0.00	Peak	131	289	HORIZONTAL
2	2356.47	51.78	54.00	-2.22	21.49	2.19	28.10	0.00	Average	131	289	HORIZONTAL
3	2436.20	114.67			84.15	2.23	28.29	0.00	Average	131	289	HORIZONTAL
4	2436.20	118.42			87.90	2.23	28.29	0.00	Peak	131	289	HORIZONTAL
5	2483.50	47.54	54.00	-6.46	16.90	2.26	28.38	0.00	Average	131	289	HORIZONTAL
6	2483.50	59.54	74.00	-14.46	28.90	2.26	28.38	0.00	Peak	131	289	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	2462.80	110.18			79.61	2.24	28.33	0.00	Average	100	286	VERTICAL
2	2462.96	114.11			83.54	2.24	28.33	0.00	Peak	100	286	VERTICAL
3	2483.50	53.67	54.00	-0.33	23.04	2.26	28.37	0.00	Average	100	286	VERTICAL
4	2483.98	65.45	74.00	-8.55	34.82	2.26	28.37	0.00	Peak	100	286	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24.5°C	Humidity	60%
Test Engineer	Jim Huang	Configurations	IEEE 802.11g CH 1, 6, 11 / Ant. 1+ Ant. 2+ Ant. 3
Test Date	Mar. 27, 2013		

Channel 1

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	2390.00	53.70	54.00	-0.30	23.31	2.22	28.17	0.00	Average	139	291	HORIZONTAL
2	2390.00	66.05	74.00	-7.95	35.66	2.22	28.17	0.00	Peak	139	291	HORIZONTAL
3	2406.39	113.04			82.61	2.22	28.21	0.00	Peak	139	291	HORIZONTAL
4	2411.20	102.63			72.20	2.22	28.21	0.00	Average	139	291	HORIZONTAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	2240.00	64.76	74.00	-9.24	34.79	2.14	27.83	0.00	Peak	119	288	VERTICAL
2	2240.20	53.84	54.00	-0.16	23.87	2.14	27.83	0.00	Average	119	288	VERTICAL
3	2437.80	104.27			73.75	2.23	28.29	0.00	Average	119	288	VERTICAL
4	2438.60	114.40			83.88	2.23	28.29	0.00	Peak	119	288	VERTICAL
5	2487.51	46.70	54.00	-7.30	16.03	2.26	28.41	0.00	Average	119	288	VERTICAL
6	2488.31	58.09	74.00	-15.91	27.42	2.26	28.41	0.00	Peak	119	288	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.


Channel 11

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	Line	Limit	Level	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	2462.80	100.03			69.46	2.24	28.33	0.00	Average	100	286	VERTICAL
2	2462.96	110.28			79.71	2.24	28.33	0.00	Peak	100	286	VERTICAL
3	2483.50	53.92	54.00	-0.08	23.29	2.26	28.37	0.00	Average	100	286	VERTICAL
4	2483.50	66.66	74.00	-7.34	36.03	2.26	28.37	0.00	Peak	100	286	VERTICAL


Item 1, 2 are the fundamental frequency at 2462 MHz.



Plot on Configuration IEEE 802.11n MCS0 20MHz / Reference Level




Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 9.APR.2013 15:15:48

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 9.APR.2013 15:16:22

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 9.APR.2013 15:16:06

Plot on Configuration IEEE 802.11n MCS0 40MHz / Reference Level




Date: 9.APR.2013 15:17:29

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 3 / 30MHz~2400MHz (down 30dBc)




Date: 9.APR.2013 15:17:49

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 3 / 2500MHz~26500MHz (down 30dBc)




Date: 9.APR.2013 15:18:04

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 9 / 30MHz~2400MHz (down 30dBc)




Date: 9.APR.2013 15:18:37

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 9 / 2500MHz~26500MHz (down 30dBc)




Date: 9.APR.2013 15:18:24


Plot on Configuration IEEE 802.11n MCS0 20MHz / Reference Level



Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 149 / 30MHz~5725MHz (down 30dBc)




Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 149 / 5850MHz~40000MHz (down 30dBc)




Date: 3.APR.2013 05:27:30

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 165 / 30MHz~5725MHz (down 30dBc)




Date: 3.APR.2013 05:28:51

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 165 / 5850MHz~40000MHz (down 30dBc)




Date: 3.APR.2013 05:28:26


Plot on Configuration IEEE 802.11n MCS0 40MHz / Reference Level




Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 151 / 30MHz~5725MHz (down 30dBc)




Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 151 / 5850MHz~40000MHz (down 30dBc)



Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 159 / 30MHz~5725MHz (down 30dBc)




Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 159 / 5850MHz~40000MHz (down 30dBc)




Date: 3.APR.2013 05:33:20


Plot on Configuration IEEE 802.11b / Reference Level



Plot on Configuration IEEE 802.11b / CH 1 / 30MHz~2400MHz (down 30dBc)




Plot on Configuration IEEE 802.11b / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 9.APR.2013 15:10:33

Plot on Configuration IEEE 802.11b / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 9.APR.2013 15:11:08

Plot on Configuration IEEE 802.11b / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 9.APR.2013 15:10:54

Plot on Configuration IEEE 802.11g / Reference Level




Date: 9.APR.2013 15:12:42

Plot on Configuration IEEE 802.11g / CH 1 / 30MHz~2400MHz (down 30dBc)




Date: 9.APR.2013 15:13:05

Plot on Configuration IEEE 802.11g / CH 1 / 2500MHz~26500MHz (down 30dBc)




Date: 9.APR.2013 15:13:18

Plot on Configuration IEEE 802.11g / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 9.APR.2013 15:13:51

Plot on Configuration IEEE 802.11g / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 9.APR.2013 15:13:38


Plot on Configuration IEEE 802.11a / Reference Level



Plot on Configuration IEEE 802.11a / CH 149 / 30MHz~5725MHz (down 30dBc)




Plot on Configuration IEEE 802.11a / CH 149 / 5850MHz~40000MHz (down 30dBc)




Date: 3.APR.2013 05:18:17

Plot on Configuration IEEE 802.11a / CH 165 / 30MHz~5725MHz (down 30dBc)



Date: 3.APR.2013 05:23:27

Plot on Configuration IEEE 802.11a / CH 165 / 5850MHz~40000MHz (down 30dBc)



Date: 3.APR.2013 05:24:05

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Oct. 23, 2012	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov.26, 2012	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9kHz ~ 30MHz	Jun. 22, 2012	Conduction (CO01-CB)
PULSE LIMITER	R&S	ESH3-Z2	100430	9K~30MHz	Feb. 21, 2013	Conduction (CO01-CB)
Impulsbegrenzer Pulse Limiter	Rohde&Schwarz	ESH3-Z2	100430	9kHz~30MHz	Feb. 21, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	0.15MHz~30MHz	Dec. 4, 2012	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	-	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Jan. 11, 2013	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 31, 2012	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100056	9KHz~40GHz	Nov. 16, 2012	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 20, 2013	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz ~ 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz ~ 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9KHz~40GHz	Oct. 08, 2012	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 05, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	3 Way	MDC2366	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	4 Way	0120A04056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz ~ 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz ~ 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz ~ 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Nov. 28, 2012	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Nov. 27, 2012	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

“*” Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085