

SYSTEM DESCRIPTION, INSTALLATION, AND MAINTENANCE MANUAL

MCS-4200/7200 Multi-Channel SATCOM System

power-on counter, 6-77, 6-83
power-on self-test, 2-9, 5-57, 6-4, 6-5, 6-6, 6-9, 6-29, 6-35
priority 4 calls, 5-66
private automatic branch exchange, 3-1
Psid-channel frequencies, 2-2, 2-6
Psmc-channel, 2-1, 2-4, 2-5
 frequency, 2-2, 2-3, 2-6
PSU. See power supply unit
push to test, 1-30
push-to-talk, 1-10, 3-14, 6-6

R

radio frequency module, 6-6
radio frequency unit, 1-9
radio frequency unit interface adapter, 1-9
 ARINC 600 connector requirements, 5-3
radio management panel, 1-4
Rd-channel, 2-4, 2-5
real-time clock, 6-19
return ID, 1-24
RF channels
 C-channel, 2-4, 2-7, 2-13, 2-15, 2-16
 P-channel, 2-1, 2-2, 2-3, 2-4, 2-6, 2-7
 R-channel, 2-3, 2-4, 2-5
 T-channel, 2-4, 2-5
RF loop back test, 6-6
RFM. See radio frequency module
Rsmc-channel, 2-4, 2-5
RTC. See real-time clock

S

SATCOM control and display unit, 1-11, 2-6, 2-17, 2-19, 2-27, 3-14, 5-65, 5-67, 5-69, 6-6, 6-7, 6-8, 6-10, 6-17, 6-20, 6-22, 6-87, 6-88
 display, 6-20, 6-21
 page, 2-11
 displays for dual systems, 6-110
 hierarchy, 6-25, 6-29
pages, 6-10, 6-20, 6-24, 6-89
 configuration data, 6-27, 6-38, 6-39, 6-40, 6-41, 6-42, 6-43, 6-44, 6-45, 6-46, 6-47, 6-48, 6-49, 6-50, 6-51, 6-52, 6-54, 6-55, 6-56, 6-57, 6-59
 data loader, 6-60, 6-61, 6-62, 6-63, 6-64, 6-65, 6-66
 ground report, 6-27, 6-79, 6-80
 ground report troubleshooting data, 6-27, 6-81, 6-82
 last leg class 3 faults, 6-27, 6-77, 6-79
 last leg report, 6-27, 6-66, 6-67
 LRU identification, 6-27, 6-71, 6-73, 6-74
 previous legs report, 6-27, 6-68, 6-69, 6-70, 6-71

SATCOM main menu, 6-24, 6-26, 6-29, 6-110
SATCOM maintenance, 6-27, 6-29, 6-59, 6-66, 6-110
SATCOM self-test, 6-35, 6-36, 6-37, 6-38
SATCOM submenu, 6-27, 6-28, 6-66
test, 6-27, 6-29, 6-30, 6-31, 6-32
troubleshooting data, 6-27, 6-75, 6-76
SATCOM main menu page, 3-15
satellite data unit, 1-16, 2-5, 2-6, 2-7, 2-10, 2-11, 2-12, 2-13, 2-16, 2-17, 2-18, 3-1, 3-2, 3-5, 3-9, 3-12, 3-15, 5-57, 5-58, 5-59, 5-60, 5-61, 5-63, 5-65, 5-66, 5-67, 5-69, 6-1, 6-3, 6-5, 6-6, 6-7, 6-8, 6-9, 6-18, 6-19, 6-20, 6-22, 6-66, 6-72, 6-84, 6-85, 6-87, 6-88, 6-89, 6-110, A-4, A-10, B-1, B-4, B-8, C-1
 ARINC 600 connector requirements, 5-3
 codec, 2-15, 2-27, 3-1, 3-14, 5-68
 configuration pin, 5-64
 cooling requirements, 4-3
 failure reporting, 6-10
 front panel
 connector, 5-1
 indicators and controls, 6-10
 light emitting diodes, 6-11
 installation dependent considerations, 4-2
 master, 2-16, 2-17, 2-18, 2-19
 mechanical installation data, 4-1
 modem, 3-5
 number, 5-64
 rear connector, 5-1
 slave, 2-16, 2-17, 2-18, 2-19
 software upload, 2-9
 software/database updates, 2-8
 to WH-10 handset actions, 3-5
 voice codec, 3-5, 3-6
scratchpad, 6-20, 6-21, 6-23, 6-65, 6-88
SDI. See source destination identifier
secure voice, coding unit, 2-15
shop replaceable unit, 6-3, 6-75, 6-77, 6-81
sign/status matrix, 5-57, 6-4, 6-5, 6-6, 6-9, 6-84, 6-87, A-19, A-21, A-22
signal conditioning unit, A-4, A-9, A-16, A-17, A-18, A-19, A-21, A-22
 automatic input selection, A-19
 built-in test, A-17, A-19
 control functions, A-18
 front panel, A-17
 light emitting diode, A-17, A-19
 manual signal selection, A-18
single channel per carrier, 1-12
SMT, surface mount technology, 1-25
software, upload, 2-8, 2-9
 validation, 2-9
source destination identifier, 5-61, 5-64, 6-16, 6-84
space segment, 1-2
spot beam, 2-1, 2-2, 2-4, 2-5, 2-6
 handover, 2-6

SYSTEM DESCRIPTION, INSTALLATION, AND MAINTENANCE MANUAL

MCS-4200/7200 Multi-Channel SATCOM System

satellite, 2-1
search table, 2-3
SRU, shop replaceable unit, 1-25
SSM. See sign/status matrix
standard ground test, 6-87
strap parity, 5-60
swift channel module, 1-23
system address label, 2-9
system table, 2-2, 2-3, 3-9

T

terminal interface function, 2-15
terrestrial data and voice, 1-2
time division multiple access, 1-12
time division multiplex, 1-12
time since power-on, 6-77, 6-83
total on-time clock, 6-18, 6-19
triple transcoder modem, 1-21

U

UTC. See coordinated universal time

V

VCM. See voice codec module
vendor equipment, 4-4, A-1
voice codec module, 3-14
 audio switching, 3-15
 dedication, 3-17
 sidetone, 3-15
 stored audio messages, 3-15
voltage standing wave ratio, 4-2, A-2

W

weight-on-wheels discrete, 6-7, 6-39

X

XTB. See cross-talk bus