

KDB 447498 D03
47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091

RF EXPOSURE REPORT

For

13.3" LCD w/Wireless Charger Module

Model: DPD1334-STQ-Q01, DPD1334-STQ-QXX (X=0~9)

Trade Name: Litemax

Issued to

Litemax Electronics Inc.
7F-1, No. 135, Lane 235, Baoqiao Rd., Xindian Dist., New Taipei City,
Taiwan 23145

Issued by

Compliance Certification Services Inc.
Wugu Laboratory
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City, Taiwan. (R.O.C.)
Issued Date: September 08, 2020

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	July 29, 2020	Initial Issue	ALL	May Lin
01	August 21, 2020	See the following Note Rev. (01)	P.5, P.8	May Lin
02	September 08, 2020	See the following Note Rev. (02)	P.1, P.5	May Lin

Rev (01):

1. Revised the section 2 · section 6.

Rev (02):

1. Revised the product name.

TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION	4
2. EUT SPECIFICATION	5
3. MEASUREMENT EQUIPMENT USED	6
4. FACILITIES AND TEST LOCATION	6
5. LIMIT	7
6. TEST RESULTS	8
7. PHOTOGRAPHS OF TEST SETUP	9

1. TEST RESULT CERTIFICATION

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
KDB 447498 D03 47 C.F.R. Part 1, Subpart I, Section 1.1310 47 C.F.R. Part 2, Subpart J, Section 2.1091	No non-compliance noted
Statements of Conformity	
Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.	

Approved by:



Kevin Tsai
Deputy Manager
Compliance Certification Services Inc.

2. EUT SPECIFICATION

EUT	13.3" LCD w/Wireless Charger Module
Model	DPD1334-STQ-Q01, DPD1334-STQ-QXX (X=0~9)
Trade Name	Litemax
Model Discrepancy	All the above models are identical except for the designation of model numbers. The suffix of (X=0~9) on model number is just for marketing purpose only.
Frequency band (Operating)	<input checked="" type="checkbox"/> 110kHz~145kHz <input type="checkbox"/> Others
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (E=614 V/m ; H=1.63 A/m)
Antenna Specification	Coil Antenna
Result Power	110kHz~145kHz 92.47 dBuV/m (3m)
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A
Received Date	June 15, 2020
Date of Test	July 21, 2020

3. MEASUREMENT EQUIPMENT USED

Equipment Used for Emissions Measurement

RF Conducted Test Site					
Equipment	Manufacturer	Model	S/N	Cal Date	Cal Due
Field Meter	Wavecontrol	SMP2	19SN1198	08/12/2019	08/11/2021
Probe (1Hz~400kHz)	Wavecontrol	WP400	19WP100597	08/12/2019	08/11/2021
Software			N/A		

Remark: Each piece of equipment is scheduled for calibration once a year.

4. FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)

Test site	Test Engineer	Remark
RF Conducted	Jane Wang	-

Remark: The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5. LIMIT

Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(b), 1.1310.

§1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of the chapter.

TABLE 1 - LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	* 100	6
3.0-30	1842/f	4.89/f	* 900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
<u>0.3-1.34</u>	<u>614</u>	<u>1.63</u>	* 100	30
1.34-30	824/f	2.19/f	* 180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Note 1 to Table 1: Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

Note 2 to Table 2: General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Report No.: T200615W05-MF

6. TEST RESULTS

No non-compliance noted.

Temperature: 24°C

Test Date: July 21, 2020

Humidity: 50% RH

Pressure: 1013 hPa / 760 mmHg

E-Field Strength

Frq. (kHz)	Probe Position S1 (V/m)	Probe Position S2 (V/m)	Probe Position S3 (V/m)	Probe Position S4 (V/m)	Probe Position From (V/m)	Limits (V/m)
Distance	15cm	15cm	15cm	15cm	20cm	
110~145	91.22	80.67	87.72	84.84	91.67	614

H-Field Strength

Frq. (kHz)	Probe Position S1 (A/m)	Probe Position S2 (A/m)	Probe Position S3 (A/m)	Probe Position S4 (A/m)	Probe Position From (A/m)	Limits (A/m)
Distance	15cm	15cm	15cm	15cm	20cm	
110~145	0.19	0.19	0.19	0.19	0.22	1.63

- End of Test Report -