

TEST REPORT – EMC Emissions

Report Number: 100115937DEN-002A
Project Number: 100115937

Report Issue Date: 6/21/2010

Product Designation: Model: AV120

Standards: FCC CFR47 Part 15, Subpart C
FCC Part 15.249
IC RSS-210e Issue 7: 2007
IC RSS-GEN Issue 2: 2007

Tested by:
Intertek Testing Services NA, Inc.
1795 Dogwood Street, Suite 200
Louisville, CO 80027

Emissions Testing Facility
40 Meadow Rd
Pinewood Springs, CO 80540

Client:
Inovonics Wireless Corporation
315 CTC Blvd.
Louisville, CO 80027

Report prepared by

Randy Thompson
Senior EMC Project Engineer

Report reviewed by

Michael Spataro
Engineering Team Leader

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TABLE OF CONTENTS

Section		Page
1	<i>Introduction and Conclusion</i>	4
2	<i>Test Summary</i>	4
3	<i>Description of Equipment Under Test</i>	6
4	<i>System setup including cable interconnection details, support equipment and simplified block diagram</i>	7
5	<i>Radiated Emissions – Intentional: Field Strength of the Fundamental & Harmonics of the Fundamental</i>	9
6	<i>AC Conducted Emissions – Not Applicable (Product Battery Operated)</i>	19
7	<i>Measurement Uncertainty</i>	20
8	<i>Revision History</i>	21

Product Under Test

Model: AV120 (Quasar Belt Pack Transceiver-shown with headset)



1 Introduction and Conclusion

The tests indicated in section 2.0 were performed on the product constructed as described in section 3.0. The remaining test sections are the verbatim text from the actual data sheets used during the investigation. These test sections include the test name, the specified test Method, a list of the actual Test Equipment Used, documentation Photos, Results and raw Data. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted.

Based on the results of our investigation, **we have concluded the product tested complies with the requirements of the standard(s) indicated**. The results obtained in this test report pertain only to the item(s) tested.

2 Test Summary

Section	Test full name	Test date	Result
5	Radiated Emissions – Intentional per FCC Part 15.249(a) (Covers IC RSS-210: Annex 2.9(a))	05/13/10	Pass
6	Conducted Emissions – FCC 15.107, Class B	-----	-----

Notes:

1. Only Intentional Radiated Emissions was tested and listed in this report per client request. Unintentional Radiated Emissions for this product was also tested & passed FCC Part 5.205/209. (Covers ICES-003/ RSS-210 section 2.7, tables 1 and 2 and CISPR 22/ AS/NZS CISPR 22) Please refer to Report Number: 100115937DEN-001.
2. This product is powered via an internal battery – Therefore, Conducted Emissions was not required for this device.

General Remarks for Radio Testing:

The following remarks are to be considered as "where applicable" and are taken into account while completing any FCC/IC/ETSI Radio tests at Intertek-Louisville.

- Testing was performed in 3 different orthogonal axes to determine the worst-case emissions from the device. The worst-case emissions are shown in this report.
- FCC CFR47 Part 15.31: Measurement Standards: In any case where the device is powered off a battery, a fresh battery was used during testing. In cases where the device is powered of an AC Supply, voltage was varied per Part 15.31 to find worst-case emissions.
- FCC CFR Part 15.35: Measurement Detector Functions and Bandwidths: FCC Part 15.35 was utilized when performing measurements within this report.
- The testing performed in accordance to FCC CFR47 Part 15.205 (restricted bands of operation) and Part 15.249 emissions and delta limits were calculated as follows:

Final Corrected Peak Measurement – Duty Cycle Correction Factor* = Final Calculated Emission
The Final Calculated Emission was then compared to the Limits in CFR47 Part 15.209 and Part 15.249 and the emission/limit delta was calculated.

- When applicable, the "Duty Cycle Correction Factor" (DTCF) is calculated as follows: $20 \times \log_{10}$ (duty cycle in 100ms) "not to exceed 20 dB"
- If the antenna is external and detachable, a conducted port power measurement may be taken directly at the antenna port whenever a conducted power limit is specified.
- If the antenna is internal and not detachable, radiated field strength measurements were taken at a calibrated open area test site.
- The following formula may be used to convert field strength (FS) in volts/meter to transmitter power (TP) output power in watts: $TP = (FS \times D)^2 / (30 \times G)$, where D is test distance (EUT-to-antenna) and G is the product's antenna numerical gain referenced to isotropic gain.
- If at the time of testing Intertek was unable to obtain the gain of the product's antenna from the manufacturer, the following calculation may be used to determine field strength limit for a test distance of 3-meters. This calculation assumes ideal isotropic radiation from the source:

$$P = 20 \times \log_{10} (E) - 95.2289$$

Where P is power in dBm, E is uV/m

3 Description of Equipment Under Test

Equipment Under Test			
Description	Manufacturer	Model Number	Serial Number
Quasar Belt Headset Transceiver	Inovonics	AV120	EMC1

Receive Date:	05/12/2010
Received Condition:	Good
Type:	Production Proto

Description of Equipment Under Test (provided by client)

The product is intended to be used in office, commercial and industrial locations, in a dry environment. The primary function of the product is a headset transceiver capable of operating in the frequency range of 902 – 928 MHz. The product has no external RF conducted port and utilizes (2) internal antennas. RF is FM modulation, 16-channels, 1 discrete frequency/channel and can operate in CW mode. The product enclosure is plastic. Product will be marketed in the US and Canada. Note that power for this product is supplied by a 3.7 VDC Battery.


Equipment Under Test Power Configuration			
Rated Voltage	Rated Current	Rated Frequency	Number of Phases
3.7 VDC Battery (AV120)	unknown	-----	-----

Operating modes of the EUT:

No.	Descriptions of EUT Exercising
1	Product Tx enabled at full transmit power, continuous wave (CW) mode.

4 System setup including cable interconnection details, support equipment and simplified block diagram**4.1 Method:**

Record the details of EUT cabling, document the support equipment, and show the interconnections in a block diagram.

4.2 EUT Block Diagram: Model – AV120

4.3 Data:

ID	Cable Description	Length	Shielding	Ferrites
1	None	---	---	---

Support Equipment			
Description	Manufacturer	Model Number	Serial Number
None	---	---	---

General notes:

1. Product has no I/O or signal cables.
2. Product did not require any support equipment.

5 Radiated Emissions – Intentional: Field Strength of the Fundamental & Harmonics of the Fundamental

5.1 Method

The test methods used comply with ANSI C63.4 and CISPR 16. Unless otherwise stated no deviations were made from **FCC CFR47, Part 15C per FCC 15.249**.

Intertek Louisville's emissions testing facility is located at 40 Meadow Rd. in Pinewood Springs CO 80540. The emissions testing facility is ISO17025:2005 accredited by NVLAP, our lab code is 200624-0, BSMI lab number is SL2-IN-E-029R, our VCCI registration no. R-1643, our FCC designation no. US5170 and our IC lab no. 2042N.

5.2 Test Equipment Used:

<u>Asset ID:</u>	<u>Description:</u>	<u>Manufacturer:</u>	<u>Model:</u>	<u>Serial:</u>	<u>Cal Date</u>	<u>Cal Due</u>
18882	Spectrum Analyzer (dc-22 GHz) Spectrum Analyzer Display	Hewlett-Packard	8566B	2410A00154	11/12/2009	11/12/2010
18660	Section (set 1)	Hewlett-Packard	85662A	2318A04983	11/12/2009	11/12/2010
18912	9 kHz- 1.3GHz Pre Amp	Hewlett-Packard	8447F	3113A05545	05/12/2009	06/12/2011
18906	Amplifier (1-4 GHz)	Mini-Circuits Lab	ZHL-42	N052792-2	05/12/2009	06/11/2011
18900	RF Pre-Amplifier (4-8 GHz)	Avantek	AFT97-8434-10F	1007	05/12/2009	06/07/2011
18901	RF Pre-Amplifier (8-18 GHz)	Avantek	AWT-18037	1002	05/12/2009	06/07/2011
18808	Log Periodic Antenna Doubled Ridged Guide Antenna (1-18 GHz)	EMCO	3146	9203-3376	11/05/2009	11/05/2010
18737		EMCO	3105	2076	04/03/2009	06/03/2010

5.3 Results:

The sample tested was found to Comply.

5.4 Setup Photographs:

Radiated Emissions Test setup – Front View



Photo:

Radiated Emissions Test setup – Rear View



Photo:

Test setup – Axis 1 (EUT Flat on Table)




Photo:

Test setup – Axis 2 (EUT Vertical)



Photo:

Test setup – Axis 3 (EUT Vertical & Rotated 90 Degrees)

**Note: Axis 3 was determined to be worst-case**

5.5 Test Data Summary: Radiated Unintentional and Spurious Emissions: CISPR 22/ICES-003/ AS/NZS CISPR 22

Test Result: Not Applicable to this test report

Minimum limit margin ----- dB at ----- MHz

Remarks: Covers FCC 15.249 (d)/ 15.209

Note: Unintentional Radiated Emissions was previously tested and passed. Refer to Report 100115937DEN-001 for details.

5.6 Test Data Summary: Field Strength of the Fundamental: FCC 15.249 (a)

Test Result: Pass

Minimum limit margin – Low Channel - 0.3 dB at 902.39 MHz

Remarks: Covers RSS-210, Annex 2.9 (a)

5.7 Test Data Summary: Field Strength of the Harmonics of Fundamental: FCC 15.249 (a) / 15.205

Test Result: Pass

Minimum limit margin – High Channel - 13.0 dB at 2720.14 MHz

Remarks: Covers RSS-210, Annex 2.9 (a)

Field Strength Measurements

Fundamental and Harmonics of the Fundamental

Test Report #:	100115937 Run 02	Test Area:	Pinewood Site 1 (3m)	Temperature:	26.4	°C
Test Method:	FCC 15.249/ IC RSS-210	Test Date:	13-May-2010	Relative Humidity:	23.9	%
EUT Model #:	AV120	EUT Power:	3.7VDC Battery	Air Pressure:	79.8	kPa
EUT Serial #:						

Manufacturer:	Inovonics	Level Key
EUT Description:	Quasar Belt Pack	Pk – Peak Nb – Narrow Band
Notes:	Quasar Drive-Thru Window Headset Transceiver	Qp – QuasiPeak Bb – Broad Band
Product tested was configured to transmit between 902.4 to 906.72 MHz only.		Av - Average

FREQ	LEVEL	CABLE / ANT / PREAMP	FINAL	POL / HGT / AZ	Duty Cycle Correction	Final Corrected	FCC/ IC Limit	DELTA
(MHz)	(dBuV)	(dB) (dB\m) (dB)	(dBuV)	(m) (DEG)	(dB)	(dBuV/m)	(dBuV/m)	(dB)

The following Duty Cycle was declared by the manufacturer: 100 %

Averaging method for pulsed signals and calculation in accordance to FCC CFR47 Part 15.35 utilized to calculate field strength emissions.

The testing performed in accordance to FCC CFR47 Part 15.205 (restricted bands of operation) and 15.249 emissions and delta limits were calculated as follows:

Final Corrected Peak Measurement – Duty Cycle Correction Factor* = Final Calculated Emission

The Final Calculated Emission was then compared to the Limits in CFR47 Part 15.209 and 15.249 and the emission/limit delta was calculated.

Duty Cycle Correction Factor (DTCF) is calculated as follows $20 \cdot \log_{10}(\text{duty cycle in 100mS})$ "not to exceed 20dB"

Part 15.249 and 15.209 Respectively

Fundamental Measurements

Low Channel Axis 1 - EUT is Flat on the table.

902.39	60.7 Pk	3.6 / 22.5 / 0.0	86.8	V / 1.2 / 160.0	0.0	86.8	94.0	-7.2
902.39	63.2 Pk	3.6 / 22.5 / 0.0	89.3	H / 1.5 / 350.0	0.0	89.3	94.0	-4.7

Axis 2 - EUT is Vertical on the table.

902.39	62.0 Pk	3.6 / 22.5 / 0.0	88.1	H / 1.3 / 182.0	0.0	88.1	94.0	-5.9
902.39	61.4 Pk	3.6 / 22.5 / 0.0	87.5	V / 1.1 / 316.0	0.0	87.5	94.0	-6.5

Axis 3 - EUT is Vertical on the table & Rotated 90 Deg.

902.39	67.6 Pk	3.6 / 22.5 / 0.0	93.7	V / 1.1 / 190.0	0.0	93.7	94.0	-0.3
902.39	56.4 Pk	3.6 / 22.5 / 0.0	82.5	H / 1.7 / 354.0	0.0	82.5	94.0	-11.5

Mid Channel Axis 1

905.03	63.5 Pk	3.6 / 22.5 / 0.0	89.7	H / 1.5 / 350.0	0.0	89.7	94.0	-4.3
905.03	60.9 Pk	3.6 / 22.5 / 0.0	87	V / 1.1 / 160.0	0.0	87.0	94.0	-7.0

Axis 2

905.03	61.8 Pk	3.6 / 22.5 / 0.0	87.9	V / 1.2 / 270.0	0.0	87.9	94.0	-6.1
905.03	62.1 Pk	3.6 / 22.5 / 0.0	88.2	H / 1.4 / 10.0	0.0	88.2	94.0	-5.8

Axis 3

905.03	55.1 Pk	3.6 / 22.5 / 0.0	81.3	H / 1.7 / 354.0	0.0	81.3	94.0	-12.7
905.03	67.3 Pk	3.6 / 22.5 / 0.0	93.5	V / 1.1 / 245.0	0.0	93.5	94.0	-0.5

Intertek

Report Number: 100115937DEN-002A

Issued: 6/21/2010

FREQ (MHz)	LEVEL (dBuV)	CABLE / ANT / PREAMP (dB)	FINAL (dBuV)	POL / HGT / AZ (m) (DEG)	Duty Cycle Correction (dB)	Final Corrected (dBuV/m)	FCC/ IC Limit (dBuV/m)	DELTA (dB)
High Channel Axis 1								
906.7	59.0 Pk	3.6 / 22.5 / 0.0	85.2	V / 1.2 / 280.0	0.0	85.2	94.0	-8.8
906.7	63.7 Pk	3.6 / 22.5 / 0.0	89.8	H / 1.5 / 5.0	0.0	89.8	94.0	-4.2
Axis 2								
906.7	62.2 Pk	3.6 / 22.5 / 0.0	88.3	H / 1.4 / 354.0	0.0	88.3	94.0	-5.7
906.7	60.8 Pk	3.6 / 22.5 / 0.0	86.9	V / 1.1 / 346.0	0.0	86.9	94.0	-7.1
Axis 3								
906.7	67.3 Pk	3.6 / 22.5 / 0.0	93.4	V / 1.1 / 212.0	0.0	93.4	94.0	-0.6
906.7	59.8 Pk	3.6 / 22.5 / 0.0	85.9	H / 1.4 / 168.0	0.0	85.9	94.0	-8.1
Axis 3 was determined to be the worst case axis								
All Harmonics will be measured in Axis 3								
Harmonics - Low Channel								
1804.78	45.1 Pk	2.8 / 26.0 / 35.7	38.1	V / 2.1 / 5.0	0.0	38.1	54.0	-15.9
1804.78	44.8 Pk	2.8 / 26.0 / 35.7	37.8	H / 1.8 / 24.0	0.0	37.8	54.0	-16.2
2707.17	41.4 Qp	3.5 / 28.2 / 36.7	36.3	V / 1.2 / 356.0	0.0	36.3	54.0	-17.7
2707.17	45.6 Pk	3.5 / 28.2 / 36.7	40.5	H / 1.0 / 12.0	0.0	40.5	54.0	-13.5
3609.56	37.9 Pk	4.5 / 30.9 / 37.3	35.9	V / 1.2 / 356.0	0.0	35.9	54.0	-18.1
3609.56	39.5 Pk	4.5 / 30.9 / 37.3	37.5	H / 1.5 / 356.0	0.0	37.5	54.0	-16.5
4511.97	37.5 Pk	5.3 / 32.2 / 39.8	35.1	H / 1.5 / 356.0	0.0	35.1	54.0	-18.9
4511.97	36.9 Pk	5.3 / 32.2 / 39.8	34.5	V / 1.4 / 12.0	0.0	34.5	54.0	-19.5
5414.36	34.6 Pk	6.0 / 32.8 / 39.3	34.1	H / 1.5 / 12.0	0.0	34.1	54.0	-19.9
5414.36	27.8 Pk	6.0 / 32.8 / 39.3	27.3	V / 1.3 / 12.0	0.0	27.3	54.0	-26.7
6316.75	32.2 Pk	6.6 / 33.8 / 39.5	33.1	H / 1.3 / 12.0	0.0	33.1	54.0	-20.9
6316.75	31.6 Pk	6.6 / 33.8 / 39.5	32.5	V / 1.3 / 12.0	0.0	32.5	54.0	-21.5
7219.14	32.1 Pk	7.3 / 35.2 / 39.9	34.7	H / 1.3 / 12.0	0.0	34.7	54.0	-19.3
7219.14	33.8 Pk	7.3 / 35.2 / 39.9	36.4	V / 1.3 / 12.0	0.0	36.4	54.0	-17.6
8121.51	43.4 Pk	7.7 / 36.2 / 46.3	40	V / 1.6 / 10.0	0.0	40.0	54.0	-14.0
8121.51	44.1 Qp	7.7 / 36.2 / 46.3	40.7	H / 1.6 / 10.0	0.0	40.7	54.0	-13.3
9023.9	40.0 Qp	8.4 / 36.8 / 47.5	37.6	V / 1.6 / 10.0	0.0	37.6	54.0	-16.4
9023.9	43.4 Qp	8.4 / 36.8 / 47.5	40.1	H / 1.6 / 10.0	0.0	40.1	54.0	-13.9
Harmonics - Mid Channel								
1810.06	43.5 Pk	2.8 / 26.0 / 35.7	36.5	H / 1.6 / 12.0	0.0	36.5	54.0	-17.5
1810.06	44.7 Pk	2.8 / 26.0 / 35.7	37.7	V / 1.8 / 12.0	0.0	37.7	54.0	-16.3
2715.09	43.4 Pk	3.5 / 28.2 / 36.7	38.3	H / 1.6 / 12.0	0.0	38.3	54.0	-15.7
2715.09	43.1 Pk	3.5 / 28.2 / 36.7	38	V / 1.3 / 354.0	0.0	38.0	54.0	-16.0
3620.12	38.8 Pk	4.5 / 30.9 / 37.4	36.9	H / 1.4 / 348.0	0.0	36.9	54.0	-17.1
3620.12	38.1 Pk	4.5 / 30.9 / 37.4	36.2	V / 1.3 / 354.0	0.0	36.2	54.0	-17.8
4525.18	38.0 Pk	5.3 / 32.1 / 39.8	35.6	V / 1.5 / 23.0	0.0	35.6	54.0	-18.4
4525.18	39.5 Pk	5.3 / 32.1 / 39.8	37.2	H / 1.7 / 23.0	0.0	37.2	54.0	-16.8
5430.21	33.3 Pk	6.1 / 32.8 / 39.3	32.9	V / 1.5 / 23.0	0.0	32.9	54.0	-21.1
5430.21	30.6 Pk	6.1 / 32.8 / 39.3	30.1	H / 1.5 / 23.0	0.0	30.1	54.0	-23.9
6335.24	30.1 Pk	6.6 / 33.8 / 39.5	31	V / 1.5 / 23.0	0.0	31.0	54.0	-23.0

Intertek

Report Number: 100115937DEN-002A

Issued: 6/21/2010

FREQ (MHz)	LEVEL (dBuV)	CABLE / ANT / PREAMP (dB)	FINAL (dBuV)	POL / HGT / AZ (m) (DEG)	Duty Cycle Correction (dB)	Final Corrected (dBuV/m)	FCC/ IC Limit (dBuV/m)	DELTA (dB)
6335.24	29.9 Pk	6.6 / 33.8 / 39.5	30.9	H / 1.5 / 23.0	0.0	30.9	54.0	-23.1
7240.27	28.4 Pk	7.3 / 35.2 / 39.8	31	V / 1.5 / 23.0	0.0	31.0	54.0	-23.0
7240.27	29.7 Pk	7.3 / 35.2 / 39.8	32.4	H / 1.5 / 23.0	0.0	32.4	54.0	-21.6
8145.3	42.0 Pk	7.8 / 36.2 / 46.3	39.6	H / 1.6 / 10.0	0.0	39.6	54.0	-14.4
8145.3	43.1 Pk	7.8 / 36.2 / 46.3	40.8	V / 1.6 / 10.0	0.0	40.8	54.0	-13.2
9050.33	45.0 Pk	8.4 / 36.8 / 47.6	40.6	H / 1.6 / 10.0	0.0	40.6	54.0	-13.4
9050.33	44.5 Pk	8.4 / 36.8 / 47.6	40.1	V / 1.6 / 10.0	0.0	40.1	54.0	-13.9
Harmonics - High Channel								
1813.4	45.1 Pk	2.8 / 26.0 / 35.7	38.2	V / 1.8 / 5.0	0.0	38.2	54.0	-15.8
1813.42	44.5 Pk	2.8 / 26.0 / 35.7	37.5	H / 1.6 / 24.0	0.0	37.5	54.0	-16.5
2720.14	44.9 Pk	3.5 / 28.2 / 36.7	39.8	V / 1.3 / 349.0	0.0	39.8	54.0	-14.2
2720.14	46.0 Pk	3.5 / 28.2 / 36.7	41	H / 1.8 / 8.0	0.0	41.0	54.0	-13.0
3626.87	38.6 Pk	4.5 / 30.9 / 37.4	36.7	V / 1.4 / 349.0	0.0	36.7	54.0	-17.3
3626.87	38.2 Pk	4.5 / 30.9 / 37.4	36.2	H / 1.6 / 10.0	0.0	36.2	54.0	-17.8
4533.57	38.4 Pk	5.3 / 32.1 / 39.7	36.1	H / 1.7 / 354.0	0.0	36.1	54.0	-17.9
4533.57	38.3 Pk	5.3 / 32.1 / 39.7	36	V / 1.6 / 10.0	0.0	36.0	54.0	-18.0
5440.27	31.2 Pk	6.1 / 32.8 / 39.3	30.8	H / 1.7 / 354.0	0.0	30.8	54.0	-23.2
5440.27	30.1 Pk	6.1 / 32.8 / 39.3	29.7	V / 1.7 / 354.0	0.0	29.7	54.0	-24.3
6346.97	32.6 Pk	6.6 / 33.8 / 39.5	33.6	H / 1.7 / 354.0	0.0	33.6	54.0	-20.4
6346.97	31.9 Pk	6.6 / 33.8 / 39.5	32.9	V / 1.7 / 354.0	0.0	32.9	54.0	-21.1
7253.67	31.6 Pk	7.3 / 35.2 / 39.8	34.3	H / 1.7 / 354.0	0.0	34.3	54.0	-19.7
7253.67	30.1 Pk	7.3 / 35.2 / 39.8	32.8	V / 1.7 / 354.0	0.0	32.8	54.0	-21.2
8160.34	45.1 Pk	7.8 / 36.2 / 46.3	40.8	V / 1.6 / 10.0	0.0	40.8	54.0	-13.2
8160.34	46.1 Pk	7.8 / 36.2 / 46.3	40.8	H / 1.6 / 10.0	0.0	40.8	54.0	-13.2
9067.04	42.9 Pk	8.4 / 36.8 / 47.6	40.5	V / 1.6 / 10.0	0.0	40.5	54.0	-13.5
9067.04	43.4 Pk	8.4 / 36.8 / 47.6	40.1	H / 1.6 / 10.0	0.0	40.1	54.0	-13.9

Example calculation:

Measured Level (dB μ V)	+	Transducer, Cable Loss & Amplifier corrections (dB)	=	Corrected Reading (dB μ V/m)	Specification Limit (dB μ V/m)	-	Corrected Reading (dB μ V/m)	=	Delta Specification (-11.1)
			=						
14.0		14.9		28.9	40.0		28.9		-11.1

Deviations, Additions, or Exclusions: None

6 AC Conducted Emissions – Not Applicable (Product Battery Operated)

6.1 Method

The test methods used comply with ANSI C63.4 and CISPR 16. Unless otherwise stated no deviations were made from **FCC Part 107, Class B**.

Intertek Louisville's emissions testing facility is located at 40 Meadow Rd. in Pinewood Springs CO 80540. The emissions testing facility is ISO17025:2005 accredited by NVLAP, our lab code is 200624-0, BSMI lab number is SL2-IN-E-029R, our VCCI registration no. R-1643, our FCC designation no. US5170 and our IC lab no. 2042N.

6.2 Test Equipment Used:

6.3 Results:

6.4 Test Setup Photographs:

6.5 Test Data:

Example calculation:

Measured Level	+	Transducer, Cable Loss & Amplifier corrections	=	Corrected Reading	Specification Limit	-	Corrected Reading	=	Delta Specification
(dB μ V)		(dB)		(dB μ V/m)	(dB μ V/m)		(dB μ V/m)		
14.0		14.9		28.9	40.0		28.9		-11.1

Deviations, Additions, or Exclusions:

7 Measurement Uncertainty

The measured value related to the corresponding limit will be used to decide whether the equipment meets the requirements.

The measurement uncertainty figures were calculated and correspond to a coverage factor of $k = 2$, providing a confidence level of respectively 95.45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian).

Measurement uncertainty Table

Parameter	Uncertainty \pm	Notes
Radiated emissions, 10kHz to 1000 MHz	4.8 dB	
Radiated emissions, 1 to 18 GHz	4.9 dB	
AC mains Conducted emissions, 150kHz to 30 MHz	3.14 dB	
Disturbance Power 30 to 1000 MHz	3.3 dB	
Telecom Port Conducted emissions, Voltage 150 kHz to 30 MHz	TBD	In Process
Harmonics	-	Meets the requirements specified by the standard.
Flicker	-	Meets the requirements specified by the standard.

8 Revision History

Revision Level	Date	Report Number	Notes
0	TBD	100115937DEN-002A	Original Issue