

FCC Test Report

(PART 24)

Report No.: RF151221C01-2

FCC ID: HFS-QTAFN5

Test Model: QTAFN5

Received Date: Dec. 21, 2015

Test Date: Dec. 26, 2015 ~ Jan. 14, 2016

Issued Date: Jan. 19, 2016

Applicant: Quanta Computer Inc.

Address: No. 188, Wen Hwa 2nd RD., Guishan District, Taoyuan City, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
(R.O.C)

Test Location (1): No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan
Hsien 333, Taiwan, R.O.C.

Test Location (2): No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan,
R.O.C



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results.....	5
2.1 Measurement Uncertainty.....	5
2.2 Test Site And Instruments	6
3 General Information	8
3.1 General Description of EUT	8
3.2 Configuration of System under Test.....	9
3.2.1 Description of Support Units	10
3.3 Test Mode Applicability and Tested Channel Detail	10
3.4 EUT Operating Conditions	13
3.5 General Description of Applied Standards.....	13
4 Test Types and Results	14
4.1 Output Power Measurement.....	14
4.1.1 Limits of Output Power Measurement	14
4.1.2 Test Procedures.....	14
4.1.3 Test Setup.....	15
4.1.4 Test Results	16
4.2 Frequency Stability Measurement	24
4.2.1 Limits of Frequency Stability Measurement.....	24
4.2.2 Test Procedure	24
4.2.3 Test Setup.....	24
4.2.4 Test Results	25
4.3 Occupied Bandwidth Measurement.....	26
4.3.1 Test Procedure	26
4.3.2 Test Setup.....	26
4.3.3 Test Result	27
4.4 Band Edge Measurement	31
4.4.1 Limits of Band Edge Measurement	31
4.4.2 Test Setup.....	31
4.4.3 Test Procedures.....	31
4.4.4 Test Results	32
4.5 Peak to Average Ratio	39
4.5.1 Limits of Peak to Average Ratio Measurement	39
4.5.2 Test Setup.....	39
4.5.3 Test Procedures.....	39
4.5.4 Test Results	40
4.6 Conducted Spurious Emissions.....	44
4.6.1 Limits of Conducted Spurious Emissions Measurement.....	44
4.6.2 Test Setup.....	44
4.6.3 Test Procedure	44
4.6.4 Test Results	45
4.7 Radiated Emission Measurement.....	47
4.7.1 Limits of Radiated Emission Measurement	47
4.7.2 Test Procedure	47
4.7.3 Deviation from Test Standard	47
4.7.4 Test Setup.....	47
4.7.5 Test Results	48
5 Pictures of Test Arrangements.....	56
Appendix – Information on the Testing Laboratories	57



A D T

Release Control Record

Issue No.	Description	Date Issued
RF151221C01-2	Original Release	Jan. 19, 2016

1 Certificate of Conformity

Product: FN5

Test Model: QTAFN5

Sample Status: Identical Prototype

Applicant: Quanta Computer Inc.

Test Date: Dec. 26, 2015 ~ Jan. 14, 2016

Standards: FCC Part 24, Subpart E

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Gina Liu , **Date:** Jan. 19, 2016

Gina Liu / Specialist

Approved by : Stanley Wu , **Date:** Jan. 19, 2016

Stanley Wu / Assistant Manager

2 Summary of Test Results

Applied Standard: FCC Part 24 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 24.232	Effective Isotropic Radiated Power	Pass	Meet the requirement of limit.
2.1046 24.232(d)	Peak to Average Ratio	Pass	Meet the requirement of limit.
2.1055 24.235	Frequency Stability	Pass	Meet the requirement of limit.
2.1049 24.238(b)	Occupied Bandwidth	Pass	Meet the requirement of limit.
24.238(b)	Band Edge Measurements	Pass	Meet the requirement of limit.
2.1051 24.238	Conducted Spurious Emissions	Pass	Meet the requirement of limit.
2.1053 24.238	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -1.85 dB at 3760 MHz.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ($\pm$)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.44 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.0153 dB
	200 MHz ~1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
	18 GHz ~ 40 GHz	1.1508 dB

2.2 Test Site And Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9038A	MY52260177	May 19, 2015	May 18, 2016
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 17, 2015	Dec. 16, 2016
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Feb. 04, 2015	Feb. 03, 2016
BILOG Antenna SCHWARZBECK	VULB 9168	9168-153	Feb. 04, 2015	Feb. 03, 2016
HORN Antenna ETS-Lindgren	3117	00143293	Feb. 05, 2015	Feb. 04, 2016
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Feb. 09, 2015	Feb. 09, 2016
Bluetooth Tester	CBT	100980	Apr. 27, 2015	Apr. 26, 2017
Loop Antenna	EM-6879	269	Jul. 31, 2015	Jul. 30, 2016
Agilent Communications Tester-Wireless	8960 Series 10	MY53201073	Jul. 03, 2015	Jul. 02, 2017
Preamplifier Agilent	310N	187226	Jun. 29, 2015	Jun. 28, 2016
Preamplifier Agilent	83017A	MY39501357	Jun. 29, 2015	Jun. 28, 2016
Power Meter Anritsu	ML2495A	1232002	Sep. 21, 2015	Sep. 20, 2016
Power Sensor Anritsu	MA2411B	1207325	Sep. 21, 2015	Sep. 20, 2016
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(R FC-SMS-100-SM S-120+RFC-SMS -100-SMS-400)	Jun. 27, 2015	Jun. 26, 2016
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(R FC-SMS-100-SM S-24)	Jun. 27, 2015	Jun. 26, 2016
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Communications Tester-Wireless Agilent	8960 Series 10	MY53201073	Jul. 03, 2015	Jul. 02, 2017
Radio Communication Analyzer Anritsu	MT8820C	6201240432	Jul. 06, 2015	Jul. 05, 2017
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA

- Note:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HsinTien Chamber 1.
 3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1 GHz if tested.
 4. The FCC Site Registration No. is 149147.
 5. The IC Site Registration No. is IC7450I-1.

3 General Information

3.1 General Description of EUT

Product	FN5	
Test Model	QTAFN5	
Status of EUT	Identical Prototype	
Power Supply Rating	5Vdc or 12Vdc (adapter) 3.8 Vdc (Li-ion battery)	
Modulation Type	GSM/GPRS	GMSK
	EDGE	GMSK, 8PSK
	WCDMA	BPSK
	LTE	QPSK, 16QAM
Frequency Range	GSM/GPRS/EDGE	1850.2 ~ 1909.8 MHz
	WCDMA	1852.4 ~ 1907.6 MHz
	LTE Band 2 (Channel Bandwidth: 1.4 MHz)	1850.7 ~ 1909.3 MHz
	LTE Band 2 (Channel Bandwidth: 3 MHz)	1851.5 ~ 1908.5 MHz
	LTE Band 2 (Channel Bandwidth: 5 MHz)	1852.5 ~ 1907.5 MHz
	LTE Band 2 (Channel Bandwidth: 10 MHz)	1855.0 ~ 1905.0 MHz
	LTE Band 2 (Channel Bandwidth: 15 MHz)	1857.5 ~ 1902.5 MHz
	LTE Band 2 (Channel Bandwidth: 20 MHz)	1860.0 ~ 1900.0 MHz
Max. EIRP Power	GSM/GPRS	857.04 mW
	EDGE	390.84 mW
	WCDMA	156.68 mW
	LTE Band 2 (Channel Bandwidth: 1.4 MHz)	235.67 mW
	LTE Band 2 (Channel Bandwidth: 3 MHz)	239.88 mW
	LTE Band 2 (Channel Bandwidth: 5 MHz)	232.27 mW
	LTE Band 2 (Channel Bandwidth: 10 MHz)	214.93 mW
	LTE Band 2 (Channel Bandwidth: 15 MHz)	248.89 mW
	LTE Band 2 (Channel Bandwidth: 20 MHz)	239.33 mW
Emission Designator	GSM/GPRS	247KGXW
	EDGE	246KG7W
	WCDMA	4M08F9W
	LTE Band 2 (Channel Bandwidth: 1.4 MHz)	1M09G7D
	LTE Band 2 (Channel Bandwidth: 3 MHz)	2M69G7D
	LTE Band 2 (Channel Bandwidth: 5 MHz)	4M49G7D
	LTE Band 2 (Channel Bandwidth: 10 MHz)	8M98G7D
	LTE Band 2 (Channel Bandwidth: 15 MHz)	13M4G7D
	LTE Band 2 (Channel Bandwidth: 20 MHz)	17M9G7D
Antenna Type	Fixed Internal Antenna	
Accessory Device	Refer to Note as below	
Data Cable Supplied	Refer to Note as below	

Note:



1. The EUT contains following accessory devices.

Product	Brand	Model	Description
Adapter	Chicony	W15-018N2A	I/P: 100-240Vac, 50-60Hz, 0.6A O/P: 5Vdc, 3A or 12Vdc, 1.5A 1.8m shielded cable w/o core
Battery	McNair	MLP446164	3.8Vdc, 2650mAh
LTE Chip	INTEL	PMB 5746	--
WLAN Chip	INTEL	WCS8170	--



2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Configuration of System under Test

<Radiated Emission Test>



<E.I.R.P. Test>



3.2.1 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1.	Earphone	N/A	N/A	N/A	N/A
2.	Communications Tester-Wireless	Agilent	8960 Series 10	MY53201073	N/A
3.	Radio Communication Analyzer	Anritsu	MT8820C	6201240432	N/A

No.	Signal Cable Description Of The Above Support Units
1.	N/A
2.	N/A
3.	N/A

Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Items 2-3 acted as communication partners to transfer data.

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports.

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

Band	EIRP	Radiated Emission
GSM	Z-plane	Y-axis
EDGE	Z-plane	Y-axis
WCDMA	Z-plane	Y-axis
LTE Band 2	Z-plane	Z-axis

GSM

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
-	EIRP	512 to 810	512, 661, 810	GSM, EDGE
-	Frequency Stability	512 to 810	661	GSM, EDGE
-	Occupied Bandwidth	512 to 810	512, 661, 810	GSM, EDGE
-	Band Edge	512 to 810	512, 810	GSM, EDGE
-	Peak to Average Ratio	512 to 810	512, 661, 810	GSM, EDGE
-	Conducuted Emission	512 to 810	661	GSM, EDGE
-	Radiated Emission	512 to 810	661	GSM, EDGE

WCDMA

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
-	EIRP	9262 to 9538	9262, 9400, 9538	WCDMA
-	Frequency Stability	9262 to 9538	9400	WCDMA
-	Occupied Bandwidth	9262 to 9538	9262, 9400, 9538	WCDMA
-	Band Edge	9262 to 9538	9262, 9538	WCDMA
-	Peak to Average Ratio	9262 to 9538	9262, 9400, 9538	WCDMA
-	Conducuted Emission	9262 to 9538	9400	WCDMA
-	Radiated Emission	9262 to 9538	9400	WCDMA

LTE Band 2

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	EIRP	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Frequency Stability	18607 to 19193	18900	1.4 MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18900	3 MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18900	5 MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18900	10 MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18900	15 MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18900	20 MHz	QPSK	1 RB / 0 RB Offset
-	Occupied Bandwidth	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3 MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10 MHz	QPSK, 16QAM	50 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15 MHz	QPSK, 16QAM	75 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK, 16QAM	100 RB / 0 RB Offset
-	Peak to Average Ratio	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK, 16QAM	1 RB / 0 RB Offset
-	Band Edge	18607 to 19193	18607	1.4 MHz	QPSK	1 RB / 0 RB Offset
						6 RB / 0 RB Offset
			19193	1.4 MHz	QPSK	1 RB / 5 RB Offset
						6 RB / 0 RB Offset
		18615 to 19185	18615	3 MHz	QPSK	1 RB / 0 RB Offset
						15 RB / 0 RB Offset
			19185	3 MHz	QPSK	1 RB / 14 RB Offset
						15 RB / 0 RB Offset
		18625 to 19175	18625	5 MHz	QPSK	1 RB / 0 RB Offset
						25 RB / 0 RB Offset

			19175	5 MHz	QPSK	1 RB / 24 RB Offset		
						25 RB / 0 RB Offset		
		18650 to 19150	18650	10 MHz	QPSK	1 RB / 0 RB Offset		
						50 RB / 0 RB Offset		
		18675 to 19125	19150	10 MHz	QPSK	1 RB / 49 RB Offset		
						50 RB / 0 RB Offset		
			18675	15 MHz	QPSK	1 RB / 0 RB Offset		
						75 RB / 0 RB Offset		
		18700 to 19100	19125	15 MHz	QPSK	1 RB / 74 RB Offset		
						75 RB / 0 RB Offset		
18700	20 MHz		QPSK	1 RB / 0 RB Offset				
				100 RB / 0 RB Offset				
	Conducted Emission	18607 to 19193	18900	1.4 MHz	QPSK	1 RB / 0 RB Offset		
		18615 to 19185	18900	3 MHz	QPSK	1 RB / 0 RB Offset		
		18625 to 19175	18900	5 MHz	QPSK	1 RB / 0 RB Offset		
		18650 to 19150	18900	10 MHz	QPSK	1 RB / 0 RB Offset		
		18675 to 19125	18900	15 MHz	QPSK	1 RB / 0 RB Offset		
		18700 to 19100	18900	20 MHz	QPSK	1 RB / 0 RB Offset		
			Radiated Emission	18607 to 19193	18900	1.4 MHz	QPSK	1 RB / 0 RB Offset
				18615 to 19185	18900	3 MHz	QPSK	1 RB / 0 RB Offset
				18625 to 19175	18900	5 MHz	QPSK	1 RB / 0 RB Offset
				18650 to 19150	18900	10 MHz	QPSK	1 RB / 0 RB Offset
18675 to 19125	18900			15 MHz	QPSK	1 RB / 0 RB Offset		
18700 to 19100	18900			20 MHz	QPSK	1 RB / 0 RB Offset		

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
EIRP	26 deg. C, 58 % RH	3.8 Vdc	Carlos Chen
Frequency Stability	26 deg. C, 58 % RH	3.8 Vdc	Carlos Chen
Occupied Bandwidth	26 deg. C, 58 % RH	3.8 Vdc	Carlos Chen
Band Edge	26 deg. C, 58 % RH	3.8 Vdc	Carlos Chen
Peak to Average Ratio	26 deg. C, 58 % RH	3.8 Vdc	Carlos Chen
Conducuted Emission	26 deg. C, 58 % RH	3.8 Vdc	Carlos Chen
Radiated Emission	25 deg. C, 65 % RH	120 Vac, 60 Hz	Charles Hsiao

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 24

ANSI/TIA/EIA-603-C 2004

NOTE: All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Mobile / Portable station are limited to 2 watts e.i.r.p.

4.1.2 Test Procedures

EIRP / ERP Measurement:


- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1 MHz for GSM, GPRS & EDGE, 5 MHz for WCDMA and CDMA, and 10 MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G.
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$. E.R.P power can be calculated from E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.P.R \text{ power} - 2.15 \text{ dBi}$.

Conducted Power Measurement:

The EUT was set up for the maximum power with GSM, GPRS, EDGE, WCDMA, CDMA, and LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

4.1.3 Test Setup

EIRP / ERP Measurement:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

Conducted Power Measurement:



4.1.4 Test Results

Conducted Output Power (dBm)

Band	GSM1900		
Channel	512	661	810
Frequency (MHz)	1850.2	1880.0	1909.8
GSM	29.96	30.03	30.01
GPRS 8	29.94	29.99	29.99
GPRS 10	29.82	29.89	29.87
EDGE 8	26.29	26.36	26.34
EDGE 10	26.16	26.23	26.21
DTM 9 (GPRS)	29.71	29.78	29.76
DTM 9 (EDGE)	25.95	26.02	26.00

Band	WCDMA II		
Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880.0	1907.6
RMC 12.2K	22.64	22.74	22.66
HSDPA Subtest-1	22.66	22.71	22.73
HSDPA Subtest-2	22.47	22.61	22.63
HSDPA Subtest-3	22.25	22.38	22.40
HSDPA Subtest-4	22.03	22.13	22.16
HSUPA Subtest-1	22.40	21.99	22.02
HSUPA Subtest-2	20.62	20.72	20.74
HSUPA Subtest-3	21.69	21.75	21.79
HSUPA Subtest-4	20.84	20.91	20.95
HSUPA Subtest-5	22.60	22.70	22.70

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 18607	Mid Ch 18900	High Ch 19193		Low Ch 18607	Mid Ch 18900	High Ch 19193	
			1850.7 MHz	1880.0 MHz	1909.3 MHz		1850.7 MHz	1880.0 MHz	1909.3 MHz	
2 / 1.4M	1	0	23.41	23.50	23.30	0	22.79	22.88	22.68	1
	1	2	23.44	23.53	23.33	0	22.82	22.91	22.71	1
	1	5	23.12	23.21	23.01	0	22.50	22.59	22.39	1
	3	0	23.76	23.85	23.65	0	23.14	23.23	23.03	1
	3	1	23.54	23.63	23.43	0	23.01	22.92	22.81	1
	3	3	23.40	23.49	23.29	0	22.78	22.87	22.67	1
	6	0	22.53	22.62	22.42	1	21.91	22.00	21.80	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 18615	Mid Ch 18900	High Ch 19185		Low Ch 18615	Mid Ch 18900	High Ch 19185	
			1851.5 MHz	1880.0 MHz	1908.5 MHz		1851.5 MHz	1880.0 MHz	1908.5 MHz	
2 / 3M	1	0	23.57	23.66	23.46	0	22.87	22.96	22.76	1
	1	7	23.60	23.69	23.49	0	22.90	22.99	22.79	1
	1	14	23.28	23.37	23.17	0	22.58	22.67	22.47	1
	8	0	23.01	22.92	22.81	1	22.31	22.22	22.11	2
	8	3	22.70	22.79	22.59	1	22.00	22.09	21.89	2
	8	7	22.56	22.65	22.45	1	21.86	21.95	21.75	2
	15	0	22.69	22.78	22.58	1	21.99	22.08	21.88	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 18625	Mid Ch 18900	High Ch 19175		Low Ch 18625	Mid Ch 18900	High Ch 19175	
			1852.5 MHz	1880.0 MHz	1907.5 MHz		1852.5 MHz	1880.0 MHz	1907.5 MHz	
2 / 5M	1	0	23.70	23.79	23.59	0	22.93	23.02	22.82	1
	1	12	23.73	23.82	23.62	0	22.96	23.05	22.85	1
	1	24	23.41	23.50	23.30	0	22.64	22.73	22.53	1
	12	0	23.14	23.05	22.94	1	22.37	22.28	22.17	2
	12	6	22.83	22.92	22.72	1	22.06	22.15	21.95	2
	12	13	22.69	22.78	22.58	1	21.92	22.01	21.81	2
	25	0	22.82	22.91	22.71	1	22.05	22.14	21.94	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 18650	Mid Ch 18900	High Ch 19150		Low Ch 18650	Mid Ch 18900	High Ch 19150	
			1855.0 MHz	1880.0 MHz	1905.0 MHz		1855.0 MHz	1880.0 MHz	1905.0 MHz	
2 / 10M	1	0	23.87	23.96	23.76	0	22.97	23.06	22.86	1
	1	24	23.90	23.99	23.79	0	23.00	23.09	22.89	1
	1	49	23.58	23.67	23.47	0	22.68	22.77	22.57	1
	25	0	23.31	23.22	23.11	1	22.41	22.32	22.21	2
	25	12	23.00	23.09	22.89	1	22.10	22.19	21.99	2
	25	25	22.86	22.95	22.75	1	21.96	22.05	21.85	2
	50	0	22.99	23.08	22.88	1	22.09	22.18	21.98	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 18675	Mid Ch 18900	High Ch 19125		Low Ch 18675	Mid Ch 18900	High Ch 19125	
			1857.5 MHz	1880.0 MHz	1902.5 MHz		1857.5 MHz	1880.0 MHz	1902.5 MHz	
2 / 15M	1	0	23.98	24.07	23.87	0	23.02	23.11	22.91	1
	1	37	24.01	24.10	23.90	0	23.05	23.14	22.94	1
	1	74	23.69	23.78	23.58	0	22.73	22.82	22.62	1
	36	0	23.42	23.33	23.22	1	22.46	22.37	22.26	2
	36	19	23.11	23.20	23.00	1	22.15	22.24	22.04	2
	36	39	22.97	23.06	22.86	1	22.01	22.10	21.90	2
	75	0	23.10	23.19	22.99	1	22.14	22.23	22.03	2

Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)
			Low Ch 18700	Mid Ch 18900	High Ch 19100		Low Ch 18700	Mid Ch 18900	High Ch 19100	
			1860.0 MHz	1880.0 MHz	1900.0 MHz		1860.0 MHz	1880.0 MHz	1900.0 MHz	
2 / 20M	1	0	24.13	24.22	24.02	0	23.11	23.20	23.00	1
	1	50	24.16	24.25	24.05	0	23.14	23.23	23.03	1
	1	99	23.84	23.93	23.73	0	22.82	22.91	22.71	1
	50	0	23.48	23.47	23.37	1	22.46	22.45	22.35	2
	50	25	23.26	23.35	23.15	1	22.24	22.33	22.13	2
	50	50	23.12	23.21	23.01	1	22.10	22.19	21.99	2
	100	0	23.25	23.34	23.14	1	22.23	22.32	22.12	2

EIRP Power (dBm)

GSM							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	512	1850.2	-17.13	44.70	27.57	571.48	H
	661	1880.0	-17.03	44.70	27.67	584.79	
	810	1909.8	-17.46	44.57	27.11	514.40	
	512	1850.2	-14.94	44.27	29.33	857.04	V
	661	1880.0	-15.79	44.87	29.08	809.10	
	810	1909.8	-15.30	44.61	29.31	853.69	

EDGE							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	512	1850.2	-21.10	44.70	23.60	229.09	H
	661	1880.0	-21.55	44.70	23.15	206.54	
	810	1909.8	-21.41	44.57	23.16	207.16	
	512	1850.2	-18.35	44.27	25.92	390.84	V
	661	1880.0	-19.43	44.87	25.44	349.95	
	810	1909.8	-19.17	44.61	25.44	350.19	

WCDMA							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	9262	1852.4	-25.21	44.70	19.49	88.92	H
	9400	1880.0	-25.42	44.70	19.28	84.72	
	9538	1907.6	-24.66	44.57	19.91	98.02	
	9262	1852.4	-22.32	44.27	21.95	156.68	V
	9400	1880.0	-23.20	44.87	21.67	146.89	
	9538	1907.6	-23.15	44.61	21.46	140.06	

LTE Band 2							
Channel Bandwidth: 1.4 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18607	1850.7	-23.27	44.70	21.43	139.00	H
	18900	1880.0	-23.67	44.70	21.03	126.77	
	19193	1909.3	-22.62	44.57	21.95	156.78	
	18607	1850.7	-20.58	44.27	23.69	233.88	V
	18900	1880.0	-21.53	44.87	23.34	215.77	
	19193	1909.3	-20.89	44.61	23.72	235.67	
Channel Bandwidth: 1.4 MHz / 16QAM							
Z	18607	1850.7	-23.72	44.70	20.98	125.31	H
	18900	1880.0	-24.07	44.70	20.63	115.61	
	19193	1909.3	-24.18	44.57	20.39	109.47	
	18607	1850.7	-22.22	44.27	22.05	160.32	V
	18900	1880.0	-22.04	44.87	22.83	191.87	
	19193	1909.3	-22.26	44.61	22.35	171.91	

LTE Band 2							
Channel Bandwidth: 3 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18615	1851.5	-22.90	44.70	21.80	151.36	H
	18900	1880.0	-23.24	44.70	21.46	139.96	
	19185	1908.5	-23.42	44.57	21.15	130.41	
	18615	1851.5	-21.03	44.27	23.24	210.86	V
	18900	1880.0	-21.07	44.87	23.80	239.88	
	19185	1908.5	-20.92	44.61	23.69	234.05	
Channel Bandwidth: 3 MHz / 16QAM							
Z	18615	1851.5	-24.37	44.70	20.33	107.89	H
	18900	1880.0	-23.80	44.70	20.90	123.03	
	19185	1908.5	-23.91	44.57	20.66	116.49	
	18615	1851.5	-21.42	44.27	22.85	192.75	V
	18900	1880.0	-22.53	44.87	22.34	171.40	
	19185	1908.5	-21.66	44.61	22.95	197.38	

LTE Band 2							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18625	1852.5	-23.69	44.70	21.01	126.18	H
	18900	1880.0	-22.83	44.70	21.87	153.82	
	19175	1907.5	-22.81	44.57	21.76	150.07	
	18625	1852.5	-21.10	44.27	23.17	207.49	V
	18900	1880.0	-21.21	44.87	23.66	232.27	
	19175	1907.5	-21.21	44.61	23.40	218.93	
Channel Bandwidth: 5 MHz / 16QAM							
Z	18625	1852.5	-24.00	44.70	20.70	117.49	H
	18900	1880.0	-23.96	44.70	20.74	118.58	
	19175	1907.5	-24.25	44.57	20.32	107.72	
	18625	1852.5	-21.61	44.27	22.66	184.50	V
	18900	1880.0	-22.83	44.87	22.04	159.96	
	19175	1907.5	-21.66	44.61	22.95	197.38	

LTE Band 2							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18650	1855.0	-22.76	44.70	21.94	156.31	H
	18900	1880.0	-23.40	44.70	21.30	134.90	
	19150	1905.0	-22.58	44.57	21.99	158.23	
	18650	1855.0	-21.05	44.27	23.22	209.89	V
	18900	1880.0	-21.65	44.87	23.22	209.89	
	19150	1905.0	-21.29	44.61	23.32	214.93	
Channel Bandwidth: 10 MHz / 16QAM							
Z	18650	1855.0	-24.19	44.70	20.51	112.46	H
	18900	1880.0	-24.00	44.70	20.70	117.49	
	19150	1905.0	-23.84	44.57	20.73	118.39	
	18650	1855.0	-22.27	44.27	22.00	158.49	V
	18900	1880.0	-22.58	44.87	22.29	169.43	
	19150	1905.0	-21.68	44.61	22.93	196.47	

LTE Band 2							
Channel Bandwidth: 15 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18675	1857.5	-23.46	44.70	21.24	133.05	H
	18900	1880.0	-22.77	44.70	21.93	155.96	
	19125	1902.5	-23.42	44.57	21.15	130.41	
	18675	1857.5	-20.31	44.27	23.96	248.89	V
	18900	1880.0	-20.98	44.87	23.89	244.91	
	19125	1902.5	-21.34	44.61	23.27	212.47	
Channel Bandwidth: 15 MHz / 16QAM							
Z	18675	1857.5	-24.63	44.70	20.07	101.62	H
	18900	1880.0	-24.06	44.70	20.64	115.88	
	19125	1902.5	-23.70	44.57	20.87	122.26	
	18675	1857.5	-21.35	44.27	22.92	195.88	V
	18900	1880.0	-22.55	44.87	22.32	170.61	
	19125	1902.5	-21.64	44.61	22.97	198.29	

LTE Band 2							
Channel Bandwidth: 20 MHz / QPSK							
Plane	Channel	Frequency (MHz)	LVL (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18700	1860.0	-23.18	44.70	21.52	141.91	H
	18900	1880.0	-23.66	44.70	21.04	127.06	
	19100	1900.0	-23.28	44.57	21.29	134.68	
	18700	1860.0	-20.98	44.27	23.29	213.30	V
	18900	1880.0	-21.08	44.87	23.79	239.33	
	19100	1900.0	-21.18	44.61	23.43	220.44	
Channel Bandwidth: 20 MHz / 16QAM							
Z	18700	1860.0	-23.71	44.70	20.99	125.60	H
	18900	1880.0	-24.24	44.70	20.46	111.17	
	19100	1900.0	-24.49	44.57	20.08	101.93	
	18700	1860.0	-22.08	44.27	22.19	165.58	V
	18900	1880.0	-22.28	44.87	22.59	181.55	
	19100	1900.0	-22.58	44.61	22.03	159.70	

4.2 Frequency Stability Measurement

4.2.1 Limits of Frequency Stability Measurement


The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

4.2.2 Test Procedure

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ± 0.5 °C during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 Test Setup



4.2.4 Test Results

Frequency Error vs. Voltage

Voltage (Volts)	Frequency Error (ppm)									Limit (ppm)
	GSM	EDGE	WCDMA	LTE Band 2						
				1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
3.8	0.001	0.001	0.001	0.00037234	0.001010638	0.000319149	0.000101064	0.000691489	0.000957447	2.5
3.5	0.001	0.001	0.000	0.001489362	0.000478723	0.000265957	0.001329787	0.001489362	0.000319149	2.5
4.2	0.001	0.001	0.000	0.000159574	0.000691489	0.001489362	0.000106383	0.000159574	0.001117021	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.6 Vdc to 4.35 Vdc.

Frequency Error vs. Temperature


Temp. (°C)	Frequency Error (ppm)									Limit (ppm)
	GSM	EDGE	WCDMA	LTE Band 2						
				1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
-10	0.000	0.001	0.000	0.001329787	0.000904255	0.001808511	0.001595745	0.00143617	0.000212766	2.5
0	0.000	0.002	0.002	0.001170213	0.000265957	0.001808511	0.001542553	0.00143617	0.001595745	2.5
10	0.002	0.000	0.002	0.001276596	0.001595745	0.001117021	0.00143617	0.001223404	0.000957447	2.5
20	-0.001	-0.002	-0.001	-0.000744681	-0.00106383	-0.000851064	-0.001861702	-0.001223404	-0.00037234	2.5
30	-0.001	-0.001	-0.002	-0.000265957	-0.001595745	-0.000531915	-0.00143617	-0.000425532	-0.000212766	2.5
40	-0.001	-0.001	-0.002	-0.000425532	-0.001223404	-0.000319149	-0.000265957	-0.000797872	-0.00106383	2.5
50	0.000	-0.002	-0.001	-0.001914894	-0.001861702	-0.001117021	-0.000691489	-0.00143617	-0.001702128	2.5
55	-0.002	0.000	-0.002	-0.001170213	-0.001276596	-0.000319149	-0.000957447	-0.001489362	-0.000159574	2.5

4.3 Occupied Bandwidth Measurement

4.3.1 Test Procedure


The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

4.3.2 Test Setup



4.3.3 Test Result

Channel	Frequency (MHz)	99 % Occupied Bandwidth (kHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)
		GSM	EDGE			
512	1850.2	247.23	244.36	9262	1852.4	4.08
661	1880.0	246.25	246.08	9400	1880.0	4.08
810	1909.8	247.80	246.37	9538	1907.6	4.08



LTE Band 2


Channel Bandwidth: 1.4 MHz

Channel Bandwidth: 3 MHz


Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18607	1850.7	1.09	1.09	18615	1851.5	2.69	2.69
18900	1880.0	1.09	1.09	18900	1880.0	2.69	2.69
19193	1909.3	1.09	1.09	19185	1908.5	2.69	2.69

Spectrum Plot of Worst Value


1.4 MHz / QPSK




1.4 MHz / 16QAM



3 MHz / QPSK



3 MHz / 16QAM



LTE Band 2


Channel Bandwidth: 5 MHz

Channel Bandwidth: 10 MHz


Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18625	1852.5	4.49	4.49	18650	1855.0	8.98	8.97
18900	1880.0	4.49	4.49	18900	1880.0	8.97	8.97
19175	1907.5	4.49	4.49	19150	1905.0	8.98	8.98

Spectrum Plot of Worst Value


5 MHz / QPSK




5 MHz / 16QAM



10 MHz / QPSK



10 MHz / 16QAM



LTE Band 2


Channel Bandwidth: 15 MHz

Channel Bandwidth: 20 MHz


Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)		Channel	Frequency (MHz)	99 % Occupied Bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18675	1857.5	13.47	13.45	18700	1860.0	17.96	17.96
18900	1880.0	13.45	13.44	18900	1880.0	17.94	17.95
19125	1902.5	13.47	13.46	19100	1900.0	17.96	17.98

Spectrum Plot of Worst Value


15 MHz / QPSK




15 MHz / 16QAM



20 MHz / QPSK



20 MHz / 16QAM




4.4 Band Edge Measurement

4.4.1 Limits of Band Edge Measurement

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.


4.4.2 Test Setup



4.4.3 Test Procedures

- All measurements were done at low and high operational frequency range.
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 3.9 kHz and VB of the spectrum is 12 kHz (GSM/GPRS/EDGE).
- The center frequency of spectrum is the band edge frequency and span is 5 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (WCDMA).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 13 kHz and VB of the spectrum is 51 kHz (LTE Bandwidth 1.4 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 30 kHz and VB of the spectrum is 100 kHz (LTE Bandwidth 3 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 100 kHz and VB of the spectrum is 300 kHz (LTE Bandwidth 5 MHz/10 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 150 kHz and VB of the spectrum is 470 kHz (LTE Bandwidth 15 MHz).
- The center frequency of spectrum is the band edge frequency and span is 1 MHz. RB of the spectrum is 180 kHz and VB of the spectrum is 560 kHz (LTE Bandwidth 20 MHz).
- Record the max trace plot into the test report.

4.4.4 Test Results





A D T

LTE Band 2

Channel Bandwidth: 1.4 MHz

Channel



18607

1 RB

Channel

19193

1 RB



Channel


18607

6 RB

Channel


19193

6 RB






A D T






A D T






A D T






A D T





A D T




4.5 Peak to Average Ratio

4.5.1 Limits of Peak to Average Ratio Measurement

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

4.5.2 Test Setup




4.5.3 Test Procedures

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1 %.

4.5.4 Test Results

Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)
		GSM	EDGE			WCDMA
512	1850.2	0.26	0.27	9262	1852.4	3.43
661	1880.0	0.31	0.29	9400	1880.0	3.28
810	1909.8	0.32	0.31	9538	1907.6	3.16



LTE Band 2

Channel Bandwidth: 1.4 MHz


Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM
18607	1850.7	5.82	6.86
18900	1880.0	5.80	6.88
19193	1909.3	4.74	5.74

Channel Bandwidth: 3 MHz


Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM
18615	1851.5	6.19	6.93
18900	1880.0	6.13	6.85
19185	1908.5	5.48	6.14

Spectrum Plot of Worst Value


1.4 MHz / QPSK




1.4 MHz / 16QAM



3 MHz / QPSK



3 MHz / 16QAM



LTE Band 2


Channel Bandwidth: 5 MHz

Channel Bandwidth: 10 MHz


Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
18625	1852.5	6.20	6.85	18650	1855.0	5.78	6.65
18900	1880.0	6.14	6.79	18900	1880.0	5.92	6.88
19175	1907.5	5.77	6.41	19150	1905.0	5.47	6.36

Spectrum Plot of Worst Value


5 MHz / QPSK




5 MHz / 16QAM



10 MHz / QPSK



10 MHz / 16QAM



LTE Band 2


Channel Bandwidth: 15 MHz

Channel Bandwidth: 20 MHz


Channel	Frequency (MHz)	Peak to Average Ratio (dB)		Channel	Frequency (MHz)	Peak to Average Ratio (dB)	
		QPSK	16QAM			QPSK	16QAM
18675	1857.5	5.87	7.00	18700	1860.0	6.15	7.13
18900	1880.0	6.09	7.43	18900	1880.0	6.18	7.18
19125	1902.5	5.31	6.48	19100	1900.0	5.55	6.47

Spectrum Plot of Worst Value


15 MHz / QPSK




15 MHz / 16QAM



20 MHz / QPSK



20 MHz / 16QAM




4.6 Conducted Spurious Emissions

4.6.1 Limits of Conducted Spurious Emissions Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13 dBm.


4.6.2 Test Setup



4.6.3 Test Procedure

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 9 kHz to 9 GHz. 20 dB attenuation pad is connected with spectrum. RBW=1 MHz and VBW=3 MHz is used for conducted emission measurement.

4.6.4 Test Results







A D T

LTE Band 2
Channel 18900


Channel Bandwidth: 1.4 MHz




Channel Bandwidth: 3 MHz




Channel Bandwidth: 5 MHz




Channel Bandwidth: 10 MHz



Channel Bandwidth: 15 MHz



Channel Bandwidth: 20 MHz



4.7 Radiated Emission Measurement

4.7.1 Limits of Radiated Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit is equal to -13 dBm.

4.7.2 Test Procedure


- Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G.
- EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
- E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power - 2.15 dBi.

NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz/3 MHz.

4.7.3 Deviation from Test Standard

No deviation.

4.7.4 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.7.5 Test Results


GSM:



Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch

A D T

Data: 13



Site : 966 chamber 1
Condition: PART 22/24 3m Horizontal
Remark : PCS 1900_Link_CH661
Tested by: Charles Hsiao
Plane : Y


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	80.49	-50.33	-38.56	-13.00	-37.33	-11.77	Peak
2	132.60	-49.92	-42.26	-13.00	-36.92	-7.66	Peak
3	193.89	-61.46	-55.55	-13.00	-48.46	-5.91	Peak
4	335.70	-73.20	-67.65	-13.00	-60.20	-5.55	Peak
5	596.80	-68.86	-69.13	-13.00	-55.86	0.27	Peak
6	958.70	-63.69	-68.82	-13.00	-50.69	5.13	Peak
7 pp	3760.00	-49.79	-65.93	-13.00	-36.79	16.14	Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14



Site : 966 chamber 1
Condition: PART 22/24 3m Vertical
Remark : PCS 1900_Link_CH661
Tested by: Charles Hsiao
Plane : Y

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	79.95	-52.76	-40.91	-13.00	-39.76	-11.85	Peak
2	118.29	-54.05	-45.67	-13.00	-41.05	-8.38	Peak
3	190.38	-66.10	-60.37	-13.00	-53.10	-5.73	Peak
4	398.70	-72.20	-69.41	-13.00	-59.20	-2.79	Peak
5	617.80	-68.34	-68.57	-13.00	-55.34	0.23	Peak
6	958.70	-64.10	-69.23	-13.00	-51.10	5.13	Peak
7 pp	3760.00	-50.67	-66.81	-13.00	-37.67	16.14	Peak


EDGE:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 chamber 1
Condition: PART 22/24 3m Horizontal
Remark : EDGE 1900_Link_CH661
Tested by: Charles Hsiao
Plane : Y


		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp 3760.00	-48.87	-65.01	-13.00	-35.87	16.14	Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10



Site : 966 chamber 1
Condition: PART 22/24 3m Vertical
Remark : EDGE 1900_Link_CH661
Tested by: Charles Hsiao
Plane : Y

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp 3760.00	-50.14	-66.28	-13.00	-37.14	16.14	Peak


WCDMA:



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 chamber 1
Condition: PART 22/24 3m Horizontal
Remark : Band II_Link_CH9400
Tested by: Charles Hsiao
Plane : Y


		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp 3760.00	-24.24	-40.38	-13.00	-11.24	16.14	Peak



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10



Site : 966 chamber 1
Condition: PART 22/24 3m Vertical
Remark : Band II_Link_CH9400
Tested by: Charles Hsiao
Plane : Y

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1 pp 3760.00	-28.71	-44.85	-13.00	-15.71	16.14	Peak

LTE Band 2

Channel Bandwidth: 20 MHz / QPSK




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13

Date: 2016-01-14



Site : 966 chamber 1
Condition: PART 22/24 3m Horizontal
Remark : LTE_Band 2_QPSK(1,50)_20M_CH18900
Tested by: Charles Hsiao
Plane : Z

			Read	Limit	Over		
	Freq	Level	Level	Line	Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	80.49	-52.62	-40.85	-13.00	-39.62	-11.77	Peak
2	116.67	-49.73	-41.22	-13.00	-36.73	-8.51	Peak
3	189.03	-59.18	-53.46	-13.00	-46.18	-5.72	Peak
4	337.80	-66.83	-61.31	-13.00	-53.83	-5.52	Peak
5	598.20	-67.94	-68.29	-13.00	-54.94	0.35	Peak
6	957.30	-64.13	-69.26	-13.00	-51.13	5.13	Peak
7 pp	3760.00	-14.85	-30.99	-13.00	-1.85	16.14	Peak
8	5640.00	-41.30	-61.77	-13.00	-28.30	20.47	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2016-01-14



Site : 966 chamber 1
 Condition: PART 22/24 3m Vertical
 Remark : LTE_Band 2_QPSK(1,50)_20M_CH18900
 Tested by: Charles Hsiao
 Plane : Z

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm/m	dBm	dBm/m	dB	dB/m	
1	30.27	-56.93	-46.39	-13.00	-43.93	-10.54	Peak
2	118.56	-59.15	-50.77	-13.00	-46.15	-8.38	Peak
3	194.16	-67.93	-62.02	-13.00	-54.93	-5.91	Peak
4	416.20	-71.53	-68.43	-13.00	-58.53	-3.10	Peak
5	640.20	-68.84	-68.82	-13.00	-55.84	-0.02	Peak
6	961.50	-63.77	-68.91	-13.00	-50.77	5.14	Peak
7 pp	3760.00	-19.84	-35.98	-13.00	-6.84	16.14	Peak
8	5640.00	-45.07	-65.54	-13.00	-32.07	20.47	Peak

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---