

### EXHIBIT 3

**Report Of Measurement**  
Includes sample calculations, block diagrams, photographs  
of test configurations and properly signed and dated report.

# TEST RESULT SUMMARY

## FCC PART 15 SUBPART B Class B Limit

MANUFACTURER'S NAME

Denso Corp

NAME OF EQUIPMENT

Superregenerative Receiver for Keyless Entry System

MODEL NUMBER

13BAT

MANUFACTURER'S ADDRESS

1-1 Showa-cho, Kariya-shi  
Aichi-ken, 448-8661 Japan

TEST REPORT NUMBER

W8508.2

TEST DATE

10 November 1998

According to testing performed at TÜV Product Service Inc, the above-mentioned unit is in compliance with the electromagnetic compatibility requirements defined in FCC Part 15.

It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics. Any modifications necessary for compliance made during testing on the above mentioned date(s) must be implemented in all production units for compliance to be maintained.

TÜV Product Service Inc, as an independent testing laboratory, declares that the equipment tested as specified above conforms to the requirements of FCC Part 15.

Date: 23 November 1998

Location: Taylors Falls MN  
USA

*Joseph C. Sausen*  
J. C. Sausen  
Test Engineer

*Joel T. Schneider*  
J. T. Schneider  
NVLAP Signatory

Not Transferable

# EMC EMISSION - TEST REPORT

Test Report File No. : **W011850801.2** Date of issue: 23 November 1998

Model / Serial No. : **13BAT /**

Product Type : **Superregenerative Receiver for Keyless Entry System**

Applicant : **Denso Corp**

Manufacturer : **Denso Corp**

License holder : **Denso Corp**

Address : **1-1 Showa-cho, Kariya-shi**

: **Aichi-ken, 448-8661 Japan**

Test Result :  **Positive  Negative**

Test Project Number  
Reference(s) : **W8508.2**

Total pages including  
Appendices : **22**

*TÜV Product Service Inc is a subcontractor to TÜV Product Service, GmbH according to the principles outlined in ISO/IEC Guide 25 and EN 45001.*

*TÜV Product Service Inc reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. TÜV Product Service Inc shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV Product Service Inc issued reports.*

*This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval. This report shall not be used by the client to claim product endorsement by NVLAP or any agency of the US government.*

*TÜV Product Service Inc and its professional staff hold government and professional organization certifications and are members of AAMI, ACIL, AEA, ANSI, IEEE, NVLAP, and VCCI*

## DIRECTORY - EMISSIONS

	Page(s)
<b>A) Documentation</b>	
Test report	<u>1 - 10</u>
Directory	<u>2</u>
Test Regulations	<u>3</u>
Deviations from standard / Summary	<u>10</u>
Test-setups (Photos)	<u>11 - 12</u>
Test-setup (drawing)	<u>Appendix A</u>
<b>B) Test data</b>	
Conducted emissions	<u>10/150 kHz - 30 MHz</u>
Radiated emissions	<u>10 kHz - 30 MHz</u>
Radiated emissions	<u>30 MHz - 1000 MHz</u>
Interference power	<u>30 MHz - 300 MHz</u>
Equivalent Radiated emissions	<u>1 GHz - 18 GHz</u>
<b>C) Appendix A</b>	
Test Data Sheets and Test Setup Drawing(s)	<u>A2 - A5</u>
<b>D) Appendix B</b>	
Constructional Data Form	<u>B2</u>
Product Information Form(s)	<u>B3</u>
<b>E) Appendix C</b>	
Measurement Protocol	<u>C1 - C2</u>

## EMISSIONS TEST REGULATIONS :

The emissions tests were performed according to following regulations:

- EN 50081-1 / 1991

- EN 55011 / 1991

- Group 1

- Group 2

- EN 55013 / 1990

- EN 55014 / 1987

- Class A

- Class B

- EN 55014 / A2:1990

- EN 55014 / 1993

- Household appliances and similar

- Portable tools

- Semiconductor devices

- EN 55015 / 1987

- EN 55015 / A1:1990

- EN 55015 / 1993

- EN 55022 / 1987

- EN 55022 / 1994

- Class A

- Class B

- Class A

- Class B

- BS

- VCCI

- FCC

- AS 3548 (1992)

- Class A

- Class B

- Class A

- Class B

- CISPR 11 (1990)

- Group 1

- Group 2

- CISPR 22 (1993)

- Class A

- Class B

- Class A

- Class B

**Environmental conditions in the lab:**

	<u>Actual</u>
Temperature	: 17 °C
Relative Humidity	: 36 %
Atmospheric pressure	: 96.8 kPa
Power supply system	: 12 VDC

**Sign Explanations:**

- not applicable
- applicable

## Emissions Test Conditions: CONDUCTED EMISSIONS (Interference Voltage)

The **CONDUCTED EMISSIONS (INTERFERENCE VOLTAGE)** measurements were performed at the following test location:

■ - Test not applicable

- Wild River Lab Large Test Site (Open Area Test Site)
- Wild River Lab Small Test Site (Open Area Test Site)
- Oakwood Lab (Open Area Test Site)
- Wild River Lab Screen Room
- New Brighton Lab Shielded Room

Test equipment used :

Model Number	Manufacturer	Description	Serial Number	Cal Date
--------------	--------------	-------------	---------------	----------

## Emissions Test Conditions: RADIATED EMISSIONS (Magnetic Field)

The **RADIATED EMISSIONS (MAGNETIC FIELD)** measurements were performed at the following test location:

- Wild River Lab Large Test Site (Open Area Test Site)
- Wild River Lab Small Test Site (Open Area Test Site)
- Oakwood Lab (Open Area Test Site)

at a test distance of :

- 3 meters
- 30 meters

■ - Test not applicable

Test equipment used :

Model Number	Manufacturer	Description	Serial Number	Cal Date
--------------	--------------	-------------	---------------	----------

## Emissions Test Conditions: RADIATED EMISSIONS (Electric Field)

The **RADIATED EMISSIONS (ELECTRIC FIELD)** measurements, in the frequency range of 30 MHz-1000 MHz, were tested in a horizontal and vertical polarization at the following test location :

- Test not applicable

- Wild River Lab Large Test Site (Open Area Test Site)
- Wild River Lab Small Test Site (Open Area Test Site)
- Oakwood Lab (Open Area Test Site)

at a test distance of :

- 3 meters
- 10 meters
- 30 meters

Test equipment used :

Model Number	Manufacturer	Description	Serial Number	Cal Date
■ - SAS-200/512	A. H. Systems	Log Periodic Antenna	147	6-98
■ - 3108	Electro-Mechanics (EMCO)	Biconical Antenna	2429	6-98
■ - 8566B	Hewlett-Packard	Spectrum Analyzer	2221A01596	4-98
■ - 85662A	Hewlett-Packard	Analyzer Display	2152A03640	4-98
■ - 85650A	Hewlett-Packard	Quasi-Peak Adapter	2811A01127	4-98
■ - ZHL-1042J	Mini-Circuits	Preamplifier	H072294-11	4-98

Use of the calibrated equipment on this list ensures traceability to national and international standards.

## Emissions Test Conditions: INTERFERENCE POWER

The **INTERFERENCE POWER** measurements were performed by using the absorbing clamp on the mains and interface cables in the frequency range 30 MHz - 300 MHz at the following test location :

- Test not applicable

- Wild River Lab Large Test Site (Open Area Test Site)
- Wild River Lab Small Test Site (Open Area Test Site)
- Oakwood Lab (Open Area Test Site)
- Wild River Lab Screen Room
- New Brighton Lab Shielded Room

Test equipment used :

Model Number	Manufacturer	Description	Serial Number	Cal Date

## Emissions Test Conditions: RADIATED EMISSIONS (Electric Field)

The **EQUIVALENT RADIATED EMISSIONS** measurements in the frequency range 1 GHz - 2 GHz were performed in a horizontal and vertical polarization at the following test location :

- Wild River Lab Large Test Site (Open Area Test Site)
- Wild River Lab Small Test Site (Open Area Test Site)
- Oakwood Lab (Open Area Test Site)
- Wild River Lab Screen Room

at a test distance of:

- 1 meters
- 3 meters
- 10 meters

- Test not applicable

**Test equipment used :**

<b>Model Number</b>	<b>Manufacturer</b>	<b>Description</b>	<b>Serial Number</b>	<b>Cal Date</b>
■ - 3115	Electro-Mechanics (EMCO)	Horn Antenna	9001-3275	9-98
■ - 8566B	Hewlett-Packard	Spectrum Analyzer	2221A01596	4-98
■ - 85662A	Hewlett-Packard	Analyzer Display	2152A03640	4-98
■ - 85650A	Hewlett-Packard	Quasi-Peak Adapter	2811A01127	4-98
■ - ZHL-1042J	Mini-Circuits	Preamplifier	H072294-11	4-98

**Equipment Under Test (EUT) Test Operation Mode - Emission tests :**

**The device under test was operated under the following conditions during emissions testing:**

- Standby
- Test program (H - Pattern)
- Test program (color bar)
- Test program (customer specific)
- Practice operation
- Normal Operating Mode
- \_\_\_\_\_

**Configuration of the device under test:**

- See Constructional Data Form in Appendix B - Page B2
- See Product Information Form in Appendix B - beginning on Page B3

**The following peripheral devices and interface cables were connected during the measurement:**

- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- \_\_\_\_\_
- unshielded power cable
- unshielded cables
- shielded cables
- customer specific cables
- \_\_\_\_\_
- \_\_\_\_\_

Type : \_\_\_\_\_

MPS.No.: \_\_\_\_\_

**Emission Test Results:**
**Conducted emissions 450 kHz - 30 MHz**

The requirements are

- MET

- NOT MET

Minimum limit margin

\_\_\_\_\_ dB

at \_\_\_\_\_ MHz

Maximum limit exceeding

\_\_\_\_\_ dB

at \_\_\_\_\_ MHz

Remarks:

**Radiated emissions (magnetic field) 10 kHz - 30 MHz**

The requirements are

- MET

- NOT MET

Minimum limit margin

\_\_\_\_\_ dB

at \_\_\_\_\_ MHz

Maximum limit exceeding

\_\_\_\_\_ dB

at \_\_\_\_\_ MHz

Remarks:

**Radiated emissions (electric field) 30 MHz - 1000 MHz**

The requirements are

- MET

- NOT MET

Minimum limit margin

\_\_\_\_\_ dB

at \_\_\_\_\_ MHz

Maximum limit exceeding

\_\_\_\_\_ dB

at \_\_\_\_\_ MHz

Remarks:

**Interference Power at the mains and interface cables 30 MHz - 300 MHz**

The requirements are

- MET

- NOT MET

Minimum limit margin

\_\_\_\_\_ dB

at \_\_\_\_\_ MHz

Maximum limit exceeding

\_\_\_\_\_ dB

at \_\_\_\_\_ MHz

Remarks:

**Equivalent Radiated emissions 1 GHz - 2 GHz**

The requirements are

- MET

- NOT MET

Minimum limit margin

\_\_\_\_\_ dB

at \_\_\_\_\_ MHz

Maximum limit exceeding

\_\_\_\_\_ dB

at \_\_\_\_\_ MHz

Remarks:

**DEVIATIONS FROM STANDARD:**

None.

**GENERAL REMARKS:****SUMMARY:**

The requirements according to the technical regulations are

- met

- not met.

The device under test does

- fulfill the general approval requirements mentioned on page 3.

- not fulfill the general approval requirements mentioned on page 3.

Testing Start Date: 10 November 1998

Testing End Date: 10 November 1998

- TÜV PRODUCT SERVICE INC -

Joel T. Schneider  
J. T. Schneider  
NVLAP Signatory

Tested By:  
J. C. Sausen

Joseph C. Sausen  
by JCS

File No. W011850801.2, Page 10 of 12

FCC ID: HYQ13BAT

Test-setup photo(s):  
Conducted emission 10/150 kHz - 30 MHz

Not Applicable

File No. W011850801.2, Page 11 of 12

FCC ID: HYQ13BAT

**Appendix A**

**Test Data Sheets**

**and**

**Test Setup Drawing(s)**


File No. W011850801.2, Page A1 of A5

**TEST SETUP FOR EMISSIONS TESTING**

WILD RIVER LAB  
Large Test Site

Notes:

1. Items shown in dotted lines are located on the floor below the test area. It is 5 meters vertically from the ground floor to the test area.
2. 50 Hz, 60 Hz, and 400 Hz are power panels for alternating current.
3. The antenna may be positioned horizontally 3, 10 or 30 meters from the center of the turntable.
4. The circle is a 6.7 meter diameter turntable.
5. A ground plane is in the plane of this sheet.
6. The test sample is shown in the azimuthal position representing zero degrees.




FCC ID: HYQ13BAT

REPORT #W8508  
RUN 2

**TÜV PRODUCT SERVICE**  
RADIATED EMISSIONS AT 3 METERS  
DENSO HYQ13BAT RECEIVER

11/10/98



File No. W011850801.2, Page A3 of A5

**T U V P R O D U C T S E R V I C E**
**RADIATED EMISSIONS**

Large Test Site  
 3 Meter Antenna Distance  
 Equipment Under Test:  
 DENSO  
 HYQ13BAT RECEIVER  
 Notes:

Report W8508 Run 2  
 Date 11/10/98 Page 1  
 Engineer \_\_\_\_\_  
 Tech: JCS \_\_\_\_\_  
 Requester \_\_\_\_\_

Frequency	Level	Factor	Cable	Final	Az	Polar\ Height	Delta	Delta
MHz	dBuV	dB	dB	dBuV/m	deg		FCC B	FCC A
<b>SCAN 30-200 MHZ</b>								
30	3.07	14	.5	17.6	--	V --	-22.4	
60	4.22	9.6	.8	14.6	--	V --	-25.4	
120.25	1.53	11	1	13.6	--	V --	-29.9	
240	1.19	14.7	1.4	17.3	--	V --	-28.7	
<b>240 MHZ DELETED</b>								
200	2.29	12.8	1.3	16.4	--	V --	-27.1	
<b>SCAN 200-1000 MHZ</b>								
314.35 MHZ MAXED AT 90 DEGREES - ANTENNA VERTICAL, 1.8 METERS HIGH								
314.35	-.58	14.2	1.6	18.8	--	V --	-27.2	
314.35 MHZ MAXED AT 220 DEGREES - ANTENNA HORIZONTAL, 1 METER HIGH								
314.35	3.05	14.2	1.6	18.8	--	H --	-27.2	
<b>NO OTHER EMISSIONS DETECTED - FOLLOWING ARE NOISE FLOOR MEASUREMENTS</b>								
240	.71	14.7	1.4	16.8	--	V --	-29.2	
480	.46	16.8	2	19.2	--	V --	-26.8	
960	.35	24	2.9	27.2	--	V --	-18.8	
<b>SCAN 1000-2000 MHZ</b>								
<b>NO EMISSIONS DETECTED - FOLLOWING ARE NOISE FLOOR MEASUREMENTS</b>								
1920	.79	29	5	34.7	--	V --	-19.3	
1600	.8	27.2	3.9	31.9	--	V --	-22.1	
1200	.44	25.3	3.3	29.1	--	V --	-24.9	

T U V P R O D U C T S E R V I C E

RADIATED EMISSIONS

Large Test Site  
 3 Meter Antenna Distance  
 Equipment Under Test:  
 DENSO  
 HYQ13BAT RECEIVER  
 Notes:

Report W8508 Run 2  
 Date 11/10/98 Page 2  
 Engineer \_\_\_\_\_  
 Tech: JCS \_\_\_\_\_  
 Requester \_\_\_\_\_

Measurement Summary

Frequency MHz	Final dBuV/m	Azimuth uV/m	Polar\ Height deg	Delta FCC B	Delta FCC A
30	17.6	7.5857	--	V --	-22.4
60	14.6	5.3703	--	V --	-25.4
120.25	13.6	4.7863	--	V --	-29.9
200	16.4	6.6069	--	V --	-27.1
240	16.8	6.9183	--	V --	-29.2
314.35	18.8	8.7096	--	H --	-27.2
480	19.2	9.1201	--	V --	-26.8
960	27.2	22.908	--	V --	-18.8
1200	29.1	28.510	--	V --	-24.9
1600	31.9	39.355	--	V --	-22.1
1920	34.7	54.325	--	V --	-19.3

Minimum Passing Margin for FCC B is 18.8 dB at 960 MHz

File W8508 Run 2

FCC ID: HYQ13BAT

**Appendix B**

Constructional Data Form

and

Product Information Form(s)

File No. W011850801.2, Page B1 of B3

**FCC ID: HYQ13BAT**

**Constructional Data Form**

**Not Applicable**

**File No. W011850801.2, Page B2 of B3**

Technical Description of the systemType number

- Receiver :13BAT

Specifications of receiver

- Nominal frequency	:314.35 MHz
- Micro computer clock frequency	:4 MHz
- Type of receiving system	:Superregenerative
- Power supply	
- Nominal supply voltage	:12 VDC (vehicle battery)
- Antenna	:Built-in type (fixed)

Description of the system operation

This system is mainly used for locking or unlocking the doors of the vehicle. The transmitter sends a radio wave signal while the button is pushed. The receiver becomes active in response to the signal from the transmitter.

Installation in vehicle

The receiver is installed inside the vehicle.

**Appendix C**
**MEASUREMENT PROTOCOL FOR FCC**
**GENERAL INFORMATION**

In compliance with FCC Docket 92-152, "Harmonization of Rules for Digital Devices Incorporate International Standards", testing for FCC compliance may be done following the ANSI C63.4-1992 procedures and using the CISPR 22 Limits.

**Measurement Uncertainty**

The test system for conducted emissions is defined as the LISN, tuned receiver or spectrum analyzer, and coaxial cable. The test system for radiated emissions is defined as the antenna, the pre-amplifier, the spectrum analyzer and the coaxial cable. These test systems have an expected uncertainty of  $\pm 4.5$  dB. The equipment comprising the test systems are calibrated on an annual basis.

**Justification**

The Equipment Under Test (EUT) is configured in a typical user arrangement in accordance with the manufacturer's instructions. A cable is connected to each available port and either terminated with a peripheral into its characteristic impedance or left unterminated. When appropriate, the cables are manually manipulated with respect to each other to obtain maximum emissions from the unit.

**CONDUCTED EMISSIONS**

The final level, expressed in dB $\mu$ V, is arrived at by taking the reading directly from the EMI receiver. This level is compared directly to the FCC limit.

To convert between dB $\mu$ V and  $\mu$ V, the following conversions apply:

$$\begin{aligned} \text{dB}\mu\text{V} &= 20(\log \mu\text{V}) \\ \mu\text{V} &= \text{Inverse log}(\text{dB}\mu\text{V}/20) \end{aligned}$$

**RADIATED EMISSIONS**

The final level, expressed in dB $\mu$ V/m, is arrived at by taking the reading from the spectrum analyzer (Level dB $\mu$ V) and adding the antenna correction factor and cable loss factor (Factor dB) to it. This result then has the FCC limit subtracted from it to provide the Delta which gives the tabular data as shown in the data sheets in Attachment B. The amplifier gain is automatically accounted for by using an analyzer offset.

Example:

Frequency (MHz)	Level (dB $\mu$ V)	+	Factor & Cable (dB)	=	Final (dB $\mu$ V/m)	-	FCC B (dB $\mu$ V/m)	=	Delta FCC B (dB)
32.21	13.9	+	16.3	=	30.2	-	40.0	=	-9.8

**DETAILS OF TEST PROCEDURES****General Standard Information**

The test methods used comply with ANSI C63.4-1992 - "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz."

**Conducted Emissions**

Conducted emissions on the 60 Hz power interface of the EUT are measured in the frequency range of 450 kHz to 30 MHz. The measurements are performed using a receiver, which has CISPR characteristic bandwidth and quasi-peak detection, and a Line Impedance Stabilization Network (LISN), with  $50\ \Omega/50\ \mu\text{H}$  (CISPR 16) characteristics. Table top equipment is placed on a non-conducting table 80 centimeters above the floor and is positioned 40 centimeters from the vertical ground plane (wall) of the screen room. In some cases, a pre-scan using a spectrum analyzer is initially performed on the units comprising the system under test to locate the highest emissions. If the minimum passing margin appears to be less than 20 dB with a peak mode measurement, the emissions are re-measured using a tuned receiver or spectrum analyzer with quasi-peak and average detection and recorded on the data sheets.

**Radiated Emissions**

Radiated emissions from the EUT are measured in the frequency range of 30 to 1000 MHz using a spectrum analyzer and appropriate broadband linearly polarized antennas. Measurements between 30 MHz and 1000 MHz are made with 120 kHz/6 dB bandwidth and quasi-peak detection and measurements above 1000 MHz are made with a 1 MHz/6 dB bandwidth and peak detection. Table top equipment is placed on a 1.0 X 1.5 meter non-conducting table 80 centimeters above the ground plane. Floor standing equipment is placed directly on the turntable/ground plane. Interface cables that are closer than 40 centimeters to the ground plane are bundled in the center in a serpentine fashion so they are at least 40 centimeters from the ground plane. Cables to simulators/testers (if used in this test) are routed through the center of the table and to a screen room located outside the test area. The antenna is positioned 3 meters horizontally from the EUT. To locate maximum emissions from the test sample the antenna is varied in height from 1 to 4 meters, measurement scans are made with both horizontal and vertical antenna polarizations and the EUT are rotated 360 degrees.