



RADIO TEST REPORT

Test Report No. : 13367627H-B-R1

Applicant : DENSO CORPORATION
Type of EUT : Cockpit Control Unit (CCU)
Model Number of EUT : DNNS117
FCC ID : HYQDNNS117
Test regulation : FCC Part 15 Subpart C: 2020
*Bluetooth part
Test Result : Complied (Refer to SECTION 3.2)


1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.
5. This test report must not be used by the customer to claim product certification, approval, or endorsement by the A2LA accreditation body.
6. This test report covers Radio technical requirements.
It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
7. The all test items in this test report are conducted by UL Japan, Inc. Ise EMC Lab.
8. The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan has been accredited.
9. The information provided from the customer for this report is identified in SECTION 1.
10. This report is a revised version of 13367627H-B. 13367627H-B is replaced with this report.

Date of test: May 24 to September 19, 2020

Representative test engineer:


Yuta Moriya
Engineer
Consumer Technology Division

Approved by:


Tsubasa Takayama
Leader
Consumer Technology Division



CERTIFICATE 5107.02

- ☐ The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan.
☒ There is no testing item of "Non-accreditation".

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

REVISION HISTORY

Original Test Report No.: 13367627H-B

Revision	Test report No.	Date	Page revised	Contents
- (Original)	13367627H-B	September 25, 2020	-	-
1	13367627H-B-R1	October 20, 2020	P.14	Addition of Remarks for Cable No.3

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Reference: Abbreviations (Including words undescribed in this report)

A2LA	The American Association for Laboratory Accreditation	MCS	Modulation and Coding Scheme
AC	Alternating Current	MRA	Mutual Recognition Arrangement
AFH	Adaptive Frequency Hopping	N/A	Not Applicable
AM	Amplitude Modulation	NIST	National Institute of Standards and Technology
Amp, AMP	Amplifier	NS	No signal detect.
ANSI	American National Standards Institute	NSA	Normalized Site Attenuation
Ant, ANT	Antenna	NVLAP	National Voluntary Laboratory Accreditation Program
AP	Access Point	OBW	Occupied Band Width
ASK	Amplitude Shift Keying	OFDM	Orthogonal Frequency Division Multiplexing
Atten., ATT	Attenuator	P/M	Power meter
AV	Average	PCB	Printed Circuit Board
BPSK	Binary Phase-Shift Keying	PER	Packet Error Rate
BR	Bluetooth Basic Rate	PHY	Physical Layer
BT	Bluetooth	PK	Peak
BT LE	Bluetooth Low Energy	PN	Pseudo random Noise
BW	BandWidth	PRBS	Pseudo-Random Bit Sequence
Cal Int	Calibration Interval	PSD	Power Spectral Density
CCK	Complementary Code Keying	QAM	Quadrature Amplitude Modulation
Ch., CH	Channel	QP	Quasi-Peak
CISPR	Comite International Special des Perturbations Radioelectriques	QPSK	Quadri-Phase Shift Keying
CW	Continuous Wave	RBW	Resolution Band Width
DBPSK	Differential BPSK	RDS	Radio Data System
DC	Direct Current	RE	Radio Equipment
D-factor	Distance factor	RF	Radio Frequency
DFS	Dynamic Frequency Selection	RMS	Root Mean Square
DQPSK	Differential QPSK	RSS	Radio Standards Specifications
DSSS	Direct Sequence Spread Spectrum	Rx	Receiving
EDR	Enhanced Data Rate	SA, S/A	Spectrum Analyzer
EIRP, e.i.r.p.	Equivalent Isotropically Radiated Power	SG	Signal Generator
EMC	ElectroMagnetic Compatibility	SVSWR	Site-Voltage Standing Wave Ratio
EMI	ElectroMagnetic Interference	TR	Test Receiver
EN	European Norm	Tx	Transmitting
ERP, e.r.p.	Effective Radiated Power	VBW	Video BandWidth
EU	European Union	Vert.	Vertical
EUT	Equipment Under Test	WLAN	Wireless LAN
Fac.	Factor		
FCC	Federal Communications Commission		
FHSS	Frequency Hopping Spread Spectrum		
FM	Frequency Modulation		
Freq.	Frequency		
FSK	Frequency Shift Keying		
GFSK	Gaussian Frequency-Shift Keying		
GNSS	Global Navigation Satellite System		
GPS	Global Positioning System		
Hori.	Horizontal		
ICES	Interference-Causing Equipment Standard		
IEC	International Electrotechnical Commission		
IEEE	Institute of Electrical and Electronics Engineers		
IF	Intermediate Frequency		
ILAC	International Laboratory Accreditation Conference		
ISED	Innovation, Science and Economic Development Canada		
ISO	International Organization for Standardization		
JAB	Japan Accreditation Board		
LAN	Local Area Network		
LIMS	Laboratory Information Management System		

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

CONTENTS	PAGE
SECTION 1: Customer information.....	5
SECTION 2: Equipment under test (EUT).....	5
SECTION 3: Test specification, procedures & results.....	7
SECTION 4: Operation of EUT during testing.....	11
SECTION 5: Radiated Spurious Emission	16
SECTION 6: Antenna Terminal Conducted Tests.....	18
APPENDIX 1: Test data	19
20dB Bandwidth, 99%Occupied Bandwidth and Carrier Frequency Separation	19
Number of Hopping Frequency	23
Dwell time.....	25
Maximum Peak Output Power.....	28
Average Output Power.....	29
Radiated Spurious Emission	31
Conducted Spurious Emission	42
Conducted Emission Band Edge compliance	48
APPENDIX 2: Test instruments	50
APPENDIX 3: Photographs of test setup	52
Radiated Spurious Emission	52
Antenna Terminal Conducted Tests.....	54

SECTION 1: Customer information

Company Name	:	DENSO CORPORATION
Address	:	1-1 Showa-cho, Kariya-shi, Aichi ken, 448-8661 Japan
Telephone Number	:	+81-566-20-3304
Facsimile Number	:	+81-566-25-4920
Contact Person	:	Naoto Makino

The information provided from the customer is as follows;

- Applicant, Type of EUT, Model Number of EUT, FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer information
- SECTION 2: Equipment under test (EUT) other than the Receipt Date
- SECTION 4: Operation of EUT during testing

* The laboratory is exempted from liability of any test results affected from the above information in SECTION 2 and 4.

SECTION 2: Equipment under test (EUT)

2.1 Identification of EUT

Type	:	Cockpit Control Unit (CCU)
Model Number	:	DNNS117
Serial Number	:	Refer to SECTION 4.2
Rating	:	DC 13.2 V
Receipt Date	:	May 21, 2020
Country of Mass-production	:	Japan
Condition	:	Production prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification	:	No Modification by the test lab.

2.2 Product Description

Model: DNNS117 (referred to as the EUT in this report) is a Cockpit Control Unit (CCU).

Radio Specification

Clock frequency (Maximum) : 40 MHz

[AM/FM (incl.RBDS)/XM Radio]

	AM	FM (incl. RBDS)	XM
Equipment type	Receiver		
Frequency of operation	530 kHz to 1710 kHz	87.75 MHz to 107.9 MHz	2333.465 MHz to 2344.045 MHz
Antenna connector type	GT13		

[WLAN (IEEE802.11b/g/n-20) / Bluetooth (Ver4.2 BR/EDR)]

	IEEE802.11b	IEEE802.11g/n (20 M band)	Bluetooth
Equipment type	Transceiver		
Frequency of operation	2412 MHz to 2462 MHz	2412 MHz to 2462 MHz	2402 MHz to 2480 MHz
Type of modulation	DSSS (CCK, DQPSK, DBPSK)	OFDM (64QAM, 16QAM, QPSK, BPSK)	FHSS (GFSK, $\pi/4$ -DQPSK, 8-DPSK)
Channel spacing	5MHz		1 MHz
Antenna type	ASSEMBLY Bluetooth/WiFi Antenna		
Antenna Connector type	MHF PLUG		
Antenna Gain	-4.15 dBi		1.35 dBi

* This test report applied to Bluetooth.

* WLAN and Bluetooth do not transmit simultaneously.

SECTION 3: Test specification, procedures & results

3.1 Test Specification

Test Specification : FCC Part 15 Subpart C
FCC Part 15 final revised on June 26, 2020 and effective July 27, 2020

Title : FCC 47 CFR Part 15 Radio Frequency Device Subpart C Intentional Radiators
Section 15.207 Conducted limits
Section 15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz,
and 5725-5850 MHz

* The revision does not affect the test result conducted before its effective date.

3.2 Procedures and results

Item	Test Procedure	Specification	Worst Margin	Results	Remarks
Conducted Emission	FCC: ANSI C63.10-2013 6. Standard test methods ISED: RSS-Gen 8.8	FCC: Section 15.207 ISED: RSS-Gen 8.8	N/A	N/A	*1)
Carrier Frequency Separation	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section 15.247(a)(1) ISED: RSS-247 5.1 (b)	See data.	Complied a)	Conducted
20dB Bandwidth	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section 15.247(a)(1) ISED: RSS-247 5.1 (a)		Complied a)	Conducted
Number of Hopping Frequency	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section 15.247(a)(1)(iii) ISED: RSS-247 5.1 (d)		Complied b)	Conducted
Dwell time	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section 15.247(a)(1)(iii) ISED: RSS-247 5.1 (d)		Complied c)	Conducted
Maximum Peak Output Power	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: RSS-Gen 6.12	FCC: Section 15.247(a)(b)(1) ISED: RSS-247 5.4 (b)		Complied d)	Conducted
Spurious Emission & Band Edge Compliance	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: RSS-Gen 6.13	FCC: Section 15.247(d) ISED: RSS-247 5.5 RSS-Gen 8.9 RSS-Gen 8.10	1.4 dB 7206.000 MHz, AV, Vert.	Complied e) / f)	Conducted/ Radiated (above 30 MHz) *2)

Note: UL Japan, Inc.'s EMI Work Procedures No. 13-EM-W0420 and 13-EM-W0422.

*1) The test is not applicable since the EUT is not the device that is designed to be connected to the public utility (AC) power line.

*2) Radiated test was selected over 30 MHz based on section 15.247(d).

a) Refer to APPENDIX 1 (data of 20dB Bandwidth, 99% Occupied Bandwidth and Carrier Frequency Separation)

b) Refer to APPENDIX 1 (data of Number of Hopping Frequency)

c) Refer to APPENDIX 1 (data of Dwell time)

d) Refer to APPENDIX 1 (data of Maximum Peak Output Power)

e) Refer to APPENDIX 1 (data of Conducted Spurious Emission)

f) Refer to APPENDIX 1 (data of Radiated Spurious Emission)

Symbols:

Complied The data of this test item has enough margin, more than the measurement uncertainty.

Complied# The data of this test item meets the limits unless the measurement uncertainty is taken into consideration.

* In case any questions arise about test procedure, ANSI C63.10: 2013 is also referred.

FCC Part 15.31 (e)

The EUT provides stable voltage constantly to the wireless transmitter regardless of input voltage.

Instead of a new battery, DC power supply was used for the test.

That does not affect the test result, therefore the EUT complies with the requirement.

FCC Part 15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the vehicle. Therefore, the equipment complies with the antenna requirement of Section 15.203.

3.3 Addition to standard

Item	Test Procedure	Specification	Worst margin	Results	Remarks
99% Occupied Bandwidth	ISED: RSS-Gen 6.7	ISED: -	N/A	- a)	Conducted
a) Refer to APPENDIX 1 (data of 20dB Bandwidth, 99% Occupied Bandwidth and Carrier Frequency Separation)					

Other than above, no addition, exclusion nor deviation has been made from the standard.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

3.4 Uncertainty

There is no applicable rule of uncertainty in this applied standard. Therefore, the results are derived depending on whether or not laboratory uncertainty is applied.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor $k=2$.
Ise EMC Lab.

Antenna Terminal test

Test Item	Uncertainty (+/-)
20 dB Bandwidth / 99 % Occupied Bandwidth	0.96 %
Maximum Peak Output Power / Average Output Power	1.4 dB
Carrier Frequency Separation	0.42 %
Dwell time / Burst rate	0.10 %
Conducted Spurious Emission	2.6 dB

Radiated emission

Measurement distance	Frequency range	Uncertainty (+/-)
3 m	9 kHz to 30 MHz	3.3 dB
10 m		3.2 dB
3 m	30 MHz to 200 MHz (Horizontal) (Vertical)	4.8 dB
		5.0 dB
	200 MHz to 1000 MHz (Horizontal) (Vertical)	5.2 dB
		6.3 dB
10 m	30 MHz to 200 MHz (Horizontal) (Vertical)	4.8 dB
		4.8 dB
	200 MHz to 1000 MHz (Horizontal) (Vertical)	5.0 dB
		5.0 dB
3 m	1 GHz to 6 GHz	4.9 dB
	6 GHz to 18 GHz	5.2 dB
1 m	10 GHz to 26.5 GHz	5.5 dB
	26.5 GHz to 40 GHz	5.5 dB
0.5 m	26.5 GHz to 40 GHz	5.5 dB
10 m	1 GHz to 18 GHz	5.2 dB

3.5 Test Location

UL Japan, Inc. Ise EMC Lab.

*A2LA Certificate Number: 5107.02 / FCC Test Firm Registration Number: 199967 / ISED Lab Company Number: 2973C

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone: +81 596 24 8999, Facsimile: +81 596 24 8124

Test site	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms	Maximum measurement distance
No.1 semi-anechoic chamber	19.2 x 11.2 x 7.7	7.0 x 6.0	No.1 Power source room	10 m
No.2 semi-anechoic chamber	7.5 x 5.8 x 5.2	4.0 x 4.0	-	3 m
No.3 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.3 Preparation room	3 m
No.3 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.4 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.4 Preparation room	3 m
No.4 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.5 semi-anechoic chamber	6.0 x 6.0 x 3.9	6.0 x 6.0	-	-
No.5 measurement room	6.4 x 6.4 x 3.0	6.4 x 6.4	-	-
No.6 shielded room	4.0 x 4.5 x 2.7	4.0 x 4.5	-	-
No.6 measurement room	4.75 x 5.4 x 3.0	4.75 x 4.15	-	-
No.7 shielded room	4.7 x 7.5 x 2.7	4.7 x 7.5	-	-
No.8 measurement room	3.1 x 5.0 x 2.7	3.1 x 5.0	-	-
No.9 measurement room	8.8 x 4.6 x 2.8	2.4 x 2.4	-	-
No.11 measurement room	6.2 x 4.7 x 3.0	4.8 x 4.6	-	-

* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0 m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

3.6 Test data, Test instruments, and Test set up

Refer to APPENDIX.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 4: Operation of EUT during testing

4.1 Operating Mode(s)


Bluetooth (BT): Transmitting (Tx), Payload: PRBS9

Details of Operating Mode(s)

Test Item	Mode	Tested frequency
Spurious Emission (Conducted/Radiated)	Tx (Hopping Off) DH5, 3DH5	2402 MHz 2441 MHz 2480 MHz
Carrier Frequency Separation	Tx (Hopping On) DH5, 3DH5	2402 MHz 2441 MHz 2480 MHz
20dB Bandwidth	Tx (Hopping Off) DH5, 3DH5	2402 MHz 2441 MHz 2480 MHz
Number of Hopping Frequency	Tx (Hopping On) DH5, 3DH5	-
Dwell time	Tx (Hopping On), -DH1, DH3, DH5 -3DH1, 3DH3, 3DH5	-
Maximum Peak Output Power	Tx (Hopping Off) DH5, 2DH5, 3DH5	2402 MHz 2441 MHz 2480 MHz
Band Edge Compliance (Conducted)	Tx DH5, 3DH5 -Hopping On -Hopping Off	2402 MHz 2480 MHz
99% Occupied Bandwidth	Tx DH5, 3DH5 -Hopping On -Hopping Off	2402 MHz 2441 MHz 2480 MHz
*As a result of preliminary test, the formal test was performed with the above modes, which had the maximum payload length (except Dwell time test) *2DH mode (2Mb/s EDR: pi/4DQPSK) was excluded for other tests than power measurement by using 3DH mode (3 Mb/s EDR: 8DPSK) as a representative. * It is considered that the non-tested packet type (e.g. inquiry) can be omitted as it is complied with above all the test items based on Bluetooth Core specification. *EUT has the power settings by the software as follows; Power settings: -3 dBm (BR) -5 dBm (EDR) Software: MSoC ver : F21SHM003-006 (Date: May 24, 2020, Storage location: EUT memory) *This setting of software is the worst case. Any conditions under the normal use do not exceed the condition of setting. In addition, end users cannot change the settings of the output power of the product.		

4.2 Configuration and peripherals

Radiated Spurious Emission



* Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.

Description of EUT and Support equipment

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Cockpit Control Unit	DNNS117	RF6-US-K3-High-014	DENSO CORPORATION	EUT
B	Center Information Display	DNNS092	SD-EU-HM-RHD-058	DENSO CORPORATION	EUT
C	GPS Antenna	86277AL150	8980044	-	-
D	AUX-Box	86257FL001	20FHI-AUX-09	-	-
E	Speaker	-	-	-	-
F	Speaker	-	-	-	-
G	Speaker	-	-	-	-
H	Speaker	-	-	-	-
I	CAN Terminated	-	-	-	-
J	Meter	85002AN01A	TN257550-6760	DENSO CORPORATION	-
K	iPod touch	A1367	C3RJ4SLADT75	Apple	-
L	NFC Card Reader	ACR1251	RR395-0056500	Advanced Card Systems Ltd.	-
M	USB Memory	USM4GR B	17116 DGGNN	SONY	-

List of cables used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	DC Cable	3.0	Unshielded	Unshielded	-
2	WLAN Cable	0.2	Shielded	Shielded	-
3	BT Cable	0.2	Shielded	Shielded	-
4	LVDS Cable	0.2	Shielded	Shielded	-
5	DC Cable	0.2	Unshielded	Unshielded	-
6	AM/FM Antenna Cable	1.4	Shielded	Shielded	-
7	XM Antenna Cable	1.4	Shielded	Shielded	-
8	USB Cable	1.5	Shielded	Shielded	-
9	USB Cable	1.5	Shielded	Shielded	-
10	Signal Cable	1.7	Unshielded	Unshielded	-
11	GNSS Antenna Cable	1.3	Shielded	Shielded	-
12	USB Cable	0.4	Shielded	Shielded	-
13	Signal Cable	1.7	Unshielded	Unshielded	-
14	Speaker Cable	0.3	Unshielded	Unshielded	-
15	Speaker Cable	1.5	Unshielded	Unshielded	-
16	Speaker Cable	1.5	Unshielded	Unshielded	-
17	Speaker Cable	1.9	Unshielded	Unshielded	-
18	Signal Cable	1.7	Unshielded	Unshielded	-
19	Signal Cable	1.7	Unshielded	Unshielded	-
20	Meter Cable	1.7	Shielded	Shielded	-
21	Audio Cable	1.5	Shielded	Shielded	-
22	USB Cable	1.0	Shielded	Shielded	-
23	USB Cable	2.0	Shielded	Shielded	-
24	DC Cable	3.0	Unshielded	Unshielded	-

UL Japan, Inc.


Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Antenna Terminal Conducted Tests



* Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.

*1) The test was performed with cables 3 connected to the measurement equipment rather than to the EUT.

Description of EUT and Support equipment

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Cockpit Control Unit	DNNS117	RF6-US-K3-High-014	DENSO CORPORATION	EUT
B	Center Information Display	DNNS092	SD-EU-HM-RHD-058	DENSO CORPORATION	EUT
C	GPS Antenna	86277AL150	8980044	-	-
D	AUX-Box	86257FL001	20FHI-AUX-09	-	-
E	Speaker	-	-	-	-
F	Speaker	-	-	-	-
G	Speaker	-	-	-	-
H	Speaker	-	-	-	-
I	CAN Terminated	-	-	-	-
J	Meter	85002AN01A	TN257550-6760	DENSO CORPORATION	-
K	NFC Card Reader	ACR1251	RR395-0056500	Advanced Card Systems Ltd.	-
L	Laptop PC	CF-N8HWC DPS	0BKSA08704	Panasonic	-
M	AC Adapter	CF-AA6372B	6372BM40990732B	Panasonic	-

List of cables used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	DC Cable	3.0	Unshielded	Unshielded	-
2	WLAN Cable	0.2	Shielded	Shielded	-
3	BT Cable	0.2	Shielded	Shielded	-
4	LVDS Cable	0.2	Shielded	Shielded	-
5	DC Cable	0.2	Unshielded	Unshielded	-
6	AM/FM Antenna Cable	1.4	Shielded	Shielded	-
7	XM Antenna Cable	1.4	Shielded	Shielded	-
8	USB Cable	1.5	Shielded	Shielded	-
9	USB Cable	1.5	Shielded	Shielded	-
10	Signal Cable	1.7	Unshielded	Unshielded	-
11	GNSS Antenna Cable	1.3	Shielded	Shielded	-
12	USB Cable	0.4	Shielded	Shielded	-
13	Signal Cable	1.7	Unshielded	Unshielded	-
14	Speaker Cable	0.3	Unshielded	Unshielded	-
15	Speaker Cable	1.5	Unshielded	Unshielded	-
16	Speaker Cable	1.5	Unshielded	Unshielded	-
17	Speaker Cable	1.9	Unshielded	Unshielded	-
18	Signal Cable	1.7	Unshielded	Unshielded	-
19	Signal Cable	1.7	Unshielded	Unshielded	-
20	Meter Cable	1.7	Shielded	Shielded	-
21	USB Cable	1.0	Shielded	Shielded	-
22	USB + LAN Cable	2.2	USB: Shielded LAN: Unshielded	USB: Shielded LAN: Unshielded	-
23	DC Cable	1.0	Unshielded	Unshielded	-
24	AC Cable	1.0	Unshielded	Unshielded	-
25	DC Cable	3.0	Unshielded	Unshielded	-

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

SECTION 5: Radiated Spurious Emission

Test Procedure

[For below 1 GHz]

EUT was placed on a urethane platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[For above 1 GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 0.5 m, raised 1.5 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with absorbent materials lined on a ground plane.

The height of the measuring antenna varied between 1 m and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

Test antenna was aimed at the EUT for receiving the maximum signal and always kept within the illumination area of the 3 dB beamwidth of the antenna.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer.

The measurements were made with the following detector function of the test receiver and the Spectrum analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

Test Antennas are used as below;

Frequency	30 MHz to 200 MHz	200 MHz to 1 GHz	Above 1 GHz
Antenna Type	Biconical	Logperiodic	Horn

In any 100 kHz bandwidth outside the restricted band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.


20 dBc was applied to the frequency over the limit of FCC 15.209 / Table 4 of RSS-Gen 8.9 (ISED) and outside the restricted band of FCC15.205 / Table 6 of RSS-Gen 8.10 (ISED).

Frequency	Below 1 GHz	Above 1 GHz		20 dBc
Instrument used	Test Receiver	Spectrum Analyzer		Spectrum Analyzer
Detector	QP	PK	AV *1)	PK
IF Bandwidth	BW 120 kHz	RBW: 1 MHz VBW: 3 MHz	RBW: 1 MHz VBW: 3 MHz Detector: Power Averaging (RMS) Trace: 100 traces Duty factor was added to the results.	RBW: 100 kHz VBW: 300 kHz

*1) Average Power Measurement was performed based on KDB 558074 D01 15.247 Meas Guidance v05r02.

Figure 2: Test Setup


Below 1 GHz



x : Center of turn table

Test Distance: 3 m

1 GHz - 10 GHz



r : Radius of an outer periphery of EUT

x : Center of turn table

Distance Factor: $20 \times \log (3.9 \text{ m} / 3.0 \text{ m}) = 2.28 \text{ dB}$


* Test Distance: $(3 + \text{Test Volume} / 2) - r = 3.9 \text{ m}$

Test Volume : 2.0 m

(Test Volume has been calibrated based on CISPR 16-1-4.)

r = 0.1 m

10 GHz - 26.5 GHz



x : Center of turn table

Distance Factor: $20 \times \log (1.0 \text{ m} / 3.0 \text{ m}) = -9.5 \text{ dB}$

* Test Distance: 1 m

The carrier level and noise levels were confirmed at each position of 0 degree and 30 degree as tilt angle of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Measurement range : 30 MHz - 26.5 GHz

Test data : APPENDIX

Test result : Pass

SECTION 6: Antenna Terminal Conducted Tests

Test Procedure

The tests were made with below setting connected to the antenna port.

Test	Span	RBW	VBW	Sweep time	Detector	Trace	Instrument used
20dB Bandwidth	3 MHz	30 kHz	100 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
99% Occupied Bandwidth *1)	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak	Max Hold	Spectrum Analyzer
Maximum Peak Output Power	-	-	-	Auto	Peak Average *2)	-	Power Meter (Sensor: 50MHz BW)
Carrier Frequency Separation	3 MHz	30 kHz	100 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
Number of Hopping Frequency	30 MHz	200 kHz	620 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
Dwell Time	Zero Span	100 kHz, 1 MHz	300 kHz, 3 MHz	As necessary capture the entire dwell time per hopping channel	Peak	Clear Write	Spectrum Analyzer
Conducted Spurious Emission *3) *4)	9 kHz to 150 kHz	200 Hz	620 Hz	Auto	Peak	Max Hold	Spectrum Analyzer
	150 kHz to 30 MHz	9.1 kHz	27 kHz				
	30 MHz to 25 GHz	100 kHz	300 kHz				
Conducted Spurious Emission Band Edge compliance	10 MHz	100 kHz	300 kHz	Auto	Peak	Max Hold	Spectrum Analyzer

*1) Peak hold was applied as Worst-case measurement.

*2) Reference data

*3) In the frequency range below 30MHz, RBW was narrowed to separate the noise contents.

It was confirmed that the noise was low enough in the radiated emissions.

(9 kHz - 150 kHz: RBW = 200 Hz, 150 kHz - 30 MHz: RBW = 9.1 kHz).

*4) The limits in CFR 47, Part 15, Subpart C, paragraph 15.209(a), are identical to those in RSS-Gen section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377 Ohms. For example, the measurement at frequency 9 kHz resulted in a level of 45.5 dBuV/m, which is equivalent to $45.5 - 51.5 = -6.0$ dBuA/m, which has the same margin, 3 dB, to the corresponding RSS-Gen Table 6 limit as it has to 15.209(a) limit.

The test results and limit are rounded off to two decimals place, so some differences might be observed.

The equipment and cables were not used for factor 0 dB of the data sheets.

Test data : APPENDIX

Test result : Pass

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

APPENDIX 1: Test data

20dB Bandwidth, 99% Occupied Bandwidth and Carrier Frequency Separation


Report No.	13367627H	
Test place	Ise EMC Lab. No.6 Shielded Room	
Date	July 27, 2020	July 28, 2020
Temperature / Humidity	23 deg. C / 61 % RH	23 deg. C / 68 % RH
Engineer	Yuta Moriya	Yuta Moriya
Mode	Tx, Hopping Off, Tx, Hopping On	

Mode	Freq. [MHz]	20dB Bandwidth [MHz]	99% Occupied Bandwidth [kHz]	Carrier Frequency Separation [MHz]	Limit for Carrier Frequency separation [MHz]
DH5	2402.0	0.955	872.368	1.000	≥ 0.637
DH5	2441.0	0.958	884.067	1.000	≥ 0.639
DH5	2480.0	0.947	859.937	1.000	≥ 0.631
DH5	Hopping On	-	78596.900	-	-
3DH5	2402.0	1.296	1175.300	1.000	≥ 0.864
3DH5	2441.0	1.292	1178.200	1.000	≥ 0.861
3DH5	2480.0	1.297	1175.900	1.000	≥ 0.865
3DH5	Hopping On	-	78700.100	-	-

Limit: Two-thirds of 20dB Bandwidth or 25kHz (whichever is greater).

No limit applies to 20dB Bandwidth.

20dB Bandwidth and 99% Occupied Bandwidth



UL Japan, Inc.


Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

20dB Bandwidth and 99% Occupied Bandwidth



UL Japan, Inc.


Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Carrier Frequency Separation



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124


Number of Hopping Frequency

Report No. 13367627H
Test place Ise EMC Lab. No.6 Shielded Room
Date July 28, 2020
Temperature / Humidity 23 deg. C / 68 % RH
Engineer Yuta Moriya
Mode Tx, Hopping On

Mode	Number of channel [channels]	Limit [channels]
DH5	79	≥ 15
3DH5	79	≥ 15

Test was not performed at AFH mode whose number of hopping channel is 20 channels because this Bluetooth radio is in compliance of Bluetooth Specification.

Number of Hopping Frequency



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Dwell time

Report No.	13367627H
Test place	Ise EMC Lab. No.6 Shielded Room
Date	September 19, 2020
Temperature / Humidity	23 deg. C / 66 % RH
Engineer	Junki Nagatomi
Mode	Tx, Hopping On

Mode	Number of transmission in a 31.6(79 Hopping x 0.4) / 12.8 (32 Hopping x 0.4) second period				Length of transmission [msec]	Result [msec]	Limit [msec]
DH1	50.6 times	/	5 sec.	x	31.6 sec.	=	320 times
DH3	25.0 times	/	5 sec.	x	31.6 sec.	=	158 times
DH5	16.8 times	/	5 sec.	x	31.6 sec.	=	107 times
3DH1	50.4 times	/	5 sec.	x	31.6 sec.	=	319 times
3DH3	25.8 times	/	5 sec.	x	31.6 sec.	=	164 times
3DH5	16.8 times	/	5 sec.	x	31.6 sec.	=	107 times

Sample Calculation

Result = Number of transmission x Length of transmission

*Average data of 5 tests.(except Inquiry)


Mode	Sampling [times]					Average [times]
	1	2	3	4	5	
DH1	51	50	50	51	51	50.6
DH3	25	25	25	25	25	25
DH5	16	17	17	17	17	16.8
3DH1	50	51	50	51	50	50.4
3DH3	26	25	26	26	26	25.8
3DH5	17	17	17	16	17	16.8

Sample Calculation

Average = Summation (Sampling 1 to 5) / 5

This device complies with the Bluetooth protocol for FHSS operation, employing a pseudo random channel selection and hopping rate to ensure that the occupancy time in $N \times 0.4s$, where N is the number of channels being used in the hopping sequence ($20 \leq N \leq 79$), is always less than $0.4s$ regardless of packet size. This is confirmed in the test report for $N = 79$.

Dwell time



UL Japan, Inc.


Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Dwell time



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Maximum Peak Output Power

Report No.	13367627H
Test place	Ise EMC Lab. No.6 Shielded Room
Date	July 28, 2020
Temperature / Humidity	23 deg. C / 68 % RH
Engineer	Yuta Moriya
Mode	Tx, Hopping Off

Mode	Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Result		Limit		Margin [dB]	Antenna Gain [dBi]	Result		Limit		Margin [dB]
					[dBm]	[mW]	[dBm]	[mW]			[dBm]	[mW]	[dBm]	[mW]	
DH5	2402.0	-13.98	0.54	10.03	-3.41	0.46	20.96	125	24.37	1.35	-2.06	0.62	36.02	4000	38.08
DH5	2441.0	-13.61	0.39	10.03	-3.19	0.48	20.96	125	24.15	1.35	-1.84	0.65	36.02	4000	37.86
DH5	2480.0	-13.27	0.44	10.03	-2.81	0.52	20.96	125	23.77	1.35	-1.46	0.72	36.02	4000	37.48
2DH5	2402.0	-14.36	0.54	10.03	-3.79	0.42	20.96	125	24.75	1.35	-2.44	0.57	36.02	4000	38.46
2DH5	2441.0	-13.94	0.39	10.03	-3.52	0.44	20.96	125	24.48	1.35	-2.17	0.61	36.02	4000	38.19
2DH5	2480.0	-13.64	0.44	10.03	-3.18	0.48	20.96	125	24.14	1.35	-1.83	0.66	36.02	4000	37.85
3DH5	2402.0	-13.75	0.54	10.03	-3.18	0.48	20.96	125	24.14	1.35	-1.83	0.66	36.02	4000	37.85
3DH5	2441.0	-13.26	0.39	10.03	-2.84	0.52	20.96	125	23.80	1.35	-1.49	0.71	36.02	4000	37.51
3DH5	2480.0	-13.29	0.44	10.03	-2.83	0.52	20.96	125	23.79	1.35	-1.48	0.71	36.02	4000	37.50

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

e.i.p. Result = Conducted Power Result + Antenna Gain

Test was not performed at AFH mode, because the decrease of number of channel (min: 20ch) at AFH mode does not influence on the output power and bandwidth of the EUT.

As this device had AFH mode and frequency separation could not meet the requirement of over 20dB BW without 2/3 relaxation, 125mW power limit was applied to it.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Average Output Power (Reference data for RF Exposure)

Report No.	13367627H
Test place	Ise EMC Lab. No.6 Shielded Room
Date	July 28, 2020
Temperature / Humidity	23 deg. C / 68 % RH
Engineer	Yuta Moriya
Mode	Tx, Hopping Off

Mode	Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Result (Time average)		Duty factor [dB]	Result (Burst power average)	
					[dBm]	[mW]		[dBm]	[mW]
DH5	2402.0	-15.57	0.54	10.03	-5.00	0.32	1.10	-3.90	0.41
DH5	2441.0	-15.18	0.39	10.03	-4.76	0.33	1.10	-3.66	0.43
DH5	2480.0	-14.82	0.44	10.03	-4.36	0.37	1.10	-3.26	0.47
2DH5	2402.0	-18.27	0.54	10.03	-7.70	0.17	1.08	-6.62	0.22
2DH5	2441.0	-17.91	0.39	10.03	-7.49	0.18	1.08	-6.41	0.23
2DH5	2480.0	-17.70	0.44	10.03	-7.24	0.19	1.08	-6.16	0.24
3DH5	2402.0	-18.25	0.54	10.03	-7.68	0.17	1.08	-6.60	0.22
3DH5	2441.0	-17.71	0.39	10.03	-7.29	0.19	1.08	-6.21	0.24
3DH5	2480.0	-17.69	0.44	10.03	-7.23	0.19	1.08	-6.15	0.24

Sample Calculation:

Result (Time average) = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss


Result (Burst power average) = Time average + Duty factor

*The equipment and cables were not used for factor 0 dB of the data sheets.


Burst Rate Confirmation

Report No. 13367627H
Test place Ise EMC Lab. No.6 Shielded Room
Date June 5, 2020
Temperature / Humidity 24 deg. C / 56 % RH
Engineer Junya Okuno
Mode Tx, Hopping Off


DH5



2DH5



3DH5



Radiated Spurious Emission

Report No. 13367627H
Test place Ise EMC Lab.
Semi Anechoic Chamber No.4 No.3
Date May 24, 2020 July 19, 2020
Temperature / Humidity 22 deg. C / 58 % RH 25 deg. C / 60 % RH
Engineer Yuichiro Yamazaki Takafumi Noguchi
(1 GHz - 26.5 GHz) (Below 1 GHz)
Mode Tx, Hopping Off, DH5 2402 MHz

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	200.000	QP	48.0	11.4	9.2	32.0	-	36.6	43.5	6.9	
Hori.	208.000	QP	48.8	11.2	9.3	32.0	-	37.3	43.5	6.2	
Hori.	216.000	QP	53.5	11.1	9.4	32.0	-	41.9	43.5	1.6	
Hori.	224.000	QP	51.5	11.1	9.4	32.0	-	40.0	46.0	6.0	
Hori.	232.000	QP	47.5	11.3	9.5	32.0	-	36.3	46.0	9.8	
Hori.	248.000	QP	46.3	11.7	9.6	32.0	-	35.7	46.0	10.4	
Hori.	2390.000	PK	42.1	27.7	5.7	31.9	-	43.6	73.9	30.3	
Hori.	4804.000	PK	39.0	31.6	7.9	31.3	-	47.1	73.9	26.8	Floor noise
Hori.	7206.000	PK	45.5	36.0	9.3	32.4	-	58.4	73.9	15.5	
Hori.	9608.000	PK	40.7	38.5	10.2	32.8	-	56.6	73.9	17.3	Floor noise
Hori.	2390.000	AV	28.4	27.7	5.7	31.9	1.1	31.0	53.9	22.9	*1)
Hori.	4804.000	AV	28.7	31.6	7.9	31.3	-	36.9	53.9	17.0	Floor noise
Hori.	7206.000	AV	35.6	36.0	9.3	32.4	1.1	49.6	53.9	4.4	
Hori.	9608.000	AV	28.4	38.5	10.2	32.8	-	44.3	53.9	9.6	Floor noise
Vert.	200.000	QP	44.8	11.4	9.2	32.0	-	33.4	43.5	10.1	
Vert.	208.000	QP	42.2	11.2	9.3	32.0	-	30.7	43.5	12.8	
Vert.	216.000	QP	50.4	11.1	9.4	32.0	-	38.8	43.5	4.7	
Vert.	224.000	QP	46.0	11.1	9.4	32.0	-	34.5	46.0	11.5	
Vert.	232.000	QP	42.5	11.3	9.5	32.0	-	31.3	46.0	14.8	
Vert.	248.000	QP	37.8	11.7	9.6	32.0	-	27.2	46.0	18.9	
Vert.	2390.000	PK	41.1	27.7	5.7	31.9	-	42.6	73.9	31.3	
Vert.	4804.000	PK	39.9	31.6	7.9	31.3	-	48.1	73.9	25.8	Floor noise
Vert.	7206.000	PK	46.4	36.0	9.3	32.4	-	59.3	73.9	14.6	
Vert.	9608.000	PK	41.0	38.5	10.2	32.8	-	57.0	73.9	16.9	Floor noise
Vert.	2390.000	AV	28.7	27.7	5.7	31.9	1.1	31.3	53.9	22.6	*1)
Vert.	4804.000	AV	27.6	31.6	7.9	31.3	-	35.7	53.9	18.2	Floor noise
Vert.	7206.000	AV	38.5	36.0	9.3	32.4	1.1	52.5	53.9	1.4	
Vert.	9608.000	AV	29.2	38.5	10.2	32.8	-	45.1	53.9	8.8	Floor noise

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Distance factor: 1 GHz - 10 GHz 20log (3.9 m / 3.0 m) = 2.28 dB

10 GHz - 26.5 GHz 20log (1.0 m / 3.0 m) = -9.5 dB

*1) Not Out of Band emission(Leakage Power)

20dBc Data Sheet

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori	2402.000	PK	85.8	27.7	5.7	31.9	87.3	-	-	Carrier
Hori	2400.000	PK	36.4	27.7	5.7	31.9	37.9	67.3	29.4	
Vert	2402.000	PK	78.7	27.7	5.7	31.9	80.2	-	-	Carrier
Vert	2400.000	PK	34.9	27.7	5.7	31.9	36.3	60.2	23.8	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)

Distance factor: 1 GHz - 10 GHz 20log (3.9 m / 3.0 m) = 2.28 dB

UL Japan, Inc.

Ise EMC Lab.



4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission (Reference Plot for band-edge)

Report No.	13367627H
Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.4
Date	May 24, 2020
Temperature / Humidity	22 deg. C / 58 % RH
Engineer	Yuichiro Yamazaki
	(1 GHz -26.5 GHz)
Mode	Tx, Hopping Off, DH5 2402 MHz



* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.

Final result of restricted band edge was shown in tabular data.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Report No.	13367627H		
Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.3	No.3	No.3
Date	July 17, 2020	July 19, 2020	July 19, 2020
Temperature / Humidity	20 deg. C / 56 % RH	23 deg. C / 70 % RH	25 deg. C / 60 % RH
Engineer	Junya Okuno	Junya Okuno	Takafumi Noguchi
	(1 GHz - 10 GHz)	(10 GHz - 26.5 GHz)	(Below 1 GHz)
Mode	Tx, Hopping Off, DH5 2441 MHz		

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	200.000	QP	48.1	11.4	9.2	32.0	-	36.7	43.5	6.8	
Hori.	208.000	QP	49.1	11.2	9.3	32.0	-	37.6	43.5	5.9	
Hori.	216.000	QP	53.3	11.1	9.4	32.0	-	41.7	43.5	1.8	
Hori.	224.000	QP	51.2	11.1	9.4	32.0	-	39.7	46.0	6.3	
Hori.	232.000	QP	47.2	11.3	9.5	32.0	-	36.0	46.0	10.1	
Hori.	248.000	QP	46.3	11.7	9.6	32.0	-	35.7	46.0	10.4	
Hori.	4882.000	PK	40.9	31.5	7.5	31.6	-	48.3	73.9	25.6	Floor noise
Hori.	7323.000	PK	44.2	36.2	8.9	32.6	-	56.7	73.9	17.2	
Hori.	9764.000	PK	44.3	38.8	9.4	33.4	-	59.1	73.9	14.8	Floor noise
Hori.	4882.000	AV	28.8	31.5	7.5	31.6	-	36.2	53.9	17.7	Floor noise
Hori.	7323.000	AV	38.3	36.2	8.9	32.6	1.1	51.9	53.9	2.0	
Hori.	9764.000	AV	30.4	38.8	9.4	33.4	-	45.2	53.9	8.7	Floor noise
Vert.	200.000	QP	44.5	11.4	9.2	32.0	-	33.1	43.5	10.4	
Vert.	208.000	QP	42.4	11.2	9.3	32.0	-	30.9	43.5	12.6	
Vert.	216.000	QP	50.2	11.1	9.4	32.0	-	38.6	43.5	4.9	
Vert.	224.000	QP	45.9	11.1	9.4	32.0	-	34.4	46.0	11.6	
Vert.	232.000	QP	42.5	11.3	9.5	32.0	-	31.3	46.0	14.8	
Vert.	248.000	QP	37.6	11.7	9.6	32.0	-	27.0	46.0	19.1	
Vert.	4882.000	PK	40.8	31.5	7.5	31.6	-	48.2	73.9	25.7	Floor noise
Vert.	7323.000	PK	44.7	36.2	8.9	32.6	-	57.1	73.9	16.8	
Vert.	9764.000	PK	44.5	38.8	9.4	33.4	-	59.3	73.9	14.6	Floor noise
Vert.	4882.000	AV	28.5	31.5	7.5	31.6	-	35.9	53.9	18.0	Floor noise
Vert.	7323.000	AV	38.7	36.2	8.9	32.6	1.1	52.3	53.9	1.6	
Vert.	9764.000	AV	30.3	38.8	9.4	33.4	-	45.1	53.9	8.8	Floor noise

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Distance factor: 1 GHz - 10 GHz $20\log(3.9\text{ m} / 3.0\text{ m}) = 2.28\text{ dB}$
 10 GHz - 26.5 GHz $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.5\text{ dB}$

Radiated Spurious Emission

Report No.	13367627H		
Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.3	No.3	No.3
Date	July 17, 2020	July 19, 2020	July 19, 2020
Temperature / Humidity	20 deg. C / 56 % RH	23 deg. C / 70 % RH	25 deg. C / 60 % RH
Engineer	Junya Okuno	Junya Okuno	Takafumi Noguchi
	(1 GHz - 10 GHz)	(10 GHz - 26.5 GHz)	(Below 1 GHz)
Mode	Tx, Hopping Off, DH5 2480 MHz		

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	200.000	QP	48.1	11.4	9.2	32.0	-	36.7	43.5	6.8	
Hori.	208.000	QP	49.0	11.2	9.3	32.0	-	37.5	43.5	6.0	
Hori.	216.000	QP	53.4	11.1	9.4	32.0	-	41.8	43.5	1.7	
Hori.	224.000	QP	51.3	11.1	9.4	32.0	-	39.8	46.0	6.2	
Hori.	232.000	QP	47.2	11.3	9.5	32.0	-	36.0	46.0	10.1	
Hori.	248.000	QP	46.3	11.7	9.6	32.0	-	35.7	46.0	10.4	
Hori.	2483.500	PK	42.7	27.5	5.4	32.7	-	42.9	73.9	31.0	
Hori.	4960.000	PK	40.4	31.6	7.5	31.6	-	47.8	73.9	26.1	Floor noise
Hori.	7440.000	PK	44.3	36.3	8.9	32.7	-	56.8	73.9	17.1	
Hori.	9920.000	PK	43.6	38.9	9.4	33.5	-	58.5	73.9	15.4	Floor noise
Hori.	2483.500	AV	34.4	27.5	5.4	32.7	1.1	35.7	53.9	18.2	*1)
Hori.	4960.000	AV	30.8	31.6	7.5	31.6	-	38.2	53.9	15.7	Floor noise
Hori.	7440.000	AV	38.2	36.3	8.9	32.7	1.1	51.8	53.9	2.1	
Hori.	9920.000	AV	31.8	38.9	9.4	33.5	-	46.6	53.9	7.3	Floor noise
Vert.	200.000	QP	44.2	11.4	9.2	32.0	-	32.8	43.5	10.7	
Vert.	208.000	QP	42.3	11.2	9.3	32.0	-	30.8	43.5	12.7	
Vert.	216.000	QP	50.4	11.1	9.4	32.0	-	38.8	43.5	4.7	
Vert.	224.000	QP	45.9	11.1	9.4	32.0	-	34.4	46.0	11.6	
Vert.	232.000	QP	42.6	11.3	9.5	32.0	-	31.4	46.0	14.7	
Vert.	248.000	QP	37.4	11.7	9.6	32.0	-	26.8	46.0	19.3	
Vert.	2483.500	PK	43.0	27.5	5.4	32.7	-	43.2	73.9	30.7	
Vert.	4960.000	PK	40.4	31.6	7.5	31.6	-	47.9	73.9	26.0	Floor noise
Vert.	7440.000	PK	44.1	36.3	8.9	32.7	-	56.6	73.9	17.3	
Vert.	9920.000	PK	43.5	38.9	9.4	33.5	-	58.4	73.9	15.5	Floor noise
Vert.	2483.500	AV	33.8	27.5	5.4	32.7	1.1	35.1	53.9	18.8	*1)
Vert.	4960.000	AV	30.9	31.6	7.5	31.6	-	38.3	53.9	15.6	Floor noise
Vert.	7440.000	AV	36.9	36.3	8.9	32.7	1.1	50.5	53.9	3.4	
Vert.	9920.000	AV	31.8	38.9	9.4	33.5	-	46.7	53.9	7.2	Floor noise

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor



*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Distance factor: 1 GHz - 10 GHz 20log (3.9 m / 3.0 m) = 2.28 dB
10 GHz - 26.5 GHz 20log (1.0 m / 3.0 m) = -9.5 dB

*1) Not Out of Band emission(Leakage Power)

Radiated Spurious Emission (Reference Plot for band-edge)

Report No.	13367627H
Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.3
Date	July 17, 2020
Temperature / Humidity	20 deg. C / 56 % RH
Engineer	Junya Okuno
	(1 GHz - 10 GHz)
Mode	Tx, Hopping Off, DH5 2480 MHz



* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.

Final result of restricted band edge was shown in tabular data.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Report No.	13367627H		
Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.3	No.3	No.3
Date	July 18, 2020	July 19, 2020	July 19, 2020
Temperature / Humidity	23 deg. C / 56 % RH	23 deg. C / 70 % RH	25 deg. C / 60 % RH
Engineer	Junya Okuno	Junya Okuno	Takafumi Noguchi
	(1 GHz - 10 GHz)	(10 GHz - 26.5 GHz)	(Below 1 GHz)
Mode	Tx, Hopping Off, 3DH5 2402 MHz		

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	200.000	QP	47.9	11.4	9.2	32.0	-	36.5	43.5	7.0	
Hori.	208.000	QP	49.0	11.2	9.3	32.0	-	37.5	43.5	6.0	
Hori.	216.000	QP	53.4	11.1	9.4	32.0	-	41.8	43.5	1.7	
Hori.	224.000	QP	51.2	11.1	9.4	32.0	-	39.7	46.0	6.3	
Hori.	232.000	QP	47.2	11.3	9.5	32.0	-	36.0	46.0	10.1	
Hori.	248.000	QP	46.2	11.7	9.6	32.0	-	35.6	46.0	10.5	
Hori.	2322.062	PK	43.7	27.9	5.3	32.8	-	44.2	73.9	29.7	
Hori.	2390.000	PK	42.1	27.7	5.4	32.7	-	42.4	73.9	31.5	
Hori.	4804.000	PK	40.4	31.6	7.5	31.7	-	47.8	73.9	26.1	Floor noise
Hori.	7206.000	PK	44.0	36.0	8.9	32.6	-	56.2	73.9	17.7	
Hori.	9608.000	PK	44.1	38.5	9.4	33.3	-	58.7	73.9	15.2	Floor noise
Hori.	2322.062	AV	38.0	27.9	5.3	32.8	1.1	39.5	53.9	14.4	*2)
Hori.	2390.000	AV	33.7	27.7	5.4	32.7	1.1	35.1	53.9	18.8	*1)
Hori.	4804.000	AV	28.8	31.6	7.5	31.7	-	36.2	53.9	17.7	Floor noise
Hori.	7206.000	AV	37.5	36.0	8.9	32.6	1.1	50.8	53.9	3.1	
Hori.	9608.000	AV	31.1	38.5	9.4	33.3	-	45.7	53.9	8.2	Floor noise
Vert.	200.000	QP	44.0	11.4	9.2	32.0	-	32.6	43.5	10.9	
Vert.	208.000	QP	42.3	11.2	9.3	32.0	-	30.8	43.5	12.7	
Vert.	216.000	QP	50.3	11.1	9.4	32.0	-	38.7	43.5	4.8	
Vert.	224.000	QP	45.9	11.1	9.4	32.0	-	34.4	46.0	11.6	
Vert.	232.000	QP	42.5	11.3	9.5	32.0	-	31.3	46.0	14.8	
Vert.	248.000	QP	37.3	11.7	9.6	32.0	-	26.7	46.0	19.4	
Vert.	2390.000	PK	42.9	27.7	5.4	32.7	-	43.2	73.9	30.7	
Vert.	4804.000	PK	40.3	31.6	7.5	31.7	-	47.7	73.9	26.2	Floor noise
Vert.	7206.000	PK	46.0	36.0	8.9	32.6	-	58.3	73.9	15.6	
Vert.	9608.000	PK	44.2	38.5	9.4	33.3	-	58.8	73.9	15.1	Floor noise
Vert.	2390.000	AV	33.8	27.7	5.4	32.7	1.1	35.2	53.9	18.7	*1)
Vert.	4804.000	AV	28.8	31.6	7.5	31.7	-	36.2	53.9	17.7	Floor noise
Vert.	7206.000	AV	39.0	36.0	8.9	32.6	1.1	52.4	53.9	1.5	
Vert.	9608.000	AV	31.1	38.5	9.4	33.3	-	45.7	53.9	8.2	Floor noise

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Distance factor: 1 GHz - 10 GHz $20\log(3.9\text{ m} / 3.0\text{ m}) = 2.28\text{ dB}$
10 GHz - 26.5 GHz $20\log(1.0\text{ m} / 3.0\text{ m}) = -9.5\text{ dB}$

*1) Not Out of Band emission(Leakage Power)

*2) Noise synchronized with duty of carrier frequency.

20dBc Data Sheet

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	2402.000	PK	83.1	27.7	5.4	32.7	83.4	-	-	Carrier
Hori.	2400.000	PK	35.9	27.7	5.4	32.7	36.3	63.4	27.2	
Vert.	2402.000	PK	79.2	27.7	5.4	32.7	79.5	-	-	Carrier
Vert.	2400.000	PK	35.0	27.7	5.4	32.7	35.3	59.5	24.1	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)

Distance factor: 1 GHz - 10 GHz $20\log(3.9\text{ m} / 3.0\text{ m}) = 2.28\text{ dB}$

UL Japan, Inc.

Ise EMC Lab.



4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission (Reference Plot for band-edge)

Report No.	13367627H
Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.3
Date	July 18, 2020
Temperature / Humidity	23 deg. C / 56 % RH
Engineer	Junya Okuno
	(1 GHz - 10 GHz)
Mode	Tx, Hopping Off, 3DH5 2402 MHz



* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.

Final result of restricted band edge was shown in tabular data.

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission

Report No.	13367627H		
Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.3	No.3	No.3
Date	July 18, 2020	July 19, 2020	July 19, 2020
Temperature / Humidity	23 deg. C / 56 % RH	23 deg. C / 70 % RH	25 deg. C / 60 % RH
Engineer	Junya Okuno	Junya Okuno	Takafumi Noguchi
	(1 GHz - 10 GHz)	(10 GHz - 26.5 GHz)	(Below 1 GHz)
Mode	Tx, Hopping Off, 3DH5 2441 MHz		

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	200.000	QP	48.0	11.4	9.2	32.0	-	36.6	43.5	6.9	
Hori.	208.000	QP	48.9	11.2	9.3	32.0	-	37.4	43.5	6.1	
Hori.	216.000	QP	53.4	11.1	9.4	32.0	-	41.8	43.5	1.7	
Hori.	224.000	QP	51.3	11.1	9.4	32.0	-	39.8	46.0	6.2	
Hori.	232.000	QP	47.2	11.3	9.5	32.0	-	36.0	46.0	10.1	
Hori.	248.000	QP	46.0	11.7	9.6	32.0	-	35.4	46.0	10.7	
Hori.	4882.000	PK	40.9	31.5	7.5	31.6	-	48.3	73.9	25.6	Floor noise
Hori.	7323.000	PK	44.3	36.2	8.9	32.6	-	56.7	73.9	17.2	
Hori.	9764.000	PK	44.5	38.8	9.4	33.4	-	59.3	73.9	14.6	Floor noise
Hori.	4882.000	AV	28.9	31.5	7.5	31.6	-	36.2	53.9	17.7	Floor noise
Hori.	7323.000	AV	37.8	36.2	8.9	32.6	1.1	51.3	53.9	2.6	
Hori.	9764.000	AV	30.4	38.8	9.4	33.4	-	45.2	53.9	8.7	Floor noise
Vert.	200.000	QP	44.0	11.4	9.2	32.0	-	32.6	43.5	10.9	
Vert.	208.000	QP	42.2	11.2	9.3	32.0	-	30.7	43.5	12.8	
Vert.	216.000	QP	50.3	11.1	9.4	32.0	-	38.7	43.5	4.8	
Vert.	224.000	QP	46.0	11.1	9.4	32.0	-	34.5	46.0	11.5	
Vert.	232.000	QP	42.5	11.3	9.5	32.0	-	31.3	46.0	14.8	
Vert.	248.000	QP	37.2	11.7	9.6	32.0	-	26.6	46.0	19.5	
Vert.	4882.000	PK	40.8	31.5	7.5	31.6	-	48.2	73.9	25.8	Floor noise
Vert.	7323.000	PK	45.4	36.2	8.9	32.6	-	57.9	73.9	16.0	
Vert.	9764.000	PK	44.7	38.8	9.4	33.4	-	59.5	73.9	14.4	Floor noise
Vert.	4882.000	AV	28.5	31.5	7.5	31.6	-	35.9	53.9	18.0	Floor noise
Vert.	7323.000	AV	38.3	36.2	8.9	32.6	1.1	51.9	53.9	2.0	
Vert.	9764.000	AV	30.3	38.8	9.4	33.4	-	45.1	53.9	8.8	Floor noise

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor

*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Distance factor: 1 GHz - 10 GHz 20log (3.9 m / 3.0 m) = 2.28 dB
10 GHz - 26.5 GHz 20log (1.0 m / 3.0 m) = -9.5 dB

Radiated Spurious Emission

Report No.	13367627H		
Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.3	No.3	No.3
Date	July 18, 2020	July 19, 2020	July 19, 2020
Temperature / Humidity	23 deg. C / 56 % RH	23 deg. C / 70 % RH	25 deg. C / 60 % RH
Engineer	Junya Okuno	Junya Okuno	Takafumi Noguchi
	(1 GHz - 10 GHz)	(10 GHz - 26.5 GHz)	(Below 1 GHz)
Mode	Tx, Hopping Off, 3DH5 2480 MHz		

Polarity	Frequency [MHz]	Detector	Reading [dBuV]	Ant.Fac. [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
Hori.	200.000	QP	47.5	11.4	9.2	32.0	-	36.1	43.5	7.4	
Hori.	208.000	QP	48.4	11.2	9.3	32.0	-	36.9	43.5	6.6	
Hori.	216.000	QP	53.4	11.1	9.4	32.0	-	41.8	43.5	1.7	
Hori.	224.000	QP	51.4	11.1	9.4	32.0	-	39.9	46.0	6.1	
Hori.	232.000	QP	47.4	11.3	9.5	32.0	-	36.2	46.0	9.8	
Hori.	248.000	QP	45.7	11.7	9.6	32.0	-	35.1	46.0	11.0	
Hori.	2483.500	PK	43.6	27.5	5.4	32.7	-	43.8	73.9	30.1	
Hori.	4960.000	PK	40.4	31.6	7.5	31.6	-	47.9	73.9	26.1	Floor noise
Hori.	7440.000	PK	42.9	36.3	8.9	32.7	-	55.4	73.9	18.5	
Hori.	9920.000	PK	43.8	38.9	9.4	33.5	-	58.6	73.9	15.3	Floor noise
Hori.	2483.500	AV	34.7	27.5	5.4	32.7	1.1	36.0	53.9	17.9	*1)
Hori.	4960.000	AV	30.9	31.6	7.5	31.6	-	38.3	53.9	15.6	Floor noise
Hori.	7440.000	AV	36.0	36.3	8.9	32.7	1.1	49.6	53.9	4.3	
Hori.	9920.000	AV	31.8	38.9	9.4	33.5	-	46.7	53.9	7.2	Floor noise
Vert.	200.000	QP	44.3	11.4	9.2	32.0	-	32.9	43.5	10.6	
Vert.	208.000	QP	41.8	11.2	9.3	32.0	-	30.3	43.5	13.2	
Vert.	216.000	QP	50.3	11.1	9.4	32.0	-	38.7	43.5	4.8	
Vert.	224.000	QP	45.9	11.1	9.4	32.0	-	34.4	46.0	11.6	
Vert.	232.000	QP	42.4	11.3	9.5	32.0	-	31.2	46.0	14.9	
Vert.	248.000	QP	37.2	11.7	9.6	32.0	-	26.6	46.0	19.5	
Vert.	2483.500	PK	42.2	27.5	5.4	32.7	-	42.4	73.9	31.5	
Vert.	4960.000	PK	31.7	31.6	7.5	31.6	-	39.1	73.9	34.8	Floor noise
Vert.	7440.000	PK	43.0	36.3	8.9	32.7	-	55.5	73.9	18.4	
Vert.	9920.000	PK	43.6	38.9	9.4	33.5	-	58.5	73.9	15.4	Floor noise
Vert.	2483.500	AV	33.7	27.5	5.4	32.7	1.1	35.0	53.9	18.9	*1)
Vert.	4960.000	AV	30.9	31.6	7.5	31.6	-	38.3	53.9	15.6	Floor noise
Vert.	7440.000	AV	35.4	36.3	8.9	32.7	1.1	49.0	53.9	4.9	
Vert.	9920.000	AV	31.8	38.9	9.4	33.5	-	46.7	53.9	7.3	Floor noise

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor



*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Distance factor: 1 GHz - 10 GHz 20log (3.9 m / 3.0 m) = 2.28 dB
10 GHz - 26.5 GHz 20log (1.0 m / 3.0 m) = -9.5 dB

*1) Not Out of Band emission(Leakage Power)

Radiated Spurious Emission (Reference Plot for band-edge)

Report No.	13367627H
Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.3
Date	July 18, 2020
Temperature / Humidity	23 deg. C / 56 % RH
Engineer	Junya Okuno
	(1 GHz - 10 GHz)
Mode	Tx, Hopping Off, 3DH5 2480 MHz



* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.

Final result of restricted band edge was shown in tabular data.

UL Japan, Inc.

Ise EMC Lab.



4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Radiated Spurious Emission (Plot data, Worst case)

Report No.	13367627H		
Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.3	No.3	No.3
Date	July 17, 2020	July 19, 2020	July 19, 2020
Temperature / Humidity	20 deg. C / 56 % RH	23 deg. C / 70 % RH	25 deg. C / 60 % RH
Engineer	Junya Okuno	Junya Okuno	Takafumi Noguchi
	(1 GHz - 10 GHz)	(10 GHz - 26.5 GHz)	(Below 1 GHz)
Mode	Tx, Hopping Off, DH5 2480 MHz		





*These plots data contains sufficient number to show the trend of characteristic features for EUT.

Conducted Spurious Emission

Report No.	13367627H
Test place	Ise EMC Lab. No.6 Shielded Room
Date	July 27, 2020
Temperature / Humidity	23 deg. C / 61 % RH
Engineer	Yuta Moriya
Mode	Tx, Hopping Off, DH5

2402 MHz



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN



Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Spurious Emission

Report No.	13367627H
Test place	Ise EMC Lab. No.6 Shielded Room
Date	July 27, 2020
Temperature / Humidity	23 deg. C / 61 % RH
Engineer	Yuta Moriya
Mode	Tx, Hopping Off, DH5

2441 MHz



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN



Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Spurious Emission

Report No.	13367627H
Test place	Ise EMC Lab. No.6 Shielded Room
Date	July 27, 2020
Temperature / Humidity	23 deg. C / 61 % RH
Engineer	Yuta Moriya
Mode	Tx, Hopping Off, DH5

2480 MHz



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN



Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Spurious Emission

Report No. 13367627H
Test place Ise EMC Lab. No.6 Shielded Room
Date July 27, 2020
Temperature / Humidity 23 deg. C / 61 % RH
Engineer Yuta Moriya
Mode Tx, Hopping Off, DH5



2402 MHz



Conducted Spurious Emission

Report No.	13367627H
Test place	Ise EMC Lab. No.6 Shielded Room
Date	July 27, 2020
Temperature / Humidity	23 deg. C / 61 % RH
Engineer	Yuta Moriya
Mode	Tx, Hopping Off, 3DH5

2441 MHz



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN



Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

Conducted Spurious Emission

Report No.	13367627H
Test place	Ise EMC Lab. No.6 Shielded Room
Date	July 27, 2020
Temperature / Humidity	23 deg. C / 61 % RH
Engineer	Yuta Moriya
Mode	Tx, Hopping Off, 3DH5

2480 MHz



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124


Conducted Emission Band Edge compliance

Report No.	13367627H	
Test place	Ise EMC Lab. No.6 Shielded Room	
Date	July 27, 2020	July 28, 2020
Temperature / Humidity	23 deg. C / 61 % RH	23 deg. C / 68 % RH
Engineer	Yuta Moriya	Yuta Moriya
Mode	Tx DH5	

Hopping On



Hopping Off



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN


Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124


Conducted Emission Band Edge compliance

Report No.	13367627H
Test place	Ise EMC Lab. No.6 Shielded Room
Date	July 27, 2020
Temperature / Humidity	23 deg. C / 61 % RH
Engineer	Yuta Moriya
Mode	Tx 3DH5

Hopping On



Hopping Off



UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

APPENDIX 2: Test instruments

Test equipment

Test Item	Local ID	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
AT	MAT-57	141333	Attenuator(10dB)	Suhner	6810.19.A	-	12/09/2019	12
AT	MCC-245	197220	Microwave cable	HUBER+SUNER	SF126E/11PC35/11P C35/2000MM	537003/126E	03/23/2020	12
AT	MRENT-130	141855	Spectrum Analyzer	Keysight Technologies Inc	E4440A	MY46187750	11/19/2019	12
AT	MPM-08	141805	Power Meter	ANRITSU	ML2495A	6K00003338	10/03/2019	12
AT	MPSE-11	141840	Power sensor	ANRITSU	MA2411B	11737	10/03/2019	12
AT	MOS-24	90289	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	0005	01/07/2020	12
AT	MMM-12	141547	DIGITAL HiTESTER	Hioki	3805	60500120	02/03/2020	12
RE	MPA-12	141581	MicroWave System Amplifier	Keysight Technologies Inc	83017A	650	10/16/2019	12
RE	MCC-141	141412	Microwave Cable	Junkosha	MWX221	1305S002R(1m) / 1405S146(5m)	-	-
RE	MOS-15	141562	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	0010	01/07/2020	12
RE	MMM-10	141545	DIGITAL HiTESTER	Hioki	3805	51201148	01/06/2020	12
RE	MJM-26	142227	Measure	KOMELON	KMC-36	-	-	-
RE	COTS-ME MI-02	178648	EMI measurement program	TSJ (Techno Science Japan)	TEPTO-DV	-	-	-
RE	MAEC-04-SVSWR	142017	AC4_Semi Anechoic Chamber(SVSWR)	TDK	Semi Anechoic Chamber 3m	DA-10005	04/04/2019	24
RE	MRENT-130	141855	Spectrum Analyzer	Keysight Technologies Inc	E4440A	MY46187750	11/19/2019	12
RE	MAEC-03	142008	AC3_Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-10005	05/22/2020	24
RE	MOS-13	141554	Thermo-Hygrometer	CUSTOM. Inc	CTH-201	1301	01/07/2020	12
RE	MMM-08	141532	DIGITAL HiTESTER	Hioki	3805	51201197	01/06/2020	12
RE	MJM-16	142183	Measure	KOMELON	KMC-36	-	-	-
RE	MAT-95	142314	Attenuator	Pasternack	PE7390-6	D/C 1504	06/17/2020	12
RE	MBA-03	141424	Biconical Antenna	Schwarzbeck Mess - Elektronik	VHA9103+BBA9106	1915	08/13/2020	12
RE	MCC-51	141323	Coaxial cable	UL Japan	-	-	07/06/2020	12
RE	MLA-22	141266	Logperiodic Antenna (200-1000MHz)	Schwarzbeck Mess - Elektronik	VUSLP9111B	9111B-191	08/13/2020	12
RE	MPA-13	141582	Pre Amplifier	SONOMA INSTRUMENT	310	260834	02/10/2020	12
RE	MTR-08	141949	Test Receiver	Rohde & Schwarz	ESCI	100767	08/18/2020	12
RE	MHF-25	141232	High Pass Filter 3.5-18.0GHz	UL Japan	HPF SELECTOR	001	09/11/2019	12
RE	MSA-04	141885	Spectrum Analyzer	Keysight Technologies Inc	E4448A	US44300523	11/21/2019	12
RE	MHA-20	141507	Horn Antenna 1-18GHz	Schwarzbeck Mess - Elektronik	BBHA9120D	258	09/26/2019	12
RE	MPA-11	141580	MicroWave System Amplifier	Keysight Technologies Inc	83017A	MY39500779	03/24/2020	12
RE	MCC-231	177964	Microwave Cable	Junkosha INC.	MMX221	1901S329(1m)/ 1902S579(5m)	03/02/2020	12
RE	MHA-16	141513	Horn Antenna 15-40GHz	Schwarzbeck Mess - Elektronik	BBHA9170	BBHA9170306	05/21/2020	12
RE	MAEC-03-SVSWR	142013	AC3_Semi Anechoic Chamber(SVSWR)	TDK	Semi Anechoic Chamber 3m	DA-10005	04/08/2019	24

UL Japan, Inc.

Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8999

Facsimile : +81 596 24 8124

***Hyphens for Last Calibration Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.**

The expiration date of the calibration is the end of the expired month.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

**Test item: RE: Radiated Emission test
AT: Antenna Terminal Conducted test**