



MEASUREMENT REPORT

FCC ID : I4L- GH20WD
APPLICANT : Micro-Star Int'l Co.,Ltd.
Application Type : Certification
Product : 2.4GHz Dongle
Model No. : GH20WD
Brand Name : msi
FCC Classification : (DTS) Digital Transmission System
FCC Rule Part(s) : Part 15.247
Test Procedure(s) : ANSI C63.10-2013
Received Date : January 04 ,2022
Test Date : January 09~13 ,2022

Tested By : 
(Peter Syu)

Reviewed By : 
(Paddy Chen)

Approved By : 
(Chenz Ker)



The test results only relate to the tested sample.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2301TWE903-U1	1.0	Original Report	2023-01-31	

CONTENTS

Description	Page
§2.1033 General Information	5
1. INTRODUCTION	6
1.1. Scope.....	6
1.2. MRT Test Location	6
2. PRODUCT INFORMATION	7
2.1. Equipment Description	7
2.2. Product Specification Subjective to this Standard.....	8
2.3. Test Mode	8
2.4. Operation Frequency / Channel List.....	9
2.5. Test Configuration	10
2.6. Test Software	10
2.7. EMI Suppression Device(s)/Modifications	10
2.8. Labeling Requirements	10
3. DESCRIPTION of TEST	11
3.1. Evaluation Procedure	11
3.2. AC Line Conducted Emissions	11
3.3. Radiated Emissions	12
4. ANTENNA REQUIREMENTS.....	13
5. TEST EQUIPMENT CALIBRATION DATE	14
6. MEASUREMENT UNCERTAINTY.....	15
7. TEST RESULT	16
7.1. Summary.....	16
7.2. 6dB Bandwidth Measurement	17
7.2.1. Test Limit.....	17
7.2.2. Test Procedure used	17
7.2.3. Test Setting	17
7.2.4. Test Setup	17
7.2.5. Test Result	18
7.3. Output Power Measurement.....	19
7.3.1. Test Limit.....	19
7.3.2. Test Procedure Used.....	19
7.3.3. Test Setting	19
7.3.4. Test Setup	19
7.3.5. Test Result of Output Power	20
7.4. Power Spectral Density Measurement	21
7.4.1. Test Limit.....	21
7.4.2. Test Procedure Used.....	21
7.4.3. Test Setting	21
7.4.4. Test Setup	21
7.4.5. Test Result	22

7.5.	Out-of-Band Spurious Emissions Emissions Measurement	23
7.5.1.	Test Limit	23
7.5.2.	Test Procedure Used	23
7.5.3.	Test Setting	23
7.5.4.	Test Setup	23
7.5.5.	Test Result	24
7.6.	Radiated Spurious Emission Measurement	27
7.6.1.	Test Limit	27
7.6.2.	Test Procedure Used	27
7.6.3.	Test Setting	27
7.6.4.	Test Setup	29
7.6.5.	Test Result	31
7.7.	Radiated Restricted Band Edge Measurement	43
7.7.1.	Test Limit	43
7.7.2.	Test Procedure Used	43
7.7.3.	Test Setting	43
7.7.4.	Test Setup	45
7.7.5.	Test Result	46
7.8.	AC Conducted Emissions Measurement	52
7.8.1.	Test Limit	52
7.8.2.	Test Setup	52
7.8.3.	Test Result	53
8.	CONCLUSION	57
	Appendix A : Test Photograph	58
	Appendix B : External Photograph	58
	Appendix C : Internal Photograph	58

§2.1033 General Information

Applicant	Micro-Star Int'l Co.,Ltd.
Applicant Address	No.69, Lide St., Zhonghe Dist.,New Taipei City 235, Taiwan
Manufacturer	Micro-Star Int'l Co.,Ltd.
Manufacturer Address	No.69, Lide St., Zhonghe Dist.,New Taipei City 235, Taiwan
Test Site	MRT Technology (Taiwan) Co., Ltd
Test Site Address	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)
MRT FCC Registration No.	291082
FCC Rule Part(s)	Part 15.247
Test Device Serial No.	#1-1 ☐ Production ☒ Pre-Production ☐ Engineering

Test Facility / Accreditations

1. MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm.
2. MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada.
3. MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Taiwan, EU and TELEC Rules.


1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



2. PRODUCT INFORMATION

2.1. Equipment Description

Product Name	2.4GHz Dongle
Model No.	GH20WD
Brand Name	msi
Specification	SRD 2.4GHz
Maximum Power	3.62dBm
Accessories	
Wireless Headset	Brand: msi Model No: 8ZC7

2.2. Product Specification Subjective to this Standard

Operating Frequency	2405.889~2477.569MHz
Type of modulation	GFSK

2.3. Test Mode

Test Mode	Mode 1: Transmit
-----------	------------------

Note: Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.

2.4. Operation Frequency / Channel List

Channel	Frequency	Channel	Frequency	Channel	Frequency
14	2405.889	62	2430.465	110	2455.041
18	2407.937	66	2432.513	114	2457.089
22	2409.985	70	2434.561	118	2459.137
26	2412.033	74	2436.609	122	2461.185
30	2414.081	78	2438.657	126	2463.233
34	2416.129	82	2440.705	130	2465.281
38	2418.177	86	2442.753	134	2467.329
42	2420.225	90	2444.801	138	2469.377
46	2422.273	94	2446.849	142	2471.425
50	2424.321	98	2448.897	146	2473.473
54	2426.369	102	2450.945	150	2475.521
58	2428.417	106	2452.993	154	2477.569

2.5. Test Configuration

This device was tested per the guidance of ANSI C63.10-2013. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.6. Test Software

The test utility software used during testing was "A8102_FCC_CE version: N/A".

2.7. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.8. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase.

However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

3. DESCRIPTION of TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 558074 D01v05r02 were used in the measurement of the **2.4GHz Dongle**.

Deviation from measurement procedure.....None

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 9'x4'x3' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50 Ω /50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment which determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

Line conducted emissions test results are shown in Section 7.8.

3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, which produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

Radiated emissions test results are shown in Section 7.6 & 7.7 .

4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the **2.4GHz Dongle**, is permanently attached.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT unit complies with the requirement of §15.203.

Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	somic	GH20WD 2.4G	PCB	-1.2dBi

5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Two-Line V-Network	R&S	ENV216	MRTTWA00020	1 year	2023/4/20
Cable	Rosnol	N1C50-RG400-B 1C50-500CM	MRTTWE00013	1 year	2023/6/19
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2023/3/9

Radiated Emissions – AC2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00001	1 year	2023/12/21
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	MRTTWA00002	1 year	2023/5/24
Broadband Hornantenna	RFSPIN	DRH18-E	MRTTWA00087	1 year	2023/5/10
Breitband Hornantenna	SCHWARZBECK	BBHA 9170	MRTTWA00004	1 year	2023/3/29
Broadband Preamplifier	EMC Instruments corporation	EMC118A45SE	MRTTWA00088	1 year	2023/5/9
Broadband Amplifier	SCHWARZBECK	BBV 9721	MRTTWA00006	1 year	2023/3/30
Signal Analyzer	R&S	FSV40	MRTTWA00007	1 year	2023/3/16
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2023/3/9
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2023/10/5
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2023/7/19
Antenna Cable	HUBERSUHNER	SF106	MRTTWE00034	1 year	2023/6/27
Cable	HUBERSUHNER	EMC105-NM-NM -3000	MRTTWE00035	1 year	2023/6/27

Conducted Test Equipment – SR5

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2023/10/5
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2023/7/19
USB Wideband Power Sensor	KEYSIGHT	U2021XA	MRTTWA00015	1 year	2023/3/16

Test Software

Software	Version	Function
e3	9.160520a	EMI Test Software
EMI	V3	EMI Test Software

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

Conducted Emission- Power Line
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 0.15MHz~30MHz: $\pm 2.53\text{dB}$
Radiated Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 9kHz~30MHz: $\pm 3.92\text{dB}$ 30MHz~1GHz: $\pm 4.25\text{dB}$ 1GHz~18GHz: $\pm 4.40\text{dB}$ 18GHz~40GHz: $\pm 4.45\text{dB}$
Frequency Error
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 78.4\text{Hz}$
Conducted Power
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.84\text{dB}$
Conducted Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 2.65\text{ dB}$
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 3.3\%$
Temp. / Humidity
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.82^\circ\text{C}/ \pm 3\%$
DC Voltage
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.3\%$

7. TEST RESULT

7.1. Summary

Product Name: 2.4GHz Dongle

FCC Classification: (DTS) Digital Transmission System

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	6dB Bandwidth	$\geq 500\text{kHz}$	Conducted	Pass	Section 7.2
15.247(b)(3)	Output Power	$\leq 30.00\text{dBm}$		Pass	Section 7.3
15.247(e)	Power Spectral Density	$\leq 8.00\text{dBm}/3\text{kHz}$		Pass	Section 7.4
15.247(d)	Out-of-Band Emissions	Conducted $\geq 30\text{dBc}$		Pass	Section 7.5
15.205 15.209	Spurious Emission	< FCC 15.209 limits	Radiated	Pass	Section 7.6
15.205 15.209	Band Edge Measurement	$\leq 74\text{dBuV/m(Peak)}$ $\leq 54\text{dBuV/m(Average)}$		Pass	Section 7.7
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 7.8

Notes:

- Determining compliance is based on the test results met the regulation limits or requirements declared by clients, and the test results don't take into account the value of measurement uncertainty.
- All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified when applicable. The test results shown in the following sections represent the worst case emissions.
- The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

7.2. 6dB Bandwidth Measurement

7.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


7.2.2. Test Procedure used

KDB 558074 D01v05r02- Section 8.2 Option 2

7.2.3. Test Setting


1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. Allow the trace was allowed to stabilize

7.2.4. Test Setup



7.2.5. Test Result

Test Mode	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)	Result
2.4GHz	CH14	2405.889	1.2760	4.4866	≥ 0.5	Pass
	CH82	2440.705	1.2710	4.4970	≥ 0.5	Pass
	CH154	2477.569	1.2550	4.5070	≥ 0.5	Pass



7.3. Output Power Measurement

7.3.1. Test Limit

The maximum out power shall be less 1 Watt (30dBm).

7.3.2. Test Procedure Used

KDB 558074 D01v05r02 - Section 8.3

7.3.3. Test Setting

Peak Power Measurement

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

7.3.4. Test Setup



7.3.5. Test Result of Output Power

Test Mode	Channel No.	Frequency (MHz)	Average Power (dBm)	Power Limit (dBm)
2.4GHz	CH14	2405.889	2.71	< 30
	CH82	2440.705	3.62	< 30
	CH154	2477.569	3.48	< 30

Note1: Output power =Reading value on power meter + cable loss.

7.4. Power Spectral Density Measurement

7.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

7.4.2. Test Procedure Used


KDB 558074 D01v05r02 - Section 8.4 Method PKPSD

7.4.3. Test Setting

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.


- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: 3 kHz.
- d) Set the VBW $\geq 3 \times$ RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.

7.4.4. Test Setup



7.4.5. Test Result

Test Mode	Channel No.	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Result
2.4GHz	CH14	2405.889	-14.89	≤ 8	Pass
	CH82	2440.705	-12.18	≤ 8	Pass
	CH154	2477.569	-13.86	≤ 8	Pass



7.5. Out-of-Band Spurious Emissions Emissions Measurement

7.5.1. Test Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on RF conducted measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.


7.5.2. Test Procedure Used

ANSI C63.10-2013 - Section 11.1 & 11.2

7.5.3. Test Setting

- (a) Set instrument center frequency to DTS channel center frequency
- (b) Set the span to ≥ 1.5 times the DTS bandwidth
- (c) Set the RBW = 100 kHz
- (d) Set the VBW $\geq 3 \times$ RBW
- (e) Detector = peak
- (f) Sweep time = auto couple
- (g) Trace mode = max hold
- (h) Allow trace to fully stabilize


7.5.4. Test Setup




7.5.5. Test Result

Test Mode	Channel No.	Frequency (MHz)	Limit	Result
2.4GHz	CH14	2405.889	30dBc	Pass
	CH82	2440.705	30dBc	Pass
	CH154	2477.569	30dBc	Pass


CH14 (2405.889MHz)




CH14 (2405.889MHz)




CH14 (2405.889MHz)




CH82 (2440.705MHz)



CH82 (2440.705MHz)




CH82 (2440.705MHz)




CH154 (2477.569MHz)



CH154 (2477.569MHz)



CH154 (2477.569MHz)



7.6. Radiated Spurious Emission Measurement

7.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [V/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

7.6.2. Test Procedure Used

ANSI C63.10-2013 - Section 11.12.2.3 (quasi-peak measurements)

ANSI C63.10-2013 - Section 11.12.2.4 (peak power measurements)

ANSI C63.10-2013 - Section 11.12.2.5 (average power measurements)

7.6.3. Test Setting

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in Table 1
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple

6. Trace mode = max hold

7. Trace was allowed to stabilize

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest

2. RBW = 1MHz

3. VBW $\geq 1/T$

4. De As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode

5. Detector = Peak


6. Sweep time = auto

7. Trace mode = max hold


8. Allow max hold to run for at least 50 times (1/duty cycle) traces

7.6.4. Test Setup


9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:



1GHz ~ 18GHz Test Setup:




18GHz ~25GHz Test Setup:



7.6.5. Test Result

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	VULB 9162	Temp. / Humidity	22°C /65%
Polarity	Horizontal	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_TX_CH 82_ANT 0	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	84.320	15.44	15.24	30.68	-9.32	40.00	100	112	QP
2	108.570	10.78	18.50	29.28	-14.22	43.50	100	173	QP
3	144.460	11.50	15.09	26.59	-16.91	43.50	100	263	QP
4	168.710	17.25	16.00	33.25	-10.25	43.50	100	266	QP
5	* 205.570	18.05	18.16	36.20	-7.30	43.50	100	280	QP
6	800.180	2.16	29.69	31.86	-14.14	46.00	100	272	QP

Note:

- " *", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	VULB 9162	Temp. / Humidity	22°C /65%
Polarity	Vertical	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_TX_CH 82_ANT 0	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	84.320	16.44	15.24	31.68	-8.32	40.00	100	104	QP
2		120.210	5.92	16.96	22.88	-20.62	43.50	100	39	QP
3		144.460	6.94	15.09	22.02	-21.48	43.50	100	0	QP
4		168.710	9.15	16.00	25.15	-18.35	43.50	100	0	QP
5		453.890	2.32	24.03	26.35	-19.65	46.00	100	270	QP
6		533.430	2.96	25.68	28.64	-17.36	46.00	100	205	QP

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	VULB 9162	Temp. / Humidity	22°C /65%
Polarity	Horizontal	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_RX_CH 82_ANT 0	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	88.310	14.68	16.53	31.21	-12.29	43.50	100	134	QP
2	105.540	11.33	18.62	29.95	-13.55	43.50	100	195	QP
3	149.020	12.96	15.24	28.20	-15.30	43.50	100	285	QP
4	165.770	16.59	15.93	32.52	-10.98	43.50	100	288	QP
5	* 209.020	17.41	18.06	35.47	-8.03	43.50	100	302	QP
6	798.170	3.45	29.67	33.13	-12.87	46.00	100	294	QP

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	VULB 9162	Temp. / Humidity	22°C /65%
Polarity	Vertical	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_RX_CH 82_ANT 0	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	88.310	14.67	16.53	31.21	-12.29	43.50	100	141	QP
2		117.180	6.15	17.39	23.55	-19.95	43.50	100	76	QP
3		149.020	8.40	15.24	23.63	-19.87	43.50	100	37	QP
4		165.770	10.48	15.93	26.42	-17.08	43.50	100	100	QP
5		457.340	3.51	24.12	27.62	-18.38	46.00	100	307	QP
6		531.420	4.26	25.65	29.91	-16.09	46.00	100	242	QP

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	DRH18-E & BBHA 9170	Temp. / Humidity	22°C /65%
Polarity	Horizontal	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_TX_CH 14_ANT 0	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	4811.778	53.85	-1.25	52.60	-21.40	74.00	300	278	Peak
2		7217.667	40.50	4.16	44.67	-29.33	74.00	200	265	Peak
3		9623.556	47.82	3.28	51.10	-22.90	74.00	100	241	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	DRH18-E & BBHA 9170	Temp. / Humidity	22°C /65%
Polarity	Vertical	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_TX_CH 14_ANT 0	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	4811.778	59.55	-1.25	58.30	-15.70	74.00	100	220	Peak
2	*	4811.778	45.42	-1.25	44.17	-9.83	54.00	100	220	Average
3		7217.667	40.00	4.16	44.17	-29.83	74.00	100	281	Peak
4		9623.556	48.00	3.28	51.28	-22.72	74.00	100	231	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	DRH18-E & BBHA 9170	Temp. / Humidity	22°C /65%
Polarity	Horizontal	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_TX_CH 82_ANT 0	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	4881.410	51.25	-1.11	50.14	-23.86	74.00	300	288	Peak
2		7322.115	40.46	4.13	44.59	-29.41	74.00	300	60	Peak
3		9762.820	41.89	3.33	45.22	-28.78	74.00	300	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	DRH18-E & BBHA 9170	Temp. / Humidity	22°C /65%
Polarity	Vertical	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_TX_CH 82_ANT 0	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	4881.410	58.71	-1.11	57.60	-16.40	74.00	100	222	Peak
2	*	4881.410	44.46	-1.11	43.35	-10.65	54.00	100	222	Average
3		7322.115	39.83	4.13	43.96	-30.04	74.00	100	0	Peak
4		9762.820	46.27	3.33	49.60	-24.40	74.00	100	200	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	DRH18-E & BBHA 9170	Temp. / Humidity	22°C /65%
Polarity	Horizontal	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_TX_CH 154_ANT 0	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4955.138	46.48	-0.96	45.51	-28.49	74.00	300	228	Peak
2	7432.707	40.41	4.08	44.50	-29.50	74.00	300	63	Peak
3	* 9910.276	42.36	3.44	45.80	-28.20	74.00	300	75	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	DRH18-E & BBHA 9170	Temp. / Humidity	22°C /65%
Polarity	Vertical	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_TX_CH 154_ANT 0	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	4955.138	60.32	-0.96	59.36	-14.64	74.00	100	223	Peak
2	*	4955.138	46.19	-0.96	45.23	-8.77	54.00	100	223	Average
3		7432.707	40.06	4.08	44.14	-29.86	74.00	100	360	Peak
4		9910.276	43.86	3.44	47.30	-26.70	74.00	100	266	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	DRH18-E & BBHA 9170	Temp. / Humidity	22°C /65%
Polarity	Horizontal	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_RX_CH 82_ANT 0	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	1033.000	45.97	-7.77	38.20	-35.80	74.00	100	253	Peak
2	1193.000	44.85	-7.93	36.92	-37.08	74.00	100	108	Peak
3	1381.000	44.82	-7.38	37.44	-36.56	74.00	100	250	Peak
4	* 1597.000	46.49	-7.66	38.84	-35.16	74.00	100	229	Peak
5	1740.000	45.96	-7.52	38.45	-35.55	74.00	100	360	Peak
6	2106.000	42.32	-5.94	36.38	-37.62	74.00	100	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	DRH18-E & BBHA 9170	Temp. / Humidity	22°C /65%
Polarity	Vertical	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_RX_CH 82_ANT 0	Test Voltage	By Notebook PC



No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	1067.000	46.75	-7.80	38.95	-35.05	74.00	100	178	Peak
2	1195.000	47.49	-7.93	39.56	-34.44	74.00	100	0	Peak
3	1394.000	44.05	-7.34	36.70	-37.30	74.00	100	307	Peak
4	* 1599.000	52.68	-7.66	45.01	-28.99	74.00	100	190	Peak
5	1800.000	45.70	-7.45	38.25	-35.75	74.00	100	0	Peak
6	1990.000	44.98	-6.30	38.68	-35.32	74.00	100	333	Peak

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

7.7. Radiated Restricted Band Edge Measurement

7.7.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [V/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 – 30	30	30
30 – 88	100	3
88 – 216	150	3
216 – 960	200	3
Above 960	500	3

7.7.2. Test Procedure Used

ANSI C63.10-2013 - Section 11.13

7.7.3. Test Setting

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = as specified in Table 1
3. VBW = 3 * RBW
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Table 1 - RBW as a function of frequency


Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW $\geq 1/T$
4. De As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = auto
7. Trace mode = max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces


7.7.4. Test Setup

1GHz ~ 18GHz Test Setup:



7.7.5. Test Result

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	DRH18-E	Temp. / Humidity	22°C /65%
Polarity	Horizontal	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_TX_CH 14_ANT 0	Test Voltage	By Notebook PC




No		Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	*	2333.835	46.39	-5.63	40.76	-33.24	74.00	100	282	Peak
2		2390.000	45.83	-5.62	40.22	-33.78	74.00	100	282	Peak
3		2406.180	101.45	-5.60	95.85	N/A	N/A	100	282	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	DRH18-E	Temp. / Humidity	22°C /65%
Polarity	Vertical	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_TX_CH 14_ANT 0	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2319.870	47.98	-5.64	42.34	-31.66	74.00	100	295	Peak
2	* 2390.000	48.41	-5.62	42.80	-31.20	74.00	100	295	Peak
3	2404.920	106.23	-5.60	100.63	N/A	N/A	100	295	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	DRH18-E	Temp. / Humidity	22°C /65%
Polarity	Horizontal	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_TX_CH 154_ANT 0	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2476.510	99.09	-5.43	93.66	N/A	N/A	100	282	Peak
2	* 2483.500	64.39	-5.42	58.98	-15.02	74.00	100	282	Peak
3	2484.520	61.08	-5.42	55.66	-18.34	74.00	100	282	Peak

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	DRH18-E	Temp. / Humidity	22°C /65%
Polarity	Horizontal	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_TX_CH 154_ANT 0	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2477.320	85.24	-5.43	79.81	N/A	N/A	100	282	Average
2	* 2483.500	49.01	-5.42	43.59	-10.41	54.00	100	282	Average
3	2484.520	43.37	-5.42	37.96	-16.04	54.00	100	282	Average

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	DRH18-E	Temp. / Humidity	22°C /65%
Polarity	Vertical	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_TX_CH 154_ANT 0	Test Voltage	By Notebook PC




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2476.510	104.09	-5.43	98.65	N/A	N/A	100	282	Peak
2	* 2483.500	70.01	-5.42	64.60	-9.40	74.00	100	282	Peak
3	2484.550	66.85	-5.42	61.44	-12.56	74.00	100	282	Peak

Note:

- "*" means this data is the worst emission level.
- C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
- Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
- The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	2.4GHz Dongle	Date of Test	2023-01-10
Factor	DRH18-E	Temp. / Humidity	22°C /65%
Polarity	Vertical	Site / Test Engineer	AC2 / Ares
Test Mode	SRD_2.4G_TX_CH 154_ANT 0	Test Voltage	By Notebook PC



No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2477.260	90.21	-5.43	84.78	N/A	N/A	100	282	Average
2	* 2483.500	54.69	-5.42	49.27	-4.73	54.00	100	282	Average
3	2485.600	49.28	-5.41	43.87	-10.13	54.00	100	282	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

7.8. AC Conducted Emissions Measurement


7.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 / RSS-Gen Limits		
Frequency (MHz)	QP (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.


Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

7.8.2. Test Setup



7.8.3. Test Result

EUT	2.4GHz Dongle	Date of Test	2023-01-13
Factor	CE_ENV216-L1 (Filter ON)	Temp. / Humidity	22.7°C /57%
Polarity	Line1	Site / Test Engineer	SR2 / Amber
Test Mode	SRD_2.4G_TX_CH 82_ANT 0	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1		0.154	26.01	9.62	35.63	-30.12	65.75	QP
2		0.154	16.67	9.62	26.29	-29.47	55.75	Average
3	*	0.600	26.66	9.65	36.31	-19.69	56.00	QP
4	*	0.600	25.16	9.65	34.80	-11.20	46.00	Average
5		1.828	14.83	9.69	24.52	-31.48	56.00	QP
6		1.828	7.51	9.69	17.19	-28.81	46.00	Average
7		2.760	12.23	9.71	21.94	-34.06	56.00	QP
8		2.760	5.62	9.71	15.32	-30.68	46.00	Average
9		6.409	8.88	9.78	18.66	-41.34	60.00	QP
10		6.409	4.01	9.78	13.79	-36.21	50.00	Average
11		19.107	12.38	9.92	22.30	-37.70	60.00	QP
12		19.107	6.67	9.92	16.59	-33.41	50.00	Average

Note:

- "*", means this data is the worst emission level.
- C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
- Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).

EUT	2.4GHz Dongle	Date of Test	2023-01-13
Factor	CE_ENV216-N (Filter ON)	Temp. / Humidity	22.7°C /57%
Polarity	Neutral	Site / Test Engineer	SR2 / Amber
Test Mode	SRD_2.4G_TX_CH 82_ANT 0	Test Voltage	AC 120V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1		0.159	23.34	9.62	32.96	-32.55	65.52	QP
2		0.159	14.27	9.62	23.89	-31.63	55.52	Average
3	*	0.600	26.75	9.65	36.40	-19.60	56.00	QP
4	*	0.600	25.29	9.65	34.94	-11.06	46.00	Average
5		1.747	16.32	9.68	26.00	-30.00	56.00	QP
6		1.747	14.21	9.68	23.89	-22.11	46.00	Average
7		2.193	13.10	9.69	22.79	-33.21	56.00	QP
8		2.193	5.00	9.69	14.69	-31.31	46.00	Average
9		2.692	13.37	9.70	23.08	-32.92	56.00	QP
10		2.692	12.23	9.70	21.93	-24.07	46.00	Average
11		19.152	10.40	9.99	20.39	-39.61	60.00	QP
12		19.152	5.76	9.99	15.75	-34.25	50.00	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).

EUT	2.4GHz Dongle	Date of Test	2023-01-13
Factor	CE_ENV216-L1 (Filter ON)	Temp. / Humidity	22.7°C /57%
Polarity	Line1	Site / Test Engineer	SR2 / Amber
Test Mode	SRD_2.4G_TX_CH 82_ANT 0	Test Voltage	AC 240V/60Hz




No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1	*	0.622	26.06	9.65	35.70	-20.30	56.00	QP
2	*	0.622	24.35	9.65	33.99	-12.01	46.00	Average
3		1.864	19.83	9.69	29.52	-26.48	56.00	QP
4		1.864	18.80	9.69	28.49	-17.51	46.00	Average
5		2.400	13.64	9.70	23.34	-32.66	56.00	QP
6		2.400	10.01	9.70	19.71	-26.29	46.00	Average
7		3.250	17.32	9.72	27.03	-28.97	56.00	QP
8		3.250	16.26	9.72	25.98	-20.02	46.00	Average
9		4.911	10.43	9.74	20.17	-35.83	56.00	QP
10		4.911	7.14	9.74	16.88	-29.12	46.00	Average
11		5.414	9.96	9.75	19.72	-40.28	60.00	QP
12		5.414	3.59	9.75	13.35	-36.65	50.00	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).

EUT	2.4GHz Dongle	Date of Test	2023-01-13
Factor	CE_ENV216-N (Filter ON)	Temp. / Humidity	22.7°C /57%
Polarity	Neutral	Site / Test Engineer	SR2 / Amber
Test Mode	SRD_2.4G_TX_CH 82_ANT 0	Test Voltage	AC 240V/60Hz



No		Frequency (MHz)	Reading (dBuV)	C.F (dB)	Measurement (dBuV)	Margin (dB)	Limit (dBuV)	Remark (QP/PK/AV)
1		0.613	21.61	9.65	31.26	-24.74	56.00	QP
2		0.613	16.64	9.65	26.29	-19.71	46.00	Average
3		1.914	18.78	9.69	28.47	-27.53	56.00	QP
4		1.914	17.15	9.69	26.84	-19.16	46.00	Average
5	*	2.319	20.24	9.70	29.94	-26.06	56.00	QP
6	*	2.319	19.17	9.70	28.87	-17.13	46.00	Average
7		2.796	19.77	9.71	29.47	-26.53	56.00	QP
8		2.796	18.67	9.71	28.38	-17.62	46.00	Average
9		4.402	15.81	9.74	25.55	-30.45	56.00	QP
10		4.402	13.07	9.74	22.81	-23.19	46.00	Average
11		12.060	12.33	9.89	22.22	-37.78	60.00	QP
12		12.060	7.31	9.89	17.21	-32.79	50.00	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = LISN Factor (dB)+ Cable Loss (dB).
3. Measurement (dBuV) = Reading(dBuV) + C.F (Correction Factor).

8. CONCLUSION

The data collected relate only the item(s) tested and show that the **2.4GHz Dongle** is in compliance with Part 15C of the FCC Rules.

Appendix A : Test Photograph

Refer to “2301TWE903-UT” file.

Appendix B : External Photograph

Refer to “2301TWE903-UE” file.

Appendix C : Internal Photograph

Refer to “2301TWE903-UI” file.

_____ The End _____