



Radio Frequency Exposure

Applicant : Micro-Star Int'l Co.,Ltd.

Address : No.69, Lide St., Zhonghe Dist. New Taipei City 235
: Taiwan

Equipment : Wireless Keyboard

Model No. : MS-8ZA9

Trade Name : msi

FCC ID : I4L-MS-8ZA9

I HEREBY CERTIFY THAT :

The sample was received on Nov. 04, 2024 and the testing was completed on Nov. 20, 2024 at Cerpass Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of Cerpass Technology Corp., the test report shall not be reproduced except in full.

Approved by:



Mark Liao / Supervisor

Laboratory Accreditation:

Cerpass Technology Corporation Test Laboratory





CONTENTS

1.	Summary of Test Procedure and Test Results	4
1.1.	Applicable Standards	4
2.	Test Configuration of Equipment under Test	5
2.1.	Feature of Equipment under Test	5
2.2.	General Information of Test	6
2.3.	Measurement Uncertainty	6
3.	Test Equipment and Ancillaries Used for Tests	7
4.	Radio Frequency Exposure	8
4.1.	Applicable Standards	8
4.2.	EUT Specification	9
4.3.	Result	9



History of this test report



1. Summary of Test Procedure and Test Results

1.1. Applicable Standards

FCC Rules and Regulations Part 2.1091

FCC Rule	Description of Test	Result
2.1091	Radio Frequency Exposure	PASS

*The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement, measurement uncertainty evaluation is not considered.



2. Test Configuration of Equipment under Test

2.1. Feature of Equipment under Test

Operation Frequency Range	2400MHz-2483.5MHz
Center Frequency Range	2402MHz-2480MHz
Modulation Type	SRD: GFSK BLE: GFSK
Modulation Technology	SRD: DTS BLE: DTS
Data Rate	SRD: GFSK: 1Mbps, 2Mbps BLE: GFSK: 1Mbps, 2Mbps
Antenna Type	PCB Print Antenna
Antenna Gain	2.94 dBi
Battery	Dongguan Lean Power New Energy Technology CO., Ltd \ WYZ606090
USB Cable	msi \ GK600 W usb cable

Note:For more details, please refer to the User's manual of the EUT.



2.2. General Information of Test

<input checked="" type="checkbox"/> Test Site	Cerpass Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel: +886-3-3226-888 Fax: +886-3-3226-881	
	FCC	TW1439, TW1079
	IC	4934E-1, 4934E-2
	Frequency Range Investigated Conducted: from 150kHz to 30 MHz Radiation: from 9 kHz to 25,000MHz	
Test Distance	The test distance of radiated emission from antenna to EUT is 3 M.	

SRD

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2024/11/20	26.5°C / 49%	Leon Huang

BLE

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2024/11/18	25°C / 50%	Sheng Hsu

2.3. Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Item	Uncertainty
AC Power Line Conduction(150K~30MHz)	±3.20dB
Radiated Spurious Emission(9KHz~30MHz)	±3.5dB
Radiated Spurious Emission(30MHz~1GHz)	±5.1dB
Radiated Spurious Emission(1GHz~40GHz)	±5.2dB
Conducted Spurious Emission	±2.1dB
6dB Bandwidth	±5.4%
20dB Bandwidth	±4.4%
Occupied Bandwidth	±4.5%
Peak Output Power(Conducted Power Meter)	±1.1dB
Dwell Time / Deactivation Time	±7.6%
Power Spectral Density	±2.0dB
Duty Cycle	±3.5%



3. Test Equipment and Ancillaries Used for Tests

SRD

Test Item	RF Conducted				
Test Site	RFCON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
Spectrum Analyzer	ROHDE & SCHWARZ	FSP 40	100047	2024/03/01	2025/02/28
Attenuator	KEYSIGHT	8491B	MY39250703	2024/02/20	2025/02/19
Cable-0.5m (1G-26.5G)	HUBER SUHNER	SUCOFLEX 102	28422/2	2024/05/13	2025/05/12
Power Meter	Anritsu	ML2495A	1224005	2024/02/17	2025/02/16
Power Sensor	Anritsu	MA2411B	1207295	2024/02/17	2025/02/16
Switch Box	Theda	1-4	TW5451159	NA	NA

BLE

Test Item	RF Conducted				
Test Site	RFCON01-NK				
Instrument	Manufacturer	Model No	Serial No	Calibration Date	Valid Date
EXA Signal Analyzer	KEYSIGHT	N9010A	MY54200207	2024/04/24	2025/04/23
Power Meter	Anritsu	ML2495A	1224005	2024/02/17	2025/02/16
Power Sensor	Anritsu	MA2411B	1207295	2024/02/17	2025/02/16
Attenuator	KEYSIGHT	8491B	MY39250703	2024/02/20	2025/02/19



4. Radio Frequency Exposure

4.1. Applicable Standards

<input type="checkbox"/>	§1.1307(b)(3)(i)(A)	The available maximum time-averaged power is no more than 1 mW, regardless of separation distance.																																																											
<input type="checkbox"/>	§1.1307(b)(3)(i)(c)	ERP is below a threshold calculated based on the distance , R between the person and the antenna / radiating structure, where $R > \lambda / 2\pi$.																																																											
		<p style="text-align: center;">TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">RF Source Frequency</th> <th colspan="2">Minimum Distance</th> <th colspan="2">Threshold ERP</th> </tr> <tr> <th>f_L MHz</th> <th>f_H MHz</th> <th>$\lambda_L / 2\pi$</th> <th>$\lambda_H / 2\pi$</th> <th colspan="2">W</th> </tr> </thead> <tbody> <tr> <td>0.3</td> <td>—</td> <td>1.34</td> <td>159 m</td> <td>—</td> <td>35.6 m</td> </tr> <tr> <td>1.34</td> <td>—</td> <td>30</td> <td>35.6 m</td> <td>—</td> <td>1.6 m</td> </tr> <tr> <td>30</td> <td>—</td> <td>300</td> <td>1.6 m</td> <td>—</td> <td>159 mm</td> </tr> <tr> <td>300</td> <td>—</td> <td>1,500</td> <td>159 mm</td> <td>—</td> <td>3.83 R^2</td> </tr> <tr> <td>1,500</td> <td>—</td> <td>100,000</td> <td>31.8 mm</td> <td>—</td> <td>0.0128 $R^2 f$</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>—</td> <td>0.5 mm</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> <td>—</td> <td>19.2 R^2</td> </tr> </tbody> </table> <p>Subscripts L and H are low and high; λ is wavelength. From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.</p>						RF Source Frequency		Minimum Distance		Threshold ERP		f_L MHz	f_H MHz	$\lambda_L / 2\pi$	$\lambda_H / 2\pi$	W		0.3	—	1.34	159 m	—	35.6 m	1.34	—	30	35.6 m	—	1.6 m	30	—	300	1.6 m	—	159 mm	300	—	1,500	159 mm	—	3.83 R^2	1,500	—	100,000	31.8 mm	—	0.0128 $R^2 f$					—	0.5 mm					—	19.2 R^2
RF Source Frequency		Minimum Distance		Threshold ERP																																																									
f_L MHz	f_H MHz	$\lambda_L / 2\pi$	$\lambda_H / 2\pi$	W																																																									
0.3	—	1.34	159 m	—	35.6 m																																																								
1.34	—	30	35.6 m	—	1.6 m																																																								
30	—	300	1.6 m	—	159 mm																																																								
300	—	1,500	159 mm	—	3.83 R^2																																																								
1,500	—	100,000	31.8 mm	—	0.0128 $R^2 f$																																																								
				—	0.5 mm																																																								
				—	19.2 R^2																																																								

Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, $\leq P_{th}$

$$P_{th} (\text{mW}) = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} (\text{mW}) = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);



4.2. EUT Specification

Frequency band (Operating)	SRD: 2402MHz ~ 2480MHz BLE: 2402MHz ~ 2480MHz
Device category	<input checked="" type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation)
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Evaluation applied	<input type="checkbox"/> Blanket 1 mW Blanket Exemption <input type="checkbox"/> MPE-based Exemption <input checked="" type="checkbox"/> SAR-based Exemption
Remark:	
<p><i>The maximum conducted output power is 2.15dBm (1.641mW) at 2402MHz (with 2.94dBi antenna gain.) For SRD</i></p> <p><i>The maximum conducted output power is 2.12dBm (1.629W) at 2402MHz (with 2.94dBi antenna gain.) For BLE</i></p>	

4.3. Result

SRD

Channel Frequency (MHz)	Max. Conducted output power (dBm)	Max. Tune up power (dBm)	Max. Tune up power (mW)	Antenna Gain (dBi)	Max.Tune up e.i.r.p. Power (dBm)	Max.Tune up e.r.p. Power (dBm)	Max.Tune up e.r.p. Power (mW)	Distance (mm)	SAR test exclusion thresholds (mW)
2402-2480	2.15	2.65	1.84	2.94	5.59	3.44	2.21	5	2.72

No non-compliance noted.

BLE

Channel Frequency (MHz)	Max. Conducted output power (dBm)	Max. Tune up power (dBm)	Max. Tune up power (mW)	Antenna Gain(dBi)	Max.Tune up e.i.r.p. Power (dBm)	Max.Tune up e.r.p. Power (dBm)	Max.Tune up e.r.p. Power (mW)	Distance (mm)	SAR test exclusion thresholds (mW)
2402-2480	2.12	2.62	1.83	2.94	5.56	3.41	2.19	5	2.72

No non-compliance noted.

-----THE END OF REPORT-----