

Prediction of MPE limit at given distance

Product Description: MP3 Player with Bluetooth

Type: DVP-FL0019

1. Introduction

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

2. Limits for Maximum Permissible Exposure

According to FCC Part 1.1307, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidelines.

According to FCC Part 1.1310 RF exposure is calculated.

Limits for General Population/ Uncontrolled Exposure

Limits for General Population/ Uncontrolled Exposure			
Frequency Range (MHz)	Electric Field Strength(E)(V/m)	Magnetic Field Strength (H)(A/m)	Power Density (S)(mW/cm ²)
0.3-1.34	614	1.63	(100)*
1.34-30	824/f	2.19/f	(180/f2)*
30-300	27.5	0.073	0.2
300-1500			f/1500
1500-100,000			1.0

3. Test result

Maximum peak output power at antenna input terminal(dBm):	1.742
Maximum peak output power at antenna input terminal(mW):	1.49
Prediction distance(cm):	20
Predication frequency(MHz):	2441
Antenna Gain (typical) (dBi):	1
Power density at predication frequency at <u>20</u> cm(mW/cm ²):	0.0005
MPE limit for RF exposure at prediction frequency(mW/cm ²):	1

4. Conclusion

The predicted power density level at 20cm is 0.0005mw/cm² which is below the uncontrolled exposure limit of 1.0mw/cm². The EUT is used at least 20cm away from user's body. It is determined as mobile equipment and complied with the MPE limit.