

No. 1 Workshop, M-10, Middle section, Science & Technology Park,

Shenzhen, Guangdong, China 518057 Telephone: +86 (0) 755 2601 2053

Fax: +86 (0) 755 2671 0594 Report No.: SZEM160500340101

Email: ee.shenzhen@sgs.com Page: 1 of 86

FCC REPORT

Application No.: SZEM1605003401CR

Applicant: Creative Labs Inc

Manufacturer: CREATIVE LABS PTE. LTD.

Product Name: Creative MUVO 2

Model No.(EUT): MF8255
Trade Mark: Creative
FCC ID: IBAMF8255

Standards: 47 CFR Part 15, Subpart C (2015)

Date of Receipt: 2016-05-18

Date of Test: 2016-05-25 to 2016-06-22

Date of Issue: 2016-07-22

Test Result: PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.



Report No.: SZEM160500340101

Page: 2 of 86

2 Version

Revision Record						
Version Chapter Date Modifier Remark						
00		2016-07-22		Original		

Authorized for issue by:		
Tested By	Benson Wang	2016-06-22
	(Benson Wang) /Project Engineer	Date
Prepared By	Iris Zhou	2016-07-22
	(Iris Zhou) /Clerk	Date
Checked By	Eric Fu	2016-07-22
	(Eric Fu) /Reviewer	Date



Report No.: SZEM160500340101

Page: 3 of 86

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 (2013)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2013)	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2013)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Carrier Frequencies Separation	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Hopping Channel Number	47 CFR Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013)	PASS
Dwell Time	47 CFR Part 15, Subpart C Section 15.247 (a)(1)		PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15, Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10 (2013)	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013)	PASS
Radiated Spurious emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 (2013)	PASS



Report No.: SZEM160500340101

Page: 4 of 86

4 Contents

			Page
1	CC	OVER PAGE	1
2	VE	ERSION	2
3	TE	ST SUMMARY	3
4	CC	ONTENTS	4
5	GE	ENERAL INFORMATION	5
	5.1	CLIENT INFORMATION	5
	5.2	GENERAL DESCRIPTION OF EUT	
	5.3	TEST ENVIRONMENT	
	5.4	DESCRIPTION OF SUPPORT UNITS	
	5.5	TEST LOCATION	
	5.6	TEST FACILITY	8
	5.7	DEVIATION FROM STANDARDS	
	5.8	ABNORMALITIES FROM STANDARD CONDITIONS	
	5.9	OTHER INFORMATION REQUESTED BY THE CUSTOMER	
	5.10	EQUIPMENT LIST	9
6	TE	EST RESULTS AND MEASUREMENT DATA	12
	6.1	Antenna Requirement	
	6.2	CONDUCTED EMISSIONS	
	6.3	CONDUCTED PEAK OUTPUT POWER	
	6.4	20DB OCCUPY BANDWIDTH	
	6.5	CARRIER FREQUENCIES SEPARATION	
	6.6	HOPPING CHANNEL NUMBER DWELL TIME	
	6.7 6.8	BAND-EDGE FOR RF CONDUCTED EMISSIONS	
	6.9	SPURIOUS RF CONDUCTED EMISSIONS	
	6.10	OTHER REQUIREMENTS FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM	
	6.11	RADIATED SPURIOUS EMISSION	
		11.1 Radiated Emission below 1GHz	
	6.1	11.2 Transmitter Emission above 1GHz	
	6.12	RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	79
7	PH	HOTOGRAPHS - EUT TEST SETUP	85
	7.1	CONDUCTED EMISSION	85
	7.2	RADIATED EMISSION	85
	7.3	RADIATED SPURIOUS EMISSION	86
8	PH	HOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	86



Report No.: SZEM160500340101

Page: 5 of 86

5 General Information

5.1 Client Information

Applicant:	Creative Labs Inc
Address of Applicant:	1901, McCarthy Boulevard, Milpitas, CA 95035, United States
Manufacturer:	CREATIVE LABS PTE. LTD.
Address of Manufacturer:	31 International Business Park, #03-01 Creative Resource, Singapore 609921

5.2 General Description of EUT

Product Name:	Creative MUVO 2
Model No.:	MF8255
Trade Mark:	Creative
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.2 dual mode
	This test report is for classic mode.
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	Portable production
Antenna Type:	Integral
Antenna Gain:	5.61dBi
Test Power Grade:	4 (Class II)
Test Software of EUT:	ACTs MP Tool (manufacturer declare)
Power Supply	Lithium Ion Battery: 3.7V 2200mAh 8.14Wh (Charge by usb port)
	Battery model: 18650-2200
	USB input: DC5V 950mA
Cable:	USB cable: 69cm shielded
Test Voltage:	120V/60Hz



Report No.: SZEM160500340101

Page: 6 of 86

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
2	2404MHz	22	2424MHz	42	2444MHz	62	2464MHz
3	2405MHz	23	2425MHz	43	2445MHz	63	2465MHz
4	2406MHz	24	2426MHz	44	2446MHz	64	2466MHz
5	2407MHz	25	2427MHz	45	2447MHz	65	2467MHz
6	2408MHz	26	2428MHz	46	2448MHz	66	2468MHz
7	2409MHz	27	2429MHz	47	2449MHz	67	2469MHz
8	2410MHz	28	2430MHz	48	2450MHz	68	2470MHz
9	2411MHz	29	2431MHz	49	2451MHz	69	2471MHz
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
12	2414MHz	32	2434MHz	52	2454MHz	72	2474MHz
13	2415MHz	33	2435MHz	53	2455MHz	73	2475MHz
14	2416MHz	34	2436MHz	54	2456MHz	74	2476MHz
15	2417MHz	35	2437MHz	55	2457MHz	75	2477MHz
16	2418MHz	36	2438MHz	56	2458MHz	76	2478MHz
17	2419MHz	37	2439MHz	57	2459MHz	77	2479MHz
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency		
The Lowest channel	2402MHz		
The Middle channel	2441MHz		
The Highest channel	2480MHz		



Report No.: SZEM160500340101

Page: 7 of 86

5.3 Test Environment

Operating Environment:				
Temperature:	25.0 °C			
Humidity:	55 % RH			
Atmospheric Pressure:	1010 mbar			

5.4 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	
Adapter	Provided by client	S005AYU0500100	

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



Report No.: SZEM160500340101

Page: 8 of 86

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

Industry Canada (IC)

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.



Report No.: SZEM160500340101

Page: 9 of 86

5.10 Equipment List

	Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2016-05-13	2017-05-13
2	LISN	Rohde & Schwarz	ENV216	SEM007-01	2015-10-09	2016-10-09
3	LISN	ETS-LINDGREN	3816/2	SEM007-02	2016-04-25	2017-04-25
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T8-02	EMC0120	2015-08-30	2016-08-30
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T4-02	EMC0121	2015-08-30	2016-08-30
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN- T2-02	EMC0122	2015-08-30	2016-08-30
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2016-04-25	2017-04-25
8	DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2015-10-09	2016-10-09



Report No.: SZEM160500340101

Page: 10 of 86

	RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2016-05-13	2017-05-13
2	EMI Test Receiver	Agilent Technologies	N9038A	SEM004-05	2015-09-16	2016-09-16
3	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEM003-01	2014-11-01	2017-11-01
4	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEM003-11	2015-10-17	2018-10-17
5	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEM003-12	2014-11-24	2017-11-24
6	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEM005-01	2016-04-25	2017-04-25
7	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A
8	DC Power Supply	Zhao Xin	RXN-305D	SEM011-02	2015-10-09	2016-10-09
9	Loop Antenna	Beijing Daze	ZN30401	SEM003-09	2015-05-13	2018-05-13

	RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2016-05-13	2017-05-13
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEM004-04	2016-04-25	2017-04-25
3	BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-02	2014-11-15	2017-11-15
4	Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2015-10-09	2016-10-09
5	Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-14
6	Low Noise Amplifier	Black Diamond Series	BDLNA- 0118- 352810	SEM005-05	2015-10-09	2016-10-09
7	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A



Report No.: SZEM160500340101

Page: 11 of 86

	RF connected test					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2015-10-09	2016-10-09
2	Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2015-10-17	2016-10-17
3	Signal Generator	Rohde & Schwarz	SML03	SEM006-02	2016-04-25	2017-04-25
4	Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2015-10-09	2016-10-09



Report No.: SZEM160500340101

Page: 12 of 86

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard requirement: 47 CFR Part 15C Section 15.203 /247(c)


15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:



The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 5.61dBi.



Report No.: SZEM160500340101

Page: 13 of 86


6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	150kHz to 30MHz				
Limit:	Function of the Control of the Contr	Limit (d	lBuV)		
	Frequency range (MHz)	Quasi-peak	Average		
	0.15-0.5	66 to 56*	56 to 46*		
	0.5-5	56	46		
	5-30	60	50		
	* Decreases with the logarithn	n of the frequency.		•	
Test Procedure:	The mains terminal disturble room.	oance voltage test was	s conducted in a shie	∍lded	
	<u> </u>				



Report No.: SZEM160500340101

Page: 14 of 86





Report No.: SZEM160500340101


Page: 15 of 86

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live line:



Site : Shielding Room Condition : CE LINE Job No. : 3401CR Test Mode: : Charge + TX


			Cable	LISN	Read		Limit	Over	
		Freq	Loss	Factor	Level	Level	Line	Limit	Remark
		MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	@	0.42373	0.01	9.60	38.17	47.78	57.37	-9.60	QP
2	@	0.42373	0.01	9.60	33.63	43.24	47.37	-4.14	AVERAGE
3	@	0.52934	0.01	9.60	35.51	45.12	56.00	-10.88	QP
4	@	0.52934	0.01	9.60	32.57	42.18	46.00	-3.82	AVERAGE
5	@	0.89917	0.02	9.62	37.25	46.89	56.00	-9.11	QP
6	@	0.89917	0.02	9.62	29.54	39.18	46.00	-6.82	AVERAGE
7	@	1.381	0.02	9.59	35.56	45.17	56.00	-10.83	QP
8	@	1.381	0.02	9.59	29.84	39.45	46.00	-6.55	AVERAGE
9	@	2.077	0.02	9.64	32.71	42.36	56.00	-13.64	QP
10	@	2.077	0.02	9.64	23.94	33.60	46.00	-12.40	AVERAGE
11		6.592	0.01	9.67	31.09	40.77	60.00	-19.23	QP
12		6.592	0.01	9.67	20.85	30.54	50.00	-19.46	AVERAGE



Report No.: SZEM160500340101

Page: 16 of 86

Neutral line:



Site : Shielding Room Condition : CE NEUTRAL Job No. : 3401CR Test Mode: : Charge + TX

	_	Cable	LISN	Read		Limit	Over	
	Freq	Loss	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 @	0.42598	0.01	9.62	35.28	44.91	57.33	-12.42	QP
2 @	0.42598	0.01	9.62	26.78	36.41	47.33	-10.92	AVERAGE
3 @	0.47612	0.01	9.63	32.11	41.75	56.41	-14.66	QP
4 @	0.47612	0.01	9.63	25.85	35.49	46.41	-10.91	AVERAGE
5 @	1.249	0.02	9.65	31.54	41.21	56.00	-14.79	QP
6 @	1.249	0.02	9.65	26.14	35.81	46.00	-10.19	AVERAGE
7	2.099	0.02	9.66	30.66	40.35	56.00	-15.65	QP
8 @	2.099	0.02	9.66	23.52	33.20	46.00	-12.80	AVERAGE
9	3.328	0.02	9.67	27.60	37.30	56.00	-18.70	QP
10	3.328	0.02	9.67	20.34	30.03	46.00	-15.97	AVERAGE
11	8.279	0.01	9.76	29.31	39.08	60.00	-20.92	QP
12	8.279	0.01	9.76	19.14	28.91	50.00	-21.09	AVERAGE

Notes:


- 1. The following Quasi-Peak and Average measurements were performed on the EUT:
- 2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.



Report No.: SZEM160500340101

Page: 17 of 86

6.3 Conducted Peak Output Power





Report No.: SZEM160500340101

Page: 18 of 86

Measurement Data

	GFSK mode					
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result			
Lowest	-4.69	20.97	Pass			
Middle	-3.76	20.97	Pass			
Highest	-3.25	20.97	Pass			
	π/4DQPSK m	node				
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result			
Lowest	-3.53	20.97	Pass			
Middle	-2.56	20.97	Pass			
Highest	-2.10	20.97	Pass			
	8DPSK mod	de				
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result			
Lowest	-3.38	20.97	Pass			
Middle	-2.32	20.97	Pass			
Highest	-1.94	20.97	Pass			




Report No.: SZEM160500340101


Page: 19 of 86

Test plot as follows:

Test mode: GFSK Test channel: Lowest



Test mode: GFSK Test channel: Middle







Report No.: SZEM160500340101

Page: 20 of 86

Test mode: GFSK Test channel: Highest











Report No.: SZEM160500340101

Page: 21 of 86

Test mode: π/4DQPSK Test channel: Middle











Report No.: SZEM160500340101

Page: 22 of 86

Test mode: 8DPSK Test channel: Lowest










Report No.: SZEM160500340101

Page: 23 of 86

Test mode: 8DPSK Test channel: Highest






Report No.: SZEM160500340101

Page: 24 of 86

6.4 20dB Occupy Bandwidth



Measurement Data

	20dB Occupy Bandwidth (kHz)				
Test channel	GFSK	π/4DQPSK	8DPSK		
Lowest	1057.692	1382.923	1331.731		
Middle	1052.884	1382.923	1330.654		
Highest	1052.884	1384.616	1330.654		




Report No.: SZEM160500340101


Page: 25 of 86

Test plot as follows:

Test mode: GFSK Test channel: Lowest











Report No.: SZEM160500340101

Page: 26 of 86

Test mode: GFSK Test channel: Highest











Report No.: SZEM160500340101

Page: 27 of 86

Test mode: π/4DQPSK Test channel: Middle











Report No.: SZEM160500340101

Page: 28 of 86

Test mode: 8DPSK Test channel: Lowest










Report No.: SZEM160500340101

Page: 29 of 86

Test mode: 8DPSK Test channel: Highest






Report No.: SZEM160500340101

Page: 30 of 86

6.5 Carrier Frequencies Separation





Report No.: SZEM160500340101

Page: 31 of 86

	GFSK mode					
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result			
Middle	996	705.128	Pass			
	π/4DQPSK mode					
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result			
Middle	981	981 923.077				
	8DPSK mode					
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result			
Middle	1017	887.821	Pass			

Note: According to section 6.4,

Mada	20dB bandwidth (kHz)	Limit (kHz)
Mode	(worse case)	(Carrier Frequencies Separation)
GFSK	1057.692	705.128
π/4DQPSK	1384.616	923.077
8DPSK	1331.731	887.821




Report No.: SZEM160500340101


Page: 32 of 86

Test plot as follows:

Test mode: GFSK Test channel: Middle










Report No.: SZEM160500340101

Page: 33 of 86








Report No.: SZEM160500340101

Page: 34 of 86

6.6 Hopping Channel Number



Measurement Data


Mode	Hopping channel numbers	Limit
GFSK	79	≥15
π/4DQPSK	79	≥15
8DPSK	79	≥15





Report No.: SZEM160500340101

Page: 35 of 86

Test plot as follows










Report No.: SZEM160500340101

Page: 36 of 86






Report No.: SZEM160500340101

Page: 37 of 86

6.7 Dwell Time



Measurement Data

Mode	Packet	Dwell time (second)	Limit (second)		
	DH1	0.12	≤0.4		
GFSK	DH3	0.30	≤0.4		
	DH5	0.23	≤0.4		
π/4DQPSK	2-DH1	0.12	≤0.4		
	2-DH3	0.22	≤0.4		
	2-DH5	0.23	≤0.4		
	3-DH1	0.11	≤0.4		
8DPSK	3-DH3	0.23	≤0.4		
	3-DH5	0.17	≤0.4		



Report No.: SZEM160500340101

Page: 38 of 86

Remark:

The test period: T= 0.4 Second/Channel x 79 Channel /10= 3.16 s

On (ms)*total number x10=dwell time (ms)

The lowest channel (2441MHz), as below:

DH1 time slot=0.392 (ms)*total number x10= 117.60 (ms)

DH3 time slot= 1.653 (ms)^* total number x10= 297.54(ms)

DH5 time slot=2.908 (ms)* total number x10= 233.28 (ms)

2-DH1 time slot=0.402 (ms)*total number x10= 120.60 (ms)

2-DH3 time slot=1.656 (ms)* total number x10= 215.28 (ms)

2-DH5 time slot=2.908 (ms)* total number x10= 232.64 (ms)

3-DH1 time slot=0.403 (ms)*total number x10= 108.81 (ms)

3-DH3 time slot=1.659 (ms)* total number x10= 232.26 (ms)

3-DH5 time slot=2.912 (ms)* total number x10= 174.72(ms)





Report No.: SZEM160500340101

Page: 39 of 86

Test plot as follows:











Report No.: SZEM160500340101

Page: 40 of 86












Report No.: SZEM160500340101

Page: 41 of 86











Report No.: SZEM160500340101

Page: 42 of 86











Report No.: SZEM160500340101

Page: 43 of 86

Test Packet: 2-DH3








Report No.: SZEM160500340101

Page: 44 of 86





Center 2.441 GHz

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."


400 μs/




Report No.: SZEM160500340101

Page: 45 of 86











Report No.: SZEM160500340101

Page: 46 of 86











Report No.: SZEM160500340101

Page: 47 of 86









Report No.: SZEM160500340101

Page: 48 of 86

6.8 Band-edge for RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)			
Test Method:	ANSI C63.10:2013 Section 7.8.6			
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane			
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.			
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.			
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type			
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.			
Instruments Used:	Refer to section 5.10 for details			
Test Results:	Pass			





Report No.: SZEM160500340101

Page: 49 of 86

Test plot as follows:











Report No.: SZEM160500340101

Page: 50 of 86

Test mode: GFSK Test channel: Highest









Report No.: SZEM160500340101

Page: 51 of 86

Test mode: π/4DQPSK Test channel: Lowest









Report No.: SZEM160500340101

Page: 52 of 86

Test mode: π/4DQPSK Test channel: Highest









Report No.: SZEM160500340101

Page: 53 of 86











Report No.: SZEM160500340101

Page: 54 of 86









Report No.: SZEM160500340101

Page: 55 of 86

6.9 Spurious RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)		
Test Method:	ANSI C63.10:2013 Section 7.8.8		
Test Setup:	Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane		
	Remark: Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.		
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.		
Exploratory Test Mode:	Non-hopping transmitting with all kind of modulation and all kind of data type		
Final Test Mode:	Through Pre-scan, find the DH1 of data type is the worst case of GFSK modulation type, 2-DH1 of data type is the worst case of $\pi/4DQPSK$ modulation type, 3-DH1 of data type is the worst case of 8DPSK modulation type.		
Instruments Used:	Refer to section 5.10 for details		
Test Results:	Pass		





Report No.: SZEM160500340101

Page: 56 of 86

Test plot as follows:

Test mode: GFSK Test channel: Lowest









Report No.: SZEM160500340101

Page: 57 of 86




Test mode:	GFSK	Test channel:	Middle
------------	------	---------------	--------






Report No.: SZEM160500340101

Page: 58 of 86









Report No.: SZEM160500340101

Page: 59 of 86

Test mode: GFSK Test channel: Highest









Report No.: SZEM160500340101

Page: 60 of 86




Test mode:	π/4DQPSK	Test channel:	Lowest
Tool mode.	117 12 31 31	1 oot onarmon.	2011001






Report No.: SZEM160500340101

Page: 61 of 86









Report No.: SZEM160500340101

Page: 62 of 86

Test mode: π/4DQPSK Test channel: Middle









Report No.: SZEM160500340101

Page: 63 of 86




Test mode:	π/4DQPSK	Test channel:	Highest
i est illoue.	II/4DQI SK	i est charinet.	riigiiest






Report No.: SZEM160500340101

Page: 64 of 86









Report No.: SZEM160500340101

Page: 65 of 86

Test mode: 8DPSK Test channel: Lowest









Report No.: SZEM160500340101

Page: 66 of 86











Report No.: SZEM160500340101

Page: 67 of 86









Report No.: SZEM160500340101

Page: 68 of 86

Test mode: 8DPSK Test channel: Highest








Report No.: SZEM160500340101

Page: 69 of 86



Remark:

Use 100kHz RBW to determine the relative limit in the band 2.4GHz to 2.5GHz, and Use 1MHz RBW to measure spurious emissions in the band 30MHz to 10GHz and 10GHz to 25GHz. The sweep points set to 30001.



Report No.: SZEM160500340101

Page: 70 of 86

6.10 Other requirements Frequency Hopping Spread Spectrum System

Test Requirement: 47 CFR Part 15C Section 15.247 (a)(1), (h) requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.


The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage


outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 1 = 511$ bits
- · Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.



Report No.: SZEM160500340101

Page: 71 of 86

Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.



Report No.: SZEM160500340101

Page: 72 of 86

6.11 Radiated Spurious Emission


Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205						
Test Method:	ANSI C63.10: 2013						
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)						
Receiver Setup:	Frequency Detector RBV				VBW	Remark	
	0.009MHz-0.090MH	0.009MHz-0.090MHz Peak		10kHz	z 30kHz	Peak	
	0.009MHz-0.090MH	0.009MHz-0.090MHz Average		10kHz	z 30kHz	Average	
	0.090MHz-0.110MH	z	Quasi-peak	10kHz	z 30kHz	Quasi-peak	
	0.110MHz-0.490MHz		Peak	10kHz	z 30kHz	Peak	
	0.110MHz-0.490MHz		Average	10kHz	30kHz	Average	
	0.490MHz -30MHz		Quasi-peak	10kHz	z 30kHz	Quasi-peak	
	30MHz-1GHz		Quasi-peak	100 kH	Iz 300kHz	Quasi-peak	
	Above 1GHz		Peak	1MHz	: 3MHz	Peak	
	Above Tariz		Peak	1MHz	10Hz	Average	
Limit:	Frequency Field strength (microvolt/meter)		Limit (dBuV/m)	Remark	Measureme distance (n		
	0.009MHz-0.490MHz	2400/F(kHz)		-	-	300	
	0.490MHz-1.705MHz	24	1000/F(kHz)	-	-	30	
	1.705MHz-30MHz		30	-	-	30	
	30MHz-88MHz		100	40.0	Quasi-peak	3	
	88MHz-216MHz 150 4		43.5	Quasi-peak 3			
	216MHz-960MHz	200		46.0	Quasi-peak	3	
	960MHz-1GHz	500		54.0	Quasi-peak	3	
	Above 1GHz	500		54.0	Average	3	
Note: 15.35(b), Unless otherwise specified, the limit on peak radio fre emissions is 20dB above the maximum permitted average emis applicable to the equipment under test. This peak limit applies to peak emission level radiated by the device.					emission limit		



Report No.: SZEM160500340101

Page: 73 of 86

Test Setup:






Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



Report No.: SZEM160500340101

Page: 74 of 86

	 g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. h. Test the EUT in the lowest channel (2402MHz),the middle channel (2441MHz),the Highest channel (2480MHz) i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. j. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Non-hopping transmitting mode with all kind of modulation and all kind of
	data type Charge + Transmitting mode.
Final Test Mode:	Through Pre-scan, find the DH1 of data type and GFSK modulation is the worst case. Pretest the EUT at Charge + Transmitting mode For below 1GHz part, through pre-scan, the worst case is the lowest channel. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass




Report No.: SZEM160500340101

Page: 75 of 86

6.11.1 Radiated Emission below 1GHz

30MHz~1GHz (QP)		
Test mode:	Charge + Transmitting	Vertical



Condition: 3m Vertical

Job No. : 3401CR Test mode: Charge+TX


		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	31.62	0.60	17.94	27.40	40.08	31.22	40.00	-8.78
2	40.42	0.61	13.00	27.38	41.36	27.59	40.00	-12.41
3	95.09	1.15	8.96	27.30	48.73	31.54	43.50	-11.96
4	113.32	1.24	8.50	27.22	47.65	30.17	43.50	-13.33
5	186.44	1.38	10.03	26.90	40.60	25.11	43.50	-18.39
6	804.60	3.22	22.04	27.38	28.27	26.15	46.00	-19.85



Report No.: SZEM160500340101

Page: 76 of 86

Test mode: Charge + Transmitting Horizontal



Condition: 3m Horizontal

Job No. : 3401CR Test mode: Charge+TX

		Cable	Ant	Preamp	Read		Limit	0ver
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	92.14	1.12	8.87	27.31	44.56	27.24	43.50	-16.26
2	100.93	1.20	9.06	27.29	43.55	26.52	43.50	-16.98
3	122.40	1.26	8.05	27.17	44.91	27.05	43.50	-16.45
4	129.92	1.28	7.90	27.13	44.52	26.57	43.50	-16.93
5	186.44	1.38	10.03	26.90	40.58	25.09	43.50	-18.41
6 p	p 857.02	3.44	22.44	27.12	32.38	31.14	46.00	-14.86



Report No.: SZEM160500340101

Page: 77 of 86

6.11.2 Transmitter Emission above 1GHz

Test mode:		GFSK(DH1)	Test channel:		Lowest	Lowest Remai		Peak
Frequency (MHz)	Antenna factors (dB/m)	Loss	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3589.562	32.08	7.66	38.40	48.47	49.81	74.00	-24.19	Vertical
4804.000	34.10	8.87	38.75	46.23	50.45	74.00	-23.55	Vertical
6051.874	34.73	10.49	38.89	46.55	52.88	74.00	-21.12	Vertical
7206.000	35.60	10.68	37.64	42.37	51.01	74.00	-22.99	Vertical
9608.000	37.10	12.50	36.35	36.11	49.36	74.00	-24.64	Vertical
12603.270	37.90	14.44	37.75	38.01	52.60	74.00	-21.40	Vertical
3748.808	32.70	7.72	38.47	45.80	47.75	74.00	-26.25	Horizontal
4804.000	34.10	8.87	38.75	47.38	51.60	74.00	-22.40	Horizontal
6034.386	34.72	10.52	38.91	46.13	52.46	74.00	-21.54	Horizontal
7206.000	35.60	10.68	37.64	42.97	51.61	74.00	-22.39	Horizontal
9608.000	37.10	12.50	36.35	35.90	49.15	74.00	-24.85	Horizontal
12603.270	37.90	14.44	37.75	37.30	51.89	74.00	-22.11	Horizontal

Test mode:		GFSK(DH1)	Te	st channel:	Middle	Rema	ırk:	Peak
Frequency (MHz)	Antenn factors (dB/m	Loss	Cable Loss (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Over limit (dB)	Polarization
3579.190	32.07	7.66	38.40	45.80	47.13	74.00	-26.87	Vertical
4882.000	34.18	8.98	38.77	46.32	50.71	74.00	-23.29	Vertical
5982.226	34.66	10.51	38.96	45.90	52.11	74.00	-21.89	Vertical
7323.000	35.54	10.72	37.59	41.11	49.78	74.00	-24.22	Vertical
9764.000	37.10	12.58	36.14	38.02	51.56	74.00	-22.44	Vertical
12603.270	37.90	14.44	37.75	38.06	52.65	74.00	-21.35	Vertical
3631.354	32.23	7.68	38.42	45.28	46.77	74.00	-27.23	Horizontal
4882.000	34.18	8.98	38.77	46.97	51.36	74.00	-22.64	Horizontal
6034.386	34.72	10.52	38.91	45.40	51.73	74.00	-22.27	Horizontal
7323.000	35.54	10.72	37.59	40.30	48.97	74.00	-25.03	Horizontal
9764.000	37.10	12.58	36.14	37.56	51.10	74.00	-22.90	Horizontal
12603.270	37.90	14.44	37.75	37.75	52.34	74.00	-21.66	Horizontal



Report No.: SZEM160500340101

Page: 78 of 86

Test mode:		GFSK(DH1)	Test	channel:	Highest	Rema	ırk:	Peak
Frequency (MHz)	Antenna factors (dB/m)	Cable Loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Over limit (dB)	Polarization
3589.562	32.08	7.66	38.40	48.19	49.53	74.00	-24.47	Vertical
4960.000	34.26	9.09	38.78	46.05	50.62	74.00	-23.38	Vertical
5999.562	34.70	10.56	38.96	46.20	52.50	74.00	-21.50	Vertical
7440.000	35.60	10.77	37.54	39.35	48.18	74.00	-25.82	Vertical
9920.000	37.22	12.67	35.93	38.36	52.32	74.00	-21.68	Vertical
12639.790	37.92	14.55	37.79	37.22	51.90	74.00	-22.10	Vertical
3770.567	32.78	7.73	38.47	45.15	47.19	74.00	-26.81	Horizontal
4960.000	34.26	9.09	38.78	45.46	50.03	74.00	-23.97	Horizontal
6034.386	34.72	10.52	38.91	45.76	52.09	74.00	-21.91	Horizontal
7440.000	35.60	10.77	37.54	39.61	48.44	74.00	-25.56	Horizontal
9920.000	37.22	12.67	35.93	38.19	52.15	74.00	-21.85	Horizontal
12658.090	37.93	14.60	37.80	36.71	51.44	74.00	-22.56	Horizontal

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

- 2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.



Report No.: SZEM160500340101

Page: 79 of 86

6.12 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205								
Test Method:	ANSI C63.10: 2013								
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)								
Limit:	Frequency Limit (dBuV/m @3m) Remark								
	30MHz-88MHz	40.0	Quasi-peak Value						
	88MHz-216MHz	43.5	Quasi-peak Value						
	216MHz-960MHz	46.0	Quasi-peak Value						
	960MHz-1GHz	54.0	Quasi-peak Value						
	Above 1GHz	54.0	Average Value						
	Above 1GHz	74.0	Peak Value						
Test Setup:									
Test Receiver		(Turntable) Ground Reference Plane Test Receiver	n Antenna Tower Antenna Tower Controller						
Figure 1. 30MH	Iz to 1GHz	Figure 2. Abov	e 1 GHz						



Report No.: SZEM160500340101

Page: 80 of 86

Test Procedure: Exploratory Test Mode:	 a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation. c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. g. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel h. Test the EUT in the lowest channel, the Highest channel i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case. j. Repeat above procedures until all frequencies measured was complete. Non-hopping transmitting mode with all kind of modulation and all kind of
	data type Charge + Transmitting mode.
Final Test Mode:	Through Pre-scan, find the DH5 of data type and GFSK modulation is the worst case.
	Pretest the EUT at Charge + Transmitting mode
	Only the worst case is recorded in the report.
Instruments Used:	Refer to section 5.10 for details
Test Results:	Pass
	I .




Report No.: SZEM160500340101

Page: 81 of 86

Test plot as follows:

Worse case mode: GFSK (DH5) Test channel: Lowest Remark: Peak Vertical



Condition: 3m Vertical Job No: : 3400CR

Mode: : 2402 Band edge

: BT


Ant Preamp Cable Read Limit Over Freq Loss Factor Factor Line Limit Level Level dBuV dBuV/m dBuV/m MHz dB dB/m 2390.000 5.34 28.57 38.11 56.60 52.40 74.00 -21.60 28.61 38.11 99.56 95.41 74.00 21.41 2 pp 2401.997 5.35



Report No.: SZEM160500340101

Page: 82 of 86

Worse case mode: GFSK (DH5) Test channel: Lowest Remark: Peak Horizontal



Condition: 3m Horizontal

Job No: : 3400CR

Mode: : 2402 Band edge

: BT


	Freq			Preamp Factor				
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 2 pm	2390.000							



Report No.: SZEM160500340101

Page: 83 of 86

Worse case mode: GFSK (DH5) Test channel: Highest Remark: Peak Vertical



Condition: 3m Vertical Job No: : 3400CR

Mode: : 2480 Band edge

: BT

Cable Ant Preamp Read Limit Over
Freq Loss Factor Factor Level Level Line Limit

MHz dB dB/m dB dBuV dBuV/m dBuV/m dBuV/m dB


1 pp 2479.855 5.41 28.97 38.12 99.12 95.38 74.00 21.38 2 2483.500 5.41 28.98 38.12 54.37 50.64 74.00 -23.36



Report No.: SZEM160500340101

Page: 84 of 86

Worse case mode: GFSK(DH5) Test channel: Highest Remark: Peak Horizontal



Condition: 3m Horizontal

Job No: : 3400CR

Mode: : 2480 Band edge

: BT

Fre	Cable q Loss	Ant Factor					
MH	z dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp 2479.90 2 2483.50							

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor



Report No.: SZEM160500340101

Page: 85 of 86

7 Photographs - EUT Test Setup

Test Model No.: MF8255

7.1 Conducted Emission



7.2 Radiated Emission






Report No.: SZEM160500340101

Page: 86 of 86

7.3 Radiated Spurious Emission



8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1605003401CR.