

MPE Calculation page

MPE Calculator	Garmin	Test Number	090610
MPE uses EIRP for calculation. EIRP is based on TX power added to the antenna gain in dBi.			
dBi = dB gain compared to an isotropic radiator.			
S = power density in mW/cm ²		Antenna Gain (dBi)	2.2
Output Power		dBi to dBd	2.17
Tx Frequency (MHz)	2457	(Watts)	0.000486
Cable Loss (dB)		(dBm)	-3.13
Antenna minus cable (dBi)			2.20
Calculated ERP (mw)			0.489
Calculated EIRP (mw)			0.807
Radiated (EIRP) dBm			-0.934
Radiated (ERP) dBm			-3.104
Occupational Limit	5.00000	mW/cm²	
General Public Limit	1.00000	mW/cm²	
<div style="border: 1px solid black; padding: 5px;"> Power density (S) = EIRP ----- = mW/cm² 4 π r² [r (cm), EIRP (mW)] </div>			
FCC radio frequency radiation exposure limits per 1.1310			
Frequency (MHz)	Occupational Limit	Public Limit	
300-1,500	f/300	f/1500	
1,500-10,000	5	1	
FCC radio frequency radiation exposure limits per 1.1310			
Frequency (MHz)	Occupational Limit @ Tx Freq (mW/cm ²)	Public Limit @ Tx Freq (mW/cm ²)	
300-1,500	8.19	1.638	
1,500-10,000	5	1	
EIRP	Distance	Distance	S
milliwatts	cm	inches	mW/cm ²
0.807	10.00	3.94	0.00064
0.807	9.00	3.54	0.00079
0.807	8.00	3.15	0.00100
0.807	7.00	2.76	0.00131
0.807	6.00	2.36	0.00178
0.807	5.00	1.97	0.00257
0.807	4.00	1.57	0.00401
0.807	3.00	1.18	0.00713
0.807	2.00	0.79	0.01605
0.807	1.00	0.39	0.06418
0.807	0.50	0.20	0.25674
0.807	0.40	0.16	0.40115
0.807	0.28	0.11	0.81867
0.807	0.25	0.10	1.02694
0.807	0.20	0.08	1.60460
Frequency (MHz)	Occupational Limit minimum Distance (cm)	Public Limit minimum distance (cm)	
300-1,500	N/A	N/A	
1,500-10,000	N/A	0.28	